

Milena (Olena)
User documentation 2.0 Id

Generated by Doxygen 1.7.1

Thu May 3 2012 19:52:38

Contents

1 Documentation of milena	1
1.1 Introduction	1
1.2 Overview of Milena.	1
1.3 Copyright and License.	2
2 Quick Reference Guide	3
2.1 Installation	4
2.1.1 Requirements	4
2.1.1.1 To compile the user examples	4
2.1.1.2 To compile the documentation (Optional)	4
2.1.1.3 To develop in Olena	4
2.1.2 Getting Olena	4
2.1.3 Building Olena	4
2.2 Foreword	4
2.2.1 Generality	4
2.2.2 Directory hierarchy	4
2.2.3 Writing and compiling a program with Olena	4
2.3 Site	4
2.4 Site set	4
2.4.1 Basic interface	4
2.4.2 Optional interface	4
2.5 Image	5
2.5.1 Definition	5
2.5.2 Possible image types	5
2.5.3 Possible value types	5
2.5.4 Domain	5
2.5.5 Border and extension	6
2.5.5.1 Image border	6

2.5.5.2	Generality on image extension	6
2.5.5.3	Different extensions	6
2.5.6	Interface	8
2.5.7	Load and save images	8
2.5.8	Create an image	8
2.5.9	Access and modify values	9
2.5.10	Image size	9
2.6	Structural elements: Window and neighborhood	10
2.6.1	Define an element	10
2.6.1.1	Window	10
2.6.1.2	Neighborhood	10
2.6.1.3	Custom structural elements	10
2.6.1.4	Conversion between Neighborhoods and Windows	10
2.7	Sites, psites and dpoints	10
2.7.1	Need for site	10
2.7.2	Need for psite	10
2.7.3	From psite to site	11
2.7.4	Dpoint	11
2.8	Iterators	11
2.9	Memory management	12
2.10	Basic routines	12
2.10.1	Fill	12
2.10.2	Paste	12
2.10.3	Blobs	13
2.10.4	Logical not	13
2.10.5	Compute	13
2.10.5.1	Accumulators	13
2.10.5.2	Example with labeling::compute()	13
2.10.6	Working with parts of an image	14
2.10.6.1	Restrict an image with a site set	14
2.10.6.2	Restrict an image with a predicate	15
2.10.6.3	Restrict an image with a C function	15
2.11	Input / Output	16
2.11.1	ImageMagick	16
2.11.2	GDCM	16
2.12	Graphs and images	16

2.12.1	Description	16
2.12.2	Example	16
2.13	Useful global variables	19
2.14	Useful macros	19
2.14.1	Variable declaration macros	19
2.14.2	Iterator type macros	19
2.14.2.1	Default iterator types	19
2.14.2.2	Forward iterator types	19
2.14.2.3	Backward iterators	19
2.14.2.4	Graph iterators	19
2.15	Common Compilation Errors	19
3	Tutorial	21
3.1	Welcome	21
3.1.1	How to learn Milena	21
3.1.2	Obtaining the library	21
3.1.3	Downloading the library	21
3.1.3.1	Downloading from SVN	21
3.1.3.2	Downloading packaged releases	21
3.1.4	Join the mailing lists	22
3.1.5	Directory structure	22
3.1.6	Documentation	22
3.1.7	Community and Support	22
3.1.8	Project status	22
3.1.9	A brief history of Milena	22
3.1.10	Contacts	22
3.2	Installation	22
3.2.1	Bootstrap (SVN Sources)	22
3.2.2	Configure	22
3.2.3	Install	22
3.2.4	Optional compilation	22
3.2.4.1	Examples	22
3.2.4.2	Tools	22
3.2.4.3	Tests	22
3.2.5	Installation content	22
3.3	Getting started with Milena	23
3.3.1	Getting familiar with genericity	23

3.3.2	First generic algorithm	23
3.3.3	Compilation	25
3.3.3.1	Include path	25
3.3.3.2	Library linking	25
3.3.3.3	Disable Debug	25
3.3.3.4	Compiler optimization flags	25
3.3.4	Debug hints	25
3.3.4.1	Using assertions and GDB	25
3.3.4.2	Traces	25
3.3.4.3	Debug routines	25
3.4	Data representation	26
3.4.1	Sites	26
3.4.2	Site sets	26
3.4.2.1	Creating a site set	26
3.4.2.2	Getting access to sites	27
3.4.3	Images	27
3.4.3.1	Creating an image	27
3.4.3.2	Reading an image from a file	27
3.4.3.3	Accessing data	27
3.5	Load and save images	27
3.6	Create your first image	27
3.7	Read and write images	28
3.8	Regions of interest	28
3.8.1	Image domain restricted by a site set	29
3.8.2	Image domain restricted by a function	29
3.8.3	Image domain restricted by a mask	29
3.8.4	Image domain restricted by a predicate	29
4	Module Index	31
4.1	Modules	31
5	Namespace Index	33
5.1	Namespace List	33
6	Class Index	37
6.1	Class Hierarchy	37
7	Class Index	81

7.1	Class List	81
8	Module Documentation	91
8.1	On site sets	91
8.1.1	Detailed Description	91
8.2	On images	91
8.2.1	Detailed Description	92
8.3	On values	92
8.3.1	Detailed Description	94
8.4	Multiple accumulators	94
8.4.1	Detailed Description	94
8.5	Graphes	94
8.5.1	Detailed Description	95
8.6	Images	95
8.6.1	Detailed Description	95
8.7	Basic types	95
8.7.1	Detailed Description	96
8.8	Image morphers	96
8.9	Values morphers	96
8.9.1	Detailed Description	97
8.10	Domain morphers	97
8.10.1	Detailed Description	97
8.11	Identity morphers	98
8.11.1	Detailed Description	98
8.12	Types	98
8.12.1	Detailed Description	99
8.13	Accumulators	99
8.13.1	Detailed Description	99
8.14	Routines	99
8.15	Canvas	99
8.16	Functions	100
8.16.1	Detailed Description	101
8.17	Neighborhoods	101
8.17.1	Detailed Description	101
8.18	1D neighborhoods	101
8.18.1	Detailed Description	102
8.18.2	Typedef Documentation	102

8.18.2.1 <code>neighb1d</code>	102
8.18.3 Function Documentation	102
8.18.3.1 <code>c2</code>	102
8.19 2D neighborhoods	102
8.19.1 Detailed Description	103
8.19.2 Typedef Documentation	103
8.19.2.1 <code>neighb2d</code>	103
8.19.3 Function Documentation	103
8.19.3.1 <code>c2_col</code>	103
8.19.3.2 <code>c2_row</code>	103
8.19.3.3 <code>c4</code>	103
8.19.3.4 <code>c8</code>	104
8.20 3D neighborhoods	104
8.20.1 Detailed Description	105
8.20.2 Typedef Documentation	105
8.20.2.1 <code>neighb3d</code>	105
8.20.3 Function Documentation	105
8.20.3.1 <code>c18</code>	105
8.20.3.2 <code>c26</code>	105
8.20.3.3 <code>c2_3d_sli</code>	106
8.20.3.4 <code>c4_3d</code>	106
8.20.3.5 <code>c6</code>	107
8.20.3.6 <code>c8_3d</code>	107
8.21 Site sets	108
8.21.1 Detailed Description	108
8.22 Basic types	108
8.22.1 Detailed Description	108
8.23 Graph based	109
8.23.1 Detailed Description	109
8.24 Complex based	109
8.24.1 Detailed Description	109
8.25 Sparse types	109
8.25.1 Detailed Description	110
8.26 Queue based	110
8.26.1 Detailed Description	110
8.27 Utilities	110

8.27.1	Detailed Description	111
8.28	Windows	111
8.28.1	Detailed Description	112
8.29	1D windows	112
8.29.1	Detailed Description	112
8.29.2	Typedef Documentation	112
8.29.2.1	segment1d	112
8.29.2.2	window1d	113
8.30	2D windows	113
8.30.1	Detailed Description	114
8.30.2	Typedef Documentation	114
8.30.2.1	disk2d	114
8.30.2.2	hline2d	114
8.30.2.3	vline2d	114
8.30.2.4	window2d	115
8.30.3	Function Documentation	115
8.30.3.1	win_c4p	115
8.30.3.2	win_c8p	115
8.31	3D windows	115
8.31.1	Detailed Description	116
8.31.2	Typedef Documentation	116
8.31.2.1	sline3d	116
8.31.2.2	sphere3d	117
8.31.2.3	window3d	117
8.31.3	Function Documentation	117
8.31.3.1	win_c4p_3d	117
8.31.3.2	win_c8p_3d	117
8.32	N-D windows	118
8.32.1	Detailed Description	118
8.33	Multiple windows	118
8.33.1	Detailed Description	118
8.34	v2w2v functions	118
8.35	v2w_w2v functions	119
8.36	vv2b functions	119
9	Namespace Documentation	121
9.1	mln Namespace Reference	121

9.1.1	Detailed Description	142
9.1.2	Typedef Documentation	145
9.1.2.1	bin_1complex_image2d	145
9.1.2.2	bin_2complex_image3df	145
9.1.2.3	box1d	145
9.1.2.4	box2d	145
9.1.2.5	box2d_h	146
9.1.2.6	box3d	146
9.1.2.7	discrete_plane_1complex_geometry	146
9.1.2.8	discrete_plane_2complex_geometry	146
9.1.2.9	dpoint1d	146
9.1.2.10	dpoint2d	146
9.1.2.11	dpoint2d_h	146
9.1.2.12	dpoint3d	147
9.1.2.13	float_2complex_image3df	147
9.1.2.14	int_u8_1complex_image2d	147
9.1.2.15	int_u8_2complex_image2d	147
9.1.2.16	int_u8_2complex_image3df	147
9.1.2.17	p_run2d	147
9.1.2.18	p_runs2d	147
9.1.2.19	point1d	148
9.1.2.20	point1df	148
9.1.2.21	point2d	148
9.1.2.22	point2d_h	148
9.1.2.23	point2df	148
9.1.2.24	point3d	148
9.1.2.25	point3df	148
9.1.2.26	rgb8_2complex_image3df	148
9.1.2.27	space_2complex_geometry	149
9.1.2.28	unsigned_2complex_image3df	149
9.1.2.29	vec2d_d	149
9.1.2.30	vec2d_f	149
9.1.2.31	vec3d_d	149
9.1.2.32	vec3d_f	149
9.1.2.33	w_window1d_float	149
9.1.2.34	w_window1d_int	149

9.1.2.35	w_window2d_float	150
9.1.2.36	w_window2d_int	150
9.1.2.37	w_window3d_float	150
9.1.2.38	w_window3d_int	150
9.1.3	Function Documentation	150
9.1.3.1	a_point_of	150
9.1.3.2	apply_p2p	150
9.1.3.3	apply_p2p	150
9.1.3.4	compose	151
9.1.3.5	duplicate	151
9.1.3.6	extend	151
9.1.3.7	extend	151
9.1.3.8	extend	152
9.1.3.9	implies	152
9.1.3.10	initialize	152
9.1.3.11	larger_than	152
9.1.3.12	make_debug_graph_image	152
9.1.3.13	mln_exact	153
9.1.3.14	mln_gen_complex_neighborhood	153
9.1.3.15	mln_gen_complex_neighborhood	153
9.1.3.16	mln_gen_complex_neighborhood	153
9.1.3.17	mln_gen_complex_neighborhood	153
9.1.3.18	mln_gen_complex_neighborhood	153
9.1.3.19	mln_gen_complex_neighborhood	154
9.1.3.20	mln_gen_complex_window	154
9.1.3.21	mln_gen_complex_window	154
9.1.3.22	mln_gen_complex_window	154
9.1.3.23	mln_gen_complex_window	154
9.1.3.24	mln_gen_complex_window	154
9.1.3.25	mln_gen_complex_window	154
9.1.3.26	mln_gen_complex_window_p	154
9.1.3.27	mln_gen_complex_window_p	154
9.1.3.28	mln_gen_complex_window_p	155
9.1.3.29	mln_gen_complex_window_p	155
9.1.3.30	mln_gen_complex_window_p	155
9.1.3.31	mln_gen_complex_window_p	155

9.1.3.32	mln_regular	155
9.1.3.33	mln_trait_op_geq	155
9.1.3.34	mln_trait_op_greater	155
9.1.3.35	mln_trait_op_leq	156
9.1.3.36	mln_trait_op_neq	156
9.1.3.37	operator!=	156
9.1.3.38	operator!=	157
9.1.3.39	operator*	157
9.1.3.40	operator++	157
9.1.3.41	operator-	157
9.1.3.42	operator-	157
9.1.3.43	operator--	158
9.1.3.44	operator<	158
9.1.3.45	operator<	158
9.1.3.46	operator<	158
9.1.3.47	operator<<	159
9.1.3.48	operator<<	159
9.1.3.49	operator<<	159
9.1.3.50	operator<<	159
9.1.3.51	operator<=	159
9.1.3.52	operator<=	159
9.1.3.53	operator<=	159
9.1.3.54	operator<=	160
9.1.3.55	operator<=	160
9.1.3.56	operator==	160
9.1.3.57	operator==	160
9.1.3.58	operator==	161
9.1.3.59	operator==	161
9.1.3.60	operator==	161
9.1.3.61	operator==	161
9.1.3.62	operator==	162
9.1.3.63	operator 	162
9.1.3.64	operator 	162
9.1.3.65	operator 	162
9.1.3.66	operator 	162
9.1.3.67	operator 	163

9.1.3.68	operator 	163
9.1.3.69	primary	163
9.1.3.70	ptransform	163
9.1.4	Variable Documentation	163
9.1.4.1	before	163
9.1.4.2	sagittal_dec	163
9.1.4.3	up	164
9.2	mln::accu Namespace Reference	164
9.2.1	Detailed Description	166
9.2.2	Function Documentation	166
9.2.2.1	compute	166
9.2.2.2	line	166
9.2.2.3	mln_meta_accu_result	167
9.2.2.4	take	167
9.3	mln::accu::image Namespace Reference	167
9.3.1	Detailed Description	167
9.4	mln::accu::impl Namespace Reference	167
9.4.1	Detailed Description	168
9.5	mln::accu::logic Namespace Reference	168
9.5.1	Detailed Description	168
9.6	mln::accu::math Namespace Reference	168
9.6.1	Detailed Description	169
9.7	mln::accu::meta::logic Namespace Reference	169
9.7.1	Detailed Description	169
9.8	mln::accu::meta::math Namespace Reference	169
9.8.1	Detailed Description	170
9.9	mln::accu::meta::shape Namespace Reference	170
9.9.1	Detailed Description	170
9.10	mln::accu::meta::stat Namespace Reference	170
9.10.1	Detailed Description	171
9.11	mln::accu::shape Namespace Reference	171
9.11.1	Detailed Description	171
9.12	mln::accu::stat Namespace Reference	171
9.12.1	Detailed Description	173
9.12.2	Function Documentation	173
9.12.2.1	operator==	173

9.13 mln::algebra Namespace Reference	173
9.13.1 Detailed Description	174
9.13.2 Function Documentation	174
9.13.2.1 ldlt_decomp	174
9.13.2.2 ldlt_solve	174
9.13.2.3 operator*	174
9.13.2.4 vprod	174
9.14 mln::arith Namespace Reference	175
9.14.1 Detailed Description	177
9.14.2 Function Documentation	177
9.14.2.1 diff_abs	177
9.14.2.2 div	178
9.14.2.3 div_cst	178
9.14.2.4 div_inplace	178
9.14.2.5 min	179
9.14.2.6 min_inplace	179
9.14.2.7 minus	179
9.14.2.8 minus	180
9.14.2.9 minus	180
9.14.2.10 minus_cst	181
9.14.2.11 minus_cst	181
9.14.2.12 minus_cst_inplace	181
9.14.2.13 minus_inplace	182
9.14.2.14 plus	182
9.14.2.15 plus	183
9.14.2.16 plus	183
9.14.2.17 plus_cst	183
9.14.2.18 plus_cst	184
9.14.2.19 plus_cst	184
9.14.2.20 plus_cst_inplace	185
9.14.2.21 plus_inplace	185
9.14.2.22 revert	185
9.14.2.23 revert_inplace	186
9.14.2.24 times	186
9.14.2.25 times_cst	186
9.14.2.26 times_inplace	187

9.15 mln::arith::impl Namespace Reference	187
9.15.1 Detailed Description	187
9.16 mln::arith::impl::generic Namespace Reference	188
9.16.1 Detailed Description	188
9.17 mln::binarization Namespace Reference	188
9.17.1 Detailed Description	188
9.17.2 Function Documentation	188
9.17.2.1 binarization	188
9.17.2.2 threshold	189
9.18 mln::border Namespace Reference	189
9.18.1 Detailed Description	189
9.18.2 Function Documentation	190
9.18.2.1 adjust	190
9.18.2.2 duplicate	190
9.18.2.3 equalize	190
9.18.2.4 fill	191
9.18.2.5 find	191
9.18.2.6 get	191
9.18.2.7 mirror	192
9.18.2.8 resize	192
9.19 mln::border::impl Namespace Reference	192
9.19.1 Detailed Description	193
9.20 mln::border::impl::generic Namespace Reference	193
9.20.1 Detailed Description	193
9.21 mln::canvas Namespace Reference	193
9.21.1 Detailed Description	194
9.21.2 Function Documentation	194
9.21.2.1 distance_front	194
9.21.2.2 distance_geodesic	194
9.22 mln::canvas::browsing Namespace Reference	194
9.22.1 Detailed Description	195
9.23 mln::canvas::impl Namespace Reference	195
9.23.1 Detailed Description	195
9.24 mln::canvas::labeling Namespace Reference	195
9.24.1 Detailed Description	196
9.24.2 Function Documentation	196

9.24.2.1	<code>blobs</code>	196
9.25	<code>mln::canvas::labeling::impl Namespace Reference</code>	196
9.25.1	Detailed Description	197
9.26	<code>mln::canvas::morpho Namespace Reference</code>	197
9.26.1	Detailed Description	197
9.27	<code>mln::convert Namespace Reference</code>	197
9.27.1	Detailed Description	199
9.27.2	Function Documentation	199
9.27.2.1	<code>from_to</code>	199
9.27.2.2	<code>from_to</code>	200
9.27.2.3	<code>from_to</code>	200
9.27.2.4	<code>from_to</code>	200
9.27.2.5	<code>mln_image_from_grid</code>	200
9.27.2.6	<code>mln_image_from_grid</code>	200
9.27.2.7	<code>mln_image_from_grid</code>	200
9.27.2.8	<code>mln_image_from_grid</code>	200
9.27.2.9	<code>mln_window</code>	200
9.27.2.10	<code>to</code>	200
9.27.2.11	<code>to_dpoint</code>	201
9.27.2.12	<code>to_fun</code>	201
9.27.2.13	<code>to_image</code>	201
9.27.2.14	<code>to_p_array</code>	201
9.27.2.15	<code>to_p_array</code>	201
9.27.2.16	<code>to_p_array</code>	201
9.27.2.17	<code>to_p_set</code>	201
9.27.2.18	<code>to_p_set</code>	202
9.27.2.19	<code>to_p_set</code>	202
9.27.2.20	<code>to_p_set</code>	202
9.27.2.21	<code>to_p_set</code>	202
9.27.2.22	<code>to_qimage</code>	202
9.27.2.23	<code>to_upper_window</code>	202
9.27.2.24	<code>to_upper_window</code>	203
9.27.2.25	<code>to_window</code>	203
9.27.2.26	<code>to_window</code>	203
9.27.2.27	<code>to_window</code>	203
9.27.3	Variable Documentation	203

9.27.3.1	to_fun	203
9.28	mln::data Namespace Reference	203
9.28.1	Detailed Description	205
9.28.2	Function Documentation	206
9.28.2.1	abs	206
9.28.2.2	abs_inplace	206
9.28.2.3	apply	206
9.28.2.4	compute	206
9.28.2.5	compute	207
9.28.2.6	convert	207
9.28.2.7	fast_median	207
9.28.2.8	fill	208
9.28.2.9	fill_with_image	208
9.28.2.10	fill_with_value	209
9.28.2.11	median	209
9.28.2.12	mln_meta_accu_result	209
9.28.2.13	paste	209
9.28.2.14	paste_without_localization	210
9.28.2.15	replace	210
9.28.2.16	saturate	210
9.28.2.17	saturate	211
9.28.2.18	saturate_inplace	211
9.28.2.19	sort_offsets_increasing	211
9.28.2.20	sort_psites_decreasing	212
9.28.2.21	sort_psites_increasing	212
9.28.2.22	stretch	212
9.28.2.23	to_enc	213
9.28.2.24	transform	213
9.28.2.25	transform	213
9.28.2.26	transform_inplace	214
9.28.2.27	transform_inplace	214
9.28.2.28	update	214
9.28.2.29	wrap	215
9.29	mln::data::approx Namespace Reference	215
9.29.1	Detailed Description	215
9.29.2	Function Documentation	215

9.29.2.1	median	215
9.29.2.2	median	216
9.29.2.3	median	216
9.30	mln::data::approx::impl Namespace Reference	217
9.30.1	Detailed Description	217
9.31	mln::data::impl Namespace Reference	217
9.31.1	Detailed Description	217
9.31.2	Function Documentation	218
9.31.2.1	paste_without_localization_fast	218
9.31.2.2	paste_without_localization_fastest	218
9.31.2.3	paste_without_localization_lines	219
9.31.2.4	stretch	219
9.31.2.5	transform_inplace_lowq	219
9.31.2.6	update_fastest	220
9.32	mln::data::impl::generic Namespace Reference	220
9.32.1	Detailed Description	221
9.32.2	Function Documentation	221
9.32.2.1	fill_with_image	221
9.32.2.2	fill_with_value	221
9.32.2.3	paste	221
9.32.2.4	transform	222
9.32.2.5	transform	222
9.32.2.6	transform_inplace	222
9.32.2.7	transform_inplace	222
9.32.2.8	update	223
9.33	mln::data::naive Namespace Reference	223
9.33.1	Detailed Description	223
9.33.2	Function Documentation	223
9.33.2.1	median	223
9.34	mln::data::naive::impl Namespace Reference	224
9.34.1	Detailed Description	224
9.35	mln::debug Namespace Reference	224
9.35.1	Detailed Description	226
9.35.2	Function Documentation	226
9.35.2.1	draw_graph	226
9.35.2.2	draw_graph	226

9.35.2.3	draw_graph	227
9.35.2.4	filename	227
9.35.2.5	format	227
9.35.2.6	format	227
9.35.2.7	format	227
9.35.2.8	format	228
9.35.2.9	iota	228
9.35.2.10	mosaic	228
9.35.2.11	println	228
9.35.2.12	println	228
9.35.2.13	println_with_border	229
9.35.2.14	put_word	229
9.35.2.15	slices_2d	229
9.35.2.16	slices_2d	229
9.35.2.17	superpose	229
9.35.2.18	superpose	229
9.35.2.19	z_order	230
9.36	mln::debug::impl Namespace Reference	230
9.36.1	Detailed Description	230
9.37	mln::def Namespace Reference	230
9.37.1	Detailed Description	231
9.37.2	Typedef Documentation	231
9.37.2.1	coord	231
9.37.2.2	coordf	231
9.37.3	Enumeration Type Documentation	231
9.37.3.1	"@21	231
9.38	mln::display Namespace Reference	231
9.38.1	Detailed Description	232
9.39	mln::display::impl Namespace Reference	232
9.39.1	Detailed Description	232
9.40	mln::display::impl::generic Namespace Reference	232
9.40.1	Detailed Description	232
9.41	mln::doc Namespace Reference	232
9.41.1	Detailed Description	233
9.42	mln::draw Namespace Reference	234
9.42.1	Detailed Description	234

9.42.2 Function Documentation	234
9.42.2.1 box	234
9.42.2.2 box_plain	235
9.42.2.3 dashed_line	235
9.42.2.4 line	235
9.42.2.5 plot	236
9.42.2.6 polygon	236
9.42.2.7 site_set	237
9.43 mln::estim Namespace Reference	237
9.43.1 Detailed Description	237
9.43.2 Function Documentation	238
9.43.2.1 mean	238
9.43.2.2 mean	238
9.43.2.3 min_max	238
9.43.2.4 sum	239
9.43.2.5 sum	239
9.44 mln::extension Namespace Reference	239
9.44.1 Detailed Description	240
9.44.2 Function Documentation	240
9.44.2.1 adjust	240
9.44.2.2 adjust	240
9.44.2.3 adjust	240
9.44.2.4 adjust	241
9.44.2.5 adjust_duplicate	241
9.44.2.6 adjust_fill	241
9.44.2.7 duplicate	241
9.44.2.8 fill	241
9.45 mln::fun Namespace Reference	242
9.45.1 Detailed Description	243
9.46 mln::fun::access Namespace Reference	243
9.46.1 Detailed Description	243
9.47 mln::fun::i2v Namespace Reference	243
9.47.1 Detailed Description	243
9.47.2 Function Documentation	244
9.47.2.1 operator<<	244
9.48 mln::fun::n2v Namespace Reference	244

9.48.1	Detailed Description	244
9.49	mln::fun::p2b Namespace Reference	244
9.49.1	Detailed Description	244
9.50	mln::fun::p2p Namespace Reference	244
9.50.1	Detailed Description	245
9.51	mln::fun::p2v Namespace Reference	245
9.51.1	Detailed Description	245
9.52	mln::fun::stat Namespace Reference	245
9.52.1	Detailed Description	245
9.53	mln::fun::v2b Namespace Reference	245
9.53.1	Detailed Description	245
9.54	mln::fun::v2i Namespace Reference	245
9.54.1	Detailed Description	246
9.55	mln::fun::v2v Namespace Reference	246
9.55.1	Detailed Description	247
9.55.2	Variable Documentation	247
9.55.2.1	f_hsi_to_rgb_3x8	247
9.55.2.2	f_hsl_to_rgb_3x8	247
9.55.2.3	f_rgb_to_hsi_f	247
9.55.2.4	f_rgb_to_hsl_f	247
9.56	mln::fun::v2w2v Namespace Reference	247
9.56.1	Detailed Description	247
9.57	mln::fun::v2w_w2v Namespace Reference	247
9.57.1	Detailed Description	248
9.58	mln::fun::vv2b Namespace Reference	248
9.58.1	Detailed Description	248
9.59	mln::fun::vv2v Namespace Reference	249
9.59.1	Detailed Description	249
9.60	mln::fun::x2p Namespace Reference	249
9.60.1	Detailed Description	249
9.61	mln::fun::x2v Namespace Reference	250
9.61.1	Detailed Description	250
9.62	mln::fun::x2x Namespace Reference	250
9.62.1	Detailed Description	250
9.63	mln::geom Namespace Reference	250
9.63.1	Detailed Description	255

9.63.2 Function Documentation	255
9.63.2.1 bbox	255
9.63.2.2 bbox	255
9.63.2.3 bbox	255
9.63.2.4 bbox	255
9.63.2.5 chamfer	255
9.63.2.6 delta	256
9.63.2.7 delta	256
9.63.2.8 delta	256
9.63.2.9 horizontal_symmetry	256
9.63.2.10 max_col	256
9.63.2.11 max_col	256
9.63.2.12 max_ind	257
9.63.2.13 max_row	257
9.63.2.14 max_row	257
9.63.2.15 max_sli	257
9.63.2.16 mesh_corner_point_area	257
9.63.2.17 mesh_curvature	258
9.63.2.18 mesh_normal	258
9.63.2.19 min_col	258
9.63.2.20 min_col	259
9.63.2.21 min_ind	259
9.63.2.22 min_row	259
9.63.2.23 min_row	259
9.63.2.24 min_sli	259
9.63.2.25 ncols	259
9.63.2.26 ncols	260
9.63.2.27 ninds	260
9.63.2.28 nrows	260
9.63.2.29 nrows	260
9.63.2.30 nsites	260
9.63.2.31 nslis	260
9.63.2.32 pmin_pmax	261
9.63.2.33 pmin_pmax	261
9.63.2.34 pmin_pmax	261
9.63.2.35 pmin_pmax	261

9.63.2.36 rotate	261
9.63.2.37 rotate	261
9.63.2.38 rotate	262
9.63.2.39 rotate	262
9.63.2.40 rotate	262
9.63.2.41 seeds2tiling	262
9.63.2.42 seeds2tiling_roundness	263
9.63.2.43 translate	263
9.63.2.44 translate	263
9.63.2.45 translate	264
9.63.2.46 vertical_symmetry	264
9.64 mln::geom::impl Namespace Reference	264
9.64.1 Detailed Description	264
9.64.2 Function Documentation	265
9.64.2.1 seeds2tiling	265
9.65 mln::graph Namespace Reference	265
9.65.1 Detailed Description	265
9.65.2 Function Documentation	266
9.65.2.1 compute	266
9.65.2.2 labeling	266
9.65.2.3 to_neighb	266
9.65.2.4 to_win	267
9.66 mln::grid Namespace Reference	267
9.66.1 Detailed Description	267
9.67 mln::histo Namespace Reference	267
9.67.1 Detailed Description	268
9.67.2 Function Documentation	268
9.67.2.1 compute	268
9.67.2.2 equalize	268
9.68 mln::histo::impl Namespace Reference	269
9.68.1 Detailed Description	269
9.69 mln::histo::impl::generic Namespace Reference	269
9.69.1 Detailed Description	269
9.70 mln::impl Namespace Reference	269
9.70.1 Detailed Description	269
9.71 mln::io Namespace Reference	269

9.71.1	Detailed Description	271
9.72	mln::io::cloud Namespace Reference	271
9.72.1	Detailed Description	271
9.72.2	Function Documentation	271
9.72.2.1	load	271
9.72.2.2	save	271
9.73	mln::io::dicom Namespace Reference	272
9.73.1	Detailed Description	272
9.73.2	Function Documentation	272
9.73.2.1	get_header	272
9.73.2.2	load	272
9.74	mln::io::dump Namespace Reference	273
9.74.1	Detailed Description	273
9.74.2	Function Documentation	273
9.74.2.1	get_header	273
9.74.2.2	load	274
9.74.2.3	save	274
9.75	mln::io::fits Namespace Reference	274
9.75.1	Detailed Description	274
9.75.2	Function Documentation	274
9.75.2.1	load	274
9.75.2.2	load	275
9.76	mln::io::fld Namespace Reference	275
9.76.1	Detailed Description	275
9.76.2	Function Documentation	276
9.76.2.1	load	276
9.76.2.2	read_header	276
9.76.2.3	write_header	276
9.77	mln::io::magick Namespace Reference	276
9.77.1	Detailed Description	277
9.77.2	Function Documentation	277
9.77.2.1	load	277
9.77.2.2	save	277
9.77.2.3	save	278
9.78	mln::io::off Namespace Reference	278
9.78.1	Detailed Description	278

9.78.2 Function Documentation	278
9.78.2.1 load	278
9.78.2.2 save	279
9.78.2.3 save_bin_alt	279
9.79 mln::io::pbm Namespace Reference	279
9.79.1 Detailed Description	280
9.79.2 Function Documentation	280
9.79.2.1 load	280
9.79.2.2 load	280
9.79.2.3 save	281
9.80 mln::io::pbm::impl Namespace Reference	281
9.80.1 Detailed Description	281
9.81 mln::io::pbms Namespace Reference	281
9.81.1 Detailed Description	281
9.81.2 Function Documentation	281
9.81.2.1 load	281
9.82 mln::io::pbms::impl Namespace Reference	282
9.82.1 Detailed Description	282
9.83 mln::io::pfm Namespace Reference	282
9.83.1 Detailed Description	282
9.83.2 Function Documentation	283
9.83.2.1 load	283
9.83.2.2 load	283
9.83.2.3 save	283
9.84 mln::io::pfm::impl Namespace Reference	283
9.84.1 Detailed Description	283
9.85 mln::io::pgm Namespace Reference	284
9.85.1 Detailed Description	284
9.85.2 Function Documentation	284
9.85.2.1 load	284
9.85.2.2 load	284
9.85.2.3 save	285
9.86 mln::io::pgms Namespace Reference	285
9.86.1 Detailed Description	285
9.86.2 Function Documentation	285
9.86.2.1 load	285

9.87 mln::io::plot Namespace Reference	285
9.87.1 Detailed Description	286
9.87.2 Function Documentation	286
9.87.2.1 load	286
9.87.2.2 save	286
9.87.2.3 save	287
9.87.2.4 save	287
9.88 mln::io::pnm Namespace Reference	287
9.88.1 Detailed Description	288
9.88.2 Function Documentation	288
9.88.2.1 load	288
9.88.2.2 load	288
9.88.2.3 load_ascii_builtin	288
9.88.2.4 load_ascii_value	288
9.88.2.5 load_raw_2d	289
9.88.2.6 max_component	289
9.88.2.7 save	289
9.89 mln::io::pnm::impl Namespace Reference	289
9.89.1 Detailed Description	289
9.90 mln::io::pnms Namespace Reference	289
9.90.1 Detailed Description	290
9.90.2 Function Documentation	290
9.90.2.1 load	290
9.90.2.2 load	290
9.91 mln::io::ppm Namespace Reference	290
9.91.1 Detailed Description	291
9.91.2 Function Documentation	291
9.91.2.1 load	291
9.91.2.2 load	291
9.91.2.3 save	291
9.92 mln::io::ppms Namespace Reference	292
9.92.1 Detailed Description	292
9.92.2 Function Documentation	292
9.92.2.1 load	292
9.93 mln::io::raw Namespace Reference	292
9.93.1 Detailed Description	293

9.93.2 Function Documentation	293
9.93.2.1 get_header	293
9.93.2.2 load	293
9.93.2.3 save	293
9.94 mln::io::tiff Namespace Reference	294
9.94.1 Detailed Description	294
9.94.2 Function Documentation	294
9.94.2.1 load	294
9.95 mln::io::txt Namespace Reference	294
9.95.1 Detailed Description	294
9.95.2 Function Documentation	295
9.95.2.1 save	295
9.96 mln::labeling Namespace Reference	295
9.96.1 Detailed Description	298
9.96.2 Function Documentation	298
9.96.2.1 background	298
9.96.2.2 blobs	299
9.96.2.3 blobs_and_compute	299
9.96.2.4 colorize	300
9.96.2.5 colorize	300
9.96.2.6 colorize	300
9.96.2.7 compute	300
9.96.2.8 compute	301
9.96.2.9 compute	301
9.96.2.10 compute	302
9.96.2.11 compute	302
9.96.2.12 compute_image	302
9.96.2.13 compute_image	303
9.96.2.14 compute_image	303
9.96.2.15 fill_holes	304
9.96.2.16 flat_zones	304
9.96.2.17 foreground	305
9.96.2.18 pack	305
9.96.2.19 pack	306
9.96.2.20 pack_inplace	306
9.96.2.21 pack_inplace	306

9.96.2.22 regional_maxima	306
9.96.2.23 regional_minima	307
9.96.2.24 relabel	307
9.96.2.25 relabel	307
9.96.2.26 relabel_inplace	308
9.96.2.27 relabel_inplace	308
9.96.2.28 superpose	308
9.96.2.29 value	309
9.96.2.30 value_and_compute	309
9.96.2.31 wrap	310
9.96.2.32 wrap	310
9.97 mln::labeling::impl Namespace Reference	310
9.97.1 Detailed Description	311
9.97.2 Function Documentation	311
9.97.2.1 compute_fastest	311
9.97.2.2 compute_fastest	312
9.98 mln::labeling::impl::generic Namespace Reference	312
9.98.1 Detailed Description	312
9.98.2 Function Documentation	313
9.98.2.1 compute	313
9.98.2.2 compute	313
9.98.2.3 compute	313
9.98.2.4 compute	314
9.99 mln::linear Namespace Reference	314
9.99.1 Detailed Description	315
9.99.2 Function Documentation	315
9.99.2.1 gaussian	315
9.99.2.2 gaussian	316
9.99.2.3 gaussian_1st_derivative	316
9.99.2.4 gaussian_1st_derivative	316
9.99.2.5 gaussian_2nd_derivative	316
9.99.2.6 mln_ch_convolve	317
9.99.2.7 mln_ch_convolve	317
9.99.2.8 mln_ch_convolve	317
9.99.2.9 mln_ch_convolve	317
9.99.2.10 mln_ch_convolve_grad	318

9.100mln::linear::impl Namespace Reference	318
9.100.1 Detailed Description	318
9.101mln::linear::local Namespace Reference	318
9.101.1 Detailed Description	318
9.101.2 Function Documentation	319
9.101.2.1 convolve	319
9.101.2.2 convolve	319
9.102mln::linear::local::impl Namespace Reference	319
9.102.1 Detailed Description	319
9.103mln::literal Namespace Reference	319
9.103.1 Detailed Description	322
9.103.2 Variable Documentation	323
9.103.2.1 black	323
9.103.2.2 blue	323
9.103.2.3 brown	323
9.103.2.4 cyan	323
9.103.2.5 dark_gray	323
9.103.2.6 green	323
9.103.2.7 identity	323
9.103.2.8 light_gray	323
9.103.2.9 lime	324
9.103.2.10magenta	324
9.103.2.11max	324
9.103.2.12medium_gray	324
9.103.2.13min	324
9.103.2.14olive	324
9.103.2.15one	324
9.103.2.16orange	324
9.103.2.17origin	325
9.103.2.18pink	325
9.103.2.19purple	325
9.103.2.20red	325
9.103.2.21teal	325
9.103.2.22violet	325
9.103.2.23white	325
9.103.2.24yellow	325

9.103.2.2 <code>zero</code>	326
9.104 <code>mln::logical Namespace Reference</code>	326
9.104.1 Detailed Description	326
9.104.2 Function Documentation	327
9.104.2.1 <code>and_inplace</code>	327
9.104.2.2 <code>and_not</code>	327
9.104.2.3 <code>and_not_inplace</code>	327
9.104.2.4 <code>not_inplace</code>	328
9.104.2.5 <code>or_inplace</code>	328
9.104.2.6 <code>xor_inplace</code>	329
9.105 <code>mln::logical::impl Namespace Reference</code>	329
9.105.1 Detailed Description	329
9.106 <code>mln::logical::impl::generic Namespace Reference</code>	329
9.106.1 Detailed Description	330
9.107 <code>mln::make Namespace Reference</code>	330
9.107.1 Detailed Description	335
9.107.2 Function Documentation	335
9.107.2.1 <code>attachment</code>	335
9.107.2.2 <code>box1d</code>	335
9.107.2.3 <code>box1d</code>	336
9.107.2.4 <code>box2d</code>	336
9.107.2.5 <code>box2d</code>	336
9.107.2.6 <code>box2d_h</code>	337
9.107.2.7 <code>box2d_h</code>	337
9.107.2.8 <code>box3d</code>	338
9.107.2.9 <code>box3d</code>	338
9.107.2.10 <code>cell</code>	339
9.107.2.11 <code>couple</code>	339
9.107.2.12 <code>detachment</code>	339
9.107.2.13 <code>dpoint2d_h</code>	339
9.107.2.14 <code>dummy_p_edges</code>	340
9.107.2.15 <code>dummy_p_edges</code>	340
9.107.2.16 <code>dummy_p_vertices</code>	340
9.107.2.17 <code>dummy_p_vertices</code>	341
9.107.2.18 <code>edge_image</code>	341
9.107.2.19 <code>edge_image</code>	341

9.107.2.20edge_image	342
9.107.2.21edge_image	342
9.107.2.22edge_image	342
9.107.2.23edge_image	343
9.107.2.24h_mat	343
9.107.2.25image	343
9.107.2.26image	343
9.107.2.27image	344
9.107.2.28image2d	344
9.107.2.29image3d	344
9.107.2.30image3d	344
9.107.2.31influence_zone_adjacency_graph	345
9.107.2.32mat	345
9.107.2.33ord_pair	345
9.107.2.34p_edges_with_mass_centers	345
9.107.2.35p_vertices_with_mass_centers	346
9.107.2.36pix	346
9.107.2.37pixel	346
9.107.2.38pixel	347
9.107.2.39point2d_h	347
9.107.2.40rag_and_labeled_wsl	347
9.107.2.41region_adjacency_graph	348
9.107.2.42relabelfun	348
9.107.2.43relabelfun	349
9.107.2.44vec	349
9.107.2.45vec	349
9.107.2.46vec	350
9.107.2.47vec	350
9.107.2.48vertex_image	350
9.107.2.49vertex_image	351
9.107.2.50voronoi	351
9.107.2.51w_window	351
9.107.2.52w_window1d	352
9.107.2.53w_window1d_int	352
9.107.2.54w_window2d	352
9.107.2.55w_window2d_int	353

9.107.2.56w_window3d	353
9.107.2.57w_window3d_int	353
9.107.2.58w_window_directional	354
9.108mln::math Namespace Reference	354
9.108.1 Detailed Description	355
9.108.2 Function Documentation	355
9.108.2.1 abs	355
9.108.2.2 abs	355
9.108.2.3 abs	355
9.109mln::metal Namespace Reference	355
9.109.1 Detailed Description	356
9.110mln::metal::impl Namespace Reference	356
9.110.1 Detailed Description	356
9.111mln::metal::math Namespace Reference	356
9.111.1 Detailed Description	356
9.112mln::metal::math::impl Namespace Reference	357
9.112.1 Detailed Description	357
9.113mln::morpho Namespace Reference	357
9.113.1 Detailed Description	360
9.113.2 Function Documentation	360
9.113.2.1 complementation	360
9.113.2.2 complementation_inplace	360
9.113.2.3 contrast	360
9.113.2.4 dilation	360
9.113.2.5 erosion	361
9.113.2.6 general	361
9.113.2.7 gradient	361
9.113.2.8 gradient_external	361
9.113.2.9 gradient_internal	361
9.113.2.10hit_or_miss	362
9.113.2.11hit_or_miss_background_closing	362
9.113.2.12hit_or_miss_background_opening	362
9.113.2.13hit_or_miss_closing	362
9.113.2.14hit_or_miss_opening	363
9.113.2.15laplacian	363
9.113.2.16line_gradient	363

9.113.2.17	meyer_wst	363
9.113.2.18	meyer_wst	364
9.113.2.19	min	364
9.113.2.20	min_inplace	364
9.113.2.21	minus	364
9.113.2.22	plus	365
9.113.2.23	rank_filter	365
9.113.2.24	thick_miss	365
9.113.2.25	thickening	365
9.113.2.26	thin_fit	365
9.113.2.27	thinning	366
9.113.2.28	top_hat_black	366
9.113.2.29	top_hat_self_complementary	366
9.113.2.30	top_hat_white	366
9.114	mln::morpho::approx Namespace Reference	367
9.114.1	Detailed Description	367
9.115	mln::morpho::attribute Namespace Reference	367
9.115.1	Detailed Description	367
9.116	mln::morpho::closing::approx Namespace Reference	367
9.116.1	Detailed Description	368
9.116.2	Function Documentation	368
9.116.2.1	structural	368
9.117	mln::morpho::elementary Namespace Reference	368
9.117.1	Detailed Description	369
9.117.2	Function Documentation	369
9.117.2.1	closing	369
9.117.2.2	mln_trait_op_minus_twice	369
9.117.2.3	opening	369
9.117.2.4	top_hat_black	369
9.117.2.5	top_hat_white	369
9.118	mln::morpho::impl Namespace Reference	370
9.118.1	Detailed Description	370
9.119	mln::morpho::impl::generic Namespace Reference	370
9.119.1	Detailed Description	370
9.120	mln::morpho::opening::approx Namespace Reference	370
9.120.1	Detailed Description	370

9.120.2 Function Documentation	371
9.120.2.1 structural	371
9.121mln::morpho::reconstruction Namespace Reference	371
9.121.1 Detailed Description	371
9.122mln::morpho::reconstruction::by_dilation Namespace Reference	371
9.122.1 Detailed Description	371
9.123mln::morpho::reconstruction::by_erosion Namespace Reference	371
9.123.1 Detailed Description	372
9.124mln::morpho::tree Namespace Reference	372
9.124.1 Detailed Description	373
9.124.2 Function Documentation	373
9.124.2.1 compute_attribute_image	373
9.124.2.2 compute_attribute_image_from	374
9.124.2.3 compute_parent	374
9.124.2.4 dual_input_max_tree	375
9.124.2.5 max_tree	376
9.124.2.6 min_tree	376
9.124.2.7 propagate_if	377
9.124.2.8 propagate_if	377
9.124.2.9 propagate_if_value	377
9.124.2.10propagate_if_value	377
9.124.2.11propagate_node_to_ancestors	378
9.124.2.12propagate_node_to_ancestors	378
9.124.2.13propagate_node_to_descendants	378
9.124.2.14propagate_node_to_descendants	379
9.124.2.15propagateRepresentative	379
9.125mln::morpho::tree::filter Namespace Reference	379
9.125.1 Detailed Description	380
9.125.2 Function Documentation	380
9.125.2.1 direct	380
9.125.2.2 filter	380
9.125.2.3 max	381
9.125.2.4 min	381
9.125.2.5 subtractive	381
9.126mln::morpho::watershed Namespace Reference	382
9.126.1 Detailed Description	382

9.126.2 Function Documentation	382
9.126.2.1 flooding	382
9.126.2.2 flooding	383
9.126.2.3 superpose	383
9.126.2.4 superpose	383
9.126.2.5 topological	384
9.127mln::morpho::watershed::watershed Namespace Reference	384
9.127.1 Detailed Description	384
9.128mln::morpho::watershed::watershed::generic Namespace Reference	384
9.128.1 Detailed Description	384
9.129mln::norm Namespace Reference	384
9.129.1 Detailed Description	385
9.129.2 Function Documentation	385
9.129.2.1 l1	385
9.129.2.2 l1_distance	386
9.129.2.3 l2	386
9.129.2.4 l2_distance	386
9.129.2.5 linfty	386
9.129.2.6 linfty_distance	386
9.129.2.7 sqr_l2	386
9.130mln::norm::impl Namespace Reference	386
9.130.1 Detailed Description	387
9.131mln::opt Namespace Reference	387
9.131.1 Detailed Description	387
9.131.2 Function Documentation	388
9.131.2.1 at	388
9.131.2.2 at	388
9.131.2.3 at	388
9.131.2.4 at	388
9.131.2.5 at	388
9.131.2.6 at	388
9.132mln::opt::impl Namespace Reference	388
9.132.1 Detailed Description	389
9.133mln::pw Namespace Reference	389
9.133.1 Detailed Description	389
9.134mln::registration Namespace Reference	389

9.134.1 Detailed Description	390
9.134.2 Function Documentation	390
9.134.2.1 get_rot	390
9.134.2.2 icp	390
9.134.2.3 icp	391
9.134.2.4 registration1	391
9.134.2.5 registration2	391
9.134.2.6 registration3	392
9.135mln::select Namespace Reference	392
9.135.1 Detailed Description	392
9.136mln::set Namespace Reference	392
9.136.1 Detailed Description	393
9.136.2 Function Documentation	393
9.136.2.1 card	393
9.136.2.2 compute	393
9.136.2.3 compute_with_weights	393
9.136.2.4 get	394
9.136.2.5 has	394
9.136.2.6 mln_meta_accu_result	394
9.136.2.7 mln_meta_accu_result	394
9.137mln::subsampling Namespace Reference	394
9.137.1 Detailed Description	395
9.137.2 Function Documentation	395
9.137.2.1 antialiased	395
9.137.2.2 antialiased	395
9.137.2.3 gaussian_subsampling	396
9.137.2.4 subsampling	396
9.138mln::tag Namespace Reference	396
9.138.1 Detailed Description	396
9.139mln::test Namespace Reference	396
9.139.1 Detailed Description	397
9.139.2 Function Documentation	397
9.139.2.1 positive	397
9.139.2.2 predicate	397
9.139.2.3 predicate	397
9.139.2.4 predicate	398

9.140mln::test::impl Namespace Reference	398
9.140.1 Detailed Description	398
9.141mln::topo Namespace Reference	398
9.141.1 Detailed Description	402
9.141.2 Function Documentation	403
9.141.2.1 detach	403
9.141.2.2 edge	403
9.141.2.3 is_facet	403
9.141.2.4 make_algebraic_face	403
9.141.2.5 operator!=	404
9.141.2.6 operator!=	404
9.141.2.7 operator!=	404
9.141.2.8 operator!=	404
9.141.2.9 operator+	405
9.141.2.10 operator-	405
9.141.2.11 operator-	405
9.141.2.12 operator-	405
9.141.2.13 operator<	405
9.141.2.14 operator<	405
9.141.2.15 operator<	406
9.141.2.16 operator<	406
9.141.2.17 operator<<	406
9.141.2.18 operator<<	406
9.141.2.19 operator<<	406
9.141.2.20 operator<<	407
9.141.2.21 operator<<	407
9.141.2.22 operator==	407
9.141.2.23 operator==	407
9.141.2.24 operator==	407
9.141.2.25 operator==	408
9.141.2.26 operator==	408
9.142mln::trace Namespace Reference	408
9.142.1 Detailed Description	408
9.143mln::trait Namespace Reference	408
9.143.1 Detailed Description	408
9.144mln::transform Namespace Reference	408

9.144.1 Detailed Description	410
9.144.2 Function Documentation	410
9.144.2.1 distance_and_closest_point_geodesic	410
9.144.2.2 distance_and_closest_point_geodesic	410
9.144.2.3 distance_and_influence_zone_geodesic	411
9.144.2.4 distance_front	411
9.144.2.5 distance_geodesic	411
9.144.2.6 hough	412
9.144.2.7 influence_zone_front	412
9.144.2.8 influence_zone_front	412
9.144.2.9 influence_zone_geodesic	412
9.144.2.10 influence_zone_geodesic_saturated	413
9.144.2.11 influence_zone_geodesic_saturated	413
9.145 mln::util Namespace Reference	413
9.145.1 Detailed Description	417
9.145.2 Typedef Documentation	417
9.145.2.1 vertex_id_t	417
9.145.3 Function Documentation	417
9.145.3.1 display_branch	417
9.145.3.2 display_tree	417
9.145.3.3 lemmings	418
9.145.3.4 make_greater_point	418
9.145.3.5 make_greater_psite	418
9.145.3.6 operator<	418
9.145.3.7 operator<<	418
9.145.3.8 operator<<	418
9.145.3.9 operator==	419
9.145.3.10 operator==	419
9.145.3.11 lord_strict	419
9.145.3.12 ord_weak	419
9.145.3.13 tree_fast_to_image	419
9.145.3.14 tree_to_fast	419
9.145.3.15 tree_to_image	420
9.146 mln::util::impl Namespace Reference	420
9.146.1 Detailed Description	420
9.147 mln::value Namespace Reference	420

9.147.1 Detailed Description	425
9.147.2 Typedef Documentation	425
9.147.2.1 float01_16	425
9.147.2.2 float01_8	425
9.147.2.3 gl16	425
9.147.2.4 gl8	425
9.147.2.5 glf	425
9.147.2.6 int_s16	426
9.147.2.7 int_s32	426
9.147.2.8 int_s8	426
9.147.2.9 int_u12	426
9.147.2.10 int_u16	426
9.147.2.11 int_u32	426
9.147.2.12 int_u8	426
9.147.2.13 label_16	426
9.147.2.14 label_32	426
9.147.2.15 label_8	427
9.147.2.16 rgb16	427
9.147.2.17 rgb8	427
9.147.3 Function Documentation	427
9.147.3.1 cast	427
9.147.3.2 equiv	427
9.147.3.3 operator*	427
9.147.3.4 operator*	427
9.147.3.5 operator+	428
9.147.3.6 operator+	428
9.147.3.7 operator-	428
9.147.3.8 operator-	428
9.147.3.9 operator/	428
9.147.3.10 operator/	428
9.147.3.11 operator<<	428
9.147.3.12 operator<<	429
9.147.3.13 operator<<	429
9.147.3.14 operator<<	429
9.147.3.15 operator<<	429
9.147.3.16 operator<<	430

9.147.3.17operator<<	430
9.147.3.18operator<<	430
9.147.3.19operator<<	431
9.147.3.20operator<<	431
9.147.3.21operator<<	431
9.147.3.22operator==	431
9.147.3.23operator==	432
9.147.3.24other	432
9.147.3.25stack	432
9.148mln::value::impl Namespace Reference	432
9.148.1 Detailed Description	432
9.149mln::win Namespace Reference	432
9.149.1 Detailed Description	434
9.149.2 Function Documentation	434
9.149.2.1 diff	434
9.149.2.2 mln_regular	434
9.149.2.3 mln_regular	434
9.149.2.4 sym	434
9.149.2.5 sym	434
10 Class Documentation	437
10.1 mln::accu::center< P, V > Struct Template Reference	437
10.1.1 Detailed Description	437
10.1.2 Member Function Documentation	438
10.1.2.1 init	438
10.1.2.2 is_valid	438
10.1.2.3 nsites	438
10.1.2.4 take_as_init	438
10.1.2.5 take_n_times	438
10.1.2.6 to_result	438
10.2 mln::accu::convolve< T1, T2, R > Struct Template Reference	439
10.2.1 Detailed Description	439
10.2.2 Member Function Documentation	439
10.2.2.1 init	439
10.2.2.2 is_valid	440
10.2.2.3 take_as_init	440
10.2.2.4 take_n_times	440

10.2.2.5	to_result	440
10.3	mln::accu::count_adjacent_vertices< F, S > Struct Template Reference	440
10.3.1	Detailed Description	441
10.3.2	Member Function Documentation	441
10.3.2.1	init	441
10.3.2.2	is_valid	441
10.3.2.3	set_value	441
10.3.2.4	take_as_init	441
10.3.2.5	take_n_times	442
10.3.2.6	to_result	442
10.4	mln::accu::count_labels< L > Struct Template Reference	442
10.4.1	Detailed Description	442
10.4.2	Member Function Documentation	443
10.4.2.1	init	443
10.4.2.2	is_valid	443
10.4.2.3	set_value	443
10.4.2.4	take_as_init	443
10.4.2.5	take_n_times	443
10.4.2.6	to_result	443
10.5	mln::accu::count_value< V > Struct Template Reference	443
10.5.1	Detailed Description	444
10.5.2	Member Function Documentation	444
10.5.2.1	init	444
10.5.2.2	is_valid	444
10.5.2.3	set_value	444
10.5.2.4	take_as_init	445
10.5.2.5	take_n_times	445
10.5.2.6	to_result	445
10.6	mln::accu::histo< V > Struct Template Reference	445
10.6.1	Detailed Description	446
10.6.2	Member Function Documentation	446
10.6.2.1	is_valid	446
10.6.2.2	take	446
10.6.2.3	take_as_init	446
10.6.2.4	take_n_times	446
10.6.2.5	vect	446

10.7 mln::accu::label_used< L > Struct Template Reference	446
10.7.1 Detailed Description	447
10.7.2 Member Function Documentation	447
10.7.2.1 init	447
10.7.2.2 is_valid	447
10.7.2.3 take	447
10.7.2.4 take_as_init	448
10.7.2.5 take_n_times	448
10.7.2.6 to_result	448
10.8 mln::accu::logic::land Struct Reference	448
10.8.1 Detailed Description	449
10.8.2 Member Function Documentation	449
10.8.2.1 init	449
10.8.2.2 is_valid	449
10.8.2.3 take_as_init	449
10.8.2.4 take_n_times	449
10.8.2.5 to_result	449
10.9 mln::accu::logic::land_basic Struct Reference	449
10.9.1 Detailed Description	450
10.9.2 Member Function Documentation	450
10.9.2.1 can_stop	450
10.9.2.2 init	450
10.9.2.3 is_valid	450
10.9.2.4 take_as_init	451
10.9.2.5 take_n_times	451
10.9.2.6 to_result	451
10.10mln::accu::logic::lor Struct Reference	451
10.10.1 Detailed Description	451
10.10.2 Member Function Documentation	452
10.10.2.1 init	452
10.10.2.2 is_valid	452
10.10.2.3 take_as_init	452
10.10.2.4 take_n_times	452
10.10.2.5 to_result	452
10.11mln::accu::logic::lor_basic Struct Reference	452
10.11.1 Detailed Description	453

10.11.2 Member Function Documentation	453
10.11.2.1 can_stop	453
10.11.2.2 init	453
10.11.2.3 is_valid	453
10.11.2.4 take_as_init	453
10.11.2.5 take_n_times	454
10.11.2.6 to_result	454
10.12mln::accu::maj_h< T > Struct Template Reference	454
10.12.1 Detailed Description	454
10.12.2 Member Function Documentation	455
10.12.2.1 init	455
10.12.2.2 is_valid	455
10.12.2.3 take_as_init	455
10.12.2.4 take_n_times	455
10.12.2.5 to_result	455
10.13mln::accu::math::count< T > Struct Template Reference	455
10.13.1 Detailed Description	456
10.13.2 Member Function Documentation	456
10.13.2.1 init	456
10.13.2.2 is_valid	456
10.13.2.3 set_value	456
10.13.2.4 take_as_init	456
10.13.2.5 take_n_times	457
10.13.2.6 to_result	457
10.14mln::accu::math::inf< T > Struct Template Reference	457
10.14.1 Detailed Description	457
10.14.2 Member Function Documentation	458
10.14.2.1 init	458
10.14.2.2 is_valid	458
10.14.2.3 take_as_init	458
10.14.2.4 take_n_times	458
10.14.2.5 to_result	458
10.15mln::accu::math::sum< T, S > Struct Template Reference	458
10.15.1 Detailed Description	459
10.15.2 Member Function Documentation	459
10.15.2.1 init	459

10.15.2.2 <code>is_valid</code>	459
10.15.2.3 <code>take_as_init</code>	459
10.15.2.4 <code>take_n_times</code>	459
10.15.2.5 <code>to_result</code>	460
10.16 <code>mln::accu::math::sup< T ></code> Struct Template Reference	460
10.16.1 Detailed Description	460
10.16.2 Member Function Documentation	460
10.16.2.1 <code>init</code>	460
10.16.2.2 <code>is_valid</code>	461
10.16.2.3 <code>take_as_init</code>	461
10.16.2.4 <code>take_n_times</code>	461
10.16.2.5 <code>to_result</code>	461
10.17 <code>mln::accu::max_site< I ></code> Struct Template Reference	461
10.17.1 Detailed Description	462
10.17.2 Member Function Documentation	462
10.17.2.1 <code>init</code>	462
10.17.2.2 <code>is_valid</code>	462
10.17.2.3 <code>take_as_init</code>	462
10.17.2.4 <code>take_n_times</code>	462
10.17.2.5 <code>to_result</code>	462
10.18 <code>mln::accu::meta::center</code> Struct Reference	463
10.18.1 Detailed Description	463
10.19 <code>mln::accu::meta::count_adjacent_vertices</code> Struct Reference	463
10.19.1 Detailed Description	464
10.20 <code>mln::accu::meta::count_labels</code> Struct Reference	464
10.20.1 Detailed Description	465
10.21 <code>mln::accu::meta::count_value</code> Struct Reference	465
10.21.1 Detailed Description	466
10.22 <code>mln::accu::meta::histo</code> Struct Reference	466
10.22.1 Detailed Description	467
10.23 <code>mln::accu::meta::label_used</code> Struct Reference	467
10.23.1 Detailed Description	468
10.24 <code>mln::accu::meta::logic::land</code> Struct Reference	468
10.24.1 Detailed Description	469
10.25 <code>mln::accu::meta::logic::land_basic</code> Struct Reference	469
10.25.1 Detailed Description	470

10.26mln::accu::meta::logic::lor Struct Reference	470
10.26.1 Detailed Description	471
10.27mln::accu::meta::logic::lor_basic Struct Reference	471
10.27.1 Detailed Description	472
10.28mln::accu::meta::maj_h Struct Reference	472
10.28.1 Detailed Description	473
10.29mln::accu::meta::math::count Struct Reference	473
10.29.1 Detailed Description	474
10.30mln::accu::meta::math::inf Struct Reference	474
10.30.1 Detailed Description	475
10.31mln::accu::meta::math::sum Struct Reference	475
10.31.1 Detailed Description	476
10.32mln::accu::meta::math::sup Struct Reference	476
10.32.1 Detailed Description	477
10.33mln::accu::meta::max_site Struct Reference	477
10.33.1 Detailed Description	478
10.34mln::accu::meta::nil Struct Reference	478
10.34.1 Detailed Description	479
10.35mln::accu::meta::p< mA > Struct Template Reference	479
10.35.1 Detailed Description	480
10.36mln::accu::meta::pair< A1, A2 > Struct Template Reference	480
10.36.1 Detailed Description	481
10.37mln::accu::meta::rms Struct Reference	481
10.37.1 Detailed Description	482
10.38mln::accu::meta::shape::bbox Struct Reference	482
10.38.1 Detailed Description	483
10.39mln::accu::meta::shape::height Struct Reference	483
10.39.1 Detailed Description	484
10.40mln::accu::meta::shape::volume Struct Reference	484
10.40.1 Detailed Description	485
10.41mln::accu::meta::stat::max Struct Reference	485
10.41.1 Detailed Description	486
10.42mln::accu::meta::stat::max_h Struct Reference	486
10.42.1 Detailed Description	487
10.43mln::accu::meta::stat::mean Struct Reference	487
10.43.1 Detailed Description	488

10.44mln::accu::meta::stat::median_alt< T > Struct Template Reference	488
10.44.1 Detailed Description	489
10.45mln::accu::meta::stat::median_h Struct Reference	489
10.45.1 Detailed Description	490
10.46mln::accu::meta::stat::min Struct Reference	490
10.46.1 Detailed Description	491
10.47mln::accu::meta::stat::min_h Struct Reference	491
10.47.1 Detailed Description	492
10.48mln::accu::meta::stat::rank Struct Reference	492
10.48.1 Detailed Description	493
10.49mln::accu::meta::stat::rank_high_quant Struct Reference	493
10.49.1 Detailed Description	494
10.50mln::accu::meta::tuple< n, > Struct Template Reference	494
10.50.1 Detailed Description	495
10.51mln::accu::meta::val< mA > Struct Template Reference	495
10.51.1 Detailed Description	496
10.52mln::accu::nil< T > Struct Template Reference	496
10.52.1 Detailed Description	497
10.52.2 Member Function Documentation	497
10.52.2.1 init	497
10.52.2.2 is_valid	497
10.52.2.3 take_as_init	497
10.52.2.4 take_n_times	497
10.52.2.5 to_result	498
10.53mln::accu::p< A > Struct Template Reference	498
10.53.1 Detailed Description	498
10.53.2 Member Function Documentation	498
10.53.2.1 init	498
10.53.2.2 is_valid	499
10.53.2.3 take_as_init	499
10.53.2.4 take_n_times	499
10.53.2.5 to_result	499
10.54mln::accu::pair< A1, A2, T > Struct Template Reference	499
10.54.1 Detailed Description	501
10.54.2 Member Function Documentation	501
10.54.2.1 first	501

10.54.2.2 <code>first_accu</code>	501
10.54.2.3 <code>init</code>	501
10.54.2.4 <code>is_valid</code>	501
10.54.2.5 <code>second</code>	501
10.54.2.6 <code>second_accu</code>	502
10.54.2.7 <code>take_as_init</code>	502
10.54.2.8 <code>take_n_times</code>	502
10.54.2.9 <code>to_result</code>	502
10.55 <code>mln::accu::rms< T, V ></code> Struct Template Reference	502
10.55.1 Detailed Description	503
10.55.2 Member Function Documentation	503
10.55.2.1 <code>init</code>	503
10.55.2.2 <code>is_valid</code>	503
10.55.2.3 <code>take_as_init</code>	503
10.55.2.4 <code>take_n_times</code>	503
10.55.2.5 <code>to_result</code>	503
10.56 <code>mln::accu::shape::bbox< P ></code> Struct Template Reference	504
10.56.1 Detailed Description	504
10.56.2 Member Function Documentation	504
10.56.2.1 <code>init</code>	504
10.56.2.2 <code>is_valid</code>	504
10.56.2.3 <code>take_as_init</code>	505
10.56.2.4 <code>take_n_times</code>	505
10.56.2.5 <code>to_result</code>	505
10.57 <code>mln::accu::shape::height< I ></code> Struct Template Reference	505
10.57.1 Detailed Description	506
10.57.2 Member Typedef Documentation	506
10.57.2.1 <code>argument</code>	506
10.57.2.2 <code>value</code>	506
10.57.3 Member Function Documentation	506
10.57.3.1 <code>init</code>	506
10.57.3.2 <code>is_valid</code>	506
10.57.3.3 <code>set_value</code>	507
10.57.3.4 <code>take_as_init</code>	507
10.57.3.5 <code>take_n_times</code>	507
10.57.3.6 <code>to_result</code>	507

10.58mln::accu::shape::volume< I > Struct Template Reference	507
10.58.1 Detailed Description	508
10.58.2 Member Typedef Documentation	508
10.58.2.1 argument	508
10.58.2.2 value	508
10.58.3 Member Function Documentation	508
10.58.3.1 init	508
10.58.3.2 is_valid	509
10.58.3.3 set_value	509
10.58.3.4 take_as_init	509
10.58.3.5 take_n_times	509
10.58.3.6 to_result	509
10.59mln::accu::site_set::rectangularity< P > Class Template Reference	509
10.59.1 Detailed Description	510
10.59.2 Constructor & Destructor Documentation	510
10.59.2.1 rectangularity	510
10.59.3 Member Function Documentation	510
10.59.3.1 area	510
10.59.3.2 bbox	510
10.59.3.3 take_as_init	511
10.59.3.4 take_n_times	511
10.59.3.5 to_result	511
10.60mln::accu::stat::deviation< T, S, M > Struct Template Reference	511
10.60.1 Detailed Description	512
10.60.2 Member Function Documentation	512
10.60.2.1 init	512
10.60.2.2 is_valid	512
10.60.2.3 take_as_init	512
10.60.2.4 take_n_times	512
10.60.2.5 to_result	512
10.61mln::accu::stat::histo3d_rgb< V > Struct Template Reference	513
10.61.1 Detailed Description	513
10.61.2 Constructor & Destructor Documentation	514
10.61.2.1 histo3d_rgb	514
10.61.3 Member Function Documentation	514
10.61.3.1 init	514

10.61.3.2 <code>is_valid</code>	514
10.61.3.3 <code>take</code>	514
10.61.3.4 <code>take</code>	514
10.61.3.5 <code>take_as_init</code>	515
10.61.3.6 <code>take_n_times</code>	515
10.61.3.7 <code>to_result</code>	515
10.62 <code>mln::accu::stat::max< T ></code> Struct Template Reference	515
10.62.1 Detailed Description	516
10.62.2 Member Function Documentation	516
10.62.2.1 <code>init</code>	516
10.62.2.2 <code>is_valid</code>	516
10.62.2.3 <code>set_value</code>	516
10.62.2.4 <code>take_as_init</code>	516
10.62.2.5 <code>take_n_times</code>	516
10.62.2.6 <code>to_result</code>	517
10.63 <code>mln::accu::stat::max_h< V ></code> Struct Template Reference	517
10.63.1 Detailed Description	517
10.63.2 Member Function Documentation	517
10.63.2.1 <code>init</code>	517
10.63.2.2 <code>is_valid</code>	518
10.63.2.3 <code>take_as_init</code>	518
10.63.2.4 <code>take_n_times</code>	518
10.63.2.5 <code>to_result</code>	518
10.64 <code>mln::accu::stat::mean< T, S, M ></code> Struct Template Reference	518
10.64.1 Detailed Description	519
10.64.2 Member Function Documentation	519
10.64.2.1 <code>count</code>	519
10.64.2.2 <code>init</code>	519
10.64.2.3 <code>is_valid</code>	519
10.64.2.4 <code>sum</code>	519
10.64.2.5 <code>take_as_init</code>	520
10.64.2.6 <code>take_n_times</code>	520
10.64.2.7 <code>to_result</code>	520
10.65 <code>mln::accu::stat::median_alt< S ></code> Struct Template Reference	520
10.65.1 Detailed Description	521
10.65.2 Member Function Documentation	521

10.65.2.1 <code>is_valid</code>	521
10.65.2.2 <code>take</code>	521
10.65.2.3 <code>take_as_init</code>	521
10.65.2.4 <code>take_n_times</code>	521
10.65.2.5 <code>to_result</code>	522
10.66 <code>mln::accu::stat::median_h< V ></code> Struct Template Reference	522
10.66.1 Detailed Description	523
10.66.2 Member Function Documentation	523
10.66.2.1 <code>init</code>	523
10.66.2.2 <code>is_valid</code>	523
10.66.2.3 <code>take_as_init</code>	523
10.66.2.4 <code>take_n_times</code>	523
10.66.2.5 <code>to_result</code>	523
10.67 <code>mln::accu::stat::meta::deviation</code> Struct Reference	523
10.67.1 Detailed Description	524
10.68 <code>mln::accu::stat::min< T ></code> Struct Template Reference	524
10.68.1 Detailed Description	525
10.68.2 Member Function Documentation	525
10.68.2.1 <code>init</code>	525
10.68.2.2 <code>is_valid</code>	525
10.68.2.3 <code>set_value</code>	525
10.68.2.4 <code>take_as_init</code>	525
10.68.2.5 <code>take_n_times</code>	526
10.68.2.6 <code>to_result</code>	526
10.69 <code>mln::accu::stat::min_h< V ></code> Struct Template Reference	526
10.69.1 Detailed Description	526
10.69.2 Member Function Documentation	527
10.69.2.1 <code>init</code>	527
10.69.2.2 <code>is_valid</code>	527
10.69.2.3 <code>take_as_init</code>	527
10.69.2.4 <code>take_n_times</code>	527
10.69.2.5 <code>to_result</code>	527
10.70 <code>mln::accu::stat::min_max< V ></code> Struct Template Reference	527
10.70.1 Detailed Description	529
10.70.2 Member Function Documentation	529
10.70.2.1 <code>first</code>	529

10.70.2.2 first_accu	529
10.70.2.3 init	529
10.70.2.4 is_valid	529
10.70.2.5 second	529
10.70.2.6 second_accu	529
10.70.2.7 take_as_init	530
10.70.2.8 take_n_times	530
10.70.2.9 to_result	530
10.71 mln::accu::stat::rank< T > Struct Template Reference	530
10.71.1 Detailed Description	531
10.71.2 Member Function Documentation	531
10.71.2.1 init	531
10.71.2.2 is_valid	531
10.71.2.3 k	531
10.71.2.4 take_as_init	531
10.71.2.5 take_n_times	531
10.71.2.6 to_result	532
10.72 mln::accu::stat::rank< bool > Struct Template Reference	532
10.72.1 Detailed Description	532
10.72.2 Member Function Documentation	532
10.72.2.1 init	532
10.72.2.2 is_valid	533
10.72.2.3 take_as_init	533
10.72.2.4 take_n_times	533
10.72.2.5 to_result	533
10.73 mln::accu::stat::rank_high_quant< T > Struct Template Reference	533
10.73.1 Detailed Description	534
10.73.2 Member Function Documentation	534
10.73.2.1 init	534
10.73.2.2 is_valid	534
10.73.2.3 take_as_init	534
10.73.2.4 take_n_times	534
10.73.2.5 to_result	534
10.74 mln::accu::stat::var< T > Struct Template Reference	535
10.74.1 Detailed Description	535
10.74.2 Member Typedef Documentation	536

10.74.2.1 <code>mean_t</code>	536
10.74.3 Member Function Documentation	536
10.74.3.1 <code>init</code>	536
10.74.3.2 <code>is_valid</code>	536
10.74.3.3 <code>mean</code>	536
10.74.3.4 <code>n_items</code>	536
10.74.3.5 <code>take_as_init</code>	536
10.74.3.6 <code>take_n_times</code>	536
10.74.3.7 <code>to_result</code>	537
10.74.3.8 <code>variance</code>	537
10.75 <code>mln::accu::stat::variance< T, S, R ></code> Struct Template Reference	537
10.75.1 Detailed Description	538
10.75.2 Member Function Documentation	538
10.75.2.1 <code>init</code>	538
10.75.2.2 <code>is_valid</code>	538
10.75.2.3 <code>mean</code>	538
10.75.2.4 <code>n_items</code>	538
10.75.2.5 <code>standard_deviation</code>	539
10.75.2.6 <code>sum</code>	539
10.75.2.7 <code>take_as_init</code>	539
10.75.2.8 <code>take_n_times</code>	539
10.75.2.9 <code>to_result</code>	539
10.75.2.10 <code>var</code>	539
10.76 <code>mln::accu::tuple< A, n, ></code> Struct Template Reference	539
10.76.1 Detailed Description	540
10.76.2 Member Function Documentation	540
10.76.2.1 <code>init</code>	540
10.76.2.2 <code>is_valid</code>	540
10.76.2.3 <code>take_as_init</code>	541
10.76.2.4 <code>take_n_times</code>	541
10.76.2.5 <code>to_result</code>	541
10.77 <code>mln::accu::val< A ></code> Struct Template Reference	541
10.77.1 Detailed Description	542
10.77.2 Member Function Documentation	542
10.77.2.1 <code>init</code>	542
10.77.2.2 <code>is_valid</code>	542

10.77.2.3 <code>take_as_init</code>	542
10.77.2.4 <code>take_n_times</code>	542
10.77.2.5 <code>to_result</code>	542
10.78 <code>mln::Accumulator< E ></code> Struct Template Reference	542
10.78.1 Detailed Description	544
10.78.2 Member Function Documentation	544
10.78.2.1 <code>take_as_init</code>	544
10.78.2.2 <code>take_n_times</code>	544
10.79 <code>mln::algebra::h_mat< d, T ></code> Struct Template Reference	544
10.79.1 Detailed Description	545
10.79.2 Member Enumeration Documentation	545
10.79.2.1 "@7	545
10.79.3 Constructor & Destructor Documentation	545
10.79.3.1 <code>h_mat</code>	545
10.79.3.2 <code>h_mat</code>	545
10.79.4 Member Function Documentation	546
10.79.4.1 <code>_1</code>	546
10.79.4.2 <code>t</code>	546
10.80 <code>mln::algebra::h_vec< d, C ></code> Class Template Reference	546
10.80.1 Detailed Description	547
10.80.2 Member Enumeration Documentation	547
10.80.2.1 "@8	547
10.80.3 Constructor & Destructor Documentation	547
10.80.3.1 <code>h_vec</code>	547
10.80.3.2 <code>h_vec</code>	547
10.80.4 Member Function Documentation	547
10.80.4.1 <code>operator mat< n, 1, U ></code>	547
10.80.4.2 <code>t</code>	548
10.80.4.3 <code>to_vec</code>	548
10.80.5 Member Data Documentation	548
10.80.5.1 <code>origin</code>	548
10.80.5.2 <code>zero</code>	548
10.81 <code>mln::bkd_pixter1d< I ></code> Class Template Reference	548
10.81.1 Detailed Description	549
10.81.2 Member Typedef Documentation	549
10.81.2.1 <code>image</code>	549

10.81.3 Constructor & Destructor Documentation	549
10.81.3.1 bkd_pixter1d	549
10.81.4 Member Function Documentation	549
10.81.4.1 next	549
10.82mln::bkd_pixter2d< I > Class Template Reference	549
10.82.1 Detailed Description	550
10.82.2 Member Typedef Documentation	550
10.82.2.1 image	550
10.82.3 Constructor & Destructor Documentation	550
10.82.3.1 bkd_pixter2d	550
10.82.4 Member Function Documentation	550
10.82.4.1 next	550
10.83mln::bkd_pixter3d< I > Class Template Reference	551
10.83.1 Detailed Description	551
10.83.2 Member Typedef Documentation	551
10.83.2.1 image	551
10.83.3 Constructor & Destructor Documentation	552
10.83.3.1 bkd_pixter3d	552
10.83.4 Member Function Documentation	552
10.83.4.1 next	552
10.84mln::box< P > Class Template Reference	552
10.84.1 Detailed Description	555
10.84.2 Member Typedef Documentation	555
10.84.2.1 bkd_piter	555
10.84.2.2 element	555
10.84.2.3 fwd_piter	556
10.84.2.4 piter	556
10.84.2.5 psite	556
10.84.2.6 site	556
10.84.3 Member Enumeration Documentation	556
10.84.3.1 "@31	556
10.84.4 Constructor & Destructor Documentation	556
10.84.4.1 box	556
10.84.4.2 box	556
10.84.4.3 box	556
10.84.5 Member Function Documentation	557

10.84.5.1 <code>bbox</code>	557
10.84.5.2 <code>crop_wrt</code>	557
10.84.5.3 <code>enlarge</code>	557
10.84.5.4 <code>enlarge</code>	557
10.84.5.5 <code>has</code>	557
10.84.5.6 <code>is_empty</code>	558
10.84.5.7 <code>is_valid</code>	558
10.84.5.8 <code>len</code>	558
10.84.5.9 <code>memory_size</code>	558
10.84.5.10 <code>merge</code>	558
10.84.5.11 <code>nsites</code>	558
10.84.5.12 <code>pcenter</code>	559
10.84.5.13 <code>pmax</code>	559
10.84.5.14 <code>pmax</code>	559
10.84.5.15 <code>pmin</code>	559
10.84.5.16 <code>pmin</code>	559
10.84.5.17 <code>to_larger</code>	559
10.84.6 Friends And Related Function Documentation	560
10.84.6.1 <code>operator<<</code>	560
10.85 <code>mln::Box< E ></code> Struct Template Reference	560
10.85.1 Detailed Description	562
10.85.2 Member Function Documentation	563
10.85.2.1 <code>bbox</code>	563
10.85.2.2 <code>is_empty</code>	563
10.85.2.3 <code>len</code>	563
10.85.2.4 <code>nsites</code>	563
10.85.3 Friends And Related Function Documentation	564
10.85.3.1 <code>diff</code>	564
10.85.3.2 <code>inter</code>	564
10.85.3.3 <code>operator<</code>	564
10.85.3.4 <code>operator<</code>	564
10.85.3.5 <code>operator<<</code>	564
10.85.3.6 <code>operator<=</code>	565
10.85.3.7 <code>operator<=</code>	565
10.85.3.8 <code>operator==</code>	565
10.85.3.9 <code>sym_diff</code>	565

10.85.3.10uni	565
10.85.3.1 lunique	566
10.86mln::box_runend_piter< P > Class Template Reference	566
10.86.1 Detailed Description	566
10.86.2 Constructor & Destructor Documentation	566
10.86.2.1 box_runend_piter	566
10.86.3 Member Function Documentation	567
10.86.3.1 next	567
10.86.3.2 run_length	567
10.87mln::box_runstart_piter< P > Class Template Reference	567
10.87.1 Detailed Description	567
10.87.2 Constructor & Destructor Documentation	568
10.87.2.1 box_runstart_piter	568
10.87.3 Member Function Documentation	568
10.87.3.1 next	568
10.87.3.2 run_length	568
10.88mln::Browsing< E > Struct Template Reference	568
10.88.1 Detailed Description	569
10.89mln::canvas::browsing::backdiagonal2d_t Struct Reference	569
10.89.1 Detailed Description	570
10.90mln::canvas::browsing::breadth_first_search_t Struct Reference	571
10.90.1 Detailed Description	571
10.91mln::canvas::browsing::depth_first_search_t Struct Reference	571
10.91.1 Detailed Description	571
10.92mln::canvas::browsing::diagonal2d_t Struct Reference	571
10.92.1 Detailed Description	572
10.93mln::canvas::browsing::dir_struct_elt_incr_update_t Struct Reference	573
10.93.1 Detailed Description	573
10.94mln::canvas::browsing::directional_t Struct Reference	574
10.94.1 Detailed Description	575
10.95mln::canvas::browsing::fwd_t Struct Reference	576
10.95.1 Detailed Description	577
10.96mln::canvas::browsing::hyper_directional_t Struct Reference	577
10.96.1 Detailed Description	578
10.97mln::canvas::browsing::snake_fwd_t Struct Reference	579
10.97.1 Detailed Description	579

10.98mln::canvas::browsing::snake_generic_t Struct Reference	580
10.98.1 Detailed Description	581
10.99mln::canvas::browsing::snake_vert_t Struct Reference	582
10.99.1 Detailed Description	582
10.10mln::canvas::chamfer< F > Struct Template Reference	583
10.100.1 Detailed Description	583
10.101mln::category< R(*)(A) > Struct Template Reference	583
10.101.1 Detailed Description	583
10.102mln::complex_image< D, G, V > Class Template Reference	584
10.102.1 Detailed Description	585
10.102.2 Member Typedef Documentation	585
10.102.2.1 geom	585
10.102.2.2 value	585
10.102.2.3 rvalue	585
10.102.2.4 skeleton	585
10.102.2.5 lvalue	585
10.102.3 Constructor & Destructor Documentation	586
10.102.3.1 complex_image	586
10.102.4 Member Function Documentation	586
10.102.4.1 domain	586
10.102.4.2 operator()	586
10.102.4.3 operator()	586
10.102.4.4 values	586
10.102.5 Member Data Documentation	586
10.102.5.1 dim	586
10.103mln::complex_neighborhood_bkd_piter< I, G, N > Class Template Reference	587
10.103.1 Detailed Description	587
10.103.2 Member Typedef Documentation	587
10.103.2.1 liter_type	587
10.103.2.2 psite	588
10.103.3 Constructor & Destructor Documentation	588
10.103.3.1 complex_neighborhood_bkd_piter	588
10.103.4 Member Function Documentation	588
10.103.4.1 liter	588
10.103.4.2 next	588
10.104mln::complex_neighborhood_fwd_piter< I, G, N > Class Template Reference	588

10.104.1	Detailed Description	589
10.104.2	Member Typedef Documentation	589
10.104.2.1	liter_type	589
10.104.2.2	psite	589
10.104.3	Constructor & Destructor Documentation	589
10.104.3.1	complex_neighborhood_fwd_piter	589
10.104.4	Member Function Documentation	590
10.104.4.1	liter	590
10.104.4.2	next	590
10.105	mln::complex_psite< D, G > Class Template Reference	590
10.105.1	Detailed Description	591
10.105.2	Constructor & Destructor Documentation	591
10.105.2.1	complex_psite	591
10.105.3	Member Function Documentation	591
10.105.3.1	change_target	591
10.105.3.2	face	592
10.105.3.3	face_id	592
10.105.3.4	invalidate	592
10.105.3.5	is_valid	592
10.105.3.6	n	592
10.105.3.7	site_set	593
10.106	mln::complex_window_bkd_piter< I, G, W > Class Template Reference	593
10.106.1	Detailed Description	593
10.106.2	Member Typedef Documentation	594
10.106.2.1	liter_type	594
10.106.2.2	psite	594
10.106.3	Constructor & Destructor Documentation	594
10.106.3.1	complex_window_bkd_piter	594
10.106.4	Member Function Documentation	594
10.106.4.1	liter	594
10.106.4.2	next	594
10.107	mln::complex_window_fwd_piter< I, G, W > Class Template Reference	595
10.107.1	Detailed Description	595
10.107.2	Member Typedef Documentation	595
10.107.2.1	liter_type	595

10.107.2. <i>psite</i>	596
10.107.3.Constructor & Destructor Documentation	596
10.107.3.1 <i>complex_window_fwd_piter</i>	596
10.107.4.Member Function Documentation	596
10.107.4.1 <i>liter</i>	596
10.107.4.2 <i>next</i>	596
10.108. <i>Inl::decorated_image< I, D ></i> Struct Template Reference	596
10.108.1.Detailed Description	597
10.108.2.Member Typedef Documentation	597
10.108.2.1 <i>llvalue</i>	597
10.108.2.2 <i>psite</i>	598
10.108.2.3 <i>rvalue</i>	598
10.108.2.4 <i>skeleton</i>	598
10.108.3.Constructor & Destructor Documentation	598
10.108.3.1 <i>decorated_image</i>	598
10.108.3.2~ <i>decorated_image</i>	598
10.108.4.Member Function Documentation	598
10.108.4.1 <i>decoration</i>	598
10.108.4.2 <i>decoration</i>	598
10.108.4.3 <i>operator decorated_image< const I, D ></i>	599
10.108.4.4 <i>operator()</i>	599
10.108.4.5 <i>operator()</i>	599
10.109. <i>Inl::Delta_Point_Site< void ></i> Struct Template Reference	599
10.109.1.Detailed Description	599
10.110. <i>Inl::doc::Accumulator< E ></i> Struct Template Reference	599
10.110.1.Detailed Description	600
10.110.2.Member Typedef Documentation	600
10.110.2.1 <i>argument</i>	600
10.110.3.Member Function Documentation	600
10.110.3.1 <i>init</i>	600
10.110.3.2 <i>take</i>	600
10.110.3.3 <i>take</i>	600
10.111. <i>Inl::doc::Box< E ></i> Struct Template Reference	601
10.111.1.Detailed Description	602
10.111.2.Member Typedef Documentation	602
10.111.2.1 <i>bkd_piter</i>	602

10.111.2.2fwd_piter	602
10.111.2.3psite	602
10.111.2.4site	602
10.111.3Member Function Documentation	603
10.111.3.1bbox	603
10.111.3.2has	603
10.111.3.3nsites	603
10.111.3.4pmax	603
10.111.3.5pmin	603
10.112mln::doc::Dpoint< E > Struct Template Reference	604
10.112.1Detailed Description	604
10.112.2Member Typedef Documentation	605
10.112.2.1coord	605
10.112.2.2dpoint	605
10.112.2.3point	605
10.112.3Member Enumeration Documentation	605
10.112.3.1"@19	605
10.112.4Member Function Documentation	605
10.112.4.1operator[]	605
10.113mln::doc::Fastest_Image< E > Struct Template Reference	606
10.113.1Detailed Description	608
10.113.2Member Typedef Documentation	608
10.113.2.1blkd_piter	608
10.113.2.2coord	608
10.113.2.3dpoint	609
10.113.2.4fwd_piter	609
10.113.2.5value	609
10.113.2.6point	609
10.113.2.7pset	609
10.113.2.8psite	609
10.113.2.9value	610
10.113.2.10kkeleton	610
10.113.2.11value	610
10.113.2.12set	610
10.113.3Member Function Documentation	610
10.113.3.1bbox	610

10.113.3.2border	611
10.113.3.3buffer	611
10.113.3.4delta_index	611
10.113.3.5domain	611
10.113.3.6has	611
10.113.3.7has	612
10.113.3.8s_valid	612
10.113.3.9nelements	612
10.113.3.10sites	612
10.113.3.1operator()	612
10.113.3.1operator()	613
10.113.3.1operator[]	613
10.113.3.1operator[]	613
10.113.3.1point_at_index	614
10.113.3.1values	614
10.114In::doc::Generalized_Pixel< E > Struct Template Reference	614
10.114.1Detailed Description	615
10.114.2Member Typedef Documentation	615
10.114.2.1image	615
10.114.2.2value	615
10.114.2.3value	615
10.114.3Member Function Documentation	616
10.114.3.1ima	616
10.114.3.2val	616
10.115In::doc::Image< E > Struct Template Reference	616
10.115.1Detailed Description	618
10.115.2Member Typedef Documentation	618
10.115.2.1bkd_piter	618
10.115.2.2coord	618
10.115.2.3dpoint	618
10.115.2.4fwd_piter	619
10.115.2.5value	619
10.115.2.6point	619
10.115.2.7pset	619
10.115.2.8psite	619
10.115.2.9value	619

10.115.2. l₁k₂e₃l₄o₅n₆t₇o₈n₉o₁₀	620
10.115.2. l₁l₂a₃l₄u₅ 	620
10.115.2. l₁l₂o₃ 	620
10.115.3 Member Function Documentation	620
10.115.3. l₁b₂b₃o₄x₅	620
10.115.3. l₁d₂o₃m₄a₅n₆	620
10.115.3. l₁h₂a₃s₄	620
10.115.3. l₁h₂a₃s₄	621
10.115.3. l₁s₂_v₃a₄l₅u₆	621
10.115.3. l₁s₂i₃s₄ 	621
10.115.3. l₁o₂p₃o₄r₅a₆t₇o₈	621
10.115.3. l₁o₂p₃o₄r₅a₆t₇o₈	621
10.115.3. l₁o₂p₃o₄r₅a₆t₇o₈v₉u₁₀	622
10.116 ln::doc::Iterator< E > Struct Template Reference	622
10.116. Detailed Description	622
10.116. Member Function Documentation	623
10.116.2. l₁in₂v₃a₄l₅u₆	623
10.116.2. l₁s₂_v₃a₄l₅u₆	623
10.116.2. l₁s₂a₃t₄ 	623
10.117 ln::doc::Neighborhood< E > Struct Template Reference	623
10.117. Detailed Description	624
10.117. Member Typedef Documentation	624
10.117.2. l₁b₂k₃d₄_n₅i₆t₇er₈	624
10.117.2. l₁d₂p₃o₄int₅ 	624
10.117.2. l₁f₂w₃d₄_n₅i₆t₇er₈	624
10.117.2. l₁n₂i₃ter₄ 	624
10.117.2. l₁o₂p₃oint₄ 	624
10.118 ln::doc::Object< E > Struct Template Reference	625
10.118. Detailed Description	625
10.119 ln::doc::Pixel_Iterator< E > Struct Template Reference	625
10.119. Detailed Description	627
10.119. Member Typedef Documentation	627
10.119.2. l₁im₂age₃	627
10.119.2. l₁v₂alue₃	627
10.119.2. l₁v₂alue₃	627
10.119.2. l₁v₂alue₃	627

10.119.3Member Function Documentation	627
10.119.3.1lma	627
10.119.3.2invalidate	628
10.119.3.3is_valid	628
10.119.3.4start	628
10.119.3.5val	628
10.120ln::doc::Point_Site< E > Struct Template Reference	628
10.120.1Detailed Description	629
10.120.2Member Typedef Documentation	629
10.120.2.1coord	629
10.120.2.2dpoint	629
10.120.2.3mesh	629
10.120.2.4point	630
10.120.3Member Enumeration Documentation	630
10.120.3.1"@20	630
10.120.4Member Function Documentation	630
10.120.4.1operator[]	630
10.120.4.2o_point	630
10.121ln::doc::Site_Iterator< E > Struct Template Reference	631
10.121.1Detailed Description	632
10.121.2Member Typedef Documentation	632
10.121.2.1psite	632
10.121.3Member Function Documentation	632
10.121.3.1invalidate	632
10.121.3.2is_valid	632
10.121.3.3operator psite	632
10.121.3.4start	632
10.122ln::doc::Site_Set< E > Struct Template Reference	633
10.122.1Detailed Description	634
10.122.2Member Typedef Documentation	634
10.122.2.1bkd_piter	634
10.122.2.2fwd_piter	634
10.122.2.3psite	634
10.122.2.4site	634
10.122.3Member Function Documentation	634
10.122.3.1has	634

10.12 mln::doc::Value_Iterator< E > Struct Template Reference	635
10.123.1 Detailed Description	636
10.123.2 Member Typedef Documentation	636
10.123.2.1 value	636
10.123.3 Member Function Documentation	636
10.123.3.1 invalidate	636
10.123.3.2 is_valid	636
10.123.3.3 operator value	636
10.123.3.4 start	636
10.124 mln::doc::Value_Set< E > Struct Template Reference	636
10.124.1 Detailed Description	637
10.124.2 Member Typedef Documentation	638
10.124.2.1 bkd_viter	638
10.124.2.2 fwd_viter	638
10.124.2.3 value	638
10.124.3 Member Function Documentation	638
10.124.3.1 has	638
10.124.3.2 index_of	638
10.124.3.3 values	638
10.124.3.4 operator[]	639
10.125 mln::doc::Weighted_Window< E > Struct Template Reference	639
10.125.1 Detailed Description	640
10.125.2 Member Typedef Documentation	640
10.125.2.1 bkd_qiter	640
10.125.2.2 dpoint	640
10.125.2.3 fwd_qiter	640
10.125.2.4 point	641
10.125.2.5 weight	641
10.125.2.6 window	641
10.125.3 Member Function Documentation	641
10.125.3.1 delta	641
10.125.3.2 is_centered	641
10.125.3.3 is_empty	641
10.125.3.4 sym	641
10.125.3.5 win	641
10.126 mln::doc::Window< E > Struct Template Reference	641

10.126.1	Detailed Description	642
10.126.2	Member Typedef Documentation	642
10.126.2.1	bkd_qiter	642
10.126.2.2	fwd_qiter	643
10.126.2.3	qiter	643
10.127	mln::Dpoint< E > Struct Template Reference	643
10.127.1	Detailed Description	643
10.127.2	Member Function Documentation	643
10.127.2.1	lto_dpoint	643
10.128	mln::dpoint< G, C > Struct Template Reference	644
10.128.1	Detailed Description	645
10.128.2	Member Typedef Documentation	645
10.128.2.1	lcoord	645
10.128.2.2	grid	646
10.128.2.3	psite	646
10.128.2.4	site	646
10.128.2.5	vec	646
10.128.3	Member Enumeration Documentation	646
10.128.3.1	"@22	646
10.128.4	Constructor & Destructor Documentation	646
10.128.4.1	dpoint	646
10.128.4.2	2dpoint	646
10.128.4.3	3dpoint	647
10.128.4.4	4dpoint	647
10.128.4.5	5dpoint	647
10.128.5	Member Function Documentation	647
10.128.5.1	operator mln::algebra::vec< dpoint< G, C >::dim, Q >	647
10.128.5.2	operator[]	647
10.128.5.3	operator[]	647
10.128.5.4	set_all	648
10.128.5.5	to_vec	648
10.129	mln::dpoints_bkd_pixter< I > Class Template Reference	648
10.129.1	Detailed Description	650
10.129.2	Constructor & Destructor Documentation	650
10.129.2.1	ldpoints_bkd_pixter	650
10.129.2.2	2dpoints_bkd_pixter	650

10.129.3Member Function Documentation	651
10.129.3.1center_val	651
10.129.3.2invalidate	651
10.129.3.3is_valid	651
10.129.3.4next	651
10.129.3.5start	651
10.129.3.6update	651
10.130hln::dpoints_fwd_pixter< I > Class Template Reference	652
10.130.1Detailed Description	653
10.130.2Constructor & Destructor Documentation	653
10.130.2.1dpoints_fwd_pixter	653
10.130.2.2dpoints_fwd_pixter	653
10.130.3Member Function Documentation	654
10.130.3.1center_val	654
10.130.3.2invalidate	654
10.130.3.3is_valid	654
10.130.3.4next	654
10.130.3.5start	654
10.130.3.6update	654
10.131hln::Edge< E > Struct Template Reference	655
10.131.1Detailed Description	655
10.132hln::edge_image< P, V, G > Class Template Reference	655
10.132.1Detailed Description	656
10.132.2Member Typedef Documentation	656
10.132.2.1edge_nbh_t	656
10.132.2.2edge_win_t	656
10.132.2.3graph_t	656
10.132.2.4nbh_t	656
10.132.2.5site_function_t	657
10.132.2.6skeleton	657
10.132.2.7win_t	657
10.132.3Constructor & Destructor Documentation	657
10.132.3.1edge_image	657
10.132.4Member Function Documentation	657
10.132.4.1operator()	657
10.133hln::extended< I > Struct Template Reference	657

10.133.1Detailed Description	658
10.133.2Member Typedef Documentation	658
10.133.2.1skeleton	658
10.133.2.2value	658
10.133.3Constructor & Destructor Documentation	658
10.133.3.1extended	658
10.133.3.2extended	659
10.133.4Member Function Documentation	659
10.133.4.1domain	659
10.1341ln::extension_fun< I, F > Class Template Reference	659
10.134.1Detailed Description	660
10.134.2Member Typedef Documentation	660
10.134.2.1rvalue	660
10.134.2.2skeleton	660
10.134.2.3value	660
10.134.3Constructor & Destructor Documentation	660
10.134.3.1extension_fun	660
10.134.3.2extension_fun	661
10.134.4Member Function Documentation	661
10.134.4.1extension	661
10.134.4.2has	661
10.134.4.3operator()	661
10.134.4.4operator()	661
10.135fnln::extension_ima< I, J > Class Template Reference	661
10.135.1Detailed Description	662
10.135.2Member Typedef Documentation	662
10.135.2.1rvalue	662
10.135.2.2skeleton	663
10.135.2.3value	663
10.135.3Constructor & Destructor Documentation	663
10.135.3.1extension_ima	663
10.135.3.2extension_ima	663
10.135.4Member Function Documentation	663
10.135.4.1extension	663
10.135.4.2has	663
10.135.4.3operator()	663

10.135.4.4operator()	664
10.136 <code>ln::extension_val< I ></code> Class Template Reference	664
10.136.1Detailed Description	665
10.136.2Member Typedef Documentation	665
10.136.2.1rvalue	665
10.136.2.2skeleton	665
10.136.2.3value	665
10.136.3Constructor & Destructor Documentation	665
10.136.3.1extension_val	665
10.136.3.2extension_val	665
10.136.4Member Function Documentation	665
10.136.4.1change_extension	665
10.136.4.2extension	666
10.136.4.3has	666
10.136.4.4operator()	666
10.136.4.5operator()	666
10.137 <code>ln::faces_psite< N, D, P ></code> Class Template Reference	666
10.137.1Detailed Description	667
10.137.2Constructor & Destructor Documentation	667
10.137.2.1faces_psite	667
10.137.2.2faces_psite	667
10.137.3Member Function Documentation	668
10.137.3.1change_target	668
10.137.3.2face	668
10.137.3.3face_id	668
10.137.3.4invalidate	668
10.137.3.5is_valid	668
10.137.3.6n	668
10.137.3.7site_set	669
10.138 <code>ln::flat_image< T, S ></code> Struct Template Reference	669
10.138.1Detailed Description	670
10.138.2Member Typedef Documentation	670
10.138.2.1lvalue	670
10.138.2.2value	670
10.138.2.3skeleton	670
10.138.2.4value	670

10.138.3. Constructor & Destructor Documentation	670
10.138.3.1.flat_image	670
10.138.3.2.flat_image	671
10.138.4. Member Function Documentation	671
10.138.4.1.domain	671
10.138.4.2.has	671
10.138.4.3.operator()	671
10.138.4.4.operator()	671
10.139. ln::fun::from_accu< A > Struct Template Reference	671
10.139.1. Detailed Description	671
10.140. ln::fun::n2v::white_gaussian< V > Struct Template Reference	672
10.140.1. Detailed Description	672
10.141. ln::fun::p2b::antilogy Struct Reference	672
10.141.1. Detailed Description	673
10.142. ln::fun::p2b::tautology Struct Reference	673
10.142.1. Detailed Description	674
10.143. ln::fun::v2b::lnot< V > Struct Template Reference	675
10.143.1. Detailed Description	675
10.144. ln::fun::v2b::threshold< V > Struct Template Reference	676
10.144.1. Detailed Description	676
10.145. ln::fun::v2v::ch_function_value< F, V > Class Template Reference	677
10.145.1. Detailed Description	677
10.146. ln::fun::v2v::component< T, i > Struct Template Reference	678
10.146.1. Detailed Description	678
10.147. ln::fun::v2v::l1_norm< V, R > Struct Template Reference	678
10.147.1. Detailed Description	679
10.148. ln::fun::v2v::l2_norm< V, R > Struct Template Reference	679
10.148.1. Detailed Description	680
10.149. ln::fun::v2v::linear< V, T, R > Struct Template Reference	680
10.149.1. Detailed Description	681
10.150. ln::fun::v2v::linfty_norm< V, R > Struct Template Reference	681
10.150.1. Detailed Description	682
10.151. ln::fun::v2v::rgb8_to_rgbn< n > Struct Template Reference	682
10.151.1. Detailed Description	683
10.151.2. Member Function Documentation	684
10.151.2.1.operator()	684

10.15 2 ln::fun::v2w2v::cos< V > Struct Template Reference	684
10.152. Detailed Description	685
10.15 3 ln::fun::v2w_w2v::l1_norm< V, R > Struct Template Reference	685
10.153. Detailed Description	686
10.15 4 ln::fun::v2w_w2v::l2_norm< V, R > Struct Template Reference	687
10.154. Detailed Description	687
10.15 5 ln::fun::v2w_w2v::lfinity_norm< V, R > Struct Template Reference	688
10.155. Detailed Description	688
10.15 6 ln::fun::vv2b::eq< L, R > Struct Template Reference	689
10.156. Detailed Description	689
10.15 7 ln::fun::vv2b::ge< L, R > Struct Template Reference	689
10.157. Detailed Description	690
10.15 8 ln::fun::vv2b::gt< L, R > Struct Template Reference	690
10.158. Detailed Description	691
10.15 9 ln::fun::vv2b::implies< L, R > Struct Template Reference	691
10.159. Detailed Description	692
10.16 0 ln::fun::vv2b::le< L, R > Struct Template Reference	692
10.160. Detailed Description	693
10.16 1 ln::fun::vv2b::lt< L, R > Struct Template Reference	693
10.161. Detailed Description	694
10.16 2 ln::fun::vv2v::diff_abs< V > Struct Template Reference	694
10.162. Detailed Description	695
10.16 3 ln::fun::vv2v::land< L, R > Struct Template Reference	695
10.163. Detailed Description	696
10.16 4 ln::fun::vv2v::land_not< L, R > Struct Template Reference	696
10.164. Detailed Description	697
10.16 5 ln::fun::vv2v::lor< L, R > Struct Template Reference	697
10.165. Detailed Description	698
10.16 6 ln::fun::vv2v::lxor< L, R > Struct Template Reference	698
10.166. Detailed Description	699
10.16 7 ln::fun::vv2v::max< V > Struct Template Reference	699
10.167. Detailed Description	700
10.16 8 ln::fun::vv2v::min< L, R > Struct Template Reference	700
10.168. Detailed Description	701
10.16 9 ln::fun::vv2v::vec< V > Struct Template Reference	701
10.169. Detailed Description	702

10.170	lnl::fun::x2p::closest_point< P > Struct Template Reference	702
10.170.1	Detailed Description	703
10.171	lnl::fun::x2v::bilinear< I > Struct Template Reference	703
10.171.1	Detailed Description	703
10.171.2	Member Function Documentation	703
10.171.2.1	operator()	703
10.171.2.2	operator()	704
10.172	lnl::fun::x2v::trilinear< I > Struct Template Reference	704
10.172.1	Detailed Description	704
10.173	lnl::fun::x2x::composed< T2, T1 > Struct Template Reference	704
10.173.1	Detailed Description	704
10.173.2	Constructor & Destructor Documentation	705
10.173.2.1	lcomposed	705
10.173.2.2	composed	705
10.174	lnl::fun::x2x::linear< I > Struct Template Reference	705
10.174.1	Detailed Description	706
10.174.2	Constructor & Destructor Documentation	706
10.174.2.1	linear	706
10.174.3	Member Function Documentation	706
10.174.3.1	operator()	706
10.174.4	Member Data Documentation	706
10.174.4.1	lma	706
10.175	lnl::fun::x2x::rotation< n, C > Struct Template Reference	706
10.175.1	Detailed Description	708
10.175.2	Member Typedef Documentation	708
10.175.2.1	ldata_t	708
10.175.2.2	invert	708
10.175.3	Constructor & Destructor Documentation	708
10.175.3.1	lrotation	708
10.175.3.2	rotation	709
10.175.3.3	rotation	709
10.175.3.4	rotation	709
10.175.4	Member Function Documentation	709
10.175.4.1	linv	709
10.175.4.2	operator()	709
10.175.4.3	set_alpha	709

10.175.4. set_axis	709
10.176. ln::fun::x2x::translation< n, C > Struct Template Reference	710
10.176.1 Detailed Description	711
10.176.2 Member Typedef Documentation	711
10.176.2.1 ldata_t	711
10.176.2.2 invert	711
10.176.3 Constructor & Destructor Documentation	711
10.176.3.1 translation	711
10.176.3.2 ranslation	712
10.176.4 Member Function Documentation	712
10.176.4.1 inv	712
10.176.4.2 operator()	712
10.176.4.3 set_t	712
10.176.4.4 t	712
10.177. ln::fun_image< F, I > Struct Template Reference	712
10.177.1 Detailed Description	713
10.177.2 Member Typedef Documentation	713
10.177.2.1 lvalue	713
10.177.2.2 rvalue	713
10.177.2.3 skeleton	714
10.177.2.4 value	714
10.177.3 Constructor & Destructor Documentation	714
10.177.3.1 fun_image	714
10.177.3.2 fun_image	714
10.177.3.3 fun_image	714
10.177.4 Member Function Documentation	714
10.177.4.1 operator()	714
10.177.4.2 operator()	714
10.178. ln::Function< E > Struct Template Reference	715
10.178.1 Detailed Description	715
10.178.2 Constructor & Destructor Documentation	715
10.178.2.1 Function	715
10.179. ln::Function< void > Struct Template Reference	715
10.179.1 Detailed Description	715
10.180. ln::Function_n2v< E > Struct Template Reference	716
10.180.1 Detailed Description	716

10.181 <code>ln::Function_v2b< E ></code> Struct Template Reference	716
10.181.1Detailed Description	717
10.182 <code>ln::Function_v2v< E ></code> Struct Template Reference	717
10.182.1Detailed Description	718
10.183 <code>ln::Function_vv2b< E ></code> Struct Template Reference	718
10.183.1Detailed Description	718
10.184 <code>ln::Function_vv2v< E ></code> Struct Template Reference	718
10.184.1Detailed Description	719
10.185 <code>ln::fwd_pixter1d< I ></code> Class Template Reference	719
10.185.1Detailed Description	720
10.185.2Member Typedef Documentation	720
10.185.2.1image	720
10.185.3Constructor & Destructor Documentation	720
10.185.3.1fwd_pixter1d	720
10.185.4Member Function Documentation	720
10.185.4.1next	720
10.186 <code>ln::fwd_pixter2d< I ></code> Class Template Reference	720
10.186.1Detailed Description	721
10.186.2Member Typedef Documentation	721
10.186.2.1image	721
10.186.3Constructor & Destructor Documentation	721
10.186.3.1fwd_pixter2d	721
10.186.4Member Function Documentation	722
10.186.4.1next	722
10.187 <code>ln::fwd_pixter3d< I ></code> Class Template Reference	722
10.187.1Detailed Description	722
10.187.2Member Typedef Documentation	722
10.187.2.1image	722
10.187.3Constructor & Destructor Documentation	723
10.187.3.1fwd_pixter3d	723
10.187.4Member Function Documentation	723
10.187.4.1next	723
10.188 <code>ln::Gdpoint< E ></code> Struct Template Reference	723
10.188.1Detailed Description	724
10.189 <code>ln::Gdpoint< void ></code> Struct Template Reference	724
10.189.1Detailed Description	724

10.196ln::geom::complex_geometry< D, P > Class Template Reference	725
10.190.1Detailed Description	725
10.190.2Constructor & Destructor Documentation	725
10.190.2.1complex_geometry	725
10.190.3Member Function Documentation	726
10.190.3.1add_location	726
10.190.3.2operator()	726
10.197ln::Gpoint< E > Struct Template Reference	726
10.191.1Detailed Description	728
10.191.2Friends And Related Function Documentation	728
10.191.2.1operator+	728
10.191.2.2operator+=	729
10.191.2.3operator-	729
10.191.2.4operator-=	730
10.191.2.5operator/	730
10.191.2.6operator<<	730
10.191.2.7operator==	731
10.198ln::Graph< E > Struct Template Reference	731
10.192.1Detailed Description	731
10.199ln::graph::attribute::card_t Struct Reference	732
10.193.1Detailed Description	732
10.193.2Member Typedef Documentation	732
10.193.2.1result	732
10.194ln::graph::attribute::representative_t Struct Reference	732
10.194.1Detailed Description	733
10.194.2Member Typedef Documentation	733
10.194.2.1result	733
10.195ln::graph_elt_mixed_neighborhood< G, S, S2 > Struct Template Reference	733
10.195.1Detailed Description	734
10.195.2Member Typedef Documentation	734
10.195.2.1bkd_niter	734
10.195.2.2fwd_niter	734
10.195.2.3niter	734
10.196ln::graph_elt_mixed_window< G, S, S2 > Class Template Reference	734
10.196.1Detailed Description	736
10.196.2Member Typedef Documentation	736

10.196.2. <code>lbkd_qiter</code>	736
10.196.2. <code>center_t</code>	736
10.196.2. <code>fwd_qiter</code>	737
10.196.2. <code>graph_element</code>	737
10.196.2. <code>psite</code>	737
10.196.2. <code>qiter</code>	737
10.196.2. <code>site</code>	737
10.196.2. <code>target</code>	737
10.196.3 Member Function Documentation	737
10.196.3. <code>ldelta</code>	737
10.196.3. <code>is_centered</code>	738
10.196.3. <code>is_empty</code>	738
10.196.3. <code>is_symmetric</code>	738
10.196.3. <code>is_valid</code>	738
10.196.3. <code>sym</code>	738
10.197 <code>ln::graph_elt_neighborhood< G, S ></code> Struct Template Reference	738
10.197.1 Detailed Description	739
10.197.2 Member Typedef Documentation	740
10.197.2. <code>lbkd_niter</code>	740
10.197.2. <code>fwd_niter</code>	740
10.197.2. <code>niter</code>	740
10.198 <code>ln::graph_elt_neighborhood_if< G, S, I ></code> Struct Template Reference	740
10.198.1 Detailed Description	741
10.198.2 Member Typedef Documentation	741
10.198.2. <code>lbkd_niter</code>	741
10.198.2. <code>fwd_niter</code>	741
10.198.2. <code>niter</code>	742
10.198.3 Constructor & Destructor Documentation	742
10.198.3. <code>lgraph_elt_neighborhood_if</code>	742
10.198.3. <code>graph_elt_neighborhood_if</code>	742
10.198.4 Member Function Documentation	742
10.198.4. <code>lmask</code>	742
10.199 <code>ln::graph_elt_window< G, S ></code> Class Template Reference	742
10.199.1 Detailed Description	744
10.199.2 Member Typedef Documentation	744
10.199.2. <code>lbkd_qiter</code>	744

10.199.2.2center_t	744
10.199.2.3fwd_qiter	745
10.199.2.4graph_element	745
10.199.2.5psite	745
10.199.2.6qiter	745
10.199.2.7site	745
10.199.2.8target	745
10.199.3Member Function Documentation	745
10.199.3.1delta	745
10.199.3.2is_centered	746
10.199.3.3is_empty	746
10.199.3.4is_symmetric	746
10.199.3.5is_valid	746
10.199.3.6sym	746
10.200hln::graph_elt_window_if< G, S, I > Class Template Reference	746
10.200.1Detailed Description	748
10.200.2Member Typedef Documentation	748
10.200.2.1bkd_qiter	748
10.200.2.2fwd_qiter	749
10.200.2.3mask_t	749
10.200.2.4psite	749
10.200.2.5qiter	749
10.200.2.6site	749
10.200.2.7target	749
10.200.3Constructor & Destructor Documentation	750
10.200.3.1graph_elt_window_if	750
10.200.3.2graph_elt_window_if	750
10.200.4Member Function Documentation	750
10.200.4.1change_mask	750
10.200.4.2delta	750
10.200.4.3is_centered	750
10.200.4.4is_empty	750
10.200.4.5is_symmetric	751
10.200.4.6is_valid	751
10.200.4.7mask	751
10.200.4.8sym	751

10.20 lnln::graph_window_base< P, E > Class Template Reference	751
10.201. Detailed Description	752
10.201.2 Member Typedef Documentation	752
10.201.2.1 site	752
10.201.3 Member Function Documentation	752
10.201.3.1 delta	752
10.201.3.2 is_centered	752
10.201.3.3 is_empty	753
10.201.3.4 is_symmetric	753
10.201.3.5 is_valid	753
10.201.3.6 sym	753
10.20 lnln::graph_window_if_piter< S, W, I > Class Template Reference	753
10.202. Detailed Description	754
10.202.2 Member Typedef Documentation	754
10.202.2.1 IP	754
10.202.3 Constructor & Destructor Documentation	754
10.202.3.1 graph_window_if_piter	754
10.202.4 Member Function Documentation	754
10.202.4.1 element	754
10.202.4.2 id	754
10.202.4.3 next	755
10.20 lnln::graph_window_piter< S, W, I > Class Template Reference	755
10.203. Detailed Description	756
10.203.2 Member Typedef Documentation	756
10.203.2.1 center_t	756
10.203.2.2 graph_element	756
10.203.2.3 P	757
10.203.3 Constructor & Destructor Documentation	757
10.203.3.1 graph_window_piter	757
10.203.3.2 graph_window_piter	757
10.203.3.3 graph_window_piter	757
10.203.4 Member Function Documentation	757
10.203.4.1 change_target_site_set	757
10.203.4.2 element	758
10.203.4.3 id	758
10.203.4.4 next	758

10.203.4.5target_site_set	758
10.204 ln ::hexa< I > Struct Template Reference	758
10.204.1.Detailed Description	760
10.204.2.Member Typedef Documentation	760
10.204.2.1bkd_piter	760
10.204.2.2fwd_piter	760
10.204.2.3value	760
10.204.2.4psite	761
10.204.2.5rvalue	761
10.204.2.6skeleton	761
10.204.2.7value	761
10.204.3.Constructor & Destructor Documentation	761
10.204.3.1hexa	761
10.204.3.2hexa	761
10.204.4.Member Function Documentation	761
10.204.4.1domain	761
10.204.4.2has	761
10.204.4.3operator()	762
10.204.4.4operator()	762
10.205 ln ::histo::array< T > Struct Template Reference	762
10.205.1.Detailed Description	762
10.206 ln ::Image< E > Struct Template Reference	762
10.206.1.Detailed Description	764
10.207 ln ::image1d< T > Struct Template Reference	764
10.207.1.Detailed Description	765
10.207.2.Member Typedef Documentation	766
10.207.2.1lvalue	766
10.207.2.2rvalue	766
10.207.2.3skeleton	766
10.207.2.4value	766
10.207.3.Constructor & Destructor Documentation	766
10.207.3.1image1d	766
10.207.3.2image1d	766
10.207.3.3image1d	766
10.207.4.Member Function Documentation	767
10.207.4.1bbox	767

10.207.4.2border	767
10.207.4.3buffer	767
10.207.4.4buffer	767
10.207.4.5delta_index	767
10.207.4.6domain	767
10.207.4.7element	767
10.207.4.8element	768
10.207.4.9has	768
10.207.4.10elements	768
10.207.4.11inds	768
10.207.4.12operator()	768
10.207.4.13operator()	768
10.207.4.14point_at_index	768
10.207.4.15bbox	769
10.208 ⁸ ln::image2d< T > Class Template Reference	769
10.208.1Detailed Description	770
10.208.2Member Typedef Documentation	771
10.208.2.1lvalue	771
10.208.2.2rvalue	771
10.208.2.3skelton	771
10.208.2.4value	771
10.208.3Constructor & Destructor Documentation	771
10.208.3.1image2d	771
10.208.3.2image2d	771
10.208.3.3image2d	771
10.208.4Member Function Documentation	772
10.208.4.1bbox	772
10.208.4.2border	772
10.208.4.3buffer	772
10.208.4.4buffer	772
10.208.4.5delta_index	772
10.208.4.6domain	772
10.208.4.7element	772
10.208.4.8element	773
10.208.4.9has	773
10.208.4.10cols	773

10.208.4. <code>lnelements</code>	773
10.208.4. <code>lrows</code>	773
10.208.4. <code>operator()</code>	773
10.208.4. <code>operator()</code>	773
10.208.4. <code>lpoint_at_index</code>	774
10.209. <code>ln::image2d_h< V ></code> Struct Template Reference	774
10.209.1.Detailed Description	775
10.209.2.Member Typedef Documentation	775
10.209.2. <code>lbkd_piter</code>	775
10.209.2. <code>2fwd_piter</code>	775
10.209.2. <code>3value</code>	776
10.209.2. <code>4psite</code>	776
10.209.2. <code>5rvalue</code>	776
10.209.2. <code>6skeleton</code>	776
10.209.2. <code>7value</code>	776
10.209.3.Constructor & Destructor Documentation	776
10.209.3. <code>limage2d_h</code>	776
10.209.4.Member Function Documentation	776
10.209.4. <code>ldomain</code>	776
10.209.4. <code>2has</code>	777
10.209.4. <code>3operator()</code>	777
10.209.4. <code>4operator()</code>	777
10.210. <code>ln::image3d< T ></code> Struct Template Reference	777
10.210.1.Detailed Description	779
10.210.2.Member Typedef Documentation	779
10.210.2. <code>llvalue</code>	779
10.210.2. <code>2rvalue</code>	779
10.210.2. <code>3skeleton</code>	779
10.210.2. <code>4value</code>	779
10.210.3.Constructor & Destructor Documentation	780
10.210.3. <code>limage3d</code>	780
10.210.3. <code>2image3d</code>	780
10.210.3. <code>3image3d</code>	780
10.210.4.Member Function Documentation	780
10.210.4. <code>lbbox</code>	780
10.210.4. <code>2border</code>	780

10.210.4.3 buffer	780
10.210.4.4 buffer	780
10.210.4.5 delta_index	781
10.210.4.6 domain	781
10.210.4.7 element	781
10.210.4.8 &element	781
10.210.4.9 has	781
10.210.4.10 cols	781
10.210.4.11 elements	781
10.210.4.12 rows	782
10.210.4.13 size	782
10.210.4.14 operator()	782
10.210.4.15 operator()	782
10.210.4.16 point_at_index	782
10.210.4.17 bbox	782
10.211 ln::image_if< I, F > Struct Template Reference	782
10.211.1Detailed Description	783
10.211.2Member Typedef Documentation	783
10.211.2.1 skeleton	783
10.211.3Constructor & Destructor Documentation	783
10.211.3.1 image_if	783
10.211.3.2 image_if	784
10.211.4Member Function Documentation	784
10.211.4.1 domain	784
10.211.4.2 operator image_if< const I, F >	784
10.212 ln::interpolated< I, F > Struct Template Reference	784
10.212.1Detailed Description	785
10.212.2Member Typedef Documentation	785
10.212.2.1 llvalue	785
10.212.2.2 psite	785
10.212.2.3 rvalue	785
10.212.2.4 skeleton	785
10.212.2.5 value	786
10.212.3Constructor & Destructor Documentation	786
10.212.3.1 interpolated	786
10.212.4Member Function Documentation	786

10.212.4. <code>lhas</code>	786
10.212.4. <code>s_valid</code>	786
10.213. <code>mln::io::dicom::dicom_header</code> Struct Reference	786
10.213.1Detailed Description	786
10.214. <code>mln::io::dump::dump_header</code> Struct Reference	786
10.214.1Detailed Description	787
10.215. <code>mln::io::fld::fld_header</code> Struct Reference	787
10.215.1Detailed Description	787
10.216. <code>mln::io::raw::raw_header</code> Struct Reference	787
10.216.1Detailed Description	787
10.217. <code>mln::Iterator< E ></code> Struct Template Reference	787
10.217.1Detailed Description	788
10.217.2Member Function Documentation	789
10.217.2.1 <code>next</code>	789
10.218. <code>mln::labeled_image< I ></code> Class Template Reference	789
10.218.1Detailed Description	791
10.218.2Member Typedef Documentation	791
10.218.2.1 <code>lbbox_t</code>	791
10.218.2.2 <code>skeleton</code>	791
10.218.3Constructor & Destructor Documentation	791
10.218.3.1 <code>labeled_image</code>	791
10.218.3.2 <code>labeled_image</code>	791
10.218.3.3 <code>labeled_image</code>	791
10.218.4Member Function Documentation	792
10.218.4.1 <code>lbbox</code>	792
10.218.4.2 <code>bboxes</code>	792
10.218.4.3 <code>labels</code>	792
10.218.4.4 <code>relabel</code>	792
10.218.4.5 <code>relabel</code>	792
10.218.4.6 <code>subdomain</code>	792
10.218.4.7 <code>update_data</code>	792
10.219. <code>mln::labeled_image_base< I, E ></code> Class Template Reference	793
10.219.1Detailed Description	794
10.219.2Member Typedef Documentation	794
10.219.2.1 <code>lbbox_t</code>	794
10.219.3Constructor & Destructor Documentation	794

10.219.3. <code>llabeled_image_base</code>	794
10.219.4 Member Function Documentation	795
10.219.4.1 <code>bbox</code>	795
10.219.4.2 <code>bboxes</code>	795
10.219.4.3 <code>nlabels</code>	795
10.219.4.4 <code>relabel</code>	795
10.219.4.5 <code>relabel</code>	795
10.219.4.6 <code>subdomain</code>	796
10.219.4.7 <code>update_data</code>	796
10.22 <code>mln::lazy_image< I, F, B ></code> Struct Template Reference	796
10.220.1 Detailed Description	797
10.220.2 Member Typedef Documentation	797
10.220.2.1 <code>lvalue</code>	797
10.220.2.2 <code>rvalue</code>	797
10.220.2.3 <code>skeleton</code>	797
10.220.3 Constructor & Destructor Documentation	798
10.220.3.1 <code>llazy_image</code>	798
10.220.3.2 <code>lLazy_image</code>	798
10.220.4 Member Function Documentation	798
10.220.4.1 <code>ldomain</code>	798
10.220.4.2 <code>has</code>	798
10.220.4.3 <code>operator()</code>	798
10.220.4.4 <code>operator()</code>	798
10.220.4.5 <code>operator()</code>	798
10.220.4.6 <code>operator()</code>	799
10.22 <code>mln::Literal< E ></code> Struct Template Reference	799
10.221.1 Detailed Description	801
10.22 <code>mln::literal::black_t</code> Struct Reference	801
10.222.1 Detailed Description	801
10.22 <code>mln::literal::blue_t</code> Struct Reference	802
10.223.1 Detailed Description	802
10.22 <code>mln::literal::brown_t</code> Struct Reference	802
10.224.1 Detailed Description	803
10.22 <code>mln::literal::cyan_t</code> Struct Reference	803
10.225.1 Detailed Description	804
10.22 <code>mln::literal::green_t</code> Struct Reference	804

10.226. Detailed Description	805
10.227. lnln::literal::identity_t Struct Reference	805
10.227. Detailed Description	806
10.228. lnln::literal::light_gray_t Struct Reference	806
10.228. Detailed Description	807
10.229. lnln::literal::lime_t Struct Reference	807
10.229. Detailed Description	808
10.230. lnln::literal::magenta_t Struct Reference	808
10.230. Detailed Description	809
10.231. lnln::literal::max_t Struct Reference	809
10.231. Detailed Description	810
10.232. lnln::literal::min_t Struct Reference	810
10.232. Detailed Description	811
10.233. lnln::literal::olive_t Struct Reference	811
10.233. Detailed Description	812
10.234. lnln::literal::one_t Struct Reference	812
10.234. Detailed Description	813
10.235. lnln::literal::orange_t Struct Reference	813
10.235. Detailed Description	814
10.236. lnln::literal::origin_t Struct Reference	814
10.236. Detailed Description	815
10.237. lnln::literal::pink_t Struct Reference	815
10.237. Detailed Description	816
10.238. lnln::literal::purple_t Struct Reference	816
10.238. Detailed Description	817
10.239. lnln::literal::red_t Struct Reference	817
10.239. Detailed Description	818
10.240. lnln::literal::teal_t Struct Reference	818
10.240. Detailed Description	819
10.241. lnln::literal::violet_t Struct Reference	819
10.241. Detailed Description	820
10.242. lnln::literal::white_t Struct Reference	820
10.242. Detailed Description	821
10.243. lnln::literal::yellow_t Struct Reference	821
10.243. Detailed Description	822
10.244. lnln::literal::zero_t Struct Reference	822

10.244. Detailed Description	823
10.245. ln::Mesh< E > Struct Template Reference	823
10.245. Detailed Description	824
10.246. ln::Meta_Accumulator< E > Struct Template Reference	824
10.246. Detailed Description	825
10.247. ln::Meta_Function< E > Struct Template Reference	826
10.247. Detailed Description	826
10.248. ln::Meta_Function_v2v< E > Struct Template Reference	827
10.248. Detailed Description	827
10.249. ln::Meta_Function_vv2v< E > Struct Template Reference	827
10.249. Detailed Description	828
10.250. ln::metal::ands< E1, E2, E3, E4, E5, E6, E7, E8 > Struct Template Reference	828
10.250. Detailed Description	828
10.251. ln::metal::converts_to< T, U > Struct Template Reference	828
10.251. Detailed Description	828
10.252. ln::metal::equal< T1, T2 > Struct Template Reference	828
10.252. Detailed Description	829
10.253. ln::metal::goes_to< T, U > Struct Template Reference	829
10.253. Detailed Description	829
10.254. ln::metal::is< T, U > Struct Template Reference	829
10.254. Detailed Description	829
10.255. ln::metal::is_a< T, M > Struct Template Reference	830
10.255. Detailed Description	830
10.256. ln::metal::is_not< T, U > Struct Template Reference	830
10.256. Detailed Description	830
10.257. ln::metal::is_not_a< T, M > Struct Template Reference	830
10.257. Detailed Description	830
10.258. ln::mixed_neigh< W > Class Template Reference	830
10.258. Detailed Description	831
10.258. Member Typedef Documentation	831
10.258.2. lbd_niter	831
10.258.2. fwd_niter	831
10.258.2. 3niter	831
10.258. Constructor & Destructor Documentation	832
10.258.3. lmixed_neigh	832
10.258.3. mixed_neigh	832

10.250 <code>ln::morpho::attribute::card< I ></code> Class Template Reference	832
10.259.1Detailed Description	832
10.259.2Member Function Documentation	833
10.259.2.1 <code>limit</code>	833
10.259.2.2 <code>is_valid</code>	833
10.259.2.3 <code>take_as_init</code>	833
10.259.2.4 <code>take_n_times</code>	833
10.259.2.5 <code>to_result</code>	833
10.260 <code>ln::morpho::attribute::count_adjacent_vertices< I ></code> Struct Template Reference	833
10.260.1Detailed Description	834
10.260.2Member Function Documentation	834
10.260.2.1 <code>limit</code>	834
10.260.2.2 <code>is_valid</code>	834
10.260.2.3 <code>take_as_init</code>	834
10.260.2.4 <code>take_n_times</code>	834
10.260.2.5 <code>to_result</code>	835
10.261 <code>ln::morpho::attribute::height< I ></code> Struct Template Reference	835
10.261.1Detailed Description	835
10.261.2Member Function Documentation	836
10.261.2.1 <code>base_level</code>	836
10.261.2.2 <code>init</code>	836
10.261.2.3 <code>is_valid</code>	836
10.261.2.4 <code>take_as_init</code>	836
10.261.2.5 <code>take_n_times</code>	836
10.261.2.6 <code>to_result</code>	836
10.262 <code>ln::morpho::attribute::sharpness< I ></code> Struct Template Reference	836
10.262.1Detailed Description	837
10.262.2Member Function Documentation	837
10.262.2.1 <code>area</code>	837
10.262.2.2 <code>height</code>	838
10.262.2.3 <code>init</code>	838
10.262.2.4 <code>is_valid</code>	838
10.262.2.5 <code>take_as_init</code>	838
10.262.2.6 <code>take_n_times</code>	838
10.262.2.7 <code>to_result</code>	838
10.262.2.8 <code>volume</code>	838

10.26 ³ ln::morpho::attribute::sum< I, S > Class Template Reference	839
10.263.1 Detailed Description	839
10.263.2 Member Function Documentation	839
10.263.2.1 limit	839
10.263.2.2 is_valid	840
10.263.2.3 set_value	840
10.263.2.4 take_as_init	840
10.263.2.5 take_n_times	840
10.263.2.6 to_result	840
10.263.2.7 untake	840
10.264 ⁴ ln::morpho::attribute::volume< I > Struct Template Reference	840
10.264.1 Detailed Description	841
10.264.2 Member Function Documentation	841
10.264.2.1 area	841
10.264.2.2 init	841
10.264.2.3 is_valid	841
10.264.2.4 take_as_init	842
10.264.2.5 take_n_times	842
10.264.2.6 to_result	842
10.265 ⁵ ln::neighb< W > Class Template Reference	842
10.265.1 Detailed Description	843
10.265.2 Member Typedef Documentation	843
10.265.2.1 blkd_niter	843
10.265.2.2 fwd_niter	843
10.265.2.3 niter	843
10.265.3 Constructor & Destructor Documentation	843
10.265.3.1 neighb	843
10.265.3.2 neighb	843
10.266 ⁶ ln::Neighborhood< E > Struct Template Reference	844
10.266.1 Detailed Description	844
10.267 ⁷ ln::Neighborhood< void > Struct Template Reference	844
10.267.1 Detailed Description	844
10.268 ⁸ ln::Object< E > Struct Template Reference	844
10.268.1 Detailed Description	845
10.269 ⁹ ln::p2p_image< I, F > Struct Template Reference	845
10.269.1 Detailed Description	846

10.269.2Member TypeDef Documentation	846
10.269.2.1skeleton	846
10.269.3Constructor & Destructor Documentation	846
10.269.3.1p2p_image	846
10.269.3.2p2p_image	846
10.269.4Member Function Documentation	846
10.269.4.1domain	846
10.269.4.2fun	846
10.269.4.3operator()	847
10.269.4.4operator()	847
10.270nlm::p_array< P > Class Template Reference	847
10.270.1Detailed Description	849
10.270.2Member TypeDef Documentation	849
10.270.2.1bkd_piter	849
10.270.2.2element	849
10.270.2.3fwd_piter	849
10.270.2.4i_element	849
10.270.2.5piter	849
10.270.2.6psite	849
10.270.3Constructor & Destructor Documentation	850
10.270.3.1p_array	850
10.270.3.2p_array	850
10.270.4Member Function Documentation	850
10.270.4.1append	850
10.270.4.2append	850
10.270.4.3change	850
10.270.4.4clear	850
10.270.4.5has	850
10.270.4.6has	851
10.270.4.7insert	851
10.270.4.8is_valid	851
10.270.4.9memory_size	851
10.270.4.10sites	851
10.270.4.1domain[]	851
10.270.4.1operator[]	852
10.270.4.1operator[]	852

10.270.4. <code>lreserve</code>	852
10.270.4. <code>lsize</code>	852
10.270.4. <code>ltd_vector</code>	852
10.271 <code>lnl::p_centered< W ></code> Class Template Reference	852
10.271.1Detailed Description	853
10.271.2Member Typedef Documentation	854
10.271.2.1 <code>lbkd_piter</code>	854
10.271.2.2 <code>element</code>	854
10.271.2.3 <code>fwd_piter</code>	854
10.271.2.4 <code>piter</code>	854
10.271.2.5 <code>psite</code>	854
10.271.2.6 <code>site</code>	854
10.271.3Constructor & Destructor Documentation	854
10.271.3.1 <code>lp_centered</code>	854
10.271.3.2 <code>p_centered</code>	854
10.271.4Member Function Documentation	855
10.271.4.1 <code>lcenter</code>	855
10.271.4.2 <code>has</code>	855
10.271.4.3 <code>is_valid</code>	855
10.271.4.4 <code>memory_size</code>	855
10.271.4.5 <code>window</code>	855
10.272 <code>lnl::p_complex< D, G ></code> Class Template Reference	855
10.272.1Detailed Description	857
10.272.2Member Typedef Documentation	857
10.272.2.1 <code>lbkd_piter</code>	857
10.272.2.2 <code>element</code>	857
10.272.2.3 <code>fwd_piter</code>	857
10.272.2.4 <code>piter</code>	857
10.272.2.5 <code>psite</code>	857
10.272.3Constructor & Destructor Documentation	858
10.272.3.1 <code>lp_complex</code>	858
10.272.4Member Function Documentation	858
10.272.4.1 <code>lcplx</code>	858
10.272.4.2 <code>cplx</code>	858
10.272.4.3 <code>geom</code>	858
10.272.4.4 <code>has</code>	858

10.272.4.5	is_valid	859
10.272.4.6	faces	859
10.272.4.7	nfaces_of_dim	859
10.272.4.8	nsites	859
10.273	mln::p_edges< G, F > Class Template Reference	859
10.273.1	Detailed Description	861
10.273.2	Member Typedef Documentation	861
10.273.2.1	bkd_piter	861
10.273.2.2	edge	861
10.273.2.3	element	861
10.273.2.4	fun_t	862
10.273.2.5	fwd_piter	862
10.273.2.6	graph_element	862
10.273.2.7	graph_t	862
10.273.2.8	piter	862
10.273.2.9	psite	862
10.273.3	Constructor & Destructor Documentation	863
10.273.3.1	lp_edges	863
10.273.3.2	p_edges	863
10.273.3.3	pp_edges	863
10.273.3.4	pp_edges	863
10.273.4	Member Function Documentation	864
10.273.4.1	function	864
10.273.4.2	graph	864
10.273.4.3	has	864
10.273.4.4	has	864
10.273.4.5	invalidate	864
10.273.4.6	is_valid	864
10.273.4.7	memory_size	865
10.273.4.8	nedges	865
10.273.4.9	nsites	865
10.274	mln::p_faces< N, D, P > Struct Template Reference	865
10.274.1	Detailed Description	866
10.274.2	Member Typedef Documentation	866
10.274.2.1	bkd_piter	866
10.274.2.2	element	866

10.274.2.3fwd_piter	867
10.274.2.4piter	867
10.274.2.5psite	867
10.274.3Constructor & Destructor Documentation	867
10.274.3.1p_faces	867
10.274.3.2p_faces	867
10.274.4Member Function Documentation	867
10.274.4.1cplx	867
10.274.4.2cplx	868
10.274.4.3is_valid	868
10.274.4.4nfaces	868
10.274.4.5nsites	868
10.275mln::p_graph_piter< S, I > Class Template Reference	868
10.275.1Detailed Description	869
10.275.2Constructor & Destructor Documentation	869
10.275.2.1p_graph_piter	869
10.275.3Member Function Documentation	869
10.275.3.1graph	869
10.275.3.2d	869
10.275.3.3mln_q_subject	870
10.275.3.4next	870
10.276mln::p_if< S, F > Class Template Reference	870
10.276.1Detailed Description	871
10.276.2Member Typedef Documentation	871
10.276.2.1bkd_piter	871
10.276.2.2element	871
10.276.2.3fwd_piter	871
10.276.2.4piter	872
10.276.2.5psite	872
10.276.3Constructor & Destructor Documentation	872
10.276.3.1p_if	872
10.276.3.2p_if	872
10.276.4Member Function Documentation	872
10.276.4.1has	872
10.276.4.2is_valid	872
10.276.4.3memory_size	872

10.276.4.4overset	873
10.276.4.5pred	873
10.276.4.6predicate	873
10.277 ⁿ ln::p_image< I > Class Template Reference	873
10.277.1Detailed Description	874
10.277.2Member Typedef Documentation	875
10.277.2.1bkd_piter	875
10.277.2.2element	875
10.277.2.3fwd_piter	875
10.277.2.4i_element	875
10.277.2.5piter	875
10.277.2.6psite	875
10.277.2.7r_element	875
10.277.2.8S	875
10.277.3Constructor & Destructor Documentation	876
10.277.3.1p_image	876
10.277.3.2p_image	876
10.277.4Member Function Documentation	876
10.277.4.1clear	876
10.277.4.2has	876
10.277.4.3insert	876
10.277.4.4is_valid	876
10.277.4.5memory_size	877
10.277.4.6nsites	877
10.277.4.7operator typename internal::p_image_site_set< I >::ret	877
10.277.4.8remove	877
10.277.4.9toggle	877
10.278 ⁿ ln::p_indexed_bkd_piter< S > Class Template Reference	877
10.278.1Detailed Description	878
10.278.2Constructor & Destructor Documentation	878
10.278.2.1p_indexed_bkd_piter	878
10.278.2.2p_indexed_bkd_piter	878
10.278.3Member Function Documentation	878
10.278.3.1index	878
10.278.3.2next	878
10.279 ⁿ ln::p_indexed_fwd_piter< S > Class Template Reference	879

10.279.1Detailed Description	879
10.279.2Constructor & Destructor Documentation	879
10.279.2.1p_indexed_fwd_piter	879
10.279.2.2p_indexed_fwd_piter	879
10.279.3Member Function Documentation	880
10.279.3.1index	880
10.279.3.2next	880
10.280hln::p_indexed_psites< S > Class Template Reference	880
10.280.1Detailed Description	880
10.281hln::p_key< K, P > Class Template Reference	880
10.281.1Detailed Description	882
10.281.2Member Typedef Documentation	882
10.281.2.1bkd_piter	882
10.281.2.2element	882
10.281.2.3fwd_piter	883
10.281.2.4_element	883
10.281.2.5piter	883
10.281.2.6psite	883
10.281.2.7r_element	883
10.281.3Constructor & Destructor Documentation	883
10.281.3.1p_key	883
10.281.4Member Function Documentation	883
10.281.4.1change_key	883
10.281.4.2change_keys	884
10.281.4.3clear	884
10.281.4.4exists_key	884
10.281.4.5has	884
10.281.4.6has	884
10.281.4.7insert	884
10.281.4.8insert	884
10.281.4.9is_valid	885
10.281.4.10key	885
10.281.4.11keys	885
10.281.4.12memory_size	885
10.281.4.13sites	885
10.281.4.14operator()	885

10.281.4. <code>l5move</code>	885
10.281.4. <code>l6move_key</code>	886
10.28 h <code>ln::p_line2d</code> Class Reference	886
10.282.1.Detailed Description	887
10.282.2.Member Typedef Documentation	887
10.282.2.1 <code>bkd_piter</code>	887
10.282.2.2 <code>element</code>	887
10.282.2.3 <code>fwd_piter</code>	887
10.282.2.4 <code>piter</code>	888
10.282.2.5 <code>psite</code>	888
10.282.2.6 <code>q_box</code>	888
10.282.3.Constructor & Destructor Documentation	888
10.282.3.1 <code>lp_line2d</code>	888
10.282.3.2 <code>p_line2d</code>	888
10.282.4.Member Function Documentation	888
10.282.4.1 <code>bbox</code>	888
10.282.4.2 <code>begin</code>	888
10.282.4.3 <code>end</code>	889
10.282.4.4 <code>has</code>	889
10.282.4.5 <code>has</code>	889
10.282.4.6 <code>s_valid</code>	889
10.282.4.7 <code>memory_size</code>	889
10.282.4.8 <code>nsites</code>	889
10.282.4.9 <code>operator[]</code>	889
10.282.4.10 <code>d_vector</code>	890
10.28 h <code>ln::p Mutable_array_of< S ></code> Class Template Reference	890
10.283.1.Detailed Description	891
10.283.2.Member Typedef Documentation	891
10.283.2.1 <code>bkd_piter</code>	891
10.283.2.2 <code>element</code>	891
10.283.2.3 <code>fwd_piter</code>	891
10.283.2.4 <code>element</code>	892
10.283.2.5 <code>piter</code>	892
10.283.2.6 <code>psite</code>	892
10.283.3.Constructor & Destructor Documentation	892
10.283.3.1 <code>lp Mutable_array_of</code>	892

10.283.4Member Function Documentation	892
10.283.4.1clear	892
10.283.4.2has	892
10.283.4.3insert	892
10.283.4.4is_valid	893
10.283.4.5memory_size	893
10.283.4.6elements	893
10.283.4.7operator[]	893
10.283.4.8operator[]	893
10.283.4.9reserve	893
10.284lnl::p_n_faces_bkd_piter< D, G > Class Template Reference	893
10.284.1Detailed Description	894
10.284.2Constructor & Destructor Documentation	894
10.284.2.1p_n_faces_bkd_piter	894
10.284.3Member Function Documentation	894
10.284.3.1n	894
10.284.3.2next	894
10.285lnl::p_n_faces_fwd_piter< D, G > Class Template Reference	895
10.285.1Detailed Description	895
10.285.2Constructor & Destructor Documentation	895
10.285.2.1p_n_faces_fwd_piter	895
10.285.3Member Function Documentation	895
10.285.3.1n	895
10.285.3.2next	896
10.286nl::p_priority< P, Q > Class Template Reference	896
10.286.1Detailed Description	898
10.286.2Member Typedef Documentation	898
10.286.2.1bkd_piter	898
10.286.2.2element	898
10.286.2.3fwd_piter	898
10.286.2.4_element	898
10.286.2.5piter	898
10.286.2.6psite	898
10.286.3Constructor & Destructor Documentation	899
10.286.3.1p_priority	899
10.286.4Member Function Documentation	899

10.286.4. <code>lclear</code>	899
10.286.4. <code>exists_priority</code>	899
10.286.4. <code>front</code>	899
10.286.4. <code>has</code>	899
10.286.4. <code>highest_priority</code>	899
10.286.4. <code>insert</code>	900
10.286.4. <code>insert</code>	900
10.286.4. <code>is_valid</code>	900
10.286.4. <code>lowest_priority</code>	900
10.286.4. <code>memory_size</code>	900
10.286.4. <code>nsites</code>	900
10.286.4. <code>operator()</code>	901
10.286.4. <code>lpop</code>	901
10.286.4. <code>lpop_front</code>	901
10.286.4. <code>priorities</code>	901
10.286.4. <code>lpush</code>	901
10.287. <code>ln::p_queue< P ></code> Class Template Reference	902
10.287.1.Detailed Description	903
10.287.2.Member Typedef Documentation	903
10.287.2. <code>lkd_piter</code>	903
10.287.2. <code>element</code>	903
10.287.2. <code>fwd_piter</code>	904
10.287.2. <code>l_element</code>	904
10.287.2. <code>piter</code>	904
10.287.2. <code>psite</code>	904
10.287.3.Constructor & Destructor Documentation	904
10.287.3. <code>lp_queue</code>	904
10.287.4.Member Function Documentation	904
10.287.4. <code>lclear</code>	904
10.287.4. <code>lfront</code>	904
10.287.4. <code>lhas</code>	904
10.287.4. <code>lhas</code>	905
10.287.4. <code>linsert</code>	905
10.287.4. <code>lis_valid</code>	905
10.287.4. <code>lmemory_size</code>	905
10.287.4. <code>lnsites</code>	905

10.287.4.9operator[]	905
10.287.4.1p _o p	906
10.287.4.1p _o p_ front	906
10.287.4.1p _u sh	906
10.287.4.1std_ deque	906
10.288ln::p_queue_fast< P > Class Template Reference	906
10.288.1Detailed Description	908
10.288.2Member Typedef Documentation	908
10.288.2.1bkd_piter	908
10.288.2.2element	908
10.288.2.3fwd_piter	908
10.288.2.4_element	909
10.288.2.5piter	909
10.288.2.6psite	909
10.288.3Constructor & Destructor Documentation	909
10.288.3.1p _u queue_fast	909
10.288.4Member Function Documentation	909
10.288.4.1clear	909
10.288.4.2compute_has	909
10.288.4.3empty	909
10.288.4.4front	909
10.288.4.5has	910
10.288.4.6has	910
10.288.4.7insert	910
10.288.4.8is_valid	910
10.288.4.9memory_size	910
10.288.4.10sites	910
10.288.4.1operator[]	911
10.288.4.1p _o p	911
10.288.4.1p _o p_ front	911
10.288.4.1purge	911
10.288.4.1push	911
10.288.4.1reserve	911
10.288.4.1std_vector	911
10.289ln::p_run< P > Class Template Reference	912
10.289.1Detailed Description	913

10.289.2Member Typedef Documentation	913
10.289.2.1bkd_piter	913
10.289.2.2element	913
10.289.2.3fwd_piter	914
10.289.2.4piter	914
10.289.2.5psite	914
10.289.2.6q_box	914
10.289.3Constructor & Destructor Documentation	914
10.289.3.1p_run	914
10.289.3.2p_run	914
10.289.3.3p_run	914
10.289.4Member Function Documentation	915
10.289.4.1bbox	915
10.289.4.2end	915
10.289.4.3has	915
10.289.4.4has	915
10.289.4.5has_index	915
10.289.4.6init	915
10.289.4.7is_valid	916
10.289.4.8length	916
10.289.4.9memory_size	916
10.289.4.10sites	916
10.289.4.1operator[]	916
10.289.4.1start	916
10.290ln::p_set< P > Class Template Reference	916
10.290.1Detailed Description	918
10.290.2Member Typedef Documentation	918
10.290.2.1bkd_piter	918
10.290.2.2element	918
10.290.2.3fwd_piter	918
10.290.2.4_element	918
10.290.2.5piter	919
10.290.2.6psite	919
10.290.2.7r_element	919
10.290.3Constructor & Destructor Documentation	919
10.290.3.1p_set	919

10.290.4Member Function Documentation	919
10.290.4.1clear	919
10.290.4.2has	919
10.290.4.3has	919
10.290.4.4has	919
10.290.4.5insert	920
10.290.4.6is_valid	920
10.290.4.7memory_size	920
10.290.4.8nsites	920
10.290.4.9operator[]	920
10.290.4.10move	920
10.290.4.1std_vector	920
10.290.4.12rيل_set	921
10.291ln::p_set_of< S > Class Template Reference	921
10.291.1Detailed Description	922
10.291.2Member Typedef Documentation	922
10.291.2.1bkd_piter	922
10.291.2.2element	922
10.291.2.3fwd_piter	922
10.291.2.4_element	922
10.291.2.5piter	923
10.291.2.6psite	923
10.291.3Constructor & Destructor Documentation	923
10.291.3.1p_set_of	923
10.291.4Member Function Documentation	923
10.291.4.1clear	923
10.291.4.2has	923
10.291.4.3insert	923
10.291.4.4is_valid	923
10.291.4.5memory_size	923
10.291.4.6nelements	924
10.291.4.7operator[]	924
10.292ln::p_transformed< S, F > Class Template Reference	924
10.292.1Detailed Description	925
10.292.2Member Typedef Documentation	925
10.292.2.1bkd_piter	925

10.292.2. <i>element</i>	925
10.292.2. <i>fwd_piter</i>	925
10.292.2. <i>piter</i>	926
10.292.2. <i>psite</i>	926
10.292.3.Constructor & Destructor Documentation	926
10.292.3. <i>lp_transformed</i>	926
10.292.3. <i>p_transformed</i>	926
10.292.4.Member Function Documentation	926
10.292.4. <i>lfunction</i>	926
10.292.4. <i>has</i>	926
10.292.4. <i>is_valid</i>	926
10.292.4. <i>memory_size</i>	927
10.292.4. <i>primary_set</i>	927
10.293. <i>ln::p_transformed_piter< Pi, S, F ></i> Struct Template Reference	927
10.293.1.Detailed Description	927
10.293.2.Constructor & Destructor Documentation	928
10.293.2. <i>lp_transformed_piter</i>	928
10.293.2. <i>p_transformed_piter</i>	928
10.293.3.Member Function Documentation	928
10.293.3. <i>lchange_target</i>	928
10.293.3. <i>next</i>	928
10.294. <i>ln::p_vaccess< V, S ></i> Class Template Reference	928
10.294.1.Detailed Description	930
10.294.2.Member Typedef Documentation	930
10.294.2. <i>lbkd_piter</i>	930
10.294.2. <i>element</i>	930
10.294.2. <i>fwd_piter</i>	930
10.294.2. <i>element</i>	930
10.294.2. <i>piter</i>	930
10.294.2. <i>set</i>	931
10.294.2. <i>psite</i>	931
10.294.2. <i>value</i>	931
10.294.2. <i>vset</i>	931
10.294.3.Constructor & Destructor Documentation	931
10.294.3. <i>lp_vaccess</i>	931
10.294.4.Member Function Documentation	931

10.294.4.1has	931
10.294.4.2has	931
10.294.4.3insert	932
10.294.4.4insert	932
10.294.4.5is_valid	932
10.294.4.6memory_size	932
10.294.4.7operator()	932
10.294.4.8values	932
10.295fmln::p_vertices< G, F > Class Template Reference	932
10.295.1Detailed Description	934
10.295.2Member Typedef Documentation	934
10.295.2.1bkd_piter	934
10.295.2.2element	935
10.295.2.3fun_t	935
10.295.2.4fwd_piter	935
10.295.2.5graph_element	935
10.295.2.6graph_t	935
10.295.2.7piter	935
10.295.2.8psite	935
10.295.2.9vertex	936
10.295.3Constructor & Destructor Documentation	936
10.295.3.1p_vertices	936
10.295.3.2p_vertices	936
10.295.3.3p_vertices	936
10.295.3.4p_vertices	936
10.295.3.5p_vertices	937
10.295.4Member Function Documentation	937
10.295.4.1function	937
10.295.4.2graph	937
10.295.4.3has	937
10.295.4.4has	937
10.295.4.5invalidate	938
10.295.4.6is_valid	938
10.295.4.7memory_size	938
10.295.4.8nsites	938
10.295.4.9nvertices	938

10.295.4.1operator()	938
10.296ln::pixel< I > Struct Template Reference	939
10.296.1Detailed Description	939
10.296.2Constructor & Destructor Documentation	940
10.296.2.1pixel	940
10.296.2.2pixel	940
10.296.3Member Function Documentation	940
10.296.3.1change_to	940
10.296.3.2is_valid	940
10.297ln::Pixel_Iterator< E > Struct Template Reference	940
10.297.1Detailed Description	941
10.297.2Member Function Documentation	941
10.297.2.1next	941
10.298ln::plain< I > Class Template Reference	942
10.298.1Detailed Description	942
10.298.2Member Typedef Documentation	942
10.298.2.1skeleton	942
10.298.3Constructor & Destructor Documentation	943
10.298.3.1plain	943
10.298.3.2plain	943
10.298.3.3plain	943
10.298.4Member Function Documentation	943
10.298.4.1operator I	943
10.298.4.2operator+=	943
10.298.4.3operator-=	943
10.299ln::Point< P > Struct Template Reference	943
10.299.1Detailed Description	945
10.299.2Member Typedef Documentation	945
10.299.2.1point	945
10.299.3Member Function Documentation	945
10.299.3.1to_point	945
10.299.4Friends And Related Function Documentation	945
10.299.4.1operator+=	945
10.299.4.2operator-=	946
10.299.4.3operator/	946
10.300ln::point< G, C > Struct Template Reference	946

10.300.1Detailed Description	949
10.300.2Member Typedef Documentation	949
10.300.2.1coord	949
10.300.2.2delta	949
10.300.2.3dpsite	949
10.300.2.4grid	949
10.300.2.5h_vec	950
10.300.2.6vec	950
10.300.3Member Enumeration Documentation	950
10.300.3.1"@30	950
10.300.4Constructor & Destructor Documentation	950
10.300.4.1point	950
10.300.4.2point	950
10.300.4.3point	950
10.300.4.4point	950
10.300.4.5point	951
10.300.5Member Function Documentation	951
10.300.5.1last_coord	951
10.300.5.2last_coord	951
10.300.5.3minus_infty	951
10.300.5.4operator+=	951
10.300.5.5operator-=	951
10.300.5.6operator[]	951
10.300.5.7operator[]	952
10.300.5.8plus_infty	952
10.300.5.9set_all	952
10.300.5.10_h_vec	952
10.300.5.11tb_vec	952
10.300.6Member Data Documentation	953
10.300.6.1origin	953
10.301mln::Point_Site< E > Struct Template Reference	953
10.301.1Detailed Description	954
10.301.2Friends And Related Function Documentation	954
10.301.2.1operator+	954
10.301.2.2operator-	955
10.301.2.3operator-	955

10.301.2.4operator<<	956
10.301.2.5operator==	956
10.302mln::Point_Site< void > Struct Template Reference	956
10.302.1Detailed Description	957
10.303mln::Proxy< E > Struct Template Reference	957
10.303.1Detailed Description	957
10.304mln::Proxy< void > Struct Template Reference	957
10.304.1Detailed Description	957
10.305mln::Pseudo_Site< E > Struct Template Reference	957
10.305.1Detailed Description	958
10.306mln::Pseudo_Site< void > Struct Template Reference	958
10.306.1Detailed Description	958
10.307mln::pw::image< F, S > Class Template Reference	958
10.307.1Detailed Description	959
10.307.2Member Typedef Documentation	959
10.307.2.1skeleton	959
10.307.3Constructor & Destructor Documentation	959
10.307.3.1image	959
10.307.3.2image	959
10.308mln::registration::closest_point_basic< P > Class Template Reference	959
10.308.1Detailed Description	960
10.309mln::registration::closest_point_with_map< P > Class Template Reference	960
10.309.1Detailed Description	960
10.310mln::Regular_Grid< E > Struct Template Reference	960
10.310.1Detailed Description	960
10.311mln::safe_image< I > Class Template Reference	961
10.311.1Detailed Description	961
10.311.2Member Typedef Documentation	961
10.311.2.1skeleton	961
10.311.3Member Function Documentation	961
10.311.3.1operator safe_image< const I >	961
10.312mln::select::p_of< P > Struct Template Reference	961
10.312.1Detailed Description	962
10.313mln::Site< E > Struct Template Reference	962
10.313.1Detailed Description	962
10.314mln::Site< void > Struct Template Reference	963

10.314. Detailed Description	963
10.315. ln::Site_Iterator< E > Struct Template Reference	963
10.315.1. Detailed Description	965
10.315.2. Member Function Documentation	965
10.315.2.1. next	965
10.316. ln::Site_Proxy< E > Struct Template Reference	965
10.316.1. Detailed Description	965
10.317. ln::Site_Proxy< void > Struct Template Reference	966
10.317.1. Detailed Description	966
10.318. ln::Site_Set< E > Struct Template Reference	966
10.318.1. Detailed Description	967
10.318.2. Friends And Related Function Documentation	968
10.318.2.1. ldiff	968
10.318.2.2. inter	968
10.318.2.3. operator<	968
10.318.2.4. operator<<	968
10.318.2.5. operator<=	968
10.318.2.6. operator==	969
10.318.2.7. sym_diff	969
10.318.2.8. uni	969
10.318.2.9. unique	969
10.319. ln::Site_Set< void > Struct Template Reference	969
10.319.1. Detailed Description	969
10.320. ln::slice_image< I > Struct Template Reference	969
10.320.1. Detailed Description	970
10.320.2. Member Typedef Documentation	970
10.320.2.1. Iskeleton	970
10.320.3. Constructor & Destructor Documentation	971
10.320.3.1. slice_image	971
10.320.3.2. slice_image	971
10.320.4. Member Function Documentation	971
10.320.4.1. ldomain	971
10.320.4.2. operator slice_image< const I >	971
10.320.4.3. operator()	971
10.320.4.4. operator()	971
10.320.4.5. sli	971

10.321 h ln::sub_image< I, S > Class Template Reference	972
10.321.1Detailed Description	972
10.321.2Member Typedef Documentation	972
10.321.2.1skeleton	972
10.321.3Constructor & Destructor Documentation	973
10.321.3.1sub_image	973
10.321.3.2sub_image	973
10.321.4Member Function Documentation	973
10.321.4.1domain	973
10.321.4.2operator sub_image< const I, S >	973
10.322 h ln::sub_image_if< I, S > Struct Template Reference	973
10.322.1Detailed Description	974
10.322.2Member Typedef Documentation	974
10.322.2.1skeleton	974
10.322.3Constructor & Destructor Documentation	974
10.322.3.1sub_image_if	974
10.322.3.2sub_image_if	974
10.322.4Member Function Documentation	974
10.322.4.1domain	974
10.323 h ln::thru_image< I, F > Class Template Reference	975
10.323.1Detailed Description	975
10.323.2Member Function Documentation	975
10.323.2.1operator thru_image< const I, F >	975
10.324 h ln::thrubin_image< I1, I2, F > Class Template Reference	975
10.324.1Detailed Description	976
10.324.2Member Typedef Documentation	976
10.324.2.1psite	976
10.324.2.2rvalue	976
10.324.2.3skeleton	976
10.324.2.4value	976
10.324.3Member Function Documentation	976
10.324.3.1operator thrubin_image< const I1, const I2, F >	976
10.325 h ln::topo::adj_higher_dim_connected_n_face_bkd_iter< D > Class Template Reference .	977
10.325.1Detailed Description	977
10.325.2Constructor & Destructor Documentation	977
10.325.2.1adj_higher_dim_connected_n_face_bkd_iter	977

10.325.3Member Function Documentation	978
10.325.3.lnext	978
10.326ln::topo::adj_higher_dim_connected_n_face_fwd_iter< D > Class Template Reference .	978
10.326.Detailed Description	978
10.326.Constructor & Destructor Documentation	979
10.326.2.ladj_higher_dim_connected_n_face_fwd_iter	979
10.326.3Member Function Documentation	979
10.326.3.lnext	979
10.327ln::topo::adj_higher_face_bkd_iter< D > Class Template Reference	979
10.327.Detailed Description	979
10.327.Constructor & Destructor Documentation	980
10.327.2.ladj_higher_face_bkd_iter	980
10.327.3Member Function Documentation	980
10.327.3.lnext	980
10.328ln::topo::adj_higher_face_fwd_iter< D > Class Template Reference	980
10.328.Detailed Description	981
10.328.Constructor & Destructor Documentation	981
10.328.2.ladj_higher_face_fwd_iter	981
10.328.3Member Function Documentation	981
10.328.3.lnext	981
10.329ln::topo::adj_lower_dim_connected_n_face_bkd_iter< D > Class Template Reference .	981
10.329.Detailed Description	982
10.329.Constructor & Destructor Documentation	982
10.329.2.ladj_lower_dim_connected_n_face_bkd_iter	982
10.329.3Member Function Documentation	982
10.329.3.lnext	982
10.330ln::topo::adj_lower_dim_connected_n_face_fwd_iter< D > Class Template Reference .	982
10.330.Detailed Description	983
10.330.Constructor & Destructor Documentation	983
10.330.2.ladj_lower_dim_connected_n_face_fwd_iter	983
10.330.3Member Function Documentation	983
10.330.3.lnext	983
10.331ln::topo::adj_lower_face_bkd_iter< D > Class Template Reference	984
10.331.Detailed Description	984
10.331.Constructor & Destructor Documentation	984
10.331.2.ladj_lower_face_bkd_iter	984

10.331.3Member Function Documentation	984
10.331.3.lnext	984
10.332mln::topo::adj_lower_face_fwd_iter< D > Class Template Reference	985
10.332.Detailed Description	985
10.332.Constructor & Destructor Documentation	985
10.332.2.ladj_lower_face_fwd_iter	985
10.332.3Member Function Documentation	985
10.332.3.lnext	985
10.333mln::topo::adj_lower_higher_face_bkd_iter< D > Class Template Reference	986
10.333.Detailed Description	986
10.333.Constructor & Destructor Documentation	986
10.333.2.ladj_lower_higher_face_bkd_iter	986
10.333.3Member Function Documentation	987
10.333.3.lnext	987
10.334mln::topo::adj_lower_higher_face_fwd_iter< D > Class Template Reference	987
10.334.Detailed Description	987
10.334.Constructor & Destructor Documentation	988
10.334.2.ladj_lower_higher_face_fwd_iter	988
10.334.3Member Function Documentation	988
10.334.3.lnext	988
10.335mln::topo::adj_m_face_bkd_iter< D > Class Template Reference	988
10.335.Detailed Description	989
10.335.Constructor & Destructor Documentation	989
10.335.2.ladj_m_face_bkd_iter	989
10.335.2.2adj_m_face_bkd_iter	989
10.335.3Member Function Documentation	989
10.335.3.lnext	989
10.336mln::topo::adj_m_face_fwd_iter< D > Class Template Reference	989
10.336.Detailed Description	990
10.336.Constructor & Destructor Documentation	990
10.336.2.ladj_m_face_fwd_iter	990
10.336.2.2adj_m_face_fwd_iter	990
10.336.3Member Function Documentation	991
10.336.3.lnext	991
10.337mln::topo::algebraic_face< D > Class Template Reference	991
10.337.Detailed Description	993

10.337.1	Constructor & Destructor Documentation	993
10.337.2.1	algebraic_face	993
10.337.2.2	algebraic_face	993
10.337.2.3	algebraic_face	993
10.337.2.4	algebraic_face	993
10.337.3	Member Function Documentation	993
10.337.3.1	cplx	993
10.337.3.2	data	994
10.337.3.3	dec_face_id	994
10.337.3.4	dec_n	994
10.337.3.5	face_id	994
10.337.3.6	higher_dim_adj_faces	994
10.337.3.7	inc_face_id	994
10.337.3.8	nc_n	994
10.337.3.9	invalidate	995
10.337.3.10	is_valid	995
10.337.3.11	lbwer_dim_adj_faces	995
10.337.3.12	l2	995
10.337.3.13	set_cplx	995
10.337.3.14	set_face_id	995
10.337.3.15	set_n	995
10.337.3.16	set_sign	996
10.337.3.17	sign	996
10.338	ln::topo::algebraic_n_face< N, D > Class Template Reference	996
10.338.1	Detailed Description	998
10.338.2	Constructor & Destructor Documentation	998
10.338.2.1	algebraic_n_face	998
10.338.2.2	algebraic_n_face	998
10.338.2.3	algebraic_n_face	998
10.338.3	Member Function Documentation	998
10.338.3.1	cplx	998
10.338.3.2	data	998
10.338.3.3	dec_face_id	999
10.338.3.4	face_id	999
10.338.3.5	higher_dim_adj_faces	999
10.338.3.6	inc_face_id	999

10.338.3.7 <i>invalidate</i>	999
10.338.3.8 <i>s_valid</i>	999
10.338.3.9 <i>lower_dim_adj_faces</i>	1000
10.338.3.10	1000
10.338.3.1 <i>set_cplx</i>	1000
10.338.3.1 <i>set_face_id</i>	1000
10.338.3.1 <i>set_sign</i>	1000
10.338.3.1 <i>sign</i>	1000
10.339 <i>lnl::topo::center_only_iter< D ></i> Class Template Reference	1001
10.339.1 <i>Detailed Description</i>	1001
10.339.2 <i>Constructor & Destructor Documentation</i>	1001
10.339.2.1 <i>center_only_iter</i>	1001
10.339.3 <i>Member Function Documentation</i>	1002
10.339.3.1 <i>next</i>	1002
10.340 <i>lnl::topo::centered_bkd_iter_adapter< D, I ></i> Class Template Reference	1002
10.340.1 <i>Detailed Description</i>	1002
10.340.2 <i>Constructor & Destructor Documentation</i>	1003
10.340.2.1 <i>centered_bkd_iter_adapter</i>	1003
10.340.3 <i>Member Function Documentation</i>	1003
10.340.3.1 <i>next</i>	1003
10.341 <i>lnl::topo::centered_fwd_iter_adapter< D, I ></i> Class Template Reference	1003
10.341.1 <i>Detailed Description</i>	1003
10.341.2 <i>Constructor & Destructor Documentation</i>	1004
10.341.2.1 <i>centered_fwd_iter_adapter</i>	1004
10.341.3 <i>Member Function Documentation</i>	1004
10.341.3.1 <i>next</i>	1004
10.342 <i>lnl::topo::complex< D ></i> Class Template Reference	1004
10.342.1 <i>Detailed Description</i>	1005
10.342.2 <i>Member Typedef Documentation</i>	1005
10.342.2.1 <i>bkd_citer</i>	1005
10.342.2.2 <i>fwd_citer</i>	1006
10.342.3 <i>Constructor & Destructor Documentation</i>	1006
10.342.3.1 <i>complex</i>	1006
10.342.4 <i>Member Function Documentation</i>	1006
10.342.4.1 <i>add_face</i>	1006
10.342.4.2 <i>add_face</i>	1006

10.342.4.3addr	1006
10.342.4.4nfaces	1006
10.342.4.5nfaces_of_dim	1007
10.342.4.6nfaces_of_static_dim	1007
10.342.4.7print	1007
10.342.4.8print_faces	1007
10.343mln::topo::face< D > Class Template Reference	1007
10.343.1Detailed Description	1009
10.343.2Constructor & Destructor Documentation	1009
10.343.2.1face	1009
10.343.2.2face	1009
10.343.2.3face	1009
10.343.3Member Function Documentation	1010
10.343.3.1cplx	1010
10.343.3.2data	1010
10.343.3.3dec_face_id	1010
10.343.3.4dec_n	1010
10.343.3.5face_id	1010
10.343.3.6higher_dim_adj_faces	1010
10.343.3.7inc_face_id	1011
10.343.3.8inc_n	1011
10.343.3.9invalidate	1011
10.343.3.10is_valid	1011
10.343.3.11bwre_dim_adj_faces	1011
10.343.3.12	1011
10.343.3.13set_cplx	1011
10.343.3.14set_face_id	1012
10.343.3.15set_n	1012
10.344mln::topo::face_bkd_iter< D > Class Template Reference	1012
10.344.1Detailed Description	1012
10.344.2Constructor & Destructor Documentation	1013
10.344.2.1face_bkd_iter	1013
10.344.3Member Function Documentation	1013
10.344.3.1next	1013
10.344.3.2start	1013
10.345mln::topo::face_fwd_iter< D > Class Template Reference	1013

10.345.1	Detailed Description	1014
10.345.2	Constructor & Destructor Documentation	1014
10.345.2.1	face_fwd_iter	1014
10.345.3	Member Function Documentation	1014
10.345.3.1	lnext	1014
10.345.3.2	start	1014
10.346	lnl::topo::is_n_face< N > Struct Template Reference	1014
10.346.1	Detailed Description	1015
10.347	lnl::topo::is_simple_2d_t< N > Struct Template Reference	1015
10.347.1	Detailed Description	1016
10.348	lnl::topo::is_simple_cell< I > Class Template Reference	1016
10.348.1	Detailed Description	1018
10.348.2	Member Typedef Documentation	1018
10.348.2.1	lpsite	1018
10.348.2.2	result	1018
10.348.3	Member Function Documentation	1018
10.348.3.1	lmln_geom	1018
10.348.3.2	operator()	1018
10.348.3.3	set_image	1019
10.348.4	Member Data Documentation	1019
10.348.4.1	ID	1019
10.349	lnl::topo::n_face< N, D > Class Template Reference	1019
10.349.1	Detailed Description	1020
10.349.2	Constructor & Destructor Documentation	1020
10.349.2.1	ln_face	1020
10.349.2.2	n_face	1021
10.349.3	Member Function Documentation	1021
10.349.3.1	lcplx	1021
10.349.3.2	data	1021
10.349.3.3	dec_face_id	1021
10.349.3.4	face_id	1021
10.349.3.5	higher_dim_adj_faces	1021
10.349.3.6	nc_face_id	1022
10.349.3.7	invalidate	1022
10.349.3.8	s_valid	1022
10.349.3.9	lower_dim_adj_faces	1022

10.349.3.1 <code>l0</code>	1022
10.349.3.1 <code>set_cplx</code>	1022
10.349.3.1 <code>set_face_id</code>	1022
10.350 <code>ln::topo::n_face_bkd_iter< D ></code> Class Template Reference	1023
10.350.1Detailed Description	1023
10.350.2Constructor & Destructor Documentation	1023
10.350.2.1 <code>n_face_bkd_iter</code>	1023
10.350.3Member Function Documentation	1024
10.350.3.1 <code>ln</code>	1024
10.350.3.2 <code>next</code>	1024
10.350.3.3 <code>start</code>	1024
10.351 <code>ln::topo::n_face_fwd_iter< D ></code> Class Template Reference	1024
10.351.1Detailed Description	1025
10.351.2Constructor & Destructor Documentation	1025
10.351.2.1 <code>n_face_fwd_iter</code>	1025
10.351.3Member Function Documentation	1025
10.351.3.1 <code>ln</code>	1025
10.351.3.2 <code>next</code>	1025
10.351.3.3 <code>start</code>	1026
10.352 <code>ln::topo::n_faces_set< N, D ></code> Class Template Reference	1026
10.352.1Detailed Description	1026
10.352.2Member Typedef Documentation	1026
10.352.2.1 <code>faces_type</code>	1026
10.352.3Member Function Documentation	1027
10.352.3.1 <code>ladd</code>	1027
10.352.3.2 <code>faces</code>	1027
10.352.3.3 <code>reserve</code>	1027
10.353 <code>ln::topo::skeleton::is_simple_point< N ></code> Struct Template Reference	1027
10.353.1Detailed Description	1027
10.354 <code>ln::topo::static_n_face_bkd_iter< N, D ></code> Class Template Reference	1028
10.354.1Detailed Description	1028
10.354.2Constructor & Destructor Documentation	1028
10.354.2.1 <code>static_n_face_bkd_iter</code>	1028
10.354.3Member Function Documentation	1029
10.354.3.1 <code>lnext</code>	1029
10.354.3.2 <code>start</code>	1029

10.355	ln::topo::static_n_face_fwd_iter< N, D > Class Template Reference	1029
10.355.1	Detailed Description	1029
10.355.2	Constructor & Destructor Documentation	1030
10.355.2.1	static_n_face_fwd_iter	1030
10.355.3	Member Function Documentation	1030
10.355.3.1	next	1030
10.355.3.2	start	1030
10.356	ln::tr_image< S, I, T > Struct Template Reference	1030
10.356.1	Detailed Description	1031
10.356.2	Member Typedef Documentation	1032
10.356.2.1	llvalue	1032
10.356.2.2	psite	1032
10.356.2.3	rvalue	1032
10.356.2.4	site	1032
10.356.2.5	skeleton	1032
10.356.2.6	value	1032
10.356.3	Constructor & Destructor Documentation	1032
10.356.3.1	tr_image	1032
10.356.4	Member Function Documentation	1033
10.356.4.1	ldomain	1033
10.356.4.2	has	1033
10.356.4.3	is_valid	1033
10.356.4.4	operator()	1033
10.356.4.5	set_tr	1033
10.356.4.6	tr	1033
10.357	ln::unproject_image< I, D, F > Struct Template Reference	1033
10.357.1	Detailed Description	1034
10.357.2	Constructor & Destructor Documentation	1034
10.357.2.1	lunproject_image	1034
10.357.2.2	unproject_image	1034
10.357.3	Member Function Documentation	1034
10.357.3.1	ldomain	1034
10.357.3.2	operator()	1035
10.357.3.3	operator()	1035
10.358	ln::util::adjacency_matrix< V > Class Template Reference	1035
10.358.1	Detailed Description	1035

10.358.1	Constructor & Destructor Documentation	1035
10.358.2.1	adjacency_matrix	1035
10.358.2.2	adjacency_matrix	1036
10.359.0	ln::util::array< T > Class Template Reference	1036
10.359.1	Detailed Description	1038
10.359.2	Member Typedef Documentation	1038
10.359.2.1	lbd_eiter	1038
10.359.2.2	eiter	1038
10.359.2.3	element	1039
10.359.2.4	fwd_eiter	1039
10.359.2.5	result	1039
10.359.3	Constructor & Destructor Documentation	1039
10.359.3.1	larray	1039
10.359.3.2	array	1039
10.359.3.3	array	1039
10.359.4	Member Function Documentation	1039
10.359.4.1	lappend	1039
10.359.4.2	append	1040
10.359.4.3	clear	1040
10.359.4.4	fill	1040
10.359.4.5	is_empty	1040
10.359.4.6	last	1040
10.359.4.7	last	1041
10.359.4.8	memory_size	1041
10.359.4.9	nelements	1041
10.359.4.10	operator()	1041
10.359.4.11	operator()	1041
10.359.4.12	operator[]	1042
10.359.4.13	operator[]	1042
10.359.4.14	reserve	1042
10.359.4.15	resize	1042
10.359.4.16	resize	1042
10.359.4.17	size	1042
10.359.4.18	std_vector	1043
10.360.0	ln::util::branch< T > Class Template Reference	1043
10.360.1	Detailed Description	1043

10.360.1	Constructor & Destructor Documentation	1043
10.360.2.1	branch	1043
10.360.3	Member Function Documentation	1044
10.360.3.1	apex	1044
10.360.3.2	util_tree	1044
10.361	ln::util::branch_iter< T > Class Template Reference	1044
10.361.1	Detailed Description	1045
10.361.2	Member Function Documentation	1045
10.361.2.1	ldepth	1045
10.361.2.2	invalidate	1045
10.361.2.3	is_valid	1045
10.361.2.4	next	1045
10.361.2.5	operator util::tree_node< T > &	1046
10.361.2.6	start	1046
10.362	ln::util::branch_iter_ind< T > Class Template Reference	1046
10.362.1	Detailed Description	1046
10.362.2	Member Function Documentation	1047
10.362.2.1	ldepth	1047
10.362.2.2	invalidate	1047
10.362.2.3	is_valid	1047
10.362.2.4	next	1047
10.362.2.5	operator util::tree_node< T > &	1047
10.362.2.6	start	1047
10.363	ln::util::couple< T, U > Class Template Reference	1047
10.363.1	Detailed Description	1048
10.363.2	Member Function Documentation	1049
10.363.2.1	lchange_both	1049
10.363.2.2	lchange_first	1049
10.363.2.3	lchange_second	1049
10.363.2.4	first	1049
10.363.2.5	second	1049
10.364	ln::util::eat Struct Reference	1049
10.364.1	Detailed Description	1050
10.365	ln::util::edge< G > Class Template Reference	1050
10.365.1	Detailed Description	1051
10.365.2	Member Typedef Documentation	1052

10.365.2.1category	1052
10.365.2.2graph_t	1052
10.365.2.3id_t	1052
10.365.2.4id_value_t	1052
10.365.3.Constructor & Destructor Documentation	1052
10.365.3.1edge	1052
10.365.4.Member Function Documentation	1052
10.365.4.1change_graph	1052
10.365.4.2graph	1052
10.365.4.3id	1053
10.365.4.4invalidate	1053
10.365.4.5is_valid	1053
10.365.4.6th_nbh_edge	1053
10.365.4.7nmax_nbh_edges	1053
10.365.4.8operator edge_id_t	1053
10.365.4.9update_id	1053
10.365.4.10l	1054
10.365.4.112	1054
10.365.4.12_other	1054
10.366.ln::util::fibonacci_heap< P, T >. Class Template Reference	1054
10.366.1.Detailed Description	1056
10.366.2.Constructor & Destructor Documentation	1056
10.366.2.1fibonacci_heap	1056
10.366.2.2fibonacci_heap	1056
10.366.3.Member Function Documentation	1056
10.366.3.1clear	1056
10.366.3.2front	1056
10.366.3.3is_empty	1057
10.366.3.4is_valid	1057
10.366.3.5nelements	1057
10.366.3.6operator=	1057
10.366.3.7pop_front	1057
10.366.3.8push	1057
10.366.3.9push	1058
10.367.ln::util::graph Class Reference	1058
10.367.1.Detailed Description	1060

10.367.2Member TypeDef Documentation	1060
10.367.2.1edge_fwd_iter	1060
10.367.2.2edge_nbh_edge_fwd_iter	1060
10.367.2.3edges_set_t	1060
10.367.2.4edges_t	1061
10.367.2.5vertex_fwd_iter	1061
10.367.2.6vertex_nbh_edge_fwd_iter	1061
10.367.2.7vertex_nbh_vertex_fwd_iter	1061
10.367.2.8vertices_t	1061
10.367.3Constructor & Destructor Documentation	1061
10.367.3.1graph	1061
10.367.3.2graph	1061
10.367.4Member Function Documentation	1062
10.367.4.1add_edge	1062
10.367.4.2add_vertex	1062
10.367.4.3add_vertices	1062
10.367.4.4e_ith_nbh_edge	1062
10.367.4.5e_nmax	1063
10.367.4.6e_nmax_nbh_edges	1063
10.367.4.7edge	1063
10.367.4.8edge	1063
10.367.4.9edges	1063
10.367.4.10has_e	1063
10.367.4.11has_v	1064
10.367.4.12subgraph_of	1064
10.367.4.13l	1064
10.367.4.14l2	1064
10.367.4.15l5_ith_nbh_edge	1064
10.367.4.16l6_ith_nbh_vertex	1064
10.367.4.17l7_nmax	1065
10.367.4.18l8_nmax_nbh_edges	1065
10.367.4.19l9_nmax_nbh_vertices	1065
10.367.4.20vertex	1065
10.368ln::util::greater_point< I > Class Template Reference	1065
10.368.1Detailed Description	1065
10.368.2Member Function Documentation	1066

10.368.2. <code>loperator()</code>	1066
10.369. <code>ln::util::greater_psite< I ></code> Class Template Reference	1066
10.369.1Detailed Description	1066
10.369.2Member Function Documentation	1066
10.369.2.1 <code>loperator()</code>	1066
10.370. <code>ln::util::head< T, R ></code> Class Template Reference	1066
10.370.1Detailed Description	1067
10.371. <code>ln::util::ignore</code> Struct Reference	1067
10.371.1Detailed Description	1067
10.372. <code>ln::util::ilcell< T ></code> Struct Template Reference	1067
10.372.1Detailed Description	1068
10.373. <code>ln::util::line_graph< G ></code> Class Template Reference	1068
10.373.1Detailed Description	1070
10.373.2Member Typedef Documentation	1070
10.373.2.1 <code>ledge_fwd_iter</code>	1070
10.373.2.2 <code>edge_nbh_edge_fwd_iter</code>	1070
10.373.2.3 <code>edges_t</code>	1070
10.373.2.4 <code>vertex_fwd_iter</code>	1070
10.373.2.5 <code>vertex_nbh_edge_fwd_iter</code>	1071
10.373.2.6 <code>vertex_nbh_vertex_fwd_iter</code>	1071
10.373.2.7 <code>vertices_t</code>	1071
10.373.3Member Function Documentation	1071
10.373.3.1 <code>e_iith_nbh_edge</code>	1071
10.373.3.2 <code>e_nmax</code>	1071
10.373.3.3 <code>e_nmax_nbh_edges</code>	1071
10.373.3.4 <code>edge</code>	1072
10.373.3.5 <code>graph</code>	1072
10.373.3.6 <code>has</code>	1072
10.373.3.7 <code>has</code>	1072
10.373.3.8 <code>has_e</code>	1072
10.373.3.9 <code>has_v</code>	1072
10.373.3.10 <code>is_subgraph_of</code>	1073
10.373.3.11 <code>I</code>	1073
10.373.3.12 <code>v</code>	1073
10.373.3.13 <code>iith_nbh_edge</code>	1073
10.373.3.14 <code>iith_nbh_vertex</code>	1073

10.373.3. l5_nmax	1074
10.373.3. l6_nmax_nbh_edges	1074
10.373.3. l7_nmax_nbh_vertices	1074
10.373.3. l8_vertex	1074
10.374 ln::util::nil Struct Reference	1074
10.374.1 Detailed Description	1075
10.375 ln::util::node< T, R > Class Template Reference	1075
10.375.1 Detailed Description	1075
10.376 ln::util::object_id< Tag, V > Class Template Reference	1075
10.376.1 Detailed Description	1076
10.376.2 Member Typedef Documentation	1077
10.376.2.1 lvalue_t	1077
10.376.3 Constructor & Destructor Documentation	1077
10.376.3.1 lobject_id	1077
10.377 ln::util::ord< T > Struct Template Reference	1077
10.377.1 Detailed Description	1077
10.378 ln::util::ord_pair< T > Struct Template Reference	1077
10.378.1 Detailed Description	1078
10.378.2 Member Function Documentation	1079
10.378.2.1 lchange_both	1079
10.378.2.2 lchange_first	1079
10.378.2.3 lchange_second	1079
10.378.2.4 first	1079
10.378.2.5 second	1079
10.379 ln::util::pix< I > Struct Template Reference	1080
10.379.1 Detailed Description	1080
10.379.2 Member Typedef Documentation	1080
10.379.2.1 lpsite	1080
10.379.2.2 lvalue	1080
10.379.3 Constructor & Destructor Documentation	1081
10.379.3.1 lpix	1081
10.379.4 Member Function Documentation	1081
10.379.4.1 lima	1081
10.379.4.2 lp	1081
10.379.4.3 lv	1081
10.380 ln::util::set< T > Class Template Reference	1081

10.380.1	Detailed Description	1083
10.380.2	Member Typedef Documentation	1084
10.380.2.1	bkd_eiter	1084
10.380.2.2	eiter	1084
10.380.2.3	element	1084
10.380.2.4	fwd_eiter	1084
10.380.3	Constructor & Destructor Documentation	1084
10.380.3.1	iset	1084
10.380.4	Member Function Documentation	1084
10.380.4.1	lclear	1084
10.380.4.2	first_element	1084
10.380.4.3	has	1085
10.380.4.4	insert	1085
10.380.4.5	insert	1085
10.380.4.6	is_empty	1086
10.380.4.7	last_element	1086
10.380.4.8	memory_size	1086
10.380.4.9	nelements	1086
10.380.4.10	operator[]	1086
10.380.4.11	remove	1087
10.380.4.12	std_vector	1087
10.381	lnln::util::site_pair< P > Class Template Reference	1087
10.381.1	Detailed Description	1088
10.381.2	Member Function Documentation	1088
10.381.2.1	lfirst	1088
10.381.2.2	pair	1089
10.381.2.3	second	1089
10.382	lnln::util::soft_heap< T, R > Class Template Reference	1089
10.382.1	Detailed Description	1090
10.382.2	Member Typedef Documentation	1090
10.382.2.1	lelement	1090
10.382.3	Constructor & Destructor Documentation	1090
10.382.3.1	lsoft_heap	1090
10.382.3.2	~soft_heap	1091
10.382.4	Member Function Documentation	1091
10.382.4.1	lclear	1091

10.382.4.2 <code>s_empty</code>	1091
10.382.4.3 <code>s_valid</code>	1091
10.382.4.4 <code>nElements</code>	1091
10.382.4.5 <code>pop_front</code>	1091
10.382.4.6 <code>push</code>	1092
10.382.4.7 <code>push</code>	1092
10.383 <code>ln::util::timer</code> Class Reference	1092
10.383.1Detailed Description	1093
10.384 <code>ln::util::tracked_ptr< T ></code> Struct Template Reference	1093
10.384.1Detailed Description	1093
10.384.2Constructor & Destructor Documentation	1094
10.384.2.1 <code>tracked_ptr</code>	1094
10.384.2.2 <code>tracked_ptr</code>	1094
10.384.2.3~ <code>tracked_ptr</code>	1094
10.384.3Member Function Documentation	1094
10.384.3.1 <code>operator bool</code>	1094
10.384.3.2 <code>operator!</code>	1094
10.384.3.3 <code>operator-></code>	1094
10.384.3.4 <code>operator-></code>	1094
10.384.3.5 <code>operator=</code>	1095
10.384.3.6 <code>operator=</code>	1095
10.385 <code>ln::util::tree< T ></code> Class Template Reference	1095
10.385.1Detailed Description	1096
10.385.2Constructor & Destructor Documentation	1096
10.385.2.1 <code>ltree</code>	1096
10.385.2.2 <code>tree</code>	1096
10.385.3Member Function Documentation	1096
10.385.3.1 <code>add_tree_down</code>	1096
10.385.3.2 <code>add_tree_up</code>	1096
10.385.3.3 <code>check_consistency</code>	1097
10.385.3.4 <code>main_branch</code>	1097
10.385.3.5 <code>root</code>	1097
10.386 <code>ln::util::tree_node< T ></code> Class Template Reference	1097
10.386.1Detailed Description	1098
10.386.2Constructor & Destructor Documentation	1099
10.386.2.1 <code>ltree_node</code>	1099

10.386.2. <code>tree_node</code>	1099
10.386.3.Member Function Documentation	1099
10.386.3.1 <code>add_child</code>	1099
10.386.3.2 <code>add_child</code>	1099
10.386.3.3 <code>check_consistency</code>	1100
10.386.3.4 <code>children</code>	1100
10.386.3.5 <code>children</code>	1100
10.386.3.6 <code>delete_tree_node</code>	1100
10.386.3.7 <code>elt</code>	1100
10.386.3.8 <code>&lt</code>	1101
10.386.3.9 <code>parent</code>	1101
10.386.3.10 <code>print</code>	1101
10.386.3.11 <code>search</code>	1101
10.386.3.12 <code>search_rec</code>	1102
10.386.3.13 <code>set_parent</code>	1102
10.387. <code>ln::util::vertex< G ></code> Class Template Reference	1102
10.387.1.Detailed Description	1104
10.387.2.Member Typedef Documentation	1104
10.387.2.1 <code>Category</code>	1104
10.387.2.2 <code>graph_t</code>	1104
10.387.2.3 <code>id_t</code>	1104
10.387.2.4 <code>id_value_t</code>	1104
10.387.3.Constructor & Destructor Documentation	1104
10.387.3.1 <code>vertex</code>	1104
10.387.4.Member Function Documentation	1105
10.387.4.1 <code>change_graph</code>	1105
10.387.4.2 <code>edge_with</code>	1105
10.387.4.3 <code>graph</code>	1105
10.387.4.4 <code>id</code>	1105
10.387.4.5 <code>invalidate</code>	1105
10.387.4.6 <code>is_valid</code>	1105
10.387.4.7 <code>ith_nbh_edge</code>	1106
10.387.4.8 <code>ith_nbh_vertex</code>	1106
10.387.4.9 <code>nmax_nbh_edges</code>	1106
10.387.4.10 <code>nmax_nbh_vertices</code>	1106
10.387.4.11 <code>operator vertex_id_t</code>	1106

10.387.4.1other	1106
10.387.4.1update_id	1106
10.388 <code>lnl::util::yes</code> Struct Reference	1107
10.388.1Detailed Description	1107
10.389 <code>lnl::Value< E ></code> Struct Template Reference	1107
10.389.1Detailed Description	1108
10.390 <code>lnl::value::float01</code> Class Reference	1109
10.390.1Detailed Description	1110
10.390.2Member Typedef Documentation	1110
10.390.2.1enc	1110
10.390.2.2equiv	1110
10.390.3Constructor & Destructor Documentation	1110
10.390.3.1float01	1110
10.390.3.2float01	1110
10.390.3.3float01	1110
10.390.4Member Function Documentation	1110
10.390.4.1nbits	1110
10.390.4.2operator float	1110
10.390.4.3set_nbits	1111
10.390.4.4to_nbits	1111
10.390.4.5value	1111
10.390.4.6value_ind	1111
10.391 <code>lnl::value::float01_f</code> Struct Reference	1111
10.391.1Detailed Description	1112
10.391.2Constructor & Destructor Documentation	1112
10.391.2.1float01_f	1112
10.391.2.2float01_f	1112
10.391.3Member Function Documentation	1112
10.391.3.1operator float	1112
10.391.3.2operator=	1112
10.391.3.3value	1112
10.392 <code>lnl::value::graylevel< n ></code> Struct Template Reference	1112
10.392.1Detailed Description	1114
10.392.2Constructor & Destructor Documentation	1114
10.392.2.1graylevel	1114
10.392.2.2graylevel	1114

10.392.2.3graylevel	1114
10.392.2.4graylevel	1114
10.392.2.5graylevel	1115
10.392.3Member Function Documentation	1115
10.392.3.1operator=	1115
10.392.3.2operator=	1115
10.392.3.3operator=	1115
10.392.3.4operator=	1115
10.392.3.5to_float	1115
10.392.3.6value	1115
10.393mln::value::graylevel_f Struct Reference	1116
10.393.1Detailed Description	1117
10.393.2Constructor & Destructor Documentation	1117
10.393.2.1graylevel_f	1117
10.393.2.2graylevel_f	1117
10.393.2.3graylevel_f	1117
10.393.2.4graylevel_f	1117
10.393.2.5graylevel_f	1117
10.393.3Member Function Documentation	1117
10.393.3.1operator graylevel< n >	1117
10.393.3.2operator=	1117
10.393.3.3operator=	1118
10.393.3.4operator=	1118
10.393.3.5operator=	1118
10.393.3.6value	1118
10.394mln::value::int_s< n > Struct Template Reference	1118
10.394.1Detailed Description	1120
10.394.2Constructor & Destructor Documentation	1120
10.394.2.1int_s	1120
10.394.2.2int_s	1120
10.394.2.3int_s	1120
10.394.3Member Function Documentation	1120
10.394.3.1operator int	1120
10.394.3.2operator=	1120
10.394.4Member Data Documentation	1120
10.394.4.1one	1120

10.394.4.2zero	1121
10.395 ln::value::int_u< n > Struct Template Reference	1121
10.395.1Detailed Description	1122
10.395.2Constructor & Destructor Documentation	1122
10.395.2.1int_u	1122
10.395.2.2int_u	1122
10.395.2.3int_u	1122
10.395.3Member Function Documentation	1122
10.395.3.1next	1122
10.395.3.2operator unsigned	1122
10.395.3.3operator-	1123
10.395.3.4operator=	1123
10.396 ln::value::int_u_sat< n > Struct Template Reference	1123
10.396.1Detailed Description	1124
10.396.2Constructor & Destructor Documentation	1124
10.396.2.1int_u_sat	1124
10.396.2.2int_u_sat	1124
10.396.3Member Function Documentation	1124
10.396.3.1operator int	1124
10.396.3.2operator+=	1125
10.396.3.3operator-=	1125
10.396.3.4operator=	1125
10.396.4Member Data Documentation	1125
10.396.4.1one	1125
10.396.4.2zero	1125
10.397 ln::value::Integer< E > Struct Template Reference	1125
10.397.1Detailed Description	1126
10.398 ln::value::Integer< void > Struct Template Reference	1126
10.398.1Detailed Description	1126
10.399 ln::value::label< n > Struct Template Reference	1126
10.399.1Detailed Description	1127
10.399.2Member Typedef Documentation	1127
10.399.2.1enc	1127
10.399.3Constructor & Destructor Documentation	1128
10.399.3.1label	1128
10.399.3.2label	1128

10.399.3. label	1128
10.399.4 Member Function Documentation	1128
10.399.4. lnext	1128
10.399.4. operator unsigned	1128
10.399.4. operator++	1128
10.399.4. operator--	1128
10.399.4. operator=	1129
10.399.4. operator=	1129
10.399.4. prev	1129
10.40 hln::value::lut_vec< S, T > Struct Template Reference	1129
10.400. Detailed Description	1131
10.400. Member Typedef Documentation	1131
10.400.2. lbd_kd_viter	1131
10.400.2. fwd_viter	1131
10.400.2. value	1131
10.400. Constructor & Destructor Documentation	1132
10.400.3. llut_vec	1132
10.400.3. lut_vec	1132
10.400.3. lut_vec	1132
10.400. Member Function Documentation	1132
10.400.4. lhas	1132
10.400.4. index_of	1132
10.400.4. values	1132
10.400.4. operator[]	1133
10.40 hln::value::proxy< I > Class Template Reference	1133
10.401. Detailed Description	1134
10.401. Member Typedef Documentation	1134
10.401.2. lenc	1134
10.401.2. equiv	1134
10.401. Constructor & Destructor Documentation	1134
10.401.3. lproxy	1134
10.401.3. proxy	1135
10.401.3. ~proxy	1135
10.401. Member Function Documentation	1135
10.401.4. loperator=	1135
10.401.4. operator=	1135

10.401.4. <code>to_value</code>	1135
10.402 <code>ln::value::qt::rgb32</code> Struct Reference	1135
10.402.1.Detailed Description	1136
10.402.2.Constructor & Destructor Documentation	1136
10.402.2.1 <code>rgb32</code>	1136
10.402.2.2 <code>rgb32</code>	1136
10.402.2.3 <code>rgb32</code>	1136
10.402.2.4 <code>rgb32</code>	1137
10.402.3.Member Function Documentation	1137
10.402.3. <code>operator=</code>	1137
10.402.3. <code>red</code>	1137
10.402.4.Member Data Documentation	1137
10.402.4. <code>lzero</code>	1137
10.403 <code>ln::value::rgb< n ></code> Struct Template Reference	1137
10.403.1.Detailed Description	1138
10.403.2.Constructor & Destructor Documentation	1138
10.403.2.1 <code>rgb</code>	1138
10.403.2.2 <code>gb</code>	1138
10.403.2.3 <code>rgb</code>	1138
10.403.2.4 <code>rgb</code>	1138
10.403.3.Member Function Documentation	1139
10.403.3. <code>operator=</code>	1139
10.403.3. <code>red</code>	1139
10.403.4.Member Data Documentation	1139
10.403.4. <code>lzero</code>	1139
10.404 <code>ln::value::set< T ></code> Struct Template Reference	1139
10.404.1.Detailed Description	1139
10.404.2.Member Function Documentation	1140
10.404.2. <code>lthe</code>	1140
10.405 <code>ln::value::sign</code> Class Reference	1140
10.405.1.Detailed Description	1141
10.405.2.Member Typedef Documentation	1141
10.405.2. <code>lenc</code>	1141
10.405.2. <code>equiv</code>	1141
10.405.3.Constructor & Destructor Documentation	1141
10.405.3. <code>lsign</code>	1141

10.405.3.2sign	1141
10.405.3.3sign	1141
10.405.4Member Function Documentation	1142
10.405.4.1operator int	1142
10.405.4.2operator=	1142
10.405.5Member Data Documentation	1142
10.405.5.1one	1142
10.405.5.2zero	1142
10.406ln::value::stack_image< n, I > Struct Template Reference	1142
10.406.1Detailed Description	1143
10.406.2Member Typedef Documentation	1143
10.406.2.1domain_t	1143
10.406.2.2value	1143
10.406.2.3psite	1144
10.406.2.4rvalue	1144
10.406.2.5skeleton	1144
10.406.2.6value	1144
10.406.3Constructor & Destructor Documentation	1144
10.406.3.1stack_image	1144
10.406.4Member Function Documentation	1144
10.406.4.1is_valid	1144
10.406.4.2operator()	1144
10.406.4.3operator()	1145
10.407ln::value::super_value< sign > Struct Template Reference	1145
10.407.1Detailed Description	1145
10.408ln::value::value_array< T, V > Struct Template Reference	1145
10.408.1Detailed Description	1145
10.408.2Constructor & Destructor Documentation	1146
10.408.2.1value_array	1146
10.408.3Member Function Documentation	1146
10.408.3.1operator()	1146
10.408.3.2operator[]	1146
10.408.3.3vset	1146
10.409ln::Value_Iterator< E > Struct Template Reference	1146
10.409.1Detailed Description	1147
10.409.2Member Function Documentation	1148

10.409.2. <i>Inext</i>	1148
10.409.3.Friends And Related Function Documentation	1148
10.409.3.1operator<<	1148
10.410. <i>lnl::Value_Set< E ></i> Struct Template Reference	1148
10.410.1Detailed Description	1149
10.411. <i>lnl::Vertex< E ></i> Struct Template Reference	1149
10.411.1Detailed Description	1149
10.412. <i>lnl::vertex_image< P, V, G ></i> Class Template Reference	1150
10.412.1Detailed Description	1151
10.412.2Member Typedef Documentation	1151
10.412.2.1graph_t	1151
10.412.2.2nbh_t	1151
10.412.2.3site_function_t	1151
10.412.2.4skeleton	1151
10.412.2.5vertex_nbh_t	1151
10.412.2.6vertex_win_t	1151
10.412.2.7win_t	1152
10.412.3Constructor & Destructor Documentation	1152
10.412.3.1vertex_image	1152
10.412.4Member Function Documentation	1152
10.412.4.1operator()	1152
10.413. <i>lnl::violent_cast_image< T, I ></i> Struct Template Reference	1152
10.413.1Detailed Description	1153
10.413.2Member Typedef Documentation	1153
10.413.2.1lvalue	1153
10.413.2.2rvalue	1153
10.413.2.3skeleton	1153
10.413.2.4value	1153
10.413.3Constructor & Destructor Documentation	1154
10.413.3.1violent_cast_image	1154
10.413.4Member Function Documentation	1154
10.413.4.1operator()	1154
10.413.4.2operator()	1154
10.414. <i>lnl::w_window< D, W ></i> Struct Template Reference	1154
10.414.1Detailed Description	1155
10.414.2Member Typedef Documentation	1156

10.414.2. <code>lbkd_qiter</code>	1156
10.414.2. <code>dpsite</code>	1156
10.414.2. <code>fwd_qiter</code>	1156
10.414.2. <code>weight</code>	1156
10.414.3. Constructor & Destructor Documentation	1156
10.414.3. <code>lw_window</code>	1156
10.414.4. Member Function Documentation	1156
10.414.4. <code>lclear</code>	1156
10.414.4. <code>linsert</code>	1156
10.414.4. <code>l_is_symmetric</code>	1157
10.414.4. <code>lstd_vector</code>	1157
10.414.4. <code>lSym</code>	1157
10.414.4. <code>lW</code>	1157
10.414.4. <code>lweights</code>	1157
10.414.4. <code>lwin</code>	1157
10.414.5. Friends And Related Function Documentation	1158
10.414.5. <code>loperator<<</code>	1158
10.414.5. <code>loperator==</code>	1158
10.415. mln::Weighted_Window< E > Struct Template Reference	1158
10.415. Detailed Description	1159
10.415. Friends And Related Function Documentation	1159
10.415.2. <code>loperator-</code>	1159
10.416. mln::win::backdiag2d Struct Reference	1159
10.416. Detailed Description	1159
10.416. Constructor & Destructor Documentation	1160
10.416.2. <code>lbackdiag2d</code>	1160
10.416.3. Member Function Documentation	1160
10.416.3. <code>llength</code>	1160
10.417. mln::win::ball< G, C > Struct Template Reference	1160
10.417. Detailed Description	1160
10.417. Constructor & Destructor Documentation	1161
10.417.2. <code>lball</code>	1161
10.417.3. Member Function Documentation	1161
10.417.3. <code>ldiameter</code>	1161
10.418. mln::win::cube3d Struct Reference	1161
10.418. Detailed Description	1161

10.418.1	Constructor & Destructor Documentation	1162
10.418.2.	lcube3d	1162
10.418.3	Member Function Documentation	1162
10.418.3.	llength	1162
10.419	lnln::win::cuboid3d Struct Reference	1162
10.419.1	Detailed Description	1163
10.419.2	Constructor & Destructor Documentation	1163
10.419.2.	lcuboid3d	1163
10.419.3	Member Function Documentation	1164
10.419.3.	ldepth	1164
10.419.3.	lheight	1164
10.419.3.	volume	1164
10.419.3.	width	1164
10.420	lnln::win::diag2d Struct Reference	1164
10.420.1	Detailed Description	1164
10.420.2	Constructor & Destructor Documentation	1165
10.420.2.	ldiag2d	1165
10.420.3	Member Function Documentation	1165
10.420.3.	llength	1165
10.421	lnln::win::line< M, i, C > Struct Template Reference	1165
10.421.1	Detailed Description	1166
10.421.2	Member Enumeration Documentation	1166
10.421.2.	l"@"87	1166
10.421.3	Constructor & Destructor Documentation	1166
10.421.3.	lline	1166
10.421.4	Member Function Documentation	1167
10.421.4.	llength	1167
10.421.4.	lsize	1167
10.422	lnln::win::multiple< W, F > Class Template Reference	1167
10.422.1	Detailed Description	1167
10.423	lnln::win::multiple_size< n, W, F > Class Template Reference	1167
10.423.1	Detailed Description	1167
10.424	lnln::win::octagon2d Struct Reference	1168
10.424.1	Detailed Description	1168
10.424.2	Constructor & Destructor Documentation	1168
10.424.2.	loctagon2d	1168

10.424.3Member Function Documentation	1169
10.424.3.larea	1169
10.424.3.length	1169
10.425mln::win::rectangle2d Struct Reference	1169
10.425.Detailed Description	1169
10.425.Constructor & Destructor Documentation	1170
10.425.2.rectangle2d	1170
10.425.3Member Function Documentation	1170
10.425.3.larea	1170
10.425.3.length	1170
10.425.3.std_vector	1170
10.425.3.width	1170
10.426mln::Window< E > Struct Template Reference	1170
10.426.Detailed Description	1171
10.427mln::window< D > Class Template Reference	1171
10.427.Detailed Description	1173
10.427.Member Typedef Documentation	1173
10.427.2.lbkd_qiter	1173
10.427.2.fwd_qiter	1173
10.427.2.qiter	1173
10.427.2.regular	1173
10.427.3Constructor & Destructor Documentation	1173
10.427.3.lwindow	1173
10.427.4Member Function Documentation	1174
10.427.4.lclear	1174
10.427.4.length	1174
10.427.4.dp	1174
10.427.4.has	1174
10.427.4.insert	1174
10.427.4.insert	1174
10.427.4.insert	1175
10.427.4.s_centered	1175
10.427.4.s_empty	1175
10.427.4.length	1175
10.427.4.print	1175
10.427.4.size	1175

10.427.4. <code>lstd_vector</code>	1176
10.427.4. <code>lsym</code>	1176
10.427.5. Friends And Related Function Documentation	1176
10.427.5. <code>loperator==</code>	1176
10.428. <code>mln::world::inter_pixel::is_separator</code> Struct Reference	1176
10.428.1. Detailed Description	1177
10.429. <code>trait::graph< I ></code> Struct Template Reference	1177
10.429.1. Detailed Description	1178
10.430. <code>trait::graph< mln::complex_image< 1, G, V > ></code> Struct Template Reference	1178
10.430.1. Detailed Description	1178
10.431. <code>trait::graph< mln::image2d< T > ></code> Struct Template Reference	1178
10.431.1. Detailed Description	1178

Chapter 1

Documentation of milena

1.1 Introduction

This is the documentation of Milena.

1.2 Overview of Milena.

- [mln](#)
- [mln::accu](#)
- [mln::algebra](#)
- [mln::arith](#)
- [mln::binarization](#)
- [mln::border](#)
- [mln::canvas](#)
- [mln::convert](#)
- [mln::data](#)
- [mln::debug](#)
- [mln::display](#)
- [mln::draw](#)
- [mln::estim](#)
- [mln::extension](#)
- [mln::fun](#)
- [mln::geom](#)
- [mln::graph](#)
- [mln::histo](#)

- [mln::io](#)
- [mln::labeling](#)
- [mln::data](#)
- [mln::linear](#)
- [mln::literal](#)
- [mln::logical](#)
- [mln::make](#)
- [mln::math](#)
- [mln::metal](#)
- [mln::morpho](#)
- [mln::norm](#)
- [mln::opt](#)
- [mln::pw](#)
- [mln::registration](#)
- [mln::set](#)
- [mln::tag](#)
- [mln::test](#)
- [mln::topo](#)
- [mln::trace](#)
- [mln::trait](#)
- [mln::transform](#)
- [mln::util](#)
- [mln::value](#)
- [mln::win](#)

1.3 Copyright and License.

Copyright (C) 2007, 2008, 2009, 2010, 2011 EPITA Research and Development (LRDE)

This documentation is part of Olena.

Olena is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, version 2 of the License.

Olena is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Olena. If not, see <<http://www.gnu.org/licenses/>>.

Chapter 2

Quick Reference Guide

- Installation
- Foreword
- Site
- Site set
- Image
- Structural elements: Window and neighborhood
- Sites, psites and dpoints
- Iterators
- Memory management
- Basic routines
- Input / Output
- Graphs and images
- Useful global variables
- Useful macros
- Common Compilation Errors

2.1 Installation

2.1.1 Requirements

2.1.1.1 To compile the user examples

2.1.1.2 To compile the documentation (Optional)

2.1.1.3 To develop in Olena

2.1.2 Getting Olena

2.1.3 Building Olena

2.2 Foreword

2.2.1 Generality

2.2.2 Directory hierarchy

2.2.3 Writing and compiling a program with Olena

2.3 Site

2.4 Site set

[Iterators](#)

2.4.1 Basic interface

2.4.2 Optional interface

```
box2d b(2,3);

// The bbox can be retrieved in constant time.
std::cout << b.bbox() << std::endl;

// nsites can be retrieved in constant time.
std::cout << "nsites = " << b.nsites() << std::endl;

[(0,0)..(1,2)]
nsites = 6

p_array<point2d> arr;
arr.insert(point2d(1,0));
arr.insert(point2d(1,1));

// The bbox is computed thanks to bbox() algorithm.
box2d box = geom::bbox(arr);
std::cout << box << std::endl;

// p_array provides nsites(),
```

```
// it can be retrieved in constant time.  
std::cout << "nsites = " << arr.nsites() << std::endl;  
  
[(1,0)..(1,1)]  
nsites = 2
```

2.5 Image

2.5.1 Definition

2.5.2 Possible image types

2.5.3 Possible value types

2.5.4 Domain

```
// Define a box2d from (-2,-3) to (3,5).  
box2d b = make::box2d(-2,-3, 3,5);  
// Initialize an image with b as domain.  
image2d<int> ima(b);  
  
std::cout << "b = " << b << std::endl;  
std::cout << "domain = " << ima.domain() << std::endl;  
  
b = [(-2,-3)..(3,5)]  
domain = [(-2,-3)..(3,5)]  
  
// Create an image on a 2D box  
// with 10 columns and 10 rows.  
image2d<bool> ima(make::box2d(10, 10));  
  
mln_site_(image2d<bool>) p1(20, 20);  
mln_site_(image2d<bool>) p2(3, 3);  
  
std::cout << "has(p1)? "  
      << (ima.has(p1) ? "true" : "false")  
      << std::endl;  
  
std::cout << "has(p2)? "  
      << (ima.has(p2) ? "true" : "false")  
      << std::endl;  
  
has(p1)? false  
has(p2)? true  
  
point2d p(9,9);  
  
// At (9, 9), both values change.  
ima1(p) = 'M';  
ima2(p) = 'W';  
  
bool b = (ima1(p) == ima2(p));  
std::cout << (b ? "True" : "False") << std::endl;  
  
False
```

2.5.5 Border and extension

2.5.5.1 Image border

2.5.5.2 Generality on image extension

imamorphed

2.5.5.3 Different extensions

```

image2d<rgb8> lena;
io::ppm::load(lena, MLN_IMG_DIR "/small.ppm");
box2d bbox_enlarged = lena.domain();
bbox_enlarged.enlarge(border::thickness);
mln_VAR(im_a_roi, lena | fun::p2b::big_chess<box2d>(lena.domain(), 10));

```

2.5.5.3.1 Extension with a value

```
mln_VAR(ext_with_val, extended_to(extend(ima_roi, literal::blue), bbox_enlarged));
```

2.5.5.3.2 Extension with a function

```
namespace mln
{
    struct my_ext : public Function_v2v<my_ext>
    {

```

```

typedef value::rgb8 result;

value::rgb8 operator()(const point2d& p) const
{
    if ((p.row() + p.col()) % 20)
        return literal::black;
    return literal::white;
}

};

} // end of namespace mln

mln_VAR(ext_with_fun, extended_to(extend(imma_roi, my_ext()), bbox_enlarged));

```

2.5.5.3.3 Extension with an image

```

mln_VAR(ext_with_ima, extend(imma_roi, lena));

// Default border size is set to 0.

// Image defined on a box2d from
// (0, 0) to (2, 2)
image2d<int> imal(2, 3);

std::cout << "imal.has(0, 0) : "
    << imal.has(point2d(0, 0)) << std::endl;

std::cout << "imal.has(-3, 0) : "
    << imal.has(point2d(-3, 0)) << std::endl;

std::cout << "imal.has(2, 5) : "
    << imal.has(point2d(2, 5)) << std::endl;

std::cout << "======" << std::endl;

// Set default border size to 0.
border::thickness = 0;

// Image defined on a box2d from
// (0, 0) to (2, 2)
image2d<int> ima2(2, 3);

std::cout << "ima2.has(0, 0) : "
    << ima2.has(point2d(0, 0)) << std::endl;

std::cout << "ima2.has(-3, 0) : "
    << ima2.has(point2d(-3, 0)) << std::endl;

std::cout << "ima2.has(2, 5) : "
    << ima2.has(point2d(2, 5)) << std::endl;

imal.has(0, 0) : 1
imal.has(-3, 0) : 1
imal.has(2, 5) : 1
=====
ima2.has(0, 0) : 1
ima2.has(-3, 0) : 0
ima2.has(2, 5) : 0

border::thickness = 30;

// Declare the image to be rotated.

```

```

image2d<value::rgb8> ima1_(220, 220);
data::fill(ima1_, literal::cyan);
border::fill(ima1_, literal::yellow);
// Set an infinite extension.
mln_VAR(ima1, extend(ima1_, pw::cst(literal::yellow)));

// Declare the output image.
image2d<value::rgb8> ima2(220, 220);
data::fill(ima2, literal::cyan);
border::fill(ima2, literal::yellow);

box2d extended_domain= ima1.domain();
extended_domain.enlarge(border::thickness);

// Draw the domain bounding box
draw::box(ima1, geom::bbox(ima1_), literal::red);
// Save the image, including its border.
doc::ppmsave(ima1 | extended_domain, "ima2d-rot");

// Define and apply a point-wise rotation
fun::x2x::rotation<2,float> rot1(0.5, literal::zero);
image2d<value::rgb8>::fwd_piter p(ima1.domain());
for_all(p)
{
    algebra::vec<2,float> pv = p.to_site().to_vec();
    algebra::vec<2,float> v = rot1.inv()(pv);
    ima2(p) = ima1(v);
}

draw::box(ima2, ima2.bbox(), literal::red);
doc::ppmsave(extended_to(ima2, extended_domain), "ima2d-rot");

my_routine(ima | ima.domain());

```

2.5.6 Interface

2.5.7 Load and save images

```

image2d<bool> ima;
io::pbm::load(ima, MLN_DOC_DIR "/img/small.pbm");

io::pbm::save(ima, MLN_DOC_DIR "/figures/ima_save.pbm");

```

2.5.8 Create an image

```

// Build an empty image;
image2d<value::int_u8> img1a;

// Build an image with 2 rows
// and 3 columns sites
image2d<value::int_u8> img1b(box2d(2, 3));
image2d<value::int_u8> img1c(2, 3);

bool vals[6][5] = {
    {0, 1, 1, 0, 0},
    {0, 1, 1, 0, 0},
    {0, 0, 0, 0, 0},
    {1, 1, 0, 1, 0},
    {1, 0, 1, 1, 1},
    {1, 0, 0, 0, 0}
};
image2d<bool> ima = make::image(vals);

```

```
image2d<value::int_u8> img2a(2, 3);
image2d<value::int_u8> img2b;

initialize(img2b, img2a);
data::fill(img2b, img2a);
```

[Fill](#)

2.5.9 Access and modify values

```
box2d b(2,3);
image2d<value::int_u8> ima(b);

// On image2d, Site <=> point2d
point2d p(1, 2);

// Associate '9' as value for the site/point2d (1,2).
// The value is returned by reference and can be changed.
opt::at(ima, 1,2) = 9;
std::cout << "opt::at(ima, 1,2) = " << opt::at(ima, 1,2)
    << std::endl;
std::cout << "ima(p) = " << ima(p) << std::endl;

std::cout << "---" << std::endl;

// Associate '2' as value for the site/point2d (1,2).
// The value is returned by reference
// and can be changed as well.
ima(p) = 2;
std::cout << "opt::at(ima, 1,2) = " << opt::at(ima, 1,2)
    << std::endl;
std::cout << "ima(p) = " << ima(p) << std::endl;

opt::at(ima, 1,2) = 9
ima(p) = 9
---
opt::at(ima, 1,2) = 2
ima(p) = 2
```

[Iterators](#)

2.5.10 Image size

```
image2d<int> ima(make::box2d(0,0, 10,12));

std::cout << "nrows = " << ima.nrows()
    << " - "
    << "ncols = " << ima.ncols()
    << std::endl;

nrows = 11 - ncols = 13
```

2.6 Structural elements: Window and neighborhood

2.6.1 Define an element

2.6.1.1 Window

2.6.1.2 Neighborhood

```
label_8 nlables;
image2d<label_8> lbl = labeling::blobs(ima, c4(), nlables);
```

2.6.1.3 Custom structural elements

```
window2d win;
win.insert(-1, -1);
win.insert(-1, 0);
win.insert(-1, 1);
```

○ -
○ X
○ -

```
bool b[9]      = { 1, 0, 0,
                  1, 0, 0,
                  1, 0, 0 };

bool b2[3][3] = { { 1, 0, 0 },
                  { 1, 0, 0 },
                  { 1, 0, 0 } };

window2d win = convert::to<window2d>(b);
window2d win2 = convert::to<window2d>(b2);
```

2.6.1.4 Conversion between Neighborhoods and Windows

2.7 Sites, psites and dpoints

2.7.1 Need for site

```
c 0 1 2 3
r
+---+---+
0 | | x | | |
+---+---+
1 | | | | |
+---+---+
```

2.7.2 Need for psite

```
unsigned my_values(const mln::point2d& p)
{
    if (p.row() == 0)
        return 8;
    return 9;
}
```

```

p_array<point2d> arr;
arr.append(point2d(3, 6));
arr.append(point2d(3, 7));
arr.append(point2d(3, 8));
arr.append(point2d(4, 8));
arr.append(point2d(4, 9));

mln_VAR(imma, my_values | arr);

c 6 7 8 9
r
  +---+
3 | |x| |
  +---+-
4 | | |
  +---+
arr[] = 0 1 2 3 4
  +---+---+-
  | |x| | |
  +---+---+-

```

2.7.3 From psite to site

2.7.4 Dpoint

```

dpoint2d dp(-1,0);
point2d p(1,1);

std::cout << p + dp << std::endl;

(0,1)

```

2.8 Iterators

```

box2d b(3, 2);
mln_piter_(box2d) p(b);

for_all(p)
    std::cout << p; //prints every site coordinates.

(0,0) (0,1) (1,0) (1,1) (2,0) (2,1)

template <typename I>
void fill(I& ima, mln_value(I) v)
{
    mln_piter(I) p(ima.domain());
    for_all(p)
        ima(p) = v;
}

template <typename I, typename J>
void paste(const I& data, J& dest)
{
    mln_piter(I) p(data.domain());
    for_all(p)
        dest(p) = data(p);
}

```

Useful macros

2.9 Memory management

```

image2d<int> ima1(box2d(2, 3));
image2d<int> ima2;
point2d p(1,2);

ima2 = ima1; // ima1.id() == ima2.id()
// and both point to the same memory area.

ima2(p) = 2; // ima1 is modified as well.

// prints "2 - 2"
std::cout << ima2(p) << " - " << ima1(p) << std::endl;
// prints "true"
std::cout << (ima2.id_() == ima1.id_()) << std::endl;

image2d<int> ima1(5, 5);
image2d<int> ima3 = duplicate(ima1); // Makes a deep copy.

point2d p(2, 2);
ima3(p) = 3;

std::cout << ima3(p) << " - " << ima1(p) << std::endl;
std::cout << (ima3.id_() == ima1.id_()) << std::endl;

3 - 0
0

```

2.10 Basic routines

2.10.1 Fill

```

image2d<char> imga(5, 5);

data::fill(imga, 'a');

data::fill((imga | box2d(1,2)).rw(), 'a');

```

2.10.2 Paste

```

image2d<unsigned char> imgb(make::box2d(5,5, 7,8));
// Initialize imga with the same domain as imgb.
image2d<unsigned char> imga(imgb.domain());

// Initialize the image values.
data::fill(imgb, 'b');

// Paste the content of imgb in imga.
data::paste(imgb, imga);

debug::println(imga);

```

```

98 98 98 98
98 98 98 98
98 98 98 98

```

```
image2d<int> ima1(5, 5);
```

```

image2d<int> ima2(10, 10);

std::cout << "ima1.domain() = " << ima1.domain()
    << std::endl;
std::cout << "ima2.domain() = " << ima2.domain()
    << std::endl;

image2d<int> ima1(5, 5);
image2d<int> ima2(10, 10);

std::cout << "ima1.domain() = " << ima1.domain()
    << std::endl;
std::cout << "ima2.domain() = " << ima2.domain()
    << std::endl;

```

2.10.3 Blobs

```

bool vals[6][5] = {
    {0, 1, 1, 0, 0},
    {0, 1, 1, 0, 0},
    {0, 0, 0, 0, 0},
    {1, 1, 0, 1, 0},
    {1, 0, 1, 1, 1},
    {1, 0, 0, 0, 0}
};
image2d<bool> ima = make::image(vals);

label_8 nlabels;
image2d<label_8> lbl = labeling::blobs(ima, c4(), nlabels);

```

2.10.4 Logical not

```

bool vals[5][5] = {
    {1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0},
    {1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0},
    {0, 1, 0, 1, 0}
};
image2d<bool> ima = make::image(vals);

image2d<bool> ima_neg = logical::not_(ima);

logical::not_inplace(ima);

```

2.10.5 Compute

2.10.5.1 Accumulators

```

data::compute(accu::meta::stat::max, ima);

data::compute(accu::meta::stat::max(), ima);

```

2.10.5.2 Example with labeling::compute()

```

bool vals[6][5] = {
    {0, 1, 1, 0, 0},

```

```

    {0, 1, 1, 0, 0},
    {0, 0, 0, 0, 0},
    {1, 1, 0, 1, 0},
    {1, 0, 1, 1, 1},
    {1, 0, 0, 0, 0}
};

image2d<bool> ima = make::image(vals);

label_8 nlabels;
image2d<label_8> lbl = labeling::blobs(ima, c4(), nlabels);

util::array<box2d> boxes =
    labeling::compute(accu::meta::shape::bbox(),
                      lbl,
                      nlabels);

for (unsigned i = 1; i <= nlabels; ++i)
    std::cout << boxes[i] << std::endl;

[(0,1)..(1,2)]
[(3,0)..(5,1)]
[(3,2)..(4,4)]

unsigned nsites = geom::nsites(ima);

```

2.10.6 Working with parts of an image

```

//function_p2b
bool my_function_p2b(mln::point2d p);

//function_p2v
//V is the value type used in the image.
template <typename V>
V my_function_p2v(mln::point2d p);

bool vals[6][5] = {
    {0, 1, 1, 0, 0},
    {0, 1, 1, 0, 0},
    {0, 0, 0, 0, 0},
    {1, 1, 0, 1, 0},
    {1, 0, 1, 1, 1},
    {1, 0, 0, 0, 0}
};
image2d<bool> ima = make::image(vals);

```

2.10.6.1 Restrict an image with a site set

```

p_array<point2d> arr;

// We add two points in the array.
arr.append(point2d(0, 1));
arr.append(point2d(4, 0));

// We restrict the image to the sites
// contained in arr and fill these ones
// with 0.
// We must call "rw()" here.
data::fill((ima | arr).rw(), 0);

debug::println((ima | arr));

```

```
mln_VAR(im2, ima | arr);
// We do not need to call "rw()" here.
data::fill(im2, 0);

-
-
-
-
```

2.10.6.2 Restrict an image with a predicate

```
label_8 nlabels;
image2d<label_8> lbl = labeling::blobs(ima, c4(), nlabels);

mln_VAR(lbl_2, lbl | (pw::value(lbl) == pw::cst(2u)));

image2d<rgb8> im2;
initialize(im2, ima);
data::fill(im2, literal::black);

data::fill((im2 | lbl_2.domain()).rw(), literal::red);

label_8 nlabels;
image2d<label_8> lab = labeling::blobs(ima, c4(), nlabels);

image2d<rgb8> im2;
initialize(im2, ima);
data::fill(im2, literal::black);

data::fill((im2 | (pw::value(lab) == pw::cst(2u))).rw(), literal::red);
```

2.10.6.3 Restrict an image with a C function

```
bool row_oddity(mln::point2d p)
{
    return p.row() % 2;
}

image2d<rgb8> im2;
initialize(im2, ima);
data::fill(im2, literal::black);

data::fill((im2 | row_oddity).rw(), literal::red);

ima | sub_D

0 1 0
1 1 1

mln_VAR(imab1, ima | (pw::value(ima) == pw::cst(1u)));
```

```

1
1 1 1

box2d b1(1,0, 1, 2);
mln_VAR(imac, imab1 | b1);

// Print:
// 1 1 1
debug::println(imac);

box2d b2(0,0, 1, 1);
// Will fail at runtime.
// ima.domain().has((0,0)) is false.
mln_VAR(imad, imab1 | b2);
debug::println(imad);

ima / sub_D

```

2.11 Input / Output

2.11.1 ImageMagick

2.11.2 GDCM

2.12 Graphs and images

2.12.1 Description

2.12.2 Example

```

0 1 2 3 4
.-----
0 |   0      2
1 |     \    /
2 |       1   |
3 |       \   |
4 |         3-4

util::graph g;

for (unsigned i = 0; i < 5; ++i)
    g.add_vertex(); // Add vertex 'i';

g.add_edge(0, 1); // Associated to edge 0.
g.add_edge(1, 2); // Associated to edge 1.
g.add_edge(1, 3); // Associated to edge 2.
g.add_edge(3, 4); // Associated to edge 3.
g.add_edge(4, 2); // Associated to edge 4.

typedef fun::i2v::array<point2d> F;
F f(5); // We need to map 5 vertices.
f(0) = point2d(0, 0);
f(1) = point2d(2, 2);
f(2) = point2d(0, 4);
f(3) = point2d(4, 3);
f(4) = point2d(4, 4);

```

```

typedef p_vertices<util::graph, F> pv_t;
pv_t pv(g, f);

template <typename S>
struct viota_t : public mln::Function_v2v< viota_t<S> >
{
    typedef unsigned result;

    viota_t(unsigned size)
    {
        v_.resize(size);
        for(unsigned i = 0; i < size; ++i)
            v_[i] = 10 + i;
    }

    unsigned
    operator()(const mln_psites(S)& p) const
    {
        return v_[p.v().id()];
    }

    protected:
        std::vector<result> v_;
};

// Constructs an image
viota_t<pv_t> viota(pv.nsites());
mln_VAR(graph_vertices_ima, viota | pv);

// Prints each vertex and its associated data.
mln_piter_(graph_vertices_ima_t) p(graph_vertices_ima.domain());
for_all(p)
    std::cout << "graph_vertices_ima(" << p << ") = "
        << graph_vertices_ima(p) << std::endl;

graph_vertices_ima((0,0)) = 10
graph_vertices_ima((2,2)) = 11
graph_vertices_ima((0,4)) = 12
graph_vertices_ima((4,3)) = 13
graph_vertices_ima((4,4)) = 14

// Function which maps sites to data.
viota_t viota(g.v_nmax());

// Iterator on vertices.
mln_vertex_iter_(util::graph) v(g);

// Prints each vertex and its associated value.
for_all(v)
    std::cout << v << " : " << viota(v) << std::endl;

0 : 10
1 : 11
2 : 12
3 : 13
4 : 14

// Iterator on vertices.
mln_vertex_iter_(util::graph) v(g);

// Iterator on v's edges.
mln_vertex_nbh_edge_iter_(util::graph) e(v);

```

```

// Prints the graph
// List all edges for each vertex.
for_all(v)
{
    std::cout << v << " : ";
    for_all(e)
        std::cout << e << " ";
    std::cout << std::endl;
}

0 : (0,1)
1 : (0,1) (1,2) (1,3)
2 : (1,2) (2,4)
3 : (1,3) (3,4)
4 : (3,4) (2,4)

// Iterator on edges.
mln_edge_iter_(util::graph) e(g);

// Iterator on edges adjacent to e.
mln_edge_nbh_edge_iter_(util::graph) ne(e);

// Prints the graph
// List all adjacent edges for each edge.
for_all(e)
{
    std::cout << e << " : ";
    for_all(ne)
        std::cout << ne << " ";
    std::cout << std::endl;
}

(0,1) : (1,2) (1,3)
(1,2) : (0,1) (1,3) (2,4)
(1,3) : (0,1) (1,2) (3,4)
(3,4) : (1,3) (2,4)
(2,4) : (1,2) (3,4)

// Iterator on vertices.
mln_vertex_iter_(util::graph) v(g);

// Iterator on vertices adjacent to v.
mln_vertex_nbh_vertex_iter_(util::graph) nv(v);

// Prints the graph
// List all adjacent edges for each edge.
for_all(v)
{
    std::cout << v << " : ";
    for_all(nv)
        std::cout << nv << " ";
    std::cout << std::endl;
}

0 : 1
1 : 0 2 3
2 : 1 4
3 : 1 4
4 : 3 2

```

2.13 Useful global variables

2.14 Useful macros

2.14.1 Variable declaration macros

2.14.2 Iterator type macros

2.14.2.1 Default iterator types

2.14.2.2 Forward iterator types

2.14.2.3 Backward iterators

2.14.2.4 Graph iterators

2.15 Common Compilation Errors

Chapter 3

Tutorial

- [Welcome](#)
- [Installation](#)
- [Getting started with Milena](#)
- [Data representation](#)
- [Load and save images](#)
- [Create your first image](#)
- [Read and write images](#)
- [Regions of interest](#)

3.1 Welcome

3.1.1 How to learn Milena

3.1.2 Obtaining the library

3.1.3 Downloading the library

3.1.3.1 Downloading from SVN

[Installation](#) [Directory structure](#) [Join the mailing lists](#)

3.1.3.2 Downloading packaged releases

[Installation](#) [Directory structure](#) [Join the mailing lists](#) [Documentation](#)

3.1.4 Join the mailing lists

3.1.5 Directory structure

3.1.6 Documentation

3.1.7 Community and Support

[Join the mailing lists](#) [Contacts](#)

3.1.8 Project status

[Join the mailing lists](#)

3.1.9 A brief history of Milena

3.1.10 Contacts

[Installation](#)

3.2 Installation

3.2.1 Bootstrap (SVN Sources)

[Configure](#)

3.2.2 Configure

3.2.3 Install

[Optional compilation](#) [Installation content](#)

3.2.4 Optional compilation

3.2.4.1 Examples

3.2.4.2 Tools

3.2.4.3 Tests

3.2.5 Installation content

[Welcome](#) [Getting started with Milena](#)

3.3 Getting started with Milena

3.3.1 Getting familiar with genericity

```
// Java or C -like code

void fill(image *ima, unsigned char v)
{
    for (int i = 0; i < ima->nrows; ++i)
        for (int j = 0; j < ima->ncols; ++j)
            ima->data[i][j] = v;
}

template <typename I>
void fill(I& ima, mln_value(I) v)
{
    mln_piter(I) p(ima.domain());
    for_all(p)
        ima(p) = v;
}

fill(ima, literal::green);

box2d b(20,20);
fill((ima | b).rw(), literal::green);
```

3.3.2 First generic algorithm

```
#include <mln/core/image/image2d.hh>
#include <mln/core/image/dmorph/image_if.hh>
#include <mln/core/alias/neighb2d.hh>

#include <mln/data/fill.hh>

#include <mln/labeling/blobs.hh>
#include <mln/labeling/compute.hh>
#include <mln/labeling/blobs.hh>

#include <mln/data/compare.hh>

#include <mln/util/array.hh>

#include <mln/value/label_8.hh>

#include <mln/accu/math/count.hh>

#include <mln/pw/all.hh>

#include <tests/data.hh>
#include <doc/tools/sample_utils.hh>

namespace mln
{

    template <typename I, typename N>
    mln_concrete(I)
    my_algorithm(const Image<I>& ima_,
                 const Neighborhood<N>& nbh_)
    {
        trace::entering("my_algorithm");

        const I& ima = exact(ima_);
        const N& nbh = exact(nbh_);
```

```

mln_precondition(imma.is_valid());
mln_precondition(nbh.is_valid());

typedef value::label_8 V;
V nlables;
mln_ch_value(I,V) lbl = labeling::blobs(imma, nbh, nlables);
util::array<unsigned>
    count = labeling::compute(accu::meta::math::count(),
                           lbl,
                           nlables);

mln_concrete(I) output;
initialize(output, imma);
data::fill(output, literal::one);

for (unsigned i = 1; i <= nlables; ++i)
    if (count[i] < 10u)
        data::fill((output | (pw::value(lbl) == pw::cst(i))).rw(),
                   literal::zero);

trace:::exiting("my_algorithm");
return output;
}

} // end of namespace mln

template <typename I, typename N>
mln_concrete(I)
my_algorithm(const Image<I>& imma_,
            const Neighborhood<N>& nbh_)

trace:::entering("my_algorithm");

```

Debug hints

```

const I& imma = exact(imma_);
const N& nbh = exact(nbh_);
mln_precondition(imma.is_valid());
mln_precondition(nbh.is_valid());

typedef value::label_8 V;
V nlables;
mln_ch_value(I,V) lbl = labeling::blobs(imma, nbh, nlables);
util::array<unsigned>
    count = labeling::compute(accu::meta::math::count(),
                           lbl,
                           nlables);

mln_concrete(I) output;
initialize(output, imma);
data::fill(output, literal::one);

for (unsigned i = 1; i <= nlables; ++i)
    if (count[i] < 10u)
        data::fill((output | (pw::value(lbl) == pw::cst(i))).rw(),
                   literal::zero);

trace:::exiting("my_algorithm");
return output;

```

3.3.3 Compilation

3.3.3.1 Include path

3.3.3.2 Library linking

[Input / Output](#)

3.3.3.3 Disable Debug

3.3.3.4 Compiler optimization flags

3.3.3.4.1 GCC

3.3.3.4.2 Other compilers

3.3.4 Debug hints

3.3.4.1 Using assertions and GDB

3.3.4.2 Traces

```
// ...
trace::quiet = false;

labeling::blobs(ima, c4(), nlables);

trace::quiet = true;

geom::bbox(ima);
// ...
```

3.3.4.3 Debug routines

```
image2d<int_u8> ima(5,5);
data::fill(ima, 2);
debug::println(ima);

2 2 2 2 2
2 2 2 2 2
2 2 2 2 2
2 2 2 2 2
2 2 2 2 2
```

```
image2d<int_u8> ima(5,5);
data::fill(ima, 2);
border::fill(ima, 7);
debug::println_with_border(ima);

7 7 7 7 7 7 7 7 7 7 7
7 7 7 7 7 7 7 7 7 7 7
7 7 7 7 7 7 7 7 7 7 7
7 7 7 2 2 2 2 2 7 7 7
7 7 7 2 2 2 2 2 7 7 7
7 7 7 2 2 2 2 2 7 7 7
```

```

7 7 7 2 2 2 2 2 7 7 7
7 7 7 2 2 2 2 2 7 7 7
7 7 7 7 7 7 7 7 7 7 7
7 7 7 7 7 7 7 7 7 7 7
7 7 7 7 7 7 7 7 7 7 7

int_u8 vals[25] = { 100, 100, 200, 200, 230,
                    100, 100, 200, 230, 230,
                    140, 140, 140, 0, 0,
                    65, 186, 65, 127, 127,
                    65, 65, 65, 127, 127 };

image2d<int_u8> ima = make::image2d(vals);
image2d<rgb8> ima_color = labeling::colorize(rgb8(), ima, 230);

```

[Installation Data representation](#)

3.4 Data representation

3.4.1 Sites

```

point2d p(3,3);
std::cout << p << std::endl;

(3,3)

```

3.4.2 Site sets

[Site set](#)

3.4.2.1 Creating a site set

```

box2d b(4,4);

(0,0), (0,1), (0,2), (0,3), (1,0), (1,1), (1,2), (1,3), (2,0), (2,1), (2,2), (2,3
), (3,0), (3,1), (3,2), (3,3),

mln_piter_(p_array<point2d>) p(arr);
for_all(p)
    std::cout << p << ", ";
    std::cout << std::endl;

(-2,-2), (-2,-1), (-2,0), (-2,1), (-2,2), (-1,-2), (-1,-1), (-1,0), (-1,1), (-1,2
), (0,-2), (0,-1), (0,0), (0,1), (0,2), (1,-2), (1,-1), (1,0), (1,1), (1,2), (2,-
2), (2,-1), (2,0), (2,1), (2,2),

mln_piter_(box2d) p(b);
for_all(p)
    std::cout << p << ", ";
    std::cout << std::endl;

(2,2), (1,2),

```

3.4.2.2 Getting access to sites

3.4.3 Images

3.4.3.1 Creating an image

3.4.3.2 Reading an image from a file

3.4.3.3 Accessing data

[Getting started with Milena Load and save images](#)

3.5 Load and save images

```
image2d<bool> ima;
io::pbm::load(ima, MLN_DOC_DIR "/img/small.pbm");

io::pbm::save(ima, MLN_DOC_DIR "/figures/ima_save.pbm");
```

[Load and save images](#) [Data representation](#) [Create your first image](#)

3.6 Create your first image

See also

[tuto2_first_image.cc](#)

```
bool vals[13][21] = {
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0},
    {0, 1, 0, 1, 0, 1, 1, 1, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0},
    {0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 0, 1, 0, 0, 1, 0, 0, 0},
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0},
    {0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 1, 0, 0, 1, 0, 0, 0, 1, 1, 0, 0, 0},
    {0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0},
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0}
};

image2d<bool> ima = make::image(vals);
```

[Create an image](#)

```
debug::println(ima);
```

```
-----  
- | - | - | | | - | - - - | - - - - | - - -  
- | - | - | - - - | - - - | - - - | - | -  
- | | | - | | | - | - - - | - - - | - | -  
- | - | - | - - - | - - - | - - - | - | -
```

A 10x10 grid of horizontal dashed lines, spaced evenly apart, forming a background pattern.

```
doc::pbmsave(ima, "tuto2_first_image");
```

Possible value types Load and save images Read and write images

3.7 Read and write images

See also

tuto3_rw_image.cc

```

image2d<value::rgb8> ima(40, 40);

data::fill(ima, literal::red);

for (def::coord row = 20; row < 30; ++row)
    for (def::coord col = 20; col < 30; ++col)
        ima(point2d(row, col)) = literal::blue;

for (def::coord row = 20; row < 30; ++row)
    for (def::coord col = 20; col < 30; ++col)
        opt::at(ima, row, col) = literal::blue;

image2d<value::rgb8> lena;
io::ppm::load(lena, MLN_IMG_DIR "/small.ppm");

data::fill(ima, lena);

data::paste(ima, lena);

```

Access and modify values Fill Paste Create your first image Regions of interest

3.8 Regions of interest

See also

tuto4 genericity and algorithms.cc

```
image2d<value::rgb8> lena;
io::ppm::load(lena, MLN_IMG_DIR "/small.ppm");

amespace data

template <typename I, typename D>
void fill(Image<I>& ima, const D& data);
```

3.8.1 Image domain restricted by a site set

```
box2d roi = make::box2d(20, 20, 39, 39);

data::fill((lena | roi).rw(), literal::green);
```

3.8.2 Image domain restricted by a function

```
p_array<point2d> arr;
for (def::coord row = geom::min_row(lena); row < geom::max_row(lena); ++row)
    for (def::coord col = geom::min_row(lena); col < geom::max_col(lena); ++col)
        if (((row + col) % 2) == 0)
            arr.append(point2d(row, col));

for (def::coord row = geom::min_row(lena); row < geom::max_row(lena); ++row)
    for (def::coord col = geom::min_row(lena); col < geom::max_col(lena); ++col)
        if (((row + col) % 2) == 0)
            opt::at(lena, row, col) = literal::green;

data::fill((lena | fun::p2b::chess()).rw(), literal::green);
```

3.8.3 Image domain restricted by a mask

```
image2d<bool> mask;
initialize(mask, lena);
data::fill(mask, false);
data::fill((mask | make::box2d(10, 10, 14, 14)).rw(), true);
data::fill((mask | make::box2d(25, 15, 29, 18)).rw(), true);
data::fill((mask | make::box2d(50, 50, 54, 54)).rw(), true);

data::fill((lena | pw::value(mask)).rw(), literal::green);
```

3.8.4 Image domain restricted by a predicate

```
image2d<bool> lena_bw = binarization::binarization(lena, keep_specific_colors()
    );
value::label_8 nlabels;
image2d<value::label_8> label = labeling::blobs(lena_bw, c8(), nlabels);

data::fill((lena | (pw::value(label) == pw::cst(0u))).rw(), literal::blue);
```

[Read and write images](#)

Chapter 4

Module Index

4.1 Modules

Here is a list of all modules:

Types	98
Graphes	94
Images	95
Basic types	95
Image morphers	96
Values morphers	96
Domain morphers	97
Identity morphers	98
Neighborhoods	101
1D neighborhoods	101
2D neighborhoods	102
3D neighborhoods	104
Site sets	108
Basic types	108
Graph based	109
Complex based	109
Sparse types	109
Queue based	110
Utilities	110
Windows	111
1D windows	112
2D windows	113
3D windows	115
N-D windows	118
Multiple windows	118
Accumulators	99
On site sets	91
On images	91
On values	92
Multiple accumulators	94
Routines	99
Canvas	99

Functions	100
v2w2v functions	118
v2w_w2v functions	119
vv2b functions	119

Chapter 5

Namespace Index

5.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

<code>mln</code> (Mln/convert/to_image.hh)	121
<code>mln::accu</code> (Namespace of accumulators)	164
<code>mln::accu::image</code> (Namespace of accumulator image routines)	167
<code>mln::accu::impl</code> (Implementation namespace of accumulator namespace)	167
<code>mln::accu::logic</code> (Namespace of logical accumulators)	168
<code>mln::accu::math</code> (Namespace of mathematic accumulators)	168
<code>mln::accu::meta::logic</code> (Namespace of logical meta-accumulators)	169
<code>mln::accu::meta::math</code> (Namespace of mathematic meta-accumulators)	169
<code>mln::accu::meta::shape</code> (Namespace of shape meta-accumulators)	170
<code>mln::accu::meta::stat</code> (Namespace of statistical meta-accumulators)	170
<code>mln::accu::shape</code> (Namespace of shape accumulators)	171
<code>mln::accu::stat</code> (Namespace of statistical accumulators)	171
<code>mln::algebra</code> (Namespace of algebraic structure)	173
<code>mln::arith</code> (Namespace of arithmetic)	175
<code>mln::arith::impl</code> (Implementation namespace of arith namespace)	187
<code>mln::arith::impl::generic</code> (Generic implementation namespace of arith namespace)	188
<code>mln::binarization</code> (Namespace of "point-wise" expression tools)	188
<code>mln::border</code> (Namespace of routines related to image virtual (outer) border)	189
<code>mln::border::impl</code> (Implementation namespace of border namespace)	192
<code>mln::border::impl::generic</code> (Generic implementation namespace of border namespace)	193
<code>mln::canvas</code> (Namespace of canvas)	193
<code>mln::canvas::browsing</code> (Namespace of browsing canvas)	194
<code>mln::canvas::impl</code> (Implementation namespace of canvas namespace)	195
<code>mln::canvas::labeling</code> (Namespace of labeling canvas)	195
<code>mln::canvas::labeling::impl</code> (Implementation namespace of labeling canvas namespace)	196
<code>mln::canvas::morpho</code> (Namespace of morphological canvas)	197
<code>mln::convert</code> (Namespace of conversion routines)	197
<code>mln::data</code> (Namespace of image processing routines related to pixel data)	203
<code>mln::data::approx</code> (Namespace of image processing routines related to pixel levels with approximation)	215
<code>mln::data::approx::impl</code> (Implementation namespace of <code>data::approx</code> namespace)	217
<code>mln::data::impl</code> (Implementation namespace of data namespace)	217
<code>mln::data::impl::generic</code> (Generic implementation namespace of data namespace)	220

mln::data::naive (Namespace of image processing routines related to pixel levels with naive approach)	223
mln::data::naive::impl (Implementation namespace of <code>data::naive</code> namespace)	224
mln::debug (Namespace of routines that help to debug)	224
mln::debug::impl (Implementation namespace of debug namespace)	230
mln::def (Namespace for core definitions)	230
mln::display (Namespace of routines that help to display images)	231
mln::display::impl (Implementation namespace of display namespace)	232
mln::display::impl::generic (Generic implementation namespace of display namespace)	232
mln::doc (The namespace <code>mln::doc</code> is only for documentation purpose)	232
mln::draw (Namespace of drawing routines)	234
mln::estim (Namespace of estimation materials)	237
mln::extension (Namespace of extension tools)	239
mln::fun (Namespace of functions)	242
mln::fun::access (Namespace for access functions)	243
mln::fun::i2v (Namespace of integer-to-value functions)	243
mln::fun::n2v (Namespace of functions from nil to value)	244
mln::fun::p2b (Namespace of functions from point to boolean)	244
mln::fun::p2p (Namespace of functions from grid point to grid point)	244
mln::fun::p2v (Namespace of functions from point to value)	245
mln::fun::stat (Namespace of statistical functions)	245
mln::fun::v2b (Namespace of functions from value to logic value)	245
mln::fun::v2i (Namespace of value-to-integer functions)	245
mln::fun::v2v (Namespace of functions from value to value)	246
mln::fun::v2w2v (Namespace of bijective functions)	247
mln::fun::v2w_w2v (Namespace of functions from value to value)	247
mln::fun::vv2b (Namespace of functions from value to value)	248
mln::fun::vv2v (Namespace of functions from a couple of values to a value)	249
mln::fun::x2p (Namespace of functions from point to value)	249
mln::fun::x2v (Namespace of functions from vector to value)	250
mln::fun::x2x (Namespace of functions from vector to vector)	250
mln::geom (Namespace of all things related to geometry)	250
mln::geom::impl (Implementation namespace of geom namespace)	264
mln::graph (Namespace of graph related routines)	265
mln::grid (Namespace of grids definitions)	267
mln::histo (Namespace of histograms)	267
mln::histo::impl (Implementation namespace of histo namespace)	269
mln::histo::impl::generic (Generic implementation namespace of histo namespace)	269
mln::impl (Implementation namespace of mln namespace)	269
mln::io (Namespace of input/output handling)	269
mln::io::cloud (Namespace of cloud input/output handling)	271
mln::io::dicom (Namespace of DICOM input/output handling)	272
mln::io::dump (Namespace of dump input/output handling)	273
mln::io::fits (Namespace of fits input/output handling)	274
mln::io::fld (Namespace of pgm input/output handling)	275
mln::io::magick (Namespace of magick input/output handling)	276
mln::io::off (Namespace of off input/output handling)	278
mln::io::pbm (Namespace of pbm input/output handling)	279
mln::io::pbm::impl (Namespace of pbm implementation details)	281
mln::io::pbms (Namespace of pbms input/output handling)	281
mln::io::pbms::impl (Namespace of pbms implementation details)	282
mln::io::pfm (Namespace of pfm input/output handling)	282
mln::io::pfm::impl (Implementation namespace of pfm namespace)	283
mln::io::pgm (Namespace of pgm input/output handling)	284

mln::io::pgms (Namespace of pgms input/output handling)	285
mln::io::plot (Namespace of plot input/output handling)	285
mln::io::pnm (Namespace of pnm input/output handling)	287
mln::io::pnm::impl (Namespace of pnm's implementation details)	289
mln::io::pnms (Namespace of pnms input/output handling)	289
mln::io::ppm (Namespace of ppm input/output handling)	290
mln::io::ppms (Namespace of ppms input/output handling)	292
mln::io::raw (Namespace of raw input/output handling)	292
mln::io::tiff (Namespace of tiff input/output handling)	294
mln::io::txt (Namespace of txt input/output handling)	294
mln::labeling (Namespace of labeling routines)	295
mln::labeling::impl (Implementation namespace of labeling namespace)	310
mln::labeling::impl::generic (Generic implementation namespace of labeling namespace)	312
mln::linear (Namespace of linear image processing routines)	314
mln::linear::impl (Namespace of linear image processing routines implementation details)	318
mln::linear::local (Specializations of local linear routines)	318
mln::linear::local::impl (Namespace of local linear routines implementation details)	319
mln::literal (Namespace of literals)	319
mln::logical (Namespace of logic)	326
mln::logical::impl (Implementation namespace of logical namespace)	329
mln::logical::impl::generic (Generic implementation namespace of logical namespace)	329
mln::make (Namespace of routines that help to make Milena's objects)	330
mln::math (Namespace of mathematical routines)	354
mln::metal (Namespace of meta-programming tools)	355
mln::metal::impl (Implementation namespace of metal namespace)	356
mln::metal::math (Namespace of static mathematical functions)	356
mln::metal::math::impl (Implementation namespace of <code>metal::math</code> namespace)	357
mln::morpho (Namespace of mathematical morphology routines)	357
mln::morpho::approx (Namespace of approximate mathematical morphology routines)	367
mln::morpho::attribute (Namespace of attributes used in mathematical morphology)	367
mln::morpho::closing::approx (Namespace of approximate mathematical morphology closing routines)	367
mln::morpho::elementary (Namespace of image processing routines of elementary mathematical morphology)	368
mln::morpho::impl (Namespace of mathematical morphology routines implementations)	370
mln::morpho::impl::generic (Namespace of mathematical morphology routines generic implementations)	370
mln::morpho::opening::approx (Namespace of approximate mathematical morphology opening routines)	370
mln::morpho::reconstruction (Namespace of morphological reconstruction routines)	371
mln::morpho::reconstruction::by_dilation (Namespace of morphological reconstruction by dilation routines)	371
mln::morpho::reconstruction::by_erosion (Namespace of morphological reconstruction by erosion routines)	371
mln::morpho::tree (Namespace of morphological tree-related routines)	372
mln::morpho::tree::filter (Namespace for attribute filtering)	379
mln::morpho::watershed (Namespace of morphological watershed routines)	382
mln::morpho::watershed::watershed (Namespace of morphological watershed routines implementations)	384
mln::morpho::watershed::watershed::generic (Namespace of morphological watershed routines generic implementations)	384
mln::norm (Namespace of norms)	384
mln::norm::impl (Implementation namespace of norm namespace)	386
mln::opt (Namespace of optional routines)	387

mln::opt::impl (Implementation namespace of opt namespace)	388
mln::pw (Namespace of "point-wise" expression tools)	389
mln::registration (Namespace of "point-wise" expression tools)	389
mln::select (Select namespace (FIXME doc))	392
mln::set (Namespace of image processing routines related to pixel sets)	392
mln::subsampling (Namespace of "point-wise" expression tools)	394
mln::tag (Namespace of image processing routines related to tags)	396
mln::test (Namespace of image processing routines related to pixel tests)	396
mln::test::impl (Implementation namespace of test namespace)	398
mln::topo (Namespace of "point-wise" expression tools)	398
mln::trace (Namespace of routines related to the trace mechanism)	408
mln::trait (Namespace where traits are defined)	408
mln::transform (Namespace of transforms)	408
mln::util (Namespace of tools using for more complex algorithm)	413
mln::util::impl (Implementation namespace of util namespace)	420
mln::value (Namespace of materials related to pixel value types)	420
mln::value::impl (Implementation namespace of value namespace)	432
mln::win (Namespace of image processing routines related to win)	432

Chapter 6

Class Index

6.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

mln::Generalized_Pixel< bkd_pixter1d< I > >	
mln::Pixel_Iterator< bkd_pixter1d< I > >
pixel_iterator_base_< I, bkd_pixter1d< I > >	
backward_pixel_iterator_base_< I, bkd_pixter1d< I > >	
mln::bkd_pixter1d< I >
mln::Generalized_Pixel< bkd_pixter2d< I > >	
mln::Pixel_Iterator< bkd_pixter2d< I > >
pixel_iterator_base_< I, bkd_pixter2d< I > >	
backward_pixel_iterator_base_< I, bkd_pixter2d< I > >	
mln::bkd_pixter2d< I >
mln::Generalized_Pixel< bkd_pixter3d< I > >	
mln::Pixel_Iterator< bkd_pixter3d< I > >
pixel_iterator_base_< I, bkd_pixter3d< I > >	
backward_pixel_iterator_base_< I, bkd_pixter3d< I > >	
mln::bkd_pixter3d< I >
mln::Generalized_Pixel< dpoints_bkd_pixter< I > >	
mln::Pixel_Iterator< dpoints_bkd_pixter< I > >
mln::dpoints_bkd_pixter< I >
mln::Generalized_Pixel< dpoints_fwd_pixter< I > >	
mln::Pixel_Iterator< dpoints_fwd_pixter< I > >
mln::dpoints_fwd_pixter< I >
mln::Generalized_Pixel< fwd_pixter1d< I > >	
mln::Pixel_Iterator< fwd_pixter1d< I > >
pixel_iterator_base_< I, fwd_pixter1d< I > >	
forward_pixel_iterator_base_< I, fwd_pixter1d< I > >	
mln::fwd_pixter1d< I >
mln::Generalized_Pixel< fwd_pixter2d< I > >	
mln::Pixel_Iterator< fwd_pixter2d< I > >
pixel_iterator_base_< I, fwd_pixter2d< I > >	
forward_pixel_iterator_base_< I, fwd_pixter2d< I > >	
mln::fwd_pixter2d< I >
mln::Generalized_Pixel< fwd_pixter3d< I > >	
mln::Pixel_Iterator< fwd_pixter3d< I > >

pixel_iterator_base< I, fwd_pixter3d< I > >	
forward_pixel_iterator_base< I, fwd_pixter3d< I > >	
mln::fwd_pixter3d< I >	722
mln::Generalized_Pixel< pixel< I > >	
mln::pixel< I >	939
mln::internal::image_base< algebra::vec< n, I::value >, I::domain_t, stack_image< n, I > >	
image_morpher< I, algebra::vec< n, I::value >, I::domain_t, stack_image< n, I > >	
image_value_morpher< I, algebra::vec< n, I::value >, stack_image< n, I > >	
mln::value::stack_image< n, I >	1142
mln::internal::image_base< const I::value, I::domain_t, E >	
image_morpher< const I, const I::value, I::domain_t, E >	
image_identity< const I, I::domain_t, E >	
mln::labeled_image_base< I, E >	793
mln::internal::image_base< const I::value, I::domain_t, labeled_image< I > >	
image_morpher< const I, const I::value, I::domain_t, labeled_image< I > >	
image_identity< const I, I::domain_t, labeled_image< I > >	
mln::labeled_image_base< I, labeled_image< I > >	793
mln::labeled_image< I >	789
mln::internal::image_base< F::result, I1::domain_t, thrubin_image< I1, I2, F > >	
image_morpher< I1, F::result, I1::domain_t, thrubin_image< I1, I2, F > >	
image_value_morpher< I1, F::result, thrubin_image< I1, I2, F > >	
mln::thrubin_image< I1, I2, F >	975
mln::internal::image_base< F::result, I::domain_t, fun_image< F, I > >	
image_morpher< I, F::result, I::domain_t, fun_image< F, I > >	
image_value_morpher< I, F::result, fun_image< F, I > >	
mln::fun_image< F, I >	712
mln::internal::image_base< F::result, S, E >	
image_primary< F::result, S, E >	
mln::internal::image_base< F::result, S, image< F, S > >	
image_primary< F::result, S, image< F, S > >	
image_base< F, S, image< F, S > >	
mln::pw::image< F, S >	958
mln::internal::image_base< fun::i2v::array< V >::result, p_edges< G, internal::efsite_selector< P, G >::site_function_t >, edge_image< P, V, G > >	
image_primary< fun::i2v::array< V >::result, p_edges< G, internal::efsite_selector< P, G >::site_function_t >, edge_image< P, V, G > >	
image_base< fun::i2v::array< V >, p_edges< G, internal::efsite_selector< P, G >::site_function_t >, edge_image< P, V, G > >	
mln::edge_image< P, V, G >	655
mln::internal::image_base< fun::i2v::array< V >::result, p_vertices< G, internal::vfsite_selector< P, G >::site_function_t >, vertex_image< P, V, G > >	
image_primary< fun::i2v::array< V >::result, p_vertices< G, internal::vfsite_selector< P, G >::site_function_t >, vertex_image< P, V, G > >	
image_base< fun::i2v::array< V >, p_vertices< G, internal::vfsite_selector< P, G >::site_function_t >, vertex_image< P, V, G > >	
mln::vertex_image< P, V, G >	1150
mln::internal::image_base< I::value, box2d, slice_image< I > >	
image_morpher< I, I::value, box2d, slice_image< I > >	
image_domain_morpher< I, box2d, slice_image< I > >	
mln::slice_image< I >	969
mln::internal::image_base< I::value, box2d_h, hexa< I > >	
image_morpher< I, I::value, box2d_h, hexa< I > >	
image_domain_morpher< I, box2d_h, hexa< I > >	
mln::hexa< I >	758

mln::internal::image_base< I::value, box< I::site >, extended< I > >	
image_morpher< I, I::value, box< I::site >, extended< I > >	
image_domain_morpher< I, box< I::site >, extended< I > >	
mln::extended< I >	657
mln::internal::image_base< I::value, D, unproject_image< I, D, F > >	
image_morpher< I, I::value, D, unproject_image< I, D, F > >	
image_domain_morpher< I, D, unproject_image< I, D, F > >	
mln::unproject_image< I, D, F >	1033
mln::internal::image_base< I::value, I::domain_t, decorated_image< I, D > >	
image_morpher< I, I::value, I::domain_t, decorated_image< I, D > >	
image_identity< I, I::domain_t, decorated_image< I, D > >	
mln::decorated_image< I, D >	596
mln::internal::image_base< I::value, I::domain_t, extension_fun< I, F > >	
image_morpher< I, I::value, I::domain_t, extension_fun< I, F > >	
image_identity< I, I::domain_t, extension_fun< I, F > >	
mln::extension_fun< I, F >	659
mln::internal::image_base< I::value, I::domain_t, extension_ima< I, J > >	
image_morpher< I, I::value, I::domain_t, extension_ima< I, J > >	
image_identity< I, I::domain_t, extension_ima< I, J > >	
mln::extension_ima< I, J >	661
mln::internal::image_base< I::value, I::domain_t, extension_val< I > >	
image_morpher< I, I::value, I::domain_t, extension_val< I > >	
image_identity< I, I::domain_t, extension_val< I > >	
mln::extension_val< I >	664
mln::internal::image_base< I::value, I::domain_t, interpolated< I, F > >	
image_morpher< I, I::value, I::domain_t, interpolated< I, F > >	
image_identity< I, I::domain_t, interpolated< I, F > >	
mln::interpolated< I, F >	784
mln::internal::image_base< I::value, I::domain_t, p2p_image< I, F > >	
image_morpher< I, I::value, I::domain_t, p2p_image< I, F > >	
image_domain_morpher< I, I::domain_t, p2p_image< I, F > >	
mln::p2p_image< I, F >	845
mln::internal::image_base< I::value, I::domain_t, plain< I > >	
image_morpher< I, I::value, I::domain_t, plain< I > >	
image_identity< I, I::domain_t, plain< I > >	
mln::plain< I >	942
mln::internal::image_base< I::value, I::domain_t, safe_image< I > >	
image_morpher< I, I::value, I::domain_t, safe_image< I > >	
image_identity< I, I::domain_t, safe_image< I > >	
mln::safe_image< I >	961
mln::internal::image_base< I::value, p_if< I::domain_t, F >, image_if< I, F > >	
image_morpher< I, I::value, p_if< I::domain_t, F >, image_if< I, F > >	
image_domain_morpher< I, p_if< I::domain_t, F >, image_if< I, F > >	
mln::image_if< I, F >	782
mln::internal::image_base< I::value, p_if< S, fun::p2b::has< I > >, sub_image_if< I, S > >	
image_morpher< I, I::value, p_if< S, fun::p2b::has< I > >, sub_image_if< I, S > >	
image_domain_morpher< I, p_if< S, fun::p2b::has< I > >, sub_image_if< I, S > >	
mln::sub_image_if< I, S >	973
mln::internal::image_base< I::value, S, E >	
image_morpher< I, I::value, S, E >	
mln::internal::image_base< I::value, S, sub_image< I, S > >	
image_morpher< I, I::value, S, sub_image< I, S > >	
image_domain_morpher< I, S, sub_image< I, S > >	
mln::sub_image< I, S >	972

mln::value::Integer< int_u< n > >	1125
mln::value::int_u< n >	1121
mln::value::Integer< int_u_sat< n > >	1125
mln::value::int_u_sat< n >	1123
mln::value::Integer< object_id< Tag, V > >	1125
mln::util::object_id< Tag, V >	1075
mln::internal::is_masked_impl_selector< S, W::mask_t::domain_t, graph_window_if_piter< S, W, I > >	
mln::graph_window_if_piter< S, W, I >	753
mln::algebra::h_mat< d, T >	544
mln::algebra::h_vec< d, C >	546
mln::canvas::chamfer< F >	583
mln::category< R(*)(A) >	583
mln::Delta_Point_Site< void >	599
mln::doc::Accumulator< E >	599
mln::doc::Generalized_Pixel< E >	614
mln::doc::Pixel_Iterator< E >	625
mln::doc::Object< E >	625
mln::doc::Dpoint< E >	604
mln::doc::Image< E >	616
mln::doc::Fastest_Image< E >	606
mln::doc::Iterator< E >	622
mln::doc::Pixel_Iterator< E >	625
mln::doc::Site_Iterator< E >	631
mln::doc::Value_Iterator< E >	635
mln::doc::Neighborhood< E >	623
mln::doc::Site_Set< E >	633
mln::doc::Box< E >	601
mln::doc::Value_Set< E >	636
mln::doc::Weighted_Window< E >	639
mln::doc::Window< E >	641
mln::doc::Point_Site< E >	628
mln::Edge< E >	655
mln::fun::from_accu< A >	671
mln::fun::internal::ch_function_value_Impl< F, V >	
mln::fun::v2v::ch_function_value< F, V >	677
mln::fun::x2p::closest_point< P >	702
mln::fun::x2x::composed< T2, T1 >	704
mln::Function< void >	715
mln::Gdpoint< void >	724
mln::Generalized_Pixel< E >	
mln::Pixel_Iterator< E >	940
mln::internal::pixel_iterator_base_	
mln::geom::complex_geometry< D, P >	725
mln::graph::attribute::card_t	732
mln::graph::attribute::representative_t	732
mln::histo::array< T >	762
mln::internal::image_base< T, S, E >	
mln::internal::neighborhood_base< W, E >	
mln::internal::neighb_base	
mln::neighb< graph_elt_mixed_window< G, S, S2 > >	842
mln::graph_elt_mixed_neighborhood< G, S, S2 >	733

mln::neighb< graph_elt_window< G, S > >	842
mln::graph_elt_neighborhood< G, S >	738
mln::neighb< graph_elt_window_if< G, S, I > >	842
mln::graph_elt_neighborhood_if< G, S, I >	740
mln::internal::pixel_impl_< I, E >	
mln::internal::pixel_iterator_base_	
mln::io::dicom::dicom_header	786
mln::io::dump::dump_header	786
mln::io::fld::fld_header	787
mln::io::raw::raw_header	787
mln::metal::ands< E1, E2, E3, E4, E5, E6, E7, E8 >	828
mln::metal::bool_< false >	
mln::metal::equal< T1::coord, T2::coord >	828
mln::metal::equal< T1::point, T2::point >	828
mln::metal::equal< T1, T2 >	828
mln::metal::converts_to< T, U >	828
mln::metal::goes_to< T, U >	829
mln::metal::is< T, U >	829
mln::metal::is_a< T, M >	830
mln::metal::is_not< T, U >	830
mln::metal::is_not_a< T, M >	830
mln::Neighborhood< void >	844
mln::Object< E >	844
mln::Browsing< E >	568
mln::Delta_Point_Site	
mln::Dpoint< E >	643
mln::Function< E >	715
mln::Function_n2v< E >	716
mln::Function_v2v< E >	717
mln::fun::x2v::bilinear< I >	703
mln::fun::x2v::trilinear< I >	704
mln::fun::x2x::linear< I >	705
mln::Function_v2b< E >	716
mln::Function_vv2b< E >	718
mln::Function_vv2v< E >	718
mln::Gdpoint< E >	723
mln::Graph< E >	731
mln::Image< E >	762
mln::Iterator< E >	787
mln::Pixel_Iterator< E >	940
mln::topo::internal::complex_iterator_base	
mln::topo::internal::complex_relative_iterator_base	
mln::Value_Iterator< E >	1146
mln::Literal< E >	799
mln::Mesh< E >	823
mln::Regular_Grid< E >	960
mln::Meta_Accumulator< E >	824
mln::Meta_Function< E >	826
mln::Meta_Function_v2v< E >	827
mln::Meta_Function_vv2v< E >	827
mln::Neighborhood< E >	844
mln::Point_Site< E >	953
mln::Proxy< E >	957

mln::Accumulator< E >	542
mln::accu::internal::base	
couple< accu::shape::bbox< P >, accu::math::count< P >, float, rectangularity< P > >	
mln::accu::site_set::rectangularity< P >	509
mln::accu::pair< min< V >, max< V > >	499
mln::accu::stat::min_max< V >	527
mln::Site_Proxy< E >	965
mln::Pseudo_Site< E >	957
mln::Site_Iterator< E >	963
mln::internal::site_iterator_base	
mln::internal::site_set_iterator_base	
mln::p_transformed_piter< Pi, S, F >	927
mln::Site< E >	962
mln::Gpoint< E >	726
mln::Site_Set< E >	966
mln::Box< E >	560
mln::Value< E >	1107
mln::Value_Set< E >	1148
mln::Weighted_Window< E >	1158
mln::Window< E >	1170
mln::graph_window_base< P, E >	751
mln::internal::window_base	
mln::Point_Site< void >	956
mln::Proxy< void >	957
mln::Pseudo_Site< void >	958
mln::registration::closest_point_basic< P >	959
mln::registration::closest_point_with_map< P >	960
mln::select::p_of< P >	961
mln::Site< void >	963
mln::Site_Proxy< void >	966
mln::Site_Set< void >	969
mln::thru_image< I, F >	975
mln::topo::complex< D >	1004
mln::topo::face< D >	1007
mln::topo::algebraic_face< D >	991
mln::topo::is_simple_2d_t< N >	1015
mln::topo::n_face< N, D >	1019
mln::topo::algebraic_n_face< N, D >	996
mln::topo::n_faces_set< N, D >	1026
mln::topo::skeleton::is_simple_point< N >	1027
mln::util::adjacency_matrix< V >	1035
mln::util::array< T >	1036
mln::util::branch< T >	1043
mln::util::branch_iter< T >	1044
mln::util::branch_iter_ind< T >	1046
mln::util::greater_point< I >	1065
mln::util::greater_psite< I >	1066
mln::util::head< T, R >	1066
mln::util::ilcell< T >	1067
mln::util::internal::edge_impl< G >	
mln::util::edge< G >	1050

mln::util::internal::vertex_impl_< G >	
mln::util::vertex< G >	1102
mln::util::node< T, R >	1075
mln::util::ord< T >	1077
mln::util::pix< I >	1080
mln::util::tracked_ptr< T >	1093
mln::util::tree< T >	1095
mln::util::tree_node< T >	1097
mln::value::float01	1109
mln::value::Integer< E >	1125
mln::value::Integer< void >	1126
mln::value::internal::value_like_< V, C, N, E >	
mln::value::float01_f	1111
mln::value::graylevel< n >	1112
mln::value::graylevel_f	1116
mln::value::int_s< n >	1118
mln::value::int_u< n >	1121
mln::value::int_u_sat< n >	1123
mln::value::label< n >	1126
mln::value::qt::rgb32	1135
mln::value::rgb< n >	1137
mln::value::set< T >	1139
mln::value::sign	1140
mln::value::super_value< sign >	1145
mln::value::value_array< T, V >	1145
mln::Vertex< E >	1149
mln::internal::neighborhood_base< W, mixed_neighb< W > >	
neighb_base< W, mixed_neighb< W > >	
mln::mixed_neighb< W >	830
mln::internal::neighborhood_base< W, neighb< W > >	
neighb_base< W, neighb< W > >	
mln::neighb< W >	842
mln::Object< abs >	844
mln::Meta_Function< abs >	826
mln::Meta_Function_v2v< abs >	827
mln::Object< abs < V > >	844
mln::Function< abs < V > >	715
mln::Function_v2v< abs < V > >	717
mln::Object< accu_result >	844
mln::Meta_Function< accu_result >	826
mln::Meta_Function_v2v< accu_result >	827
mln::Object< adj_higher_dim_connected_n_face_bkd_iter< D > >	844
mln::Iterator< adj_higher_dim_connected_n_face_bkd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_higher_dim_connected_n_face_bkd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_bkd_iter< D > >	
backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_bkd_iter< D > >	
mln::topo::adj_higher_dim_connected_n_face_bkd_iter< D >	977
mln::Object< adj_higher_dim_connected_n_face_fwd_iter< D > >	844
mln::Iterator< adj_higher_dim_connected_n_face_fwd_iter< D > >	787

complex_iterator_base< algebraic_face< D >, adj_higher_dim_connected_n_face_fwd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_fwd_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_fwd_iter< D > >	
mln::topo::adj_higher_dim_connected_n_face_fwd_iter< D >	978
mln::Object< adj_higher_face_bkd_iter< D > >	844
mln::Iterator< adj_higher_face_bkd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_higher_face_bkd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_bkd_iter< D > >	
backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_bkd_iter< D > >	
mln::topo::adj_higher_face_bkd_iter< D >	979
mln::Object< adj_higher_face_fwd_iter< D > >	844
mln::Iterator< adj_higher_face_fwd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_higher_face_fwd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_fwd_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_fwd_iter< D > >	
mln::topo::adj_higher_face_fwd_iter< D >	980
mln::Object< adj_lower_dim_connected_n_face_bkd_iter< D > >	844
mln::Iterator< adj_lower_dim_connected_n_face_bkd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_lower_dim_connected_n_face_bkd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_bkd_iter< D > >	
backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_bkd_iter< D > >	
mln::topo::adj_lower_dim_connected_n_face_bkd_iter< D >	981
mln::Object< adj_lower_dim_connected_n_face_fwd_iter< D > >	844
mln::Iterator< adj_lower_dim_connected_n_face_fwd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_lower_dim_connected_n_face_fwd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_fwd_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_fwd_iter< D > >	
mln::topo::adj_lower_dim_connected_n_face_fwd_iter< D >	982
mln::Object< adj_lower_face_bkd_iter< D > >	844
mln::Iterator< adj_lower_face_bkd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_lower_face_bkd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_bkd_iter< D > >	
backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_bkd_iter< D > >	
mln::topo::adj_lower_face_bkd_iter< D >	984
mln::Object< adj_lower_face_fwd_iter< D > >	844
mln::Iterator< adj_lower_face_fwd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_lower_face_fwd_iter< D > >	

complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_fwd_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_fwd_iter< D > >	
mln::topo::adj_lower_face_fwd_iter< D >	985
mln::Object< adj_lower_higher_face_bkd_iter< D > >	844
mln::Iterator< adj_lower_higher_face_bkd_iter< D > >	787
complex_relative_iterator_sequence< adj_higher_face_bkd_iter< D >, adj_lower_face_bkd_iter< D >, adj_lower_higher_face_bkd_iter< D > >	
mln::topo::adj_lower_higher_face_bkd_iter< D >	986
mln::Object< adj_lower_higher_face_fwd_iter< D > >	844
mln::Iterator< adj_lower_higher_face_fwd_iter< D > >	787
complex_relative_iterator_sequence< adj_lower_face_fwd_iter< D >, adj_higher_face_fwd_iter< D >, adj_lower_higher_face_fwd_iter< D > >	
mln::topo::adj_lower_higher_face_fwd_iter< D >	987
mln::Object< adj_m_face_bkd_iter< D > >	844
mln::Iterator< adj_m_face_bkd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_m_face_bkd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_bkd_iter< D > >	
backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_bkd_iter< D > >	
mln::topo::adj_m_face_bkd_iter< D >	988
mln::Object< adj_m_face_fwd_iter< D > >	844
mln::Iterator< adj_m_face_fwd_iter< D > >	787
complex_iterator_base< algebraic_face< D >, adj_m_face_fwd_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_fwd_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_fwd_iter< D > >	
mln::topo::adj_m_face_fwd_iter< D >	989
mln::Object< all_to< T > >	844
mln::Function< all_to< T > >	715
mln::Function_v2v< all_to< T > >	717
mln::Object< antilogy >	844
mln::Function< antilogy >	715
mln::Function_v2v< antilogy >	717
mln::Function_v2b< antilogy >	716
mln::fun::p2b::antilogy	672
mln::Object< array1d< T, Size > >	844
mln::Object< array2d< T, r, c > >	844
mln::Object< array3d< T, s, r, c > >	844
mln::Object< array_bkd_iter< T > >	844
mln::Proxy< array_bkd_iter< T > >	957
mln::Object< array_fwd_iter< T > >	844
mln::Proxy< array_fwd_iter< T > >	957
mln::Object< asc_propagation >	844
mln::Object< backdiag2d >	844
mln::Window< backdiag2d >	1170
window_base< dpoint2d, backdiag2d >	

classical_window_base< dpoint2d, backdiag2d >	1159
mln::win::backdiag2d	844
mln::Object< backdiagonal2d_t >	568
mln::Browsing< backdiagonal2d_t >	569
mln::canvas::browsing::backdiagonal2d_t	569
mln::Object< ball< G, C > >	844
mln::Window< ball< G, C > >	1170
window_base< dpoint< G, C >, ball< G, C > >	
classical_window_base< dpoint< G, C >, ball< G, C > >	
mln::win::ball< G, C >	1160
mln::Object< bbox >	844
mln::Meta_Accumulator< bbox >	824
mln::accu::meta::shape::bbox	482
mln::Object< bbox< P > >	844
mln::Proxy< bbox< P > >	957
mln::Accumulator< bbox< P > >	542
base< const box< P > &, bbox< P > >	
mln::accu::shape::bbox< P >	504
mln::Object< big_chess< B > >	844
mln::Function< big_chess< B > >	715
mln::Function_v2v< big_chess< B > >	717
mln::Function_v2b< big_chess< B > >	716
mln::Object< bin_off_loader >	844
mln::Object< bin_off_saver >	844
mln::Object< binary< Fun, T1, T2 > >	844
mln::Function< binary< Fun, T1, T2 > >	715
mln::Function_v2v< binary< Fun, T1, T2 > >	717
mln::Object< bkd_pixter1d< I > >	844
mln::Iterator< bkd_pixter1d< I > >	787
mln::Pixel_Iterator< bkd_pixter1d< I > >	940
mln::Object< bkd_pixter2d< I > >	844
mln::Iterator< bkd_pixter2d< I > >	787
mln::Pixel_Iterator< bkd_pixter2d< I > >	940
mln::Object< bkd_pixter3d< I > >	844
mln::Iterator< bkd_pixter3d< I > >	787
mln::Pixel_Iterator< bkd_pixter3d< I > >	940
mln::Object< black_t >	844
mln::Literal< black_t >	799
mln::literal::black_t	801
mln::Object< blue >	844
mln::Meta_Function< blue >	826
mln::Meta_Function_v2v< blue >	827
mln::Object< blue_t >	844
mln::Literal< blue_t >	799
mln::literal::blue_t	802
mln::Object< box< P > >	844
mln::Site_Set< box< P > >	966
mln::Box< box< P > >	560

mln::box< P >	552
mln::Object< box_runend_piter< P > >	844
mln::Proxy< box_runend_piter< P > >	957
mln::Site_Proxy< box_runend_piter< P > >	965
mln::Site_Iterator< box_runend_piter< P > >	963
site_iterator_base< box< P >, box_runend_piter< P > >	
site_set_iterator_base< box< P >, box_runend_piter< P > >	
mln::box_runend_piter< P >	566
mln::Object< box_runstart_piter< P > >	844
mln::Proxy< box_runstart_piter< P > >	957
mln::Site_Proxy< box_runstart_piter< P > >	965
mln::Site_Iterator< box_runstart_piter< P > >	963
site_iterator_base< box< P >, box_runstart_piter< P > >	
site_set_iterator_base< box< P >, box_runstart_piter< P > >	
mln::box_runstart_piter< P >	567
mln::Object< breadth_first_search_t >	844
mln::Browsing< breadth_first_search_t >	568
graph_first_search_t< breadth_first_search_t, std::queue >	
mln::canvas::browsing::breadth_first_search_t	571
mln::Object< brown_t >	844
mln::Literal< brown_t >	799
mln::literal::brown_t	802
mln::Object< card< I > >	844
mln::Proxy< card< I > >	957
mln::Accumulator< card< I > >	542
base< unsigned, card< I > >	
mln::morpho::attribute::card< I >	832
mln::Object< cast< V > >	844
mln::Function< cast< V > >	715
mln::Function_v2v< cast< V > >	717
mln::Object< center >	844
mln::Meta_Accumulator< center >	824
mln::accu::meta::center	463
mln::Object< center< P, V > >	844
mln::Proxy< center< P, V > >	957
mln::Accumulator< center< P, V > >	542
base< V, center< P, V > >	
mln::accu::center< P, V >	437
mln::Object< center_only_iter< D > >	844
mln::Iterator< center_only_iter< D > >	787
complex_iterator_base< algebraic_face< D >, center_only_iter< D > >	
complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, center_only_iter< D > >	
forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, center_only_iter< D > >	
mln::topo::center_only_iter< D >	1001
mln::Object< centered_bkd_iter_adapter< D, I > >	844
mln::Iterator< centered_bkd_iter_adapter< D, I > >	787
complex_relative_iterator_sequence< I, center_only_iter< D >, centered_bkd_iter_adapter< D, I > >	

mln::topo::centered_bkd_iter_adapter< D, I >	1002
mln::Object< centered_fwd_iter_adapter< D, I > >	844
mln::Iterator< centered_fwd_iter_adapter< D, I > >	787
complex_relative_iterator_sequence< center_only_iter< D >, I, centered_fwd_iter_adapter< D, I > >	
mln::topo::centered_fwd_iter_adapter< D, I >	1003
mln::Object< ch_function_value< F, V > >	844
mln::Function< ch_function_value< F, V > >	715
mln::Function_v2v< ch_function_value< F, V > >	717
mln::fun::v2v::ch_function_value< F, V >	677
mln::Object< ch_piter_image< I, Fwd > >	844
mln::Image< ch_piter_image< I, Fwd > >	762
mln::Object< chess >	844
mln::Function< chess >	715
mln::Function_v2v< chess >	717
mln::Function_v2b< chess >	716
mln::Object< col >	844
mln::Meta_Function< col >	826
mln::Meta_Function_v2v< col >	827
mln::Object< colorize >	844
mln::Function< colorize >	715
mln::Function_v2v< colorize >	717
mln::Object< comp >	844
mln::Meta_Function< comp >	826
mln::Meta_Function_v2v< comp >	827
mln::Object< comp_count >	844
mln::Meta_Function< comp_count >	826
mln::Meta_Function_v2v< comp_count >	827
mln::Object< complex_image< D, G, V > >	844
mln::Image< complex_image< D, G, V > >	762
mln::Object< complex_neighborhood_bkd_piter< I, G, N > >	844
mln::Proxy< complex_neighborhood_bkd_piter< I, G, N > >	957
mln::Site_Proxy< complex_neighborhood_bkd_piter< I, G, N > >	965
mln::Site_Iterator< complex_neighborhood_bkd_piter< I, G, N > >	963
site_iterator_base< N, complex_neighborhood_bkd_piter< I, G, N > >	
site_relative_iterator_base< N, complex_neighborhood_bkd_piter< I, G, N > >	
mln::complex_neighborhood_bkd_piter< I, G, N >	587
mln::Object< complex_neighborhood_fwd_piter< I, G, N > >	844
mln::Proxy< complex_neighborhood_fwd_piter< I, G, N > >	957
mln::Site_Proxy< complex_neighborhood_fwd_piter< I, G, N > >	965
mln::Site_Iterator< complex_neighborhood_fwd_piter< I, G, N > >	963
site_iterator_base< N, complex_neighborhood_fwd_piter< I, G, N > >	
site_relative_iterator_base< N, complex_neighborhood_fwd_piter< I, G, N > >	
mln::complex_neighborhood_fwd_piter< I, G, N >	588
mln::Object< complex_psite< D, G > >	844
mln::Proxy< complex_psite< D, G > >	957
mln::Site_Proxy< complex_psite< D, G > >	965
mln::Pseudo_Site< complex_psite< D, G > >	957
pseudo_site_base_< const G::site &, complex_psite< D, G > >	

mln::complex_psite< D, G >	590
mln::Object< complex_window_bkd_piter< I, G, W > >	844
mln::Proxy< complex_window_bkd_piter< I, G, W > >	957
mln::Site_Proxy< complex_window_bkd_piter< I, G, W > >	965
mln::Site_Iterator< complex_window_bkd_piter< I, G, W > >	963
site_iterator_base< W, complex_window_bkd_piter< I, G, W > >	
site_relative_iterator_base< W, complex_window_bkd_piter< I, G, W > >	
mln::complex_window_bkd_piter< I, G, W >	593
mln::Object< complex_window_fwd_piter< I, G, W > >	844
mln::Proxy< complex_window_fwd_piter< I, G, W > >	957
mln::Site_Proxy< complex_window_fwd_piter< I, G, W > >	965
mln::Site_Iterator< complex_window_fwd_piter< I, G, W > >	963
site_iterator_base< W, complex_window_fwd_piter< I, G, W > >	
site_relative_iterator_base< W, complex_window_fwd_piter< I, G, W > >	
mln::complex_window_fwd_piter< I, G, W >	595
mln::Object< component< T, i > >	844
mln::Function< component< T, i > >	715
mln::Function_v2v< component< T, i > >	717
mln::fun::v2v::component< T, i >	678
mln::Object< compose >	844
mln::Meta_Function< compose >	826
mln::Meta_Function_vv2v< compose >	827
mln::Object< composition< mln::Meta_Function_v2v, F, mln::Meta_Function_v2v, G > > . .	844
mln::Meta_Function< composition< mln::Meta_Function_v2v, F, mln::Meta_Function_v2v,	
G > >	826
mln::Meta_Function_v2v< composition< mln::Meta_Function_v2v, F, mln::Meta_-	
Function_v2v, G > >	827
mln::Object< composition< mln::Meta_Function_v2v, F, mln::Meta_Function_vv2v, G > > . .	844
mln::Meta_Function< composition< mln::Meta_Function_v2v, F, mln::Meta_Function_-	
vv2v, G > >	826
mln::Meta_Function_vv2v< composition< mln::Meta_Function_v2v, F, mln::Meta_-	
Function_vv2v, G > >	827
mln::Object< concrete >	844
mln::Object< convert< V > >	844
mln::Function< convert< V > >	715
mln::Function_v2v< convert< V > >	717
mln::Object< convolve< T1, T2, R > >	844
mln::Proxy< convolve< T1, T2, R > >	957
mln::Accumulator< convolve< T1, T2, R > >	542
base< R, convolve< T1, T2, R > >	
mln::accu::convolve< T1, T2, R >	439
mln::Object< cos >	844
mln::Meta_Function< cos >	826
mln::Meta_Function_v2v< cos >	827
mln::Object< cos< V > >	844
mln::Function< cos< V > >	715
mln::Function_v2v< cos< V > >	717
mln::fun::v2w2v::cos< V >	684
mln::Object< count >	844

mln::Meta_Accumulator< count >	824
mln::accu::meta::math::count	473
mln::Object< count< T > >	844
mln::Proxy< count< T > >	957
mln::Accumulator< count< T > >	542
base< unsigned, count< T > >	
mln::accu::math::count< T >	455
mln::Object< count_adjacent_vertices >	844
mln::Meta_Accumulator< count_adjacent_vertices >	824
mln::accu::meta::count_adjacent_vertices	463
mln::Object< count_adjacent_vertices< F, S > >	844
mln::Proxy< count_adjacent_vertices< F, S > >	957
mln::Accumulator< count_adjacent_vertices< F, S > >	542
base< unsigned, count_adjacent_vertices< F, S > >	
mln::accu::count_adjacent_vertices< F, S >	440
mln::Object< count_adjacent_vertices< I > >	844
mln::Proxy< count_adjacent_vertices< I > >	957
mln::Accumulator< count_adjacent_vertices< I > >	542
base< unsigned, count_adjacent_vertices< I > >	
mln::morpho::attribute::count_adjacent_vertices< I >	833
mln::Object< count_labels >	844
mln::Meta_Accumulator< count_labels >	824
mln::accu::meta::count_labels	464
mln::Object< count_labels< L > >	844
mln::Proxy< count_labels< L > >	957
mln::Accumulator< count_labels< L > >	542
base< unsigned, count_labels< L > >	
mln::accu::count_labels< L >	442
mln::Object< count_value >	844
mln::Meta_Accumulator< count_value >	824
mln::accu::meta::count_value	465
mln::Object< count_value< V > >	844
mln::Proxy< count_value< V > >	957
mln::Accumulator< count_value< V > >	542
base< unsigned, count_value< V > >	
mln::accu::count_value< V >	443
mln::Object< couple< T, U > >	844
mln::util::couple< T, U >	1047
mln::Object< cube >	844
mln::Mesh< cube >	823
mln::Regular_Grid< cube >	960
mln::Object< cube3d >	844
mln::Window< cube3d >	1170
window_base< dpoint3d, cube3d >	
classical_window_base< dpoint3d, cube3d >	
mln::win::cube3d	1161
mln::Object< cuboid3d >	844
mln::Window< cuboid3d >	1170
window_base< dpoint3d, cuboid3d >	

classical_window_base< dpoint3d, cuboid3d >	
mln::win::cuboid3d	1162
mln::Object< cyan_t >	844
mln::Literal< cyan_t >	799
mln::literal::cyan_t	803
mln::Object< d_t >	844
mln::Function< d_t >	715
mln::Function_vv2v< d_t >	718
mln::Object< dark_gray_t >	844
mln::Literal< dark_gray_t >	799
mln::Object< dashed_line_f< I, dim > >	844
mln::Function< dashed_line_f< I, dim > >	715
mln::Function_v2v< dashed_line_f< I, dim > >	717
mln::Function_v2b< dashed_line_f< I, dim > >	716
mln::Object< decorated_image< I, D > >	844
mln::Image< decorated_image< I, D > >	762
mln::Object< depth1st_piter< T > >	844
mln::Proxy< depth1st_piter< T > >	957
mln::Site_Proxy< depth1st_piter< T > >	965
mln::Site_Iterator< depth1st_piter< T > >	963
mln::Object< depth_first_search_t >	844
mln::Browsing< depth_first_search_t >	568
graph_first_search_t< depth_first_search_t, std::stack >	
mln::canvas::browsing::depth_first_search_t	571
mln::Object< desc_propagation >	844
mln::Object< deviation >	844
mln::Meta_Accumulator< deviation >	824
mln::accu::stat::meta::deviation	523
mln::Object< deviation< T, S, M > >	844
mln::Proxy< deviation< T, S, M > >	957
mln::Accumulator< deviation< T, S, M > >	542
base< M, deviation< T, S, M > >	
mln::accu::stat::deviation< T, S, M >	511
mln::Object< diag2d >	844
mln::Window< diag2d >	1170
window_base< dpoint2d, diag2d >	
classical_window_base< dpoint2d, diag2d >	
mln::win::diag2d	1164
mln::Object< diagonal2d_t >	844
mln::Browsing< diagonal2d_t >	568
mln::canvas::browsing::diagonal2d_t	571
mln::Object< diff_abs< V > >	844
mln::Function< diff_abs< V > >	715
mln::Function_vv2v< diff_abs< V > >	718
mln::fun::vv2v::diff_abs< V >	694
mln::Object< dir_struct_elt_incr_update_t >	844
mln::Browsing< dir_struct_elt_incr_update_t >	568
mln::canvas::browsing::dir_struct_elt_incr_update_t	573

mln::Object< directional_t >	844
mln::Browsing< directional_t >	568
mln::canvas::browsing::directional_t	574
mln::Object< dist >	844
mln::Function< dist >	715
mln::Function_vv2v< dist >	718
mln::Object< dist_t >	844
mln::Function< dist_t >	715
mln::Function_vv2v< dist_t >	718
mln::Object< dn_leaf_piter< T > >	844
mln::Proxy< dn_leaf_piter< T > >	957
mln::Site_Proxy< dn_leaf_piter< T > >	965
mln::Site_Iterator< dn_leaf_piter< T > >	963
mln::Object< dn_node_piter< T > >	844
mln::Proxy< dn_node_piter< T > >	957
mln::Site_Proxy< dn_node_piter< T > >	965
mln::Site_Iterator< dn_node_piter< T > >	963
mln::Object< dn_site_piter< T > >	844
mln::Proxy< dn_site_piter< T > >	957
mln::Site_Proxy< dn_site_piter< T > >	965
mln::Site_Iterator< dn_site_piter< T > >	963
mln::Object< dpoint< G, C > >	844
mln::Gdpoint< dpoint< G, C > >	723
mln::dpoint< G, C >	644
mln::Object< dpoints_bkd_pixter< I > >	844
mln::Iterator< dpoints_bkd_pixter< I > >	787
mln::Pixel_Iterator< dpoints_bkd_pixter< I > >	940
mln::Object< dpoints_fwd_pixter< I > >	844
mln::Iterator< dpoints_fwd_pixter< I > >	787
mln::Pixel_Iterator< dpoints_fwd_pixter< I > >	940
mln::Object< dpsites_bkd_piter< V > >	844
mln::Proxy< dpsites_bkd_piter< V > >	957
mln::Site_Proxy< dpsites_bkd_piter< V > >	965
mln::Site_Iterator< dpsites_bkd_piter< V > >	963
mln::Object< dpsites_fwd_piter< V > >	844
mln::Proxy< dpsites_fwd_piter< V > >	957
mln::Site_Proxy< dpsites_fwd_piter< V > >	965
mln::Site_Iterator< dpsites_fwd_piter< V > >	963
mln::Object< eat >	844
mln::util::eat	1049
mln::Object< edge_bkd_iterator< G > >	844
mln::Proxy< edge_bkd_iterator< G > >	957
mln::Object< edge_fwd_iterator< G > >	844
mln::Proxy< edge_fwd_iterator< G > >	957
mln::Object< edge_image< P, V, G > >	844
mln::Image< edge_image< P, V, G > >	762
mln::Object< edge_nbh_edge_bkd_iterator< G > >	844
mln::Proxy< edge_nbh_edge_bkd_iterator< G > >	957

mln::Object< edge_nbh_edge_fwd_iterator< G > >	844
mln::Proxy< edge_nbh_edge_fwd_iterator< G > >	957
mln::Object< edge_to_color< I, V > >	844
mln::Function< edge_to_color< I, V > >	715
mln::Function_v2v< edge_to_color< I, V > >	717
mln::Object< enc< V > >	844
mln::Function< enc< V > >	715
mln::Function_v2v< enc< V > >	717
mln::Object< eq< L, R > >	844
mln::Function< eq< L, R > >	715
mln::Function_vv2b< eq< L, R > >	718
mln::fun::vv2b::eq< L, R >	689
mln::Object< extended< I > >	844
mln::Image< extended< I > >	762
mln::Object< extension_fun< I, F > >	844
mln::Image< extension_fun< I, F > >	762
mln::Object< extension_ima< I, J > >	844
mln::Image< extension_ima< I, J > >	762
mln::Object< extension_val< I > >	844
mln::Image< extension_val< I > >	762
mln::Object< f_16_to_8 >	844
mln::Function< f_16_to_8 >	715
mln::Function_v2v< f_16_to_8 >	717
mln::Object< f_box1d_t >	844
mln::Function< f_box1d_t >	715
mln::Function_v2v< f_box1d_t >	717
mln::Function_v2b< f_box1d_t >	716
mln::Object< f_box2d_t >	844
mln::Function< f_box2d_t >	715
mln::Function_v2v< f_box2d_t >	717
mln::Function_v2b< f_box2d_t >	716
mln::Object< f_box3d_t >	844
mln::Function< f_box3d_t >	715
mln::Function_v2v< f_box3d_t >	717
mln::Function_v2b< f_box3d_t >	716
mln::Object< f_hsi_to_rgb_< T_rgb > >	844
mln::Function< f_hsi_to_rgb_< T_rgb > >	715
mln::Function_v2v< f_hsi_to_rgb_< T_rgb > >	717
mln::Object< f_hsl_to_rgb_< T_rgb > >	844
mln::Function< f_hsl_to_rgb_< T_rgb > >	715
mln::Function_v2v< f_hsl_to_rgb_< T_rgb > >	717
mln::Object< f_rgb_to_hsi_< T_hsi > >	844
mln::Function< f_rgb_to_hsi_< T_hsi > >	715
mln::Function_v2v< f_rgb_to_hsi_< T_hsi > >	717
mln::Object< f_rgb_to_hsl_< T_hsl > >	844
mln::Function< f_rgb_to_hsl_< T_hsl > >	715
mln::Function_v2v< f_rgb_to_hsl_< T_hsl > >	717
mln::Object< face_bkd_iter< D > >	844

mln::Iterator< face_bkd_iter< D > >	787
complex_iterator_base< topo::face< D >, face_bkd_iter< D > >	
complex_set_iterator_base< topo::face< D >, face_bkd_iter< D > >	
mln::topo::face_bkd_iter< D >	1012
mln::Object< face_fwd_iter< D > >	844
mln::Iterator< face_fwd_iter< D > >	787
complex_iterator_base< topo::face< D >, face_fwd_iter< D > >	
complex_set_iterator_base< topo::face< D >, face_fwd_iter< D > >	
mln::topo::face_fwd_iter< D >	1013
mln::Object< faces_psites< N, D, P > >	844
mln::Proxy< faces_psites< N, D, P > >	957
mln::Site_Proxy< faces_psites< N, D, P > >	965
mln::Pseudo_Site< faces_psites< N, D, P > >	957
pseudo_site_base< const P &, faces_psites< N, D, P > >	
mln::faces_psites< N, D, P >	666
mln::Object< fibonacci_heap< P, T > >	844
mln::util::fibonacci_heap< P, T >	1054
mln::Object< flat_image< T, S > >	844
mln::Image< flat_image< T, S > >	762
mln::Object< float01 >	844
mln::Value< float01 >	1107
mln::Object< float01_f >	844
mln::Value< float01_f >	1107
mln::Object< float_off_loader >	844
mln::Object< float_off_saver >	844
mln::Object< fold< P, dir_0, dir_1, dir_2 > >	844
mln::Function< fold< P, dir_0, dir_1, dir_2 > >	715
mln::Function_v2v< fold< P, dir_0, dir_1, dir_2 > >	717
mln::Object< from_accu< A > >	844
mln::Meta_Function< from_accu< A > >	826
mln::Meta_Function_v2v< from_accu< A > >	827
mln::Object< fun_image< F, I > >	844
mln::Image< fun_image< F, I > >	762
mln::Object< function< meta::blue< value::rgb< n > > >	844
mln::Function< function< meta::blue< value::rgb< n > > >	715
mln::Function_v2v< function< meta::blue< value::rgb< n > > >	717
mln::Object< function< meta::first< util::couple< T, U > > >	844
mln::Function< function< meta::first< util::couple< T, U > > >	715
mln::Function_v2v< function< meta::first< util::couple< T, U > > >	717
mln::Object< function< meta::green< value::rgb< n > > >	844
mln::Function< function< meta::green< value::rgb< n > > >	715
mln::Function_v2v< function< meta::green< value::rgb< n > > >	717
mln::Object< function< meta::red< value::rgb< n > > >	844
mln::Function< function< meta::red< value::rgb< n > > >	715
mln::Function_v2v< function< meta::red< value::rgb< n > > >	717
mln::Object< function< meta::second< util::couple< T, U > > >	844
mln::Function< function< meta::second< util::couple< T, U > > >	715
mln::Function_v2v< function< meta::second< util::couple< T, U > > >	717

mln::Object< function< meta::to_enc< T > >	844
mln::Function< function< meta::to_enc< T > >>	715
mln::Function_v2v< function< meta::to_enc< T > >>	717
mln::Object< fwd_pixter1d< I > >	844
mln::Iterator< fwd_pixter1d< I > >	787
mln::Pixel_Iterator< fwd_pixter1d< I > >	940
mln::Object< fwd_pixter2d< I > >	844
mln::Iterator< fwd_pixter2d< I > >	787
mln::Pixel_Iterator< fwd_pixter2d< I > >	940
mln::Object< fwd_pixter3d< I > >	844
mln::Iterator< fwd_pixter3d< I > >	787
mln::Pixel_Iterator< fwd_pixter3d< I > >	940
mln::Object< fwd_t >	844
mln::Browsing< fwd_t >	568
mln::canvas::browsing::fwd_t	576
mln::Object< ge< L, R > >	844
mln::Function< ge< L, R > >	715
mln::Function_vv2b< ge< L, R > >	718
mln::fun::vv2b::ge< L, R >	689
mln::Object< graph >	844
mln::Graph< graph >	731
graph_base< graph >	
mln::util::graph	1058
mln::Object< graph_elt_mixed_window< G, S, S2 > >	844
mln::Window< graph_elt_mixed_window< G, S, S2 > >	1170
mln::graph_window_base< S2::fun_t::result, graph_elt_mixed_window< G, S, S2 > >	751
mln::graph_elt_mixed_window< G, S, S2 >	734
mln::Object< graph_elt_window< G, S > >	844
mln::Window< graph_elt_window< G, S > >	1170
mln::graph_window_base< S::fun_t::result, graph_elt_window< G, S > >	751
mln::graph_elt_window< G, S >	742
mln::Object< graph_elt_window_if< G, S, I > >	844
mln::Window< graph_elt_window_if< G, S, I > >	1170
mln::graph_window_base< S::fun_t::result, graph_elt_window_if< G, S, I > >	751
mln::graph_elt_window_if< G, S, I >	746
mln::Object< graph_window_if_piter< S, W, I > >	844
mln::Proxy< graph_window_if_piter< S, W, I > >	957
mln::Site_Proxy< graph_window_if_piter< S, W, I > >	965
mln::Site_Iterator< graph_window_if_piter< S, W, I > >	963
site_iterator_base< W, graph_window_if_piter< S, W, I > >	
site_relative_iterator_base< W, graph_window_if_piter< S, W, I > >	
mln::graph_window_if_piter< S, W, I >	753
mln::Object< graph_window_piter< S, W, I > >	844
mln::Proxy< graph_window_piter< S, W, I > >	957
mln::Site_Proxy< graph_window_piter< S, W, I > >	965
mln::Site_Iterator< graph_window_piter< S, W, I > >	963
site_iterator_base< W, graph_window_piter< S, W, I > >	
site_relative_iterator_base< W, graph_window_piter< S, W, I >, W::center_t >	
mln::graph_window_piter< S, W, I >	755

mln::Object< gray_f >	844
mln::Value< gray_f >	1107
mln::Object< graylevel< n > >	844
mln::Value< graylevel< n > >	1107
mln::Object< graylevel_f >	844
mln::Value< graylevel_f >	1107
mln::Object< green >	844
mln::Meta_Function< green >	826
mln::Meta_Function_v2v< green >	827
mln::Object< green_t >	844
mln::Literal< green_t >	799
mln::literal::green_t	804
mln::Object< gt< L, R > >	844
mln::Function< gt< L, R > >	715
mln::Function_vv2b< gt< L, R > >	718
mln::fun::vv2b::gt< L, R >	690
mln::Object< has< I > >	844
mln::Function< has< I > >	715
mln::Function_v2v< has< I > >	717
mln::Function_v2b< has< I > >	716
mln::Object< height >	844
mln::Meta_Accumulator< height >	824
mln::accu::meta::shape::height	483
mln::Object< height< I > >	844
mln::Proxy< height< I > >	957
mln::Accumulator< height< I > >	542
base< unsigned, height< I > >	
mln::accu::shape::height< I >	505
mln::morpho::attribute::height< I >	835
mln::Object< hexa >	844
mln::Mesh< hexa >	823
mln::Regular_Grid< hexa >	960
mln::Object< hexa< I > >	844
mln::Image< hexa< I > >	762
mln::Object< hexa< image2d< V > >>	844
mln::Image< hexa< image2d< V > >>	762
mln::Object< histo >	844
mln::Meta_Accumulator< histo >	824
mln::accu::meta::histo	466
mln::Object< histo3d_rgb >	844
mln::Meta_Accumulator< histo3d_rgb >	824
mln::Object< histo3d_rgb< V > >	844
mln::Proxy< histo3d_rgb< V > >	957
mln::Accumulator< histo3d_rgb< V > >	542
base< image3d< unsigned >, histo3d_rgb< V > >	
mln::accu::stat::histo3d_rgb< V >	513
mln::Object< histo< V > >	844
mln::Proxy< histo< V > >	957

mln::Accumulator< histo< V > >	542
base< const std::vector< unsigned > &, histo< V > >	
mln::accu::histo< V >	445
mln::Object< hyper_directional_t >	844
mln::Browsing< hyper_directional_t >	568
mln::canvas::browsing::hyper_directional_t	577
mln::Object< id2element< G, Elt > >	844
mln::Function< id2element< G, Elt > >	715
mln::Function_v2v< id2element< G, Elt > >	717
mln::Object< identity_t >	844
mln::Literal< identity_t >	799
mln::literal::identity_t	805
mln::Object< ignore >	844
mln::util::ignore	1067
mln::Object< image1d< T > >	844
mln::Image< image1d< T > >	762
mln::Object< image2d< T > >	844
mln::Image< image2d< T > >	762
mln::Object< image3d< T > >	844
mln::Image< image3d< T > >	762
mln::Object< image< F, S > >	844
mln::Image< image< F, S > >	762
mln::Object< image_if< I, F > >	844
mln::Image< image_if< I, F > >	762
mln::Object< implies< L, R > >	844
mln::Function< implies< L, R > >	715
mln::Function_vv2b< implies< L, R > >	718
mln::fun::vv2b::implies< L, R >	691
mln::Object< index_of_value< bool > >	844
mln::Function< index_of_value< bool > >	715
mln::Function_v2v< index_of_value< bool > >	717
mln::Object< index_of_value< T > >	844
mln::Function< index_of_value< T > >	715
mln::Function_v2v< index_of_value< T > >	717
mln::Object< inf >	844
mln::Meta_Accumulator< inf >	824
mln::accu::meta::math::inf	474
mln::Meta_Function< inf >	826
mln::Meta_Function_vv2v< inf >	827
mln::Object< inf< T > >	844
mln::Proxy< inf< T > >	957
mln::Accumulator< inf< T > >	542
base< const T &, inf< T > >	
mln::accu::math::inf< T >	457
mln::Object< int_s< n > >	844
mln::Value< int_s< n > >	1107
mln::Object< int_u8_off_saver >	844
mln::Object< int_u< n > >	844

mln::Value< int_u< n > >	1107
mln::Object< int_u_sat< n > >	844
mln::Value< int_u_sat< n > >	1107
mln::Object< interpolated< I, F > >	844
mln::Image< interpolated< I, F > >	762
mln::Object< iota >	844
mln::Function< iota >	715
mln::Function_v2v< iota >	717
mln::Object< is_dot >	844
mln::Function< is_dot >	715
mln::Function_v2v< is_dot >	717
mln::Function_v2b< is_dot >	716
mln::Object< is_edge >	844
mln::Function< is_edge >	715
mln::Function_v2v< is_edge >	717
mln::Function_v2b< is_edge >	716
mln::Object< is_n_face< N > >	844
mln::Function< is_n_face< N > >	715
mln::Function_v2v< is_n_face< N > >	717
mln::Function_v2b< is_n_face< N > >	716
mln::topo::is_n_face< N >	1014
mln::Object< is_pixel >	844
mln::Function< is_pixel >	715
mln::Function_v2v< is_pixel >	717
mln::Function_v2b< is_pixel >	716
mln::Object< is_row_odd >	844
mln::Function< is_row_odd >	715
mln::Function_v2v< is_row_odd >	717
mln::Function_v2b< is_row_odd >	716
mln::Object< is_separator >	844
mln::Function< is_separator >	715
mln::Function_v2v< is_separator >	717
mln::Function_v2b< is_separator >	716
mln::world::inter_pixel::is_separator	1176
mln::Object< is_simple_cell< I > >	844
mln::Function< is_simple_cell< I > >	715
mln::Function_v2v< is_simple_cell< I > >	717
mln::Function_v2b< is_simple_cell< I > >	716
mln::topo::is_simple_cell< I >	1016
mln::Object< ithcomp >	844
mln::Meta_Function< ithcomp >	826
mln::Meta_Function_vv2v< ithcomp >	827
mln::Object< keep_specific_colors >	844
mln::Function< keep_specific_colors >	715
mln::Function_v2v< keep_specific_colors >	717
mln::Function_v2b< keep_specific_colors >	716
mln::Object< ll >	844
mln::Meta_Function< ll >	826

mln::Meta_Function_v2v< 11 >	827
mln::Object< 11_norm< V > >	844
mln::Function< 11_norm< V > >	715
mln::Function_v2v< 11_norm< V > >	717
mln::Object< 11_norm< V, R > >	844
mln::Function< 11_norm< V, R > >	715
mln::Function_v2v< 11_norm< V, R > >	717
mln::fun::v2v::11_norm< V, R >	678
mln::fun::v2w_w2v::11_norm< V, R >	685
mln::Object< l2 >	844
mln::Meta_Function< l2 >	826
mln::Meta_Function_v2v< l2 >	827
mln::Object< l2_norm< V, R > >	844
mln::Function< l2_norm< V, R > >	715
mln::Function_v2v< l2_norm< V, R > >	717
mln::fun::v2v::l2_norm< V, R >	679
mln::fun::v2w_w2v::l2_norm< V, R >	687
mln::Object< label< n > >	844
mln::Value< label< n > >	1107
mln::Object< label_used >	844
mln::Meta_Accumulator< label_used >	824
mln::accu::meta::label_used	467
mln::Object< label_used< L > >	844
mln::Proxy< label_used< L > >	957
mln::Accumulator< label_used< L > >	542
base< const fun::i2v::array< bool > &, label_used< L > >	
mln::accu::label_used< L >	446
mln::Object< labeled_image< I > >	844
mln::Image< labeled_image< I > >	762
mln::Object< land >	844
mln::Meta_Accumulator< land >	824
mln::accu::meta::logic::land	468
mln::Proxy< land >	957
mln::Accumulator< land >	542
base< bool, land >	
mln::accu::logic::land	448
mln::Object< land< L, R > >	844
mln::Function< land< L, R > >	715
mln::Function_vv2v< land< L, R > >	718
mln::fun::vv2v::land< L, R >	695
mln::Object< land_basic >	844
mln::Meta_Accumulator< land_basic >	824
mln::accu::meta::logic::land_basic	469
mln::Proxy< land_basic >	957
mln::Accumulator< land_basic >	542
base< bool, land_basic >	
mln::accu::logic::land_basic	449
mln::Object< land_not< L, R > >	844
mln::Function< land_not< L, R > >	715

mln::Function_vv2v< land_not< L, R > >	718
mln::fun::vv2v::land_not< L, R >	696
mln::Object< lazy_image< I, F, B > >	844
mln::Image< lazy_image< I, F, B > >	762
mln::Object< le< L, R > >	844
mln::Function< le< L, R > >	715
mln::Function_vv2b< le< L, R > >	718
mln::fun::vv2b::le< L, R >	692
mln::Object< light_gray_t >	844
mln::Literal< light_gray_t >	799
mln::literal::light_gray_t	806
mln::Object< lime_t >	844
mln::Literal< lime_t >	799
mln::literal::lime_t	807
mln::Object< line< M, i, C > >	844
mln::Window< line< M, i, C > >	1170
window_base< dpoint< M, C >, line< M, i, C > >	
classical_window_base< dpoint< M, C >, line< M, i, C > >	
mln::win::line< M, i, C >	1165
mln::Object< line_graph< G > >	844
mln::Graph< line_graph< G > >	731
graph_base< line_graph< G > >	
mln::util::line_graph< G >	1068
mln::Object< linear< V, T, R > >	844
mln::Function< linear< V, T, R > >	715
mln::Function_v2v< linear< V, T, R > >	717
mln::fun::v2v::linear< V, T, R >	680
mln::Object< linear_sat< V, T, R > >	844
mln::Function< linear_sat< V, T, R > >	715
mln::Function_v2v< linear_sat< V, T, R > >	717
mln::Object< linfty >	844
mln::Meta_Function< linfty >	826
mln::Meta_Function_v2v< linfty >	827
mln::Object< linfty_norm< V, R > >	844
mln::Function< linfty_norm< V, R > >	715
mln::Function_v2v< linfty_norm< V, R > >	717
mln::fun::v2v::linfty_norm< V, R >	681
mln::fun::v2w_w2v::linfty_norm< V, R >	688
mln::Object< lnot< V > >	844
mln::Function< lnot< V > >	715
mln::Function_v2v< lnot< V > >	717
mln::Function_v2b< lnot< V > >	716
mln::fun::v2b::lnot< V >	675
mln::Object< lor >	844
mln::Meta_Accumulator< lor >	824
mln::accu::meta::logic::lor	470
mln::Proxy< lor >	957
mln::Accumulator< lor >	542

base< bool, lor >	
mln::accu::logic::lor	451
mln::Object< lor< L, R > >	844
mln::Function< lor< L, R > >	715
mln::Function_vv2v< lor< L, R > >	718
mln::fun::vv2v::lor< L, R >	697
mln::Object< lor_basic >	844
mln::Meta_Accumulator< lor_basic >	824
mln::accu::meta::logic::lor_basic	471
mln::Proxy< lor_basic >	957
mln::Accumulator< lor_basic >	542
base< bool, lor_basic >	
mln::accu::logic::lor_basic	452
mln::Object< lt< L, R > >	844
mln::Function< lt< L, R > >	715
mln::Function_vv2b< lt< L, R > >	718
mln::fun::vv2b::lt< L, R >	693
mln::Object< lut_vec< S, T > >	844
mln::Value_Set< lut_vec< S, T > >	1148
mln::value::lut_vec< S, T >	1129
mln::Object< lxor< L, R > >	844
mln::Function< lxor< L, R > >	715
mln::Function_vv2v< lxor< L, R > >	718
mln::fun::vv2v::lxor< L, R >	698
mln::Object< magenta_t >	844
mln::Literal< magenta_t >	799
mln::literal::magenta_t	808
mln::Object< mahalanobis< V > >	844
mln::Function< mahalanobis< V > >	715
mln::Function_v2v< mahalanobis< V > >	717
mln::Object< maj_h >	844
mln::Meta_Accumulator< maj_h >	824
mln::accu::meta::maj_h	472
mln::Object< maj_h< T > >	844
mln::Proxy< maj_h< T > >	957
mln::Accumulator< maj_h< T > >	542
base< const T &, maj_h< T > >	
mln::accu::maj_h< T >	454
mln::Object< mat< n, m, T > >	844
mln::Object< max >	844
mln::Meta_Accumulator< max >	824
mln::accu::meta::stat::max	485
mln::Object< max< T > >	844
mln::Proxy< max< T > >	957
mln::Accumulator< max< T > >	542
base< const T &, max< T > >	
mln::accu::stat::max< T >	515
mln::Object< max< V > >	844
mln::Function< max< V > >	715

mln::Function_vv2v< max< V > >	718
mln::fun::vv2v::max< V >	699
mln::Object< max_h >	844
mln::Meta_Accumulator< max_h >	824
mln::accu::meta::stat::max_h	486
mln::Object< max_h< V > >	844
mln::Proxy< max_h< V > >	957
mln::Accumulator< max_h< V > >	542
base< const V &, max_h< V > >	
mln::accu::stat::max_h< V >	517
mln::Object< max_site >	844
mln::Meta_Accumulator< max_site >	824
mln::accu::meta::max_site	477
mln::Object< max_site< I > >	844
mln::Proxy< max_site< I > >	957
mln::Accumulator< max_site< I > >	542
base< I::psite, max_site< I > >	
mln::accu::max_site< I >	461
mln::Object< max_t >	844
mln::Literal< max_t >	799
mln::literal::max_t	809
mln::Object< mean >	844
mln::Meta_Accumulator< mean >	824
mln::accu::meta::stat::mean	487
mln::Meta_Function< mean >	826
mln::Meta_Function_v2v< mean >	827
mln::Object< mean< T, S, M > >	844
mln::Proxy< mean< T, S, M > >	957
mln::Accumulator< mean< T, S, M > >	542
base< M, mean< T, S, M > >	
mln::accu::stat::mean< T, S, M >	518
mln::Object< median_alt< S > >	844
mln::Proxy< median_alt< S > >	957
mln::Accumulator< median_alt< S > >	542
base< const S::value &, median_alt< S > >	
mln::accu::stat::median_alt< S >	520
mln::Object< median_alt< T > >	844
mln::Meta_Accumulator< median_alt< T > >	824
mln::accu::meta::stat::median_alt< T >	488
mln::Object< median_alt< value::set< T > > >	844
mln::Proxy< median_alt< value::set< T > > >	957
mln::Accumulator< median_alt< value::set< T > > >	542
base< const value::set< T >::value &, median_alt< value::set< T > >>	
mln::accu::stat::median_alt< value::set< T > >	520
mln::Object< median_h >	844
mln::Meta_Accumulator< median_h >	824
mln::accu::meta::stat::median_h	489
mln::Object< median_h< V > >	844
mln::Proxy< median_h< V > >	957

mln::Accumulator< median_h< V > >	542
base< const V &, median_h< V > >	
mln::accu::stat::median_h< V >	522
mln::Object< medium_gray_t >	844
mln::Literal< medium_gray_t >	799
mln::Object< min >	844
mln::Meta_Accumulator< min >	824
mln::accu::meta::stat::min	490
mln::Object< min< L, R > >	844
mln::Function< min< L, R > >	715
mln::Function_vv2v< min< L, R > >	718
mln::fun::vv2v::min< L, R >	700
mln::Object< min< T > >	844
mln::Proxy< min< T > >	957
mln::Accumulator< min< T > >	542
base< const T &, min< T > >	
mln::accu::stat::min< T >	524
mln::Object< min_h >	844
mln::Meta_Accumulator< min_h >	824
mln::accu::meta::stat::min_h	491
mln::Object< min_h< V > >	844
mln::Proxy< min_h< V > >	957
mln::Accumulator< min_h< V > >	542
base< const V &, min_h< V > >	
mln::accu::stat::min_h< V >	526
mln::Object< min_t >	844
mln::Literal< min_t >	799
mln::literal::min_t	810
mln::Object< mirror< B > >	844
mln::Function< mirror< B > >	715
mln::Function_v2v< mirror< B > >	717
mln::Object< mixed_neighb< W > >	844
mln::Neighborhood< mixed_neighb< W > >	844
mln::Object< mln::util::set< T > >	844
mln::util::set< T >	1081
mln::Object< multi_site< P > >	844
mln::Object< multiple< W, F > >	844
mln::Window< multiple< W, F > >	1170
window_base< W::dpsite, multiple< W, F > >	
mln::win::multiple< W, F >	1167
mln::Object< multiple_qiter< W, F > >	844
mln::Proxy< multiple_qiter< W, F > >	957
mln::Site_Proxy< multiple_qiter< W, F > >	965
mln::Site_Iterator< multiple_qiter< W, F > >	963
mln::Object< multiple_size< n, W, F > >	844
mln::Window< multiple_size< n, W, F > >	1170
window_base< W::dpsite, multiple_size< n, W, F > >	
mln::win::multiple_size< n, W, F >	1167

mln::Object< multiple_size_qiter< n, W, F > >	844
mln::Proxy< multiple_size_qiter< n, W, F > >	957
mln::Site_Proxy< multiple_size_qiter< n, W, F > >	965
mln::Site_Iterator< multiple_size_qiter< n, W, F > >	963
mln::Object< my_box2d >	844
mln::Function< my_box2d >	715
mln::Function_v2v< my_box2d >	717
mln::Function_v2b< my_box2d >	716
mln::Object< my_ext >	844
mln::Function< my_ext >	715
mln::Function_v2v< my_ext >	717
mln::Object< my_fun< G > >	844
mln::Function< my_fun< G > >	715
mln::Object< my_image2d< T > >	844
mln::Image< my_image2d< T > >	762
mln::Object< my_values_t >	844
mln::Function< my_values_t >	715
mln::Function_v2v< my_values_t >	717
mln::Object< myfun >	844
mln::Function< myfun >	715
mln::Function_vv2v< myfun >	718
mln::Object< mysqrt >	844
mln::Function< mysqrt >	715
mln::Function_v2v< mysqrt >	717
mln::Object< n_face_bkd_iter< D > >	844
mln::Iterator< n_face_bkd_iter< D > >	787
complex_iterator_base< topo::face< D >, n_face_bkd_iter< D > >	
complex_set_iterator_base< topo::face< D >, n_face_bkd_iter< D > >	
mln::topo::n_face_bkd_iter< D >	1023
mln::Object< n_face_fwd_iter< D > >	844
mln::Iterator< n_face_fwd_iter< D > >	787
complex_iterator_base< topo::face< D >, n_face_fwd_iter< D > >	
complex_set_iterator_base< topo::face< D >, n_face_fwd_iter< D > >	
mln::topo::n_face_fwd_iter< D >	1024
mln::Object< neighb< graph_elt_mixed_window< G, S, S2 > > >	844
mln::Neighborhood< neighb< graph_elt_mixed_window< G, S, S2 > > >	844
mln::Object< neighb< graph_elt_window< G, S > > >	844
mln::Neighborhood< neighb< graph_elt_window< G, S > > >	844
mln::Object< neighb< graph_elt_window_if< G, S, I > > >	844
mln::Neighborhood< neighb< graph_elt_window_if< G, S, I > > >	844
mln::Object< neighb< W > >	844
mln::Neighborhood< neighb< W > >	844
mln::Object< neighb_bkd_niter< W > >	844
mln::Proxy< neighb_bkd_niter< W > >	957
mln::Site_Proxy< neighb_bkd_niter< W > >	965
mln::Site_Iterator< neighb_bkd_niter< W > >	963
mln::Object< neighb_fwd_niter< W > >	844
mln::Proxy< neighb_fwd_niter< W > >	957

mln::Site_Proxy< neighb_fwd_niter< W > >	965
mln::Site_Iterator< neighb_fwd_niter< W > >	963
mln::Object< nil >	844
mln::Meta_Accumulator< nil >	824
mln::accu::meta::nil	478
mln::util::nil	1074
mln::Object< nil< T > >	844
mln::Proxy< nil< T > >	957
mln::Accumulator< nil< T > >	542
base< util::ignore, nil< T > >	
mln::accu::nil< T >	496
mln::Object< not_to_remove >	844
mln::Function< not_to_remove >	715
mln::Function_v2v< not_to_remove >	717
mln::Function_v2b< not_to_remove >	716
mln::Object< object_id< Tag, V > >	844
mln::Value< object_id< Tag, V > >	1107
mln::Object< octagon2d >	844
mln::Window< octagon2d >	1170
window_base< dpoint2d, octagon2d >	
classical_window_base< dpoint2d, octagon2d >	
mln::win::octagon2d	1168
mln::Object< olive_t >	844
mln::Literal< olive_t >	799
mln::literal::olive_t	811
mln::Object< one_t >	844
mln::Literal< one_t >	799
mln::literal::one_t	812
mln::Object< orange_t >	844
mln::Literal< orange_t >	799
mln::literal::orange_t	813
mln::Object< ord_pair< T > >	844
mln::util::ord_pair< T >	1077
mln::Object< origin_t >	844
mln::Literal< origin_t >	799
mln::literal::origin_t	814
mln::Object< P >	844
mln::Point_Site< P >	953
mln::Point< P >	943
mln::Object< p2p_image< I, F > >	844
mln::Image< p2p_image< I, F > >	762
mln::Object< p< A > >	844
mln::Proxy< p< A > >	957
mln::Accumulator< p< A > >	542
base< const A::result &, p< A > >	
mln::accu::p< A >	498
mln::Object< p< mA > >	844
mln::Meta_Accumulator< p< mA > >	824

mln::accu::meta::p< mA >	479
mln::Object< p_array< P > >	844
mln::Site_Set< p_array< P > >	966
site_set_base_< P, p_array< P > >	
mln::p_array< P >	847
mln::Object< p_centered< W > >	844
mln::Site_Set< p_centered< W > >	966
site_set_base_< W::psite, p_centered< W > >	
mln::p_centered< W >	852
mln::Object< p_centered_piter< W > >	844
mln::Proxy< p_centered_piter< W > >	957
mln::Site_Proxy< p_centered_piter< W > >	965
mln::Site_Iterator< p_centered_piter< W > >	963
mln::Object< p_complex< D, G > >	844
mln::Site_Set< p_complex< D, G > >	966
site_set_base_< complex_psite< D, G >, p_complex< D, G > >	
mln::p_complex< D, G >	855
mln::Object< p_double_piter< S, I1, I2 > >	844
mln::Proxy< p_double_piter< S, I1, I2 > >	957
mln::Site_Proxy< p_double_piter< S, I1, I2 > >	965
mln::Site_Iterator< p_double_piter< S, I1, I2 > >	963
mln::Object< p_double_psite< S, Sp > >	844
mln::Proxy< p_double_psite< S, Sp > >	957
mln::Site_Proxy< p_double_psite< S, Sp > >	965
mln::Pseudo_Site< p_double_psite< S, Sp > >	957
mln::Object< p_edges< G, F > >	844
mln::Site_Set< p_edges< G, F > >	966
site_set_base_< F::result, p_edges< G, F > >	
mln::p_edges< G, F >	859
mln::Object< p_edges_psite< G, F > >	844
mln::Proxy< p_edges_psite< G, F > >	957
mln::Site_Proxy< p_edges_psite< G, F > >	965
mln::Pseudo_Site< p_edges_psite< G, F > >	957
mln::Object< p_faces< N, D, P > >	844
mln::Site_Set< p_faces< N, D, P > >	966
site_set_base_< faces_psite< N, D, P >, p_faces< N, D, P > >	
mln::p_faces< N, D, P >	865
mln::Object< p_graph_piter< S, I > >	844
mln::Proxy< p_graph_piter< S, I > >	957
mln::Site_Proxy< p_graph_piter< S, I > >	965
mln::Site_Iterator< p_graph_piter< S, I > >	963
site_iterator_base< S, p_graph_piter< S, I > >	
site_set_iterator_base< S, p_graph_piter< S, I > >	
mln::p_graph_piter< S, I >	868
mln::Object< p_if< S, F > >	844
mln::Site_Set< p_if< S, F > >	966
site_set_base_< S::psite, p_if< S, F > >	
mln::p_if< S, F >	870
mln::Object< p_image< I > >	844

mln::Site_Set< p_image< I > >	966
site_set_base_< I::psite, p_image< I > >	
mln::p_image< I >	873
mln::Object< p_indexed_bkd_piter< S > >	844
mln::Proxy< p_indexed_bkd_piter< S > >	957
mln::Site_Proxy< p_indexed_bkd_piter< S > >	965
mln::Site_Iterator< p_indexed_bkd_piter< S > >	963
site_iterator_base< S, p_indexed_bkd_piter< S > >	
site_set_iterator_base< S, p_indexed_bkd_piter< S > >	
mln::p_indexed_bkd_piter< S >	877
mln::Object< p_indexed_fwd_piter< S > >	844
mln::Proxy< p_indexed_fwd_piter< S > >	957
mln::Site_Proxy< p_indexed_fwd_piter< S > >	965
mln::Site_Iterator< p_indexed_fwd_piter< S > >	963
site_iterator_base< S, p_indexed_fwd_piter< S > >	
site_set_iterator_base< S, p_indexed_fwd_piter< S > >	
mln::p_indexed_fwd_piter< S >	879
mln::Object< p_indexed_psite< S > >	844
mln::Proxy< p_indexed_psite< S > >	957
mln::Site_Proxy< p_indexed_psite< S > >	965
mln::Pseudo_Site< p_indexed_psite< S > >	957
pseudo_site_base_< const S::element &, p_indexed_psite< S > >	
mln::p_indexed_psite< S >	880
mln::Object< p_key< K, P > >	844
mln::Site_Set< p_key< K, P > >	966
site_set_base_< P, p_key< K, P > >	
mln::p_key< K, P >	880
mln::Object< p_line2d >	844
mln::Site_Set< p_line2d >	966
site_set_base_< point2d, p_line2d >	
mln::p_line2d	886
mln::Object< p Mutable_array_of< S > >	844
mln::Site_Set< p Mutable_array_of< S > >	966
site_set_base_< S::site, p Mutable_array_of< S > >	
mln::p Mutable_array_of< S >	890
mln::Object< p_n_faces_bkd_piter< D, G > >	844
mln::Proxy< p_n_faces_bkd_piter< D, G > >	957
mln::Site_Proxy< p_n_faces_bkd_piter< D, G > >	965
mln::Site_Iterator< p_n_faces_bkd_piter< D, G > >	963
site_iterator_base< p_complex< D, G >, p_n_faces_bkd_piter< D, G > >	
site_set_iterator_base< p_complex< D, G >, p_n_faces_bkd_piter< D, G > >	
p_complex_piter_base_< topo::n_face_bkd_iter< D >, p_complex< D, G >, G::site, p_n_faces_bkd_piter< D, G > >	
mln::p_n_faces_bkd_piter< D, G >	893
mln::Object< p_n_faces_fwd_piter< D, G > >	844
mln::Proxy< p_n_faces_fwd_piter< D, G > >	957
mln::Site_Proxy< p_n_faces_fwd_piter< D, G > >	965
mln::Site_Iterator< p_n_faces_fwd_piter< D, G > >	963
site_iterator_base< p_complex< D, G >, p_n_faces_fwd_piter< D, G > >	
site_set_iterator_base< p_complex< D, G >, p_n_faces_fwd_piter< D, G > >	

p_complex_piter_base_< topo::n_face_fwd_iter< D >, p_complex< D, G >, G::site, p_n_faces_fwd_piter< D, G >>	895
mln::p_n_faces_fwd_piter< D, G >	
mln::Object< p_priority< P, Q > >	844
mln::Site_Set< p_priority< P, Q > >	966
site_set_base_< Q::site, p_priority< P, Q > >	
mln::p_priority< P, Q >	896
mln::Object< p_queue< P > >	844
mln::Site_Set< p_queue< P > >	966
site_set_base_< P, p_queue< P > >	
mln::p_queue< P >	902
mln::Object< p_queue_fast< P > >	844
mln::Site_Set< p_queue_fast< P > >	966
site_set_base_< P, p_queue_fast< P > >	
mln::p_queue_fast< P >	906
mln::Object< p_run< P > >	844
mln::Site_Set< p_run< P > >	966
site_set_base_< P, p_run< P > >	
mln::p_run< P >	912
mln::Object< p_run_psite< P > >	844
mln::Proxy< p_run_psite< P > >	957
mln::Site_Proxy< p_run_psite< P > >	965
mln::Pseudo_Site< p_run_psite< P > >	957
mln::Object< p_set< P > >	844
mln::Site_Set< p_set< P > >	966
site_set_base_< P, p_set< P > >	
mln::p_set< P >	916
mln::Object< p_set_of< S > >	844
mln::Site_Set< p_set_of< S > >	966
site_set_base_< S::site, p_set_of< S > >	
mln::p_set_of< S >	921
mln::Object< p_transformed< S, F > >	844
mln::Site_Set< p_transformed< S, F > >	966
site_set_base_< S::psite, p_transformed< S, F > >	
mln::p_transformed< S, F >	924
mln::Object< p_transformed_piter< Pi, S, F > >	844
mln::Proxy< p_transformed_piter< Pi, S, F > >	957
mln::Site_Proxy< p_transformed_piter< Pi, S, F > >	965
mln::Site_Iterator< p_transformed_piter< Pi, S, F > >	963
mln::Object< p_vaccess< V, S > >	844
mln::Site_Set< p_vaccess< V, S > >	966
site_set_base_< S::site, p_vaccess< V, S > >	
mln::p_vaccess< V, S >	928
mln::Object< p_vertices< G, F > >	844
mln::Site_Set< p_vertices< G, F > >	966
site_set_base_< F::result, p_vertices< G, F > >	
mln::p_vertices< G, F >	932
mln::Object< p_vertices_psite< G, F > >	844
mln::Proxy< p_vertices_psite< G, F > >	957

mln::Site_Proxy< p_vertices_psite< G, F > >	965
mln::Pseudo_Site< p_vertices_psite< G, F > >	957
mln::Object< pair< A1, A2 > >	844
mln::Meta_Accumulator< pair< A1, A2 > >	824
mln::accu::meta::pair< A1, A2 >	480
mln::Object< pair< A1, A2, T > >	844
mln::Proxy< pair< A1, A2, T > >	957
mln::Accumulator< pair< A1, A2, T > >	542
base< std::pair< A1::result, A2::result >, pair< A1, A2, T > >	
mln::accu::pair< A1, A2, T >	499
mln::Object< pair< min< V >, max< V >, mln_argument(min< V >) > >	844
mln::Proxy< pair< min< V >, max< V >, mln_argument(min< V >) > >	957
mln::Accumulator< pair< min< V >, max< V >, mln_argument(min< V >) > >	542
mln::Object< pink_t >	844
mln::Literal< pink_t >	799
mln::literal::pink_t	815
mln::Object< pixel< I > >	844
mln::pixel< I >	939
mln::Object< plain< I > >	844
mln::Image< plain< I > >	762
mln::Object< point< G, C > >	844
mln::Site< point< G, C > >	962
mln::Gpoint< point< G, C > >	726
mln::point< G, C >	946
mln::Object< point_from_value< T > >	844
mln::Function< point_from_value< T > >	715
mln::Function_v2v< point_from_value< T > >	717
mln::Object< projection< P, dir > >	844
mln::Function< projection< P, dir > >	715
mln::Function_v2v< projection< P, dir > >	717
mln::Object< proxy< I > >	844
mln::Proxy< proxy< I > >	957
mln::value::proxy< I >	1133
mln::Object< purple_t >	844
mln::Literal< purple_t >	799
mln::literal::purple_t	816
mln::Object< qrde >	844
mln::Function< qrde >	715
mln::Function_v2v< qrde >	717
mln::Object< qt_rgb_to_int_u< n > >	844
mln::Function< qt_rgb_to_int_u< n > >	715
mln::Function_v2v< qt_rgb_to_int_u< n > >	717
mln::Object< quat >	844
mln::Value< quat >	1107
mln::Object< rank >	844
mln::Meta_Accumulator< rank >	824
mln::accu::meta::stat::rank	492
mln::Object< rank< bool > >	844

mln::Proxy< rank< bool > >	957
mln::Accumulator< rank< bool > >	542
base< bool, rank< bool > >	
mln::accu::stat::rank< bool >	532
mln::Object< rank< T > >	844
mln::Proxy< rank< T > >	957
mln::Accumulator< rank< T > >	542
base< const T &, rank< T > >	
mln::accu::stat::rank< T >	530
mln::Object< rank_high_quant >	844
mln::Meta_Accumulator< rank_high_quant >	824
mln::accu::meta::stat::rank_high_quant	493
mln::Object< rank_high_quant< T > >	844
mln::Proxy< rank_high_quant< T > >	957
mln::Accumulator< rank_high_quant< T > >	542
base< const T &, rank_high_quant< T > >	
mln::accu::stat::rank_high_quant< T >	533
mln::Object< rectangle2d >	844
mln::Window< rectangle2d >	1170
window_base< dpoint2d, rectangle2d >	
classical_window_base< dpoint2d, rectangle2d >	
mln::win::rectangle2d	1169
mln::Object< rectangularity< P > >	844
mln::Proxy< rectangularity< P > >	957
mln::Accumulator< rectangularity< P > >	542
mln::Object< red >	844
mln::Meta_Function< red >	826
mln::Meta_Function_v2v< red >	827
mln::Object< red_t >	844
mln::Literal< red_t >	799
mln::literal::red_t	817
mln::Object< ref_data >	844
mln::Function< ref_data >	715
mln::Function_v2v< ref_data >	717
mln::Object< rgb32 >	844
mln::Value< rgb32 >	1107
mln::Object< rgb8_off_loader >	844
mln::Object< rgb8_off_saver >	844
mln::Object< rgb8_to_rgbn< n > >	844
mln::Function< rgb8_to_rgbn< n > >	715
mln::Function_v2v< rgb8_to_rgbn< n > >	717
mln::fun::v2v::rgb8_to_rgbn< n >	682
mln::Object< rgb< n > >	844
mln::Value< rgb< n > >	1107
mln::Object< rgb_to_dist< T, n > >	844
mln::Function< rgb_to_dist< T, n > >	715
mln::Function_v2v< rgb_to_dist< T, n > >	717
mln::Object< rgb_to_int_u< n > >	844
mln::Function< rgb_to_int_u< n > >	715

mln::Function_v2v< rgb_to_int_u< n > >	717
mln::Object< rgb_to_luma< T_luma > >	844
mln::Function< rgb_to_luma< T_luma > >	715
mln::Function_v2v< rgb_to_luma< T_luma > >	717
mln::Object< rgbn_to_lbl8< n > >	844
mln::Function< rgbn_to_lbl8< n > >	715
mln::Function_v2v< rgbn_to_lbl8< n > >	717
mln::Object< rms >	844
mln::Meta_Accumulator< rms >	824
mln::accu::meta::rms	481
mln::Object< rms< T, V > >	844
mln::Proxy< rms< T, V > >	957
mln::Accumulator< rms< T, V > >	542
base< V, rms< T, V > >	502
mln::accu::rms< T, V >	502
mln::Object< rotation< n, C > >	844
mln::Function< rotation< n, C > >	715
mln::Function_v2v< rotation< n, C > >	717
mln::fun::x2x::rotation< n, C >	706
mln::Object< round< R > >	844
mln::Function< round< R > >	715
mln::Function_v2v< round< R > >	717
mln::Object< row >	844
mln::Meta_Function< row >	826
mln::Meta_Function_v2v< row >	827
mln::Object< safe_image< I > >	844
mln::Image< safe_image< I > >	762
mln::Object< saturate< V > >	844
mln::Function< saturate< V > >	715
mln::Function_v2v< saturate< V > >	717
mln::Object< saturate_rgb8 >	844
mln::Function< saturate_rgb8 >	715
mln::Function_v2v< saturate_rgb8 >	717
mln::Object< scomp< ith > >	844
mln::Meta_Function< scomp< ith > >	826
mln::Meta_Function_v2v< scomp< ith > >	827
mln::Object< set_bkd_iter< T > >	844
mln::Proxy< set_bkd_iter< T > >	957
mln::Object< set_fwd_iter< T > >	844
mln::Proxy< set_fwd_iter< T > >	957
mln::Object< sharpness< I > >	844
mln::Proxy< sharpness< I > >	957
mln::Accumulator< sharpness< I > >	542
base< double, sharpness< I > >	836
mln::morpho::attribute::sharpness< I >	836
mln::Object< shell< F, I > >	844
mln::Proxy< shell< F, I > >	957
mln::Object< sign >	844

mln::Value< sign >	1107
mln::Object< site_pair< P > >	844
mln::util::site_pair< P >	1087
mln::Object< sli >	844
mln::Meta_Function< sli >	826
mln::Meta_Function_v2v< sli >	827
mln::Object< slice_image< I > >	844
mln::Image< slice_image< I > >	762
mln::Object< snake_fwd_t >	844
mln::Browsing< snake_fwd_t >	568
mln::canvas::browsing::snake_fwd_t	579
mln::Object< snake_generic_t >	844
mln::Browsing< snake_generic_t >	568
mln::canvas::browsing::snake_generic_t	580
mln::Object< snake_vert_t >	844
mln::Browsing< snake_vert_t >	568
mln::canvas::browsing::snake_vert_t	582
mln::Object< soft_heap< T, R > >	844
mln::util::soft_heap< T, R >	1089
mln::Object< sqrt >	844
mln::Function< sqrt >	715
mln::Function_v2v< sqrt >	717
mln::Object< square >	844
mln::Mesh< square >	823
mln::Regular_Grid< square >	960
mln::Object< stack_image< n, I > >	844
mln::Image< stack_image< n, I > >	762
mln::Object< static_n_face_bkd_iter< N, D > >	844
mln::Iterator< static_n_face_bkd_iter< N, D > >	787
complex_iterator_base< topo::face< D >, static_n_face_bkd_iter< N, D > >	
complex_set_iterator_base< topo::face< D >, static_n_face_bkd_iter< N, D > >	
mln::topo::static_n_face_bkd_iter< N, D >	1028
mln::Object< static_n_face_fwd_iter< N, D > >	844
mln::Iterator< static_n_face_fwd_iter< N, D > >	787
complex_iterator_base< topo::face< D >, static_n_face_fwd_iter< N, D > >	
complex_set_iterator_base< topo::face< D >, static_n_face_fwd_iter< N, D > >	
mln::topo::static_n_face_fwd_iter< N, D >	1029
mln::Object< sub_image< I, S > >	844
mln::Image< sub_image< I, S > >	762
mln::Object< sub_image_if< I, S > >	844
mln::Image< sub_image_if< I, S > >	762
mln::Object< sum >	844
mln::Meta_Accumulator< sum >	824
mln::accu::meta::math::sum	475
mln::Object< sum< I, S > >	844
mln::Proxy< sum< I, S > >	957
mln::Accumulator< sum< I, S > >	542
base< S, sum< I, S > >	

mln::morpho::attribute::sum< I, S >	839
mln::Object< sum< T, S > >	844
mln::Proxy< sum< T, S > >	957
mln::Accumulator< sum< T, S > >	542
base< const S &, sum< T, S > >	
mln::accu::math::sum< T, S >	458
mln::Object< sup >	844
mln::Meta_Accumulator< sup >	824
mln::accu::meta::math::sup	476
mln::Meta_Function< sup >	826
mln::Meta_Function_vv2v< sup >	827
mln::Object< sup< T > >	844
mln::Proxy< sup< T > >	957
mln::Accumulator< sup< T > >	542
base< const T &, sup< T > >	
mln::accu::math::sup< T >	460
mln::Object< tautology >	844
mln::Function< tautology >	715
mln::Function_v2v< tautology >	717
mln::Function_v2b< tautology >	716
mln::fun::p2b::tautology	673
mln::Object< teal_t >	844
mln::Literal< teal_t >	799
mln::literal::teal_t	818
mln::Object< test >	844
mln::Function< test >	715
mln::Function_v2v< test >	717
mln::Object< threshold< V > >	844
mln::Function< threshold< V > >	715
mln::Function_v2v< threshold< V > >	717
mln::Function_v2b< threshold< V > >	716
mln::fun::v2b::threshold< V >	676
mln::Object< thru_image< I, F > >	844
mln::Image< thru_image< I, F > >	762
mln::Object< thrubin_image< I1, I2, F > >	844
mln::Image< thrubin_image< I1, I2, F > >	762
mln::Object< tick >	844
mln::Mesh< tick >	823
mln::Regular_Grid< tick >	960
mln::Object< timer >	844
mln::Proxy< timer >	957
mln::util::timer	1092
mln::Object< to16bits >	844
mln::Function< to16bits >	715
mln::Function_v2v< to16bits >	717
mln::Object< to19bits >	844
mln::Function< to19bits >	715
mln::Function_v2v< to19bits >	717

mln::Object< to23bits >	844
mln::Function< to23bits >	715
mln::Function_v2v< to23bits >	717
mln::Object< to27bits >	844
mln::Function< to27bits >	715
mln::Function_v2v< to27bits >	717
mln::Object< to8bits >	844
mln::Function< to8bits >	715
mln::Function_v2v< to8bits >	717
mln::Object< tofloat01 >	844
mln::Function< tofloat01 >	715
mln::Function_v2v< tofloat01 >	717
mln::Object< tr_image< S, I, T > >	844
mln::Image< tr_image< S, I, T > >	762
mln::Object< transformed_image< I, F > >	844
mln::Image< transformed_image< I, F > >	762
mln::Object< translation< n, C > >	844
mln::Function< translation< n, C > >	715
mln::Function_v2v< translation< n, C > >	717
mln::fun::x2x::translation< n, C >	710
mln::Object< translation_t< P > >	844
mln::Function< translation_t< P > >	715
mln::Function_v2v< translation_t< P > >	717
mln::Object< tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >	844
mln::Proxy< tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >	957
mln::Accumulator< tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >	542
base< boost::tuple< BOOST_PP_REPEAT(10, RESULT_ACCU, Le Ricard ya que ca de vrai!) >, tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >	539
mln::Object< tuple< n, BOOST_PP_ENUM_PARAMS(10, T)> >	844
mln::Meta_Accumulator< tuple< n, BOOST_PP_ENUM_PARAMS(10, T)> >	824
mln::accu::meta::tuple< n, >	494
mln::Object< unary< Fun, T > >	844
mln::Function< unary< Fun, T > >	715
mln::Function_v2v< unary< Fun, T > >	717
mln::Object< unproject_image< I, D, F > >	844
mln::Image< unproject_image< I, D, F > >	762
mln::Object< up_leaf_piter< T > >	844
mln::Proxy< up_leaf_piter< T > >	957
mln::Site_Proxy< up_leaf_piter< T > >	965
mln::Site_Iterator< up_leaf_piter< T > >	963
mln::Object< up_node_piter< T > >	844
mln::Proxy< up_node_piter< T > >	957
mln::Site_Proxy< up_node_piter< T > >	965
mln::Site_Iterator< up_node_piter< T > >	963
mln::Object< up_site_piter< T > >	844
mln::Proxy< up_site_piter< T > >	957
mln::Site_Proxy< up_site_piter< T > >	965

mln::Site_Iterator< up_site_piter< T > >	963
mln::Object< val< A > >	844
mln::Proxy< val< A > >	957
mln::Accumulator< val< A > >	542
base< const A::result &, val< A > >	
mln::accu::val< A >	541
mln::Object< val< mA > >	844
mln::Meta_Accumulator< val< mA > >	824
mln::accu::meta::val< mA >	495
mln::Object< value_at_index< bool > >	844
mln::Function< value_at_index< bool > >	715
mln::Function_v2v< value_at_index< bool > >	717
mln::Object< value_at_index< T > >	844
mln::Function< value_at_index< T > >	715
mln::Function_v2v< value_at_index< T > >	717
mln::Object< var< T > >	844
mln::Proxy< var< T > >	957
mln::Accumulator< var< T > >	542
base< algebra::mat< T::dim, T::dim, float >, var< T > >	
mln::accu::stat::var< T >	535
mln::Object< variance< T, S, R > >	844
mln::Proxy< variance< T, S, R > >	957
mln::Accumulator< variance< T, S, R > >	542
base< R, variance< T, S, R > >	
mln::accu::stat::variance< T, S, R >	537
mln::Object< vec< 1, T > >	844
mln::Object< vec< 2, T > >	844
mln::Object< vec< 3, T > >	844
mln::Object< vec< 4, T > >	844
mln::Object< vec< n, C > >	844
mln::Object< vec< n, T > >	844
mln::Object< vec< V > >	844
mln::Function< vec< V > >	715
mln::Function_vv2v< vec< V > >	718
mln::fun::vv2v::vec< V >	701
mln::Object< vertex< G > >	844
mln::Site< vertex< G > >	962
mln::util::vertex< G >	1102
mln::Object< vertex_bkd_iterator< G > >	844
mln::Proxy< vertex_bkd_iterator< G > >	957
mln::Object< vertex_fwd_iterator< G > >	844
mln::Proxy< vertex_fwd_iterator< G > >	957
mln::Object< vertex_image< P, V, G > >	844
mln::Image< vertex_image< P, V, G > >	762
mln::Object< vertex_nbh_edge_bkd_iterator< G > >	844
mln::Proxy< vertex_nbh_edge_bkd_iterator< G > >	957
mln::Object< vertex_nbh_edge_fwd_iterator< G > >	844
mln::Proxy< vertex_nbh_edge_fwd_iterator< G > >	957
mln::Object< vertex_nbh_vertex_bkd_iterator< G > >	844

mln::Proxy< vertex_nbh_vertex_bkd_iterator< G > >	957
mln::Object< vertex_nbh_vertex_fwd_iterator< G > >	844
mln::Proxy< vertex_nbh_vertex_fwd_iterator< G > >	957
mln::Object< violent_cast_image< T, I > >	844
mln::Image< violent_cast_image< T, I > >	762
mln::Object< violet_t >	844
mln::Literal< violet_t >	799
mln::literal::violet_t	819
mln::Object< viota_t >	844
mln::Function< viota_t >	715
mln::Function_v2v< viota_t >	717
mln::Object< viota_t< S > >	844
mln::Function< viota_t< S > >	715
mln::Function_v2v< viota_t< S > >	717
mln::Object< volume >	844
mln::Meta_Accumulator< volume >	824
mln::accu::meta::shape::volume	484
mln::Object< volume< I > >	844
mln::Proxy< volume< I > >	957
mln::Accumulator< volume< I > >	542
base< unsigned, volume< I > >	507
mln::accu::shape::volume< I >	840
mln::Object< W >	844
mln::Object< w_window< D, W > >	844
mln::Weighted_Window< w_window< D, W > >	1158
weighted_window_base< mln::window< D >, w_window< D, W > >	1154
mln::w_window< D, W >	1154
mln::Object< white_gaussian< V > >	844
mln::Function< white_gaussian< V > >	715
mln::Function_n2v< white_gaussian< V > >	716
mln::fun::n2v::white_gaussian< V >	672
mln::Object< white_t >	844
mln::Literal< white_t >	799
mln::literal::white_t	820
mln::Object< window< D > >	844
mln::Window< window< D > >	1170
window_base< D, window< D > >	1171
mln::window< D >	1171
mln::Object< wrap >	844
mln::Function< wrap >	715
mln::Function_v2v< wrap >	717
mln::Object< wrap< L > >	844
mln::Function< wrap< L > >	715
mln::Function_v2v< wrap< L > >	717
mln::Object< yellow_t >	844
mln::Literal< yellow_t >	799
mln::literal::yellow_t	821

mln::Object< yes >	844
mln::util::yes	1107
mln::Object< zero_t >	844
mln::Literal< zero_t >	799
mln::literal::zero_t	822
mln::internal::pixel_impl_< I, bkd_pixter1d< I > >	
pixel_iterator_base_< I, bkd_pixter1d< I > >	
mln::internal::pixel_impl_< I, bkd_pixter2d< I > >	
pixel_iterator_base_< I, bkd_pixter2d< I > >	
mln::internal::pixel_impl_< I, bkd_pixter3d< I > >	
pixel_iterator_base_< I, bkd_pixter3d< I > >	
mln::internal::pixel_impl_< I, dpoints_bkd_pixter< I > >	
mln::dpoints_bkd_pixter< I >	648
mln::internal::pixel_impl_< I, dpoints_fwd_pixter< I > >	
mln::dpoints_fwd_pixter< I >	652
mln::internal::pixel_impl_< I, fwd_pixter1d< I > >	
pixel_iterator_base_< I, fwd_pixter1d< I > >	
mln::internal::pixel_impl_< I, fwd_pixter2d< I > >	
pixel_iterator_base_< I, fwd_pixter2d< I > >	
mln::internal::pixel_impl_< I, fwd_pixter3d< I > >	
pixel_iterator_base_< I, fwd_pixter3d< I > >	
mln::internal::pixel_impl_< I, pixel< I > >	
mln::pixel< I >	939
trait::graph< I >	1177
trait::graph< mln::complex_image< 1, G, V > >	1178
trait::graph< mln::image2d< T > >	1178

Chapter 7

Class Index

7.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

mln::accu::center< P, V > (Mass center accumulator)	437
mln::accu::convolve< T1, T2, R > (Generic convolution accumulator class)	439
mln::accu::count_adjacent_vertices< F, S > (Accumulator class counting the number of vertices adjacent to a set of mln::p_edges_psite (i.e., a set of edges))	440
mln::accu::count_labels< L > (Count the number of different labels in an image)	442
mln::accu::count_value< V > (Define an accumulator that counts the occurrence of a given value)	443
mln::accu::histo< V > (Generic histogram class over a value set with type V)	445
mln::accu::label_used< L > (References all the labels used)	446
mln::accu::logic::land ("Logical-and" accumulator)	448
mln::accu::logic::land_basic ("Logical-and" accumulator)	449
mln::accu::logic::lor ("Logical-or" accumulator)	451
mln::accu::logic::lor_basic ("Logical-or" accumulator class)	452
mln::accu::maj_h< T > (Compute the majority value)	454
mln::accu::math::count< T > (Generic counter accumulator)	455
mln::accu::math::inf< T > (Generic inf accumulator class)	457
mln::accu::math::sum< T, S > (Generic sum accumulator class)	458
mln::accu::math::sup< T > (Generic sup accumulator class)	460
mln::accu::max_site< I > (Define an accumulator that computes the first site with the maximum value in an image)	461
mln::accu::meta::center (Meta accumulator for center)	463
mln::accu::meta::count_adjacent_vertices (Meta accumulator for count_adjacent_vertices) . . .	463
mln::accu::meta::count_labels (Meta accumulator for count_labels)	464
mln::accu::meta::count_value (FIXME: How to write a meta accumulator with a constructor taking a generic argument? Meta accumulator for count_value)	465
mln::accu::meta::histo (Meta accumulator for histo)	466
mln::accu::meta::label_used (Meta accumulator for label_used)	467
mln::accu::meta::logic::land (Meta accumulator for land)	468
mln::accu::meta::logic::land_basic (Meta accumulator for land_basic)	469
mln::accu::meta::logic::lor (Meta accumulator for lor)	470
mln::accu::meta::logic::lor_basic (Meta accumulator for lor_basic)	471
mln::accu::meta::maj_h (Meta accumulator for maj_h)	472
mln::accu::meta::math::count (Meta accumulator for count)	473
mln::accu::meta::math::inf (Meta accumulator for inf)	474

mln::accu::meta::math::sum (Meta accumulator for sum)	475
mln::accu::meta::math::sup (Meta accumulator for sup)	476
mln::accu::meta::max_site (Meta accumulator for max_site)	477
mln::accu::meta::nil (Meta accumulator for nil)	478
mln::accu::meta::p< mA > (Meta accumulator for p)	479
mln::accu::meta::pair< A1, A2 > (Meta accumulator for pair)	480
mln::accu::meta::rms (Meta accumulator for rms)	481
mln::accu::meta::shape::bbox (Meta accumulator for bbox)	482
mln::accu::meta::shape::height (Meta accumulator for height)	483
mln::accu::meta::shape::volume (Meta accumulator for volume)	484
mln::accu::meta::stat::max (Meta accumulator for max)	485
mln::accu::meta::stat::max_h (Meta accumulator for max_h)	486
mln::accu::meta::stat::mean (Meta accumulator for mean)	487
mln::accu::meta::stat::median_alt< T > (Meta accumulator for median_alt)	488
mln::accu::meta::stat::median_h (Meta accumulator for median_h)	489
mln::accu::meta::stat::min (Meta accumulator for min)	490
mln::accu::meta::stat::min_h (Meta accumulator for min_h)	491
mln::accu::meta::stat::rank (Meta accumulator for rank)	492
mln::accu::meta::stat::rank_high_quant (Meta accumulator for rank_high_quant)	493
mln::accu::meta::tuple< n, > (Meta accumulator for tuple)	494
mln::accu::meta::val< mA > (Meta accumulator for val)	495
mln::accu::nil< T > (Define an accumulator that does nothing)	496
mln::accu::p< A > (Generic p of accumulators)	498
mln::accu::pair< A1, A2, T > (Generic pair of accumulators)	499
mln::accu::rms< T, V > (Generic root mean square accumulator class)	502
mln::accu::shape::bbox< P > (Generic bounding box accumulator class)	504
mln::accu::shape::height< I > (Height accumulator)	505
mln::accu::shape::volume< I > (Volume accumulator class)	507
mln::accu::site_set::rectangularity< P > (Compute the rectangularity of a site set)	509
mln::accu::stat::deviation< T, S, M > (Generic standard deviation accumulator class)	511
mln::accu::stat::histo3d_rgb< V > (Define a histogram as accumulator which returns an image3d)	513
mln::accu::stat::max< T > (Generic max accumulator class)	515
mln::accu::stat::max_h< V > (Generic max function based on histogram over a value set with type V)	517
mln::accu::stat::mean< T, S, M > (Generic mean accumulator class)	518
mln::accu::stat::median_alt< S > (Generic median_alt function based on histogram over a value set with type S)	520
mln::accu::stat::median_h< V > (Generic median function based on histogram over a value set with type V)	522
mln::accu::stat::meta::deviation (Meta accumulator for deviation)	523
mln::accu::stat::min< T > (Generic min accumulator class)	524
mln::accu::stat::min_h< V > (Generic min function based on histogram over a value set with type V)	526
mln::accu::stat::min_max< V > (Generic min and max accumulator class)	527
mln::accu::stat::rank< T > (Generic rank accumulator class)	530
mln::accu::stat::rank< bool > (Rank accumulator class for Boolean)	532
mln::accu::stat::rank_high_quant< T > (Generic rank accumulator class)	533
mln::accu::stat::var< T > (Var accumulator class)	535
mln::accu::stat::variance< T, S, R > (Variance accumulator class)	537
mln::accu::tuple< A, n, > (Generic tuple of accumulators)	539
mln::accu::val< A > (Generic val of accumulators)	541
mln::Accumulator< E > (Base class for implementation of accumulators)	542
mln::algebra::h_mat< d, T > (N-Dimensional matrix with homogeneous coordinates)	544
mln::algebra::h_vec< d, C > (N-Dimensional vector with homogeneous coordinates)	546

mln::bkd_pixter1d< I > (Backward pixel iterator on a 1-D image with border)	548
mln::bkd_pixter2d< I > (Backward pixel iterator on a 2-D image with border)	549
mln::bkd_pixter3d< I > (Backward pixel iterator on a 3-D image with border)	551
mln::box< P > (Generic box class: site set containing points of a regular grid)	552
mln::Box< E > (Base class for implementation classes of boxes)	560
mln::box_runend_piter< P > (A generic backward iterator on points by lines)	566
mln::box_runstart_piter< P > (A generic forward iterator on points by lines)	567
mln::Browsing< E > (Base class for implementation classes that are browsings)	568
mln::canvas::browsing::backdiagonal2d_t (Browsing in a certain direction)	569
mln::canvas::browsing::breadth_first_search_t (Breadth-first search algorithm for graph, on vertices)	571
mln::canvas::browsing::depth_first_search_t (Breadth-first search algorithm for graph, on vertices)	571
mln::canvas::browsing::diagonal2d_t (Browsing in a certain direction)	571
mln::canvas::browsing::dir_struct_elt_incr_update_t (Browsing in a certain direction with a segment)	573
mln::canvas::browsing::directional_t (Browsing in a certain direction)	574
mln::canvas::browsing::fwd_t (Canvas for forward browsing)	576
mln::canvas::browsing::hyper_directional_t (Browsing in a certain direction)	577
mln::canvas::browsing::snake_fwd_t (Browsing in a snake-way, forward)	579
mln::canvas::browsing::snake_generic_t (Multidimentional Browsing in a given-way)	580
mln::canvas::browsing::snake_vert_t (Browsing in a snake-way, forward)	582
mln::canvas::chamfer< F > (Compute chamfer distance)	583
mln::category< R(*)(A) > (Category declaration for a unary C function)	583
mln::complex_image< D, G, V > (Image based on a complex)	584
mln::complex_neighborhood_bkd_piter< I, G, N > (Backward iterator on complex neighborhood)	587
mln::complex_neighborhood_fwd_piter< I, G, N > (Forward iterator on complex neighborhood)	588
mln::complex_psite< D, G > (Point site associated to a mln::p_complex)	590
mln::complex_window_bkd_piter< I, G, W > (Backward iterator on complex window)	593
mln::complex_window_fwd_piter< I, G, W > (Forward iterator on complex window)	595
mln::decorated_image< I, D > (Image that can have additional features)	596
mln::Delta_Point_Site< void > (Delta point site category flag type)	599
mln::doc::Accumulator< E > (Documentation class for mln::Accumulator)	599
mln::doc::Box< E > (Documentation class for mln::Box)	601
mln::doc::Dpoint< E > (Documentation class for mln::Dpoint)	604
mln::doc::Fastest_Image< E > (Documentation class for the concept of images that have the speed property set to "fastest")	606
mln::doc::Generalized_Pixel< E > (Documentation class for mln::Generalized_Pixel)	614
mln::doc::Image< E > (Documentation class for mln::Image)	616
mln::doc::Iterator< E > (Documentation class for mln::Iterator)	622
mln::doc::Neighborhood< E > (Documentation class for mln::Neighborhood)	623
mln::doc::Object< E > (Documentation class for mln::Object)	625
mln::doc::Pixel_Iterator< E > (Documentation class for mln::Pixel_Iterator)	625
mln::doc::Point_Site< E > (Documentation class for mln::Point_Site)	628
mln::doc::Site_Iterator< E > (Documentation class for mln::Site_Iterator)	631
mln::doc::Site_Set< E > (Documentation class for mln::Site_Set)	633
mln::doc::Value_Iterator< E > (Documentation class for mln::Value_Iterator)	635
mln::doc::Value_Set< E > (Documentation class for mln::Value_Set)	636
mln::doc::Weighted_Window< E > (Documentation class for mln::Weighted_Window)	639
mln::doc::Window< E > (Documentation class for mln::Window)	641
mln::Dpoint< E > (Base class for implementation of delta-point classes)	643
mln::dpoint< G, C > (Generic delta-point class)	644

<code>mln::dpoints_bkd_pixter< I ></code> (A generic backward iterator on the pixels of a dpoint-based window or neighborhood)	648
<code>mln::dpoints_fwd_pixter< I ></code> (A generic forward iterator on the pixels of a dpoint-based window or neighborhood)	652
<code>mln::Edge< E ></code> (<code>Edge</code> category flag type)	655
<code>mln::edge_image< P, V, G ></code> (<code>Image</code> based on graph edges)	655
<code>mln::extended< I ></code> (Makes an image become restricted by a point set)	657
<code>mln::extension_fun< I, F ></code> (Extends the domain of an image with a function)	659
<code>mln::extension_ima< I, J ></code> (Extends the domain of an image with an image)	661
<code>mln::extension_val< I ></code> (Extends the domain of an image with a value)	664
<code>mln::faces_psite< N, D, P ></code> (<code>Point</code> site associated to a <code>mln::p_faces</code>)	666
<code>mln::flat_image< T, S ></code> (<code>Image</code> with a single value)	669
<code>mln::fun::from_accu< A ></code> (Wrap an accumulator into a function)	671
<code>mln::fun::n2v::white_gaussian< V ></code> (Generate a White Gaussian Noise)	672
<code>mln::fun::p2b::antilogy</code> (A <code>p2b</code> function always returning <code>false</code>)	672
<code>mln::fun::p2b::tautology</code> (A <code>p2b</code> function always returning <code>true</code>)	673
<code>mln::fun::v2b::lnot< V ></code> (Functor computing logical-not on a value)	675
<code>mln::fun::v2b::threshold< V ></code> (Threshold function)	676
<code>mln::fun::v2v::ch_function_value< F, V ></code> (Wrap a function <code>v2v</code> and convert its result to another type)	677
<code>mln::fun::v2v::component< T, i ></code> (Functor that accesses the <i>i</i> -th component of a value)	678
<code>mln::fun::v2v::l1_norm< V, R ></code> (L1-norm)	678
<code>mln::fun::v2v::l2_norm< V, R ></code> (L2-norm)	679
<code>mln::fun::v2v::linear< V, T, R ></code> (Linear function. $f(v) = a * v + b$. V is the type of input values; T is the type used to compute the result; R is the result type)	680
<code>mln::fun::v2v::linthy_norm< V, R ></code> (L-infty norm)	681
<code>mln::fun::v2v::rgb8_to_rgn< n ></code> (Convert a <code>rgb8</code> value to a <code>rgn</code> , $n < 8$)	682
<code>mln::fun::v2w2v::cos< V ></code> (Cosinus bijective functor)	684
<code>mln::fun::v2w_w2v::l1_norm< V, R ></code> (L1-norm)	685
<code>mln::fun::v2w_w2v::l2_norm< V, R ></code> (L2-norm)	687
<code>mln::fun::v2w_w2v::linfty_norm< V, R ></code> (L-infty norm)	688
<code>mln::fun::vv2b::eq< L, R ></code> (Functor computing equal between two values)	689
<code>mln::fun::vv2b::ge< L, R ></code> (Functor computing "greater or equal than" between two values)	689
<code>mln::fun::vv2b::gt< L, R ></code> (Functor computing "greater than" between two values)	690
<code>mln::fun::vv2b::implies< L, R ></code> (Functor computing logical-implies between two values)	691
<code>mln::fun::vv2b::le< L, R ></code> (Functor computing "lower or equal than" between two values)	692
<code>mln::fun::vv2b::lt< L, R ></code> (Functor computing "lower than" between two values)	693
<code>mln::fun::vv2v::diff_abs< V ></code> (A functor computing the <code>diff_abs</code> imum of two values)	694
<code>mln::fun::vv2v::land< L, R ></code> (Functor computing logical-and between two values)	695
<code>mln::fun::vv2v::land_not< L, R ></code> (Functor computing logical and-not between two values)	696
<code>mln::fun::vv2v::lor< L, R ></code> (Functor computing logical-or between two values)	697
<code>mln::fun::vv2v::lxor< L, R ></code> (Functor computing logical-xor between two values)	698
<code>mln::fun::vv2v::max< V ></code> (A functor computing the maximum of two values)	699
<code>mln::fun::vv2v::min< L, R ></code> (A functor computing the minimum of two values)	700
<code>mln::fun::vv2v::vec< V ></code> (A functor computing the vecimum of two values)	701
<code>mln::fun::x2p::closest_point< P ></code> (FIXME: doxygen + concept checking)	702
<code>mln::fun::x2v::bilinear< I ></code> (Represent a bilinear interpolation of values from an underlying image)	703
<code>mln::fun::x2v::trilinear< I ></code> (Represent a trilinear interpolation of values from an underlying image)	704
<code>mln::fun::x2x::composed< T2, T1 ></code> (Represent a composition of two transformations)	704
<code>mln::fun::x2x::linear< I ></code> (Represent a linear interpolation of values from an underlying image)	705
<code>mln::fun::x2x::rotation< n, C ></code> (Represent a rotation function)	706
<code>mln::fun::x2x::translation< n, C ></code> (Translation function-object)	710

mln::fun_image< F, I > (Image read through a function)	712
mln::Function< E > (Base class for implementation of function-objects)	715
mln::Function< void > (Function category flag type)	715
mln::Function_n2v< E > (Base class for implementation of function-objects from Nil to value)	716
mln::Function_v2b< E > (Base class for implementation of function-objects from a value to a Boolean)	716
mln::Function_v2v< E > (Base class for implementation of function-objects from value to value)	717
mln::Function_vv2b< E > (Base class for implementation of function-objects from a couple of values to a Boolean)	718
mln::Function_vv2v< E > (Base class for implementation of function-objects from a couple of values to a value)	718
mln::fwd_pixter1d< I > (Forward pixel iterator on a 1-D image with border)	719
mln::fwd_pixter2d< I > (Forward pixel iterator on a 2-D image with border)	720
mln::fwd_pixter3d< I > (Forward pixel iterator on a 3-D image with border)	722
mln::Gdpoint< E > (FIXME: Doc!)	723
mln::Gdpoint< void > (Delta point site category flag type)	724
mln::geom::complex_geometry< D, P > (A functor returning the sites of the faces of a complex where the locations of each 0-face is stored)	725
mln::Gpoint< E > (Base class for implementation of point classes)	726
mln::Graph< E > (Base class for implementation of graph classes)	731
mln::graph::attribute::card_t (Compute the cardinality of every component in a graph)	732
mln::graph::attribute::representative_t (Compute the representative vertex of every component in a graph)	732
mln::graph_elt_mixed_neighborhood< G, S, S2 > (Elementary neighborhood on graph class)	733
mln::graph_elt_mixed_window< G, S, S2 > (Elementary window on graph class)	734
mln::graph_elt_neighborhood< G, S > (Elementary neighborhood on graph class)	738
mln::graph_elt_neighborhood_if< G, S, I > (Elementary neighborhood_if on graph class)	740
mln::graph_elt_window< G, S > (Elementary window on graph class)	742
mln::graph_elt_window_if< G, S, I > (Custom window on graph class)	746
mln::graph_window_base< P, E >	751
mln::graph_window_if_piter< S, W, I > (Forward iterator on line graph window)	753
mln::graph_window_piter< S, W, I > (Forward iterator on line graph window)	755
mln::hexa< I > (Hexagonal image class)	758
mln::histo::array< T > (Generic histogram class over a value set with type T)	762
mln::Image< E > (Base class for implementation of image classes)	762
mln::image1d< T > (Basic 1D image class)	764
mln::image2d< T > (Basic 2D image class)	769
mln::image2d_h< V > (2d image based on an hexagonal mesh)	774
mln::image3d< T > (Basic 3D image class)	777
mln::image_if< I, F > (Image which domain is restricted by a function 'site -> Boolean')	782
mln::interpolated< I, F > (Makes the underlying image being accessed with floating coordinates)	784
mln::io::dicom::dicom_header (Store dicom file header)	786
mln::io::dump::dump_header (Store dump file header)	786
mln::io::fld::fld_header (Define the header structure of an AVS field data file)	787
mln::io::raw::raw_header (Store raw file header)	787
mln::Iterator< E > (Base class for implementation classes that are iterators)	787
mln::labeled_image< I > (Morpher providing an improved interface for labeled image)	789
mln::labeled_image_base< I, E > (Base class Morpher providing an improved interface for labeled image)	793
mln::lazy_image< I, F, B > (Image values are computed on the fly)	796
mln::Literal< E > (Base class for implementation classes of literals)	799
mln::literal::black_t (Type of literal black)	801
mln::literal::blue_t (Type of literal blue)	802
mln::literal::brown_t (Type of literal brown)	802

mln::literal::cyan_t (Type of literal cyan)	803
mln::literal::green_t (Type of literal green)	804
mln::literal::identity_t (Type of literal identity)	805
mln::literal::light_gray_t (Type of literal grays)	806
mln::literal::lime_t (Type of literal lime)	807
mln::literal::magenta_t (Type of literal magenta)	808
mln::literal::max_t (Type of literal max)	809
mln::literal::min_t (Type of literal min)	810
mln::literal::olive_t (Type of literal olive)	811
mln::literal::one_t (Type of literal one)	812
mln::literal::orange_t (Type of literal orange)	813
mln::literal::origin_t (Type of literal origin)	814
mln::literal::pink_t (Type of literal pink)	815
mln::literal::purple_t (Type of literal purple)	816
mln::literal::red_t (Type of literal red)	817
mln::literal::teal_t (Type of literal teal)	818
mln::literal::violet_t (Type of literal violet)	819
mln::literal::white_t (Type of literal white)	820
mln::literal::yellow_t (Type of literal yellow)	821
mln::literal::zero_t (Type of literal zero)	822
mln::Mesh< E > (Base class for implementation classes of meshes)	823
mln::Meta_Accumulator< E > (Base class for implementation of meta accumulators)	824
mln::Meta_Function< E > (Base class for implementation of meta functions)	826
mln::Meta_Function_v2v< E > (Base class for implementation of function-objects from value to value)	827
mln::Meta_Function_vv2v< E > (Base class for implementation of function-objects from value to value)	827
mln::metal::ands< E1, E2, E3, E4, E5, E6, E7, E8 > (Ands type)	828
mln::metal::converts_to< T, U > ("converts-to" check)	828
mln::metal::equal< T1, T2 > (Definition of a static 'equal' test)	828
mln::metal::goes_to< T, U > ("goes-to" check)	829
mln::metal::is< T, U > ("is" check)	829
mln::metal::is_a< T, M > ("is_a" check)	830
mln::metal::is_not< T, U > ("is_not" check)	830
mln::metal::is_not_a< T, M > ("is_not_a" static Boolean expression)	830
mln::mixed_neighb< W > (Adapter class from window to neighborhood)	830
mln::morpho::attribute::card< I > (Cardinality accumulator class)	832
mln::morpho::attribute::count_adjacent_vertices< I > (Count_Adjacent_Vertices accumulator class)	833
mln::morpho::attribute::height< I > (Height accumulator class)	835
mln::morpho::attribute::sharpness< I > (Sharpness accumulator class)	836
mln::morpho::attribute::sum< I, S > (Suminality accumulator class)	839
mln::morpho::attribute::volume< I > (Volume accumulator class)	840
mln::neighb< W > (Adapter class from window to neighborhood)	842
mln::Neighborhood< E > (Base class for implementation classes that are neighborhoods) . . .	844
mln::Neighborhood< void > (Neighborhood category flag type)	844
mln::Object< E > (Base class for almost every class defined in Milena)	844
mln::p2p_image< I, F > (FIXME: Doc!)	845
mln::p_array< P > (Multi-set of sites)	847
mln::p_centered< W > (Site set corresponding to a window centered on a site)	852
mln::p_complex< D, G > (A complex psite set based on the N-faces of a complex of dimension D (a D-complex))	855
mln::p_edges< G, F > (Site set mapping graph edges and image sites)	859

<code>mln::p_faces< N, D, P ></code> (A complex psite set based on the N-faces of a complex of dimension D (a D-complex))	865
<code>mln::p_graph_piter< S, I ></code> (Generic iterator on point sites of a <code>mln::S</code>)	868
<code>mln::p_if< S, F ></code> (<code>Site</code> set restricted w.r.t)	870
<code>mln::p_image< I ></code> (<code>Site</code> set based on an image of Booleans)	873
<code>mln::p_indexed_bkd_piter< S ></code> (Backward iterator on sites of an indexed site set)	877
<code>mln::p_indexed_fwd_piter< S ></code> (Forward iterator on sites of an indexed site set)	879
<code>mln::p_indexed_psite< S ></code> (Psite class for indexed site sets such as <code>p_array</code>)	880
<code>mln::p_key< K, P ></code> (Priority queue class)	880
<code>mln::p_line2d</code> (2D discrete line of points)	886
<code>mln::p Mutable_array_of< S ></code> (<code>P Mutable_array_of</code> is a mutable array of site sets)	890
<code>mln::p_n_faces_bkd_piter< D, G ></code> (Backward iterator on the n-faces sites of an <code>mln::p_complex<D, G></code>)	893
<code>mln::p_n_faces_fwd_piter< D, G ></code> (Forward iterator on the n-faces sites of an <code>mln::p_complex<D, G></code>)	895
<code>mln::p_priority< P, Q ></code> (Priority queue)	896
<code>mln::p_queue< P ></code> (Queue of sites (based on <code>std::deque</code>))	902
<code>mln::p_queue_fast< P ></code> (Queue of sites class (based on <code>p_array</code>))	906
<code>mln::p_run< P ></code> (<code>Point</code> set class in run)	912
<code>mln::p_set< P ></code> (Mathematical set of sites (based on <code>util::set</code>))	916
<code>mln::p_set_of< S ></code> (<code>P Set_of</code> is a set of site sets)	921
<code>mln::p_transformed< S, F ></code> (<code>Site</code> set transformed through a function)	924
<code>mln::p_transformed_piter< Pi, S, F ></code> (<code>Iterator</code> on <code>p_transformed<S,F></code>)	927
<code>mln::p_vaccess< V, S ></code> (<code>Site</code> set in which sites are grouped by their associated value)	928
<code>mln::p_vertices< G, F ></code> (<code>Site</code> set based mapping graph vertices to sites)	932
<code>mln::pixel< I ></code> (Generic pixel class)	939
<code>mln::Pixel_Ierator< E ></code> (Base class for the implementation of pixel iterator classes)	940
<code>mln::plain< I ></code> (Prevents an image from sharing its data)	942
<code>mln::Point< P ></code> (Base class for implementation of point classes)	943
<code>mln::point< G, C ></code> (Generic point class)	946
<code>mln::Point_Site< E ></code> (Base class for implementation classes of the notion of "point site")	953
<code>mln::Point_Site< void ></code> (<code>Point</code> site category flag type)	956
<code>mln::Proxy< E ></code> (Base class for implementation classes of the notion of "proxy")	957
<code>mln::Proxy< void ></code> (<code>Proxy</code> category flag type)	957
<code>mln::Pseudo_Site< E ></code> (Base class for implementation classes of the notion of "pseudo site")	957
<code>mln::Pseudo_Site< void ></code> (<code>Pseudo_Site</code> category flag type)	958
<code>mln::pw::image< F, S ></code> (A generic point-wise image implementation)	958
<code>mln::registration::closest_point_basic< P ></code> (Closest point functor based on map distance)	959
<code>mln::registration::closest_point_with_map< P ></code> (Closest point functor based on map distance)	960
<code>mln::Regular_Grid< E ></code> (Base class for implementation classes of regular grids)	960
<code>mln::safe_image< I ></code> (Makes an image accessible at undefined location)	961
<code>mln::select::p_of< P ></code> (Structure <code>p_of</code>)	961
<code>mln::Site< E ></code> (Base class for classes that are explicitly sites)	962
<code>mln::Site< void ></code> (<code>Site</code> category flag type)	963
<code>mln::Site_Ierator< E ></code> (Base class for implementation of classes of iterator on points)	963
<code>mln::Site_Proxy< E ></code> (Base class for implementation classes of the notion of "site proxy")	965
<code>mln::Site_Proxy< void ></code> (<code>Site_Proxy</code> category flag type)	966
<code>mln::Site_Set< E ></code> (Base class for implementation classes of site sets)	966
<code>mln::Site_Set< void ></code> (<code>Site_Set</code> category flag type)	969
<code>mln::slice_image< I ></code> (2D image extracted from a slice of a 3D image)	969
<code>mln::sub_image< I, S ></code> (<code>Image</code> having its domain restricted by a site set)	972
<code>mln::sub_image_if< I, S ></code> (<code>Image</code> having its domain restricted by a site set and a function)	973
<code>mln::thru_image< I, F ></code> (Morph image values through a function)	975
<code>mln::thrubin_image< I1, I2, F ></code> (Morphes values from two images through a binary function) .	975

mln::topo::adj_higher_dim_connected_n_face_bkd_iter< D > (Backward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>)	977
mln::topo::adj_higher_dim_connected_n_face_fwd_iter< D > (Forward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>)	978
mln::topo::adj_higher_face_bkd_iter< D > (Backward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>)	979
mln::topo::adj_higher_face_fwd_iter< D > (Forward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>)	980
mln::topo::adj_lower_dim_connected_n_face_bkd_iter< D > (Backward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>)	981
mln::topo::adj_lower_dim_connected_n_face_fwd_iter< D > (Forward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>)	982
mln::topo::adj_lower_face_bkd_iter< D > (Backward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>)	984
mln::topo::adj_lower_face_fwd_iter< D > (Forward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>)	985
mln::topo::adj_lower_higher_face_bkd_iter< D > (Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>)	986
mln::topo::adj_lower_higher_face_fwd_iter< D > (Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>)	987
mln::topo::adj_m_face_bkd_iter< D > (Backward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex)	988
mln::topo::adj_m_face_fwd_iter< D > (Forward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex)	989
mln::topo::algebraic_face< D > (Algebraic face handle in a complex; the face dimension is dynamic)	991
mln::topo::algebraic_n_face< N, D > (Algebraic N-face handle in a complex)	996
mln::topo::center_only_iter< D > (Iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>)	1001
mln::topo::centered_bkd_iter_adapter< D, I > (Forward complex relative iterator adapters adding the central (reference) point to the set of iterated faces)	1002
mln::topo::centered_fwd_iter_adapter< D, I > (Backward complex relative iterator adapters adding the central (reference) point to the set of iterated faces)	1003
mln::topo::complex< D > (General complex of dimension D)	1004
mln::topo::face< D > (Face handle in a complex; the face dimension is dynamic)	1007
mln::topo::face_bkd_iter< D > (Backward iterator on all the faces of an mln::complex<D>) .	1012
mln::topo::face_fwd_iter< D > (Forward iterator on all the faces of an mln::complex<D>) .	1013
mln::topo::is_n_face< N > (A functor testing whether a mln::complex_psite is an N-face) . .	1014
mln::topo::is_simple_2d_t< N > (Test if a point is simple or not)	1015
mln::topo::is_simple_cell< I > (A predicate for the simplicity of a point based on the collapse property of the attachment)	1016
mln::topo::n_face< N, D > (N-face handle in a complex)	1019
mln::topo::n_face_bkd_iter< D > (Backward iterator on all the faces of an mln::complex<D>)	1023
mln::topo::n_face_fwd_iter< D > (Forward iterator on all the faces of an mln::complex<D>)	1024
mln::topo::n_faces_set< N, D > (Set of face handles of dimension N)	1026
mln::topo::skeleton::is_simple_point< N >	1027
mln::topo::static_n_face_bkd_iter< N, D > (Backward iterator on all the N-faces of a mln::complex<D>)	1028
mln::topo::static_n_face_fwd_iter< N, D > (Forward iterator on all the N-faces of a mln::complex<D>)	1029

mln::tr_image< S, I, T > (Transform an image by a given transformation)	1030
mln::unproject_image< I, D, F > (Un-projects an image)	1033
mln::util::adjacency_matrix< V > (A class of adjacency matrix)	1035
mln::util::array< T > (A dynamic array class)	1036
mln::util::branch< T > (Class of generic branch)	1043
mln::util::branch_iter< T > (Basic 2D image class)	1044
mln::util::branch_iter_ind< T > (Basic 2D image class)	1046
mln::util::couple< T, U > (Definition of a couple)	1047
mln::util::eat (Eat structure)	1049
mln::util::edge< G > (Edge of a graph G)	1050
mln::util::fibonacci_heap< P, T > (Fibonacci heap)	1054
mln::util::graph (Undirected graph)	1058
mln::util::greater_point< I > (A "greater than" functor comparing points w.r.t)	1065
mln::util::greater_psites< I > (A "greater than" functor comparing psites w.r.t)	1066
mln::util::head< T, R > (Top structure of the soft heap)	1066
mln::util::ignore (Ignore structure)	1067
mln::util::ilcell< T > (Element of an item list. Store the data (key) used in soft_heap)	1067
mln::util::line_graph< G > (Undirected line graph of a graph of type G)	1068
mln::util::nil (Nil structure)	1074
mln::util::node< T, R > (Meta-data of an element in the heap)	1075
mln::util::object_id< Tag, V > (Base class of an object id)	1075
mln::util::ord< T > (Function-object that defines an ordering between objects with type T : <i>lhs</i> R <i>rhs</i>)	1077
mln::util::ord_pair< T > (Ordered pair structure s.a)	1077
mln::util::pix< I > (Structure pix)	1080
mln::util::set< T > (An "efficient" mathematical set class)	1081
mln::util::site_pair< P > (A pair of sites)	1087
mln::util::soft_heap< T, R > (Soft heap)	1089
mln::util::timer (Timer structure)	1092
mln::util::tracked_ptr< T > (Smart pointer for shared data with tracking)	1093
mln::util::tree< T > (Class of generic tree)	1095
mln::util::tree_node< T > (Class of generic tree_node for tree)	1097
mln::util::vertex< G > (Vertex of a graph G)	1102
mln::util::yes (Object that always says "yes")	1107
mln::Value< E > (Base class for implementation classes of values)	1107
mln::value::float01 (Class for floating values restricted to the interval [0..1] and discretized with n bits)	1109
mln::value::float01_f (Class for floating values restricted to the interval [0..1])	1111
mln::value::graylevel< n > (General gray-level class on n bits)	1112
mln::value::graylevel_f (General gray-level class on n bits)	1116
mln::value::int_s< n > (Signed integer value class)	1118
mln::value::int_u< n > (Unsigned integer value class)	1121
mln::value::int_u_sat< n > (Unsigned integer value class with saturation behavior)	1123
mln::value::Integer< E > (Concept of integer)	1125
mln::value::Integer< void > (Category flag type)	1126
mln::value::label< n > (Label value class)	1126
mln::value::lut_vec< S, T > (Class that defines FIXME)	1129
mln::value::proxy< I > (Generic proxy class for an image pixel value)	1133
mln::value::qt::rgb32 (Color class for red-green-blue where every component is n-bit encoded) .	1135
mln::value::rgb< n > (Color class for red-green-blue where every component is n-bit encoded)	1137
mln::value::set< T > (Class that defines the set of values of type T)	1139
mln::value::sign (Value type composed by the set (-1, 0, 1) sign value type is a subset of the int value type)	1140
mln::value::stack_image< n, I > (Stack image class)	1142

<code>mln::value::super_value< sign ></code> (Specializations:)	1145
<code>mln::value::value_array< T, V ></code> (Generic array class over indexed by a value set with type <code>T</code>)	1145
<code>mln::Value_Iterator< E ></code> (Base class for implementation of classes of iterator on values)	1146
<code>mln::Value_Set< E ></code> (Base class for implementation classes of sets of values)	1148
<code>mln::Vertex< E ></code> (<code>Vertex</code> category flag type)	1149
<code>mln::vertex_image< P, V, G ></code> (<code>Image</code> based on graph vertices)	1150
<code>mln::violent_cast_image< T, I ></code> (Violently cast image values to a given type)	1152
<code>mln::w_window< D, W ></code> (Generic <code>w_window</code> class)	1154
<code>mln::Weighted_Window< E ></code> (Base class for implementation classes that are weighted-windows)	1158
<code>mln::win::backdiag2d</code> (Diagonal line window defined on the 2D square grid)	1159
<code>mln::win::ball< G, C ></code> (Generic ball window defined on a given grid)	1160
<code>mln::win::cube3d</code> (Cube window defined on the 3D grid)	1161
<code>mln::win::cuboid3d</code> (Cuboid defined on the 3-D square grid)	1162
<code>mln::win::diag2d</code> (Diagonal line window defined on the 2D square grid)	1164
<code>mln::win::line< M, i, C ></code> (Generic line window defined on a given grid in the given dimension)	1165
<code>mln::win::multiple< W, F ></code> (Multiple window)	1167
<code>mln::win::multiple_size< n, W, F ></code> (Definition of a multiple-size window)	1167
<code>mln::win::octagon2d</code> (Octagon window defined on the 2D square grid)	1168
<code>mln::win::rectangle2d</code> (Rectangular window defined on the 2D square grid)	1169
<code>mln::Window< E ></code> (Base class for implementation classes that are windows)	1170
<code>mln::window< D ></code> (Generic window class)	1171
<code>mln::world::inter_pixel::is_separator</code> (Functor returning whether a site is a separator in an inter-pixel image)	1176
<code>trait::graph< I ></code> (Graph traits)	1177
<code>trait::graph< mln::complex_image< 1, G, V > ></code> (Graph traits for 1-complexes images)	1178
<code>trait::graph< mln::image2d< T > ></code> (Graph traits for <code>mln::image2d</code>)	1178

Chapter 8

Module Documentation

8.1 On site sets

Accumulators working on site sets.

Classes

- struct `mln::accu::center< P, V >`
Mass center accumulator.
- struct `mln::accu::math::count< T >`
Generic counter accumulator.
- struct `mln::accu::shape::bbox< P >`
Generic bounding box accumulator class.
- class `mln::accu::site_set::rectangularity< P >`
Compute the rectangularity of a site set.

8.1.1 Detailed Description

Accumulators working on site sets.

8.2 On images

Accumulators working on images.

Classes

- struct `mln::accu::count_adjacent_vertices< F, S >`
Accumulator class counting the number of vertices adjacent to a set of `mln::p_edges_psite` (i.e., a set of edges).

- struct [mln::accu::max_site< I >](#)
Define an accumulator that computes the first site with the maximum value in an image.
- struct [mln::accu::shape::height< I >](#)
Height accumulator.
- struct [mln::accu::shape::volume< I >](#)
Volume accumulator class.

8.2.1 Detailed Description

Accumulators working on images.

8.3 On values

Accumulators working on image values.

Classes

- struct [mln::accu::convolve< T1, T2, R >](#)
Generic convolution accumulator class.
- struct [mln::accu::count_labels< L >](#)
Count the number of different labels in an image.
- struct [mln::accu::count_value< V >](#)
Define an accumulator that counts the occurrence of a given value.
- struct [mln::accu::histo< V >](#)
Generic histogram class over a value set with type V.
- struct [mln::accu::label_used< L >](#)
References all the labels used.
- struct [mln::accu::logic::land](#)
"Logical-and" accumulator.
- struct [mln::accu::logic::land_basic](#)
"Logical-and" accumulator.
- struct [mln::accu::logic::lor](#)
"Logical-or" accumulator.
- struct [mln::accu::logic::lor_basic](#)
"Logical-or" accumulator class.

- struct `mln::accu::maj_h< T >`
Compute the majority value.
- struct `mln::accu::math::inf< T >`
Generic inf accumulator class.
- struct `mln::accu::math::sum< T, S >`
Generic sum accumulator class.
- struct `mln::accu::math::sup< T >`
Generic sup accumulator class.
- struct `mln::accu::rms< T, V >`
Generic root mean square accumulator class.
- struct `mln::accu::stat::deviation< T, S, M >`
Generic standard deviation accumulator class.
- struct `mln::accu::stat::histo3d_rgb< V >`
Define a histogram as accumulator which returns an `image3d`.
- struct `mln::accu::stat::max< T >`
Generic max accumulator class.
- struct `mln::accu::stat::max_h< V >`
Generic max function based on histogram over a value set with type `V`.
- struct `mln::accu::stat::mean< T, S, M >`
Generic mean accumulator class.
- struct `mln::accu::stat::median_alt< S >`
Generic `median_alt` function based on histogram over a value set with type `S`.
- struct `mln::accu::stat::median_h< V >`
Generic median function based on histogram over a value set with type `V`.
- struct `mln::accu::stat::min< T >`
Generic min accumulator class.
- struct `mln::accu::stat::min_h< V >`
Generic min function based on histogram over a value set with type `V`.
- struct `mln::accu::stat::min_max< V >`
Generic min and max accumulator class.
- struct `mln::accu::stat::rank< T >`
Generic rank accumulator class.
- struct `mln::accu::stat::rank< bool >`
rank accumulator class for Boolean.

- struct [mln::accu::stat::rank_high_quant< T >](#)
Generic rank accumulator class.
- struct [mln::accu::stat::var< T >](#)
Var accumulator class.
- struct [mln::accu::stat::variance< T, S, R >](#)
Variance accumulator class.

8.3.1 Detailed Description

Accumulators working on image values.

8.4 Multiple accumulators

Set of special accumulators for computing several accumulators at the same time.

Classes

- struct [mln::accu::pair< A1, A2, T >](#)
Generic pair of accumulators.
- struct [mln::accu::tuple< A, n, >](#)
Generic tuple of accumulators.

8.4.1 Detailed Description

Set of special accumulators for computing several accumulators at the same time.

8.5 Graphs

All graphs implementations.

Classes

- class [mln::util::graph](#)
Undirected graph.
- class [mln::util::line_graph< G >](#)
Undirected line graph of a graph of type G .

8.5.1 Detailed Description

All graphs implementations.

8.6 Images

All the generic image types provided in Olena.

Modules

- [Basic types](#)

Concrete images.

- [Image morphers](#)

Morpher on both image values and domain.

- [Values morphers](#)

Morpher on image values.

- [Domain morphers](#)

Morpher on image domain.

- [Identity morphers](#)

Morpher adding new functionnalities.

8.6.1 Detailed Description

All the generic image types provided in Olena.

8.7 Basic types

Concrete images.

Classes

- class [mln::complex_image< D, G, V >](#)

Image based on a complex.

- class [mln::edge_image< P, V, G >](#)

Image based on graph edges.

- struct [mln::flat_image< T, S >](#)

Image with a single value.

- struct [mln::image1d< T >](#)

Basic 1D image class.

- class [mln::image2d< T >](#)
Basic 2D image class.
- struct [mln::image2d_h< V >](#)
2d image based on an hexagonal mesh.
- struct [mln::image3d< T >](#)
Basic 3D image class.
- class [mln::pw::image< F, S >](#)
A generic point-wise image implementation.
- class [mln::vertex_image< P, V, G >](#)
Image based on graph vertices.

8.7.1 Detailed Description

Concrete images.

8.8 Image morphers

Morpher on both image values and domain.

Morpher on both image values and domain.

8.9 Values morphers

Morpher on image values.

Classes

- struct [mln::fun_image< F, I >](#)
Image read through a function.
- class [mln::thru_image< I, F >](#)
Morph image values through a function.
- class [mln::thrubin_image< I1, I2, F >](#)
Morphes values from two images through a binary function.
- struct [mln::violent_cast_image< T, I >](#)
Violently cast image values to a given type.

8.9.1 Detailed Description

Morpher on image values.

8.10 Domain morphers

Morpher on image domain.

Classes

- struct [mln::extended< I >](#)
Makes an image become restricted by a point set.
- class [mln::extension_fun< I, F >](#)
Extends the domain of an image with a function.
- class [mln::extension_ima< I, J >](#)
Extends the domain of an image with an image.
- class [mln::extension_val< I >](#)
Extends the domain of an image with a value.
- struct [mln::hexa< I >](#)
hexagonal image class.
- struct [mln::image_if< I, F >](#)
Image which domain is restricted by a function 'site -> Boolean'.
- struct [mln::p2p_image< I, F >](#)
FIXME: Doc!
- struct [mln::slice_image< I >](#)
2D image extracted from a slice of a 3D image.
- class [mln::sub_image< I, S >](#)
Image having its domain restricted by a site set.
- struct [mln::sub_image_if< I, S >](#)
Image having its domain restricted by a site set and a function.
- struct [mln::unproject_image< I, D, F >](#)
Un-projects an image.

8.10.1 Detailed Description

Morpher on image domain.

8.11 Identity morphers

Morpher adding new functionnalities.

Classes

- struct [mln::decorated_image< I, D >](#)
Image that can have additional features.
- class [mln::labeled_image< I >](#)
Morpher providing an improved interface for labeled image.
- struct [mln::lazy_image< I, F, B >](#)
Image values are computed on the fly.
- class [mln::plain< I >](#)
Prevents an image from sharing its data.
- class [mln::safe_image< I >](#)
Makes an image accessible at undefined location.
- struct [mln::tr_image< S, I, T >](#)
Transform an image by a given transformation.

8.11.1 Detailed Description

Morpher adding new functionnalities.

8.12 Types

Milena Object types.

Modules

- [Graphes](#)
All graphes implementations.
- [Images](#)
All the generic image types provided in Olena.
- [Neighborhoods](#)
All the predefined generic neighborhoods.
- [Site sets](#)
All Site set types.

- [Utilities](#)

Miscalleneous useful containers/structures.

- [Windows](#)

All the predefined generic windows.

8.12.1 Detailed Description

Milena Object types.

8.13 Accumulators

All accumulator types.

Modules

- [On site sets](#)

Accumulators working on site sets.

- [On images](#)

Accumulators working on images.

- [On values](#)

Accumulators working on image values.

- [Multiple accumulators](#)

Set of special accumulators for computing several accumulators at the same time.

8.13.1 Detailed Description

All accumulator types.

8.14 Routines

All algorithms/routines provided in Milena.

All algorithms/routines provided in Milena.

8.15 Canvas

All canvas.

All canvas.

8.16 Functions

All predefined functions.

Classes

- struct [mln::Function< E >](#)
Base class for implementation of function-objects.
- struct [mln::Function_n2v< E >](#)
Base class for implementation of function-objects from Nil to value.
- struct [mln::Function_v2b< E >](#)
Base class for implementation of function-objects from a value to a Boolean.
- struct [mln::Function_v2v< E >](#)
Base class for implementation of function-objects from value to value.
- struct [mln::Function_vv2b< E >](#)
Base class for implementation of function-objects from a couple of values to a Boolean.
- struct [mln::Function_vv2v< E >](#)
Base class for implementation of function-objects from a couple of values to a value.

Namespaces

- namespace [mln::fun::i2v](#)
Namespace of integer-to-value functions.
- namespace [mln::fun::n2v](#)
Namespace of functions from nil to value.
- namespace [mln::fun::stat](#)
Namespace of statistical functions.
- namespace [mln::fun::v2i](#)
Namespace of value-to-integer functions.
- namespace [mln::fun::v2v](#)
Namespace of functions from value to value.

Modules

- [v2w2v functions](#)
All bijective functions.

- [v2w_w2v functions](#)

All bijective function.

- [vv2b functions](#)

All functions mapping two values to a logical value.

8.16.1 Detailed Description

All predefined functions.

8.17 Neighborhoods

All the predefined generic neighborhoods.

Modules

- [1D neighborhoods](#)

Predefined 1D neighborhoods.

- [2D neighborhoods](#)

Predefined 2D neighborhoods.

- [3D neighborhoods](#)

Predefined 3D neighborhoods.

8.17.1 Detailed Description

All the predefined generic neighborhoods.

8.18 1D neighborhoods

Predefined 1D neighborhoods.

Typedefs

- [typedef neighb< window1d > mln::neighb1d](#)

Type alias for a neighborhood defined on the 1D square grid with integer coordinates.

Functions

- [const neighb1d & mln::c2 \(\)](#)

2-connectivity neighborhood on the 1D grid.

8.18.1 Detailed Description

Predefined 1D neighborhoods.

8.18.2 Typedef Documentation

8.18.2.1 `typedef neighb<window1d> mln::neighb1d`

Type alias for a neighborhood defined on the 1D square grid with integer coordinates.

Definition at line 47 of file `neighb1d.hh`.

8.18.3 Function Documentation

8.18.3.1 `const neighb1d & mln::c2() [inline]`

2-connectivity neighborhood on the 1D grid.



Returns

A `neighb1d`.

Definition at line 67 of file `neighb1d.hh`.

8.19 2D neighborhoods

Predefined 2D neighborhoods.

Typedefs

- `typedef neighb< window2d > mln::neighb2d`
Type alias for a neighborhood defined on the 2D square grid with integer coordinates.

Functions

- `const neighb2d & mln::c2_col()`
Vertical 2-connectivity neighborhood on the 2D grid.
- `const neighb2d & mln::c2_row()`
Horizontal 2-connectivity neighborhood on the 2D grid.
- `const neighb2d & mln::c4()`
4-connectivity neighborhood on the 2D grid.
- `const neighb2d & mln::c8()`
8-connectivity neighborhood on the 2D grid.

8.19.1 Detailed Description

Predefined 2D neighborhoods.

8.19.2 Typedef Documentation

8.19.2.1 `typedef neighb<window2d> mln::neighb2d`

Type alias for a neighborhood defined on the 2D square grid with integer coordinates.

Definition at line 51 of file core/alias/neighb2d.hh.

8.19.3 Function Documentation

8.19.3.1 `const neighb2d & mln::c2_col() [inline]`

Vertical 2-connectivity neighborhood on the 2D grid.

```
-- o --
-- x --
-- o --
```

Returns

A neighb2d.

Definition at line 190 of file core/alias/neighb2d.hh.

8.19.3.2 `const neighb2d & mln::c2_row() [inline]`

Horizontal 2-connectivity neighborhood on the 2D grid.

```
-- - -
o x o
-- - -
```

Returns

A neighb2d.

Definition at line 176 of file core/alias/neighb2d.hh.

8.19.3.3 `const neighb2d & mln::c4() [inline]`

4-connectivity neighborhood on the 2D grid.

```
-- o --
o x o
-- o --
```

Returns

A `neighb2d`.

Definition at line 148 of file `core/alias/neighb2d.hh`.

8.19.3.4 const neighb2d & mln::c8() [inline]

8-connectivity neighborhood on the 2D grid.

```
o o o
o x o
o o o
```

Returns

A `neighb2d`.

Definition at line 162 of file `core/alias/neighb2d.hh`.

8.20 3D neighborhoods

Predefined 3D neighborhoods.

Typedefs

- `typedef neighb< window3d > mln::neighb3d`

Type alias for a neighborhood defined on the 3D square grid with integer coordinates.

Functions

- `const neighb3d & mln::c18()`
18-connectivity neighborhood on the 3D grid.
- `const neighb3d & mln::c26()`
26-connectivity neighborhood on the 3D grid.
- `const neighb3d & mln::c2_3d_sli()`
depth 2-connectivity neighborhood on the 3D grid.
- `const neighb3d & mln::c4_3d()`
4-connectivity neighborhood on the 3D grid.
- `const neighb3d & mln::c6()`
6-connectivity neighborhood on the 3D grid.
- `const neighb3d & mln::c8_3d()`
8-connectivity neighborhood on the 3D grid.

8.20.1 Detailed Description

Predefined 3D neighborhoods.

8.20.2 Typedef Documentation

8.20.2.1 `typedef neighb<window3d> mln::neighb3d`


Type alias for a neighborhood defined on the 3D square grid with integer coordinates.

Definition at line 50 of file `neighb3d.hh`.

8.20.3 Function Documentation

8.20.3.1 `const neighb3d & mln::c18() [inline]`

18-connectivity neighborhood on the 3D grid.



Returns

A `neighb3d`.


Definition at line 288 of file `neighb3d.hh`.

References `mln::c6()`, `mln::window< D >::insert()`, and `mln::win::sym()`.

Referenced by `mln::c26()`.

8.20.3.2 `const neighb3d & mln::c26() [inline]`

26-connectivity neighborhood on the 3D grid.



o o o

Returns

A neighbor3d.

Definition at line 309 of file neighbor3d.hh.

References mln::c18(), mln::window< D >::insert(), and mln::win::sym().

8.20.3.3 const neighbor3d & mln::c2_3d_sli() [inline]

depth 2-connectivity neighborhood on the 3D grid.

. . .
. o .
. . .

. . .
. x .
. . .

. . .
. o .
. . .

Returns

A neighbor3d.

Definition at line 226 of file neighbor3d.hh.

References mln::window< D >::insert().

8.20.3.4 const neighbor3d & mln::c4_3d() [inline]

4-connectivity neighborhood on the 3D grid.

. . .
. . .
. . .

. o .
o x o
. o .

. . .
. . .
. . .

Returns

A neighbor3d.

Definition at line 241 of file neighb3d.hh.

References mln::window< D >::insert(), and mln::win::sym().

8.20.3.5 const neighb3d & mln::c6() [inline]

6-connectivity neighborhood on the 3D grid.

```
    . . .
    . o .
    . . .

    . o .
o x o
. o .

    . . .
. o .
. . .
```

Returns

A neighb3d.

Definition at line 271 of file neighb3d.hh.

References mln::window< D >::insert(), and mln::win::sym().

Referenced by mln::c18().

8.20.3.6 const neighb3d & mln::c8_3d() [inline]

8-connectivity neighborhood on the 3D grid.

```
    . . .
    . . .
    . . .

    o o o
o x o
o o o

    . . .
. . .
. . .
```

Returns

A neighb3d.

Definition at line 257 of file neighb3d.hh.

8.21 Site sets

All Site set types.

Modules

- [Basic types](#)

Basic site sets.

- [Graph based](#)

Site sets based on a graph.

- [Complex based](#)

Site sets based on a complexes.

- [Sparse types](#)

Sparse site sets.

- [Queue based](#)

Site sets based on a queue.

8.21.1 Detailed Description

All Site set types.

8.22 Basic types

Basic site sets.

Classes

- class [mln::box< P >](#)

Generic box class: site set containing points of a regular grid.

- class [mln::p_line2d](#)

2D discrete line of points.

- class [mln::pMutableArrayOf< S >](#)

pMutableArrayOf is a mutable array of site sets.

- class [mln::pRun< P >](#)

Point set class in run.

8.22.1 Detailed Description

Basic site sets.

8.23 Graph based

Site sets based on a graph.

Classes

- class [mln::p_edges< G, F >](#)
Site set mapping graph edges and image sites.
- struct [mln::p_faces< N, D, P >](#)
A complex psite set based on the N-faces of a complex of dimension D (a D-complex).
- class [mln::p_vertices< G, F >](#)
Site set based mapping graph vertices to sites.

8.23.1 Detailed Description

Site sets based on a graph.

8.24 Complex based

Site sets based on a complexes.

Classes

- class [mln::p_complex< D, G >](#)
A complex psite set based on the N-faces of a complex of dimension D (a D-complex).

8.24.1 Detailed Description

Site sets based on a complexes.

8.25 Sparse types

Sparse site sets.

Classes

- class [mln::p_array< P >](#)
Multi-set of sites.
- class [mln::p_centered< W >](#)
Site set corresponding to a window centered on a site.

- class [mln::p_if< S, F >](#)
Site set restricted w.r.t.
- class [mln::p_image< I >](#)
Site set based on an image of Booleans.
- class [mln::p_set< P >](#)
Mathematical set of sites (based on [util::set](#)).
- class [mln::p_transformed< S, F >](#)
Site set transformed through a function.
- class [mln::p_vaccess< V, S >](#)
Site set in which sites are grouped by their associated value.

8.25.1 Detailed Description

Sparse site sets.

8.26 Queue based

Site sets based on a queue.

Classes

- class [mln::p_key< K, P >](#)
Priority queue class.
- class [mln::p_priority< P, Q >](#)
Priority queue.
- class [mln::p_queue< P >](#)
Queue of sites (based on [std::deque](#)).
- class [mln::p_queue_fast< P >](#)
Queue of sites class (based on [p_array](#).

8.26.1 Detailed Description

Site sets based on a queue.

8.27 Utilities

Miscalleneous useful containers/structures.

Classes

- class `mln::util::adjacency_matrix< V >`
A class of adjacency matrix.
- class `mln::util::array< T >`
A dynamic array class.
- class `mln::util::couple< T, U >`
Definition of a couple.
- struct `mln::util::eat`
Eat structure.
- class `mln::util::fibonacci_heap< P, T >`
Fibonacci heap.
- struct `mln::util::ignore`
Ignore structure.
- struct `mln::util::nil`
Nil structure.
- struct `mln::util::ord_pair< T >`
Ordered pair structure s.a.
- class `mln::util::set< T >`
An "efficient" mathematical set class.
- class `mln::util::site_pair< P >`
A pair of sites.
- class `mln::util::soft_heap< T, R >`
Soft heap.
- struct `mln::util::tracked_ptr< T >`
Smart pointer for shared data with tracking.
- struct `mln::util::yes`
Object that always says "yes".

8.27.1 Detailed Description

Miscalleneous useful containers/structures.

8.28 Windows

All the predefined generic windows.

Modules

- [1D windows](#)

Predefined 1D windows.

- [2D windows](#)

Predefined 2D windows.

- [3D windows](#)

Predefined 3D windows.

- [N-D windows](#)

Predefined N-D windows.

- [Multiple windows](#)

Generic multiple windows.

8.28.1 Detailed Description

All the predefined generic windows.

8.29 1D windows

Predefined 1D windows.

Typedefs

- [typedef line< grid::tick, 0, def::coord > mln::win::segment1d](#)

Segment window defined on the 1D grid.

- [typedef window< mln::dpoint1d > mln::window1d](#)

Type alias for a window with arbitrary shape, defined on the 1D square grid with integer coordinates.

8.29.1 Detailed Description

Predefined 1D windows.

8.29.2 Typedef Documentation

8.29.2.1 [typedef line<grid::tick, 0, def::coord> mln::win::segment1d](#)

Segment window defined on the 1D grid.

An segment1d is centered and symmetric; so its height (length) is odd.

For instance:

○ x ○

is defined with length = 3.

Definition at line 56 of file segment1d.hh.

8.29.2.2 `typedef window<mln::dpoint1d> mln::window1d`

Type alias for a window with arbitrary shape, defined on the 1D square grid with integer coordinates.

Definition at line 47 of file window1d.hh.

8.30 2D windows

Predefined 2D windows.

Classes

- struct `mln::win::backdiag2d`

Diagonal line window defined on the 2D square grid.

- struct `mln::win::diag2d`

Diagonal line window defined on the 2D square grid.

- struct `mln::win::octagon2d`

Octagon window defined on the 2D square grid.

- struct `mln::win::rectangle2d`

Rectangular window defined on the 2D square grid.

Typedefs

- `typedef ball<grid::square, def::coord > mln::win::disk2d`

2D disk window; precisely, ball-shaped window defined on the 2D square grid.

- `typedef line<grid::square, 1, def::coord > mln::win::hline2d`

Horizontal line window defined on the 2D square grid.

- `typedef line<grid::square, 0, def::coord > mln::win::vline2d`

Vertical line window defined on the 2D square grid.

- `typedef window<mln::dpoint2d> mln::window2d`

Type alias for a window with arbitrary shape, defined on the 2D square grid with integer coordinates.

Functions

- const window2d & `mln::win_c4p ()`
4-connectivity window on the 2D grid, including the center.
- const window2d & `mln::win_c8p ()`
8-connectivity window on the 2D grid, including the center.

8.30.1 Detailed Description

Predefined 2D windows.

8.30.2 Typedef Documentation

8.30.2.1 `typedef ball<grid::square, def::coord> mln::win::disk2d`

2D disk window; precisely, ball-shaped window defined on the 2D square grid.

Definition at line 49 of file disk2d.hh.

8.30.2.2 `typedef line<grid::square, 1, def::coord> mln::win::hline2d`

Horizontal line window defined on the 2D square grid.

An hline2d is centered and symmetric; so its height is 1 and its width (length) is odd.

For instance:

○ ○ × ○ ○

is defined with length = 5.

Definition at line 57 of file hline2d.hh.

8.30.2.3 `typedef line<grid::square, 0, def::coord> mln::win::vline2d`

Vertical line window defined on the 2D square grid.

An vline2d is centered and symmetric; so its width is 1 and its height (length) is odd.

For instance:

○
×
○

is defined with length = 3.

Definition at line 58 of file vline2d.hh.

8.30.2.4 `typedef window<mln::dpoint2d> mln::window2d`

Type alias for a window with arbitrary shape, defined on the 2D square grid with integer coordinates.

Definition at line 49 of file `window2d.hh`.

8.30.3 Function Documentation

8.30.3.1 `const window2d & mln::win_c4p() [inline]`

4-connectivity window on the 2D grid, including the center.

```
- o -  
o x o  
- o -
```

Returns

A `window2d`.

Definition at line 105 of file `window2d.hh`.

References `mln::window< D >::insert()`, and `mln::window< D >::size()`.

8.30.3.2 `const window2d & mln::win_c8p() [inline]`

8-connectivity window on the 2D grid, including the center.

```
o o o  
o x o  
o o o
```

Returns

A `window2d`.

Definition at line 121 of file `window2d.hh`.

References `mln::window< D >::insert()`, and `mln::window< D >::size()`.

8.31 3D windows

Predefined 3D windows.

Classes

- struct [mln::win::cube3d](#)

Cube window defined on the 3D grid.

- struct [mln::win::cuboid3d](#)

Cuboid defined on the 3-D square grid.

Typedefs

- **typedef line< grid::cube, 0, def::coord > mln::win::sline3d**
Depth line window defined on the 3D cubic grid.
- **typedef ball< grid::cube, def::coord > mln::win::sphere3d**
3D sphere window; precisely, ball-shaped window defined on the 3D cubic grid.
- **typedef window< mln::dpoint3d > mln::window3d**
Type alias for a window with arbitrary shape, defined on the 3D square grid with integer coordinates.

Functions

- **const window3d & mln::win_c4p_3d ()**
4-connectivity window on the 3D grid, including the center.
- **const window3d & mln::win_c8p_3d ()**
8-connectivity window on the 3D grid, including the center.

8.31.1 Detailed Description

Predefined 3D windows.

8.31.2 Typedef Documentation

8.31.2.1 **typedef line<grid::cube, 0, def::coord> mln::win::sline3d**

Depth line window defined on the 3D cubic grid.

An sline3d is centered and symmetric; so its height and its width are 1 and its depth is odd.

For instance:

```
  . . .
  . o .
  . . .

  . . .
  . x .
  . . .

  . . .
  . o .
  . . .
```

is defined with length = 3.

Definition at line 68 of file sline3d.hh.

8.31.2.2 `typedef ball<grid::cube, def::coord> mln::win::sphere3d`

3D sphere window; precisely, ball-shaped window defined on the 3D cubic grid.

Definition at line 47 of file sphere3d.hh.


8.31.2.3 `typedef window<mln::dpoint3d> mln::window3d`

Type alias for a window with arbitrary shape, defined on the 3D square grid with integer coordinates.

Definition at line 48 of file window3d.hh.

8.31.3 Function Documentation**8.31.3.1 `const window3d & mln::win_c4p_3d() [inline]`**

4-connectivity window on the 3D grid, including the center.

**Returns**


A window3d.

Definition at line 119 of file window3d.hh.

References mln::window< D >::insert(), and mln::window< D >::size().

8.31.3.2 `const window3d & mln::win_c8p_3d() [inline]`

8-connectivity window on the 3D grid, including the center.

**Returns**

A window3d.

Definition at line 135 of file window3d.hh.

References mln::window< D >::insert(), and mln::window< D >::size().

8.32 N-D windows

Predefined N-D windows.

Classes

- struct [mln::win::ball< G, C >](#)
Generic ball window defined on a given grid.
- struct [mln::win::line< M, i, C >](#)
Generic line window defined on a given grid in the given dimension.

8.32.1 Detailed Description

Predefined N-D windows.

8.33 Multiple windows

Generic multiple windows.

Classes

- class [mln::win::multiple< W, F >](#)
Multiple window.
- class [mln::win::multiple_size< n, W, F >](#)
Definition of a multiple-size window.

8.33.1 Detailed Description

Generic multiple windows.

8.34 v2w2v functions

All bijective functions.

All bijective functions.

8.35 v2w_w2v functions

All bijective function.

All bijective function.

8.36 vv2b functions

All functions mapping two values to a logical value.

All functions mapping two values to a logical value.

Chapter 9

Namespace Documentation

9.1 mln Namespace Reference

[mln/convert/to_image.hh](#)

Namespaces

- namespace `accu`
Namespace of accumulators.
- namespace `algebra`
Namespace of algebraic structure.
- namespace `arith`
Namespace of arithmetic.
- namespace `binarization`
Namespace of "point-wise" expression tools.
- namespace `border`
Namespace of routines related to image virtual (outer) border.
- namespace `canvas`
Namespace of canvas.
- namespace `convert`
Namespace of conversion routines.
- namespace `data`
Namespace of image processing routines related to pixel data.
- namespace `debug`
Namespace of routines that help to debug.
- namespace `def`

Namespace for core definitions.

- namespace **display**

Namespace of routines that help to display images.

- namespace **doc**

The namespace `mln::doc` is only for documentation purpose.

- namespace **draw**

Namespace of drawing routines.

- namespace **estim**

Namespace of estimation materials.

- namespace **extension**

Namespace of extension tools.

- namespace **fun**

Namespace of functions.

- namespace **geom**

Namespace of all things related to geometry.

- namespace **graph**

Namespace of graph related routines.

- namespace **grid**

Namespace of grids definitions.

- namespace **histo**

Namespace of histograms.

- namespace **impl**

Implementation namespace of `mln` namespace.

- namespace **io**

Namespace of input/output handling.

- namespace **labeling**

Namespace of labeling routines.

- namespace **linear**

Namespace of linear image processing routines.

- namespace **literal**

Namespace of literals.

- namespace **logical**

Namespace of logic.

- namespace [make](#)
Namespace of routines that help to make Milena's objects.
- namespace [math](#)
Namespace of mathematical routines.
- namespace [metal](#)
Namespace of meta-programming tools.
- namespace [morpho](#)
Namespace of mathematical morphology routines.
- namespace [norm](#)
Namespace of norms.
- namespace [opt](#)
Namespace of optional routines.
- namespace [pw](#)
Namespace of "point-wise" expression tools.
- namespace [registration](#)
Namespace of "point-wise" expression tools.
- namespace [select](#)
Select namespace (FIXME doc).
- namespace [set](#)
Namespace of image processing routines related to pixel sets.
- namespace [subsampling](#)
Namespace of "point-wise" expression tools.
- namespace [tag](#)
Namespace of image processing routines related to tags.
- namespace [test](#)
Namespace of image processing routines related to pixel tests.
- namespace [topo](#)
Namespace of "point-wise" expression tools.
- namespace [trace](#)
Namespace of routines related to the trace mechanism.
- namespace [trait](#)
Namespace where traits are defined.
- namespace [transform](#)
Namespace of transforms.

- namespace [util](#)
Namespace of tools using for more complex algorithm.
- namespace [value](#)
Namespace of materials related to pixel value types.
- namespace [win](#)
Namespace of image processing routines related to win.

Classes

- struct [Accumulator](#)
Base class for implementation of accumulators.
- class [bkd_pixter1d](#)
Backward pixel iterator on a 1-D image with border.
- class [bkd_pixter2d](#)
Backward pixel iterator on a 2-D image with border.
- class [bkd_pixter3d](#)
Backward pixel iterator on a 3-D image with border.
- class [box](#)
Generic box class: site set containing points of a regular grid.
- struct [Box](#)
Base class for implementation classes of boxes.
- class [box_runend_piter](#)
A generic backward iterator on points by lines.
- class [box_runstart_piter](#)
A generic forward iterator on points by lines.
- struct [Browsing](#)
Base class for implementation classes that are browsings.
- struct [category< R\(*\)\(A\) >](#)
Category declaration for a unary C function.
- class [complex_image](#)
Image based on a complex.
- class [complex_neighborhood_bkd_piter](#)
Backward iterator on complex neighborhood.

- class [complex_neighborhood_fwd_piter](#)
Forward iterator on complex neighborhood.
- class [complex_psite](#)
Point site associated to a [mln::p_complex](#).
- class [complex_window_bkd_piter](#)
Backward iterator on complex window.
- class [complex_window_fwd_piter](#)
Forward iterator on complex window.
- struct [decorated_image](#)
Image that can have additional features.
- struct [Delta_Point_Site< void >](#)
Delta point site category flag type.
- struct [dpoint](#)
Generic delta-point class.
- struct [Dpoint](#)
Base class for implementation of delta-point classes.
- class [dpoints_bkd_pixter](#)
A generic backward iterator on the pixels of a dpoint-based window or neighborhood.
- class [dpoints_fwd_pixter](#)
A generic forward iterator on the pixels of a dpoint-based window or neighborhood.
- struct [Edge](#)
edge category flag type.
- class [edge_image](#)
Image based on graph edges.
- struct [extended](#)
Makes an image become restricted by a point set.
- class [extension_fun](#)
Extends the domain of an image with a function.
- class [extension_ima](#)
Extends the domain of an image with an image.
- class [extension_val](#)
Extends the domain of an image with a value.
- class [faces_psite](#)
Point site associated to a [mln::p_faces](#).

- struct [flat_image](#)
Image with a single value.
- struct [fun_image](#)
Image read through a function.
- struct [Function](#)
Base class for implementation of function-objects.
- struct [Function< void >](#)
Function category flag type.
- struct [Function_n2v](#)
Base class for implementation of function-objects from Nil to value.
- struct [Function_v2b](#)
Base class for implementation of function-objects from a value to a Boolean.
- struct [Function_v2v](#)
Base class for implementation of function-objects from value to value.
- struct [Function_vv2b](#)
Base class for implementation of function-objects from a couple of values to a Boolean.
- struct [Function_vv2v](#)
Base class for implementation of function-objects from a couple of values to a value.
- class [fwd_pixter1d](#)
Forward pixel iterator on a 1-D image with border.
- class [fwd_pixter2d](#)
Forward pixel iterator on a 2-D image with border.
- class [fwd_pixter3d](#)
Forward pixel iterator on a 3-D image with border.
- struct [Gdpoint](#)
FIXME: Doc!
- struct [Gdpoint< void >](#)
Delta point site category flag type.
- struct [Gpoint](#)
Base class for implementation of point classes.
- struct [Graph](#)
Base class for implementation of graph classes.
- struct [graph_elt_mixed_neighborhood](#)

Elementary neighborhood on graph class.

- class [graph_elt_mixed_window](#)
Elementary window on graph class.
- struct [graph_elt_neighborhood](#)
Elementary neighborhood on graph class.
- struct [graph_elt_neighborhood_if](#)
Elementary neighborhood_if on graph class.
- class [graph_elt_window](#)
Elementary window on graph class.
- class [graph_elt_window_if](#)
Custom window on graph class.
- class [graph_window_base](#)
- class [graph_window_if_piter](#)
Forward iterator on line graph window.
- class [graph_window_piter](#)
Forward iterator on line graph window.
- struct [hexa](#)
hexagonal image class.
- struct [Image](#)
Base class for implementation of image classes.
- struct [image1d](#)
Basic 1D image class.
- class [image2d](#)
Basic 2D image class.
- struct [image2d_h](#)
2d image based on an hexagonal mesh.
- struct [image3d](#)
Basic 3D image class.
- struct [image_if](#)
Image which domain is restricted by a function 'site -> Boolean'.
- struct [interpolated](#)
Makes the underlying image being accessed with floating coordinates.
- struct [Iterator](#)
Base class for implementation classes that are iterators.

- class [labeled_image](#)
Morpher providing an improved interface for labeled image.
- class [labeled_image_base](#)
Base class Morpher providing an improved interface for labeled image.
- struct [lazy_image](#)
Image values are computed on the fly.
- struct [Literal](#)
Base class for implementation classes of literals.
- struct [Mesh](#)
Base class for implementation classes of meshes.
- struct [Meta_Accumulator](#)
Base class for implementation of meta accumulators.
- struct [Meta_Function](#)
Base class for implementation of meta functions.
- struct [Meta_Function_v2v](#)
Base class for implementation of function-objects from value to value.
- struct [Meta_Function_vv2v](#)
Base class for implementation of function-objects from value to value.
- class [mixed_neighb](#)
Adapter class from window to neighborhood.
- class [neighb](#)
Adapter class from window to neighborhood.
- struct [Neighborhood](#)
Base class for implementation classes that are neighborhoods.
- struct [Neighborhood< void >](#)
Neighborhood category flag type.
- struct [Object](#)
Base class for almost every class defined in Milena.
- struct [p2p_image](#)
FIXME: Doc!
- class [p_array](#)
Multi-set of sites.
- class [p_centered](#)

Site set corresponding to a window centered on a site.

- class [p_complex](#)

A complex psite set based on the N-faces of a complex of dimension D (a D-complex).

- class [p_edges](#)

Site set mapping graph edges and image sites.

- struct [p_faces](#)

A complex psite set based on the N-faces of a complex of dimension D (a D-complex).

- class [p_graph_piter](#)

Generic iterator on point sites of a `mln::S`.

- class [p_if](#)

Site set restricted w.r.t.

- class [p_image](#)

Site set based on an image of Booleans.

- class [p_indexed_bkd_piter](#)

Backward iterator on sites of an indexed site set.

- class [p_indexed_fwd_piter](#)

Forward iterator on sites of an indexed site set.

- class [p_indexed_psite](#)

Psite class for indexed site sets such as [p_array](#).

- class [p_key](#)

Priority queue class.

- class [p_line2d](#)

2D discrete line of points.

- class [p_mutable_array_of](#)

[p_mutable_array_of](#) is a mutable array of site sets.

- class [p_n_faces_bkd_piter](#)

Backward iterator on the n-faces sites of an `mln::p_complex<D, G>`.

- class [p_n_faces_fwd_piter](#)

Forward iterator on the n-faces sites of an `mln::p_complex<D, G>`.

- class [p_priority](#)

Priority queue.

- class [p_queue](#)

Queue of sites (based on `std::deque`).

- class [p_queue_fast](#)
Queue of sites class (based on [p_array](#)).
- class [p_run](#)
Point set class in run.
- class [p_set](#)
Mathematical set of sites (based on [util::set](#)).
- class [p_set_of](#)
p_set_of is a set of site sets.
- class [p_transformed](#)
Site set transformed through a function.
- struct [p_transformed_piter](#)
Iterator on p_transformed<S,F>.
- class [p_vaccess](#)
Site set in which sites are grouped by their associated value.
- class [p_vertices](#)
Site set based mapping graph vertices to sites.
- struct [pixel](#)
Generic pixel class.
- struct [Pixel_Iterator](#)
Base class for the implementation of pixel iterator classes.
- class [plain](#)
Prevents an image from sharing its data.
- struct [point](#)
Generic point class.
- struct [Point](#)
Base class for implementation of point classes.
- struct [Point_Site](#)
Base class for implementation classes of the notion of "point site".
- struct [Point_Site< void >](#)
Point site category flag type.
- struct [Proxy](#)
Base class for implementation classes of the notion of "proxy".
- struct [Proxy< void >](#)
Proxy category flag type.

- struct [Pseudo_Site](#)
Base class for implementation classes of the notion of "pseudo site".
- struct [Pseudo_Site< void >](#)
Pseudo_Site category flag type.
- struct [Regular_Grid](#)
Base class for implementation classes of regular grids.
- class [safe_image](#)
Makes an image accessible at undefined location.
- struct [Site](#)
Base class for classes that are explicitly sites.
- struct [Site< void >](#)
Site category flag type.
- struct [Site_Iterator](#)
Base class for implementation of classes of iterator on points.
- struct [Site_Proxy](#)
Base class for implementation classes of the notion of "site proxy".
- struct [Site_Proxy< void >](#)
Site_Proxy category flag type.
- struct [Site_Set](#)
Base class for implementation classes of site sets.
- struct [Site_Set< void >](#)
Site_Set category flag type.
- struct [slice_image](#)
2D image extracted from a slice of a 3D image.
- class [sub_image](#)
Image having its domain restricted by a site set.
- struct [sub_image_if](#)
Image having its domain restricted by a site set and a function.
- class [thru_image](#)
Morph image values through a function.
- class [thrubin_image](#)
Morphes values from two images through a binary function.
- struct [tr_image](#)

Transform an image by a given transformation.

- struct [unproject_image](#)
Un-projects an image.
- struct [Value](#)
Base class for implementation classes of values.
- struct [Value_Iterator](#)
Base class for implementation of classes of iterator on values.
- struct [Value_Set](#)
Base class for implementation classes of sets of values.
- struct [Vertex](#)
Vertex category flag type.
- class [vertex_image](#)
Image based on graph vertices.
- struct [violent_cast_image](#)
Violently cast image values to a given type.
- struct [w_window](#)
Generic w_window class.
- struct [Weighted_Window](#)
Base class for implementation classes that are weighted_windows.
- class [window](#)
Generic window class.
- struct [Window](#)
Base class for implementation classes that are windows.

Typedefs

- typedef [mln::complex_image< 1, mln::discrete_plane_1complex_geometry, bool > bin_1complex_image2d](#)
Type alias for a binary image based on a 1-complex, where 0-faces are located at discrete (integer) 2-dimensional points.
- typedef [mln::complex_image< 2, mln::space_2complex_geometry, bool > bin_2complex_image3df](#)
Type alias for a binary image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.
- typedef [box< mln::point1d > box1d](#)
Type alias for a box defined on the 1D square grid with integer coordinates.

- **typedef `box< mln::point2d > box2d`**
Type alias for a box defined on the 2D square grid with integer coordinates.
- **typedef `box< point2d_h > box2d_h`**
FIXME.
- **typedef `box< point3d > box3d`**
Type alias for a box defined on the 3D square grid with integer coordinates.
- **typedef `mln::geom::complex_geometry< 1, point2d > discrete_plane_1complex_geometry`**
Type alias for the geometry of a 1-complex (e.g., a graph) located in a discrete 2-dimensional plane (with integer coordinates).
- **typedef `mln::geom::complex_geometry< 2, point2d > discrete_plane_2complex_geometry`**
Type alias for the geometry of a 2-complex located in a discrete 2-dimensional plane (with integer coordinates).
- **typedef `dpoint< mln::grid::tick, def::coord > dpoint1d`**
Type alias for a delta-point defined on the 1D square grid with integer coordinates.
- **typedef `dpoint< mln::grid::square, mln::def::coord > dpoint2d`**
Type alias for a delta-point defined on the 2D square grid with integer coordinates.
- **typedef `dpoint< mln::grid::hexa, def::coord > dpoint2d_h`**
Type alias for a delta-point defined on the 2D square grid with integer coordinates.
- **typedef `dpoint< mln::grid::cube, def::coord > dpoint3d`**
Type alias for a delta-point defined on the 3D square grid with integer coordinates.
- **typedef `mln::complex_image< 2, mln::space_2complex_geometry, float > float_2complex_image3df`**
Type alias for a floating-point image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.
- **typedef `mln::complex_image< 1, mln::discrete_plane_1complex_geometry, mln::value::int_u8 > int_u8_1complex_image2d`**
Type alias for an 8-bit gray-level image based on a 1-complex, where 0-faces are located at discrete (integer) 2-dimensional points.
- **typedef `mln::complex_image< 2, mln::discrete_plane_2complex_geometry, mln::value::int_u8 > int_u8_2complex_image2d`**
Type alias for an 8-bit gray-level image based on a 2-complex, where 0-faces are located at discrete (integer) 2-dimensional points.
- **typedef `mln::complex_image< 2, mln::space_2complex_geometry, mln::value::int_u8 > int_u8_2complex_image3df`**
Type alias for an 8-bit gray-level image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.
- **typedef `neighb< window1d > neighb1d`**

Type alias for a neighborhood defined on the 1D square grid with integer coordinates.

- **typedef `neighb< window2d > neighb2d`**

Type alias for a neighborhood defined on the 2D square grid with integer coordinates.

- **typedef `neighb< window3d > neighb3d`**

Type alias for a neighborhood defined on the 3D square grid with integer coordinates.

- **typedef `p_run< point2d > p_run2d`**

Type alias for a run of 2d points.

- **typedef `p_set_of< p_run2d > p_runs2d`**

Type alias for a set of runs of 2d points.

- **typedef `point< grid::tick, def::coordf > point1df`**

Type alias for a point defined on the 1D ruler with floating-point coordinates.

- **typedef `point< mln::grid::square, mln::def::coordf > point2df`**

Type alias for a point defined on the 2D square grid with floating-point coordinates.

- **typedef `point< grid::cube, def::coordf > point3df`**

Type alias for a point defined on the 3D square grid with floating-point coordinates.

- **typedef `mln::complex_image< 2, mln::space_2complex_geometry, mln::value::rgb8 > rgb8_-2complex_image3df`**

Type alias for a (3x8-bit) RGB image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

- **typedef `mln::geom::complex_geometry< 2, point3df > space_2complex_geometry`**

Type alias for the geometry of a 2-complex located in a 3-dimensional space (with floating-point coordinates).

- **typedef `mln::complex_image< 2, mln::space_2complex_geometry, unsigned > unsigned_-2complex_image3df`**

Type alias for a gray-level image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

- **typedef `algebra::vec< 2u, double > vec2d_d`**

2D vector with double coordinates.

- **typedef `algebra::vec< 2u, float > vec2d_f`**

2D vector with float coordinates.

- **typedef `algebra::vec< 3u, double > vec3d_d`**

3D vector with double coordinates.

- **typedef `algebra::vec< 3u, float > vec3d_f`**

3D vector with float coordinates.

- **typedef `w_window< dpoint1d, float > w_window1d_float`**

Type alias for a [w_window](#) with arbitrary shape, defined on the 1D grid (with integer coordinates) and whose weights are floating values.

- `typedef w_window< dpoint1d, int > w_window1d_int`

Type alias for a [w_window](#) with arbitrary shape, defined on the 1D grid (with integer coordinates) and whose weights are integers.

- `typedef w_window< dpoint2d, float > w_window2d_float`

Type alias for a [w_window](#) with arbitrary shape, defined on the 2D square grid (with integer coordinates) and whose weights are floating values.

- `typedef w_window< dpoint2d, int > w_window2d_int`

Type alias for a [w_window](#) with arbitrary shape, defined on the 2D square grid (with integer coordinates) and whose weights are integers.

- `typedef w_window< dpoint3d, float > w_window3d_float`

Type alias for a [w_window](#) with arbitrary shape, defined on the 3D grid (with integer coordinates) and whose weights are floating values.

- `typedef w_window< dpoint3d, int > w_window3d_int`

Type alias for a [w_window](#) with arbitrary shape, defined on the 3D grid (with integer coordinates) and whose weights are integers.

- `typedef window< mln::dpoint1d > window1d`

Type alias for a window with arbitrary shape, defined on the 1D square grid with integer coordinates.

- `typedef window< mln::dpoint2d > window2d`

Type alias for a window with arbitrary shape, defined on the 2D square grid with integer coordinates.

- `typedef window< mln::dpoint3d > window3d`

Type alias for a window with arbitrary shape, defined on the 3D square grid with integer coordinates.

- `typedef point< grid::tick, def::coord > point1d`

Type alias for a point defined on the 1D ruler with integer coordinates.

- `typedef point< mln::grid::square, mln::def::coord > point2d`

Type alias for a point defined on the 2D square grid with integer coordinates.

- `typedef point< grid::hexa, def::coord > point2d_h`

Type alias for a point defined on the 2D hexagonal grid with integer coordinates.

- `typedef point< grid::cube, def::coord > point3d`

Type alias for a point defined on the 3D square grid with integer coordinates.

Functions

- `template<typename I >`
`I::psite a_point_of (const Image< I > &ima)`

Give a point of an image.

- template<typename I , typename F >
`p2p_image< I, F > apply_p2p (Image< I > &ima, const Function_v2v< F > &f)`
FIXME: Doc!
- template<typename I , typename F >
`p2p_image< const I, F > apply_p2p (const Image< I > &ima, const Function_v2v< F > &f)`
FIXME: Doc!
- const `neighb3d & c18 ()`
18-connectivity neighborhood on the 3D grid.
- const `neighb1d & c2 ()`
2-connectivity neighborhood on the 1D grid.
- const `neighb3d & c26 ()`
26-connectivity neighborhood on the 3D grid.
- const `neighb3d & c2_3d_sli ()`
depth 2-connectivity neighborhood on the 3D grid.
- const `neighb2d & c2_col ()`
Vertical 2-connectivity neighborhood on the 2D grid.
- const `neighb2d & c2_row ()`
Horizontal 2-connectivity neighborhood on the 2D grid.
- const `neighb2d & c4 ()`
4-connectivity neighborhood on the 2D grid.
- const `neighb3d & c4_3d ()`
4-connectivity neighborhood on the 3D grid.
- const `neighb3d & c6 ()`
6-connectivity neighborhood on the 3D grid.
- const `neighb2d & c8 ()`
8-connectivity neighborhood on the 2D grid.
- const `neighb3d & c8_3d ()`
8-connectivity neighborhood on the 3D grid.
- template<typename T2 , typename T1 >
`fun::x2x::composed< T2, T1 > compose (T2 f, T1 g)`
Do a composition of two transformations.
- template<typename I >
`mln::trait::concrete< I >::ret duplicate (const Image< I > &model)`
Duplicate the image model with the values of the image data.

- template<typename I , typename F >
extension_fun< const I, F > **extend** (const **Image**< I > &ima, const **Function_v2v**< F > &fun)
Routines for domain extension with a function.
- template<typename I , typename J >
extension_ima< const I, const J > **extend** (const **Image**< I > &ima, const **Image**< J > &ext)
Routines for domain extension with an image.
- template<typename I >
extension_val< const I > **extend** (const **Image**< I > &ima, const typename I::value &val)
Routines for domain extension with a value.
- bool **implies** (bool leexpr, bool rexpr)
Implication.
- template<typename I , typename J >
void **initialize** (**Image**< I > &target, const **Image**< J > &model)
- template<typename P >
box< P > **larger_than** (const **box**< P > a, const **box**< P > b)
Return the minimum box including box a and box b.
- template<typename I , typename V , typename E >
image2d< typename I::value > **make_debug_graph_image** (const I &input, const V &ima_v, const E &ima_e, const **value::rgb8** &bg)
Draw a graph.
- **mln_gen_complex_neighborhood** (complex_higher_dim_connected_n_face_neighborhood, complex_higher_dim_connected_n_face_window)
Neighborhood centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face.
- **mln_gen_complex_neighborhood** (complex_m_face_neighborhood, complex_m_face_window)
Neighborhood centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face.
- **mln_gen_complex_neighborhood** (complex_lower_neighborhood, complex_lower_window)
Neighborhood centered on an n-face of complex returning its adjacent (n-1)-faces.
- **mln_gen_complex_neighborhood** (complex_higher_neighborhood, complex_higher_window)
Neighborhood centered on an n-face of complex returning its adjacent (n+1)-faces.
- **mln_gen_complex_neighborhood** (complex_lower_higher_neighborhood, complex_lower_higher_window)
Neighborhood centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces.
- **mln_gen_complex_neighborhood** (complex_lower_dim_connected_n_face_neighborhood, complex_lower_dim_connected_n_face_window)
Neighborhood centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face.

- `mln_gen_complex_window` (`complex_lower_window`, `topo::adj_lower_face_fwd_iter`, `topo::adj_lower_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n-1)-faces.
- `mln_gen_complex_window` (`complex_higher_window`, `topo::adj_higher_face_fwd_iter`, `topo::adj_higher_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n+1)-faces.
- `mln_gen_complex_window` (`complex_lower_higher_window`, `topo::adj_lower_higher_face_fwd_iter`, `topo::adj_lower_higher_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces.
- `mln_gen_complex_window` (`complex_lower_dim_connected_n_face_window`, `topo::adj_lower_dim_connected_n_face_fwd_iter`, `topo::adj_lower_dim_connected_n_face_bkd_iter`)
Window centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face.
- `mln_gen_complex_window` (`complex_higher_dim_connected_n_face_window`, `topo::adj_higher_dim_connected_n_face_fwd_iter`, `topo::adj_higher_dim_connected_n_face_bkd_iter`)
Window centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face.
- `mln_gen_complex_window` (`complex_m_face_window`, `topo::adj_m_face_fwd_iter`, `topo::adj_m_face_bkd_iter`)
Window centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face.
- `mln_gen_complex_window_p` (`complex_lower_window_p`, `topo::adj_lower_face_fwd_iter`, `topo::adj_lower_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n-1)-faces as well as the center n-face.
- `mln_gen_complex_window_p` (`complex_higher_window_p`, `topo::adj_higher_face_fwd_iter`, `topo::adj_higher_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n+1)-faces as well as the center n-face.
- `mln_gen_complex_window_p` (`complex_lower_higher_window_p`, `topo::adj_lower_higher_face_fwd_iter`, `topo::adj_lower_higher_face_bkd_iter`)
Window centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces as well as the center n-face.
- `mln_gen_complex_window_p` (`complex_lower_dim_connected_n_face_window_p`, `topo::adj_lower_dim_connected_n_face_fwd_iter`, `topo::adj_lower_dim_connected_n_face_bkd_iter`)
Window centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face, as well as this center n-face.
- `mln_gen_complex_window_p` (`complex_higher_dim_connected_n_face_window_p`, `topo::adj_higher_dim_connected_n_face_fwd_iter`, `topo::adj_higher_dim_connected_n_face_bkd_iter`)
Window centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face, as well as this center n-face.
- `mln_gen_complex_window_p` (`complex_m_face_window_p`, `topo::adj_m_face_fwd_iter`, `topo::adj_m_face_bkd_iter`)
Window centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face, as well as this center n-face.

- template<typename W1 , typename W2 >
mln_regular (W1) operator-(const **Window**< W1 > &win1
Set difference between a couple of windows win1 and win2.
- template<typename O1 , typename O2 >
mln_trait_op_geq (O1, O2) operator>
General definition of the "greater than or equal to" operator.
- template<typename O1 , typename O2 >
mln_trait_op_greater (O1, O2) operator>(const **Object**< O1 > &lhs
General definition of the "greater than" operator.
- template<typename O1 , typename O2 >
mln_trait_op_leq (O1, O2) operator<
Default definition of the "less than or equal to" operator.
- template<typename O1 , typename O2 >
mln_trait_op_neq (O1, O2) operator!
General definition of the "not equal to" operator.
- template<typename P , typename S >
P operator* (const **Gpoint**< P > &p, const value::scalar_< S > &s)
Multiply a point p by a scalar s.
- template<typename S >
S & operator++ (value::Scalar< S > &rhs)
Pre-incrementation for any scalar type.
- template<typename P , typename D >
P operator- (const **Gpoint**< P > &p, const **Gdpoint**< D > &dp)
Subtract a delta-point dp to a grid point p.
- template<typename N1 , typename N2 >
neighb< typename N1::window::regular > operator- (const **Neighborhood**< N1 > &ngh1, const **Neighborhood**< N2 > &ngh2)
Set difference between a couple of neighborhoods ngh1 and ngh2.
- template<typename S >
S & operator-- (value::Scalar< S > &rhs)
Pre-decrementation for any scalar type.
- template<typename L , typename R >
bool operator< (const **Image**< L > &lhs, const **Image**< R > &rhs)
Point-wise test if the pixel values of lhs are point-wise less than the pixel values of rhs.
- template<typename I , typename G , typename W >
std::ostream & operator<< (std::ostream &os, const **complex_window_fwd_piter**< I, G, W > &p)
*Print an **mln::complex_window_fwd_piter**.*

- template<typename I , typename G , typename W >
`std::ostream & operator<< (std::ostream &os, const complex_window_bkd_piter< I, G, W > &p)`
Print an [mln::complex_window_bkd_piter](#).

- template<typename I , typename G , typename N >
`std::ostream & operator<< (std::ostream &os, const complex_neighborhood_fwd_piter< I, G, N > &p)`
Print an [mln::complex_neighborhood_fwd_piter](#).

- template<typename I , typename G , typename N >
`std::ostream & operator<< (std::ostream &os, const complex_neighborhood_bkd_piter< I, G, N > &p)`
Print an [mln::complex_neighborhood_bkd_piter](#).

- template<unsigned N, unsigned D, typename P >
`bool operator<= (const p_faces< N, D, P > &lhs, const p_faces< N, D, P > &rhs)`
Inclusion of a [mln::p_faces](#) in another one.

- template<typename G , typename F >
`bool operator<= (const p_edges< G, F > &lhs, const p_edges< G, F > &rhs)`
Inclusion of a [mln::p_edges](#) in another one.

- template<typename L , typename R >
`bool operator<= (const Image< L > &lhs, const Image< R > &rhs)`
Point-wise test if the pixel values of `lhs` are point-wise less than or equal to the pixel values of `rhs`.

- template<unsigned D, typename G >
`bool operator<= (const p_complex< D, G > &lhs, const p_complex< D, G > &rhs)`
Inclusion of a [mln::p_complex](#) in another one.

- template<typename G , typename F >
`bool operator<= (const p_vertices< G, F > &lhs, const p_vertices< G, F > &rhs)`
Inclusion of a [mln::p_vertices](#) in another one.

- template<typename G , typename F >
`bool operator<= (const p_edges< G, F > &lhs, const p_edges< G, F > &rhs)`
Comparison between two [mln::p_edges](#)'s.

- template<typename L , typename R >
`bool operator== (const Image< L > &lhs, const Image< R > &rhs)`
Point-wise test if the pixel values of `lhs` are equal to the pixel values of `rhs`.

- template<unsigned D, typename G >
`bool operator== (const p_complex< D, G > &lhs, const p_complex< D, G > &rhs)`
Comparison between two [mln::p_complex](#)'s.

- template<unsigned N, unsigned D, typename P >
`bool operator== (const p_faces< N, D, P > &lhs, const p_faces< N, D, P > &rhs)`
Comparison between two [mln::p_faces](#)'s.

- template<typename G , typename F >
`bool operator== (const p_vertices< G, F > &lhs, const p_vertices< G, F > &rhs)`
Comparison between two `mln::p_vertices`'s.

- template<typename I , typename F >
`image_if< I, F > operator| (Image< I > &ima, const Function_v2b< F > &f)`
ima | f creates an `image_if` with the image ima and the function f.

- template<typename V , typename G , typename P >
`edge_image< P, V, G > operator| (const fun::i2v::array< V > &edge_values, const p_edges< G, fun::i2v::array< P > > &pe)`
Construct a edge image from a `fun::i2v::array` and a `p_edges`.

- template<typename S , typename F >
`p_if< S, F > operator| (const Site_Set< S > &s, const Function_v2b< F > &f)`
Restrict a site set s to points that verify f.

- template<typename F , typename S >
`pw::image< F, S > operator| (const Function_v2v< F > &f, const Site_Set< S > &ps)`
Construct an image from a function and a site set.

- template<typename I , typename F >
`image_if< const I, F > operator| (const Image< I > &ima, const Function_v2b< F > &f)`
ima | f creates an `image_if` with the image ima and the function f.

- template<typename V , typename G , typename P >
`vertex_image< P, V, G > operator| (const fun::i2v::array< V > &vertex_values, const p_vertices< G, fun::i2v::array< P > > &pv)`
Construct a vertex image from a `fun::i2v::array` and a `p_vertices`.

- template<typename I >
`const internal::primary_type< I >::ret & primary (const Image< I > &input)`
FIXME: Doc!

- template<typename S , typename F >
`p_transformed< S, F > ptransform (const Site_Set< S > &s, const Function_v2v< F > &f)`
Transform a site set s through the function f.

- const `window2d & win_c4p ()`
4-connectivity window on the 2D grid, including the center.

- const `window3d & win_c4p_3d ()`
4-connectivity window on the 3D grid, including the center.

- const `window2d & win_c8p ()`
8-connectivity window on the 2D grid, including the center.

- const `window3d & win_c8p_3d ()`
8-connectivity window on the 3D grid, including the center.

- template<unsigned N, unsigned D, typename P >
 bool **operator==** (const **faces_psite**< N, D, P > &lhs, const **faces_psite**< N, D, P > &rhs)
Comparison of two instances of [mln::faces_psite](#).
- template<unsigned N, unsigned D, typename P >
 bool **operator!=** (const **faces_psite**< N, D, P > &lhs, const **faces_psite**< N, D, P > &rhs)
Is lhs equal to rhs?
- template<unsigned N, unsigned D, typename P >
 bool **operator<** (const **faces_psite**< N, D, P > &lhs, const **faces_psite**< N, D, P > &rhs)
Is lhs “less” than rhs?

- template<typename T >
mln_exact (T)*exact(T *ptr)
Exact cast routine for mln objects.

- template<unsigned D, typename G >
 bool **operator==** (const **complex_psite**< D, G > &lhs, const **complex_psite**< D, G > &rhs)
Comparison of two instances of [mln::complex_psite](#).
- template<unsigned D, typename G >
 bool **operator!=** (const **complex_psite**< D, G > &lhs, const **complex_psite**< D, G > &rhs)
Is lhs not equal to rhs?
- template<unsigned D, typename G >
 bool **operator<** (const **complex_psite**< D, G > &lhs, const **complex_psite**< D, G > &rhs)
Is lhs “less” than rhs?

Variables

- const **dpoint1d before = dpoint1d(-1)**
Definition of a shortcut for delta point in 1d.
- const **dpoint2d up = dpoint2d(-1, 0)**
Definition of a shortcut for delta point in 2d.
- const **dpoint3d sagittal_dec = dpoint3d(0, 0, -1)**
Definition of a shortcut for delta point in 3d.

9.1.1 Detailed Description

[mln/convert/to_image.hh](#) This implementation is not an usual heap, it allows to set an error rate so that some nodes may be "corrupted".

Generic class for hierarchical queues.

Merge with [mln/topo/skeleton/is_simple_point.hh](#) The fastest version give an approximation of the result.

The generic dual input tree algorithm for high quantized image.

The dual input tree algorithm specialized for low quantized image.

[mln/linear/convolve_directional.hh](#)

Read AVS header from a file.

Define a function which aborts a process in io module.

Forward declaration.

[mln/core/def/all.hh](#)

The namespace mln corresponds to the Milena (mini-Olena) project.

This accumulator uses an [mln::util::pix](#) (pixel) to update the reference level, area and volume information of the component.

The class mln/accu/volume is not a general-purpose accumulator; it is used to implement volume-based connected filters.

See also

[mln::morpho::closing::volume](#)
[mln::morpho::opening::volume](#)

The functor should provide the following methods:

- template <typename g>=""> void init(const Graph<G>& g) Will be called at the beginning.
- bool to_be_treated(unsigned id) Return whether this vertex has already been marked or if it may be a component representative.
- void new_component_from_vertex(unsigned id) will be called for the first vertex encountered for each component.
- void process_vertex(unsigned id) Will be called for each vertex queued.
- bool to_be_queued(unsigned id) Return whether this vertex has already been marked or if it can be added to the current component.
- void added_to_queue(unsigned id) Will be called for every vertex encountered in each component, except the first one.
- void next_component() Will be called after all vertices from a component have been treated.
- void final() Will be called at the end;

Conversions to [mln::Image](#).

FIXME: Re-write this description.

The contents of mln mimics the contents of the olena project but in a simplified way. Some classes have the same name in both projects and roughly have the same behavior.

Warning

The Milena project is independent from the Olena project; the user has to choose between both the project she wants to work with.

File that includes all core definitions.

The set of operators defined in this file is:

```

l += r : l = l + r, -> l&
l -= r : l = l - r, -> l&
l *= r : l = l * r, -> l&
l /= r : l = l / r, -> l&
l %= r : l = l % r, -> l&

+ r      : -> r
- r      : -> (0 - r)

l ++
l --
++ r    : r += 1, -> r&
-- r    : r -= 1, -> r&

l != r  : -> !(l == r)

l > r   : -> (r < l)
l >= r  : -> (r <= l)
l <= r  : -> ! (r < l)  warning: re-define when partial ordering

```

As a consequence, the set of operators to be defined along with a client class is:

```

l + r
l - r
l * r
l / r

l == r

l < r
l <= r  in case of partial ordering

```

Convolution by a line-shaped (directional) kernel.

This implementation is based on P. Salembier algorithm using hierarchical queues. This implies a low-quantized input image so that the number of queues is limited.

TODO: Think about how to extend f domain in a more generic way. The actual implementation doubles the size of the first dimension. It implies a boxed domain.

TODO: Use the less functor. The actual implementation is for max-tree.

TODO: During the canonization pass, we build the tree site set from the sorted site set of f, so that we compute twice f histogram (can be avoided).

This implementation is based on tarjan's union method, so that image quantization does not impact on the computation time.

TODO: Think about how to extend f domain in a more generic way. The actual implementation doubles the size of the first dimension. It implies a boxed domain.

TODO: Use the less functor. The actual implementation is for max-tree.

Do we want it to be exact?

Hierarchical queues are often used with connected operators (P. Salembier's max tree algorithm relies on these queues). To be efficient, the hierarchy is a static array and each are preallocated using an histogram.

FIXME: consider hqueues as a site set ?

A "corrupted node" means that its correct order is not totally preserved for performance reasons. Of course, it will have an impact on the returned values. As a result, be ware of not using this data structure if the element order is relevant for to you.

A corruption threshold can be passed to the constructor. This threshold means that if nodes have a rank higher than this threshold they can be "corrupted" and therefore their rank can be reduced. Tuning this threshold may have an impact on the structure entropy thus on the returned values order. It may also have an impact on the performance.

More implementation details are available in: "The soft heap: an approximate priority queue with optimal error rate", Bernard Chazelle, JACM, 2000.

URL: <http://www.cs.princeton.edu/~chazelle/pubs/sheap.pdf>

9.1.2 Typedef Documentation

9.1.2.1 `typedef mln::complex_image<1, mln::discrete_plane_1complex_geometry, bool>` `mln::bin_1complex_image2d`

Type alias for a binary image based on a 1-complex, where 0-faces are located at discrete (integer) 2-dimensional points.

Definition at line 53 of file mln/core/alias/complex_image.hh.

9.1.2.2 `typedef mln::complex_image<2, mln::space_2complex_geometry, bool>` `mln::bin_2complex_image3df`

Type alias for a binary image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

Definition at line 85 of file mln/core/alias/complex_image.hh.

9.1.2.3 `typedef box<mln::point1d> mln::box1d`

Type alias for a box defined on the 1D square grid with integer coordinates.

See also

[mln::win::rectangle1d](#).

Definition at line 47 of file core/alias/box1d.hh.

9.1.2.4 `typedef box<mln::point2d> mln::box2d`

Type alias for a box defined on the 2D square grid with integer coordinates.

See also

[mln::win::rectangle2d](#).

Definition at line 45 of file core/alias/box2d.hh.

9.1.2.5 `typedef box<point2d_h> mln::box2d_h`

FIXME.

Definition at line 47 of file core/alias/box2d_h.hh.

9.1.2.6 `typedef box<point3d> mln::box3d`

Type alias for a box defined on the 3D square grid with integer coordinates.

See also

`mln::win::rectangle3d`.

Definition at line 45 of file core/alias/box3d.hh.

9.1.2.7 `typedef mln::geom::complex_geometry<1, point2d> mln::discrete_plane_1complex_-geometry`

Type alias for the geometry of a 1-complex (e.g., a graph) located in a discrete 2-dimensional plane (with integer coordinates).

Definition at line 45 of file core/alias/complex_geometry.hh.

9.1.2.8 `typedef mln::geom::complex_geometry<2, point2d> mln::discrete_plane_2complex_-geometry`

Type alias for the geometry of a 2-complex located in a discrete 2-dimensional plane (with integer coordinates).

Definition at line 50 of file core/alias/complex_geometry.hh.

9.1.2.9 `typedef dpoint<mln::grid::tick, def::coord> mln::dpoint1d`

Type alias for a delta-point defined on the 1D square grid with integer coordinates.

Definition at line 44 of file dpoint1d.hh.

9.1.2.10 `typedef dpoint<mln::grid::square, mln::def::coord> mln::dpoint2d`

Type alias for a delta-point defined on the 2D square grid with integer coordinates.

Definition at line 44 of file dpoint2d.hh.

9.1.2.11 `typedef dpoint<mln::grid::hexa, def::coord> mln::dpoint2d_h`

Type alias for a delta-point defined on the 2D square grid with integer coordinates.

Definition at line 45 of file core/alias/dpoint2d_h.hh.

9.1.2.12 `typedef dpoint<mln::grid::cube, def::coord> mln::dpoint3d`

Type alias for a delta-point defined on the 3D square grid with integer coordinates.

Definition at line 43 of file dpoint3d.hh.

9.1.2.13 `typedef mln::complex_image<2, mln::space_2complex_geometry, float> mln::float_2complex_image3df`

Type alias for a floating-point image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

Definition at line 106 of file mln/core/alias/complex_image.hh.

9.1.2.14 `typedef mln::complex_image<1, mln::discrete_plane_1complex_geometry, mln::value::int_u8> mln::int_u8_1complex_image2d`

Type alias for an 8-bit gray-level image based on a 1-complex, where 0-faces are located at discrete (integer) 2-dimensional points.

Definition at line 61 of file mln/core/alias/complex_image.hh.

9.1.2.15 `typedef mln::complex_image<2, mln::discrete_plane_2complex_geometry, mln::value::int_u8> mln::int_u8_2complex_image2d`

Type alias for an 8-bit gray-level image based on a 2-complex, where 0-faces are located at discrete (integer) 2-dimensional points.

Definition at line 74 of file mln/core/alias/complex_image.hh.

9.1.2.16 `typedef mln::complex_image<2, mln::space_2complex_geometry, mln::value::int_u8> mln::int_u8_2complex_image3df`

Type alias for an 8-bit gray-level image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

Definition at line 92 of file mln/core/alias/complex_image.hh.

9.1.2.17 `typedef p_run<point2d> mln::p_run2d`

Type alias for a run of 2d points.

Definition at line 42 of file p_run2d.hh.

9.1.2.18 `typedef p_set_of<p_run2d> mln::p_runs2d`

Type alias for a set of runs of 2d points.

Definition at line 42 of file p_runs2d.hh.

9.1.2.19 `typedef point< grid::tick, def::coord > mln::point1d`

Type alias for a point defined on the 1D ruler with integer coordinates.

Definition at line 45 of file point1d.hh.

9.1.2.20 `typedef point<grid::tick, def::coordf> mln::point1df`

Type alias for a point defined on the 1D ruler with floating-point coordinates.

Definition at line 49 of file point1d.hh.

9.1.2.21 `typedef point< grid::square, def::coord > mln::point2d`

Type alias for a point defined on the 2D square grid with integer coordinates.

Definition at line 45 of file point2d.hh.

9.1.2.22 `typedef point< grid::hexa, def::coord > mln::point2d_h`

Type alias for a point defined on the 2D hexagonal grid with integer coordinates.

Definition at line 43 of file core/alias/point2d_h.hh.

9.1.2.23 `typedef point<mln::grid::square, mln::def::coordf> mln::point2df`

Type alias for a point defined on the 2D square grid with floating-point coordinates.

Definition at line 49 of file point2d.hh.

9.1.2.24 `typedef point< grid::cube, def::coord > mln::point3d`

Type alias for a point defined on the 3D square grid with integer coordinates.

Definition at line 44 of file point3d.hh.

9.1.2.25 `typedef point<grid::cube, def::coordf> mln::point3df`

Type alias for a point defined on the 3D square grid with floating-point coordinates.

Definition at line 48 of file point3d.hh.

9.1.2.26 `typedef mln::complex_image<2, mln::space_2complex_geometry, mln::value::rgb8> mln::rgb8_2complex_image3df`

Type alias for a (3x8-bit) RGB image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

Definition at line 113 of file mln/core/alias/complex_image.hh.

9.1.2.27 `typedef mln::geom::complex_geometry<2, point3df> mln::space_2complex_geometry`

Type alias for the geometry of a 2-complex located in a 3-dimensional space (with floating-point coordinates).

Definition at line 54 of file core/alias/complex_geometry.hh.

9.1.2.28 `typedef mln::complex_image<2, mln::space_2complex_geometry, unsigned> mln::unsigned_2complex_image3df`

Type alias for a gray-level image based on a 2-complex, where 0-faces are located at floating-point 3-dimensional points.

Definition at line 99 of file mln/core/alias/complex_image.hh.

9.1.2.29 `typedef algebra::vec<2u,double> mln::vec2d_d`

2D vector with double coordinates.

Definition at line 43 of file vec2d.hh.

9.1.2.30 `typedef algebra::vec<2u,float> mln::vec2d_f`

2D vector with float coordinates.

Definition at line 40 of file vec2d.hh.

9.1.2.31 `typedef algebra::vec<3u,double> mln::vec3d_d`

3D vector with double coordinates.

Definition at line 43 of file vec3d.hh.

9.1.2.32 `typedef algebra::vec<3u,float> mln::vec3d_f`

3D vector with float coordinates.

Definition at line 40 of file vec3d.hh.

9.1.2.33 `typedef w_window<dpoint1d, float> mln::w_window1d_float`

Type alias for a [w_window](#) with arbitrary shape, defined on the 1D grid (with integer coordinates) and whose weights are floating values.

Definition at line 45 of file w_window1d_float.hh.

9.1.2.34 `typedef w_window<dpoint1d, int> mln::w_window1d_int`

Type alias for a [w_window](#) with arbitrary shape, defined on the 1D grid (with integer coordinates) and whose weights are integers.

Definition at line 45 of file core/alias/w_window1d_int.hh.

9.1.2.35 `typedef w_window<dpoint2d, float> mln::w_window2d_float`

Type alias for a `w_window` with arbitrary shape, defined on the 2D square grid (with integer coordinates) and whose weights are floating values.

Definition at line 45 of file `w_window2d_float.hh`.

9.1.2.36 `typedef w_window<dpoint2d, int> mln::w_window2d_int`

Type alias for a `w_window` with arbitrary shape, defined on the 2D square grid (with integer coordinates) and whose weights are integers.

Definition at line 45 of file `core/alias/w_window2d_int.hh`.

9.1.2.37 `typedef w_window<dpoint3d, float> mln::w_window3d_float`

Type alias for a `w_window` with arbitrary shape, defined on the 3D grid (with integer coordinates) and whose weights are floating values.

Definition at line 45 of file `w_window3d_float.hh`.

9.1.2.38 `typedef w_window<dpoint3d, int> mln::w_window3d_int`

Type alias for a `w_window` with arbitrary shape, defined on the 3D grid (with integer coordinates) and whose weights are integers.

Definition at line 45 of file `core/alias/w_window3d_int.hh`.

9.1.3 Function Documentation

9.1.3.1 `template<typename I> I::psite mln::a_point_of(const Image<I> & ima) [inline]`

Give a point of an image.

Definition at line 51 of file `a_point_of.hh`.

9.1.3.2 `template<typename I, typename F> p2p_image<I, F> mln::apply_p2p(Image<I> & ima, const Function_v2v<F> & f) [inline]`

FIXME: Doc!

Definition at line 242 of file `p2p_image.hh`.

Referenced by `mln::debug::mosaic()`, and `mln::debug::slices_2d()`.

9.1.3.3 `template<typename I, typename F> p2p_image<const I, F> mln::apply_p2p(const Image<I> & ima, const Function_v2v<F> & f) [inline]`

FIXME: Doc!

Definition at line 256 of file `p2p_image.hh`.

9.1.3.4 template<typename T2 , typename T1 > fun::x2x::composed< T2, T1 > mln::compose (T2 *f*, T1 *g*) [inline]

Do a composition of two transformations.

Parameters

- [in] *f* The second transformation.
- [in] *g* The first transformation.

Returns

The composed transformation fog.

Definition at line 306 of file composed.hh.

References compose().

Referenced by compose(), and mln::geom::rotate().

9.1.3.5 template<typename I > mln::trait::concrete< I >::ret mln::duplicate (const Image< I > & *model*) [inline]

Duplicate the image *model* with the values of the image *data*.

Parameters

- [in] *model* The image to be duplicated.

Returns

The duplicate.

Precondition

model.is_valid

Definition at line 56 of file core/routine/duplicate.hh.

References mln::data::fill(), and initialize().

Referenced by mln::registration::icp(), mln::plain< I >::operator I(), mln::geom::rotate(), mln::geom::impl::seeds2tiling(), and mln::labeling::superpose().

9.1.3.6 template<typename I , typename F > extension_fun< const I, F > mln::extend (const Image< I > & *ima*, const Function_v2v< F > & *fun*) [inline]

Routines for domain extension with a function.

Definition at line 140 of file extend.hh.

Referenced by mln::geom::translate().

9.1.3.7 template<typename I , typename J > extension_ima< const I, const J > mln::extend (const Image< I > & *ima*, const Image< J > & *ext*)

Routines for domain extension with an image.

Definition at line 162 of file extend.hh.

9.1.3.8 template<typename I> extension_val< const I > mln::extend (const Image< I > & ima, const typename I::value & val) [inline]

Routines for domain extension with a value.

Definition at line 175 of file extend.hh.

9.1.3.9 bool mln::implies (bool lepxr, bool rexpr) [inline]

Implication.

Definition at line 68 of file contract.hh.

Referenced by mln::p_line2d::is_valid().

9.1.3.10 template<typename I, typename J> void mln::initialize (Image< I > & target, const Image< J > & model) [inline]

Initialize the image `target` with data extracted from image `model`.

Parameters

[in, out] `target` The image to be initialized.

[in] `model` The image to provide data for the initialization.

Precondition

(not `target.is_valid()`) and `model.is_valid`

Definition at line 56 of file initialize.hh.

Referenced by `duplicate()`, `mln::histo::equalize()`, `mln::morpho::tree::filter::filter()`, `mln::linear::gaussian()`, `mln::linear::gaussian_1st_derivative()`, `mln::linear::gaussian_2nd_derivative()`, `mln::graph::labeling()`, `mln::io::magick::load()`, `mln::io::dicom::load()`, `make_debug_graph_image()`, `mln::morpho::tree::filter::max()`, `mln::morpho::meyer_wst()`, `mln::morpho::tree::filter::min()`, `mln::arith::min()`, `mln::arith::minus()`, `mln::arith::plus()`, `mln::arith::revert()`, `mln::geom::rotate()`, `mln::data::impl::stretch()`, `mln::morpho::watershed::topological()`, and `mln::data::impl::generic::transform()`.

9.1.3.11 template<typename P> box< P > mln::larger_than (const box< P > a, const box< P > b) [inline]

Return the minimum box including box `a` and box `b`.

Definition at line 362 of file core/site_set/box.hh.

References `mln::box< P >::pmax()`, and `mln::box< P >::pmin()`.

9.1.3.12 template<typename I, typename V, typename E> image2d<typename I::value> mln::make_debug_graph_image (const I & input, const V & ima_v, const E & ima_e, const value::rgb8 & bg) [inline]

Draw a graph.

Definition at line 123 of file demos/graph/region_adjacency_graph.cc.

References `mln::box< P >::crop_wrt()`, `mln::image2d< T >::domain()`, `mln::debug::draw_graph()`, `mln::data::fill()`, `mln::literal::green`, `initialize()`, and `mln::convert::to()`.

9.1.3.13 template<typename T> mln::mln_exact(T) [inline]

Exact cast routine for mln objects.

This set of routines can be used to downcast an object towards its exact type. The only argument, respectively `ptr` or `ref`, should be an [mln::Object](#).

The parameter `E` is the exact type of the object.

Returns

The return follows the nature of the argument (either a pointer or a reference, const or not).

Definition at line 92 of file routine/exact.hh.

Referenced by `mln::geom::rotate()`, `mln::Accumulator< E >::take_as_init()`, `mln::Accumulator< E >::take_n_times()`, `mln::convert::to()`, and `mln::geom::translate()`.

9.1.3.14 mln::mln_gen_complex_neighborhood(complex_higher_neighborhood , complex_higher_window)

[Neighborhood](#) centered on an n-face of complex returning its adjacent (n+1)-faces.

9.1.3.15 mln::mln_gen_complex_neighborhood(complex_lower_higher_neighborhood , complex_lower_higher_window)

[Neighborhood](#) centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces.

9.1.3.16 mln::mln_gen_complex_neighborhood(complex_lower_dim_connected_n_face_neighborhood , complex_lower_dim_connected_n_face_window)

[Neighborhood](#) centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face.

9.1.3.17 mln::mln_gen_complex_neighborhood(complex_higher_dim_connected_n_face_neighborhood , complex_higher_dim_connected_n_face_window)

[Neighborhood](#) centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face.

9.1.3.18 mln::mln_gen_complex_neighborhood(complex_m_face_neighborhood , complex_m_face_window)

[Neighborhood](#) centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face.

9.1.3.19 `mln::mln_gen_complex_neighborhood (complex_lower_neighborhood , complex_lower_window)`

`Neighborhood` centered on an n-face of complex returning its adjacent (n-1)-faces.

9.1.3.20 `mln::mln_gen_complex_window (complex_lower_window , topo::adj_lower_face_fwd_iter , topo::adj_lower_face_bkd_iter)`

`Window` centered on an n-face of complex returning its adjacent (n-1)-faces.

9.1.3.21 `mln::mln_gen_complex_window (complex_higher_window , topo::adj_higher_face_fwd_iter , topo::adj_higher_face_bkd_iter)`

`Window` centered on an n-face of complex returning its adjacent (n+1)-faces.

9.1.3.22 `mln::mln_gen_complex_window (complex_lower_higher_window , topo::adj_lower_higher_face_fwd_iter , topo::adj_lower_higher_face_bkd_iter)`

`Window` centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces.

9.1.3.23 `mln::mln_gen_complex_window (complex_lower_dim_connected_n_face_window , topo::adj_lower_dim_connected_n_face_fwd_iter , topo::adj_lower_dim_connected_n_face_bkd_iter)`

`Window` centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face.

9.1.3.24 `mln::mln_gen_complex_window (complex_higher_dim_connected_n_face_window , topo::adj_higher_dim_connected_n_face_fwd_iter , topo::adj_higher_dim_connected_n_face_bkd_iter)`

`Window` centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face.

9.1.3.25 `mln::mln_gen_complex_window (complex_m_face_window , topo::adj_m_face_fwd_iter , topo::adj_m_face_bkd_iter)`

`Window` centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face.

9.1.3.26 `mln::mln_gen_complex_window_p (complex_lower_window_p , topo::adj_lower_face_fwd_iter , topo::adj_lower_face_bkd_iter)`

`Window` centered on an n-face of complex returning its adjacent (n-1)-faces as well as the center n-face.

9.1.3.27 `mln::mln_gen_complex_window_p (complex_higher_window_p , topo::adj_higher_face_fwd_iter , topo::adj_higher_face_bkd_iter)`

`Window` centered on an n-face of complex returning its adjacent (n+1)-faces as well as the center n-face.

9.1.3.28 `mln::mln_gen_complex_window_p (complex_lower_higher_window_p , topo::adj_lower_higher_face_fwd_iter , topo::adj_lower_higher_face_bkd_iter)`

[Window](#) centered on an n-face of complex returning its adjacent (n-1)-faces and (n+1)-faces as well as the center n-face.

9.1.3.29 `mln::mln_gen_complex_window_p (complex_higher_dim_connected_n_face_window_p , topo::adj_higher_dim_connected_n_face_fwd_iter , topo::adj_higher_dim_connected_n_face_bkd_iter)`

[Window](#) centered on an n-face of complex returning the n-faces sharing an (n+1)-face with the center n-face, as well as this center n-face.

9.1.3.30 `mln::mln_gen_complex_window_p (complex_lower_dim_connected_n_face_window_p , topo::adj_lower_dim_connected_n_face_fwd_iter , topo::adj_lower_dim_connected_n_face_bkd_iter)`

[Window](#) centered on an n-face of complex returning the n-faces sharing an (n-1)-face with the center n-face, as well as this center n-face.

9.1.3.31 `mln::mln_gen_complex_window_p (complex_m_face_window_p , topo::adj_m_face_fwd_iter , topo::adj_m_face_bkd_iter)`

[Window](#) centered on an n-face of complex returning the m-faces transitively adjacent to this center n-face, as well as this center n-face.

9.1.3.32 `template<typename W1 , typename W2 > mln::mln_regular (W1) const [inline]`

Set difference between a couple of windows `win1` and `win2`.

Inter a window `win` with a delta-point `dp`.

It just calls `mln::win::diff`.

9.1.3.33 `template<typename O1 , typename O2 > mln::mln_trait_op_geq (O1 , O2)`

General definition of the "greater than or equal to" operator.

The "greater than or equal to" operator is here defined for every Milena objects. It relies on the definition of the "less than or equal to" operator. It returns "rhs \leq lhs".

Warning

There shall not be any other definition of this operator in Milena when applying on a couple of `mln::Object`.

9.1.3.34 `template<typename O1 , typename O2 > mln::mln_trait_op_greater (O1 , O2) const`

General definition of the "greater than" operator.

The "greater than" operator is here defined for every milena objects. It relies on the definition of the "less than" operator. It returns "rhs $<$ lhs".

Warning

There shall not be any other definition of this operator in Milena when applying on a couple of [mln::Object](#).

9.1.3.35 template<typename O1 , typename O2 > mln::mln_trait_op_leq (O1 , O2)

Default definition of the "less than or equal to" operator.

A default version of the "less than or equal to" operator is defined for every Milena objects. It relies on the definition of the "less than" operator. It returns "not (rhs < lhs)".

Warning

In the case of partial ordering between objects, this operator has to be re-defined.

**9.1.3.36 template<typename O1 , typename O2 > mln::mln_trait_op_neq (O1 , O2)
[inline]****Initial value:**

```
(const Object<O1>& lhs, const Object<O2>& rhs)
{
    return ! (exact(lhs) == exact(rhs));
}

template <typename O1, typename O2>
inline
mln_trait_op_greater(O1, O2)
operator>(const Object<O1>& lhs, const Object<O2>& rhs)
{
    return exact(rhs) < exact(lhs);
}

template <typename O1
```

General definition of the "not equal to" operator.

The "not equal to" operator is here defined for every milena objects. It relies on the definition of the "equal to" operator. It returns "not (lhs == rhs)".

Warning

There shall not be any other definition of this operator in Milena when applying on a couple of [mln::Object](#).

9.1.3.37 template<unsigned D, typename G > bool mln::operator!= (const complex_psite< D, G > & lhs, const complex_psite< D, G > & rhs)

Is *lhs* not equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::p_complex](#).

Definition at line 353 of file complex_psite.hh.

References [mln::complex_psite< D, G >::face\(\)](#), and [mln::complex_psite< D, G >::site_set\(\)](#).

9.1.3.38 template<unsigned N, unsigned D, typename P > bool mln::operator!= (const faces_psite< N, D, P > & lhs, const faces_psite< N, D, P > & rhs)

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same mln::complex.

Definition at line 336 of file faces_psite.hh.

References mln::faces_psite< N, D, P >::face(), and mln::faces_psite< N, D, P >::site_set().

9.1.3.39 template<typename P , typename S > P mln::operator* (const Gpoint< P > & p, const value::scalar_< S > & s) [inline]

Multiply a point *p* by a scalar *s*.

Definition at line 405 of file gpoint.hh.

9.1.3.40 template<typename S > S & mln::operator++ (value::Scalar< S > & rhs) [inline]

Pre-incrementation for any scalar type.

Definition at line 77 of file concept/scalar.hh.

References mln::literal::one.

9.1.3.41 template<typename N1 , typename N2 > N2 neighb< typename N1::window::regular > mln::operator- (const Neighborhood< N1 > & nbh1, const Neighborhood< N2 > & nbh2)

Set difference between a couple of neighborhoods *nbh1* and *nbh2*.

It just calls [mln::win::diff](#).

Definition at line 155 of file win/diff.hh.

References mln::win::diff().

9.1.3.42 template<typename P , typename D > P mln::operator- (const Gpoint< P > & p, const Gdpoint< D > & dp) [inline]

Substract a delta-point *dp* to a grid point *p*.

Parameters

[in] *p* A grid point.

[in] *dp* A delta-point.

The type of *dp* has to compatible with the type of *p*.

Returns

A point (temporary object).

See also

[mln::Gdpoint](#)
[mln::Gdpoint](#)

Definition at line 395 of file gpoint.hh.

9.1.3.43 template<typename S > S & mln::operator-- (value::Scalar< S > & rhs) [inline]

Pre-decrementation for any scalar type.

Definition at line 85 of file concept/scalar.hh.

References mln::literal::one.

9.1.3.44 template<unsigned D, typename G > bool mln::operator< (const complex_psitem< D, G > & lhs, const complex_psitem< D, G > & rhs)

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting psites.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::p_complex](#).

Definition at line 362 of file complex_psitem.hh.

9.1.3.45 template<unsigned N, unsigned D, typename P > bool mln::operator< (const faces_psitem< N, D, P > & lhs, const faces_psitem< N, D, P > & rhs)

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting psites.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::complex](#).

Definition at line 345 of file faces_psitem.hh.

9.1.3.46 template<typename L , typename R > bool mln::operator< (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise test if the pixel values of *lhs* are point-wise less than the pixel values of *rhs*.

Parameters

[in] **lhs** A first image.
 [in] **rhs** A second image.

Precondition

lhs.domain == rhs.domain

Definition at line 107 of file compare.hh.

References [mln::test::predicate\(\)](#).

9.1.3.47 template<typename I , typename G , typename W > std::ostream & mln::operator<< (std::ostream & ostr, const complex_window_bkd_piter< I, G, W > & p) [inline]

Print an [mln::complex_window_bkd_piter](#).

Definition at line 401 of file [complex_window_piter.hh](#).

9.1.3.48 template<typename I , typename G , typename W > std::ostream & mln::operator<< (std::ostream & ostr, const complex_window_fwd_piter< I, G, W > & p) [inline]

Print an [mln::complex_window_fwd_piter](#).

Definition at line 292 of file [complex_window_piter.hh](#).

9.1.3.49 template<typename I , typename G , typename N > std::ostream & mln::operator<< (std::ostream & ostr, const complex_neighborhood_fwd_piter< I, G, N > & p) [inline]

Print an [mln::complex_neighborhood_fwd_piter](#).

Definition at line 292 of file [complex_neighborhood_piter.hh](#).

9.1.3.50 template<typename I , typename G , typename N > std::ostream & mln::operator<< (std::ostream & ostr, const complex_neighborhood_bkd_piter< I, G, N > & p) [inline]

Print an [mln::complex_neighborhood_bkd_piter](#).

Definition at line 399 of file [complex_neighborhood_piter.hh](#).

9.1.3.51 template<unsigned D, typename G > bool mln::operator<= (const p_complex< D, G > & lhs, const p_complex< D, G > & rhs)

Inclusion of a [mln::p_complex](#) in another one.

This inclusion relation is very strict for the moment, since our infrastructure for complexes is simple: a [mln::p_complex](#) is included in another one if their are equal.

Definition at line 330 of file [p_complex.hh](#).

9.1.3.52 template<typename G , typename F > bool mln::operator<= (const p_edges< G, F > & lhs, const p_edges< G, F > & rhs)

Inclusion of a [mln::p_edges](#) in another one.

Definition at line 338 of file [p_edges.hh](#).

9.1.3.53 template<typename L , typename R > bool mln::operator<= (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise test if the pixel values of `lhs` are point-wise less than or equal to the pixel values of `rhs`.

Parameters

- [in] ***lhs*** A first image.
- [in] ***rhs*** A second image.

Precondition

`lhs.domain == rhs.domain`

Definition at line 126 of file compare.hh.

References `mln::test::predicate()`.

9.1.3.54 template<typename G , typename F > bool mln::operator<= (const p_vertices< G, F > & lhs, const p_vertices< G, F > & rhs)

Inclusion of a `mln::p_vertices` in another one.

This inclusion relation is very strict for the moment, since our infrastructure for graphs is simple: a `mln::p_vertices` is included in another one if their are equal.

Definition at line 399 of file p_vertices.hh.

9.1.3.55 template<unsigned N, unsigned D, typename P > bool mln::operator<= (const p_faces< N, D, P > & lhs, const p_faces< N, D, P > & rhs)

Inclusion of a `mln::p_faces` in another one.

This inclusion relation is very strict for the moment, since our infrastructure for complexes is simple: a `mln::p_faces` is included in another one if their are equal.

Definition at line 287 of file p_faces.hh.

9.1.3.56 template<unsigned N, unsigned D, typename P > bool mln::operator== (const p_faces< N, D, P > & lhs, const p_faces< N, D, P > & rhs)

Comparison between two `mln::p_faces`'s.

Two `mln::p_faces`'s are considered equal if they share the same complex.

Definition at line 278 of file p_faces.hh.

References `mln::p_faces< N, D, P >::cplx()`.

9.1.3.57 template<unsigned N, unsigned D, typename P > bool mln::operator== (const faces_psite< N, D, P > & lhs, const faces_psite< N, D, P > & rhs)

Comparison of two instances of `mln::faces_psite`.

Is `lhs` equal to `rhs`?

Precondition

Arguments `lhs` and `rhs` must belong to the same `mln::complex`.

Definition at line 327 of file faces_psite.hh.

References `mln::faces_psite< N, D, P >::face()`, and `mln::faces_psite< N, D, P >::site_set()`.

9.1.3.58 template<typename L , typename R > bool mln::operator==(const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise test if the pixel values of *lhs* are equal to the pixel values of *rhs*.

Parameters

[in] *lhs* A first image.

[in] *rhs* A second image.

Precondition

lhs.domain == rhs.domain

Definition at line 86 of file compare.hh.

References mln::test::predicate().

9.1.3.59 template<unsigned D, typename G > bool mln::operator==(const p_complex< D, G > & lhs, const p_complex< D, G > & rhs)

Comparison between two [mln::p_complex](#)'s.

Two [mln::p_complex](#)'s are considered equal if they share the same complex.

Definition at line 321 of file p_complex.hh.

References mln::p_complex< D, G >::cplx().

9.1.3.60 template<unsigned D, typename G > bool mln::operator==(const complex_psite< D, G > & lhs, const complex_psite< D, G > & rhs)

Comparison of two instances of [mln::complex_psite](#).

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::p_complex](#).

Definition at line 344 of file complex_psite.hh.

References mln::complex_psite< D, G >::face(), and mln::complex_psite< D, G >::site_set().

9.1.3.61 template<typename G , typename F > bool mln::operator==(const p_vertices< G, F > & lhs, const p_vertices< G, F > & rhs)

Comparison between two [mln::p_vertices](#)'s.

Two [mln::p_vertices](#)'s are considered equal if they share the same graph.

Definition at line 392 of file p_vertices.hh.

References mln::p_vertices< G, F >::graph().

9.1.3.62 template<typename G , typename F > bool mln::operator==(const p_edges< G, F > & lhs, const p_edges< G, F > & rhs)

Comparison between two [mln::p_edges](#)'s.

Two [mln::p_edges](#)'s are considered equal if they share the same graph.

Definition at line 331 of file [p_edges.hh](#).

References [mln::p_edges< G, F >::graph\(\)](#).

9.1.3.63 template<typename F , typename S > pw::image<F,S> mln::operator|(const Function_v2v< F > & f, const Site_Set< S > & ps)

Construct an image from a function and a site set.

image = function | site_set.

Definition at line 138 of file [pw/image.hh](#).

9.1.3.64 template<typename V , typename G , typename P > edge_image<P,V,G> mln::operator|(const fun::i2v::array< V > & edge_values, const p_edges< G, fun::i2v::array< P > > & pe)

Construct a edge image from a [fun::i2v::array](#) and a [p_edges](#).

image = [fun::i2v::array](#) | [p_edges](#).

Definition at line 217 of file [core/image/edge_image.hh](#).

9.1.3.65 template<typename S , typename F > p_if<S,F> mln::operator|(const Site_Set< S > & s, const Function_v2b< F > & f)

Restrict a site set *s* to points that verify *f*.

Parameters

[in] *s* A site set.

[in] *f* A function from point to Boolean.

Returns

A subset of points.

Definition at line 147 of file [p_if.hh](#).

9.1.3.66 template<typename V , typename G , typename P > vertex_image<P,V,G> mln::operator|(const fun::i2v::array< V > & vertex_values, const p_vertices< G, fun::i2v::array< P > > & pv)

Construct a vertex image from a [fun::i2v::array](#) and a [p_vertices](#).

image = [fun::i2v::array](#) | [p_vertices](#).

Definition at line 215 of file [core/image/vertex_image.hh](#).

9.1.3.67 template<typename I , typename F > image_if<I,F> mln::operator| (Image< I > & ima, const Function_v2b< F > & f)

ima | f creates an [image_if](#) with the image ima and the function f.

Definition at line 233 of file image_if.hh.

9.1.3.68 template<typename I , typename F > image_if<const I,F> mln::operator| (const Image< I > & ima, const Function_v2b< F > & f)

ima | f creates an [image_if](#) with the image ima and the function f.

Definition at line 242 of file image_if.hh.

9.1.3.69 template<typename I > const internal::primary_type< I >::ret & mln::primary (const Image< I > & input) [inline]

FIXME: Doc!

Definition at line 129 of file primary.hh.

Referenced by mln::border::resize().

9.1.3.70 template<typename S , typename F > p_transformed< S, F > mln::ptransform (const Site_Set< S > & s, const Function_v2v< F > & f) [inline]

Transform a site set s through the function f.

Parameters

[in] *s* A site set.

[in] *f* A function from site to site.

Returns

The transformed site set.

Definition at line 145 of file p_transformed.hh.

9.1.4 Variable Documentation

9.1.4.1 const dpoint1d mln::before = dpoint1d(-1)

Definition of a shortcut for delta point in 1d.

Definition at line 73 of file dpoint1d.hh.

9.1.4.2 const dpoint3d mln::sagittal_dec = dpoint3d(0, 0, -1)

Definition of a shortcut for delta point in 3d.

Definition at line 72 of file dpoint3d.hh.

9.1.4.3 const dpoint2d mln::up = dpoint2d(-1, 0)

Definition of a shortcut for delta point in 2d.

Definition at line 76 of file dpoint2d.hh.

9.2 mln::accu Namespace Reference

Namespace of accumulators.

Namespaces

- namespace [image](#)
Namespace of accumulator image routines.
- namespace [impl](#)
Implementation namespace of accumulator namespace.
- namespace [logic](#)
Namespace of logical accumulators.
- namespace [math](#)
Namespace of mathematic accumulators.
- namespace [shape](#)
Namespace of shape accumulators.
- namespace [stat](#)
Namespace of statistical accumulators.

Classes

- struct [center](#)
Mass center accumulator.
- struct [convolve](#)
Generic convolution accumulator class.
- struct [count_adjacent_vertices](#)
Accumulator class counting the number of vertices adjacent to a set of mln::p_edges_psite (i.e., a set of edges).
- struct [count_labels](#)
Count the number of different labels in an image.
- struct [count_value](#)
Define an accumulator that counts the occurrence of a given value.

- struct [histo](#)

Generic histogram class over a value set with type V.

- struct [label_used](#)

References all the labels used.

- struct [maj_h](#)

Compute the majority value.

- struct [max_site](#)

Define an accumulator that computes the first site with the maximum value in an image.

- struct [nil](#)

Define an accumulator that does nothing.

- struct [p](#)

Generic p of accumulators.

- struct [pair](#)

Generic pair of accumulators.

- struct [rms](#)

Generic root mean square accumulator class.

- struct [tuple](#)

Generic tuple of accumulators.

- struct [val](#)

Generic val of accumulators.

Functions

- template<typename A , typename I >

A::result [compute](#) (const [Accumulator](#)< A > &a, const [Image](#)< I > &input)

Make an accumulator compute the pixels of the image input.

- template<typename Meta_Accu , unsigned Dir, typename I , typename O >

void [line](#) (const [Image](#)< I > &input, const typename I::site &p_start, unsigned len, unsigned half_length, [Image](#)< O > &output)

- template<typename A , typename I >

[mln_meta_accu_result](#) (A, [util::pix](#)< I >) compute(const [Meta_Accumulator](#)< A > &a)

Make an accumulator compute the pixels of the image input.

- template<typename A , typename I >

void [take](#) (const [Image](#)< I > &input, [Accumulator](#)< A > &a)

Make an accumulator take the pixels of the image input.

9.2.1 Detailed Description

Namespace of accumulators.

9.2.2 Function Documentation

9.2.2.1 template<typename A , typename I > A::result mln::accu::compute (const Accumulator< A > & a, const Image< I > & input) [inline]

Make an accumulator compute the pixels of the image `input`.

Parameters

[in] `input` The input image.

[in] `a` An accumulator.

This routine runs:

`a.take(make::pix(input, p));` on all pixels on the images.

Warning

This routine does not perform `a.init()`.

Definition at line 130 of file accu/compute.hh.

9.2.2.2 template<typename Meta_Accu , unsigned Dir, typename I , typename O > void mln::accu::line (const Image< I > & input, const typename I::site & p_start, unsigned len, unsigned half_length, Image< O > & output)

Line an accumulator onto the pixel values of the image `input`.

Parameters

[in] `input` The input image.

[in] `p_start` The starting site of the line.

[in] `len` The line length.

[in] `half_length` The half length of the line.

[in, out] `output` The resulting image.

This routine runs:

```
tmp = a
```

```
tmp.init()
```

```
accu::take(input, tmp)
```

```
return tmp.to_result()
```

Definition at line 381 of file accu/line.hh.

9.2.2.3 template<typename A , typename I > mln::accu::mln_meta_accu_result (A , util::pix< I >) const [inline]

Make an accumulator compute the pixels of the image `input`.

Parameters

- [in] `input` The input image.
- [in] `a` A meta accumulator.

This routine runs:

`a.take(make::pix(input, p));` on all pixels on the images.

Warning

This routine does not perform `a.init()`.

9.2.2.4 template<typename A , typename I > void mln::accu::take (const Image< I > & `input`, Accumulator< A > & `a`) [inline]

Make an accumulator take the pixels of the image `input`.

Parameters

- [in] `input` The input image.
- [in, out] `a` The accumulator.

This routine runs:

for all `p` of `input`, `a.take(pix(input, p))`

Warning

This routine does not perform `a.init()`.

Definition at line 87 of file `take.hh`.

9.3 mln::accu::image Namespace Reference

Namespace of accumulator image routines.

9.3.1 Detailed Description

Namespace of accumulator image routines.

9.4 mln::accu::impl Namespace Reference

Implementation namespace of accumulator namespace.

9.4.1 Detailed Description

Implementation namespace of accumulator namespace.

9.5 mln::accu::logic Namespace Reference

Namespace of logical accumulators.

Classes

- struct [land](#)
"Logical-and" accumulator.
- struct [land_basic](#)
"Logical-and" accumulator.
- struct [lor](#)
"Logical-or" accumulator.
- struct [lor_basic](#)
"Logical-or" accumulator class.

9.5.1 Detailed Description

Namespace of logical accumulators.

9.6 mln::accu::math Namespace Reference

Namespace of mathematic accumulators.

Classes

- struct [count](#)
Generic counter accumulator.
- struct [inf](#)
Generic inf accumulator class.
- struct [sum](#)
Generic sum accumulator class.
- struct [sup](#)
Generic sup accumulator class.

9.6.1 Detailed Description

Namespace of mathematic accumulators.

9.7 mln::accu::meta::logic Namespace Reference

Namespace of logical meta-accumulators.

Classes

- struct [land](#)
Meta accumulator for land.
- struct [land_basic](#)
Meta accumulator for land_basic.
- struct [lor](#)
Meta accumulator for lor.
- struct [lor_basic](#)
Meta accumulator for lor_basic.

9.7.1 Detailed Description

Namespace of logical meta-accumulators.

9.8 mln::accu::meta::math Namespace Reference

Namespace of mathematic meta-accumulators.

Classes

- struct [count](#)
Meta accumulator for count.
- struct [inf](#)
Meta accumulator for inf.
- struct [sum](#)
Meta accumulator for sum.
- struct [sup](#)
Meta accumulator for sup.

9.8.1 Detailed Description

Namespace of mathematic meta-accumulators.

9.9 mln::accu::meta::shape Namespace Reference

Namespace of shape meta-accumulators.

Classes

- struct [bbox](#)
Meta accumulator for bbox.
- struct [height](#)
Meta accumulator for height.
- struct [volume](#)
Meta accumulator for volume.

9.9.1 Detailed Description

Namespace of shape meta-accumulators.

9.10 mln::accu::meta::stat Namespace Reference

Namespace of statistical meta-accumulators.

Classes

- struct [max](#)
Meta accumulator for max.
- struct [max_h](#)
Meta accumulator for max.
- struct [mean](#)
Meta accumulator for mean.
- struct [median_alt](#)
Meta accumulator for median_alt.
- struct [median_h](#)
Meta accumulator for median_h.
- struct [min](#)

Meta accumulator for min.

- struct [min_h](#)

Meta accumulator for min.

- struct [rank](#)

Meta accumulator for rank.

- struct [rank_high_quant](#)

Meta accumulator for rank_high_quant.

9.10.1 Detailed Description

Namespace of statistical meta-accumulators.

9.11 mln::accu::shape Namespace Reference

Namespace of shape accumulators.

Classes

- struct [bbox](#)

Generic bounding box accumulator class.

- struct [height](#)

Height accumulator.

- struct [volume](#)

Volume accumulator class.

9.11.1 Detailed Description

Namespace of shape accumulators.

9.12 mln::accu::stat Namespace Reference

Namespace of statistical accumulators.

Classes

- struct [deviation](#)

Generic standard deviation accumulator class.

- struct [histo3d_rgb](#)

Define a histogram as accumulator which returns an [image3d](#).

- struct [max](#)

Generic max accumulator class.

- struct [max_h](#)

Generic max function based on histogram over a value set with type V.

- struct [mean](#)

Generic mean accumulator class.

- struct [median_alt](#)

Generic [median_alt](#) function based on histogram over a value set with type S.

- struct [median_h](#)

Generic median function based on histogram over a value set with type V.

- struct [min](#)

Generic min accumulator class.

- struct [min_h](#)

Generic min function based on histogram over a value set with type V.

- struct [min_max](#)

Generic min and max accumulator class.

- struct [rank](#)

Generic rank accumulator class.

- struct [rank< bool >](#)

rank accumulator class for Boolean.

- struct [rank_high_quant](#)

Generic rank accumulator class.

- struct [var](#)

Var accumulator class.

- struct [variance](#)

Variance accumulator class.

Functions

- template<typename V >

```
bool operator== (const histo3d\_rgb< V > &histo1, const histo3d\_rgb< V > &histo2)
```

Check whether an histogram is equal to an other one.

9.12.1 Detailed Description

Namespace of statistical accumulators.

9.12.2 Function Documentation

9.12.2.1 template<typename V> bool mln::accu::stat::operator==(const histo3d_rgb< V > &histo1, const histo3d_rgb< V > &histo2)

Check whether an histogram is equal to another one.

Parameters

- [in] **histo1** the first histogram to compare with.
- [in] **histo2** the second histogram.

The operator compares all the bins from the two histograms. Nobody uses this method unless unitary tests.

Definition at line 315 of file histo3d_rgb.hh.

References mln::image3d< T >::domain().

9.13 mln::algebra Namespace Reference

Namespace of algebraic structure.

Classes

- struct **h_mat**
N-Dimensional matrix with homogeneous coordinates.
- class **h_vec**
N-Dimensional vector with homogeneous coordinates.

Functions

- template<unsigned N, typename T>
bool ldlt_decomp (mat< N, N, T > &A, vec< N, T > &rdiag)
Perform LDL^T decomposition of a symmetric positive definite matrix.
- template<unsigned N, typename T>
void ldlt_solve (const mat< N, N, T > &A, const vec< N, T > &rdiag, const vec< N, T > &B, vec< N, T > &x)
Solve $A x = B$ after [mln::algebra::ldlt_decomp](#).
- template<unsigned n, typename T, typename U>
mln::trait::value_< typename mln::trait::op::times< T, U >::ret >::sum operator* (const vec< n, T > &lhs, const vec< n, U > &rhs)
Scalar product (dot product).

- template<typename T , typename U >
 $\text{vec} < 3, \text{typename mln::trait::op::times} < T, U > :: \text{ret} >$ **vprod** (const $\text{vec} < 3, T > \& \text{lhs}$, const $\text{vec} < 3, U > \& \text{rhs}$)
Vectorial product (cross product).

9.13.1 Detailed Description

Namespace of algebraic structure.

9.13.2 Function Documentation

9.13.2.1 template<unsigned N, typename T > bool mln::algebra::ldlt_decomp (mat< N, N, T > & A, vec< N, T > & rdiag) [inline]

Perform LDL^T decomposition of a symmetric positive definite matrix.

Like Cholesky, but no square roots. Overwrites lower triangle of matrix.

From Trimesh's ldltc routine.

Definition at line 79 of file misc.hh.

Referenced by mln::geom::mesh_curvature().

9.13.2.2 template<unsigned N, typename T > void mln::algebra::ldlt_solve (const mat< N, N, T > & A, const vec< N, T > & rdiag, const vec< N, T > & B, vec< N, T > & x) [inline]

Solve $A x = B$ after **mln::algebra::ldlt_decomp**.

Definition at line 112 of file misc.hh.

Referenced by mln::geom::mesh_curvature().

9.13.2.3 template<unsigned n, typename T , typename U > mln::trait::value_ < typename mln::trait::op::times< T, U > :: ret > :: sum mln::algebra::operator* (const vec< n, T > & lhs, const vec< n, U > & rhs) [inline]

Scalar product (dot product).

Definition at line 632 of file algebra/vec.hh.

References mln::literal::zero.

9.13.2.4 template<typename T , typename U > vec< 3, typename mln::trait::op::times< T, U > :: ret > mln::algebra::vprod (const vec< 3, T > & lhs, const vec< 3, U > & rhs) [inline]

Vectorial product (cross product).

Definition at line 713 of file algebra/vec.hh.

References vprod().

Referenced by mln::geom::mesh_corner_point_area(), mln::geom::mesh_curvature(), mln::geom::mesh_normal(), and vprod().

9.14 mln::arith Namespace Reference

Namespace of arithmetic.

Namespaces

- namespace **impl**
Implementation namespace of arith namespace.

Functions

- template<typename I >
 mln::trait::concrete< I >::ret **diff_abs** (const **Image**< I > &lhs, const **Image**< I > &rhs)
Point-wise absolute difference of images lhs and rhs.
- template<typename L , typename R , typename O >
 void **div** (const **Image**< L > &lhs, const **Image**< R > &rhs, **Image**< O > &output)
Point-wise division of images lhs and rhs.
- template<typename I , typename V , typename O >
 void **div_cst** (const **Image**< I > &input, const V &val, **Image**< O > &output)
Point-wise division of the value val to image input.
- template<typename L , typename R >
 void **div_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)
Point-wise division of image rhs in image lhs.
- template<typename L , typename R >
 mln::trait::concrete< L >::ret **min** (const **Image**< L > &lhs, const **Image**< R > &rhs)
Point-wise min of images lhs and rhs.
- template<typename L , typename R >
 void **min_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)
Point-wise min of image lhs in image rhs.
- template<typename L , typename R >
 mln::trait::op::minus< L, R >::ret **minus** (const **Image**< L > &lhs, const **Image**< R > &rhs)
Point-wise addition of images lhs and rhs.
- template<typename L , typename R , typename F >
 mln::trait::ch_value< L, typename F::result >::ret **minus** (const **Image**< L > &lhs, const **Image**< R > &rhs, const **Function_v2v**< F > &f)
Point-wise addition of images lhs and rhs.

- template<typename V , typename L , typename R >
`mln::trait::ch_value< L, V >::ret minus (const Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of images lhs and rhs.

- template<typename I , typename V >
`mln::trait::op::minus< I, V >::ret minus_cst (const Image< I > &input, const V &val)`
Point-wise addition of the value val to image input.

- template<typename I , typename V , typename F >
`mln::trait::ch_value< I, typename F::result >::ret minus_cst (const Image< I > &input, const V &val, const Function_v2v< F > &f)`
Point-wise addition of the value val to image input.

- template<typename I , typename V >
`I & minus_cst_inplace (Image< I > &input, const V &val)`
Point-wise addition of the value val to image input.

- template<typename L , typename R >
`void minus_inplace (Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of image rhs in image lhs.

- template<typename L , typename R , typename F >
`mln::trait::ch_value< L, typename F::result >::ret plus (const Image< L > &lhs, const Image< R > &rhs, const Function_v2v< F > &f)`
Point-wise addition of images lhs and rhs.

- template<typename V , typename L , typename R >
`mln::trait::ch_value< L, V >::ret plus (const Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of images lhs and rhs.

- template<typename L , typename R >
`mln::trait::op::plus< L, R >::ret plus (const Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of images lhs and rhs.

- template<typename I , typename V >
`mln::trait::op::plus< I, V >::ret plus_cst (const Image< I > &input, const V &val)`
Point-wise addition of the value val to image input.

- template<typename I , typename V , typename F >
`mln::trait::ch_value< I, typename F::result >::ret plus_cst (const Image< I > &input, const V &val, const Function_v2v< F > &f)`
Point-wise addition of the value val to image input.

- template<typename W , typename I , typename V >
`mln::trait::ch_value< I, W >::ret plus_cst (const Image< I > &input, const V &val)`
Point-wise addition of the value val to image input.

- template<typename I , typename V >
`I & plus_cst_inplace (Image< I > &input, const V &val)`
Point-wise addition of the value val to image input.

- template<typename L , typename R >
`void plus_inplace (Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of image rhs in image lhs.
- template<typename I >
`mln::trait::concrete< I >::ret revert (const Image< I > &input)`
Point-wise reversion of image input.
- template<typename I >
`void revert_inplace (Image< I > &input)`
Point-wise in-place reversion of image input.
- template<typename L , typename R , typename O >
`void times (const Image< L > &lhs, const Image< R > &rhs, Image< O > &output)`
Point-wise addition of images lhs and rhs.
- template<typename I , typename V , typename O >
`void times_cst (const Image< I > &input, const V &val, Image< O > &output)`
Point-wise addition of the value val to image input.
- template<typename L , typename R >
`void times_inplace (Image< L > &lhs, const Image< R > &rhs)`
Point-wise addition of image rhs in image lhs.

9.14.1 Detailed Description

Namespace of arithmetic.

9.14.2 Function Documentation

9.14.2.1 template<typename I > mln::trait::concrete< I >::ret mln::arith::diff_abs (const Image< I > & lhs, const Image< I > & rhs) [inline]

Point-wise absolute difference of images lhs and rhs.

Parameters

- [in] **lhs** First operand image.
- [in] **rhs** Second operand image.

Returns

The result image.

Precondition

`lhs.domain == rhs.domain`

Definition at line 63 of file arith/diff_abs.hh.

References mln::data::transform().

9.14.2.2 template<typename L , typename R , typename O > void mln::arith::div (const Image< L > & lhs, const Image< R > & rhs, Image< O > & output) [inline]

Point-wise division of images *lhs* and *rhs*.

Parameters

- [in] *lhs* First operand image.
- [in] *rhs* Second operand image.
- [out] *output* The result image.

Precondition

```
output.domain == lhs.domain == rhs.domain
```

Definition at line 227 of file arith/div.hh.

9.14.2.3 template<typename I , typename V , typename O > void mln::arith::div_est (const Image< I > & input, const V & val, Image< O > & output) [inline]

Point-wise division of the value *val* to image *input*.

Parameters

- [in] *input* The image.
- [in] *val* The value.
- [out] *output* The result image.

Precondition

```
output.domain == input.domain
```

Definition at line 242 of file arith/div.hh.

References div_cst().

Referenced by div_cst().

9.14.2.4 template<typename L , typename R > void mln::arith::div_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise division of image *rhs* in image *lhs*.

Parameters

- [in] *lhs* First operand image (subject to division).
- [in, out] *rhs* Second operand image (to div *lhs*).

This addition performs:

for all p of *rhs.domain*

lhs(p) /= *rhs*(p)

Precondition

```
rhs.domain <= lhs.domain
```

Definition at line 255 of file arith/div.hh.

References div_inplace().

Referenced by div_inplace().

9.14.2.5 template<typename L , typename R > mln::trait::concrete< L >::ret mln::arith::min (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise min of images *lhs* and *rhs*.

Parameters

[in] *lhs* First operand image.

[in] *rhs* Second operand image.

Returns

The result image.

Precondition

```
lhs.domain == rhs.domain
```

Definition at line 112 of file arith/min.hh.

References mln::initialize().

9.14.2.6 template<typename L , typename R > void mln::arith::min_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise min of image *lhs* in image *rhs*.

Parameters

[in, out] *lhs* First operand image.

[in] *rhs* Second operand image.

Precondition

```
rhs.domain == lhs.domain
```

Definition at line 128 of file arith/min.hh.

9.14.2.7 template<typename L , typename R > mln::trait::op::minus< L, R >::ret mln::arith::minus (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of images *lhs* and *rhs*.

Parameters

[in] *lhs* First operand image.

[in] ***rhs*** Second operand image.

Returns

The result image.

Precondition

`lhs.domain == rhs.domain`

Definition at line 331 of file arith/minus.hh.

References `mln::initialize()`.

9.14.2.8 template<typename L , typename R , typename F > mln::trait::ch_value< L, typename F::result >::ret mln::arith::minus (const Image< L > & *lhs*, const Image< R > & *rhs*, const Function_v2v< F > & *f*) [inline]

Point-wise addition of images `lhs` and `rhs`.

Parameters

[in] ***lhs*** First operand image.

[in] ***rhs*** Second operand image.

[in] ***f*** `Function`.

Returns

The result image.

Precondition

`lhs.domain == rhs.domain`

Definition at line 350 of file arith/minus.hh.

References `mln::initialize()`.

9.14.2.9 template<typename V , typename L , typename R > mln::trait::ch_value< L, V >::ret mln::arith::minus (const Image< L > & *lhs*, const Image< R > & *rhs*) [inline]

Point-wise addition of images `lhs` and `rhs`.

Parameters

[in] ***lhs*** First operand image.

[in] ***rhs*** Second operand image.

Returns

The result image.

The free parameter `V` sets the destination value type.

Precondition

`lhs.domain == rhs.domain`

Definition at line 369 of file arith/minus.hh.

9.14.2.10 template<typename I , typename V > mln::trait::op::minus< I, V >::ret mln::arith::minus_cst (const Image< I > & input, const V & val) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in] *input* The image.
- [in] *val* The value.

Returns

The result image.

Precondition

input.is_valid

Definition at line 387 of file arith/minus.hh.

9.14.2.11 template<typename I , typename V , typename F > mln::trait::ch_value< I, typename F::result >::ret mln::arith::minus_cst (const Image< I > & input, const V & val, const Function_v2v< F > & f) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in] *input* The image.
- [in] *val* The value.
- [in] *f* Function.

Returns

The result image.

Precondition

input.is_valid

Definition at line 405 of file arith/minus.hh.

9.14.2.12 template<typename I , typename V > I & mln::arith::minus_cst_inplace (Image< I > & input, const V & val) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in, out] *input* The image.
- [in] *val* The value.

Precondition

input.is_valid

Definition at line 440 of file arith/minus.hh.

References minus_cst_inplace(), and minus_inplace().

Referenced by minus_cst_inplace().

9.14.2.13 template<typename L , typename R > void mln::arith::minus_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of image rhs in image lhs.

Parameters

[in, out] **lhs** First operand image (subject to addition).

[in] **rhs** Second operand image (to be added to lhs).

This addition performs:

for all p of rhs.domain

lhs(p) -= rhs(p)

Precondition

```
rhs.domain == lhs.domain
```

Definition at line 424 of file arith/minus.hh.

References minus_inplace().

Referenced by minus_cst_inplace(), and minus_inplace().

9.14.2.14 template<typename L , typename R , typename F > mln::trait::ch_value< L, typename F::result >::ret mln::arith::plus (const Image< L > & lhs, const Image< R > & rhs, const Function_v2v< F > & f) [inline]

Point-wise addition of images lhs and rhs.

Parameters

[in] **lhs** First operand image.

[in] **rhs** Second operand image.

[in] **f Function**.

Returns

The result image.

Precondition

```
lhs.domain == rhs.domain
```

Definition at line 367 of file arith/plus.hh.

References mln::initialize().

9.14.2.15 template<typename V , typename L , typename R > mln::trait::ch_value< L, V >::ret mln::arith::plus (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of images *lhs* and *rhs*.

Parameters

- [in] *lhs* First operand image.
- [in] *rhs* Second operand image.

Returns

The result image.

The free parameter *V* sets the destination value type.

Precondition

```
lhs.domain == rhs.domain
```

Definition at line 386 of file arith/plus.hh.

9.14.2.16 template<typename L , typename R > mln::trait::op::plus< L, R >::ret mln::arith::plus (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of images *lhs* and *rhs*.

Parameters

- [in] *lhs* First operand image.
- [in] *rhs* Second operand image.

Returns

The result image.

Precondition

```
lhs.domain == rhs.domain
```

Definition at line 348 of file arith/plus.hh.

References mln::initialize().

9.14.2.17 template<typename I , typename V > mln::trait::op::plus< I, V >::ret mln::arith::plus_cst (const Image< I > & input, const V & val) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in] *input* The image.
- [in] *val* The value.

Returns

The result image.

Precondition

`input.is_valid`

Definition at line 404 of file arith/plus.hh.

Referenced by `plus_cst()`.

9.14.2.18 template<typename I , typename V , typename F > mln::trait::ch_value< I, typename F::result >::ret mln::arith::plus_cst (const Image< I > & *input*, const V & *val*, const Function_v2v< F > & *f*) [inline]

Point-wise addition of the value `val` to image `input`.

Parameters

- [in] `input` The image.
- [in] `val` The value.
- [in] `f` Function.

Returns

The result image.

Precondition

`input.is_valid`

Definition at line 422 of file arith/plus.hh.

9.14.2.19 template<typename W , typename I , typename V > mln::trait::ch_value< I, W >::ret mln::arith::plus_cst (const Image< I > & *input*, const V & *val*) [inline]

Point-wise addition of the value `val` to image `input`.

Parameters

- [in] `input` The image.
- [in] `val` The value.

Returns

The result image.

Precondition

`input.is_valid`

Definition at line 441 of file arith/plus.hh.

References `plus_cst()`.

9.14.2.20 template<typename I , typename V > I & mln::arith::plus_cst_inplace (Image< I > & input, const V & val) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in, out] *input* The image.
- [in] *val* The value.

Precondition

```
input.is_valid
```

Definition at line 475 of file arith/plus.hh.

References plus_cst_inplace(), and plus_inplace().

Referenced by plus_cst_inplace().

9.14.2.21 template<typename L , typename R > void mln::arith::plus_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of image *rhs* in image *lhs*.

Parameters

- [in, out] *lhs* First operand image (subject to addition).
- [in] *rhs* Second operand image (to be added to *lhs*).

This addition performs:

for all p of rhs.domain

lhs(p) += *rhs*(p)

Precondition

```
rhs.domain == lhs.domain
```

Definition at line 459 of file arith/plus.hh.

References plus_inplace().

Referenced by plus_cst_inplace(), and plus_inplace().

9.14.2.22 template<typename I > mln::trait::concrete< I >::ret mln::arith::revert (const Image< I > & input) [inline]

Point-wise reversion of image *input*.

Parameters

- [in] *input* the input image.

Returns

The result image.

Precondition

```
input.is_valid
```

It performs:

for all p of input.domain

$\text{output}(p) = \min + (\max - \text{input}(p))$

Definition at line 158 of file revert.hh.

References `mln::initialize()`.

9.14.2.23 template<typename I> void mln::arith::revert_inplace (Image< I > & *input*) [inline]

Point-wise in-place reversion of image *input*.

Parameters

[in, out] *input* The target image.

Precondition

```
input.is_valid
```

It performs:

for all p of input.domain

$\text{input}(p) = \min + (\max - \text{input}(p))$

Definition at line 174 of file revert.hh.

9.14.2.24 template<typename L, typename R, typename O> void mln::arith::times (const Image< L > & *lhs*, const Image< R > & *rhs*, Image< O > & *output*) [inline]

Point-wise addition of images *lhs* and *rhs*.

Parameters

[in] *lhs* First operand image.

[in] *rhs* Second operand image.

[out] *output* The result image.

Precondition

```
output.domain == lhs.domain == rhs.domain
```

Definition at line 226 of file arith/times.hh.

9.14.2.25 template<typename I, typename V, typename O> void mln::arith::times_cst (const Image< I > & *input*, const V & *val*, Image< O > & *output*) [inline]

Point-wise addition of the value *val* to image *input*.

Parameters

- [in] **input** The image.
- [in] **val** The value.
- [out] **output** The result image.

Precondition

```
output.domain == input.domain
```

Definition at line 241 of file arith/times.hh.

References times_cst().

Referenced by times_cst().

9.14.2.26 template<typename L , typename R > void mln::arith::times_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise addition of image rhs in image lhs.

Parameters

- [in] **lhs** First operand image (subject to addition).
- [in, out] **rhs** Second operand image (to be added to lhs).

This addition performs:

for all p of rhs.domain

lhs(p) *= rhs(p)

Precondition

```
rhs.domain <= lhs.domain
```

Definition at line 254 of file arith/times.hh.

References times_inplace().

Referenced by times_inplace().

9.15 mln::arith::impl Namespace Reference

Implementation namespace of arith namespace.

Namespaces

- namespace **generic**

Generic implementation namespace of arith namespace.

9.15.1 Detailed Description

Implementation namespace of arith namespace.

9.16 mln::arith::impl::generic Namespace Reference

Generic implementation namespace of arith namespace.

9.16.1 Detailed Description

Generic implementation namespace of arith namespace.

9.17 mln::binarization Namespace Reference

Namespace of "point-wise" expression tools.

Functions

- template<typename I , typename F >
mln::trait::ch_value< I, bool >::ret **binarization** (const **Image**< I > &input, const **Function_v2b**< F > &fun)

Thresholds the values of input so that they can be stored in the output binary image.

- template<typename I >
mln::trait::ch_value< I, bool >::ret **threshold** (const **Image**< I > &input, const typename I::value threshold)

Thresholds the values of input so that they can be stored in the output binary image.

9.17.1 Detailed Description

Namespace of "point-wise" expression tools.

9.17.2 Function Documentation

- 9.17.2.1 template<typename I , typename F > mln::trait::ch_value< I, bool >::ret
mln::binarization::binarization (const Image< I > & input, const Function_v2b< F >
& fun) [inline]**

Thresholds the values of *input* so that they can be stored in the *output* binary image.

Parameters

[in] **input** The input image.

[in] **fun** The thresholding function, from value(I) to bool.

for_all(p), output(p) = fun(p)

Definition at line 86 of file binarization.hh.

Referenced by `threshold()`.

9.17.2.2 template<typename I> mln::trait::ch_value< I, bool >::ret mln::binarization::threshold (const Image< I > & input, const typename I::value threshold) [inline]

Thresholds the values of `input` so that they can be stored in the `output` binary image.

Parameters

- [in] `input` The input image.
- [in] `threshold` The threshold.

If `input(p)` is greater or equal than the threshold, the value in the output image in the same point will be TRUE, else FALSE.

Definition at line 61 of file binarization/threshold.hh.

References binarization().

9.18 mln::border Namespace Reference

Namespace of routines related to image virtual (outer) border.

Namespaces

- namespace `impl`
Implementation namespace of border namespace.

Functions

- template<typename I>
void `adjust` (const `Image< I >` &ima, unsigned min_thickness)
- template<typename I>
void `duplicate` (const `Image< I >` &ima)
- template<typename I, typename J>
void `equalize` (const `Image< I >` &ima1, const `Image< J >` &ima2, unsigned min_thickness)
- template<typename I>
void `fill` (const `Image< I >` &ima, const typename I::value &v)
- template<typename I>
unsigned `find` (const `Image< I >` &ima)
- template<typename I>
unsigned `get` (const `Image< I >` &ima)
- template<typename I>
void `mirror` (const `Image< I >` &ima)
- template<typename I>
void `resize` (const `Image< I >` &ima, unsigned thickness)

Facade.

9.18.1 Detailed Description

Namespace of routines related to image virtual (outer) border.

9.18.2 Function Documentation

9.18.2.1 template<typename I> void mln::border::adjust (const Image< I > & ima, unsigned min_thickness) [inline]

Adjust the virtual (outer) border of image `ima` so that its size is at least `min_thickness`.

Parameters

- [in, out] `ima` The image whose border is to be adjusted.
- [in] `min_thickness` The expected border minimum thickness.

Precondition

`ima` has to be initialized.

Warning

If the image border is already larger than `min_thickness`, this routine is a no-op.

Definition at line 62 of file border/adjust.hh.

References `get()`, and `resize()`.

9.18.2.2 template<typename I> void mln::border::duplicate (const Image< I > & ima)

Assign the virtual (outer) border of image `ima` with the duplicate of the inner border of this image.

Parameters

- [in, out] `ima` The image whose border is to be duplicated.

Precondition

`ima` has to be initialized.

Definition at line 252 of file border/duplicate.hh.

References `get()`.

9.18.2.3 template<typename I, typename J> void mln::border::equalize (const Image< I > & ima1, const Image< J > & ima2, unsigned min_thickness) [inline]

Equalize the virtual (outer) border of images `ima1` and `ima2` so that their size is equal and is at least `min_thickness`.

Parameters

- [in, out] `ima1` The first image whose border is to be equalized.
- [in, out] `ima2` The second image whose border is to be equalized.
- [in] `min_thickness` The expected border minimum thickness of both images.

Precondition

`ima1` has to be initialized.
`ima2` has to be initialized.

Warning

If both image borders already have the same thickness and if this thickness is larger than `min_thickness`, this routine is a no-op.

Definition at line 112 of file border/equalize.hh.

References `get()`.

9.18.2.4 template<typename I> void mln::border::fill (const Image< I > & ima, const typename I::value & v) [inline]

Fill the virtual (outer) border of image `ima` with the single value `v`.

Parameters

[in, out] `ima` The image whose border is to be filled.

[in] `v` The value to assign to all border pixels.

Precondition

`ima` has to be initialized.

Definition at line 201 of file border/fill.hh.

9.18.2.5 template<typename I> unsigned mln::border::find (const Image< I > & ima) [inline]

Find the virtual (outer) border thickness of image `ima`.

Parameters

[in] `ima` The image.

Returns

The border thickness (0 if there is no border).

Precondition

`ima` has to be initialized.

Definition at line 95 of file find.hh.

9.18.2.6 template<typename I> unsigned mln::border::get (const Image< I > & ima) [inline]

Get the virtual (outer) border thickness of image `ima`.

Parameters

[in] `ima` The image.

Returns

The border thickness (0 if there is no border).

Precondition

ima has to be initialized.

Definition at line 90 of file border/get.hh.

Referenced by `adjust()`, `duplicate()`, and `equalize()`.

**9.18.2.7 template<typename I> void mln::border::mirror (const Image< I > & *ima*)
[inline]**

Mirror the virtual (outer) border of image *ima* with the (inner) level contents of this image.

Parameters

[in, out] *ima* The image whose border is to be mirrored.

Precondition

ima has to be initialized.

Definition at line 211 of file border/mirror.hh.

**9.18.2.8 template<typename I> void mln::border::resize (const Image< I > & *ima*, unsigned
thickness) [inline]**

Facade.

Resize the virtual (outer) border of image *ima* to exactly *thickness*.

Parameters

[in, out] *ima* The image whose border is to be resized.

[in] *thickness* The expected border thickness.

Precondition

ima has to be initialized.

Warning

If the image border already has the expected thickness, this routine is a no-op.

Definition at line 126 of file resize.hh.

References `mln::primary()`, and `resize()`.

Referenced by `adjust()`, and `resize()`.

9.19 mln::border::impl Namespace Reference

Implementation namespace of border namespace.

Namespaces

- namespace [generic](#)

Generic implementation namespace of border namespace.

9.19.1 Detailed Description

Implementation namespace of border namespace.

9.20 mln::border::impl::generic Namespace Reference

Generic implementation namespace of border namespace.

9.20.1 Detailed Description

Generic implementation namespace of border namespace.

9.21 mln::canvas Namespace Reference

Namespace of canvas.

Namespaces

- namespace [browsing](#)

Namespace of browsing canvas.

- namespace [impl](#)

Implementation namespace of canvas namespace.

- namespace [labeling](#)

Namespace of labeling canvas.

- namespace [morpho](#)

Namespace of morphological canvas.

Classes

- struct [chamfer](#)

Compute chamfer distance.

Functions

- template<typename I , typename N , typename W , typename D , typename F >
`mln::trait::ch_value< I, D >::ret distance_front (const Image< I > &input, const Neighborhood< N > &nbh, const Weighted_Window< W > &w_win, D max, F &functor)`
Canvas of discrete distance computation by thick front propagation.
- template<typename I , typename N , typename D , typename F >
`mln::trait::ch_value< I, D >::ret distance_geodesic (const Image< I > &input, const Neighborhood< N > &nbh, D max, F &functor)`
Discrete geodesic distance canvas.

9.21.1 Detailed Description

Namespace of canvas.

9.21.2 Function Documentation

- 9.21.2.1 template<typename I , typename N , typename W , typename D , typename F >
`mln::trait::ch_value< I, D >::ret mln::canvas::distance_front (const Image< I > & input, const Neighborhood< N > & nbh, const Weighted_Window< W > & w_win, D max, F & functor) [inline]`**

Canvas of discrete distance computation by thick front propagation.

Definition at line 397 of file canvas/distance_front.hh.

Referenced by `mln::transform::influence_zone_front()`.

- 9.21.2.2 template<typename I , typename N , typename D , typename F >
`mln::trait::ch_value< I, D >::ret mln::canvas::distance_geodesic (const Image< I > & input, const Neighborhood< N > & nbh, D max, F & functor) [inline]`**

Discrete geodesic distance canvas.

Definition at line 321 of file canvas/distance_geodesic.hh.

Referenced by `mln::transform::influence_zone_geodesic_saturated()`.

9.22 mln::canvas::browsing Namespace Reference

Namespace of browsing canvas.

Classes

- struct **backdiagonal2d_t**
Browsing in a certain direction.
- struct **breadth_first_search_t**

Breadth-first search algorithm for graph, on vertices.

- struct [depth_first_search_t](#)
Breadth-first search algorithm for graph, on vertices.
- struct [diagonal2d_t](#)
Browsing in a certain direction.
- struct [dir_struct_elt_incr_update_t](#)
Browsing in a certain direction with a segment.
- struct [directional_t](#)
Browsing in a certain direction.
- struct [fwd_t](#)
Canvas for forward browsing.
- struct [hyper_directional_t](#)
Browsing in a certain direction.
- struct [snake_fwd_t](#)
Browsing in a snake-way, forward.
- struct [snake_generic_t](#)
Multidimensional Browsing in a given-way.
- struct [snake_vert_t](#)
Browsing in a snake-way, forward.

9.22.1 Detailed Description

Namespace of browsing canvas.

9.23 mln::canvas::impl Namespace Reference

Implementation namespace of canvas namespace.

9.23.1 Detailed Description

Implementation namespace of canvas namespace.

9.24 mln::canvas::labeling Namespace Reference

Namespace of labeling canvas.

Namespaces

- namespace **impl**

Implementation namespace of labeling canvas namespace.

Functions

- template<typename I , typename N , typename L , typename F >
mln::trait::ch_value< I, L >::ret **blobs** (const **Image**< I > &input_, const **Neighborhood**< N > &nbh_, L &nlabels, F &functor)

Canvas for connected component labeling of the binary objects of a binary image using a queue-based algorithm.

9.24.1 Detailed Description

Namespace of labeling canvas.

9.24.2 Function Documentation

- 9.24.2.1 template<typename I , typename N , typename L , typename F > mln::trait::ch_value< I, L >::ret mln::canvas::labeling::blobs (const **Image**< I > & input_, const **Neighborhood**< N > & nbh_, L & nlabels, F & functor) [inline]**

Canvas for connected component labeling of the binary objects of a binary image using a queue-based algorithm.

Parameters

- [in] **input** The input image.
- [in] **nbh** The connexity of the objects.
- [out] **nlabels** The Number of labels. Its value is set in the algorithms.
- [in, out] **functor** A functor computing data while labeling.

Returns

The label image.

Precondition

The input image has to be binary (checked at compile-time).

A fast queue is used so that the algorithm is not recursive and can handle large binary objects (blobs).

Definition at line 167 of file canvas/labeling/blobs.hh.

9.25 mln::canvas::labeling::impl Namespace Reference

Implementation namespace of labeling canvas namespace.

9.25.1 Detailed Description

Implementation namespace of labeling canvas namespace.

9.26 mln::canvas::morpho Namespace Reference

Namespace of morphological canvas.

9.26.1 Detailed Description

Namespace of morphological canvas.

9.27 mln::convert Namespace Reference

Namespace of conversion routines.

Functions

- template<typename V >
`void from_to (const float &from, Value< V > &to)`
Conversion of a float from towards a value to.
- template<typename V >
`void from_to (const int &from, Value< V > &to)`
Conversion of a int from towards a value to.
- template<typename V >
`void from_to (const double &from, Value< V > &to)`
Conversion of a double from towards a value to.
- template<typename V >
`void from_to (const unsigned &from, Value< V > &to)`
Conversion of an unsigned from towards a value to.
- template<typename S >
`mln_image_from_grid (typename S::site::grid, bool) to_image(const Site_Set< S > &pset)`
Convert a point set pset into a binary image.
- template<typename W >
`mln_image_from_grid (typename W::site::grid, bool) to_image(const Window< W > &win)`
Convert a window win into a binary image.
- template<typename W >
`mln_image_from_grid (typename W::site::grid, mln_weight(W)) to_image(const Weighted_Window< W > &w_win)`
Convert a weighted window w_win into an image.

- template<typename N >
`mln_image_from_grid` (typename N::site::grid, bool) `to_image`(const `Neighborhood< N >` &nbh)
Convert a neighborhood nbh into a binary image.
- template<typename N >
`mln_window` (N) `to_window`(const `Neighborhood< N >` &nbh)
Convert a neighborhood nbh into a window.
- template<typename T , typename O >
T `to` (const O &from)
Conversion of the object from towards an object with type T.
- template<typename P >
P::dpoint `to_dpoint` (const `Point_Site< P >` &p)
Convert a point site p into a delta-point.
- template<typename I >
pw::value_< I > `to_fun` (const `Image< I >` &ima)
Convert an image into a function.
- template<typename T >
`image1d< unsigned >` `to_image` (const `histo::array< T >` &h)
Convert an histo h into an image1d<unsigned>.
- template<typename I >
`p_array< typename I::psite >` `to_p_array` (const `Image< I >` &img)
Convert an image img into a p_array.
- template<typename S >
`p_array< typename S::psite >` `to_p_array` (const `Site_Set< S >` &pset)
Convert a point set pset into a p_array (point set vector).
- template<typename W >
`p_array< typename W::psite >` `to_p_array` (const `Window< W >` &win, const typename W::psite &p)
Convert a window win centered at point p into a p_array (point set vector).
- template<typename N >
`p_set< typename N::psite >` `to_p_set` (const `Neighborhood< N >` &nbh)
Convert a neighborhood nbh into a site set.
- template<typename I >
`p_set< typename I::psite >` `to_p_set` (const `Image< I >` &ima)
Convert a binary image ima into a site set.
- template<typename P , typename C >
`p_set< P >` `to_p_set` (const std::set< P, C > &s)
Convert an std::set s of sites into a site set.
- template<typename S >
`p_set< typename S::psite >` `to_p_set` (const `Site_Set< S >` &ps)

Convert any site set `ps` into a '`mlnp_set`' site set.

- template<typename W >
`p_set< typename W::psite > to_p_set (const Window< W > &win)`

Convert a `Window` `win` into a site set.

- template<typename I >
`QImage to_qimage (const Image< I > &ima)`

Convert a Milena image to a `Qimage`.

- template<typename N >
`window< typename N::dpoint > to_upper_window (const Neighborhood< N > &nbb)`

Convert a neighborhood `nbb` into an upper window.

- template<typename W >
`window< typename W::dpsite > to_upper_window (const Window< W > &win)`

Convert a window `nbb` into an upper window.

- template<typename D , typename C >
`window< D > to_window (const std::set< D, C > &s)`

Convert an `std::set` `s` of delta-sites into a window.

- template<typename I >
`window< typename I::site::dpsite > to_window (const Image< I > &ima)`

Convert a binary image `ima` into a window.

- template<typename S >
`window< typename S::site::dpsite > to_window (const Site_Set< S > &pset)`

Convert a site set `pset` into a window.

Variables

- `fun::C< R(*)(A)> to_fun (R(*f)(A))`
Convert a C unary function into an `mln::fun::C`.

9.27.1 Detailed Description

Namespace of conversion routines.

9.27.2 Function Documentation

9.27.2.1 template<typename V > void mln::convert::from_to (const float & *from*, Value< V > & *to*)

Conversion of a float `from` towards a value `to`.

9.27.2.2 template<typename V> void mln::convert::from_to (const int & *from*, Value< V > & *to*)

Conversion of a int *from* towards a value *to*.

9.27.2.3 template<typename V> void mln::convert::from_to (const double & *from*, Value< V > & *to*)

Conversion of a double *from* towards a value *to*.

9.27.2.4 template<typename V> void mln::convert::from_to (const unsigned & *from*, Value< V > & *to*)

Conversion of an unsigned *from* towards a value *to*.

9.27.2.5 template<typename S> mln::convert::mln_image_from_grid (typename S::site::grid , bool) const [inline]

Convert a point set pset into a binary image.

Width of the converted image will be pset.bbox + 2 * border.

9.27.2.6 template<typename W> mln::convert::mln_image_from_grid (typename W::site::grid , bool) const

Convert a window *win* into a binary image.

9.27.2.7 template<typename W> mln::convert::mln_image_from_grid (typename W::site::grid , mln_weight(W)) const

Convert a weighted window *w_win* into an image.

9.27.2.8 template<typename N> mln::convert::mln_image_from_grid (typename N::site::grid , bool) const

Convert a neighborhood *nbh* into a binary image.

9.27.2.9 template<typename N> mln::convert::mln_window (N) const [inline]

Convert a neighborhood *nbh* into a window.

Definition at line 74 of file to_window.hh.

9.27.2.10 template<typename T, typename O> T mln::convert::to (const O & *from*) [inline]

Conversion of the object *from* towards an object with type *T*.

Definition at line 63 of file to.hh.

References mln::mln_exact().

Referenced by mln::make_debug_graph_image().

9.27.2.11 template<typename P> P::dpoint mln::convert::to_dpoint (const Point_Site< P > & p) [inline]

Convert a point site *p* into a delta-point.

Definition at line 52 of file to_dpoint.hh.

9.27.2.12 template<typename I> pw::value_<I> mln::convert::to_fun (const Image< I > & ima)

Convert an image into a function.

Definition at line 64 of file to_fun.hh.

9.27.2.13 template<typename T> image1d<unsigned> mln::convert::to_image (const histo::array< T > & h)

Convert an histo *h* into an image1d<unsigned>.

9.27.2.14 template<typename I> p_array< typename I::psite > mln::convert::to_p_array (const Image< I > & img) [inline]

Convert an image *img* into a [p_array](#).

Definition at line 98 of file to_p_array.hh.

References mln::p_array< P >::append().

9.27.2.15 template<typename S> p_array< typename S::psite > mln::convert::to_p_array (const Site_Set< S > & pset) [inline]

Convert a point set *pset* into a [p_array](#) (point set vector).

Definition at line 68 of file to_p_array.hh.

References mln::p_array< P >::append().

9.27.2.16 template<typename W> p_array< typename W::psite > mln::convert::to_p_array (const Window< W > & win, const typename W::psite & p) [inline]

Convert a window *win* centered at point *p* into a [p_array](#) (point set vector).

Definition at line 82 of file to_p_array.hh.

References mln::p_array< P >::append(), and mln::p_array< P >::reserve().

9.27.2.17 template<typename N> p_set< typename N::psite > mln::convert::to_p_set (const Neighborhood< N > & nbh) [inline]

Convert a neighborhood *nbh* into a site set.

Definition at line 83 of file to_p_set.hh.

References mln::p_set< P >::insert().

9.27.2.18 template<typename I> p_set< typename I::psite > mln::convert::to_p_set (const Image< I > & ima) [inline]

Convert a binary image `ima` into a site set.

Definition at line 97 of file to_p_set.hh.

References mln::p_set< P >::insert().

9.27.2.19 template<typename P, typename C> p_set< P > mln::convert::to_p_set (const std::set< P, C > & s) [inline]

Convert an std::set `s` of sites into a site set.

`C` is the comparison functor.

Definition at line 130 of file to_p_set.hh.

References mln::p_set< P >::insert().

9.27.2.20 template<typename S> p_set< typename S::psite > mln::convert::to_p_set (const Site_Set< S > & ps) [inline]

Convert any site set `ps` into a 'mln_p_set' site set.

Definition at line 144 of file to_p_set.hh.

References mln::p_set< P >::insert().

9.27.2.21 template<typename W> p_set< typename W::psite > mln::convert::to_p_set (const Window< W > & win) [inline]

Convert a `Window` `win` into a site set.

Definition at line 117 of file to_p_set.hh.

References mln::p_set< P >::insert().

9.27.2.22 template<typename I> QImage mln::convert::to_qimage (const Image< I > & ima) [inline]

Convert a Milena image to a QImage.

Definition at line 279 of file to_qimage.hh.

9.27.2.23 template<typename N> window< typename N::dpoint > mln::convert::to_upper_window (const Neighborhood< N > & nbh) [inline]

Convert a neighborhood `nbh` into an upper window.

Definition at line 82 of file to_upper_window.hh.

References mln::window< D >::insert().

**9.27.2.24 template<typename W> window< typename W::dpsite >
mln::convert::to_upper_window (const Window< W > & win) [inline]**

Convert a window `nbh` into an upper window.

Definition at line 67 of file `to_upper_window.hh`.

References mln::window< D >::insert().

**9.27.2.25 template<typename D, typename C> window< D > mln::convert::to_window (const
std::set< D, C > & s) [inline]**

Convert an `std::set` `s` of delta-sites into a window.

Definition at line 128 of file `to_window.hh`.

References mln::window< D >::insert().

**9.27.2.26 template<typename I> window< typename I::site::dpsite > mln::convert::to_window (const
Image< I > & ima) [inline]**

Convert a binary image `ima` into a window.

Definition at line 94 of file `to_window.hh`.

References mln::window< D >::insert().

Referenced by `to_window()`.

**9.27.2.27 template<typename S> window< typename S::site::dpsite > mln::convert::to_window
(const Site_Set< S > & pset) [inline]**

Convert a site set `pset` into a window.

Definition at line 117 of file `to_window.hh`.

References `to_window()`.

9.27.3 Variable Documentation

9.27.3.1 pw::value_< I > mln::convert::to_fun [inline]

Convert a C unary function into an `mln::fun::C`.

Definition at line 45 of file `to_fun.hh`.

9.28 mln::data Namespace Reference

Namespace of image processing routines related to pixel data.

Namespaces

- namespace **approx**
Namespace of image processing routines related to pixel levels with approximation.
- namespace **impl**
Implementation namespace of data namespace.
- namespace **naive**
Namespace of image processing routines related to pixel levels with naive approach.

Functions

- template<typename I, typename O >
`void abs (const Image< I > &input, Image< O > &output)`
- template<typename I >
`void abs_inplace (Image< I > &input)`
- template<typename I , typename F >
`void apply (Image< I > &input, const Function_v2v< F > &f)`
- template<typename A , typename I >
`A::result compute (const Accumulator< A > &a, const Image< I > &input)`
Compute an accumulator onto the pixel values of the image `input`.
- template<typename A , typename I >
`A::result compute (Accumulator< A > &a, const Image< I > &input)`
Compute an accumulator onto the pixel values of the image `input`.
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret convert (const V &v, const Image< I > &input)`
Convert the image `input` by changing the value type.
- template<typename I , typename W , typename O >
`void fast_median (const Image< I > &input, const Window< W > &win, Image< O > &output)`
- template<typename I , typename D >
`void fill (Image< I > &ima, const D &data)`
- template<typename I , typename J >
`void fill_with_image (Image< I > &ima, const Image< J > &data)`
Fill the image `ima` with the values of the image `data`.
- template<typename I , typename W >
`mln::trait::concrete< I >::ret median (const Image< I > &input, const Window< W > &win)`
- template<typename A , typename I >
`mln_meta_accu_result (A, typename I::value) compute(const Meta_Accumulator< A > &a)`
Compute an accumulator onto the pixel values of the image `input`.
- template<typename I , typename J >
`void paste (const Image< I > &input, Image< J > &output)`
Paste the contents of image `input` into the image `output`.

- template<typename I , typename J >
`void paste_without_localization (const Image< I > &input, Image< J > &output)`
Paste the contents of image `input` into the image `output` without taking into account the localization of sites.

- template<typename I >
`void replace (Image< I > &input, const typename I::value &old_value, const typename I::value &new_value)`
- template<typename I , typename V >
`mln::trait::ch_value< I, V >::ret saturate (const Image< I > &input, const V &min, const V &max)`
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret saturate (V v, const Image< I > &input)`
- template<typename I >
`void saturate_inplace (Image< I > &input, const typename I::value &min, const typename I::value &max)`
- template<typename I >
`util::array< unsigned > sort_offsets_increasing (const Image< I > &input)`
Sort pixel offsets of the image `input` wrt increasing pixel values.

- template<typename I >
`p_array< typename I::psite > sort_psites_decreasing (const Image< I > &input)`
- template<typename I >
`p_array< typename I::psite > sort_psites_increasing (const Image< I > &input)`
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret stretch (const V &v, const Image< I > &input)`
- template<typename I , typename O >
`void to_enc (const Image< I > &input, Image< O > &output)`
- template<typename I1 , typename I2 , typename F >
`mln::trait::ch_value< I1, typename F::result >::ret transform (const Image< I1 > &input1, const Image< I2 > &input2, const Function_vv2v< F > &f)`
- template<typename I , typename F >
`mln::trait::ch_value< I, typename F::result >::ret transform (const Image< I > &input, const Function_v2v< F > &f)`
- template<typename I1 , typename I2 , typename F >
`void transform_inplace (Image< I1 > &ima, const Image< I2 > &aux, const Function_vv2v< F > &f)`
- template<typename I , typename F >
`void transform_inplace (Image< I > &ima, const Function_v2v< F > &f)`
- template<typename A , typename I >
`A::result update (Accumulator< A > &a, const Image< I > &input)`
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret wrap (const V &v, const Image< I > &input)`
Routine to wrap values such as $0 \rightarrow 0$ and $[l, l_{max}]$ maps to $[l, L_{max}]$ (using modulus).

- template<typename I , typename V >
`void fill_with_value (Image< I > &ima, const V &val)`
Fill the whole image `ima` with the single value `v`.

9.28.1 Detailed Description

Namespace of image processing routines related to pixel data.

9.28.2 Function Documentation

9.28.2.1 template<typename I, typename O> void mln::data::abs (const Image< I > & *input*, Image< O > & *output*) [inline]

Apply the absolute value (abs) function to image pixel values.

Parameters

[in] *input* The input image.

[out] *output* The output image.

Definition at line 68 of file data/abs.hh.

References transform().

9.28.2.2 template<typename I> void mln::data::abs_inplace (Image< I > & *input*) [inline]

Apply the absolute value (abs) function to image pixel values.

Parameters

[in, out] *input* The input image.

Definition at line 80 of file data/abs.hh.

References apply().

9.28.2.3 template<typename I, typename F> void mln::data::apply (Image< I > & *input*, const Function_v2v< F > & *f*) [inline]

Apply a function-object to the image *input*.

Parameters

[in, out] *input* The input image.

[in] *f* The function-object.

This routine runs:

for all p of *input*, *input*(p) = *f*(*input*(p))

This routine is equivalent to data::transform(*input*, *f*, *input*) but it is faster since a single iterator is required.

Definition at line 95 of file apply.hh.

Referenced by abs_inplace(), and saturate_inplace().

9.28.2.4 template<typename A, typename I> A::result mln::data::compute (const Accumulator< A > & *a*, const Image< I > & *input*) [inline]

Compute an accumulator onto the pixel values of the image *input*.

Be ware that the given accumulator won't be modified and won't store any result.

Parameters

[in] *a* An accumulator.

[in] *input* The input image.

Returns

The accumulator result.

It fully relies on [data::update](#).

Definition at line 93 of file data/compute.hh.

Referenced by mln::labeled_image< I >::labeled_image(), mln::estim::mean(), mln::estim::min_max(), and mln::estim::sum().

9.28.2.5 template<typename A , typename I > A::result mln::data::compute (Accumulator< A > & *a*, const Image< I > & *input*) [inline]

Compute an accumulator onto the pixel values of the image *input*.

Parameters

[in, out] *a* An accumulator.

[in] *input* The input image.

Returns

The accumulator result.

It fully relies on [data::update](#).

Definition at line 104 of file data/compute.hh.

9.28.2.6 template<typename V , typename I > mln::trait::ch_value< I, V >::ret mln::data::convert (const V & *v*, const Image< I > & *input*) [inline]

Convert the image *input* by changing the value type.

Parameters

[in] *v* A value of the destination type.

[in] *input* The input image.

Definition at line 154 of file mln/data/convert.hh.

Referenced by mln::morpho::watershed::superpose(), and mln::debug::superpose().

9.28.2.7 template<typename I , typename W , typename O > void mln::data::fast_median (const Image< I > & *input*, const Window< W > & *win*, Image< O > & *output*) [inline]

Compute in *output* the median filter of image *input* by the window *win*.

Parameters

- [in] **input** The image to be filtered.
- [in] **win** The window.
- [in, out] **output** The output image.

Precondition

`input` and `output` have to be initialized.

Definition at line 167 of file `fast_median.hh`.

9.28.2.8 template<typename I , typename D > void mln::data::fill (Image< I > & *ima*, const D & *data*) [inline]

Fill the whole image `ima` with the data provided by `aux`.

Parameters

- [in, out] **ima** The image to be filled.
- [in] **data** The auxiliary data to fill the image `ima`.

Precondition

`ima` has to be initialized.

Definition at line 138 of file `data/fill.hh`.

Referenced by `mln::draw::box_plain()`, `mln::draw::dashed_line()`, `mln::topo::detach()`, `mln::util::display_branch()`, `mln::transform::distance_and_closest_point_geodesic()`, `mln::duplicate()`, `mln::make::edge_image()`, `mln::morpho::tree::filter::filter()`, `mln::transform::hough()`, `mln::registration::icp()`, `mln::accu::stat::histo3d_rgb< V >::init()`, `mln::graph::labeling()`, `mln::morpho::laplacian()`, `mln::make_debug_graph_image()`, `mln::morpho::tree::filter::max()`, `mln::geom::mesh_corner_point_area()`, `mln::geom::mesh_normal()`, `mln::morpho::meyer_wst()`, `mln::morpho::tree::filter::min()`, `mln::debug::mosaic()`, `mln::debug::slices_2d()`, `mln::morpho::watershed::superpose()`, `mln::debug::superpose()`, `mln::morpho::watershed::topological()`, and `mln::geom::translate()`.

9.28.2.9 template<typename I , typename J > void mln::data::fill_with_image (Image< I > & *ima*, const Image< J > & *data*) [inline]

Fill the image `ima` with the values of the image `data`.

Parameters

- [in, out] **ima** The image to be filled.
- [in] **data** The image.

Warning

The definition domain of `ima` has to be included in the one of `data`.

Precondition

`ima.domain <= data.domain`.

Definition at line 124 of file `fill_with_image.hh`.

9.28.2.10 template<typename I , typename V > void mln::data::fill_with_value (Image< I > & ima, const V & val) [inline]

Fill the whole image *ima* with the single value *v*.

Parameters

[in, out] *ima* The image to be filled.

[in] *val* The value to assign to all sites.

Precondition

ima has to be initialized.

Definition at line 130 of file fill_with_value.hh.

Referenced by mln::p_image< I >::clear().

9.28.2.11 template<typename I , typename W > mln::trait::concrete< I >::ret mln::data::median (const Image< I > & input, const Window< W > & win)

Compute in *output* the median filter of image *input* by the window *win*.

Parameters

[in] *input* The image to be filtered.

[in] *win* The window.

Precondition

input have to be initialized.

Definition at line 270 of file median.hh.

9.28.2.12 template<typename A , typename I > mln::data::mln_meta_accu_result (A , typename I::value) const [inline]

Compute an accumulator onto the pixel values of the image *input*.

Parameters

[in] *a* A meta-accumulator.

[in] *input* The input image.

Returns

The accumulator result.

9.28.2.13 template<typename I , typename J > void mln::data::paste (const Image< I > & input, Image< J > & output) [inline]

Paste the contents of image *input* into the image *output*.

Parameters

- [in] ***input*** The input image providing pixels values.
- [in, out] ***output*** The image in which values are assigned.

This routine runs:

for all p of *input*, *output*(p) = *input*(p).

Warning

The definition domain of *input* has to be included in the one of *output*; so using [mln::safe_image](#) does not make pasting outside the output domain work.

Precondition

input.domain <= *output*.domain

Definition at line 137 of file paste.hh.

Referenced by [mln::make::image3d\(\)](#), [mln::draw::line\(\)](#), [mln::debug::mosaic\(\)](#), [mln::geom::rotate\(\)](#), [mln::debug::slices_2d\(\)](#), and [mln::labeling::superpose\(\)](#).

9.28.2.14 template<typename I , typename J > void mln::data::paste_without_localization (const Image< I > & *input*, Image< J > & *output*) [inline]

Paste the contents of image *input* into the image *output* without taking into account the localization of sites.

Parameters

- [in] ***input*** The input image providing pixels values.
- [in, out] ***output*** The image in which values are assigned.

Definition at line 349 of file paste_without_localization.hh.

9.28.2.15 template<typename I > void mln::data::replace (Image< I > & *input*, const typename I::value & *old_value*, const typename I::value & *new_value*)

Replace *old_value* by *new_value* in the image *input*

Parameters

- [in] ***input*** The input image.
- [in] ***old_value*** The value to be replaced...
- [in] ***new_value*** ...by this one.

Definition at line 88 of file replace.hh.

9.28.2.16 template<typename V , typename I > mln::trait::ch_value< I, V >::ret mln::data::saturate (V *v*, const Image< I > & *input*) [inline]

Apply the saturate function to image pixel values.

Parameters

[in] *v* A value of the output type.

[in] *input* The input image.

The saturation is based on the min and max values of the output value type. This assumes that the range of values in the input image is larger than the one of the output image.

Definition at line 87 of file data/saturate.hh.

References transform().

**9.28.2.17 template<typename I , typename V > mln::trait::ch_value< I, V >::ret
mln::data::saturate (const Image< I > & *input*, const V & *min*, const V & *max*) [inline]**

Apply the saturate function to image pixel values.

Parameters

[in] *input* The input image.

[in] *min* The minimum output value.

[in] *max* The maximum output value.

Definition at line 103 of file data/saturate.hh.

References transform().

9.28.2.18 template<typename I > void mln::data::saturate_inplace (Image< I > & *input*, const typename I::value & *min*, const typename I::value & *max*) [inline]

Apply the saturate function to image pixel values.

Parameters

[in, out] *input* The input image.

[in] *min* The minimum output value.

[in] *max* The maximum output value

Definition at line 119 of file data/saturate.hh.

References apply().

9.28.2.19 template<typename I > util::array< unsigned > mln::data::sort_offsets_increasing (const Image< I > & *input*) [inline]

Sort pixel offsets of the image *input* wrt increasing pixel values.

Definition at line 298 of file sort_offsets.hh.

9.28.2.20 template<typename I> p_array< typename I::psite > mln::data::sort_psites_-decreasing (const Image< I > & *input*) [inline]

Sort psites the image *input* through a function *f* to set the *output* image in decreasing way.

Parameters

[in] *input* The input image.

Precondition

input.is_valid

Definition at line 229 of file sort_psites.hh.

Referenced by mln::morpho::tree::min_tree().

9.28.2.21 template<typename I> p_array< typename I::psite > mln::data::sort_psites_-increasing (const Image< I > & *input*) [inline]

Sort psites the image *input* through a function *f* to set the *output* image in increasing way.

Parameters

[in] *input* The input image.

Precondition

input.is_valid

Definition at line 219 of file sort_psites.hh.

Referenced by mln::morpho::tree::max_tree().

9.28.2.22 template<typename V, typename I> mln::trait::ch_value< I, V >::ret mln::data::stretch (const V & *v*, const Image< I > & *input*) [inline]

Stretch the values of *input* so that they can be stored in *output*.

Parameters

[in] *v* A value to set the output value type.

[in] *input* The input image.

Returns

A stretch image with values of the same type as *v*.

Precondition

input.is_valid

Definition at line 128 of file stretch.hh.

References mln::data::impl::stretch().

9.28.2.23 template<typename I , typename O > void mln::data::to_enc (const Image< I > & input, Image< O > & output) [inline]

Set the `output` image with the encoding values of the image `input` pixels.

Parameters

- [in] `input` The input image.
- [out] `output` The result image.

Precondition

```
output.domain >= input.domain
```

Definition at line 60 of file data/to_enc.hh.

References transform().

9.28.2.24 template<typename I , typename F > mln::trait::ch_value< I, typename F::result >::ret mln::data::transform (const Image< I > & input, const Function_v2v< F > & f) [inline]

Transform the image `input` through a function `f`.

Parameters

- [in] `input` The input image.
- [in] `f` The function.

This routine runs:

for all `p` of `input`, `output(p) = f(input(p))`.

Definition at line 202 of file data/transform.hh.

Referenced by `abs()`, `mln::logical::and_not()`, `mln::labeling::colorize()`, `mln::arith::diff_abs()`, `mln::labeling::fill_holes()`, `mln::linear::mln_ch_convolve()`, `mln::linear::mln_ch_convolve_grad()`, `mln::labeling::pack()`, `mln::labeling::pack_inplace()`, `mln::labeling::relabel()`, `saturate()`, `mln::data::impl::stretch()`, `to_enc()`, `mln::labeling::wrap()`, and `wrap()`.

9.28.2.25 template<typename I1 , typename I2 , typename F > mln::trait::ch_value< I1, typename F::result >::ret mln::data::transform (const Image< I1 > & input1, const Image< I2 > & input2, const Function_vv2v< F > & f) [inline]

Transform two images `input1` `input2` through a function `f`.

Parameters

- [in] `input1` The 1st input image.
- [in] `input2` The 2nd input image.
- [in] `f` The function.

This routine runs:

for all `p` of `input`, `output(p) = f(input1(p), input2(p))`.

Definition at line 219 of file data/transform.hh.

9.28.2.26 template<typename I1 , typename I2 , typename F > void mln::data::transform_inplace (Image< I1 > & ima, const Image< I2 > & aux, const Function_vv2v< F > & f)

Transform inplace the image *ima* with the image *aux* through a function *f*.

Parameters

[in] *ima* The image to be transformed.

[in] *aux* The auxiliary image.

[in] *f* The function.

This routine runs:

for all p of *ima*, *ima*(p) = *f*(*ima*(p), *aux*(p)).

Definition at line 502 of file transform_inplace.hh.

9.28.2.27 template<typename I , typename F > void mln::data::transform_inplace (Image< I > & ima, const Function_v2v< F > & f)

Transform inplace the image *ima* through a function *f*.

Parameters

[in, out] *ima* The image to be transformed.

[in] *f* The function.

This routine runs:

for all p of *ima*, *ima*(p) = *f*(*ima*(p)).

Definition at line 490 of file transform_inplace.hh.

Referenced by *mln::logical::and_inplace()*, *mln::logical::and_not_inplace()*, *mln::logical::not_inplace()*, *mln::logical::or_inplace()*, *mln::labeling::relabel_inplace()*, and *mln::logical::xor_inplace()*.

9.28.2.28 template<typename A , typename I > A::result mln::data::update (Accumulator< A > & a, const Image< I > & input) [inline]

Update an accumulator with the pixel values of the image *input*.

Parameters

[in] *a* The accumulator.

[in] *input* The input image.

Returns

The accumulator result.

Definition at line 191 of file update.hh.

9.28.2.29 template<typename V , typename I > mln::trait::ch_value< I, V >::ret mln::data::wrap (const V & v, const Image< I > & input)

Routine to wrap values such as 0 -> 0 and [1, lmax] maps to [1, Lmax] (using modulus).

Parameters

- [in] *v* The target value type.
- [in] *input* Input image.

Returns

An image with wrapped values.

Definition at line 65 of file data/wrap.hh.

References transform().

9.29 mln::data::approx Namespace Reference

Namespace of image processing routines related to pixel levels with approximation.

Namespaces

- namespace [impl](#)
Implementation namespace of [data::approx](#) namespace.

Functions

- template<typename I >
`mln::trait::concrete< I >::ret median (const Image< I > &input, const win::rectangle2d &win)`
- template<typename I >
`mln::trait::concrete< I >::ret median (const Image< I > &input, const win::octagon2d &win)`
- template<typename I >
`mln::trait::concrete< I >::ret median (const Image< I > &input, const win::disk2d &win)`

9.29.1 Detailed Description

Namespace of image processing routines related to pixel levels with approximation.

9.29.2 Function Documentation

9.29.2.1 template<typename I > mln::trait::concrete< I >::ret mln::data::approx::median (const Image< I > & input, const win::rectangle2d & win) [inline]

Compute in *output* an approximate of the median filter of image *input* by the 2D rectangle *win*.

Parameters

- [in] *input* The image to be filtered.

[in] **win** The rectangle.

The approximation is based on a vertical median ran after an horizontal median.

Precondition

input and output have to be initialized.

Definition at line 112 of file approx/median.hh.

Referenced by median().

9.29.2.2 template<typename I > mln::trait::concrete< I >::ret mln::data::approx::median (const Image< I > & input, const win::octagon2d & win) [inline]

Compute in output an approximate of the median filter of image input by the 2D octagon win.

Parameters

[in] **input** The image to be filtered.

[in] **win** The octagon.

The approximation is based on a vertical median and an horizontal median an two diagonal median.

Precondition

input and output have to be initialized.

Definition at line 159 of file approx/median.hh.

References median().

9.29.2.3 template<typename I > mln::trait::concrete< I >::ret mln::data::approx::median (const Image< I > & input, const win::disk2d & win) [inline]

Compute in output an approximate of the median filter of image input by the 2D disk win.

Parameters

[in] **input** The image to be filtered.

[in] **win** The disk.

The approximation is based on a vertical median and an horizontal median an two diagonal median.

Precondition

input and output have to be initialized.

Definition at line 132 of file approx/median.hh.

References median().

9.30 mln::data::approx::impl Namespace Reference

Implementation namespace of [data::approx](#) namespace.

9.30.1 Detailed Description

Implementation namespace of [data::approx](#) namespace.

9.31 mln::data::impl Namespace Reference

Implementation namespace of data namespace.

Namespaces

- namespace [generic](#)
Generic implementation namespace of data namespace.

Functions

- template<typename I , typename J >
`void paste_without_localization_fast (const Image< I > &input_, Image< J > &output_)`
Paste data to an image without using localization. Performs a point-wise copy.
- template<typename I , typename J >
`void paste_without_localization_fastest (const Image< I > &input_, Image< J > &output_)`
Paste data to an image without using localization. Performs a one-block memory copy.
- template<typename I , typename J >
`void paste_without_localization_lines (const Image< I > &input_, Image< J > &output_)`
Paste data to an image without using localization. Performs a line-per-line memory copy.
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret stretch (const V &v, const Image< I > &input)`
Generic implementation of [data::stretch](#).
- template<typename I , typename F >
`void transform_inplace_lowq (Image< I > &input_, const Function_v2v< F > &f_)`
Specialized implementation.
- template<typename A , typename I >
`A::result update_fastest (Accumulator< A > &a_, const Image< I > &input_)`
Fastest implementation of [data::update](#).

9.31.1 Detailed Description

Implementation namespace of data namespace.

9.31.2 Function Documentation

9.31.2.1 template<typename I , typename J > void mln::data::impl::paste_without_localization_fast (const Image< I > & *input_*, Image< J > & *output_*) [inline]

Paste data to an image without using localization. Performs a point-wise copy.

input and *output* must have both the following properties:

- mln::trait::image::value_alignment::with_grid
- mln::trait::image::value_storage::one_block
- mln::trait::image::value_access::direct
- mln::trait::image::ext_domain::some

They must also fulfill the following conditions:

- Same domain size.

Definition at line 220 of file paste_without_localization.hh.

9.31.2.2 template<typename I , typename J > void mln::data::impl::paste_without_localization_fastest (const Image< I > & *input_*, Image< J > & *output_*) [inline]

Paste data to an image without using localization. Performs a one-block memory copy.

input and *output* must have both the following properties:

- mln::trait::image::value_alignment::with_grid
- mln::trait::image::value_storage::one_block
- mln::trait::image::value_access::direct
- mln::trait::image::ext_domain::some

They must also fulfill the following conditions:

- Same border size.
- Same domain size.
- Same value type.

Definition at line 142 of file paste_without_localization.hh.

9.31.2.3 template<typename I , typename J > void mln::data::impl::paste_without_localization_lines (const Image< I > & *input_*, Image< J > & *output_*) [inline]

Paste data to an image without using localization. Performs a line-per-line memory copy.

input and *output* must have both the following properties:

- mln::trait::image::value_alignment::with_grid
- mln::trait::image::value_storage::one_block
- mln::trait::image::value_access::direct
- mln::trait::image::ext_domain::some

They must also fulfill the following conditions:

- Same domain size.
- Same value type.

Definition at line 179 of file paste_without_localization.hh.

9.31.2.4 template<typename V , typename I > mln::trait::ch_value< I , V >::ret mln::data::impl::stretch (const V & *v*, const Image< I > & *input*) [inline]

Generic implementation of [data::stretch](#).

Parameters

[in] *v* A value to set the output value type.

[in] *input* The input image.

Returns

A stretch image with values of the same type as *v*.

Definition at line 83 of file stretch.hh.

References [mln::initialize\(\)](#), [mln::estim::min_max\(\)](#), and [mln::data::transform\(\)](#).

Referenced by [mln::data::stretch\(\)](#).

9.31.2.5 template<typename I , typename F > void mln::data::impl::transform_inplace_lowq (Image< I > & *input_*, const Function_v2v< F > & *f_*)

Specialized implementation.

Definition at line 203 of file transform_inplace.hh.

9.31.2.6 template<typename A , typename I > A ::result mln::data::impl::update_fastest (Accumulator< A > & *a_*, const Image< I > & *input_*) [inline]

Fastest implementation of [data::update](#).

Parameters

- [in] *a_* The accumulator.
- [in] *input_* The input image.

Returns

The accumulator result.

Definition at line 129 of file update.hh.

9.32 mln::data::impl::generic Namespace Reference

Generic implementation namespace of data namespace.

Functions

- template<typename I , typename J >
void [fill_with_image](#) (Image< I > &*ima_*, const Image< J > &*data_*)
Generic implementation.
- template<typename I , typename V >
void [fill_with_value](#) (Image< I > &*ima_*, const V &*val*)
*Fill the whole image *ima* with the single value *v*.*
- template<typename I , typename J >
void [paste](#) (const Image< I > &*input_*, Image< J > &*output_*)
Generic implementation of [data::paste](#).
- template<typename I , typename F >
mln::trait::ch_value< I, typename F::result >::ret [transform](#) (const Image< I > &*input_*, const Function_v2v< F > &*f_*)
Generic implementation of [data::transform](#).
- template<typename I1 , typename I2 , typename F >
mln::trait::ch_value< I1, typename F::result >::ret [transform](#) (const Image< I1 > &*input1_*, const Image< I2 > &*input2_*, const Function_vv2v< F > &*f_*)
Generic implementation of [data::transform](#).
- template<typename I1 , typename I2 , typename F >
void [transform_inplace](#) (Image< I1 > &*ima_*, const Image< I2 > &*aux_*, const Function_vv2v< F > &*f_*)
Generic implementation of [transform_inplace](#).
- template<typename I , typename F >
void [transform_inplace](#) (Image< I > &*ima_*, const Function_v2v< F > &*f_*)

Generic implementation of transform_inplace.

- template<typename A , typename I >
A::result **update** (**Accumulator**< A > &a_, const **Image**< I > &input_)
Generic implementation of [data::update](#).

9.32.1 Detailed Description

Generic implementation namespace of data namespace.

9.32.2 Function Documentation

9.32.2.1 template<typename I , typename J > void mln::data::impl::generic::fill_with_image (Image< I > & ima_ , const Image< J > & data_)

Generic implementation.

Parameters

- [in, out] **ima_** The image to be filled.
- [in] **data_** The image.

Definition at line 100 of file fill_with_image.hh.

9.32.2.2 template<typename I , typename V > void mln::data::impl::generic::fill_with_value (Image< I > & ima_ , const V & val)

Fill the whole image **ima** with the single value **v**.

Parameters

- [in, out] **ima_** The image to be filled.
- [in] **val** The value to assign to all sites.

Precondition

ima has to be initialized.

Definition at line 103 of file fill_with_value.hh.

9.32.2.3 template<typename I , typename J > void mln::data::impl::generic::paste (const Image< I > & input_ , Image< J > & output_) [inline]

Generic implementation of [data::paste](#).

Parameters

- [in] **input_** The input image providing pixels values.
- [in, out] **output_** The image in which values are assigned.

Definition at line 111 of file paste.hh.

9.32.2.4 template<typename I , typename F > mln::trait::ch_value< I , typename F ::result >::ret mln::data::impl::generic::transform (const Image< I > & *input*_, const Function_v2v< F > & *f*_)

Generic implementation of [data::transform](#).

Parameters

- [in] *input*_ The input image.
- [in] *f*_ The function.

Definition at line 137 of file data/transform.hh.

References mln::initialize().

9.32.2.5 template<typename I1 , typename I2 , typename F > mln::trait::ch_value< I1 , typename F ::result >::ret mln::data::impl::generic::transform (const Image< I1 > & *input1*_, const Image< I2 > & *input2*_ , const Function_vv2v< F > & *f*_)

Generic implementation of [data::transform](#).

Parameters

- [in] *input1*_ The 1st input image.
- [in] *input2*_ The 2nd input image.
- [in] *f*_ The function.

Definition at line 166 of file data/transform.hh.

References mln::initialize().

9.32.2.6 template<typename I1 , typename I2 , typename F > void mln::data::impl::generic::transform_inplace (Image< I1 > & *ima*_ , const Image< I2 > & *aux*_ , const Function_vv2v< F > & *f*_)

Generic implementation of transform_inplace.

Parameters

- [in] *ima*_ The image to be transformed.
- [in] *aux*_ The auxiliary image.
- [in] *f*_ The function.

Definition at line 176 of file transform_inplace.hh.

9.32.2.7 template<typename I , typename F > void mln::data::impl::generic::transform_inplace (Image< I > & *ima*_ , const Function_v2v< F > & *f*_)

Generic implementation of transform_inplace.

Parameters

- [in, out] *ima*_ The image to be transformed.

[in] *f_* The function.

Definition at line 149 of file transform_inplace.hh.

9.32.2.8 template<typename A , typename I > A ::result mln::data::impl::generic::update (Accumulator< A > & *a_*, const Image< I > & *input_*) [inline]

Generic implementation of [data::update](#).

Parameters

[in] *a_* The accumulator.

[in] *input_* The input image.

Returns

The accumulator result.

Definition at line 100 of file update.hh.

9.33 mln::data::naive Namespace Reference

Namespace of image processing routines related to pixel levels with naive approach.

Namespaces

- namespace [impl](#)

Implementation namespace of data::naive namespace.

Functions

- template<typename I , typename W , typename O >
void [median](#) (const Image< I > &*input*, const Window< W > &*win*, Image< O > &*output*)
Compute in output the median filter of image input by the window win.

9.33.1 Detailed Description

Namespace of image processing routines related to pixel levels with naive approach.

9.33.2 Function Documentation

9.33.2.1 template<typename I , typename W , typename O > void mln::data::naive::median (const Image< I > & *input*, const Window< W > & *win*, Image< O > & *output*) [inline]

Compute in *output* the median filter of image *input* by the window *win*.

Parameters

- [in] **input** The image to be filtered.
- [in] **win** The window.
- [in, out] **output** The output image.

This is a NAIIVE version for test / comparison purpose so do NOT use it.

Precondition

`input` and `output` have to be initialized.

See also

[mln::data::median](#)

Definition at line 99 of file naive/median.hh.

9.34 mln::data::naive::impl Namespace Reference

Implementation namespace of [data::naive](#) namespace.

9.34.1 Detailed Description

Implementation namespace of [data::naive](#) namespace.

9.35 mln::debug Namespace Reference

Namespace of routines that help to debug.

Namespaces

- namespace **impl**
Implementation namespace of debug namespace.

Functions

- template<typename I , typename G , typename F >
void **draw_graph** ([Image](#)< I > &ima, const [p_vertices](#)< G, F > &pv, typename I::value vcolor, typename I::value ecolor)
Draw an image `ima` from a [mln::p_vertices](#) `pv`, with value `vcolor` for vertices, value `ecolor` for edges and 0 for the background.
- template<typename I , typename G , typename F , typename V , typename E >
void **draw_graph** ([Image](#)< I > &ima, const [p_vertices](#)< G, F > &pv, const [Function](#)< V > &vcolor_f_, const [Function](#)< E > &ecolor_f_)
Draw an image `ima` from a [mln::p_vertices](#) `pv`.

- template<typename I, typename G, typename F, typename V, typename E>
`void draw_graph (Image< I > &ima, const p_vertices< util::line_graph< G >, F > &pv, const Function< V > &vcolor_f_, const Function< E > &ecolor_f_)`
Draw an image `ima` from a `mln::p_vertices` `pv`.
- std::string `filename` (const std::string &filename, int id)
Constructs and returns a formatted output file name.
- signed short `format` (signed char v)
Format a signed char to print it properly, i.e., like an integer value.
- unsigned short `format` (unsigned char v)
Format an unsigned char to print it properly, i.e., like an integer value.
- template<typename T>
`const T & format (const T &v)`
Default version for formatting a value is a no-op.
- char `format` (bool v)
Format a Boolean to print it nicely: "1" for true and "-" for false.
- template<typename I>
`void iota (Image< I > &input, unsigned base_index)`
- template<typename I>
`mln::trait::concrete< I >::ret mosaic (const util::array< I > &input, unsigned n_horizontal, const typename I::value &bg)`
Create a single image from an array of image.
- template<typename I>
`void println (const std::string &msg, const Image< I > &input)`
Print the message `msg` and the image `input` on the standard output.
- template<typename I>
`void println (const Image< I > &input)`
Print the image `input` on the standard output.
- template<typename I>
`void println_with_border (const Image< I > &input)`
Print the image `input` on the standard output.
- void `put_word` (image2d< char > &inout, const point2d &word_start, const std::string &word)
Put the word starting at location `word_start` in the image `inout`.
- template<typename I>
`image2d< typename I::value > slices_2d (const Image< I > &input, unsigned n_horizontal, unsigned n_vertical, const typename I::value &bg)`
Create a 2D image of the slices of the 3D image `input`.

- template<typename I >
`image2d< typename I::value > slices_2d` (const `Image< I >` &input, float ratio_hv, const typename I::value &bg)

Create a 2D image of the slices of the 3D image input.

- template<typename I , typename J >
`mln::trait::ch_value< I, value::rgb8 >::ret superpose` (const `Image< I >` &input, const `Image< J >` &object)
- template<typename I , typename J >
`mln::trait::ch_value< I, value::rgb8 >::ret superpose` (const `Image< I >` &input_, const `Image< J >` &object_, const `value::rgb8` &object_color)

Superpose two images.

- template<typename I >
`void z_order` (`Image< I >` &input)

9.35.1 Detailed Description

Namespace of routines that help to debug.

9.35.2 Function Documentation

9.35.2.1 template<typename I , typename G , typename F > void mln::debug::draw_graph (`Image< I >` & ima, const `p_vertices< G, F >` & pv, typename I::value vcolor, typename I::value ecolor) [inline]

Draw an image `ima` from a `mln::p_vertices` `pv`, with value `vcolor` for vertices, value `ecolor` for edges and 0 for the background.

Definition at line 142 of file `draw_graph.hh`.

References `mln::p_vertices< G, F >::graph()`, and `mln::draw::line()`.

Referenced by `mln::make_debug_graph_image()`.

9.35.2.2 template<typename I , typename G , typename F , typename V , typename E > void mln::debug::draw_graph (`Image< I >` & ima, const `p_vertices< G, F >` & pv, const `Function< V >` & vcolor_f_, const `Function< E >` & ecolor_f_) [inline]

Draw an image `ima` from a `mln::p_vertices` `pv`.

Colors for vertices are defined through `vcolor_f_`. Colors for edges are defined though `ecolor_f_`.

Definition at line 173 of file `draw_graph.hh`.

References `mln::draw::box_plain()`, `mln::box< P >::crop_wrt()`, `mln::p_vertices< G, F >::graph()`, and `mln::draw::line()`.

9.35.2.3 template<typename I , typename G , typename F , typename V , typename E > void mln::debug::draw_graph(Image< I > & ima, const p_vertices< util::line_graph< G >, F > & pv, const Function< V > & vcolor_f_, const Function< E > & ecolor_f_) [inline]

Draw an image `ima` from a `mln::p_vertices` `pv`.

Colors for vertices are defined through `vcolor_f_`. Colors for edges are defined though `ecolor_f_`.

Definition at line 211 of file `draw_graph.hh`.

References `mln::p_line2d::begin()`, `mln::p_line2d::end()`, `mln::p_vertices< G, F >::graph()`, and `mln::draw::line()`.

9.35.2.4 std::string mln::debug::filename(const std::string & filename, int id = -1) [inline]

Constructs and returns a formatted output file name.

The file name is formatted as follow:

‘filename_prefix‘_‘id‘_‘filename‘

Where:

- ‘filename_prefix‘ can be set through the global variable `debug::internal::filename_prefix`.

‘postfix_id‘ is autoincremented by default. Its value can be forced.

- ‘filename‘ is the given filename

Definition at line 86 of file `filename.hh`.

9.35.2.5 signed short mln::debug::format(signed char v) [inline]

Format a signed char to print it properly, i.e., like an integer value.

Definition at line 78 of file `format.hh`.

9.35.2.6 unsigned short mln::debug::format(unsigned char v) [inline]

Format an unsigned char to print it properly, i.e., like an integer value.

Definition at line 85 of file `format.hh`.

9.35.2.7 template<typename T > const T & mln::debug::format(const T & v) [inline]

Default version for formatting a value is a no-op.

Definition at line 64 of file `format.hh`.

Referenced by `mln::value::operator<<()`, and `mln::Gpoint< E >::operator<<()`.

9.35.2.8 char mln::debug::format (bool v) [inline]

Format a Boolean to print it nicely: "|" for true and "-" for false.

Definition at line 71 of file format.hh.

9.35.2.9 template<typename I> void mln::debug::iota (Image< I > & input, unsigned base_index) [inline]

Fill the image *input* with successive values.

Parameters

[in, out] *input* The image in which values are assigned.

Definition at line 88 of file debug/iota.hh.

References iota().

Referenced by iota().

9.35.2.10 template<typename I> mln::trait::concrete< I >::ret mln::debug::mosaic (const util::array< I > & input, unsigned n_horizontal, const typename I::value & bg) [inline]

Create a single image from an array of image.

The size of the output image is defined by:

width = n_horizontal * max(input[i].ncols()) height = (input.size() / n_horizontal) * max(input[i].nrows())

Returns

a single image where all the input images are displayed as a mosaic.

Definition at line 77 of file mosaic.hh.

References mln::apply_p2p(), mln::data::fill(), and mln::data::paste().

9.35.2.11 template<typename I> void mln::debug::println (const std::string & msg, const Image< I > & input)

Print the message *msg* and the image *input* on the standard output.

Definition at line 98 of file println.hh.

References println().

9.35.2.12 template<typename I> void mln::debug::println (const Image< I > & input) [inline]

Print the image *input* on the standard output.

Definition at line 87 of file println.hh.

References mln::geom::bbox().

Referenced by println().

9.35.2.13 template<typename I > void mln::debug::println_with_border (const Image< I > & input) [inline]

Print the image `input` on the standard output.

Definition at line 79 of file `println_with_border.hh`.

References `mln::geom::bbox()`.

9.35.2.14 void mln::debug::put_word (image2d< char > & inout, const point2d & word_start, const std::string & word) [inline]

Put the `word` starting at location `word_start` in the image `inout`.

Definition at line 55 of file `put_word.hh`.

References `mln::image2d< T >::has()`, and `mln::point< G, C >::last_coord()`.

9.35.2.15 template<typename I > image2d< typename I::value > mln::debug::slices_2d (const Image< I > & input, unsigned n_horizontal, unsigned n_vertical, const typename I::value & bg) [inline]

Create a 2D image of the slices of the 3D image `input`.

Definition at line 79 of file `slices_2d.hh`.

References `mln::apply_p2p()`, `mln::data::fill()`, and `mln::data::paste()`.

Referenced by `slices_2d()`.

9.35.2.16 template<typename I > image2d< typename I::value > mln::debug::slices_2d (const Image< I > & input, float ratio_hv, const typename I::value & bg)

Create a 2D image of the slices of the 3D image `input`.

Definition at line 162 of file `slices_2d.hh`.

References `slices_2d()`.

9.35.2.17 template<typename I , typename J > mln::trait::ch_value< I, value::rgb8 >::ret mln::debug::superpose (const Image< I > & input, const Image< J > & object)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 106 of file `debug/superpose.hh`.

References `mln::literal::red`, and `superpose()`.

9.35.2.18 template<typename I , typename J > mln::trait::ch_value< I, value::rgb8 >::ret mln::debug::superpose (const Image< I > & input_, const Image< J > & object_, const value::rgb8 & object_color)

Superpose two images.

Parameters

- [in] ***input_*** An image. Its value type must be convertible toward `value::rgb8` thanks to a conversion operator or `convert::from_to`.
- [in] ***object_*** A scalar or labeled image. Objects used for superposition. have their pixel values different from 0.
- [in] ***object_color*** The color used to draw the objects in `object_`.

Precondition

`input_` and `object_` must have the same domain.

Returns

A color image.

Definition at line 79 of file `debug/superpose.hh`.

References `mln::data::convert()`, `mln::data::fill()`, and `mln::literal::zero`.

Referenced by `superpose()`.

9.35.2.19 template<typename I> void mln::debug::z_order(Image<I> & *input*) [inline]

Fill the image `input` with Z-order (curve) values.

Parameters

- [in, out] ***input*** The image in which values are assigned.

Reference: [http://en.wikipedia.org/wiki/Z-order_\(curve\)](http://en.wikipedia.org/wiki/Z-order_(curve))

Definition at line 142 of file `z_order.hh`.

9.36 mln::debug::impl Namespace Reference

Implementation namespace of debug namespace.

9.36.1 Detailed Description

Implementation namespace of debug namespace.

9.37 mln::def Namespace Reference

Namespace for core definitions.

TypeDefs

- `typedef short coord`

Definition of the default coordinate type: 'short'.

- **typedef float coordf**

Definition of the floating coordinate type.

Enumerations

- **enum**

Definition of the number of bits of the low quantization threshold.

9.37.1 Detailed Description

Namespace for core definitions.

9.37.2 Typedef Documentation

9.37.2.1 **typedef short mln::def::coord**

Definition of the default coordinate type: 'short'.

Definition at line 43 of file coord.hh.

9.37.2.2 **typedef float mln::def::coordf**

Definition of the floating coordinate type.

Definition at line 41 of file coordf.hh.

9.37.3 Enumeration Type Documentation

9.37.3.1 **anonymous enum**

Definition of the number of bits of the low quantization threshold.

Definition at line 43 of file low_quant_nbits.hh.

9.38 mln::display Namespace Reference

Namespace of routines that help to display images.

Namespaces

- namespace **impl**

Implementation namespace of display namespace.

9.38.1 Detailed Description

Namespace of routines that help to display images.

9.39 mln::display::impl Namespace Reference

Implementation namespace of display namespace.

Namespaces

- namespace [generic](#)
Generic implementation namespace of display namespace.

9.39.1 Detailed Description

Implementation namespace of display namespace.

9.40 mln::display::impl::generic Namespace Reference

Generic implementation namespace of display namespace.

9.40.1 Detailed Description

Generic implementation namespace of display namespace.

9.41 mln::doc Namespace Reference

The namespace [mln::doc](#) is only for documentation purpose.

Classes

- struct [Accumulator](#)
Documentation class for [mln::Accumulator](#).
- struct [Box](#)
Documentation class for [mln::Box](#).
- struct [Dpoint](#)
Documentation class for [mln::Dpoint](#).
- struct [Fastest_Image](#)
Documentation class for the concept of images that have the speed property set to "fastest".

- struct [Generalized_Pixel](#)
Documentation class for mln::Generalized_Pixel.
- struct [Image](#)
Documentation class for mln::Image.
- struct [Iterator](#)
Documentation class for mln::Iterator.
- struct [Neighborhood](#)
Documentation class for mln::Neighborhood.
- struct [Object](#)
Documentation class for mln::Object.
- struct [Pixel_Iterator](#)
Documentation class for mln::Pixel_Iterator.
- struct [Point_Site](#)
Documentation class for mln::Point_Site.
- struct [Site_Iterator](#)
Documentation class for mln::Site_Iterator.
- struct [Site_Set](#)
Documentation class for mln::Site_Set.
- struct [Value_Iterator](#)
Documentation class for mln::Value_Iterator.
- struct [Value_Set](#)
Documentation class for mln::Value_Set.
- struct [Weighted_Window](#)
Documentation class for mln::Weighted_Window.
- struct [Window](#)
Documentation class for mln::Window.

9.41.1 Detailed Description

The namespace [mln::doc](#) is only for documentation purpose. Since concepts are not yet part of the C++ Standard, they are not explicitly expressed in code. Their documentation is handled by their respective ghost class, located in this namespace.

Warning

The ghost classes located in [mln::doc](#) should not be used by the client.

9.42 mln::draw Namespace Reference

Namespace of drawing routines.

Functions

- template<typename I , typename B >
void **box** (**Image**< I > &ima, const **Box**< B > &b, const typename I::value &v)
- template<typename I , typename B >
void **box_plain** (**Image**< I > &ima, const **Box**< B > &b, const typename I::value &v)
- template<typename I >
void **dashed_line** (**Image**< I > &ima, const typename I::psite &beg, const typename I::psite &end, const typename I::value &v)
- template<typename I >
void **line** (**Image**< I > &ima, const typename I::psite &beg, const typename I::psite &end, const typename I::value &v)
- template<typename I >
void **plot** (**Image**< I > &ima, const typename I::point &p, const typename I::value &v)
- template<typename I >
void **polygon** (**Image**< I > &ima, const **p_array**< typename I::site > &par, const typename I::value &v, unsigned output_ratio)
- template<typename I , typename S >
void **site_set** (**Image**< I > &ima, const **Site_Set**< S > &s, const typename I::value &v, unsigned output_ratio=1)

9.42.1 Detailed Description

Namespace of drawing routines.

9.42.2 Function Documentation

9.42.2.1 template<typename I , typename B > void mln::draw::box (**Image**< I > & ima, const **Box**< B > & b, const typename I::value & v) [inline]

Draw a box at value v in image ima

Parameters

- [in,out] **ima** The image to be drawn.
- [in] **b** the boxto draw.
- [in] **v** The value to assign to all drawn pixels.

Precondition

- ima has to be initialized.
- ima has beg.
- ima has end.

Definition at line 72 of file draw/box.hh.

References line().

9.42.2.2 template<typename I , typename B > void mln::draw::box_plain (Image< I > & ima, const Box< B > & b, const typename I::value & v) [inline]

Draw a plain box at value *v* in image *ima*

Parameters

- [in, out] *ima* The image to be drawn.
- [in] *b* the box to draw.
- [in] *v* The value to assign to all drawn pixels.

Precondition

- ima* has to be initialized.
- ima* has *beg*.
- ima* has *end*.

Definition at line 71 of file box_plain.hh.

References mln::data::fill().

Referenced by mln::debug::draw_graph().

9.42.2.3 template<typename I > void mln::draw::dashed_line (Image< I > & ima, const typename I::psite & beg, const typename I::psite & end, const typename I::value & v) [inline]

Draw a dashed line at level *v* in image *ima* between the points *beg* and *end*.

Parameters

- [in, out] *ima* The image to be drawn.
- [in] *beg* The start point to drawn dashed_line.
- [in] *end* The end point to drawn dashed_line.
- [in] *v* The value to assign to all drawn pixels.

Precondition

- ima* has to be initialized.
- ima* has *beg*.
- ima* has *end*.

Definition at line 91 of file dashed_line.hh.

References mln::data::fill().

9.42.2.4 template<typename I > void mln::draw::line (Image< I > & ima, const typename I::psite & beg, const typename I::psite & end, const typename I::value & v) [inline]

Draw a line at level *v* in image *ima* between the points *beg* and *end*.

Parameters

- [in, out] *ima* The image to be drawn.

[in] ***beg*** The start point to drawn line.

[in] ***end*** The end point to drawn line.

[in] ***v*** The value to assign to all drawn pixels.

Precondition

ima has to be initialized.

ima has *beg*.

ima has *end*.

Definition at line 72 of file draw/line.hh.

References mln::data::paste().

Referenced by box(), mln::debug::draw_graph(), and polygon().

9.42.2.5 template<typename I> void mln::draw::plot (Image< I > & ima, const typename I::point & p, const typename I::value & v)

Plot a point at level *v* in image *ima*

Parameters

[in, out] ***ima*** The image to be drawn.

[in] ***p*** The point to be plotted.

[in] ***v*** The value to assign to all drawn pixels.

Precondition

ima has to be initialized.

ima has *p*.

9.42.2.6 template<typename I> void mln::draw::polygon (Image< I > & ima, const p_array< typename I::site > & par, const typename I::value & v, unsigned output_ratio)

Draw a polygon at level *v* in image *ima*.

Parameters

[in, out] ***ima*** The image to be drawn.

[in] ***par*** The polygon site set.

[in] ***v*** The value to assign to all drawn pixels.

Precondition

ima has to be initialized.

Definition at line 70 of file polygon.hh.

References line().

9.42.2.7 template<typename I , typename S > void mln::draw::site_set (Image< I > & ima, const Site_Set< S > & s, const typename I::value & v, unsigned output_ratio = 1)

Draw a sites with value v in image ima

Parameters

- [in, out] **ima** The image to be drawn.
- [in] **s** the site set to draw.
- [in] **v** The value to assign to all drawn pixels.
- [in] **output_ratio** size ratio between output image and the image from which the bboxes were calculated.

Precondition

s is included in ima domain.

Definition at line 65 of file mln/draw/site_set.hh.

9.43 mln::estim Namespace Reference

Namespace of estimation materials.

Functions

- template<typename I >
mln::value::props< typename I::value >::sum **mean** (const Image< I > &input)
Compute the mean value of the pixels of image input.
- template<typename S , typename I , typename M >
void **mean** (const Image< I > &input, M &result)
Compute the mean value of the pixels of image input.
- template<typename I >
void **min_max** (const Image< I > &input, typename I::value &min, typename I::value &max)
Compute the min and max values of the pixels of image input.
- template<typename I >
mln::value::props< typename I::value >::sum **sum** (const Image< I > &input)
Compute the sum value of the pixels of image input.
- template<typename I , typename S >
void **sum** (const Image< I > &input, S &result)
Compute the sum value of the pixels of image input.

9.43.1 Detailed Description

Namespace of estimation materials.

9.43.2 Function Documentation

9.43.2.1 template<typename I> mln::value::props< typename I::value >::sum mln::estim::mean (const Image< I > & *input*) [inline]

Compute the mean value of the pixels of image *input*.

Parameters

[in] *input* The image.

Returns

The mean value.

Definition at line 68 of file estim/mean.hh.

References mln::data::compute().

9.43.2.2 template<typename S, typename I, typename M> void mln::estim::mean (const Image< I > & *input*, M & *result*) [inline]

Compute the mean value of the pixels of image *input*.

Parameters

[in] *input* The image.

[out] *result* The mean value.

The free parameter *S* is the type used to compute the summation.

Definition at line 76 of file estim/mean.hh.

References mln::data::compute().

9.43.2.3 template<typename I> void mln::estim::min_max (const Image< I > & *input*, typename I::value & *min*, typename I::value & *max*) [inline]

Compute the min and max values of the pixels of image *input*.

Parameters

[in] *input* The image.

[out] *min* The minimum pixel value of *input*.

[out] *max* The maximum pixel value of *input*.

Definition at line 61 of file estim/min_max.hh.

References mln::data::compute().

Referenced by mln::data::impl::stretch(), and mln::make::voronoi().

9.43.2.4 template<typename I> mln::value::props< typename I::value >::sum mln::estim::sum (const Image< I > & input) [inline]

Compute the sum value of the pixels of image `input`.

Parameters

[in] `input` The image.

Returns

The sum value.

Definition at line 67 of file estim/sum.hh.

References mln::data::compute().

9.43.2.5 template<typename I, typename S> void mln::estim::sum (const Image< I > & input, S & result) [inline]

Compute the sum value of the pixels of image `input`.

Parameters

[in] `input` The image.

[out] `result` The sum value.

Definition at line 75 of file estim/sum.hh.

References mln::data::compute().

9.44 mln::extension Namespace Reference

Namespace of extension tools.

Functions

- template<typename I, typename W>
void `adjust` (const `Image< I >` &ima, const `Window< W >` &win)
Adjust the domain extension of image `ima` with the size of the window `win`.
- template<typename I, typename W>
void `adjust` (const `Image< I >` &ima, const `Weighted_Window< W >` &wwin)
Adjust the domain extension of image `ima` with the size of the weighted window `wwin`.
- template<typename I>
void `adjust` (const `Image< I >` &ima, unsigned delta)
Adjust the domain extension of image `ima` with the size `delta`.
- template<typename I, typename N>
void `adjust` (const `Image< I >` &ima, const `Neighborhood< N >` &nbh)

Adjust the domain extension of image `ima` with the size of the neighborhood `nbh`.

- template<typename I, typename W >
`void adjust_duplicate (const Image< I > &ima, const Window< W > &win)`
Adjust then duplicate.
- template<typename I, typename W >
`void adjust_fill (const Image< I > &ima, const Window< W > &win, const typename I::value &val)`
Adjust then fill.
- template<typename I >
`void duplicate (const Image< I > &ima)`
Assign the contents of the domain extension by duplicating the values of the inner boundary of image `ima`.
- template<typename I >
`void fill (const Image< I > &ima, const typename I::value &val)`

9.44.1 Detailed Description

Namespace of extension tools.

9.44.2 Function Documentation

9.44.2.1 template<typename I, typename W > void mln::extension::adjust (const Image< I > & ima, const Window< W > & win)

Adjust the domain extension of image `ima` with the size of the window `win`.

Definition at line 89 of file extension/adjust.hh.

References `mln::geom::delta()`.

Referenced by `adjust()`, `adjust_duplicate()`, and `adjust_fill()`.

9.44.2.2 template<typename I, typename W > void mln::extension::adjust (const Image< I > & ima, const Weighted_Window< W > & wwin)

Adjust the domain extension of image `ima` with the size of the weighted window `wwin`.

Definition at line 97 of file extension/adjust.hh.

References `adjust()`, and `mln::geom::delta()`.

9.44.2.3 template<typename I > void mln::extension::adjust (const Image< I > & ima, unsigned delta)

Adjust the domain extension of image `ima` with the size `delta`.

Definition at line 113 of file extension/adjust.hh.

References `adjust()`.

9.44.2.4 template<typename I , typename N > void mln::extension::adjust (const Image< I > & ima, const Neighborhood< N > & nbh)

Adjust the domain extension of image `ima` with the size of the neighborhood `nbh`.

Definition at line 105 of file extension/adjust.hh.

References `adjust()`, and `mln::geom::delta()`.

9.44.2.5 template<typename I , typename W > void mln::extension::adjust_duplicate (const Image< I > & ima, const Window< W > & win)

Adjust then duplicate.

Definition at line 70 of file adjust_duplicate.hh.

References `adjust()`, and `duplicate()`.

9.44.2.6 template<typename I , typename W > void mln::extension::adjust_fill (const Image< I > & ima, const Window< W > & win, const typename I::value & val)

Adjust then fill.

Definition at line 72 of file adjust_fill.hh.

References `adjust()`, and `fill()`.

9.44.2.7 template<typename I > void mln::extension::duplicate (const Image< I > & ima)

Assign the contents of the domain extension by duplicating the values of the inner boundary of image `ima`.

Definition at line 58 of file extension/duplicate.hh.

Referenced by `adjust_duplicate()`.

9.44.2.8 template<typename I > void mln::extension::fill (const Image< I > & ima, const typename I::value & val)

Fill the domain extension of image `ima` with the single value `v`.

Parameters

[in, out] ***ima*** The image whose domain extension is to be filled.

[in] ***val*** The value to assign.

Precondition

`ima` has to be initialized.

Definition at line 173 of file extension/fill.hh.

Referenced by `adjust_fill()`.

9.45 mln::fun Namespace Reference

Namespace of functions.

Namespaces

- namespace [access](#)

Namespace for access functions.

- namespace [i2v](#)

Namespace of integer-to-value functions.

- namespace [n2v](#)

Namespace of functions from nil to value.

- namespace [p2b](#)

Namespace of functions from point to boolean.

- namespace [p2p](#)

Namespace of functions from grid point to grid point.

- namespace [p2v](#)

Namespace of functions from point to value.

- namespace [stat](#)

Namespace of statistical functions.

- namespace [v2b](#)

Namespace of functions from value to logic value.

- namespace [v2i](#)

Namespace of value-to-integer functions.

- namespace [v2v](#)

Namespace of functions from value to value.

- namespace [v2w2v](#)

Namespace of bijective functions.

- namespace [v2w_w2v](#)

Namespace of functions from value to value.

- namespace [vv2b](#)

Namespace of functions from value to value.

- namespace [vv2v](#)

Namespace of functions from a couple of values to a value.

- namespace [x2p](#)

Namespace of functions from point to value.

- namespace [x2v](#)

Namespace of functions from vector to value.

- namespace [x2x](#)

Namespace of functions from vector to vector.

Classes

- struct [from_accu](#)

Wrap an accumulator into a function.

9.45.1 Detailed Description

Namespace of functions. Forward declarations.

`fun::i2v::array`

Forward declaration.

9.46 mln::fun::access Namespace Reference

Namespace for access functions.

9.46.1 Detailed Description

Namespace for access functions.

9.47 mln::fun::i2v Namespace Reference

Namespace of integer-to-value functions.

Functions

- template<typename T >
 `std::ostream & operator<< (std::ostream &ostr, const array< T > &a)`
 Operator<<.

9.47.1 Detailed Description

Namespace of integer-to-value functions.

9.47.2 Function Documentation

9.47.2.1 template<typename T> std::ostream & mln::fun::i2v::operator<< (std::ostream & ostr, const array< T > & a)

Operator<<.

Definition at line 353 of file fun/i2v/array.hh.

9.48 mln::fun::n2v Namespace Reference

Namespace of functions from nil to value.

Classes

- struct [white_gaussian](#)
Generate a White Gaussian Noise.

9.48.1 Detailed Description

Namespace of functions from nil to value.

9.49 mln::fun::p2b Namespace Reference

Namespace of functions from point to boolean.

Classes

- struct [antilogy](#)
A p2b function always returning false.
- struct [tautology](#)
A p2b function always returning true.

9.49.1 Detailed Description

Namespace of functions from point to boolean.

9.50 mln::fun::p2p Namespace Reference

Namespace of functions from grid point to grid point.

9.50.1 Detailed Description

Namespace of functions from grid point to grid point.

9.51 mln::fun::p2v Namespace Reference

Namespace of functions from point to value.

9.51.1 Detailed Description

Namespace of functions from point to value.

9.52 mln::fun::stat Namespace Reference

Namespace of statistical functions.

9.52.1 Detailed Description

Namespace of statistical functions.

9.53 mln::fun::v2b Namespace Reference

Namespace of functions from value to logic value.

Classes

- struct [Inot](#)

Functor computing logical-not on a value.

- struct [threshold](#)

Threshold function.

9.53.1 Detailed Description

Namespace of functions from value to logic value.

9.54 mln::fun::v2i Namespace Reference

Namespace of value-to-integer functions.

9.54.1 Detailed Description

Namespace of value-to-integer functions.

9.55 mln::fun::v2v Namespace Reference

Namespace of functions from value to value.

Classes

- class [ch_function_value](#)
Wrap a function v2v and convert its result to another type.
- struct [component](#)
Functor that accesses the i-th component of a value.
- struct [l1_norm](#)
L1-norm.
- struct [l2_norm](#)
L2-norm.
- struct [linear](#)
*Linear function. f(v) = a * v + b. V is the type of input values; T is the type used to compute the result; R is the result type.*
- struct [linfty_norm](#)
L-infty norm.
- struct [rgb8_to_rgn](#)
Convert a rgb8 value to a rgn, n < 8.

Variables

- [f_hsi_to_rgb_3x8_t f_hsi_to_rgb_3x8](#)
Global variable.
- [f_hsl_to_rgb_3x8_t f_hsl_to_rgb_3x8](#)
Global variables.
- [f_rgb_to_hsi_f_t f_rgb_to_hsi_f](#)
Global variables.
- [f_rgb_to_hsl_f_t f_rgb_to_hsl_f](#)
Global variables.

9.55.1 Detailed Description

Namespace of functions from value to value.

9.55.2 Variable Documentation

9.55.2.1 f_hsi_to_rgb_3x8_t mln::fun::v2v::f_hsi_to_rgb_3x8

Global variable.

Definition at line 74 of file hsi_to_rgb.hh.

9.55.2.2 f_hsl_to_rgb_3x8_t mln::fun::v2v::f_hsl_to_rgb_3x8

Global variables.

Definition at line 92 of file hsl_to_rgb.hh.

9.55.2.3 f_rgb_to_hsi_f_t mln::fun::v2v::f_rgb_to_hsi_f

Global variables.

Definition at line 66 of file rgb_to_hsi.hh.

9.55.2.4 f_rgb_to_hsl_f_t mln::fun::v2v::f_rgb_to_hsl_f

Global variables.

Definition at line 75 of file rgb_to_hsl.hh.

9.56 mln::fun::v2w2v Namespace Reference

Namespace of bijective functions.

Classes

- struct [cos](#)

Cosinus bijective functor.

9.56.1 Detailed Description

Namespace of bijective functions.

9.57 mln::fun::v2w_w2v Namespace Reference

Namespace of functions from value to value.

Classes

- struct [l1_norm](#)
L1-norm.
- struct [l2_norm](#)
L2-norm.
- struct [linfty_norm](#)
L-infty norm.

9.57.1 Detailed Description

Namespace of functions from value to value.

9.58 mln::fun::vv2b Namespace Reference

Namespace of functions from value to value.

Classes

- struct [eq](#)
Functor computing equal between two values.
- struct [ge](#)
Functor computing "greater or equal than" between two values.
- struct [gt](#)
Functor computing "greater than" between two values.
- struct [implies](#)
Functor computing logical-implies between two values.
- struct [le](#)
Functor computing "lower or equal than" between two values.
- struct [lt](#)
Functor computing "lower than" between two values.

9.58.1 Detailed Description

Namespace of functions from value to value.

9.59 mln::fun::vv2v Namespace Reference

Namespace of functions from a couple of values to a value.

Classes

- struct [diff_abs](#)
A functor computing the diff_absimum of two values.
- struct [land](#)
Functor computing logical-and between two values.
- struct [land_not](#)
Functor computing logical and-not between two values.
- struct [lor](#)
Functor computing logical-or between two values.
- struct [lxor](#)
Functor computing logical-xor between two values.
- struct [max](#)
A functor computing the maximum of two values.
- struct [min](#)
A functor computing the minimum of two values.
- struct [vec](#)
A functor computing the vecimum of two values.

9.59.1 Detailed Description

Namespace of functions from a couple of values to a value.

9.60 mln::fun::x2p Namespace Reference

Namespace of functions from point to value.

Classes

- struct [closest_point](#)
FIXME: doxygen + concept checking.

9.60.1 Detailed Description

Namespace of functions from point to value.

9.61 mln::fun::x2v Namespace Reference

Namespace of functions from vector to value.

Classes

- struct [bilinear](#)
Represent a bilinear interpolation of values from an underlying image.
- struct [trilinear](#)
Represent a trilinear interpolation of values from an underlying image.

9.61.1 Detailed Description

Namespace of functions from vector to value.

9.62 mln::fun::x2x Namespace Reference

Namespace of functions from vector to vector.

Classes

- struct [composed](#)
Represent a composition of two transformations.
- struct [linear](#)
Represent a linear interpolation of values from an underlying image.
- struct [rotation](#)
Represent a rotation function.
- struct [translation](#)
Translation function-object.

9.62.1 Detailed Description

Namespace of functions from vector to vector.

9.63 mln::geom Namespace Reference

Namespace of all things related to geometry.

Namespaces

- namespace **impl**

Implementation namespace of geom namespace.

Classes

- class **complex_geometry**

A functor returning the sites of the faces of a complex where the locations of each 0-face is stored.

Functions

- template<typename S >
box< typename S::site > **bbox** (const **Site_Set**< S > &pset)
Compute the precise bounding box of a point set pset.
- template<typename I >
box< typename I::site > **bbox** (const **Image**< I > &ima)
Compute the precise bounding box of a point set pset.
- template<typename W >
box< typename W::psite > **bbox** (const **Window**< W > &win)
Compute the precise bounding box of a window win.
- template<typename W >
box< typename W::psite > **bbox** (const **Weighted_Window**< W > &win)
Compute the precise bounding box of a weighted window win.
- template<typename I , typename W >
mln::trait::ch_value< I, unsigned >::ret **chamfer** (const **Image**< I > &input_, const W &w_win_,
unsigned max=mln_max(unsigned))
Apply chamfer algorithm to a binary image.
- template<typename W >
unsigned **delta** (const **Window**< W > &win)
Compute the delta of a window win.
- template<typename W >
unsigned **delta** (const **Weighted_Window**< W > &wwin)
Compute the delta of a weighted window wwin.
- template<typename N >
unsigned **delta** (const **Neighborhood**< N > &nbb)
Compute the delta of a neighborhood nbb.
- template<typename I >
mln::trait::concrete< I >::ret **horizontal_symmetry** (const **Image**< I > &input)
Perfoms a horizontal symmetry.

- template<typename I >
I::site::coord **max_col** (const [Image](#)< I > &ima)
Give the maximum column of an image.
- template<typename B >
B::site::coord **max_col** (const [Box](#)< B > &b)
Give the maximum col of an box 2d or 3d.
- template<typename I >
I::site::coord **max_ind** (const [Image](#)< I > &ima)
Give the maximum ind of an image.
- template<typename I >
I::site::coord **max_row** (const [Image](#)< I > &ima)
Give the maximum row of an image.
- template<typename B >
B::site::coord **max_row** (const [Box](#)< B > &b)
Give the maximum row of an box 2d or 3d.
- template<typename I >
I::site::coord **max_sli** (const [Image](#)< I > &ima)
Give the maximum sli of an image.
- std::pair< [complex_image](#)< 2, [mln::space_2complex_geometry](#), [algebra::vec](#)< 3, float > >,
[complex_image](#)< 2, [mln::space_2complex_geometry](#), float > > [mesh_corner_point_area](#) (const [p_complex](#)< 2, [space_2complex_geometry](#) > &mesh)
Compute the area “belonging” to normals at vertices.
- std::pair< [complex_image](#)< 2, [mln::space_2complex_geometry](#), float >, [complex_image](#)< 2, [mln::space_2complex_geometry](#), float > > [mesh_curvature](#) (const [p_complex](#)< 2, [space_2complex_geometry](#) > &mesh)
Compute the principal curvatures of a surface at vertices.
- [complex_image](#)< 2, [mln::space_2complex_geometry](#), [algebra::vec](#)< 3, float > > [mesh_normal](#) (const [p_complex](#)< 2, [space_2complex_geometry](#) > &mesh)
Compute normals at vertices.
- template<typename I >
I::site::coord **min_col** (const [Image](#)< I > &ima)
Give the minimum column of an image.
- template<typename B >
B::site::coord **min_col** (const [Box](#)< B > &b)
Give the minimum column of an box 2d or 3d.
- template<typename I >
I::site::coord **min_ind** (const [Image](#)< I > &ima)
Give the minimum ind of an image.

- template<typename I >
I::site::coord **min_row** (const **Image**< I > &ima)
Give the minimum row of an image.
- template<typename B >
B::site::coord **min_row** (const **Box**< B > &b)
Give the minimum row of an box 2d or 3d.
- template<typename I >
I::site::coord **min_sli** (const **Image**< I > &ima)
Give the minimum sli of an image.
- template<typename I >
unsigned **ncols** (const **Image**< I > &ima)
Give the number of columns of an image.
- template<typename B >
unsigned **ncols** (const **Box**< B > &b)
Give the number of cols of a box 2d or 3d.
- template<typename I >
unsigned **ninds** (const **Image**< I > &ima)
Give the number of inds of an image.
- template<typename I >
unsigned **nrows** (const **Image**< I > &ima)
Give the number of rows of an image.
- template<typename B >
unsigned **nrows** (const **Box**< B > &b)
Give the number of rows of a box 2d or 3d.
- template<typename I >
unsigned **nsites** (const **Image**< I > &input)
Compute the number of sites of the image `input`.
- template<typename I >
unsigned **nslis** (const **Image**< I > &ima)
Give the number of slices of an image.
- template<typename S >
void **pmin_pmax** (const **Site_Set**< S > &s, typename S::site &pmin, typename S::site &pmax)
Compute the minimum and maximum points, `pmin` and `max`, of point set `s`.
- template<typename S >
std::pair< typename S::site, typename S::site > **pmin_pmax** (const **Site_Set**< S > &s)
Compute the minimum and maximum points of point set `s`.
- template<typename I >
std::pair< typename I::site, typename I::site > **pmin_pmax** (const **Site_Iterator**< I > &p)
Compute the minimum and maximum points when browsing with iterator `p`.

- template<typename I >
`void pmin_pmax (const Site_Iterator< I > &p, typename I::site &pmin, typename I::site &pmax)`
Compute the minimum and maximum points, `pmin` and `max`, when browsing with iterator `p`.
- template<typename I , typename Ext >
`mln::trait::concrete< I >::ret rotate (const Image< I > &input, double angle, const Ext &extension)`
- template<typename B >
`B rotate (const Box< B > &box, double angle)`
This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. The rotation center `ref` is set to `box.pcenter()`.
- template<typename I , typename Ext , typename S >
`mln::trait::concrete< I >::ret rotate (const Image< I > &input, double angle, const Ext &extension, const Site_Set< S > &output_domain)`
Perform a rotation from the center of an image.
- template<typename I >
`mln::trait::concrete< I >::ret rotate (const Image< I > &input, double angle)`
This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Use `literal::zero` as default value for the extension.
- template<typename B >
`B rotate (const Box< B > &box_, double angle, const typename B::site &ref)`
Rotate a box.
- template<typename I , typename N >
`mln::trait::concrete< I >::ret seeds2tiling (const Image< I > &ima_, const Neighborhood< N > &nbh)`
Take a labeled image `ima_` with seeds and extend them until creating tiles.
- template<typename I , typename V , typename Ext , typename S >
`mln::trait::concrete< I >::ret translate (const Image< I > &input, const algebra::vec< I::site::dim, V > &ref, const Ext &extension, const Site_Set< S > &output_domain)`
Perform a translation from the center of an image.
- template<typename I , typename V >
`mln::trait::concrete< I >::ret translate (const Image< I > &input, const algebra::vec< I::site::dim, V > &ref)`
This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Use `literal::zero` as default value for the extension.
- template<typename I , typename V , typename Ext >
`mln::trait::concrete< I >::ret translate (const Image< I > &input, const algebra::vec< I::site::dim, V > &ref, const Ext &extension)`
- template<typename I >
`mln::trait::concrete< I >::ret vertical_symmetry (const Image< I > &input)`
Perfoms a vertical symmetry.
- template<typename I , typename N >
`I seeds2tiling_roundness (Image< I > &ima_, const w_window2d_int &w_win, unsigned max, const Neighborhood< N > &nbh_)`

Take a labeled image `ima_` with seeds and extend them until creating tiles rounder than the primary version.

9.63.1 Detailed Description

Namespace of all things related to geometry. Namespace of essential things related to geometry.

9.63.2 Function Documentation

9.63.2.1 template<typename S> box< typename S::site > mln::geom::bbox (const Site_Set< S > & pset) [inline]

Compute the precise bounding box of a point set `pset`.

Definition at line 122 of file geom/bbox.hh.

Referenced by `bbox()`, `mln::transform::distance_and_closest_point_geodesic()`, `mln::registration::icp()`, `max_col()`, `max_row()`, `max_sli()`, `min_col()`, `min_row()`, `min_sli()`, `mln::debug::println()`, `mln::debug::println_with_border()`, and `rotate()`.

9.63.2.2 template<typename I> box< typename I::site > mln::geom::bbox (const Image< I > & ima)

Compute the precise bounding box of a point set `pset`.

Definition at line 133 of file geom/bbox.hh.

References `bbox()`.

9.63.2.3 template<typename W> box< typename W::psite > mln::geom::bbox (const Window< W > & win)

Compute the precise bounding box of a window `win`.

Definition at line 143 of file geom/bbox.hh.

References `mln::literal::origin`.

9.63.2.4 template<typename W> box< typename W::psite > mln::geom::bbox (const Weighted_Window< W > & win)

Compute the precise bounding box of a weighted window `win`.

Definition at line 156 of file geom/bbox.hh.

References `bbox()`.

9.63.2.5 template<typename I, typename W> mln::trait::ch_value< I, unsigned >::ret mln::geom::chamfer (const Image< I > & input_, const W & w_win_, unsigned max = mln_max(unsigned))

Apply chamfer algorithm to a binary image.

Definition at line 113 of file geom/chamfer.hh.

9.63.2.6 template<typename W> unsigned mln::geom::delta (const Window< W > & win)

Compute the delta of a window *win*.

Definition at line 96 of file delta.hh.

Referenced by mln::extension::adjust(), and delta().

9.63.2.7 template<typename W> unsigned mln::geom::delta (const Weighted_Window< W > & wwin)

Compute the delta of a weighted window *wwin*.

Definition at line 105 of file delta.hh.

References delta().

9.63.2.8 template<typename N> unsigned mln::geom::delta (const Neighborhood< N > & nbh)

Compute the delta of a neighborhood *nbh*.

Definition at line 112 of file delta.hh.

References delta().

9.63.2.9 template<typename I> mln::trait::concrete< I >::ret mln::geom::horizontal_symmetry (const Image< I > & input)

Perfoms a horizontal symmetry.

Definition at line 172 of file horizontal_symmetry.hh.

9.63.2.10 template<typename I> I::site::coord mln::geom::max_col (const Image< I > & ima) [inline]

Give the maximum column of an image.

Definition at line 56 of file max_col.hh.

References bbox().

Referenced by mln::io::magick::load(), and ncols().

9.63.2.11 template<typename B> B::site::coord mln::geom::max_col (const Box< B > & b) [inline]

Give the maximum col of an box 2d or 3d.

Definition at line 67 of file max_col.hh.

9.63.2.12 template<typename I> I::site::coord mln::geom::max_ind (const Image< I > & ima) [inline]

Give the maximum ind of an image.

Definition at line 51 of file max_ind.hh.

Referenced by ninds().

9.63.2.13 template<typename I> I::site::coord mln::geom::max_row (const Image< I > & ima) [inline]

Give the maximum row of an image.

Definition at line 57 of file max_row.hh.

References bbox().

Referenced by mln::io::magick::load(), and nrows().

9.63.2.14 template<typename B> B::site::coord mln::geom::max_row (const Box< B > & b) [inline]

Give the maximum row of an box 2d or 3d.

Definition at line 68 of file max_row.hh.

9.63.2.15 template<typename I> I::site::coord mln::geom::max_sli (const Image< I > & ima) [inline]

Give the maximum sli of an image.

Definition at line 53 of file max_sli.hh.

References bbox().

Referenced by nslis().

9.63.2.16 std::pair< complex_image< 2, mln::space_2complex_geometry, algebra::vec<3, float> >, complex_image< 2, mln::space_2complex_geometry, float > > mln::geom::mesh_corner_point_area (const p_complex< 2, space_2complex_geometry > & mesh) [inline]

Compute the area “belonging” to normals at vertices.

Inspired from the method Trimesh::need_pointareas of the Trimesh library.

See also

<http://www.cs.princeton.edu/gfx/proj/trimesh2/>

From the documentation of Trimesh:

“Compute the area “belonging” to each vertex or each corner of a triangle (defined as Voronoi area restricted to the 1-ring of a vertex, or to the triangle).”

Definition at line 249 of file misc.hh.

References mln::data::fill(), mln::norm::sqr_l2(), mln::algebra::vprod(), and mln::literal::zero.

Referenced by mesh_curvature().

```
9.63.2.17 std::pair< complex_image< 2, mln::space_2complex_geometry, float >, complex_image< 2, mln::space_2complex_geometry, float > >
mln::geom::mesh_curvature ( const p_complex< 2, space_2complex_geometry > &
mesh ) [inline]
```

Compute the principal curvatures of a surface at vertices.

These principal curvatures are names kappa_1 and kappa_2 in

Sylvie Philipp-Foliguet, Michel Jordan Laurent Najman and Jean Cousty. Artwork 3D Model Database Indexing and Classification.

Parameters

[in] **mesh** The surface (triangle mesh) on which the curvature is to be computed.

Definition at line 486 of file misc.hh.

References mln::algebra::ldlt_decomp(), mln::algebra::ldlt_solve(), mesh_corner_point_area(), mesh_normal(), mln::algebra::vprod(), and mln::literal::zero.

```
9.63.2.18 complex_image< 2, mln::space_2complex_geometry, algebra::vec<3, float> >
mln::geom::mesh_normal ( const p_complex< 2, space_2complex_geometry > & mesh
) [inline]
```

Compute normals at vertices.

Inspired from the method Trimesh::need_normals of the Trimesh library.

See also

<http://www.cs.princeton.edu/gfx/proj/trimesh2/>

For simplicity purpose, and contrary to Trimesh, this routine only compute normals from a mesh, not from a cloud of points.

Definition at line 161 of file misc.hh.

References mln::data::fill(), mln::norm::sqr_l2(), mln::algebra::vprod(), and mln::literal::zero.

Referenced by mesh_curvature().

```
9.63.2.19 template<typename I > I::site::coord mln::geom::min_col ( const Image< I > & ima )
[inline]
```

Give the minimum column of an image.

Definition at line 57 of file min_col.hh.

References bbox().

Referenced by mln::transform::hough(), mln::io::magick::load(), and ncols().

9.63.2.20 template<typename B> B::site::coord mln::geom::min_col (const Box< B > & b) [inline]

Give the minimum column of an box 2d or 3d.

Definition at line 68 of file min_col.hh.

9.63.2.21 template<typename I> I::site::coord mln::geom::min_ind (const Image< I > & ima) [inline]

Give the minimum ind of an image.

Definition at line 51 of file min_ind.hh.

Referenced by ninds().

9.63.2.22 template<typename I> I::site::coord mln::geom::min_row (const Image< I > & ima) [inline]

Give the minimum row of an image.

Definition at line 60 of file min_row.hh.

References bbox().

Referenced by mln::transform::hough(), mln::io::magick::load(), and nrows().

9.63.2.23 template<typename B> B::site::coord mln::geom::min_row (const Box< B > & b) [inline]

Give the minimum row of an box 2d or 3d.

Definition at line 71 of file min_row.hh.

9.63.2.24 template<typename I> I::site::coord mln::geom::min_sli (const Image< I > & ima) [inline]

Give the minimum sli of an image.

Definition at line 53 of file min_sli.hh.

References bbox().

Referenced by nslis().

9.63.2.25 template<typename I> unsigned mln::geom::ncols (const Image< I > & ima) [inline]

Give the number of columns of an image.

Definition at line 57 of file ncols.hh.

References max_col(), and min_col().

Referenced by mln::labeling::impl::compute_fastest(), mln::subsampling::gaussian_subsampling(), mln::transform::hough(), ncols(), mln::io::magick::save(), and mln::subsampling::subsampling().

9.63.2.26 template<typename B > unsigned mln::geom::ncols (const Box< B > & b)

Give the number of cols of a box 2d or 3d.

Definition at line 67 of file ncols.hh.

References max_col(), min_col(), and ncols().

**9.63.2.27 template<typename I > unsigned mln::geom::ninds (const Image< I > & ima)
[inline]**

Give the number of inds of an image.

Definition at line 52 of file ninds.hh.

References max_ind(), and min_ind().

**9.63.2.28 template<typename I > unsigned mln::geom::nrows (const Image< I > & ima)
[inline]**

Give the number of rows of an image.

Definition at line 57 of file nrows.hh.

References max_row(), and min_row().

Referenced by mln::subsampling::gaussian_subsampling(), mln::transform::hough(), nrows(), mln::io::magick::save(), and mln::subsampling::subsampling().

9.63.2.29 template<typename B > unsigned mln::geom::nrows (const Box< B > & b)

Give the number of rows of a box 2d or 3d.

Definition at line 66 of file nrows.hh.

References max_row(), min_row(), and nrows().

**9.63.2.30 template<typename I > unsigned mln::geom::nsites (const Image< I > & input)
[inline]**

Compute the number of sites of the image *input*.

Definition at line 52 of file nsites.hh.

Referenced by pmin_pmax().

**9.63.2.31 template<typename I > unsigned mln::geom::nslis (const Image< I > & ima)
[inline]**

Give the number of slices of an image.

Definition at line 53 of file nslis.hh.

References max_sli(), and min_sli().

9.63.2.32 template<typename S> std::pair< typename S::site, typename S::site > mln::geom::pmin_pmax(const Site_Set< S > & s) [inline]

Compute the minimum and maximum points of point set *s*.

Definition at line 157 of file pmin_pmax.hh.

References nsites().

Referenced by pmin_pmax().

9.63.2.33 template<typename S> void mln::geom::pmin_pmax(const Site_Set< S > & s, typename S::site & pmin, typename S::site & pmax) [inline]

Compute the minimum and maximum points, *pmin* and *max*, of point set *s*.

Definition at line 148 of file pmin_pmax.hh.

References nsites().

9.63.2.34 template<typename I> std::pair< typename I::site, typename I::site > mln::geom::pmin_pmax(const Site_Iterator< I > & p) [inline]

Compute the minimum and maximum points when browsing with iterator *p*.

Definition at line 106 of file pmin_pmax.hh.

References pmin_pmax().

9.63.2.35 template<typename I> void mln::geom::pmin_pmax(const Site_Iterator< I > & p, typename I::site & pmin, typename I::site & pmax) [inline]

Compute the minimum and maximum points, *pmin* and *max*, when browsing with iterator *p*.

Definition at line 84 of file pmin_pmax.hh.

9.63.2.36 template<typename I> mln::trait::concrete< I >::ret mln::geom::rotate(const Image< I > & input, double angle)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Use [literal::zero](#) as default value for the extension.

Definition at line 197 of file rotate.hh.

References rotate(), and [mln::literal::zero](#).

9.63.2.37 template<typename I, typename Ext> mln::trait::concrete< I >::ret mln::geom::rotate(const Image< I > & input, double angle, const Ext & extension)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 185 of file rotate.hh.

References rotate().

9.63.2.38 template<typename B > B mln::geom::rotate (const Box< B > & box, double angle)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. The rotation center `ref` is set to `box.pcenter()`.

Definition at line 252 of file rotate.hh.

References `rotate()`.

9.63.2.39 template<typename I , typename Ext , typename S > mln::trait::concrete< I >::ret mln::geom::rotate (const Image< I > & input, double angle, const Ext & extension, const Site_Set< S > & output_domain)

Perform a rotation from the center of an image.

Parameters

[in] `input` An image.

[in] `angle` An angle in degrees.

[in] `extension` Function, image or value which will be used as extension. This extension allows to map values to sites which were not part of the domain before the rotation.

[in] `output_domain` The domain of the output image. An invalid domain, causes the routine to use a domain large enough to display the whole original image.

Returns

An image with the same domain as `input`.

Definition at line 123 of file rotate.hh.

References `bbox()`, `mln::compose()`, `mln::duplicate()`, `mln::initialize()`, `mln::mln_exact()`, `mln::literal::origin`, and `mln::data::paste()`.

Referenced by `rotate()`.

9.63.2.40 template<typename B > B mln::geom::rotate (const Box< B > & box_, double angle, const typename B::site & ref)

Rotate a box.

FIXME: the return type may be too generic and may lead to invalid covariance.

Definition at line 205 of file rotate.hh.

References `mln::compose()`, `mln::literal::origin`, and `mln::accu::shape::bbox< P >::to_result()`.

9.63.2.41 template<typename I , typename N > mln::trait::concrete< I >::ret mln::geom::seeds2tiling (const Image< I > & ima_, const Neighborhood< N > & nbh) [inline]

Take a labeled image `ima_` with seeds and extend them until creating tiles.

Parameters

[in, out] `ima_` The labeled image with seed.

[in] ***nbh*** The neighborhood to use on this algorithm.

Returns

A tiled image.

Precondition

ima_ has to be initialized.

Definition at line 136 of file seeds2tiling.hh.

References mln::geom::impl::seeds2tiling().

9.63.2.42 template<typename I , typename N > I mln::geom::seeds2tiling_roundness (Image<I> & *ima_*, const w_window2d_int & *w_win*, unsigned *max*, const Neighborhood<N> & *nbh_*) [inline]

Take a labeled image *ima_* with seeds and extend them until creating tiles rounder than the primary version.

Parameters

[in, out] ***ima_*** The labeled image with seed.

[in] ***w_win*** The weight window using by [geom::chamfer](#) to compute distance.

[in] ***max*** Unsigned using by [geom::chamfer](#) to compute the distance.

[in] ***nbh_*** The neighborhood to use on this algorithm.

Precondition

ima_ has to be initialized.

Definition at line 128 of file seeds2tiling_roundness.hh.

9.63.2.43 template<typename I , typename V > mln::trait::concrete< I >::ret mln::geom::translate (const Image< I > & *input*, const algebra::vec< I::site::dim, V > & *ref*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Use [literal::zero](#) as default value for the extension.

Definition at line 146 of file translate.hh.

References [translate\(\)](#), and [mln::literal::zero](#).

9.63.2.44 template<typename I , typename V , typename Ext , typename S > mln::trait::concrete< I >::ret mln::geom::translate (const Image< I > & *input*, const algebra::vec< I::site::dim, V > & *ref*, const Ext & *extension*, const Site_Set< S > & *output_domain*)

Perform a translation from the center of an image.

Parameters

[in] ***input*** An image.

[in] ***ref*** The translation vector.

[in] ***extension Function***, image or value which will be used as extension. This extension allows to map values to sites which where not part of the domain before the translation.

[in] ***output_domain*** The domain of the output image. An invalid domain, causes the routine to use the translated input_ domain.

Returns

An image with the same domain as `input`.

Definition at line 99 of file `translate.hh`.

References `mln::extend()`, `mln::data::fill()`, and `mln::mln_exact()`.

Referenced by `translate()`.

**9.63.2.45 template<typename I , typename V , typename Ext > mln::trait::concrete< I >::ret
`mln::geom::translate (const Image< I > & input, const algebra::vec< I::site::dim, V > & ref, const Ext & extension)`**

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 132 of file `translate.hh`.

References `translate()`.

9.63.2.46 template<typename I > mln::trait::concrete< I >::ret mln::geom::vertical_symmetry (const Image< I > & input)

Perfoms a vertical symmetry.

Definition at line 174 of file `vertical_symmetry.hh`.

9.64 mln::geom::impl Namespace Reference

Implementation namespace of geom namespace.

Functions

- `template<typename I , typename N >
 mln::trait::concrete< I >::ret seeds2tiling (const Image< I > &ima_, const Neighborhood< N > &nbh_)`

Generic implementation of geom::seed2tiling.

9.64.1 Detailed Description

Implementation namespace of geom namespace.

9.64.2 Function Documentation

**9.64.2.1 template<typename I , typename N > mln::trait::concrete< I >::ret
mln::geom::impl::seeds2tiling (const Image< I > & ima_ , const Neighborhood< N > & nbh_) [inline]**

Generic implementation of geom::seed2tiling.

Parameters

- [in, out] **ima_** The labeled image with seed.
- [in] **nbh_** The neighborhood to use on this algorithm.

Definition at line 77 of file seeds2tiling.hh.

References mln::duplicate(), mln::p_queue< P >::front(), mln::p_queue< P >::pop(), and mln::p_queue< P >::push().

Referenced by mln::geom::seeds2tiling().

9.65 mln::graph Namespace Reference

Namespace of graph related routines.

Functions

- template<typename G , typename F >
F::result **compute** (const **Graph**< G > &g_ , F &functor)
Base routine to compute attributes on a graph.
- template<typename I , typename N , typename L >
mln::trait::ch_value< I, L >::ret **labeling** (const **Image**< I > &graph_image_ , const **Neighborhood**< N > &nbh_ , L &nlabels)
Label graph components.
- template<typename I , typename M >
graph_elt_neighborhood_if< mln_graph(I), typename I::domain_t, M > **to_neighb** (const **Image**< I > &graph_image_ , const **Image**< M > &graph_mask_image_)
Make a custom graph neighborhood from a mask image.
- template<typename I , typename M >
graph_elt_window_if< mln_graph(I), typename I::domain_t, M > **to_win** (const **Image**< I > &graph_image_ , const **Image**< M > &graph_mask_image_)
Make a custom graph window from a mask image.

9.65.1 Detailed Description

Namespace of graph related routines.

9.65.2 Function Documentation

9.65.2.1 template<typename G , typename F > F::result mln::graph::compute (const Graph< G > & g , F & functor)

Base routine to compute attributes on a graph.

Parameters

- [in] *g*_ A graph.
- [in] *functor* A functor implementing the right interface.

Returns

The computed data.

See also

[canvas::browsing::depth_first_search](#)

Definition at line 63 of file graph/compute.hh.

9.65.2.2 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret mln::graph::labeling (const Image< I > & graph_image_ , const Neighborhood< N > & nbh_ , L & nlabels)

Label graph components.

[Vertex](#) with id 0, usually used to represent the background component, will be labeled with an id different from 0. Therefore, the labeling starts from 1.

Parameters

- [in] *graph_image*_ A graph image (

See also

[vertex_image](#), [edge_image](#)).

Parameters

- [in] *nbh*_ A graph neighborhood.
- [in, out] *nlabels* The number of labels found.

Returns

a [Graph](#) image of labels.

Definition at line 72 of file labeling.hh.

References [mln::labeling::blobs\(\)](#), [mln::data::fill\(\)](#), and [mln::initialize\(\)](#).

9.65.2.3 template<typename I , typename M > graph_elt_neighborhood_if< mln_graph(I), typename I::domain_t, M > mln::graph::to_neighb (const Image< I > & graph_image_ , const Image< M > & graph_mask_image_)

Make a custom graph neighborhood from a mask image.

Parameters

[in] *graph_image_* A graph image (

See also

[vertex_image](#) and [edge_image](#)).

Parameters

[in] *graph_mask_image_* A graph image of bool used as a mask.

Returns

A masked neighborhood on graph.

Definition at line 57 of file `to_neighb.hh`.

9.65.2.4 template<typename I , typename M > graph_elt_window_if< mln_graph(I), typename I::domain_t, M > mln::graph::to_win (const Image< I > & *graph_image_*, const Image< M > & *graph_mask_image_*)

Make a custom graph window from a mask image.

Parameters

[in] *graph_image_* A graph image (

See also

[vertex_image](#) and [edge_image](#)).

Parameters

[in] *graph_mask_image_* A graph image of bool used as a mask.

Returns

A masked window on graph.

Definition at line 57 of file `to_win.hh`.

9.66 mln::grid Namespace Reference

Namespace of grids definitions.

9.66.1 Detailed Description

Namespace of grids definitions. Compute the `image::space` trait from a point type.

9.67 mln::histo Namespace Reference

Namespace of histograms.

Namespaces

- namespace **impl**
Implementation namespace of histo namespace.

Classes

- struct **array**
Generic histogram class over a value set with type T.

Functions

- template<typename I >
histo::array< typename I::value > compute (const **Image< I >** &**input**)
Compute the histogram of image input.
- template<typename I >
mln::trait::concrete< I >::ret equalize (const **Image< I >** &**input**)
Equalizes the histogram of image input.

9.67.1 Detailed Description

Namespace of histograms.

9.67.2 Function Documentation

9.67.2.1 template<typename I > histo::array< typename I::value > mln::histo::compute (const **Image< I >** & **input**) [inline]

Compute the histogram of image **input**.

Definition at line 79 of file histo/compute.hh.

Referenced by **equalize()**.

9.67.2.2 template<typename I > mln::trait::concrete< I >::ret mln::histo::equalize (const **Image< I >** & **input**)

Equalizes the histogram of image **input**.

Author

J. Fabrizio, R. Levillain

Definition at line 55 of file histo/equalize.hh.

References **compute()**, and **mln::initialize()**.

9.68 mln::histo::impl Namespace Reference

Implementation namespace of histo namespace.

Namespaces

- namespace [generic](#)
Generic implementation namespace of histo namespace.

9.68.1 Detailed Description

Implementation namespace of histo namespace.

9.69 mln::histo::impl::generic Namespace Reference

Generic implementation namespace of histo namespace.

9.69.1 Detailed Description

Generic implementation namespace of histo namespace.

9.70 mln::impl Namespace Reference

Implementation namespace of mln namespace.

9.70.1 Detailed Description

Implementation namespace of mln namespace.

9.71 mln::io Namespace Reference

Namespace of input/output handling.

Namespaces

- namespace [cloud](#)
Namespace of cloud input/output handling.
- namespace [dicom](#)
Namespace of DICOM input/output handling.
- namespace [dump](#)

Namespace of dump input/output handling.

- namespace **fits**

Namespace of fits input/output handling.

- namespace **fld**

Namespace of pgm input/output handling.

- namespace **magick**

Namespace of magick input/output handling.

- namespace **off**

Namespace of off input/output handling.

- namespace **pbm**

Namespace of pbm input/output handling.

- namespace **pbms**

Namespace of pbms input/output handling.

- namespace **pfm**

Namespace of pfm input/output handling.

- namespace **pgm**

Namespace of pgm input/output handling.

- namespace **pgms**

Namespace of pgms input/output handling.

- namespace **plot**

Namespace of plot input/output handling.

- namespace **pnm**

Namespace of pnm input/output handling.

- namespace **pnms**

Namespace of pnms input/output handling.

- namespace **ppm**

Namespace of ppm input/output handling.

- namespace **ppms**

Namespace of ppms input/output handling.

- namespace **raw**

Namespace of raw input/output handling.

- namespace **tiff**

Namespace of tiff input/output handling.

- namespace [txt](#)

Namespace of txt input/output handling.

9.71.1 Detailed Description

Namespace of input/output handling.

9.72 mln::io::cloud Namespace Reference

Namespace of cloud input/output handling.

Functions

- template<typename P >

void [load](#) ([p_array](#)< P > &arr, const std::string &filename)

Load a cloud of points.

- template<typename P >

void [save](#) (const [p_array](#)< P > &arr, const std::string &filename)

Load a cloud of points.

9.72.1 Detailed Description

Namespace of cloud input/output handling.

9.72.2 Function Documentation

9.72.2.1 template<typename P > void mln::io::cloud::load ([p_array](#)< P > & arr, const std::string & filename)

Load a cloud of points.

Parameters

[in, out] **arr** the site set where to load the data.

[in] **filename** file to load.

Definition at line 88 of file cloud/load.hh.

9.72.2.2 template<typename P > void mln::io::cloud::save (const [p_array](#)< P > & arr, const std::string & filename)

Load a cloud of points.

Parameters

- [in] ***arr*** the cloud of points to save.
- [in] ***filename*** the destination.

Definition at line 83 of file cloud/save.hh.

9.73 mln::io::dicom Namespace Reference

Namespace of DICOM input/output handling.

Classes

- struct **dicom_header**
Store dicom file header.

Functions

- **dicom_header get_header (const std::string &filename)**
Retrieve header in a dicom file.
- template<typename I >
void load (Image< I > &ima, const std::string &filename)

9.73.1 Detailed Description

Namespace of DICOM input/output handling.

9.73.2 Function Documentation

9.73.2.1 **dicom_header mln::io::dicom::get_header (const std::string & filename)**

Retrieve header in a dicom file.

Definition at line 76 of file dicom/get_header.hh.

References mln::util::array< T >::append().

9.73.2.2 **template<typename I > void mln::io::dicom::load (Image< I > & ima, const std::string & filename) [inline]**

Load a DICOM file in a Milena image.

Parameters

- [out] ***ima*** A reference to the image which will receive data.
- [in] ***filename*** The source.

Common compilation flags to link to gdcm if this file is used:

-lgdcmCommon -lgdcmDICT -lgdcmDSED -lgdcmIOD -lgdcmMSFF -lgdcmexpat -lgdcmjpeg12 -lgdcmjpeg16 -lgdcmjpeg8 -lgdcmopenjpeg -lgdcmuuid -lgdcmzlib

Definition at line 96 of file dicom/load.hh.

References mln::initialize().

9.74 mln::io::dump Namespace Reference

Namespace of dump input/output handling.

Classes

- struct [dump_header](#)

Store dump file header.

Functions

- [dump_header get_header](#) (const std::string &filename)

Retrieve header in a dump file.

- template<typename I >

void [load](#) ([Image](#)< I > &ima_, const std::string &filename)

Load a Milena image by dumped into a file.

- template<typename I >

void [save](#) (const [Image](#)< I > &ima_, const std::string &filename)

Save a Milena image by dumping its data to a file.

9.74.1 Detailed Description

Namespace of dump input/output handling.

9.74.2 Function Documentation

9.74.2.1 [dump_header mln::io::dump::get_header \(const std::string & filename \)](#)

Retrieve header in a dump file.

Definition at line 68 of file dump/get_header.hh.

References mln::util::array< T >::resize().

9.74.2.2 template<typename I> void mln::io::dump::load (Image< I > & ima_, const std::string & filename)

Load a Milena image by dumped into a file.

Parameters

- [in, out] *ima_* The image to load.
- [in] *filename* the destination.

Definition at line 171 of file dump/load.hh.

9.74.2.3 template<typename I> void mln::io::dump::save (const Image< I > & ima_, const std::string & filename)

Save a Milena image by dumping its data to a file.

Parameters

- [in] *ima_* The image to save.
- [in] *filename* the destination.

Definition at line 131 of file dump/save.hh.

9.75 mln::io::fits Namespace Reference

Namespace of fits input/output handling.

Functions

- void `load (image2d< float > &ima, const std::string &filename)`
Load a fits image in a Milena image.
- `image2d< float > load (const std::string &filename)`
Load a fits image in a image2d<float>.

9.75.1 Detailed Description

Namespace of fits input/output handling.

9.75.2 Function Documentation

9.75.2.1 void mln::io::fits::load (image2d< float > & ima, const std::string & filename) [inline]

Load a fits image in a Milena image.

Parameters

- [out] *ima* A reference to the image2d<float> which will receive data.
- [in] *filename* The source.

Definition at line 132 of file fits/load.hh.

9.75.2.2 image2d< float > mln::io::fits::load (const std::string & *filename*) [inline]

Load a fits image in a image2d<float>.

Parameters

- [in] *filename* The image source.

Returns

An image2d<float> which contains loaded data.

Definition at line 85 of file fits/load.hh.

9.76 mln::io::fld Namespace Reference

Namespace of pgm input/output handling.

Classes

- struct **fld_header**
Define the header structure of an AVS field data file.

Functions

- template<typename I >
void load (**Image**< I > &ima_, const char *filename)
Load an image from an AVS field file.
- **fld_header read_header** (std::istream &ins)
Read the header form an AVS field file.
- **void write_header** (std::ostream &file, const **fld_header** &h)
Write the AVS header in a file.

9.76.1 Detailed Description

Namespace of pgm input/output handling.

9.76.2 Function Documentation

9.76.2.1 template<typename I> void mln::io::fld::load (Image< I > & *ima_*, const char * *filename*) [inline]

Load an image from an AVS field file.

Parameters

- [in, out] *ima_* The image to load.
- [in] *filename* The path to the AVS file.

Definition at line 198 of file fld/load.hh.

References mln::box< P >::pmax(), mln::box< P >::pmin(), and read_header().

9.76.2.2 fld_header mln::io::fld::read_header (std::istream & *ins*) [inline]

Read the header form an AVS field file.

Parameters

- ins* The file to read.

Returns

The header.

Definition at line 73 of file fld/load_header.hh.

Referenced by load().

9.76.2.3 void mln::io::fld::write_header (std::ostream & *file*, const fld_header & *h*) [inline]

Write the AVS header in a file.

Parameters

- file* The file to write.
- h* The AVS header.

Definition at line 58 of file write_header.hh.

9.77 mln::io::magick Namespace Reference

Namespace of magick input/output handling.

Functions

- template<typename I>
void [load](#) (Image< I > &ima, const std::string &filename)

Load data from a file into a Milena image using Magick++.

- template<typename I , typename J >
void **save** (const **Image**< I > &ima, const **Image**< J > &opacity_mask, const std::string &filename)

Save a Milena image into a file using Magick++.

- template<typename I >
void **save** (const **Image**< I > &ima, const std::string &filename)

Save a Milena image into a file using Magick++.

9.77.1 Detailed Description

Namespace of magick input/output handling.

9.77.2 Function Documentation

9.77.2.1 template<typename I > void mln::io::magick::load (**Image**< I > & *ima*, const std::string & *filename*) [inline]

Load data from a file into a Milena image using Magick++.

Parameters

[out] *ima* The image data are loaded into.

[in] *filename* The name of the input file.

Definition at line 139 of file magick/load.hh.

References mln::initialize(), mln::geom::max_col(), mln::geom::max_row(), mln::geom::min_col(), and mln::geom::min_row().

9.77.2.2 template<typename I , typename J > void mln::io::magick::save (const **Image**< I > & *ima*, const **Image**< J > & *opacity_mask*, const std::string & *filename*)

Save a Milena image into a file using Magick++.

Parameters

[in] *ima* The image to save.

[in] *opacity_mask* Mask used to set pixel opacity_mask in output image. Output format must support this feature to be taken into account.

[in] *filename* The name of the output file.

Definition at line 228 of file magick/save.hh.

References mln::geom::ncols(), and mln::geom::nrows().

9.77.2.3 template<typename I > void mln::io::magick::save (const Image< I > & *ima*, const std::string & *filename*) [inline]

Save a Milena image into a file using Magick++.

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

- [in] *ima* The image to save.
- [in] *filename* The name of the output file.

Definition at line 288 of file magick/save.hh.

9.78 mln::io::off Namespace Reference

Namespace of off input/output handling.

Functions

- void [load \(bin_2complex_image3df &ima, const std::string &filename\)](#)
Load a (binary) OFF image into a complex image.
- void [save \(const bin_2complex_image3df &ima, const std::string &filename\)](#)
Save a (binary) OFF image into a complex image.
- template<typename I >
void [save_bin_alt \(const I &ima, const std::string &filename\)](#)
FIXME: Similar to [mln::io::off::save\(const bin_2complex_image3df&, const std::string&\)](#), but does not save faces whose value is 'false'.

9.78.1 Detailed Description

Namespace of off input/output handling.

9.78.2 Function Documentation

9.78.2.1 void mln::io::off::load (bin_2complex_image3df & *ima*, const std::string & *filename*)

Load a (binary) OFF image into a complex image.

Load a 3x8-bit RGB (color) OFF image into a complex image.

Load a floating-point OFF image into a complex image.

Parameters

- [out] *ima* A reference to the image to construct.
- [in] *filename* The name of the file to load.

The image is said binary since data only represent the existence of faces.

Parameters

[out] *ima* A reference to the image to construct.

[in] *filename* The name of the file to load.

Read floating-point data is attached to 2-faces only; 1-faces and 0-faces are set to 0.0f.

Definition at line 195 of file off/load.hh.

9.78.2.2 void mln::io::off::save (const bin_2complex_image3df & *ima*, const std::string & *filename*)

Save a (binary) OFF image into a complex image.

Save a 3x8-bit RGB (color) OFF image into a complex image.

Save a floating-point value grey-level OFF image into a complex image.

Save an 8-bit grey-level OFF image into a complex image.

Parameters

[in] *ima* The image to save.

[in] *filename* The name of the file where to save the image.

The image is said binary since data represent only the existence of faces.

Parameters

[in] *ima* The image to save.

[in] *filename* The name of the file where to save the image.

Only data is attached to 2-faces is saved; the OFF file cannot store data attached to faces of other dimensions.

Definition at line 189 of file off/save.hh.

9.78.2.3 template<typename I> void mln::io::off::save_bin_alt (const I & *ima*, const std::string & *filename*)

FIXME: Similar to [mln::io::off::save\(const bin_2complex_image3df&, const std::string&\)](#), but does not save faces whose value is ‘false’.

Definition at line 59 of file save_bin_alt.hh.

9.79 mln::io::pbm Namespace Reference

Namespace of pbm input/output handling.

Namespaces

- namespace `impl`
Namespace of pbm implementation details.

Functions

- void `load (image2d< bool > &ima, const std::string &filename)`
Load a pbm image in a Milena image.
- `image2d< bool > load (const std::string &filename)`
Load a pbm image in a image2d<float>.
- template<typename I >
void `save (const Image< I > &ima, const std::string &filename)`

9.79.1 Detailed Description

Namespace of pbm input/output handling.

9.79.2 Function Documentation

9.79.2.1 void `mln::io::pbm::load (image2d< bool > & ima, const std::string & filename) [inline]`

Load a pbm image in a Milena image.

Parameters

- [out] `ima` A reference to the `image2d<bool>` which will receive data.
[in] `filename` The source.

Definition at line 156 of file `pbm/load.hh`.

9.79.2.2 `image2d< bool > mln::io::pbm::load (const std::string & filename) [inline]`

Load a pbm image in a `image2d<float>`.

Parameters

- [in] `filename` The image source.

Returns

An `image2d<float>` which contains loaded data.

Definition at line 128 of file `pbm/load.hh`.

9.79.2.3 template<typename I> void mln::io::pbm::save (const Image< I > & *ima*, const std::string & *filename*) [inline]

Save a Milena image as a pbm image.

Parameters

- [in] *ima* The image to save.
- [in, out] *filename* the destination.

Definition at line 118 of file pbm/save.hh.

9.80 mln::io::pbm::impl Namespace Reference

Namespace of pbm implementation details.

9.80.1 Detailed Description

Namespace of pbm implementation details.

9.81 mln::io::pbms Namespace Reference

Namespace of pbms input/output handling.

Namespaces

- namespace [impl](#)
Namespace of pbms implementation details.

Functions

- void [load](#) (*image3d*< bool > &*ima*, const [util::array](#)< std::string > &*filenames*)
Load pbms images as slices of a 3D Milena image.

9.81.1 Detailed Description

Namespace of pbms input/output handling.

9.81.2 Function Documentation

9.81.2.1 void mln::io::pbms::load (*image3d*< bool > & *ima*, const [util::array](#)< std::string > & *filenames*) [inline]

Load pbms images as slices of a 3D Milena image.

Parameters

[out] *ima* A reference to the 3D image which will receive data.

[in] *filenames* The list of 2D images to load..

Definition at line 65 of file pbms/load.hh.

9.82 mln::io::pbms::impl Namespace Reference

Namespace of pbms implementation details.

9.82.1 Detailed Description

Namespace of pbms implementation details.

9.83 mln::io::pfm Namespace Reference

Namespace of pfm input/output handling.

Namespaces

- namespace [impl](#)

Implementation namespace of pfm namespace.

Functions

- void [load \(image2d< float > &ima, const std::string &filename\)](#)

Load a pfm image in a Milena image.

- [image2d< float > load \(const std::string &filename\)](#)

Load a pfm image in a image2d<float>.

- template<typename I >

void [save \(const Image< I > &ima, const std::string &filename\)](#)

Save a Milena image as a pfm image.

9.83.1 Detailed Description

Namespace of pfm input/output handling.

9.83.2 Function Documentation

9.83.2.1 void mln::io::pfm::load (`image2d< float > & ima`, `const std::string & filename`) [inline]

Load a pfm image in a Milena image.

Parameters

[out] *ima* A reference to the `image2d<float>` which will receive data.

[in] *filename* The source.

Definition at line 162 of file pfm/load.hh.

9.83.2.2 `image2d< float > mln::io::pfm::load (const std::string & filename)` [inline]

Load a pfm image in a `image2d<float>`.

Parameters

[in] *filename* The image source.

Returns

An `image2d<float>` which contains loaded data.

Definition at line 138 of file pfm/load.hh.

9.83.2.3 template<typename I> void mln::io::pfm::save (`const Image< I > & ima`, `const std::string & filename`) [inline]

Save a Milena image as a pfm image.

Parameters

[in] *ima* The image to save.

[in, out] *filename* the destination.

Definition at line 101 of file pfm/save.hh.

9.84 mln::io::pfm::impl Namespace Reference

Implementation namespace of pfm namespace.

9.84.1 Detailed Description

Implementation namespace of pfm namespace.

9.85 mln::io::pgm Namespace Reference

Namespace of pgm input/output handling.

Functions

- template<typename I >
void **load** ([Image](#)< I > &ima, const std::string &filename)
Load a pgm image in a Milena image.
- template<typename V >
[image2d](#)< V > **load** (const std::string &filename)
Load a pgm image in a Milena image.
- template<typename I >
void **save** (const [Image](#)< I > &ima, const std::string &filename)

9.85.1 Detailed Description

Namespace of pgm input/output handling.

9.85.2 Function Documentation

9.85.2.1 template<typename I > void mln::io::pgm::load ([Image](#)< I > & ima, const std::string & filename) [inline]

Load a pgm image in a Milena image.

Parameters

- [out] *ima* A reference to the image which will receive data.
[in] *filename* The source.

Definition at line 87 of file pgm/load.hh.

9.85.2.2 template<typename V > [image2d](#)< V > mln::io::pgm::load (const std::string & filename) [inline]

Load a pgm image in a Milena image.

To use this routine, you should specialize the template whith the value type of the image loaded. (ex : [load<value::int_u8>](#)("..."))

Parameters

- [in] *filename* The image source.

Returns

An [image2d](#) which contains loaded data.

Definition at line 77 of file pgm/load.hh.

9.85.2.3 template<typename I > void mln::io::pgm::save (const Image< I > & *ima*, const std::string & *filename*) [inline]

Save a Milena image as a pgm image.

Parameters

- [in] *ima* The image to save.
- [in, out] *filename* the destination.

Definition at line 77 of file pgm/save.hh.

9.86 mln::io::pgms Namespace Reference

Namespace of pgms input/output handling.

Functions

- template<typename V >
void **load** (*image3d*< V > &*ima*, const *util::array*< std::string > &*filenames*)
Load pgm images as slices of a 3D Milena image.

9.86.1 Detailed Description

Namespace of pgms input/output handling.

9.86.2 Function Documentation

9.86.2.1 template<typename V > void mln::io::pgms::load (*image3d*< V > & *ima*, const *util::array*< std::string > & *filenames*) [inline]

Load pgm images as slices of a 3D Milena image.

Parameters

- [out] *ima* A reference to the 3D image which will receive data.
- [in] *filenames* The list of 2D images to load..

Definition at line 69 of file pgms/load.hh.

9.87 mln::io::plot Namespace Reference

Namespace of plot input/output handling.

Functions

- template<typename I >
void **load** (`util::array< I > &arr, const std::string &filename)`
- template<typename T >
void **save** (`const histo::array< T > &arr, const std::string &filename)`)
- template<typename T >
void **save** (`const util::array< T > &arr, const std::string &filename, int start_value=0)`
Save a Milena array in a plot file.

- template<typename I >
void **save** (`const image1d< I > &ima, const std::string &filename)`
Save a Milena 1D image in a plot file.

9.87.1 Detailed Description

Namespace of plot input/output handling.

9.87.2 Function Documentation

9.87.2.1 template<typename I > void mln::io::plot::load (`util::array< I > & arr, const std::string & filename`) [inline]

Load a Milena 1D image from a plot file.

Parameters

- [in] **ima** A reference to the image to load.
- [out] **filename** The output file.
- [in] **start_value** The start index value of the plot (optional).

Load a Milena array from a plot file.

Parameters

- [in] **arr** A reference to the array to load.
- [out] **filename** The output file.

Definition at line 93 of file plot/load.hh.

References `mln::util::array< T >::append()`, and `mln::util::array< T >::clear()`.

9.87.2.2 template<typename T > void mln::io::plot::save (`const histo::array< T > & arr, const std::string & filename`) [inline]

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 103 of file plot/save.hh.

9.87.2.3 template<typename T > void mln::io::plot::save (const util::array< T > & arr, const std::string & filename, int start_value = 0) [inline]

Save a Milena array in a plot file.

Parameters

- [in] **arr** A reference to the array to save.
- [out] **filename** The output file.
- [in] **start_value** The start index value of the plot (optional).

Definition at line 89 of file plot/save.hh.

References mln::util::array< T >::nelements().

9.87.2.4 template<typename I > void mln::io::plot::save (const image1d< I > & ima, const std::string & filename)

Save a Milena 1D image in a plot file.

Parameters

- [in] **ima** A reference to the image to save.
- [out] **filename** The output file.

9.88 mln::io::pnm Namespace Reference

Namespace of pnm input/output handling.

Namespaces

- namespace **impl**
Namespace of pnm's implementation details.

Functions

- template<typename V >
image2d< V > load (char type_, const std::string &filename)
main function : load pnm format
- template<typename I >
void load (char type_, **Image< I >** &ima_, const std::string &filename)
An other way to load pnm files : the destination is an argument to check if the type match the file to load.
- template<typename I >
void load_ascii_builtin (std::ifstream &file, I &ima)
load_ascii for builtin value types.

- template<typename I >
void **load_ascii_value** (std::ifstream &file, I &ima)
load_ascii for Milena value types.

- template<typename I >
void **load_raw_2d** (std::ifstream &file, I &ima)
load_raw_2d.

- template<typename V >
unsigned int **max_component** (const V &)
Give the maximum value which can be stored as a component value type V.

- template<typename I >
void **save** (char type, const **Image**< I > &ima_, const std::string &filename)

9.88.1 Detailed Description

Namespace of pnm input/output handling.

9.88.2 Function Documentation

9.88.2.1 template<typename V > **image2d**<V> **mln::io::pnm::load** (**char type_**, **const std::string & filename**) [inline]

main function : load pnm format

Definition at line 210 of file pnm/load.hh.

References `load_raw_2d()`, and `max_component()`.

9.88.2.2 template<typename I > void **mln::io::pnm::load** (**char type_**, **Image**< I > & **ima_**, **const std::string & filename**) [inline]

An other way to load pnm files : the destination is an argument to check if the type match the file to load.

Definition at line 257 of file pnm/load.hh.

References `mln::make::box2d()`, `load_raw_2d()`, and `max_component()`.

9.88.2.3 template<typename I > void **mln::io::pnm::load_ascii_builtin** (**std::ifstream & file**, **I & ima**) [inline]

`load_ascii` for builtin value types.

Definition at line 178 of file pnm/load.hh.

9.88.2.4 template<typename I > void **mln::io::pnm::load_ascii_value** (**std::ifstream & file**, **I & ima**) [inline]

`load_ascii` for Milena value types.

Definition at line 164 of file pnm/load.hh.

9.88.2.5 template<typename I > void mln::io::pnm::load_raw_2d (std::ifstream & file, I & ima) [inline]

load_raw_2d.

for all pnm 8/16 bits formats

Definition at line 198 of file pnm/load.hh.

Referenced by load().

9.88.2.6 template<typename V > unsigned int mln::io::pnm::max_component (const V &) [inline]

Give the maximum value which can be stored as a component value type V.

Definition at line 56 of file max_component.hh.

Referenced by load().

9.88.2.7 template<typename I > void mln::io::pnm::save (char type, const Image< I > & ima_, const std::string & filename) [inline]

Save a Milena image as a pnm image.

Parameters

[in] **type** The type of the image to save (can be PPM, PGM, PBM).

[in] **ima_** The image to save.

[in, out] **filename** the destination.

Definition at line 185 of file pnm/save.hh.

9.89 mln::io::pnm::impl Namespace Reference

Namespace of pnm's implementation details.

9.89.1 Detailed Description

Namespace of pnm's implementation details.

9.90 mln::io::pnms Namespace Reference

Namespace of pnms input/output handling.

Functions

- template<typename V >
void **load** (char type, **image3d**< V > &ima, const **util::array**< std::string > &filenames)

Load pnm images as slices of a 3D Milena image.

- void **load** (char type, **image3d**< bool > &ima, const **util::array**< std::string > &filenames)

9.90.1 Detailed Description

Namespace of pnms input/output handling.

9.90.2 Function Documentation

9.90.2.1 template<typename V> void mln::io::pnms::load (char type, image3d< V > & ima, const util::array< std::string > & filenames) [inline]

Load pnm images as slices of a 3D Milena image.

Parameters

- [in] **type** The type of the pnm files.
- [out] **ima** A reference to the 3D image which will receive data.
- [in] **filenames** The list of 2D images to load..

Definition at line 79 of file pnms/load.hh.

References `mln::make::image3d()`, `mln::util::array< T >::is_empty()`, and `mln::util::array< T >::nelements()`.

Referenced by `load()`.

9.90.2.2 void mln::io::pnms::load (char type, image3d< bool > & ima, const util::array< std::string > & filenames) [inline]

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 102 of file pnms/load.hh.

References `mln::make::image3d()`, `mln::util::array< T >::is_empty()`, `load()`, and `mln::util::array< T >::nelements()`.

9.91 mln::io::ppm Namespace Reference

Namespace of ppm input/output handling.

Functions

- template<typename I >
void **load** (**Image**< I > &ima, const std::string &filename)
Load a ppm image in a Milena image.

- template<typename V >
`image2d< V > load` (const std::string &filename)
Load a ppm image in a Milena image.
- template<typename I >
`void save` (const `Image< I >` &ima, const std::string &filename)

9.91.1 Detailed Description

Namespace of ppm input/output handling.

9.91.2 Function Documentation

9.91.2.1 template<typename I > void mln::io::ppm::load (`Image< I >` & *ima*, const std::string & *filename*) [inline]

Load a ppm image in a Milena image.

Parameters

- [out] *ima* A reference to the image which will receive data.
- [in] *filename* The source.

Definition at line 89 of file ppm/load.hh.

9.91.2.2 template<typename V > `image2d< V >` mln::io::ppm::load (const std::string & *filename*) [inline]

Load a ppm image in a Milena image.

To use this routine, you should specialize the template whith the value type of the image loaded. (ex : `load<value::int_u8>("...")`)

Parameters

- [in] *filename* The image source.

Returns

An `image2d` which contains loaded data.

Definition at line 79 of file ppm/load.hh.

9.91.2.3 template<typename I > void mln::io::ppm::save (const `Image< I >` & *ima*, const std::string & *filename*) [inline]

Save a Milena image as a ppm image.

Parameters

- [in] *ima* The image to save.

[in, out] *filename* the destination.

Definition at line 65 of file ppm/save.hh.

Referenced by mln::registration::icp().

9.92 mln::io::ppms Namespace Reference

Namespace of ppms input/output handling.

Functions

- template<typename V >
void **load** (*image3d*< V > &*ima*, const *util::array*< std::string > &*filenames*)

Load ppm images as slices of a 3D Milena image.

9.92.1 Detailed Description

Namespace of ppms input/output handling.

9.92.2 Function Documentation

- 9.92.2.1 template<typename V > void mln::io::ppms::load (*image3d*< V > & *ima*, const *util::array*< std::string > & *filenames*) [inline]**

Load ppm images as slices of a 3D Milena image.

Parameters

[out] *ima* A reference to the 3D image which will receive data.

[in] *filenames* The list of 2D images to load..

Definition at line 67 of file ppms/load.hh.

9.93 mln::io::raw Namespace Reference

Namespace of raw input/output handling.

Classes

- struct **raw_header**
Store raw file header.

Functions

- **raw_header get_header (const std::string &filename)**
Retrieve header in a raw file.
- template<typename I >
void load (Image< I > &ima_, const std::string &filename)
Load an image saved as a raw data file.
- template<typename I >
void save (const Image< I > &ima_, const std::string &filename)
Save a Milena image as a raw data file.

9.93.1 Detailed Description

Namespace of raw input/output handling.

9.93.2 Function Documentation

9.93.2.1 raw_header mln::io::raw::get_header (const std::string & filename)

Retrieve header in a raw file.

Definition at line 68 of file raw/get_header.hh.

References mln::util::array< T >::resize().

9.93.2.2 template<typename I > void mln::io::raw::load (Image< I > & ima_, const std::string & filename)

Load an image saved as a raw data file.

Parameters

- [in, out] **ima_** The image to load.
- [in] **filename** the destination.

This routine try to read two input files: 'filename' and 'filename.info'. 'filename' is the raw data. 'filename.info' store various information about the image.

Definition at line 184 of file raw/load.hh.

9.93.2.3 template<typename I > void mln::io::raw::save (const Image< I > & ima_, const std::string & filename)

Save a Milena image as a raw data file.

Parameters

- [in] **ima_** The image to save.
- [in] **filename** the destination.

This routine produce two output files: 'filename' and 'filename.info'. 'filename' is the raw data. 'filename.info' store various information about the image.

Definition at line 135 of file raw/save.hh.

9.94 mln::io::tiff Namespace Reference

Namespace of tiff input/output handling.

Functions

- template<typename I >
void **load** ([Image](#)< I > &ima_, const std::string &filename)

Load a TIFF image to a Milena image.

9.94.1 Detailed Description

Namespace of tiff input/output handling.

9.94.2 Function Documentation

- 9.94.2.1 template<typename I > void mln::io::tiff::load ([Image](#)< I > & ima_, const std::string & filename) [inline]**

Load a TIFF image to a Milena image.

Definition at line 323 of file tiff/load.hh.

9.95 mln::io::txt Namespace Reference

Namespace of txt input/output handling.

Functions

- void **save** (const [image2d](#)< char > &ima, const std::string &filename)
Save an image as txt file.

9.95.1 Detailed Description

Namespace of txt input/output handling.

9.95.2 Function Documentation

9.95.2.1 void mln::io::txt::save (const image2d< char > & ima, const std::string & filename) [inline]

Save an image as txt file.

Parameters

- [in] *ima* The image to save. Must be an image of char.
- [in] *filename* the destination.

Definition at line 63 of file txt/save.hh.

References mln::image2d< T >::domain().

9.96 mln::labeling Namespace Reference

Namespace of labeling routines.

Namespaces

- namespace **impl**
Implementation namespace of labeling namespace.

Functions

- template<typename I , typename N , typename L >
`mln::trait::ch_value< I, L >::ret background (const Image< I > &input, const Neighborhood< N > &nbh, L &nlabels)`
- template<typename I , typename N , typename L >
`mln::trait::ch_value< I, L >::ret blobs (const Image< I > &input, const Neighborhood< N > &nbh, L &nlabels)`

Connected component labeling of the binary objects of a binary image.

- template<typename I , typename N , typename L , typename A >
`util::couple< mln::trait::ch_value< I, L >::ret, util::couple< util::array< typename A::result >, util::array< A > > > blobs_and_compute (const Image< I > &input, const Neighborhood< N > &nbh, L &nlabels, const Accumulator< A > &accu)`
- template<typename V , typename L >
`mln::trait::ch_value< L, V >::ret colorize (const V &value, const Image< L > &labeled_image, const typename L::value &nlabels)`

Create a new color image from a labeled image and fill each component with a random color.

- template<typename V , typename L >
`mln::trait::ch_value< L, V >::ret colorize (const V &value, const Image< L > &labeled_image)`
- template<typename L >
`mln::trait::ch_value< L, mln::value::rgb8 >::ret colorize (const Image< L > &input, const typename L::value &nlabels)`

- template<typename A , typename I , typename L >
`util::array< mln_meta_accu_result(A, typename I::value)> compute (const Meta_Accumulator< A > &a, const Image< I > &input, const Image< L > &label, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename A , typename L >
`util::array< typename A::result > compute (const Accumulator< A > &a, const Image< L > &label, const typename L::value &nlabels)`
Compute an accumulator onto the pixel sites of each component domain of label.
- template<typename A , typename L >
`util::array< mln_meta_accu_result(A, typename L::psite)> compute (const Meta_Accumulator< A > &a, const Image< L > &label, const typename L::value &nlabels)`
Compute an accumulator onto the pixel sites of each component domain of label.
- template<typename A , typename I , typename L >
`util::array< typename A::result > compute (util::array< A > &a, const Image< I > &input, const Image< L > &label, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename A , typename I , typename L >
`util::array< typename A::result > compute (const Accumulator< A > &a, const Image< I > &input, const Image< L > &label, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename A , typename I , typename L >
`mln::trait::ch_value< L, typename A::result >::ret compute_image (const util::array< typename A::result > &a, const Image< I > &input, const Image< L > &labels, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename A , typename I , typename L >
`mln::trait::ch_value< L, typename A::result >::ret compute_image (const Accumulator< A > &accu, const Image< I > &input, const Image< L > &labels, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename A , typename I , typename L >
`mln::trait::ch_value< L, typename mln::internal::meta_accu_ret_result_helper< A, typename I::value >::result >::ret compute_image (const Meta_Accumulator< A > &accu, const Image< I > &input, const Image< L > &labels, const typename L::value &nlabels)`
Compute an accumulator onto the pixel values of the image input.
- template<typename I , typename N , typename L >
`mln::trait::concrete< I >::ret fill_holes (const Image< I > &input, const Neighborhood< N > &nbh, L &nlabels)`
Filling holes of a single object in a binary image.
- template<typename I , typename N , typename L >
`mln::trait::ch_value< I, L >::ret flat_zones (const Image< I > &input, const Neighborhood< N > &nbh, L &nlabels)`
Connected component labeling of the flat zones of an image.

- template<typename I , typename N , typename L >
mln::trait::ch_value< I, L >::ret **foreground** (const **Image**< I > &input, const **Neighborhood**< N > &nbh, L &nlabels)

- template<typename I >
mln::trait::concrete< I >::ret **pack** (const **Image**< I > &**label**, typename I::value &new_nlabels, fun::i2v::array< typename I::value > &**repack_fun**)

Relabel a labeled image in order to have a contiguous labeling.

- template<typename I >
mln::trait::concrete< I >::ret **pack** (const **Image**< I > &**label**, typename I::value &new_nlabels)

- template<typename I >
void pack_inplace (**Image**< I > &**label**, typename I::value &new_nlabels)

- template<typename I >
void pack_inplace (**Image**< I > &**label**, typename I::value &new_nlabels, fun::i2v::array< typename I::value > &**repack_fun**)

Relabel inplace a labeled image in order to have a contiguous labeling.

- template<typename I , typename N , typename L >
mln::trait::ch_value< I, L >::ret **regional_maxima** (const **Image**< I > &input, const **Neighborhood**< N > &nbh, L &nlabels)

- template<typename I , typename N , typename L >
mln::trait::ch_value< I, L >::ret **regional_minima** (const **Image**< I > &input, const **Neighborhood**< N > &nbh, L &nlabels)

- template<typename I , typename F >
mln::trait::concrete< I >::ret **relabel** (const **Image**< I > &**label**, const typename I::value &nlabels, typename I::value &new_nlabels, const **Function_v2b**< F > &fv2b)

Remove components and relabel a labeled image.

- template<typename I , typename F >
mln::trait::concrete< I >::ret **relabel** (const **Image**< I > &**label**, const typename I::value &nlabels, const **Function_v2v**< F > &fv2v)

Remove components and relabel a labeled image.

- template<typename I , typename F >
void relabel_inplace (**Image**< I > &**label**, const typename I::value &nlabels, const **Function_v2v**< F > &fv2v)

Remove components and relabel a labeled image inplace.

- template<typename I , typename F >
void relabel_inplace (**Image**< I > &**label**, const typename I::value &nlabels, const **Function_v2b**< F > &fv2b)

Remove components and relabel a labeled image inplace.

- template<typename I , typename J >
mln::trait::concrete< I >::ret **superpose** (const **Image**< I > &lhs, const typename I::value &lhs_nlabels, const **Image**< J > &rhs, const typename J::value &rhs_nlabels, typename I::value &new_nlabels)

Superpose two labeled image.

- template<typename I , typename N , typename L >
`mln::trait::ch_value< I, L >::ret value (const Image< I > &input, const typename I::value &val, const Neighborhood< N > &nbh, L &nlabels)`
Connected component labeling of the image sites at a given value.
- template<typename I , typename N , typename L , typename A >
`util::couple< mln::trait::ch_value< I, L >::ret, util::couple< util::array< typename A::result >, util::array< A > > > value_and_compute (const Image< I > &input, const typename I::value &val, const Neighborhood< N > &nbh, L &nlabels, const Accumulator< A > &accu)`
Connected component labeling of the image sites at a given value.
- template<typename V , typename I >
`mln::trait::ch_value< I, V >::ret wrap (const V &value_type, const Image< I > &input)`
Wrap labels such as $0 \rightarrow 0$ and $[1, lmax]$ maps to $[1, Lmax]$ (using modulus).
- template<typename I >
`mln::trait::ch_value< I, mln::value::label_8 >::ret wrap (const Image< I > &input)`
Wrap labels such as $0 \rightarrow 0$ and $[1, lmax]$ maps to $[1, Lmax]$ (using modulus).

9.96.1 Detailed Description

Namespace of labeling routines.

9.96.2 Function Documentation

9.96.2.1 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret `mln::labeling::background (const Image< I > & input, const Neighborhood< N > & nbh, L & nlabels) [inline]`

Connected component labeling of the background part in a binary image.

Parameters

- [in] `input` The input image.
- [in] `nbh` The connexity of the background.
- [out] `nlabels` The number of labels.

Returns

The label image.

Precondition

The input image has to be binary (checked at compile-time).

This routine actually calls `mln::labeling::value` with the value set to `false`.

See also

[mln::labeling::value](#)

Definition at line 69 of file background.hh.

References value().

Referenced by fill_holes().

**9.96.2.2 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret
mln::labeling::blobs (const Image< I > & *input*, const Neighborhood< N > & *nbh*, L
& *nlabels*) [inline]**

Connected component labeling of the binary objects of a binary image.

Parameters

[in] *input* The input image.

[in] *nbh* The connexity of the objects.

[out] *nlabels* The Number of labels. Its value is set in the algorithms.

Returns

The label image.

Precondition

The input image has to be binary (checked at compile-time).

A fast queue is used so that the algorithm is not recursive and can handle large binary objects (blobs).

Definition at line 102 of file labeling/blobs.hh.

Referenced by blobs_and_compute(), and mln::graph::labeling().

**9.96.2.3 template<typename I , typename N , typename L , typename A > util::couple<
mln::trait::ch_value< I, L >::ret, util::couple< util::array< typename A::result >,
util::array< A > > > mln::labeling::blobs_and_compute (const Image< I > & *input*,
const Neighborhood< N > & *nbh*, L & *nlabels*, const Accumulator< A > & *accu*)**

Label an image and compute given accumulators.

Parameters

[in] *input* A binary image.

[in] *nbh* A neighborhood used for labeling.

[in, out] *nlabels* The number of labels found.

[in] *accu* An accumulator to be computed while labeling.

Returns

The labeled image, computed attributes for each regions and an array of the accumulators used to compute the attributes.

Definition at line 160 of file blobs_and_compute.hh.

References blobs(), and mln::make::couple().

**9.96.2.4 template<typename V , typename L > mln::trait::ch_value< L, V >::ret
mln::labeling::colorize (const V & value, const Image< L > & labeled_image, const
typename L::value & nlabels) [inline]**

Create a new color image from a labeled image and fill each component with a random color.

litera::black is used for component 0, e.g. the background. Min and max values for RGB values can be set through the global variables mln::labeling::colorize_::min_value and mln::labeling::colorize_::max_value.

Parameters

[in] **value** value type used in the returned image.
[in] **labeled_image** A labeled image (

See also

[labeling::blobs](#)).

Parameters

[in] **nlabels** Number of labels.

Definition at line 190 of file colorize.hh.

References mln::literal::black, and mln::data::transform().

Referenced by colorize().

**9.96.2.5 template<typename V , typename L > mln::trait::ch_value< L, V >::ret
mln::labeling::colorize (const V & value, const Image< L > & labeled_image)
[inline]**

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 228 of file colorize.hh.

References colorize(), and compute().

**9.96.2.6 template<typename L > mln::trait::ch_value< L, mln::value::rgb8 >::ret
mln::labeling::colorize (const Image< L > & input, const typename L::value & nlabels) [inline]**

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 247 of file colorize.hh.

References colorize().

**9.96.2.7 template<typename A , typename I , typename L > util::array<
mln_meta_accu_result(A, typename I::value)> mln::labeling::compute (const
Meta_Accumulator< A > & a, const Image< I > & input, const Image< L > & label,
const typename L::value & nlabels) [inline]**

Compute an accumulator onto the pixel values of the image `input`.

for each component of the image `label`.

Parameters

- [in] *a* A meta-accumulator.
- [in] *input* The input image.
- [in] *label* The labeled image.
- [in] *nlabels* The number of labels in *label*.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 734 of file labeling/compute.hh.

References compute().

**9.96.2.8 template<typename A , typename L > util::array< typename A::result >
mln::labeling::compute (const Accumulator< A > & *a*, const Image< L > & *label*,
const typename L::value & *nlabels*) [inline]**

Compute an accumulator onto the pixel sites of each component domain of *label*.

Parameters

- [in] *a* An accumulator.
- [in] *label* The labeled image.
- [in] *nlabels* The number of labels in *label*.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 771 of file labeling/compute.hh.

**9.96.2.9 template<typename A , typename L > util::array< mln_meta_accu_result(A, typename
L::psite)> mln::labeling::compute (const Meta_Accumulator< A > & *a*, const Image<
L > & *label*, const typename L::value & *nlabels*) [inline]**

Compute an accumulator onto the pixel sites of each component domain of *label*.

Parameters

- [in] *a* A meta-accumulator.
- [in] *label* The labeled image.
- [in] *nlabels* The number of labels in *label*.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 792 of file labeling/compute.hh.

References compute().

9.96.2.10 template<typename A , typename I , typename L > util::array< typename A::result > mln::labeling::compute (util::array< A > & a, const Image< I > & input, const Image< L > & label, const typename L::value & nlabels) [inline]

Compute an accumulator onto the pixel values of the image `input`.
for each component of the image `label`.

Parameters

- [in] `a` An array of accumulator.
- [in] `input` The input image.
- [in] `label` The labeled image.
- [in] `nlabels` The number of labels in `label`.

Returns

A `util::array` of accumulator result (one result per label).

Definition at line 696 of file labeling/compute.hh.

9.96.2.11 template<typename A , typename I , typename L > util::array< typename A::result > mln::labeling::compute (const Accumulator< A > & a, const Image< I > & input, const Image< L > & label, const typename L::value & nlabels) [inline]

Compute an accumulator onto the pixel values of the image `input`.
for each component of the image `label`.

Parameters

- [in] `a` An accumulator.
- [in] `input` The input image.
- [in] `label` The labeled image.
- [in] `nlabels` The number of labels in `label`.

Returns

A `util::array` of accumulator result (one result per label).

Definition at line 715 of file labeling/compute.hh.

Referenced by `colorize()`, `compute()`, `compute_image()`, `fill_holes()`, `mln::make::p_edges_with_mass_centers()`, `mln::make::p_vertices_with_mass_centers()`, `pack()`, and `pack_inplace()`.

9.96.2.12 template<typename A , typename I , typename L > mln::trait::ch_value< L , typename A ::result >::ret mln::labeling::compute_image (const util::array< typename A::result > & a, const Image< I > & input, const Image< L > & labels, const typename L::value & nlabels)

Compute an accumulator onto the pixel values of the image `input`.
for each component of the image `label`.

Parameters

- [in] ***a*** The [mln::p_array](#) of accumulator result.
- [in] ***input*** The input image (values).
- [in] ***labels*** The label image.
- [in] ***nlabels*** The count of labels.

Returns

The image where labels are replaced by the result of the accumulator.

Referenced by [compute_image\(\)](#).

9.96.2.13 template<typename A , typename I , typename L > mln::trait::ch_value< L, typename A::result >::ret mln::labeling::compute_image (const Accumulator< A > & *accu***, const Image< I > & ***input***, const Image< L > & ***labels***, const typename L::value & ***nlabels***) [inline]**

Compute an accumulator onto the pixel values of the image ***input***.
for each component of the image ***label***.

Parameters

- [in] ***accu*** The accumulator.
- [in] ***input*** The input image (values).
- [in] ***labels*** The label image.
- [in] ***nlabels*** The count of labels.

Returns

The image where labels are replaced by the result of the accumulator.

Definition at line 161 of file [compute_image.hh](#).

References [compute\(\)](#), and [compute_image\(\)](#).

9.96.2.14 template<typename A , typename I , typename L > mln::trait::ch_value< L, typename mln::internal::meta_accu_ret_result_helper< A, typename I::value >::result >::ret mln::labeling::compute_image (const Meta_Accumulator< A > & *accu***, const Image< I > & ***input***, const Image< L > & ***labels***, const typename L::value & ***nlabels***) [inline]**

Compute an accumulator onto the pixel values of the image ***input***.
for each component of the image ***label***.

Parameters

- [in] ***accu*** The meta-accumulator.
- [in] ***input*** The input image (values).
- [in] ***labels*** The label image.
- [in] ***nlabels*** The count of labels.

Returns

The image where labels are replaced by the result of the accumulator.

Definition at line 181 of file compute_image.hh.

References compute(), and compute_image().

**9.96.2.15 template<typename I , typename N , typename L > mln::trait::concrete< I >::ret
`mln::labeling::fill_holes (const Image< I > & input, const Neighborhood< N > &`
`nbh, L & nlabels) [inline]`**

Filling holes of a single object in a binary image.

Parameters

- [in] **input** The input image.
- [in] **nbh** The connexity of the background.
- [out] **nlabels** The number of labels.

Returns

The binary image with a simple object without holes.

Precondition

The input image has to be binary (checked at compile-time).

This routine actually calls [mln::labeling::background](#)

See also

[mln::labeling::background](#)

Definition at line 73 of file fill_holes.hh.

References background(), compute(), mln::util::array< T >::nelements(), and mln::data::transform().

**9.96.2.16 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret
`mln::labeling::flat_zones (const Image< I > & input, const Neighborhood< N > &`
`nbh, L & nlabels)`**

Connected component labeling of the flat zones of an image.

Parameters

- [in] **input** The input image.
- [in] **nbh** The connexity of the flat zones.
- [out] **nlabels** The number of labels.

Returns

The label image.

Definition at line 124 of file flat_zones.hh.

**9.96.2.17 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret
mln::labeling::foreground (const Image< I > & *input*, const Neighborhood< N > &
nbh, L & *nlabels*) [inline]**

Connected component labeling of the object part in a binary image.

Parameters

- [in] *input* The input image.
- [in] *nbh* The connexity of the foreground.
- [out] *nlabels* The number of labels.

Returns

The label image.

Precondition

The input image has to be binary (checked at compile-time).

This routine actually calls [mln::labeling::value](#) with the value set to `true`.

See also

[mln::labeling::value](#)

Definition at line 69 of file foreground.hh.

References `value()`.

**9.96.2.18 template<typename I > mln::trait::concrete< I >::ret mln::labeling::pack (const
Image< I > & *label*, typename I::value & *new_nlabels*, fun::i2v::array< typename
I::value > & *repack_fun*)**

Relabel a labeled image in order to have a contiguous labeling.

Parameters

- [in] *label* The labeled image.
- [out] *new_nlabels* The number of labels after relabeling.
- [out] *repack_fun* The function used to repack the labels.

Returns

The relabeled image.

Definition at line 124 of file pack.hh.

References `compute()`, `mln::make::relabelfun()`, and `mln::data::transform()`.

Referenced by `pack()`.

9.96.2.19 template<typename I > mln::trait::concrete< I >::ret mln::labeling::pack (const Image< I > & *label*, typename I::value & *new_nlabels*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 115 of file pack.hh.

References pack().

9.96.2.20 template<typename I > void mln::labeling::pack_inplace (Image< I > & *label*, typename I::value & *new_nlabels*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 148 of file pack.hh.

References pack_inplace().

9.96.2.21 template<typename I > void mln::labeling::pack_inplace (Image< I > & *label*, typename I::value & *new_nlabels*, fun::i2v::array< typename I::value > & *repack_fun*)

Relabel inplace a labeled image in order to have a contiguous labeling.

Parameters

- [in] *label* The labeled image.
- [out] *new_nlabels* The number of labels after relabeling.
- [out] *repack_fun* The function used to repack the labels.

Definition at line 157 of file pack.hh.

References compute(), mln::make::relabelfun(), and mln::data::transform().

Referenced by pack_inplace().

9.96.2.22 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret mln::labeling::regional_maxima (const Image< I > & *input*, const Neighborhood< N > & *nbh*, L & *nlabels*)

Connected component labeling of the regional maxima of an image.

Parameters

- [in] *input* The input image.
- [in] *nbh* The connexity of the regional maxima.
- [out] *nlabels* The number of labeled regions.

Returns

The label image.

Definition at line 130 of file regional_maxima.hh.

**9.96.2.23 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret
mln::labeling::regional_minima (const Image< I > & *input*, const Neighborhood< N > & *nbh*, L & *nlabels*)**

Connected component labeling of the regional minima of an image.

Parameters

- [in] *input* The input image.
- [in] *nbh* The connexity of the regional minima.
- [out] *nlabels* The number of labeled regions.

Returns

The label image.

Definition at line 140 of file regional_minima.hh.

Referenced by mln::morpho::meyer_wst().

**9.96.2.24 template<typename I , typename F > mln::trait::concrete< I >::ret
mln::labeling::relabel (const Image< I > & *label*, const typename I::value & *nlabels*,
typename I::value & *new_nlabels*, const Function_v2b< F > & *fv2b*) [inline]**

Remove components and relabel a labeled image.

Parameters

- [in] *label* the labeled image.
- [in] *nlabels* the number of labels in *label*.
- [out] *new_nlabels* the number of labels after relabeling.
- [in] *fv2b* function returning whether a label must be replaced by the background.

Returns

the relabeled image.

Definition at line 200 of file relabel.hh.

References mln::make::relabelfun().

Referenced by superpose().

**9.96.2.25 template<typename I , typename F > mln::trait::concrete< I >::ret
mln::labeling::relabel (const Image< I > & *label*, const typename I::value & *nlabels*,
const Function_v2v< F > & *fv2v*) [inline]**

Remove components and relabel a labeled image.

Parameters

- [in] *label* the labeled image.
- [in] *nlabels* the number of labels in *label*.

[in] *fv2v* function returning the new component id for each pixel value.

Returns

the relabeled image.

Definition at line 179 of file relabel.hh.

References mln::data::transform().

**9.96.2.26 template<typename I , typename F > void mln::labeling::relabel_inplace (Image< I > & *label*, const typename I::value & *nlabels*, const Function_v2v< F > & *fv2v*)
[inline]**

Remove components and relabel a labeled image inplace.

Parameters

[in, out] *label* the labeled image.

[in] *nlabels* the number of labels in *label*.

[in] *fv2v* function returning the new component id for each pixel value.

Definition at line 221 of file relabel.hh.

References mln::data::transform_inplace().

**9.96.2.27 template<typename I , typename F > void mln::labeling::relabel_inplace (Image< I > & *label*, const typename I::value & *nlabels*, const Function_v2b< F > & *fv2b*)
[inline]**

Remove components and relabel a labeled image inplace.

Parameters

[in, out] *label* the labeled image.

[in] *nlabels* the number of labels in *label*.

[in] *fv2b* function returning whether a label must be replaced by the background.

Definition at line 240 of file relabel.hh.

References mln::make::relabelfun().

Referenced by mln::labeled_image_base< I, E >::relabel().

**9.96.2.28 template<typename I , typename J > mln::trait::concrete< I >::ret
mln::labeling::superpose (const Image< I > & *lhs*, const typename I::value &
lhs_nlabels, const Image< J > & *rhs*, const typename J::value & *rhs_nlabels*,
typename I::value & *new_nlabels*)**

Superpose two labeled image.

Labels in *lhs* are preserved in the output. Labels of *rhs* are renumbered from the last label value of *lhs*. It avoids duplicate label values in several components.

Parameters

- [in] ***lhs*** A labeled image.
- [in] ***lhs_nlabels*** The number of labels in *lhs*.
- [in] ***rhs*** A labeled image.
- [in] ***rhs_nlabels*** The number of labels in *rhs*.
- [out] ***new_nlabels*** The number of labels in the output image.

Returns

An image with all the components of *rhs* and *lhs*.

Precondition

rhs and *lhs* must have the same domain.
The value type of *rhs* must be convertible towards *lhs*'s.

Definition at line 83 of file labeling/superpose.hh.

References mln::duplicate(), mln::value::equiv(), mln::data::paste(), relabel(), and mln::literal::zero.

**9.96.2.29 template<typename I , typename N , typename L > mln::trait::ch_value< I, L >::ret
mln::labeling::value (const Image< I > & *input*, const typename I::value & *val*, const
Neighborhood< N > & *nbh*, L & *nlabels*)**

Connected component labeling of the image sites at a given value.

Parameters

- [in] ***input*** The input image.
- [in] ***val*** The value to consider.
- [in] ***nbh*** The connectivity of components.
- [out] ***nlabels*** The number of labels.

Returns

The label image.

Definition at line 149 of file labeling/value.hh.

Referenced by background(), and foreground().

**9.96.2.30 template<typename I , typename N , typename L , typename A > util::couple<
mln::trait::ch_value< I, L >::ret, util::couple< util::array< typename A::result >,
util::array< A > > > mln::labeling::value_and_compute (const Image< I > & *input*,
const typename I::value & *val*, const Neighborhood< N > & *nbh*, L & *nlabels*, const
Accumulator< A > & *accu*)**

Connected component labeling of the image sites at a given value.

Parameters

- [in] ***input*** The input image.

[in] ***val*** The value to consider.
 [in] ***nbh*** The connectivity of components.
 [out] ***nlabels*** The number of labels.

Returns

The label image.

Definition at line 212 of file value_and_compute.hh.

References mln::make::couple().

**9.96.2.31 template<typename V , typename I > mln::trait::ch_value< I, V >::ret
`mln::labeling::wrap (const V & value_type, const Image< I > & input) [inline]`**

Wrap labels such as 0 -> 0 and [1, lmax] maps to [1, Lmax] (using modulus).

Parameters

[in] ***value_type*** The type used to wrap the label type.
 [in] ***input*** The label image.

Returns

A new image with values wrapped with type V.

Definition at line 75 of file labeling/wrap.hh.

References mln::data::transform().

Referenced by wrap().

**9.96.2.32 template<typename I > mln::trait::ch_value< I, mln::value::label_8 >::ret
`mln::labeling::wrap (const Image< I > & input) [inline]`**

Wrap labels such as 0 -> 0 and [1, lmax] maps to [1, Lmax] (using modulus).

Use label_8 as label type.

Parameters

[in] ***input*** The label image.

Returns

A new image with values wrapped with type label_8.

Definition at line 93 of file labeling/wrap.hh.

References wrap().

9.97 mln::labeling::impl Namespace Reference

Implementation namespace of labeling namespace.

Namespaces

- namespace **generic**

Generic implementation namespace of labeling namespace.

Functions

- template<typename A , typename I , typename L >
`util::array< typename A::result > compute_fastest (const Accumulator< A > &a_, const Image< I > &input_, const Image< L > &label_, const typename L::value &nlabels)`

Fastest implementation of [labeling::compute](#).

- template<typename A , typename I , typename L >
`util::array< typename A::result > compute_fastest (util::array< A > &accus, const Image< I > &input_, const Image< L > &label_, const typename L::value &nlabels)`

Fastest implementation of [labeling::compute](#).

9.97.1 Detailed Description

Implementation namespace of labeling namespace.

9.97.2 Function Documentation

- 9.97.2.1 template<typename A , typename I , typename L > util::array<typename A ::result> mln::labeling::impl::compute_fastest (const Accumulator< A > & a_ , const Image< I > & input_ , const Image< L > & label_ , const typename L::value & nlabels) [inline]**

Fastest implementation of [labeling::compute](#).

Parameters

- [in] **a_** An accumulator.
- [in] **input_** The input image.
- [in] **label_** The labeled image.
- [in] **nlabels** The number of labels in `label`.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 373 of file labeling/compute.hh.

References `mln::geom::ncols()`.

9.97.2.2 template<typename A , typename I , typename L > util::array<typename A ::result> mln::labeling::impl::compute_fastest (util::array< A > & accus, const Image< I > & input_, const Image< L > & label_, const typename L::value & nlabels) [inline]

Fastest implementation of [labeling::compute](#).

Parameters

- [in] **accus** An array of accumulators.
- [in] **input_** The input image.
- [in] **label_** The labeled image.
- [in] **nlabels** The number of labels in `label`.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 427 of file labeling/compute.hh.

References `mln::geom::ncols()`, `mln::util::array< T >::resize()`, and `mln::util::array< T >::size()`.

9.98 mln::labeling::impl::generic Namespace Reference

Generic implementation namespace of labeling namespace.

Functions

- template<typename A , typename L >
`util::array< typename A::result > compute (const Accumulator< A > &a_, const Image< L > &label_, const typename L::value &nlabels)`
Generic implementation of [labeling::compute](#).
- template<typename A , typename L >
`util::array< typename A::result > compute (util::array< A > &accus, const Image< L > &label_, const typename L::value &nlabels)`
Generic implementation of [labeling::compute](#).
- template<typename A , typename I , typename L >
`util::array< typename A::result > compute (util::array< A > &accus, const Image< I > &input_, const Image< L > &label_, const typename L::value &nlabels)`
Generic implementation of [labeling::compute](#).
- template<typename A , typename I , typename L >
`util::array< typename A::result > compute (const Accumulator< A > &a_, const Image< I > &input_, const Image< L > &label_, const typename L::value &nlabels)`
Generic implementation of [labeling::compute](#).

9.98.1 Detailed Description

Generic implementation namespace of labeling namespace.

9.98.2 Function Documentation

**9.98.2.1 template<typename A , typename L > util::array<typename A ::result>
 mln::labeling::impl::generic::compute (const Accumulator< A > & *a*_, const Image< L > & *label*_, const typename L::value & *nlabels*) [inline]**

Generic implementation of [labeling::compute](#).

Parameters

- [in] *a*_ An accumulator.
- [in] *label*_ The labeled image.
- [in] *nlabels* The number of labels in *label*.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 204 of file labeling/compute.hh.

**9.98.2.2 template<typename A , typename L > util::array<typename A ::result>
 mln::labeling::impl::generic::compute (util::array< A > & *accus*, const Image< L > & *label*_, const typename L::value & *nlabels*) [inline]**

Generic implementation of [labeling::compute](#).

Parameters

- [in] *accus*_ An array of accumulators. If the size is set to *nlabels* + 1, the accumulators are considered as initialized. Otherwise, the size is adjusted.
- [in] *label*_ The labeled image.
- [in] *nlabels* The number of labels in *label*.

Returns

A [util::array](#) of accumulator result (one result per label).

Definition at line 241 of file labeling/compute.hh.

References `mln::util::array< T >::resize()`, and `mln::util::array< T >::size()`.

**9.98.2.3 template<typename A , typename I , typename L > util::array<typename A ::result>
 mln::labeling::impl::generic::compute (util::array< A > & *accus*, const Image< I > & *input*_, const Image< L > & *label*_, const typename L::value & *nlabels*) [inline]**

Generic implementation of [labeling::compute](#).

Parameters

- [in] *accus* An array of accumulators.
- [in] *input*_ The input image.
- [in] *label*_ The labeled image.

[in] ***nlabels*** The number of labels in `label`.

Returns

A `util::array` of accumulator result (one result per label).

Definition at line 321 of file `labeling/compute.hh`.

References `mln::util::array< T >::resize()`, and `mln::util::array< T >::size()`.

```
9.98.2.4 template<typename A , typename I , typename L > util::array<typename A ::result>
    mln::labeling::impl::generic::compute ( const Accumulator< A > & a_ , const Image< I > & input_ , const Image< L > & label_ , const typename L::value & nlabels )
    [inline]
```

Generic implementation of `labeling::compute`.

Parameters

[in] ***a*_** An accumulator.

[in] ***input*_** The input image.

[in] ***label*_** The labeled image.

[in] ***nlabels*** The number of labels in `label`.

Returns

A `util::array` of accumulator result (one result per label).

Definition at line 283 of file `labeling/compute.hh`.

9.99 mln::linear Namespace Reference

Namespace of linear image processing routines.

Namespaces

- namespace `impl`

Namespace of linear image processing routines implementation details.

- namespace `local`

Specializations of local linear routines.

Functions

- template<typename I >


```
mln::trait::concrete< I >::ret gaussian (const Image< I > &input, float sigma)
```

Gaussian filter of an image input.

- template<typename I >
mln::trait::concrete< I >::ret **gaussian** (const **Image**< I > &input, float sigma, int dir)
- template<typename I >
mln::trait::concrete< I >::ret **gaussian_1st_derivative** (const **Image**< I > &input, float sigma)
- template<typename I >
mln::trait::concrete< I >::ret **gaussian_1st_derivative** (const **Image**< I > &input, float sigma, int dir)
- template<typename I >
mln::trait::concrete< I >::ret **gaussian_2nd_derivative** (const **Image**< I > &input, float sigma, int dir)
- template<typename I , typename W , unsigned Sh, unsigned Sv>
mln_ch_convolve (I, W) convolve_2x1d(const **Image**< I > &input)
- template<typename I , typename W >
mln_ch_convolve (I, W) convolve(const **Image**< I > &input)
- template<typename I , typename W , unsigned S>
mln_ch_convolve (I, W) convolve_directional(const **Image**< I > &input)
- template<typename I >
mln_ch_convolve_grad (I, int) sobel_2d(const **Image**< I > &input)
Compute the vertical component of the 2D Sobel gradient.
- template<typename I >
mln_ch_convolve (I, int) sobel_2d_h(const **Image**< I > &input)
Sobel_2d gradient components.

9.99.1 Detailed Description

Namespace of linear image processing routines.

9.99.2 Function Documentation

9.99.2.1 template<typename I > mln::trait::concrete< I >::ret mln::linear::gaussian (const **Image**< I > & *input*, float *sigma*) [inline]

Gaussian filter of an image *input*.

Precondition

output.domain = input.domain

Apply an approximated gaussian filter of *sigma* on *input*. This filter is applied in all the input image direction.

Precondition

input.is_valid

Definition at line 750 of file gaussian.hh.

References *mln::initialize()*.

Referenced by *mln::subsampling::gaussian_subsampling()*.

9.99.2.2 template<typename I> mln::trait::concrete< I >::ret mln::linear::gaussian (const Image< I > & input, float sigma, int dir) [inline]

Apply an approximated gaussian filter of `sigma` on `input`. on a specific direction `dir` if `dir = 0`, the filter is applied on the first image dimension. if `dir = 1`, the filter is applied on the second image dimension. And so on...

Precondition

```
input.is_valid
dir < dimension(input)
```

Definition at line 653 of file gaussian.hh.

References mln::initialize().

9.99.2.3 template<typename I> mln::trait::concrete< I >::ret mln::linear::gaussian_1st_derivative (const Image< I > & input, float sigma) [inline]

Apply an approximated first derivative gaussian filter of `sigma` on `input` This filter is applied in all the input image direction.

Precondition

```
input.is_valid
```

Definition at line 779 of file gaussian.hh.

References mln::initialize().

9.99.2.4 template<typename I> mln::trait::concrete< I >::ret mln::linear::gaussian_1st_derivative (const Image< I > & input, float sigma, int dir) [inline]

Apply an approximated first derivative gaussian filter of `sigma` on `input`. on a specific direction `dir` if `dir = 0`, the filter is applied on the first image dimension. if `dir = 1`, the filter is applied on the second image dimension. And so on...

Precondition

```
input.is_valid
dir < dimension(input)
```

Definition at line 685 of file gaussian.hh.

References mln::initialize().

9.99.2.5 template<typename I> mln::trait::concrete< I >::ret mln::linear::gaussian_2nd_derivative (const Image< I > & input, float sigma, int dir) [inline]

Apply an approximated second derivative gaussian filter of `sigma` on `input`. on a specific direction `dir` if `dir = 0`, the filter is applied on the first image dimension. if `dir = 1`, the filter is applied on the second image dimension. And so on...

Precondition

```
input.is_valid
dir < dimension(input)
```

Definition at line 718 of file gaussian.hh.

References mln::initialize().

9.99.2.6 template<typename I> mln::linear::mln_ch_convolve (I, int) const [inline]

Sobel_2d gradient components.

Compute the L1 norm of the 2D Sobel gradient.

Compute the vertical component of the 2D Sobel gradient.

Compute the horizontal component of the 2D Sobel gradient.

Definition at line 142 of file sobel_2d.hh.

References mln_ch_convolve(), mln_ch_convolve_grad(), and mln::data::transform().

**9.99.2.7 template<typename I, typename W, unsigned Sh, unsigned Sv>
 mln::linear::mln_ch_convolve (I, W) const**

Convolution of an image `input` by two weighted line-shapes windows.

Warning

The weighted window is used as-is, considering that its symmetrization is handled by the client.

Precondition

```
input.is_valid
```

9.99.2.8 template<typename I, typename W> mln::linear::mln_ch_convolve (I, W) const

Convolution of an image `input` by the weighted window `w_win`.

Warning

Computation of `output` (`p`) is performed with the value type of `output`.

The weighted window is used as-is, considering that its symmetrization is handled by the client.

Precondition

```
input.is_valid
```

Referenced by mln_ch_convolve(), and mln_ch_convolve_grad().

**9.99.2.9 template<typename I, typename W, unsigned S> mln::linear::mln_ch_convolve (I, W
) const [inline]**

Convolution of an image `input` by a line-shaped (directional) weighted window defined by the array of weights.

Warning

Computation of `output` (`p`) is performed with the value type of `output`.
The weighted window is used as-is, considering that its symmetrization is handled by the client.

Precondition

`input.is_valid`

9.99.2.10 template<typename I> mln::linear::mln_ch_convolve_grad (I, int) const

Compute the vertical component of the 2D Sobel gradient.

Definition at line 124 of file `sobel_2d.hh`.

References `mln_ch_convolve()`, and `mln::data::transform()`.

Referenced by `mln_ch_convolve()`.

9.100 mln::linear::impl Namespace Reference

Namespace of linear image processing routines implementation details.

9.100.1 Detailed Description

Namespace of linear image processing routines implementation details.

9.101 mln::linear::local Namespace Reference

Specializations of local linear routines.

Namespaces

- namespace `impl`
Namespace of local linear routines implementation details.

Functions

- template<typename I, typename P, typename W, typename R>
`void convolve (const Image< I > &input, const Site< P > &p, const Weighted_Window< W > &w_win, R &result)`
- template<typename P, typename W, typename R>
`void convolve (const Generalized_Pixel< P > &p, const Weighted_Window< W > &w_win, R &result)`

9.101.1 Detailed Description

Specializations of local linear routines.

9.101.2 Function Documentation

**9.101.2.1 template<typename I , typename P , typename W , typename R > void
mln::linear::local::convolve (const Image< I > & *input*, const Site< P > & *p*, const
Weighted_Window< W > & *w_win*, R & *result*) [inline]**

Local convolution of image *input* at point *p* by the weighted window *w_win*.

Warning

Computation of the *result* is performed with the type *R*.

The weighted window is used as-is, considering that its symmetrization is handled by the client.

Definition at line 149 of file linear/local/convolve.hh.

Referenced by convolve().

**9.101.2.2 template<typename P , typename W , typename R > void mln::linear::local::convolve (const Generalized_Pixel< P > & *p*, const Weighted_Window< W > & *w_win*, R &
result) [inline]**

Local convolution around (generalized) pixel by the weighted window *w_win*.

Warning

Computation of the *result* is performed with the type *R*.

The weighted window is used as-is, considering that its symmetrization is handled by the client.

Definition at line 161 of file linear/local/convolve.hh.

References convolve().

9.102 mln::linear::local::impl Namespace Reference

Namespace of local linear routines implementation details.

9.102.1 Detailed Description

Namespace of local linear routines implementation details.

9.103 mln::literal Namespace Reference

Namespace of literals.

Classes

- struct [black_t](#)
Type of literal black.

- struct [blue_t](#)
Type of literal blue.
- struct [brown_t](#)
Type of literal brown.
- struct [cyan_t](#)
Type of literal cyan.
- struct [green_t](#)
Type of literal green.
- struct [identity_t](#)
Type of literal identity.
- struct [light_gray_t](#)
Type of literal grays.
- struct [lime_t](#)
Type of literal lime.
- struct [magenta_t](#)
Type of literal magenta.
- struct [max_t](#)
Type of literal max.
- struct [min_t](#)
Type of literal min.
- struct [olive_t](#)
Type of literal olive.
- struct [one_t](#)
Type of literal one.
- struct [orange_t](#)
Type of literal orange.
- struct [origin_t](#)
Type of literal origin.
- struct [pink_t](#)
Type of literal pink.
- struct [purple_t](#)
Type of literal purple.
- struct [red_t](#)
Type of literal red.

- struct `teal_t`
Type of literal teal.
- struct `violet_t`
Type of literal violet.
- struct `white_t`
Type of literal white.
- struct `yellow_t`
Type of literal yellow.
- struct `zero_t`
Type of literal zero.

Variables

- const `black_t` & `black` = `black_t()`
Literal black.
- const `blue_t` & `blue` = `blue_t()`
Literal blue.
- const `brown_t` & `brown` = `brown_t()`
Literal brown.
- const `cyan_t` & `cyan` = `cyan_t()`
Literal cyan.
- const `dark_gray_t` & `dark_gray` = `dark_gray_t()`
Literal dark gray.
- const `green_t` & `green` = `green_t()`
Literal green.
- const `identity_t` & `identity` = `identity_t()`
Literal identity.
- const `light_gray_t` & `light_gray` = `light_gray_t()`
Literal light gray.
- const `lime_t` & `lime` = `lime_t()`
Literal lime.
- const `magenta_t` & `magenta` = `magenta_t()`
Literal magenta.

- const `max_t` & `max = max_t()`
Literal `max`.
- const `medium_gray_t` & `medium_gray = medium_gray_t()`
Literal `medium_gray`.
- const `min_t` & `min = min_t()`
Literal `min`.
- const `olive_t` & `olive = olive_t()`
Literal `olive`.
- const `one_t` & `one = one_t()`
Literal `one`.
- const `orange_t` & `orange = orange_t()`
Literal `orange`.
- const `origin_t` & `origin = origin_t()`
Literal `origin`.
- const `pink_t` & `pink = pink_t()`
Literal `pink`.
- const `purple_t` & `purple = purple_t()`
Literal `purple`.
- const `red_t` & `red = red_t()`
Literal `red`.
- const `teal_t` & `teal = teal_t()`
Literal `teal`.
- const `violet_t` & `violet = violet_t()`
Literal `violet`.
- const `white_t` & `white = white_t()`
Literal `white`.
- const `yellow_t` & `yellow = yellow_t()`
Literal `yellow`.
- const `zero_t` & `zero = zero_t()`
Literal `zero`.

9.103.1 Detailed Description

Namespace of literals.

9.103.2 Variable Documentation

9.103.2.1 const black_t & mln::literal::black = black_t()

Literal black.

Definition at line 60 of file black.hh.

Referenced by mln::labeling::colorize(), and mln::registration::icp().

9.103.2.2 const blue_t & mln::literal::blue = blue_t()

Literal blue.

Definition at line 162 of file colors.hh.

9.103.2.3 const brown_t & mln::literal::brown = brown_t()

Literal brown.

Definition at line 164 of file colors.hh.

9.103.2.4 const cyan_t & mln::literal::cyan = cyan_t()

Literal cyan.

Definition at line 178 of file colors.hh.

9.103.2.5 const dark_gray_t & mln::literal::dark_gray = dark_gray_t()

Literal dark gray.

Definition at line 70 of file grays.hh.

9.103.2.6 const green_t & mln::literal::green = green_t()

Literal green.

Definition at line 160 of file colors.hh.

Referenced by mln::registration::icp(), and mln::make_debug_graph_image().

9.103.2.7 const identity_t & mln::literal::identity = identity_t()

Literal identity.

Definition at line 54 of file identity.hh.

9.103.2.8 const light_gray_t & mln::literal::light_gray = light_gray_t()

Literal light gray.

Definition at line 66 of file grays.hh.

9.103.2.9 const lime_t & mln::literal::lime = lime_t()

[Literal](#) lime.

Definition at line 166 of file colors.hh.

9.103.2.10 const magenta_t & mln::literal::magenta = magenta_t()

[Literal](#) magenta.

Definition at line 180 of file colors.hh.

9.103.2.11 const max_t & mln::literal::max = max_t()

[Literal](#) max.

Definition at line 66 of file literal/max.hh.

9.103.2.12 const medium_gray_t & mln::literal::medium_gray = medium_gray_t()

[Literal](#) medium_gray.

Definition at line 68 of file grays.hh.

9.103.2.13 const min_t & mln::literal::min = min_t()

[Literal](#) min.

Definition at line 66 of file literal/min.hh.

9.103.2.14 const olive_t & mln::literal::olive = olive_t()

[Literal](#) olive.

Definition at line 184 of file colors.hh.

9.103.2.15 const one_t & mln::literal::one = one_t()

[Literal](#) one.

Definition at line 69 of file one.hh.

Referenced by mln::algebra::h_vec< d, C >::h_vec(), mln::operator++(), and mln::operator--().

9.103.2.16 const orange_t & mln::literal::orange = orange_t()

[Literal](#) orange.

Definition at line 168 of file colors.hh.

9.103.2.17 const origin_t & mln::literal::origin = origin_t()

[Literal](#) origin.

Definition at line 55 of file origin.hh.

Referenced by mln::win::ball< G, C >::ball(), mln::geom::bbox(), mln::box< P >::box(), mln::geom::rotate(), and mln::make::w_window().

9.103.2.18 const pink_t & mln::literal::pink = pink_t()

[Literal](#) pink.

Definition at line 170 of file colors.hh.

9.103.2.19 const purple_t & mln::literal::purple = purple_t()

[Literal](#) purple.

Definition at line 172 of file colors.hh.

9.103.2.20 const red_t & mln::literal::red = red_t()

[Literal](#) red.

Definition at line 158 of file colors.hh.

Referenced by mln::morpho::watershed::superpose(), and mln::debug::superpose().

9.103.2.21 const teal_t & mln::literal::teal = teal_t()

[Literal](#) teal.

Definition at line 174 of file colors.hh.

9.103.2.22 const violet_t & mln::literal::violet = violet_t()

[Literal](#) violet.

Definition at line 176 of file colors.hh.

9.103.2.23 const white_t & mln::literal::white = white_t()

[Literal](#) white.

Definition at line 60 of file white.hh.

Referenced by mln::registration::icp().

9.103.2.24 const yellow_t & mln::literal::yellow = yellow_t()

[Literal](#) yellow.

Definition at line 182 of file colors.hh.

9.103.2.25 const zero_t & mln::literal::zero = zero_t()

Literal zero.

Definition at line 69 of file zero.hh.

Referenced by mln::transform::influence_zone_geodesic_saturated(), mln::accu::shape::volume< I >::init(), mln::accu::stat::variance< T, S, R >::init(), mln::morpho::attribute::sum< I, S >::init(), mln::accu::math::sum< T, S >::init(), mln::accu::rms< T, V >::init(), mln::accu::stat::histo3d_rgb< V >::init(), mln::accu::convolve< T1, T2, R >::init(), mln::accu::center< P, V >::init(), mln::window< D >::is_centered(), mln::accu::stat::variance< T, S, R >::mean(), mln::accu::stat::var< T >::mean(), mln::geom::mesh_corner_point_area(), mln::geom::mesh_curvature(), mln::geom::mesh_normal(), mln::morpho::meyer_wst(), mln::algebra::operator*(), mln::test::positive(), mln::make::relabelfun(), mln::geom::rotate(), mln::accu::shape::volume< I >::set_value(), mln::morpho::watershed::superpose(), mln::labeling::superpose(), mln::debug::superpose(), mln::accu::stat::var< T >::to_result(), mln::geom::translate(), and mln::make::w_window_directional().

9.104 mln::logical Namespace Reference

Namespace of logic.

Namespaces

- namespace **impl**

Implementation namespace of logical namespace.

Functions

- template<typename L , typename R >
void **and_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)
- template<typename L , typename R >
mln::trait::ch_value< L, typename mln::fun::vv2v::land_not< typename L::value, typename R::value >::result >::ret **and_not** (const **Image**< L > &lhs, const **Image**< R > &rhs)
- template<typename L , typename R >
void **and_not_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)
- template<typename I >
void **not_inplace** (**Image**< I > &input)
- template<typename L , typename R >
void **or_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)
- template<typename L , typename R >
void **xor_inplace** (**Image**< L > &lhs, const **Image**< R > &rhs)

9.104.1 Detailed Description

Namespace of logic.

9.104.2 Function Documentation

9.104.2.1 template<typename L , typename R > void mln::logical::and_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise in-place "logical and" of image `rhs` in image `lhs`.

Parameters

[in, out] `lhs` First operand image.

[in] `rhs` Second operand image.

It performs:

for all p of `rhs.domain`

`lhs(p) = lhs(p) and rhs(p)`

Precondition

`rhs.domain >= lhs.domain`

Definition at line 91 of file logical/and.hh.

References mln::data::transform_inplace().

9.104.2.2 template<typename L , typename R > mln::trait::ch_value< L, typename mln::fun::vv2v::land_not< typename L::value, typename R::value >::result >::ret mln::logical::and_not (const Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise "logical and-not" between images `lhs` and `rhs`.

Parameters

[in] `lhs` First operand image.

[in] `rhs` Second operand image.

Returns

The result image.

Precondition

`lhs.domain == rhs.domain`

Definition at line 76 of file and_not.hh.

References mln::data::transform().

9.104.2.3 template<typename L , typename R > void mln::logical::and_not_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise in-place "logical and-not" of image `rhs` in image `lhs`.

Parameters

- [in, out] ***lhs*** First operand image.
- [in] ***rhs*** Second operand image.

It performs:

for all p of rhs.domain

$$\text{lhs}(p) = \text{lhs}(p) \text{ and not rhs}(p)$$

Precondition

`rhs.domain >= lhs.domain`

Definition at line 91 of file and_not.hh.

References mln::data::transform_inplace().

9.104.2.4 template<typename I> void mln::logical::not_inplace (Image< I > & *input*) [inline]

Point-wise in-place "logical not" of image *input*.

Parameters

- [in, out] ***input*** The target image.

It performs:

for all p of input.domain

$$\text{input}(p) = \text{not input}(p)$$

Precondition

`input.is_valid`

Definition at line 88 of file logical/not.hh.

References mln::data::transform_inplace().

9.104.2.5 template<typename L, typename R> void mln::logical::or_inplace (Image< L > & *lhs*, const Image< R > & *rhs*) [inline]

Point-wise in-place "logical or" of image *rhs* in image *lhs*.

Parameters

- [in, out] ***lhs*** First operand image.
- [in] ***rhs*** Second operand image.

It performs:

for all p of rhs.domain

$$\text{lhs}(p) = \text{lhs}(p) \text{ or rhs}(p)$$

Precondition

```
rhs.domain >= lhs.domain
```

Definition at line 91 of file logical/or.hh.

References mln::data::transform_inplace().

9.104.2.6 template<typename L , typename R > void mln::logical::xor_inplace (Image< L > & lhs, const Image< R > & rhs) [inline]

Point-wise in-place "logical xor" of image `rhs` in image `lhs`.

Parameters

[in, out] ***lhs*** First operand image.

[in] ***rhs*** Second operand image.

It performs:

for all p of `rhs.domain`

$$\text{lhs}(p) = \text{lhs}(p) \text{ xor } \text{rhs}(p)$$

Precondition

```
rhs.domain >= lhs.domain
```

Definition at line 91 of file logical/xor.hh.

References mln::data::transform_inplace().

9.105 mln::logical::impl Namespace Reference

Implementation namespace of logical namespace.

Namespaces

- namespace **generic**

Generic implementation namespace of logical namespace.

9.105.1 Detailed Description

Implementation namespace of logical namespace.

9.106 mln::logical::impl::generic Namespace Reference

Generic implementation namespace of logical namespace.

9.106.1 Detailed Description

Generic implementation namespace of logical namespace.

9.107 mln::make Namespace Reference

Namespace of routines that help to make Milena's objects.

Functions

- template<unsigned D, typename G , typename V >
`p_set< complex_psit< D, G >> attachment` (const `complex_psit< D, G >` &f, const `complex_-image< D, G, V >` &ima)
Compute the attachment of the cell corresponding to the facet f to the image ima.
- `mln::box1d box1d` (`def::coord` min_ind, `def::coord` max_ind)
Create an `mln::box1d`.
- `mln::box1d box1d` (unsigned ninds)
Create an `mln::box1d`.
- `mln::box2d box2d` (unsigned nrows, unsigned ncols)
Create an `mln::box2d`.
- `mln::box2d box2d` (`def::coord` min_row, `def::coord` min_col, `def::coord` max_row, `def::coord` max_col)
Create an `mln::box2d`.
- `mln::box2d_h box2d_h` (`def::coord` min_row, `def::coord` min_col, `def::coord` max_row, `def::coord` max_col)
Create an `mln::box2d_h`.
- `mln::box2d_h box2d_h` (unsigned nrows, unsigned ncols)
Create an `mln::box2d_h`.
- `mln::box3d box3d` (unsigned nslis, unsigned nrows, unsigned ncols)
Create an `mln::box3d`.
- `mln::box3d box3d` (`def::coord` min_sli, `def::coord` min_row, `def::coord` min_col, `def::coord` max_sli, `def::coord` max_row, `def::coord` max_col)
Create an `mln::box3d`.
- template<unsigned D, typename G >
`p_set< complex_psit< D, G >> cell` (const `complex_psit< D, G >` &f)
Compute the set of faces of the cell corresponding to the facet f.
- template<typename T , typename U >
`util::couple< T, U > couple` (const T &val1, const T &val2)
Construct an `mln::util::couple` on-the-fly.

- template<unsigned D, typename G , typename V >
`p_set< complex_psit< D, G >> detachment` (const `complex_psit< D, G >` &f, const `complex_-image< D, G, V >` &ima)
Compute the detachment of the cell corresponding to the facet f to the image ima.
- `mln::dpoint2d_h dpoint2d_h` (`def::coord` row, `def::coord` col)
Create an `mln::dpoint2d_h`.
- template<typename G , typename P >
`p_edges< G, pw::cst_< P >> dummy_p_edges` (const `Graph< G >` &g_, const P &dummy_site)
Create a `p_edges` which associate a graph element to a constant site.
- template<typename G >
`p_edges< G > dummy_p_edges` (const `Graph< G >` &g)
Create a `p_edges` which associate a graph element to a constant site.
- template<typename G , typename P >
`p_vertices< G, pw::cst_< P >> dummy_p_vertices` (const `Graph< G >` &g_, const P &dummy_site)
Create a `p_vertices` which associate a graph element to a constant site.
- template<typename G >
`p_vertices< G > dummy_p_vertices` (const `Graph< G >` &g)
Create a `p_vertices` which associate a graph element to a constant site.
- template<typename V , typename G >
`mln::edge_image< void, V, G > edge_image` (const `Graph< G >` &g, const `fun::i2v::array< V >` &fv)
Construct an edge image.
- template<typename FV , typename G >
`mln::edge_image< void, typename FV::result, G > edge_image` (const `Graph< G >` &g, const `Function_v2v< FV >` &fv)
Construct an edge image.
- template<typename FP , typename FV , typename G >
`mln::edge_image< typename FP::result, typename FV::result, G > edge_image` (const `Graph< G >` &g_, const `Function_v2v< FP >` &fp, const `Function_v2v< FV >` &fv)
Construct an edge image.
- template<typename P , typename V , typename G , typename FP , typename FV >
`mln::edge_image< typename FP::result, typename FV::result, G > edge_image` (const `mln::vertex_-image< P, V, G >` &v_imma_, const `p_edges< G, FP >` pe, const `Function_vv2v< FV >` &fv_)
Construct an edge image.
- template<typename P , typename V , typename G , typename FV >
`mln::edge_image< void, typename FV::result, G > edge_image` (const `mln::vertex_image< P, V, G >` &v_imma_, const `Function_vv2v< FV >` &fv_)
Construct an edge image.

- template<typename P , typename V , typename G , typename F >
`mln::edge_image< void, bool, G > edge_image` (const `mln::vertex_image< P, V, G >` &v_im_, const `Function_v2b< F >` &fv_)

Construct an edge image.

- template<typename T , unsigned N>
`algebra::h_mat< mlc_sqrt_int(N), T > h_mat` (const `T(&tab)[N]`)

Create an `mln::algebra::mat<n,n,T>`.

- template<typename V , unsigned L>
`mln::image1d< V > image` (`V(&values)[L]`)

Create an `image1d` from an 1D array of values.

- template<typename V , unsigned R, unsigned C>
`mln::image2d< V > image` (`V(&values)[R][C]`)

Create an `image2d` from an 2D array of values.

- template<typename V , unsigned S, unsigned R, unsigned C>
`mln::image3d< V > image` (`V(&values)[S][R][C]`)

Create an `image3d` from an 3D array of values.

- template<typename V , unsigned S>
`mln::image2d< V > image2d` (`V(&values)[S]`)

Create an `image2d` from an 2D array of values.

- template<typename I >
`mln::image3d< typename I::value > image3d` (const `Image< I >` &ima)

Create an `image3d` from a 2D image.

- template<typename I >
`mln::image3d< typename I::value > image3d` (const `util::array< I >` &ima)

Create an `image3d` from an array of 2D images.

- template<typename I , typename N >
`util::graph influence_zone_adjacency_graph` (const `Image< I >` &iz_, const `Neighborhood< N >` &nbh, const typename I::value &nlabels)

Create a graph from an influence zone image.

- template<unsigned n, unsigned m, typename T >
`algebra::mat< n, m, T > mat` (const `T(&tab)[n *m]`)

Create an `mln::algebra::mat<n,m,T>`.

- template<typename T >
`util::ord_pair< T > ord_pair` (const `T &val1, const T &val2`)

Construct an `mln::util::ord_pair` on-the-fly.

- template<typename W , typename G >
`p_edges< G, fun::i2v::array< util::site_pair< typename W::site > >> p_edges_with_mass_centers` (const `Image< W >` &wst_, const `Graph< G >` &g_)

Construct a `p_edges` from a watershed image and a region adjacency graph (RAG).

- template<typename W , typename G >
`p_vertices< G, fun::i2v::array< typename W::site > >` `p_vertices_with_mass_centers` (const `Image< W >` &wst_, const `Graph< G >` &g_)
Construct a `p_vertices` from a watershed image and a region adjacency graph (RAG).

- template<typename I >
`mln::util::pix< I >` `pix` (const `Image< I >` &ima, const typename I::psite &p)
Create an `mln::util::pix` from an image `ima` and a psite `p`.

- template<typename I >
`mln::pixel< I >` `pixel` (`Image< I >` &ima, const typename I::psite &p)
Create a `mln::pixel` from a mutable image `ima` and a point `p`.

- template<typename I >
`mln::pixel< const I >` `pixel` (const `Image< I >` &ima, const typename I::psite &p)
Create a `mln::pixel` from a constant image `ima` and a point `p`.

- `mln::point2d_h` `point2d_h` (def::coord row, def::coord col)
Create an `mln::point2d_h`.

- template<typename I , typename N >
`util::couple< util::graph, typename mln::trait::concrete< I >::ret >` `rag_and_labeled_wsl` (const `Image< I >` &wshd_, const `Neighborhood< N >` &nbh_, const typename I::value &nbasins)
Create a region adjacency graph and a label image of the watershed line from a watershed image.

- template<typename I , typename N >
`util::graph` `region_adjacency_graph` (const `Image< I >` &wshd_, const `Neighborhood< N >` &nbh, const typename I::value &nbasins)
Create a region adjacency graph from a watershed image.

- template<typename V , typename F >
`fun::i2v::array< V >` `relabelfun` (const `Function_v2b< F >` &fv2b, const V &nlabels, V &new_nlabels)
Create a i2v function from a v2b function.

- template<typename V , typename F >
`fun::i2v::array< V >` `relabelfun` (const `Function_v2v< F >` &fv2v, const V &nlabels, V &new_nlabels)
Create a i2v function from a v2v function.

- template<typename T >
`algebra::vec< 1, T >` `vec` (const T &v_0)
Create an `mln::algebra::vec<n,T>`.

- template<typename T >
`algebra::vec< 4, T >` `vec` (const T &v_0, const T &v_1, const T &v_2, const T &v_3)
Create an `mln::algebra::vec<4,T>`.

- template<typename T >
`algebra::vec< 3, T >` `vec` (const T &v_0, const T &v_1, const T &v_2)
Create an `mln::algebra::vec<3,T>`.

- template<typename T >
`algebra::vec< 2, T > vec` (const T &v_0, const T &v_1)
Create an `mln::algebra::vec<2,T>`.
- template<typename G , typename FV >
`mln::vertex_image< void, typename FV::result, G > vertex_image` (const `Graph< G > &g`, const `Function_v2v< FV > &fv`)
Construct a vertex image.
- template<typename FP , typename FV , typename G >
`mln::vertex_image< typename FP::result, typename FV::result, G > vertex_image` (const `Graph< G > &g`, const `Function_v2v< FP > &fp`, const `Function_v2v< FV > &fv`)
Construct a vertex image.
- template<typename I , typename N >
`p_vertices< util::graph, fun::i2v::array< typename I::site > > voronoi` (`Image< I > &ima_`, `Image< I > &orig_`, const `Neighborhood< N > &nbh`)
Apply the Voronoi algorithm on `ima_` with the original image `orig_` for node computing with neighborhood `nbh`.
- template<typename W , typename F >
`mln::w_window< typename W::dpsite, typename F::result > w_window` (const `Window< W > &win`, const `Function_v2v< F > &wei`)
Create a `mln::w_window` from a window and a weight function.
- template<typename W , unsigned M>
`mln::w_window< mln::dpoint1d, W > w_window1d` (`W(&weights)[M]`)
Create a 1D `mln::w_window` from an array of weights.
- template<unsigned M>
`mln::w_window1d_int w_window1d_int` (`int(&weights)[M]`)
Create a `mln::w_window1d_int`.
- template<typename W , unsigned S>
`mln::w_window< mln::dpoint2d, W > w_window2d` (`W(&weights)[S]`)
Create a 2D `mln::w_window` from an array of weights.
- template<unsigned M>
`mln::w_window2d_int w_window2d_int` (`int(&weights)[M]`)
Create a `mln::w_window2d_int`.
- template<typename W , unsigned M>
`mln::w_window< mln::dpoint3d, W > w_window3d` (`W(&weights)[M]`)
Create a 3D `mln::w_window` from an array of weights.
- template<unsigned M>
`mln::w_window3d_int w_window3d_int` (`int(&weights)[M]`)
Create a `mln::w_window3d_int`.

- template<typename D , typename W , unsigned L>
`mln::w_window< D, W > w_window_directional (const Gdpoint< D > &dp, W(&weights)[L])`
Create a directional centered weighted window.

9.107.1 Detailed Description

Namespace of routines that help to make Milena's objects.

9.107.2 Function Documentation

- 9.107.2.1 template<unsigned D, typename G , typename V > p_set< complex_psite< D, G > >**
mln::make::attachment (const complex_psite< D, G > & f, const complex_image< D,
G, V > & ima) [inline]

Compute the attachment of the cell corresponding to the facet *f* to the image *ima*.

Precondition

f is a facet (it does not belong to any face of higher dimension).
ima is an image of Boolean values.

Returns

a set of faces containing the attachment.

We do not use the formal definition of the attachment here (see *couprie.08.pami*). We use the following (equivalent) definition: an N-face F in CELL is in the attachment of CELL to IMA if it is adjacent to at least an (N-1)-face or an (N+1)-face that does not belong to CELL.

Definition at line 68 of file attachment.hh.

References `cell()`, and `mln::topo::is_facet()`.

Referenced by `mln::topo::is_simple_cell< I >::operator()()`.

- 9.107.2.2 mln::box1d mln::make::box1d (def::coord min_ind, def::coord max_ind)**
[inline]

Create an `mln::box1d`.

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

[in] ***min_ind*** Minimum index.
 [in] ***max_ind*** Maximum index.

Precondition

`max_ind >= min_ind`.

Returns

A 1D box.

Definition at line 79 of file make/box1d.hh.

References box1d().

9.107.2.3 `mln::box1d mln::make::box1d (unsigned ninds) [inline]`

Create an [mln::box1d](#).

Parameters

[in] *ninds* Number of indices.

Precondition

ninds != 0 and *ncols* != 0.

Returns

A 1D box.

Definition at line 70 of file make/box1d.hh.

Referenced by box1d(), and [mln::image1d< T >::image1d\(\)](#).

9.107.2.4 `mln::box2d mln::make::box2d (unsigned nrows, unsigned ncols) [inline]`

Create an [mln::box2d](#).

Parameters

[in] *nrows* Number of rows.

[in] *ncols* Number of columns.

Precondition

nrows != 0 and *ncols* != 0.

Returns

A 2D box.

Definition at line 78 of file make/box2d.hh.

Referenced by [mln::image2d< T >::image2d\(\)](#), and [mln::io::pnm::load\(\)](#).

9.107.2.5 `mln::box2d mln::make::box2d (def::coord min_row, def::coord min_col, def::coord max_row, def::coord max_col) [inline]`

Create an [mln::box2d](#).

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

[in] *min_row* Index of the top most row.

[in] ***min_col*** Index of the left most column.
[in] ***max_row*** Index of the bottom most row.
[in] ***max_col*** Index of the right most column.

Precondition

`max_row >= min_row and max_col >= min_col.`

Returns

A 2D box.

Definition at line 88 of file make/box2d.hh.

9.107.2.6 `mln::box2d_h mln::make::box2d_h (def::coord min_row, def::coord min_col, def::coord max_row, def::coord max_col) [inline]`

Create an [mln::box2d_h](#).

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

[in] ***min_row*** Index of the top most row.
[in] ***min_col*** Index of the left most column.
[in] ***max_row*** Index of the bottom most row.
[in] ***max_col*** Index of the right most column.

Precondition

`max_row >= min_row and max_col >= min_col.`

Returns

A 2D_H box.

Definition at line 85 of file make/box2d_h.hh.

References [point2d_h\(\)](#).

9.107.2.7 `mln::box2d_h mln::make::box2d_h (unsigned nrows, unsigned ncols) [inline]`

Create an [mln::box2d_h](#).

Parameters

[in] ***nrows*** Number of rows.
[in] ***ncols*** Number of columns.

Precondition

`nrows != 0 and ncols != 0.`

Returns

A 2D_H box.

Definition at line 75 of file make/box2d_h.hh.

References point2d_h().

9.107.2.8 mln::box3d mln::make::box3d (**unsigned nslis, unsigned nrows, unsigned ncols) [inline]**

Create an [mln::box3d](#).

Parameters

[in] **nslis** Number of slices.

[in] **nrows** Number of rows.

[in] **ncols** Number of columns.

Precondition

`ninds != 0 and ncols != 0 and nslis != 0`.

Returns

A 3D box.

Definition at line 80 of file make/box3d.hh.

Referenced by `image3d()`, and `mln::image3d< T >::image3d()`.

9.107.2.9 mln::box3d mln::make::box3d (**def::coord min_sli, def::coord min_row, def::coord min_col, def::coord max_sli, def::coord max_row, def::coord max_col) [inline]**

Create an [mln::box3d](#).

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

[in] **min_sli** Index of the lowest slice.

[in] **min_row** Index of the top most row.

[in] **min_col** Index of the left most column.

[in] **max_sli** Index of the highest slice.

[in] **max_row** Index of the bottom most row.

[in] **max_col** Index of the right most column.

Precondition

`max_sli >= min_sli.`

`max_row >= min_row.`

`max_col >= min_col.`

Returns

A 3D box.

Definition at line 92 of file make/box3d.hh.

**9.107.2.10 template<unsigned D, typename G> p_set< complex_psite< D, G > >
mln::make::cell (const complex_psite< D, G > & f) [inline]**

Compute the set of faces of the cell corresponding to the facet f .

Precondition

f is a facet (it does not belong to any face of higher dimension).

Returns

An [mln::p_set](#) of sites (faces) containing the attachment.

Definition at line 63 of file cell.hh.

References [mln::topo::is_facet\(\)](#), and [mln::complex_psite< D, G >::n\(\)](#).

Referenced by [attachment\(\)](#), and [detachment\(\)](#).

**9.107.2.11 template<typename T, typename U> util::couple<T,U> mln::make::couple (const
T & val1, const T & val2)**

Construct an [mln::util::couple](#) on-the-fly.

Referenced by [mln::labeling::blobs_and_compute\(\)](#), [mln::transform::distance_and_closest_point_geodesic\(\)](#), [mln::transform::distance_and_influence_zone_geodesic\(\)](#), and [mln::labeling::value_and_compute\(\)](#).

**9.107.2.12 template<unsigned D, typename G, typename V> p_set< complex_psite< D, G > >
mln::make::detachment (const complex_psite< D, G > & f, const complex_image<
D, G, V > & ima) [inline]**

Compute the detachment of the cell corresponding to the facet f to the image ima .

Precondition

f is a facet (it does not belong to any face of higher dimension).

ima is an image of Boolean values.

Returns

a set of faces containing the detachment.

We do not use the formal definition of the detachment here (see [couplie.08.pami](#)). We use the following (equivalent) definition: an N-face F in CELL is not in the detachment of CELL from IMA if it is adjacent to at least an (N-1)-face or an (N+1)-face that does not belong to CELL.

Definition at line 68 of file detachment.hh.

References [cell\(\)](#), and [mln::topo::is_facet\(\)](#).

Referenced by [mln::topo::detach\(\)](#).

**9.107.2.13 mln::dpoint2d_h mln::make::dpoint2d_h (def::coord row, def::coord col)
[inline]**

Create an [mln::dpoint2d_h](#).

Parameters

- [in] ***row*** Row coordinate.
- [in] ***col*** Column coordinate.

Returns

A 2D dpoint.

Definition at line 55 of file make/dpoint2d_h.hh.

9.107.2.14 template<typename G , typename P > p_edges< G, pw::cst_< P > >
mln::make::dummy_p_edges (const Graph< G > & g_, const P & dummy_site)

Create a [p_edges](#) which associate a graph element to a constant site.

Parameters

- [in] ***g_*** A graph.
- [in] ***dummy_site*** The dummy site mapped to graph edges.

Returns

A [p_edges](#).

Definition at line 77 of file dummy_p_edges.hh.

9.107.2.15 template<typename G > p_edges< G > mln::make::dummy_p_edges (const Graph< G > & g)

Create a [p_edges](#) which associate a graph element to a constant site.

0 (int) is used as dummy site.

Parameters

- [in] ***g*** A graph.

Returns

A [p_edges](#).

Definition at line 93 of file dummy_p_edges.hh.

9.107.2.16 template<typename G , typename P > p_vertices< G, pw::cst_< P > >
mln::make::dummy_p_vertices (const Graph< G > & g_, const P & dummy_site)

Create a [p_vertices](#) which associate a graph element to a constant site.

Parameters

- [in] ***g_*** A graph.
- [in] ***dummy_site*** The dummy site mapped to graph vertices.

Returns

A [p_vertices](#).

Definition at line 77 of file dummy_p_vertices.hh.

9.107.2.17 template<typename G> p_vertices< G > mln::make::dummy_p_vertices (const Graph< G > & g)

Create a [p_vertices](#) which associate a graph element to a constant site.

0 (int) is used as dummy site.

Parameters

[in] *g* A graph.

Returns

A [p_vertices](#).

Definition at line 93 of file dummy_p_vertices.hh.

9.107.2.18 template<typename V, typename G> mln::edge_image< void, V, G > mln::make::edge_image (const Graph< G > & g, const fun::i2v::array< V > & fv) [inline]

Construct an edge image.

Parameters

[in] *g* A graph.

[in] *fv* A function mapping edge ids to values.

Returns

an edge image.

Definition at line 141 of file make/edge_image.hh.

9.107.2.19 template<typename FV, typename G> mln::edge_image< void, typename FV::result, G > mln::make::edge_image (const Graph< G > & g, const Function_v2v< FV > & fv)

Construct an edge image.

Parameters

[in] *g* A graph.

[in] *fv* A function mapping edge ids to values.

Returns

an edge image.

Definition at line 155 of file make/edge_image.hh.

9.107.2.20 template<typename FP , typename FV , typename G > mln::edge_image< typename FP::result, typename FV::result, G > mln::make::edge_image (const Graph< G > & g_, const Function_v2v< FP > & fp, const Function_v2v< FV > & fv) [inline]

Construct an edge image.

Parameters

- [in] *g_* A graph.
- [in] *fp* A function mapping edge ids to sites.
- [in] *fv* A function mapping edge ids to values.

Returns

an edge image.

Definition at line 179 of file make/edge_image.hh.

9.107.2.21 template<typename P , typename V , typename G , typename FP , typename FV > mln::edge_image< typename FP::result, typename FV::result, G > mln::make::edge_image (const mln::vertex_image< P, V, G > & v_im_ , const p_edges< G, FP > pe, const Function_vv2v< FV > & fv_) [inline]

Construct an edge image.

Parameters

- [in] *v_im_* A vertex image.
- [in] *pe* A *p_edges* mapping graph elements to sites.
- [in] *fv_* A function mapping two vertex ids to a value. The result is associated to the corresponding edge.

Returns

an edge image.

Definition at line 199 of file make/edge_image.hh.

9.107.2.22 template<typename P , typename V , typename G , typename FV > mln::edge_image< void, typename FV::result, G > mln::make::edge_image (const mln::vertex_image< P, V, G > & v_im_ , const Function_vv2v< FV > & fv_) [inline]

Construct an edge image.

Parameters

- [in] *v_im_* A vertex image.
- [in] *fv_* A function mapping two vertices' values to a value. The result is associated to the corresponding edge.

Returns

an edge image without localization information mapped to graph elements.

Definition at line 225 of file make/edge_image.hh.

9.107.2.23 template<typename P , typename V , typename G , typename F > mln::edge_image< void, bool, G > mln::make::edge_image (const mln::vertex_image< P, V, G > & *v ima_*, const Function_v2b< F > & *fv_*) [inline]

Construct an edge image.

Parameters

- [in] *v ima_* A vertex image.
- [in] *fv_* A predicate on a vertex's value. The (Boolean) result is associated to the edges adjacent to the vertex.

Returns

an edge image without localization information mapped to graph elements.

Definition at line 250 of file make/edge_image.hh.

References mln::data::fill().

9.107.2.24 template<typename T , unsigned N> algebra::h_mat< mlc_sqrt_int(N), T > mln::make::h_mat (const T(&) *tab[N]*) [inline]

Create an mln::algebra::mat<n,n,T>.

Definition at line 60 of file make/h_mat.hh.

Referenced by mln::fun::x2x::rotation< n, C >::rotation().

9.107.2.25 template<typename V , unsigned L> mln::image1d< V > mln::make::image (V(&) *values[L]*)

Create an [image1d](#) from an 1D array of values.

Parameters

- [in] *values* 1D array.

Returns

A 1D image.

Definition at line 85 of file make/image.hh.

9.107.2.26 template<typename V , unsigned R, unsigned C> mln::image2d< V > mln::make::image (V(&) *values[R][C]*)

Create an [image2d](#) from an 2D array of values.

Parameters

- [in] *values* 2D array.

Returns

A 2D image.

Definition at line 97 of file make/image.hh.

References mln::opt::at().

9.107.2.27 template<typename V , unsigned S, unsigned R, unsigned C> mln::image3d< V > mln::make::image (V(&) values[S][R][C])

Create an [image3d](#) from an 3D array of values.

Parameters

[in] *values* 3D array.

Returns

A 3D image.

Definition at line 112 of file make/image.hh.

References mln::opt::at().

9.107.2.28 template<typename V , unsigned S> mln::image2d< V > mln::make::image2d (V(&) values[S])

Create an [image2d](#) from an 2D array of values.

Parameters

[in] *values* 2D array.

Returns

A 2D image.

Definition at line 61 of file make/image2d.hh.

9.107.2.29 template<typename I > mln::image3d< typename I::value > mln::make::image3d (const Image< I > & ima) [inline]

Create an [image3d](#) from a 2D image.

Definition at line 92 of file make/image3d.hh.

References box3d(), and mln::data::paste().

9.107.2.30 template<typename I > mln::image3d< typename I::value > mln::make::image3d (const util::array< I > & ima) [inline]

Create an [image3d](#) from an array of 2D images.

Definition at line 70 of file make/image3d.hh.

References box3d(), mln::util::array< T >::is_empty(), mln::util::array< T >::nelements(), mln::data::paste(), mln::box< P >::pmax(), and mln::box< P >::pmin().

Referenced by mln::io::pnms::load().

9.107.2.31 template<typename I , typename N > util::graph mln::make::influence_zone_- adjacency_graph (const Image< I > & iz_, const Neighborhood< N > & nbh, const typename I::value & nlabels) [inline]

Create a graph from an influence zone image.

Parameters

- [in] **iz** influence zone image.
- [in] **nbh** A neighborhood.
- [in] **nlabels** number of influence zone in **iz**.

Returns

[util::graph Graph](#) based on the adjacency of the influence zones.

Definition at line 175 of file influence_zone_adjacency_graph.hh.

9.107.2.32 template<unsigned n, unsigned m, typename T > algebra::mat< n, m, T > mln::make::mat (const T(&) tab[n *m]) [inline]

Create an [mln::algebra::mat<n,m,T>](#).

Parameters

- [in] **tab** Array of values.

Precondition

The array dimension has to be $n * m$.

Definition at line 61 of file make/mat.hh.

9.107.2.33 template<typename T > util::ord_pair< T > mln::make::ord_pair (const T & val1, const T & val2) [inline]

Construct an [mln::util::ord_pair](#) on-the-fly.

Definition at line 277 of file ord_pair.hh.

9.107.2.34 template<typename W , typename G > p_edges< G, fun::i2v::array< util::site_pair< typename W::site > >> mln::make::p_edges_with_mass_centers (const Image< W > & wst_, const Graph< G > & g_) [inline]

Construct a [p_edges](#) from a watershed image and a region adjacency graph (RAG).

Map each graph edge to a pair of mass centers of two adjacent regions.

Parameters

- wst_** A watershed image.
- g_** A region adjacency graph.

Returns

A [p_edges](#).

See also

[edge_image](#), [p_edges](#), [make::region_adjacency_graph](#)

Definition at line 81 of file `p_edges_with_mass_centers.hh`.

References `mln::labeling::compute()`.

9.107.2.35 template<typename W , typename G > p_vertices< G, fun::i2v::array< typename W::site > > mln::make::p_vertices_with_mass_centers (const Image< W > & wst_, const Graph< G > & g_) [inline]

Construct a [p_vertices](#) from a watershed image and a region adjacency graph (RAG).

Map each graph vertex to the mass center of its corresponding region.

Parameters

wst_ A watershed image.

g_ A region adjacency graph.

Returns

A [p_vertices](#).

See also

[edge_image](#), [vertex_image](#), [p_vertices](#), [p_edges](#), [make::region_adjacency_graph](#)

Definition at line 77 of file `p_vertices_with_mass_centers.hh`.

References `mln::labeling::compute()`.

9.107.2.36 template<typename I > mln::util::pix< I > mln::make::pix (const Image< I > & ima, const typename I::psite & p) [inline]

Create an [mln::util::pix](#) from an image `ima` and a psite `p`.

Parameters

[in] *ima* The input image.

[in] *p* The point site.

Returns

An [mln::util::pix](#).

Definition at line 58 of file `make/pix.hh`.

9.107.2.37 template<typename I > mln::pixel< I > mln::make::pixel (Image< I > & ima, const typename I::psite & p) [inline]

Create a [mln::pixel](#) from a mutable image `ima` and a point `p`.

Definition at line 63 of file `make/pixel.hh`.

9.107.2.38 template<typename I> mln::pixel< const I > mln::make::pixel (const Image< I > & ima, const typename I::psite & p) [inline]

Create a `mln::pixel` from a constant image `ima` and a point `p`.

Definition at line 55 of file `make/pixel.hh`.

9.107.2.39 mln::point2d_h mln::make::point2d_h (def::coord row, def::coord col) [inline]

Create an `mln::point2d_h`.

Parameters

[in] `row` Row coordinate.

[in] `col` Column coordinate.

Returns

A 2D point.

Definition at line 55 of file `make/point2d_h.hh`.

Referenced by `box2d_h()`.

9.107.2.40 template<typename I, typename N> util::couple< util::graph, typename mln::trait::concrete< I >::ret > mln::make::rag_and_labeled_wsl (const Image< I > & wshd_, const Neighborhood< N > & nbh_, const typename I::value & nbasins) [inline]

Create a region adjacency graph and a label image of the watershed line from a watershed image.

Parameters

[in] `wshd_` Watershed image.

[in] `nbh_` Neighborhood

[in] `nbasins` Number of influence zone in `wshd_`.

Returns

A couple. First element is the graph, second element is an image with a labeled watershed line.

<pre> ----- 1 1 1 0 2 2 0 3 1 1 0 2 2 2 0 3 1 0 4 0 2 0 3 3 0 4 4 4 0 5 0 3 ----- </pre>	<pre> ----- . . . 1 . . . 2 1 . . . 2 . . 1 . 3 . 4 . . 1 . . . 5 . 6 . ----- </pre>
--	--

Watershed image Labeled watershed line
(watershed line labeled with 0)

|
|
|
v

```

1 -- 2 - 3
 \ / /
4 -- 5

```

Region Adjacency graph (RAG)

Definition at line 229 of file rag_and_labeled_wsl.hh.

9.107.2.41 template<typename I , typename N > util::graph mln::make::region_adjacency_graph (const Image< I > & wshd_ , const Neighborhood< N > & nbh, const typename I::value & nbasins) [inline]

Create a region adjacency graph from a watershed image.

Parameters

- [in] **wshd_** watershed image.
- [in] **nbh** A neighborhood.
- [in] **nbasins** number of influence zone in wshd.

Returns

util::graph Graph based on the adjacency of the influence zones.

Definition at line 179 of file region_adjacency_graph.hh.

9.107.2.42 template<typename V , typename F > fun::i2v::array< V > mln::make::relabelfun (const Function_v2b< F > & fv2b, const V & nlabels, V & new_nlabels) [inline]

Create a i2v function from a v2b function.

This function can be used to relabel a labeled image.

Parameters

- [in] **fv2b** A v2b function.
- [in] **nlabels** The number of labels.
- [in] **new_nlabels** The number of labels after relabeling.

Returns

a i2v function.

See also

[mln::labeling::relabel](#)

Definition at line 83 of file relabelfun.hh.

References mln::literal::zero.

Referenced by mln::labeling::pack(), mln::labeling::pack_inplace(), mln::labeling::relabel(), mln::labeled_image_base< I, E >::relabel(), and mln::labeling::relabel_inplace().

9.107.2.43 template<typename V , typename F > fun::i2v::array< V > mln::make::relabelfun (const Function_v2v< F > & fv2v, const V & nlabels, V & new_nlabels) [inline]

Create a i2v function from a v2v function.

This function can be used to relabel a labeled image.

Parameters

- [in] *fv2v* A v2v function. This function maps an id to an already existing one.
- [in] *nlabels* The number of labels.
- [in] *new_nlabels* The number of labels after relabeling.

Returns

a i2v function.

See also

[mln::labeling::relabel](#)

Definition at line 106 of file relabelfun.hh.

References mln::literal::zero.

9.107.2.44 template<typename T > algebra::vec< 1, T > mln::make::vec (const T & v_0) [inline]

Create an mln::algebra::vec<n,T>.

Parameters

- [in] *v_0* First coordinate.

Returns

A 1D vector.

Definition at line 91 of file make/vec.hh.

9.107.2.45 template<typename T > algebra::vec< 4, T > mln::make::vec (const T & v_0, const T & v_1, const T & v_2, const T & v_3) [inline]

Create an mln::algebra::vec<4,T>.

Parameters

- [in] *v_0* First coordinate.
- [in] *v_1* Second coordinate.
- [in] *v_2* Third coordinate.
- [in] *v_3* Fourth coordinate.

Returns

A 4D vector.

Definition at line 121 of file make/vec.hh.

9.107.2.46 template<typename T> algebra::vec< 3, T > mln::make::vec (const T & *v_0*, const T & *v_1*, const T & *v_2*) [inline]

Create an mln::algebra::vec<3,T>.

Parameters

- [in] *v_0* First coordinate.
- [in] *v_1* Second coordinate.
- [in] *v_2* Third coordinate.

Returns

A 3D vector.

Definition at line 110 of file make/vec.hh.

9.107.2.47 template<typename T> algebra::vec< 2, T > mln::make::vec (const T & *v_0*, const T & *v_1*) [inline]

Create an mln::algebra::vec<2,T>.

Parameters

- [in] *v_0* First coordinate.
- [in] *v_1* Second coordinate.

Returns

A 2D vector.

Definition at line 100 of file make/vec.hh.

9.107.2.48 template<typename G, typename FV> mln::vertex_image< void, typename FV::result, G > mln::make::vertex_image (const Graph< G > & *g*, const Function_v2v< FV > & *fv*)

Construct a vertex image.

Parameters

- [in] *g* A graph.
- [in] *fv* A function mapping vertex ids to values.

Returns

A vertex image.

Definition at line 77 of file make/vertex_image.hh.

9.107.2.49 template<typename FP , typename FV , typename G > mln::vertex_image< typename FP::result, typename FV::result, G > mln::make::vertex_image (const Graph< G > & *g*_, const Function_v2v< FP > & *fp*, const Function_v2v< FV > & *fv*)

Construct a vertex image.

Parameters

- [in] *g*_ A graph.
- [in] *fp* A function mapping vertex ids to sites.
- [in] *fv* A function mapping vertex ids to values.

Returns

A vertex image.

Definition at line 92 of file make/vertex_image.hh.

9.107.2.50 template<typename I , typename N > p_vertices< util::graph, fun::i2v::array< typename I::site > > mln::make::voronoi (Image< I > & *ima*_, Image< I > & *orig*_, const Neighborhood< N > & *nbh*) [inline]

Apply the Voronoi algorithm on *ima*_ with the original image *orig*_ for node computing with neighborhood *nbh*.

Parameters

- [in] *ima*_ The labeling image.
- [in] *orig*_ The original image.
- [in] *nbh* The neighborhood for computing algorithm.

Returns

The computed graph.

Definition at line 68 of file voronoi.hh.

References mln::util::graph::add_edge(), mln::util::graph::add_vertex(), and mln::estim::min_max().

9.107.2.51 template<typename W , typename F > mln::w_window< typename W::dpsite, typename F::result > mln::make::w_window (const Window< W > & *win*, const Function_v2v< F > & *wei*) [inline]

Create a [mln::w_window](#) from a window and a weight function.

Parameters

- [in] *win* A simple window.
- [in] *wei* A weight function.

Returns

A weighted window.

Definition at line 63 of file make/w_window.hh.

References mln::w_window< D, W >::insert(), and mln::literal::origin.

**9.107.2.52 template<typename W , unsigned M> mln::w_window< mln::dpoint1d, W >
mln::make::w_window1d (W(&) weights[M]) [inline]**

Create a 1D [mln::w_window](#) from an array of weights.

Parameters

[in] **weights** Array.

Precondition

The array size, M, has to be a square of an odd integer.

Returns

A 1D weighted window.

Definition at line 63 of file w_window1d.hh.

References mln::w_window< D, W >::insert().

Referenced by w_window1d_int().

9.107.2.53 template<unsigned M> mln::w_window1d_int mln::make::w_window1d_int (int(&) weights[M]) [inline]

Create a [mln::w_window1d_int](#).

Parameters

[in] **weights** Array of integers.

Precondition

The array size, M, has to be a square of an odd integer.

Returns

A 1D int-weighted window.

Definition at line 61 of file make/w_window1d_int.hh.

References w_window1d().

**9.107.2.54 template<typename W , unsigned S> mln::w_window< mln::dpoint2d, W >
mln::make::w_window2d (W(&) weights[S]) [inline]**

Create a 2D [mln::w_window](#) from an array of weights.

Parameters

[in] **weights** Array.

Precondition

The array size, S, has to be a square of an odd integer.

Returns

A 2D weighted window.

Definition at line 62 of file w_window2d.hh.

Referenced by w_window2d_int().

9.107.2.55 template<unsigned M> mln::w_window2d_int mln::make::w_window2d_int (int(& weights[M])) [inline]

Create a [mln::w_window2d_int](#).

Parameters

[in] **weights** Array of integers.

Precondition

The array size, M, has to be a square of an odd integer.

Returns

A 2D int-weighted window.

Definition at line 61 of file make/w_window2d_int.hh.

References w_window2d().

9.107.2.56 template<typename W , unsigned M> mln::w_window< mln::dpoint3d, W > mln::make::w_window3d (W(&) weights[M]) [inline]

Create a 3D [mln::w_window](#) from an array of weights.

Parameters

[in] **weights** Array.

Precondition

The array size, M, has to be a cube of an odd integer.

Returns

A 3D weighted window.

Definition at line 64 of file w_window3d.hh.

References mln::w_window< D, W >::insert().

Referenced by w_window3d_int().

9.107.2.57 template<unsigned M> mln::w_window3d_int mln::make::w_window3d_int (int(& weights[M])) [inline]

Create a [mln::w_window3d_int](#).

Parameters

[in] **weights** Array of integers.

Precondition

The array size, M, has to be a cube of an odd integer.

Returns

A 3D int-weighted window.

Definition at line 61 of file make/w_window3d_int.hh.

References w_window3d().

**9.107.2.58 template<typename D , typename W , unsigned L> mln::w_window< D, W >
mln::make::w_window_directional (const Gdpoint< D > & dp, W(&) weights[L])
[inline]**

Create a directional centered weighted window.

Parameters

[in] **dp** A delta-point to set the orientation.

[in] **weights** An array of weights.

Returns

A weighted window.

The window length L has to be odd.

Definition at line 61 of file w_window_directional.hh.

References mln::w_window< D, W >::insert(), and mln::literal::zero.

9.108 mln::math Namespace Reference

Namespace of mathematical routines.

Functions

- template<typename T >
T **abs** (const T &v)
Generic version.
- template<unsigned n>
value::int_u< n > **abs** (const value::int_u< n > &v)
Specialization for mln::value::int_u.
- int **abs** (int v)
Specializations for existing overloads of std::abs.

9.108.1 Detailed Description

Namespace of mathematical routines.

9.108.2 Function Documentation

9.108.2.1 template<typename T > T mln::math::abs (const T & v) [inline]

Generic version.

Definition at line 74 of file math/abs.hh.

Referenced by abs(), and mln::morpho::line_gradient().

9.108.2.2 int mln::math::abs (int v) [inline]

Specializations for existing overloads of std::abs.

Reference: ISO/IEC 14882:2003 C++ standard, section 26.5 (C Library, [lib.c.math]).

Definition at line 79 of file math/abs.hh.

References abs().

9.108.2.3 template<unsigned n> value::int_u< n > mln::math::abs (const value::int_u< n > & v) [inline]

Specialization for [mln::value::int_u](#).

Definition at line 88 of file math/abs.hh.

9.109 mln::metal Namespace Reference

Namespace of meta-programming tools.

Namespaces

- namespace [impl](#)
Implementation namespace of metal namespace.
- namespace [math](#)
Namespace of static mathematical functions.

Classes

- struct [ands](#)
Ands type.
- struct [converts_to](#)

"converts-to" check.

- struct [equal](#)

Definition of a static 'equal' test.

- struct [goes_to](#)

"goes-to" check.

- struct [is](#)

"is" check.

- struct [is_a](#)

"is_a" check.

- struct [is_not](#)

"is_not" check.

- struct [is_not_a](#)

"is_not_a" static Boolean expression.

9.109.1 Detailed Description

Namespace of meta-programming tools.

9.110 mln::metal::impl Namespace Reference

Implementation namespace of metal namespace.

9.110.1 Detailed Description

Implementation namespace of metal namespace.

9.111 mln::metal::math Namespace Reference

Namespace of static mathematical functions.

Namespaces

- namespace [impl](#)

Implementation namespace of [metal::math](#) namespace.

9.111.1 Detailed Description

Namespace of static mathematical functions.

9.112 mln::metal::math::impl Namespace Reference

Implementation namespace of [metal::math](#) namespace.

9.112.1 Detailed Description

Implementation namespace of [metal::math](#) namespace.

9.113 mln::morpho Namespace Reference

Namespace of mathematical morphology routines.

Namespaces

- namespace [approx](#)
Namespace of approximate mathematical morphology routines.

- namespace [attribute](#)
Namespace of attributes used in mathematical morphology.

- namespace [elementary](#)
Namespace of image processing routines of elementary mathematical morphology.

- namespace [impl](#)
Namespace of mathematical morphology routines implementations.

- namespace [reconstruction](#)
Namespace of morphological reconstruction routines.

- namespace [tree](#)
Namespace of morphological tree-related routines.

- namespace [watershed](#)
Namespace of morphological watershed routines.

Functions

- template<typename I >
`mln::trait::concrete< I >::ret complementation (const Image< I > &input)`
- template<typename I >
`void complementation_inplace (Image< I > &input)`
- template<typename I , typename W >
`mln::trait::concrete< I >::ret contrast (const Image< I > &input, const Window< W > &win)`
- template<typename I , typename W >
`mln::trait::concrete< I >::ret dilation (const Image< I > &input, const Window< W > &win)`
Morphological dilation.

- template<typename I , typename W >
`mln::trait::concrete< I >::ret erosion (const Image< I > &input, const Window< W > &win)`
Morphological erosion.
- template<typename Op , typename I , typename W >
`mln::trait::concrete< I >::ret general (const Op &op, const Image< I > &input, const Window< W > &win)`
Morphological general routine.
- template<typename I , typename W >
`mln::trait::concrete< I >::ret gradient (const Image< I > &input, const Window< W > &win)`
Morphological gradient.
- template<typename I , typename W >
`mln::trait::concrete< I >::ret gradient_external (const Image< I > &input, const Window< W > &win)`
Morphological external gradient.
- template<typename I , typename W >
`mln::trait::concrete< I >::ret gradient_internal (const Image< I > &input, const Window< W > &win)`
Morphological internal gradient.
- template<typename I , typename Wh , typename Wm >
`mln::trait::concrete< I >::ret hit_or_miss (const Image< I > &input, const Window< Wh > &win_hit, const Window< Wm > &win_miss)`
Morphological hit-or-miss.
- template<typename I , typename Wh , typename Wm >
`mln::trait::concrete< I >::ret hit_or_miss_background_closing (const Image< I > &input, const Window< Wh > &win_hit, const Window< Wm > &win_miss)`
Morphological hit-or-miss closing of the background.
- template<typename I , typename Wh , typename Wm >
`mln::trait::concrete< I >::ret hit_or_miss_background_opening (const Image< I > &input, const Window< Wh > &win_hit, const Window< Wm > &win_miss)`
Morphological hit-or-miss opening of the background.
- template<typename I , typename Wh , typename Wm >
`mln::trait::concrete< I >::ret hit_or_miss_closing (const Image< I > &input, const Window< Wh > &win_hit, const Window< Wm > &win_miss)`
Morphological hit-or-miss closing.
- template<typename I , typename Wh , typename Wm >
`mln::trait::concrete< I >::ret hit_or_miss_opening (const Image< I > &input, const Window< Wh > &win_hit, const Window< Wm > &win_miss)`
Morphological hit-or-miss opening.
- template<typename I , typename W , typename O >
`void laplacian (const Image< I > &input, const Window< W > &win, Image< O > &output)`

- template<typename V >
edge_image< **util::site_pair**< **point2d** >, V, **util::graph** > **line_gradient** (const **mln::image2d**< V > &ima)

*Create a line graph image representing the gradient norm of a **mln::image2d**.*

- template<typename L , typename I , typename N >
mln::trait::ch_value< I, L >::ret **meyer_wst** (const **Image**< I > &input, const **Neighborhood**< N > &nbh, L &nbasins)

Meyer's Watershed Transform (WST) algorithm.

- template<typename L , typename I , typename N >
mln::trait::ch_value< I, L >::ret **meyer_wst** (const **Image**< I > &input, const **Neighborhood**< N > &nbh)

Meyer's Watershed Transform (WST) algorithm, with no count of basins.

- template<typename I , typename J >
mln::trait::concrete< I >::ret **min** (const **Image**< I > &lhs, const **Image**< J > &rhs)
- template<typename I , typename J >
void min_inplace (**Image**< I > &lhs, const **Image**< J > &rhs)
- template<typename I , typename J >
mln::trait::concrete< I >::ret **minus** (const **Image**< I > &lhs, const **Image**< J > &rhs)
- template<typename I , typename J >
mln::trait::concrete< I >::ret **plus** (const **Image**< I > &lhs, const **Image**< J > &rhs)
- template<typename I , typename W >
mln::trait::concrete< I >::ret **rank_filter** (const **Image**< I > &input, const **Window**< W > &win, unsigned k)

Morphological rank_filter.

- template<typename I , typename Wfg , typename Wbg >
mln::trait::concrete< I >::ret **thick_miss** (const **Image**< I > &input, const **Window**< Wfg > &win_fg, const **Window**< Wbg > &win_bg)
- template<typename I , typename Wfg , typename Wbg >
mln::trait::concrete< I >::ret **thickening** (const **Image**< I > &input, const **Window**< Wfg > &win_fg, const **Window**< Wbg > &win_bg)
- template<typename I , typename Wfg , typename Wbg >
mln::trait::concrete< I >::ret **thin_fit** (const **Image**< I > &input, const **Window**< Wfg > &win_fg, const **Window**< Wbg > &win_bg)
- template<typename I , typename Wfg , typename Wbg >
mln::trait::concrete< I >::ret **thinning** (const **Image**< I > &input, const **Window**< Wfg > &win_fg, const **Window**< Wbg > &win_bg)

Morphological thinning.

- template<typename I , typename W >
mln::trait::concrete< I >::ret **top_hat_black** (const **Image**< I > &input, const **Window**< W > &win)

Morphological black top-hat (for background / dark objects).

- template<typename I , typename W >
mln::trait::concrete< I >::ret **top_hat_self_complementary** (const **Image**< I > &input, const **Window**< W > &win)

Morphological self-complementary top-hat.

- template<typename I , typename W >
mln::trait::concrete< I >::ret **top_hat_white** (const **Image**< I > &input, const **Window**< W > &win)

Morphological white top-hat (for object / light objects).

9.113.1 Detailed Description

Namespace of mathematical morphology routines.

9.113.2 Function Documentation

9.113.2.1 template<typename I > mln::trait::concrete< I >::ret mln::morpho::complementation (const **Image**< I > & *input*) [inline]

Morphological complementation: either a logical "not" (if morpho on sets) or an arithmetical complementation (if morpho on functions).

Definition at line 116 of file complementation.hh.

Referenced by `hit_or_miss_background_closing()`, `hit_or_miss_background_opening()`, `hit_or_miss_closing()`, and `thinning()`.

9.113.2.2 template<typename I > void mln::morpho::complementation_inplace (**Image**< I > & *input*) [inline]

Morphological complementation, inplace version: either a logical "not" (if morpho on sets) or an arithmetical complementation (if morpho on functions).

Definition at line 130 of file complementation.hh.

9.113.2.3 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::contrast (const **Image**< I > & *input*, const **Window**< W > & *win*) [inline]

Morphological contrast operator (based on top-hats).

This operator is $\text{Id} + \text{wth_B} - \text{bth_B}$.

Definition at line 57 of file contrast.hh.

References `plus()`, `top_hat_black()`, and `top_hat_white()`.

9.113.2.4 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::dilation (const **Image**< I > & *input*, const **Window**< W > & *win*) [inline]

Morphological dilation.

Definition at line 162 of file dilation.hh.

References `general()`.

Referenced by gradient(), gradient_external(), hit_or_miss_background_opening(), hit_or_miss_opening(), laplacian(), mln::morpho::opening::approx::structural(), and mln::morpho::closing::approx::structural().

**9.113.2.5 template<typename I , typename W > mln::trait::concrete< I >::ret
 mln::morpho::erosion (const Image< I > & input, const Window< W > & win)
 [inline]**

Morphological erosion.

Definition at line 163 of file erosion.hh.

References general().

Referenced by gradient(), gradient_internal(), laplacian(), mln::morpho::opening::approx::structural(), and mln::morpho::closing::approx::structural().

**9.113.2.6 template<typename Op , typename I , typename W > mln::trait::concrete< I >::ret
 mln::morpho::general (const Op & op, const Image< I > & input, const Window< W > & win) [inline]**

Morphological general routine.

Definition at line 168 of file general.hh.

Referenced by dilation(), and erosion().

**9.113.2.7 template<typename I , typename W > mln::trait::concrete< I >::ret
 mln::morpho::gradient (const Image< I > & input, const Window< W > & win)
 [inline]**

Morphological gradient.

This operator is d_B - e_B.

Definition at line 76 of file gradient.hh.

References dilation(), erosion(), minus(), and mln::test::positive().

**9.113.2.8 template<typename I , typename W > mln::trait::concrete< I >::ret
 mln::morpho::gradient_external (const Image< I > & input, const Window< W > &
 win) [inline]**

Morphological external gradient.

This operator is d_B - Id.

Definition at line 110 of file gradient.hh.

References dilation(), minus(), and mln::test::positive().

**9.113.2.9 template<typename I , typename W > mln::trait::concrete< I >::ret
 mln::morpho::gradient_internal (const Image< I > & input, const Window< W > &
 win) [inline]**

Morphological internal gradient.

This operator is $\text{Id} - e_B$.

Definition at line 93 of file gradient.hh.

References erosion(), minus(), and mln::test::positive().

9.113.2.10 template<typename I , typename Wh , typename Wm > mln::trait::concrete< I >::ret mln::morpho::hit_or_miss (const Image< I > & input, const Window< Wh > & win_hit, const Window< Wm > & win_miss) [inline]

Morphological hit-or-miss.

This operator is $HMT_{(Bh,Bm)} = e_{Bh} \wedge (e_{Bm} o C)$.

Definition at line 276 of file hit_or_miss.hh.

Referenced by thickening(), and thinning().

9.113.2.11 template<typename I , typename Wh , typename Wm > mln::trait::concrete< I >::ret mln::morpho::hit_or_miss_background_closing (const Image< I > & input, const Window< Wh > & win_hit, const Window< Wm > & win_miss) [inline]

Morphological hit-or-miss closing of the background.

This operator is $C o HMT_{\text{opeBG}} o C$.

Definition at line 357 of file hit_or_miss.hh.

References complementation(), hit_or_miss_background_opening(), and hit_or_miss_closing().

9.113.2.12 template<typename I , typename Wh , typename Wm > mln::trait::concrete< I >::ret mln::morpho::hit_or_miss_background_opening (const Image< I > & input, const Window< Wh > & win_hit, const Window< Wm > & win_miss) [inline]

Morphological hit-or-miss opening of the background.

This operator is $HMT_{\text{opeBG}} = HMT_{(Bm,Bh)} o C = d_{(-Bm)} o HMT_{(Bh,Bm)}$.

Definition at line 314 of file hit_or_miss.hh.

References complementation(), dilation(), hit_or_miss_opening(), and mln::win::sym().

Referenced by hit_or_miss_background_closing(), and thick_miss().

9.113.2.13 template<typename I , typename Wh , typename Wm > mln::trait::concrete< I >::ret mln::morpho::hit_or_miss_closing (const Image< I > & input, const Window< Wh > & win_hit, const Window< Wm > & win_miss) [inline]

Morphological hit-or-miss closing.

This operator is $C o HMT_{\text{ope}} o C$.

Definition at line 337 of file hit_or_miss.hh.

References complementation(), and hit_or_miss_opening().

Referenced by hit_or_miss_background_closing().

9.113.2.14 template<typename I , typename Wh , typename Wm > mln::trait::concrete< I >::ret mln::morpho::hit_or_miss_opening (const Image< I > & *input*, const Window< Wh > & *win_hit*, const Window< Wm > & *win_miss*) [inline]

Morphological hit-or-miss opening.

This operator is HMTope_(Bh,Bm) = d_(-Bh) o HMT_(Bh,Bm).

Definition at line 294 of file hit_or_miss.hh.

References dilation(), and mln::win::sym().

Referenced by hit_or_miss_background_opening(), hit_or_miss_closing(), and thin_fit().

9.113.2.15 template<typename I , typename W , typename O > void mln::morpho::laplacian (const Image< I > & *input*, const Window< W > & *win*, Image< O > & *output*) [inline]

Morphological laplacian.

This operator is (d_B - Id) - (Id - e_B).

Definition at line 63 of file laplacian.hh.

References dilation(), erosion(), mln::data::fill(), and minus().

9.113.2.16 template<typename V > edge_image< util::site_pair< point2d >, V, util::graph > mln::morpho::line_gradient (const mln::image2d< V > & *ima*)

Create a line graph image representing the gradient norm of a [mln::image2d](#).

Definition at line 70 of file line_gradient.hh.

References mln::math::abs(), mln::image2d< T >::domain(), mln::box< P >::has(), mln::window< D >::insert(), and mln::Box< E >::nsites().

9.113.2.17 template<typename L , typename I , typename N > mln::trait::ch_value< I, L >::ret mln::morpho::meyer_wst (const Image< I > & *input*, const Neighborhood< N > & *nbh*, L & *nbasins*)

Meyer's Watershed Transform (WST) algorithm.

Parameters

[in] *input* The input image.

[in] *nbh* The connexity of markers.

[out] *nbasins* The number of basins.

- *L* is the type of labels, used to number the watershed itself (with the minimal value), and the basins.
- *I* is the exact type of the input image.
- *N* is the exact type of the neighborhood used to express *input*'s connexity.

Definition at line 108 of file meyer_wst.hh.

References mln::data::fill(), mln::p_priority< P, Q >::front(), mln::initialize(), mln::p_priority< P, Q >::pop(), mln::p_priority< P, Q >::push(), mln::labeling::regional_minima(), and mln::literal::zero.

9.113.2.18 template<typename L , typename I , typename N > mln::trait::ch_value< I, L >::ret mln::morpho::meyer_wst (const Image< I > & *input*, const Neighborhood< N > & *nbh*)

Meyer's Watershed Transform (WST) algorithm, with no count of basins.

Parameters

[in] *input* The input image.

[in] *nbh* The connexity of markers.

- L is the type of labels, used to number the watershed itself (with the minimal value), and the basins.
- I is the exact type of the input image.
- N is the exact type of the neighborhood used to express *input*'s connexity.

Note that the first parameter, L, is not automatically valued from the type of the actual argument during implicit instantiation: you have to explicitly pass this parameter at call sites.

Definition at line 202 of file meyer_wst.hh.

9.113.2.19 template<typename I , typename J > mln::trait::concrete< I >::ret mln::morpho::min (const Image< I > & *lhs*, const Image< J > & *rhs*) [inline]

Morphological min: either a logical "and" (if morpho on sets) or an arithmetical min (if morpho on functions).

Definition at line 112 of file morpho/min.hh.

9.113.2.20 template<typename I , typename J > void mln::morpho::min_inplace (Image< I > & *lhs*, const Image< J > & *rhs*) [inline]

Morphological min, inplace version: either a logical "and" (if morpho on sets) or an arithmetical min (if morpho on functions).

Definition at line 125 of file morpho/min.hh.

9.113.2.21 template<typename I , typename J > mln::trait::concrete< I >::ret mln::morpho::minus (const Image< I > & *lhs*, const Image< J > & *rhs*) [inline]

Morphological minus: either a logical "and not" (if morpho on sets) or an arithmetical minus (if morpho on functions).

Definition at line 87 of file morpho/minus.hh.

Referenced by gradient(), gradient_external(), gradient_internal(), laplacian(), thin_fit(), thinning(), top_hat_black(), mln::morpho::elementary::top_hat_black(), top_hat_self_complementary(), top_hat_white(), and mln::morpho::elementary::top_hat_white().

9.113.2.22 template<typename I , typename J > mln::trait::concrete< I >::ret mln::morpho::plus (const Image< I > & lhs, const Image< J > & rhs) [inline]

Morphological plus: either a "logical or" (if morpho on sets) or an "arithmetical plus" (if morpho on functions).

Definition at line 86 of file morpho/plus.hh.

Referenced by contrast(), thick_miss(), and thickening().

9.113.2.23 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::rank_filter (const Image< I > & input, const Window< W > & win, unsigned k) [inline]

Morphological rank_filter.

Definition at line 213 of file rank_filter.hh.

9.113.2.24 template<typename I , typename Wfg , typename Wbg > mln::trait::concrete< I >::ret mln::morpho::thick_miss (const Image< I > & input, const Window< Wfg > & win_fg, const Window< Wbg > & win_bg) [inline]

Morphological thick-miss.

This operator is THICK_B = Id + HMTopeBG_B, where B = (Bfg, Bbg).

Definition at line 59 of file thick_miss.hh.

References hit_or_miss_background_opening(), and plus().

9.113.2.25 template<typename I , typename Wfg , typename Wbg > mln::trait::concrete< I >::ret mln::morpho::thickening (const Image< I > & input, const Window< Wfg > & win_fg, const Window< Wbg > & win_bg) [inline]

Morphological thickening.

This operator is THICK_B = Id + HMT_B, where B = (Bfg, Bbg).

Definition at line 88 of file thickening.hh.

References hit_or_miss(), and plus().

Referenced by thinning().

9.113.2.26 template<typename I , typename Wfg , typename Wbg > mln::trait::concrete< I >::ret mln::morpho::thin_fit (const Image< I > & input, const Window< Wfg > & win_fg, const Window< Wbg > & win_bg) [inline]

Morphological thin-fit.

This operator is THIN_B = Id - HMTope_B where B = (Bfg, Bbg).

Definition at line 87 of file thin_fit.hh.

References hit_or_miss_opening(), and minus().

9.113.2.27 template<typename I , typename Wfg , typename Wbg > mln::trait::concrete< I >::ret mln::morpho::thinning (const Image< I > & *input*, const Window< Wfg > & *win_fg*, const Window< Wbg > & *win_bg*) [inline]

Morphological thinning.

This operator is THIN_B = Id - HMT_B, where B = (Bfg, Bbg).

Definition at line 90 of file thinning.hh.

References complementation(), hit_or_miss(), minus(), and thickening().

9.113.2.28 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::top_hat_black (const Image< I > & *input*, const Window< W > & *win*) [inline]

Morphological black top-hat (for background / dark objects).

This operator is clo_B - Id.

Definition at line 102 of file top_hat.hh.

References minus(), and mln::test::positive().

Referenced by contrast().

9.113.2.29 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::top_hat_self_complementary (const Image< I > & *input*, const Window< W > & *win*) [inline]

Morphological self-complementary top-hat.

This operator is

= top_hat_white + top_hat_black

= (*input* - opening) + (closing - *input*)

= closing - opening.

Definition at line 121 of file top_hat.hh.

References minus(), and mln::test::positive().

9.113.2.30 template<typename I , typename W > mln::trait::concrete< I >::ret mln::morpho::top_hat_white (const Image< I > & *input*, const Window< W > & *win*) [inline]

Morphological white top-hat (for object / light objects).

This operator is Id - ope_B.

Definition at line 83 of file top_hat.hh.

References minus(), and mln::test::positive().

Referenced by contrast().

9.114 mln::morpho::approx Namespace Reference

Namespace of approximate mathematical morphology routines.

9.114.1 Detailed Description

Namespace of approximate mathematical morphology routines.

9.115 mln::morpho::attribute Namespace Reference

Namespace of attributes used in mathematical morphology.

Classes

- class [card](#)
Cardinality accumulator class.
- struct [count_adjacent_vertices](#)
Count_Adjacent_Vertices accumulator class.
- struct [height](#)
Height accumulator class.
- struct [sharpness](#)
Sharpness accumulator class.
- class [sum](#)
Suminality accumulator class.
- struct [volume](#)
Volume accumulator class.

9.115.1 Detailed Description

Namespace of attributes used in mathematical morphology.

9.116 mln::morpho::closing::approx Namespace Reference

Namespace of approximate mathematical morphology closing routines.

Functions

- template<typename I , typename W >
mln::trait::concrete< I >::ret [structural](#) (const [Image](#)< I > &input, const [Window](#)< W > &win)
Approximate of morphological structural closing.

9.116.1 Detailed Description

Namespace of approximate mathematical morphology closing routines.

9.116.2 Function Documentation

**9.116.2.1 template<typename I , typename W > mln::trait::concrete< I >::ret
mln::morpho::closing::approx::structural (const Image< I > & input, const
Window< W > & win) [inline]**

Approximate of morphological structural closing.

This operator is `e_{-B} o d_B`.

Definition at line 65 of file closing/approx/structural.hh.

References `mln::morpho::dilation()`, `mln::morpho::erosion()`, and `mln::win::sym()`.

9.117 mln::morpho::elementary Namespace Reference

Namespace of image processing routines of elementary mathematical morphology.

Functions

- template<typename I , typename N >
`mln::trait::concrete< I >::ret closing (const Image< I > &input, const Neighborhood< N > &nbh)`

Morphological elementary closing.

- template<typename I , typename N >
`mln_trait_op_minus_twice (typename mln::trait::concrete< I >::ret) laplacian(const Image< I > &input`

Morphological elementary laplacian.

- template<typename I , typename N >
`mln::trait::concrete< I >::ret opening (const Image< I > &input, const Neighborhood< N > &nbh)`

Morphological elementary opening.

- template<typename I , typename N >
`mln::trait::concrete< I >::ret top_hat_black (const Image< I > &input, const Neighborhood< N > &nbh)`

Morphological elementary black top-hat (for background / dark objects).

- template<typename I , typename N >
`mln::trait::concrete< I >::ret top_hat_white (const Image< I > &input, const Neighborhood< N > &nbh)`

Morphological elementary white top-hat (for object / light objects).

9.117.1 Detailed Description

Namespace of image processing routines of elementary mathematical morphology.

9.117.2 Function Documentation

**9.117.2.1 template<typename I , typename N > mln::trait::concrete< I >::ret
 mln::morpho::elementary::closing (const Image< I > & input, const Neighborhood<
 N > & nbh) [inline]**

Morphological elementary closing.

This operator is e o d.

Definition at line 58 of file closing.hh.

Referenced by top_hat_black().

**9.117.2.2 template<typename I , typename N > mln::morpho::elementary::mln_-
 trait_op_minus_twice (typename mln::trait::concrete< I >::ret) const
 [inline]**

Morphological elementary laplacian.

This operator is (d - id) - (id - e).

**9.117.2.3 template<typename I , typename N > mln::trait::concrete< I >::ret
 mln::morpho::elementary::opening (const Image< I > & input, const Neighborhood<
 N > & nbh) [inline]**

Morphological elementary opening.

This operator is d o e.

Definition at line 58 of file opening.hh.

Referenced by top_hat_white().

**9.117.2.4 template<typename I , typename N > mln::trait::concrete< I >::ret
 mln::morpho::elementary::top_hat_black (const Image< I > & input, const
 Neighborhood< N > & nbh) [inline]**

Morphological elementary black top-hat (for background / dark objects).

This operator is clo - Id.

Definition at line 105 of file elementary/top_hat.hh.

References closing(), mln::morpho::minus(), and mln::test::positive().

**9.117.2.5 template<typename I , typename N > mln::trait::concrete< I >::ret
 mln::morpho::elementary::top_hat_white (const Image< I > & input, const
 Neighborhood< N > & nbh) [inline]**

Morphological elementary white top-hat (for object / light objects).

This operator is Id - ope.

Definition at line 85 of file elementary/top_hat.hh.

References mln::morpho::minus(), opening(), and mln::test::positive().

9.118 mln::morpho::impl Namespace Reference

Namespace of mathematical morphology routines implementations.

Namespaces

- namespace [generic](#)

Namespace of mathematical morphology routines generic implementations.

9.118.1 Detailed Description

Namespace of mathematical morphology routines implementations.

9.119 mln::morpho::impl::generic Namespace Reference

Namespace of mathematical morphology routines generic implementations.

9.119.1 Detailed Description

Namespace of mathematical morphology routines generic implementations.

9.120 mln::morpho::opening::approx Namespace Reference

Namespace of approximate mathematical morphology opening routines.

Functions

- template<typename I , typename W >
mln::trait::concrete< I >::ret [structural](#) (const [Image](#)< I > &input, const [Window](#)< W > &win)
Approximate of morphological structural opening.

9.120.1 Detailed Description

Namespace of approximate mathematical morphology opening routines.

9.120.2 Function Documentation

9.120.2.1 `template<typename I , typename W > mln::trait::concrete< I >::ret
mln::morpho::opening::approx::structural (const Image< I > & input, const
Window< W > & win) [inline]`

Approximate of morphological structural opening.

This operator is `d_{-B} o e_B`.

Definition at line 64 of file opening/approx/structural.hh.

References `mln::morpho::dilation()`, `mln::morpho::erosion()`, and `mln::win::sym()`.

9.121 mln::morpho::reconstruction Namespace Reference

Namespace of morphological reconstruction routines.

Namespaces

- namespace [by_dilation](#)

Namespace of morphological reconstruction by dilation routines.

- namespace [by_erosion](#)

Namespace of morphological reconstruction by erosion routines.

9.121.1 Detailed Description

Namespace of morphological reconstruction routines.

9.122 mln::morpho::reconstruction::by_dilation Namespace Reference

Namespace of morphological reconstruction by dilation routines.

9.122.1 Detailed Description

Namespace of morphological reconstruction by dilation routines.

9.123 mln::morpho::reconstruction::by_erosion Namespace Reference

Namespace of morphological reconstruction by erosion routines.

9.123.1 Detailed Description

Namespace of morphological reconstruction by erosion routines.

9.124 mln::morpho::tree Namespace Reference

Namespace of morphological tree-related routines.

Namespaces

- namespace `filter`

Namespace for attribute filtering.

Functions

- template<typename A , typename T >
`mln::trait::ch_value< typename T::function, typename A::result >::ret compute_attribute_image (const Accumulator< A > &a, const T &t, mln::trait::ch_value< typename T::function, A >::ret *accu_image=0)`

Compute an attribute image using tree with a parent relationship between sites.

- template<typename A , typename T , typename V >
`mln::trait::ch_value< typename T::function, typename A::result >::ret compute_attribute_image_from (const Accumulator< A > &a, const T &t, const Image< V > &values, mln::trait::ch_value< typename T::function, A >::ret *accu_image=0)`

The same as `compute_attribute_image` but uses the values stored by `values` image instead.

- template<typename I , typename N , typename S >
`mln::trait::ch_value< I, typename I::psite >::ret compute_parent (const Image< I > &f, const Neighborhood< N > &nbh, const Site_Set< S > &s)`

Compute a tree with a parent relationship between sites.

- template<typename I , typename N >
`data< I, p_array< typename I::psite > > dual_input_max_tree (const Image< I > &f, const Image< I > &m, const Neighborhood< N > &nbh)`

Compute the dual input max tree using mask-based connectivity.

- template<typename I , typename N >
`data< I, p_array< typename I::psite > > max_tree (const Image< I > &f, const Neighborhood< N > &nbh)`

Compute a canonized max-tree.

- template<typename I , typename N >
`data< I, p_array< typename I::psite > > min_tree (const Image< I > &f, const Neighborhood< N > &nbh)`

Compute a canonized min-tree.

- template<typename T , typename A , typename P , typename W >
void **propagate_if** (const T &tree, **Image**< A > &a_, const way_of_propagation< W > &prop_, const **Function_v2b**< P > &pred_, const typename A::value &v)
- template<typename T , typename A , typename P >
void **propagate_if** (const T &tree, **Image**< A > &a_, const desc_propagation &prop_, const **Function_v2b**< P > &pred_)
- template<typename T , typename A , typename W >
void **propagate_if_value** (const T &tree, **Image**< A > &a_, const way_of_propagation< W > &prop, const typename A::value &v)
- template<typename T , typename A , typename W >
void **propagate_if_value** (const T &tree, **Image**< A > &a_, const way_of_propagation< W > &prop_, const typename A::value &v, const typename A::value &v_prop)
- template<typename T , typename A >
void **propagate_node_to_ancestors** (typename A::psite n, const T &t, **Image**< A > &a_, const typename A::value &v)
- template<typename T , typename A >
void **propagate_node_to_ancestors** (typename A::psite n, const T &t, **Image**< A > &a_)
- template<typename T , typename A >
void **propagate_node_to_descendants** (typename A::psite n, const T &t, **Image**< A > &a_, const typename A::value &v, unsigned *nb_leaves=0)
- template<typename T , typename A >
void **propagate_node_to_descendants** (typename A::psite &n, const T &t, **Image**< A > &a_, unsigned *nb_leaves=0)
- template<typename T , typename F >
void **propagateRepresentative** (const T &t, **Image**< F > &f_)

Propagate the representative node's value to non-representative points of the component.

9.124.1 Detailed Description

Namespace of morphological tree-related routines.

9.124.2 Function Documentation

9.124.2.1 template<typename A , typename T > mln::trait::ch_value< typename T::function, typename A::result >::ret mln::morpho::tree::compute_attribute_image (const Accumulator< A > & a, const T & t, mln::trait::ch_value< typename T::function, A >::ret * accu_image = 0) [inline]

Compute an attribute image using tree with a parent relationship between sites.

In the attribute image, the resulting value at a node is the 'sum' of its sub-components value + the attribute value at this node.

Warning: s translates the ordering related to the "natural" childhood relationship. The parenthood is thus inverted w.r.t. to s.

It is very convenient since all processing upon the parent tree are performed following s (in the default "forward" way).

FIXME: Put it more clearly...

The parent result image verifies:

- p is root iff parent(p) == p
- p is a node iff either p is root or f(parent(p)) != f(p).

Parameters

[in] *a* Attribute.
 [in] *t* Component tree.
 [out] *accu_image* Optional argument used to store image of attribute accumulator.

Returns

The attribute image.

Definition at line 216 of file compute_attribute_image.hh.

Referenced by compute_attribute_image_from().

9.124.2.2 template<typename A , typename T , typename V > mln::trait::ch_value< typename T::function, typename A::result >::ret mln::morpho::tree::compute_attribute_image _from (const Accumulator< A > & a, const T & t, const Image< V > & values, mln::trait::ch_value< typename T::function, A >::ret * accu_image = 0) [inline]

The same as compute_attribute_image but uses the values stored by *values* image instead.

Parameters

[in] *a* Attribute.
 [in] *t* Component tree.
 [in] *values* Value image.
 [out] *accu_image* Optional argument used to store image.

Returns

Definition at line 233 of file compute_attribute_image.hh.

References compute_attribute_image().

9.124.2.3 template<typename I , typename N , typename S > mln::trait::ch_value< I, typename I::psite >::ret mln::morpho::tree::compute_parent (const Image< I > & f, const Neighborhood< N > & nbh, const Site_Set< S > & s) [inline]

Compute a tree with a parent relationship between sites.

Warning: *s* translates the ordering related to the "natural" childhood relationship. The parenthood is thus inverted w.r.t. to *s*.

It is very convenient since most processing routines upon the parent tree are performed following *s* (in the default "forward" way). Indeed that is the way to propagate information from parents to children.

The parent result image verifies:

- p is root iff parent(p) == p

- p is a node iff either p is root or $f(\text{parent}(p)) \neq f(p)$.

The choice "s means childhood" is consistent with labeling in binary images. In that particular case, while browsing the image in forward scan (video), we expect to find first a tree root (a first point, representative of a component) and then the other component points. Please note that it leads to increasing values of labels in the "natural" video scan.

Since mathematical morphology on functions is related to morphology on sets, we clearly want to keep the equivalence between "component labeling" and "component filtering" using trees.

FIXME: Put it more clearly... Insert pictures!

A binary image:

- | | - -
- | | - |
- - - - -
- - | | -

where '|' means true and '-' means false.

Its labeling:

```
0 1 1 0 0
0 1 1 0 2
0 0 0 0 0
0 0 3 3 0
```

The corresponding forest:

```
x o . x x
x . . x o
x x x x x
x x o . x
```

where 'x' means "no data", 'o' is a tree root (representative point for a component), and '.' is a tree regular (non-root) point (in a component by not its representative point).

The forest, with the parent relationship looks like:

```
o < .
^ r
. . o
o < .
```

Definition at line 286 of file compute_parent.hh.

9.124.2.4 template<typename I , typename N > morpho::tree::data< I, p_array< typename I::psite > > mln::morpho::tree::dual_input_max_tree (const Image< I > & f, const Image< I > & m, const Neighborhood< N > & nbh) [inline]

Compute the dual input max tree using mask-based connectivity.

Parameters

- [in] ***f*** The original image.
- [in] ***m*** The connectivity mask.
- [in] ***nbh*** The neighborhood of the mask.

Returns

The computed tree.

Definition at line 109 of file dual_input_tree.hh.

**9.124.2.5 template<typename I , typename N > data< I, p_array< typename I::psite > >
 mln::morpho::tree::max_tree (const Image< I > & *f*, const Neighborhood< N > &
nbh) [inline]**

Compute a canonized max-tree.

Parameters

- [in] ***f*** The input image.
- [in] ***nbh*** The neighborhood.

Returns

The corresponding max-tree structure.

Definition at line 100 of file component_tree.hh.

References mln::data::sort_psites_increasing().

**9.124.2.6 template<typename I , typename N > data< I, p_array< typename I::psite > >
 mln::morpho::tree::min_tree (const Image< I > & *f*, const Neighborhood< N > &
nbh) [inline]**

Compute a canonized min-tree.

Parameters

- [in] ***f*** The input image.
- [in] ***nbh*** The neighborhood.

Returns

The corresponding min-tree structure.

Definition at line 77 of file component_tree.hh.

References mln::data::sort_psites_decreasing().

**9.124.2.7 template<typename T , typename A , typename P , typename W > void
mln::morpho::tree::propagate_if(const T & tree, Image< A > & a_, const
way_of_propagation< W > & prop_, const Function_v2b< P > & pred_, const
typename A::value & v) [inline]**

Propagate nodes checking the predicate `pred` in the way defined by `way_of_propagation`.

Parameters

tree Component tree used for propagation.
a_ Attributed image where values are propagated.
prop_ Propagate node in ascendant or descendant way.
pred_ Predicate that node must check to be propagated.
v Value to be propagated. (By default `v` is the value at the node being propagated).

Definition at line 293 of file propagate_if.hh.

Referenced by `propagate_if()`, `propagate_if_value()`, and `mln::morpho::tree::filter::subtractive()`.

**9.124.2.8 template<typename T , typename A , typename P > void
mln::morpho::tree::propagate_if(const T & tree, Image< A > & a_, const
desc_propagation & prop_, const Function_v2b< P > & pred_) [inline]**

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 310 of file propagate_if.hh.

References `propagate_if()`.

**9.124.2.9 template<typename T , typename A , typename W > void
mln::morpho::tree::propagate_if_value(const T & tree, Image< A > & a_, const
way_of_propagation< W > & prop, const typename A::value & v) [inline]**

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 278 of file propagate_if.hh.

References `propagate_if()`.

**9.124.2.10 template<typename T , typename A , typename W > void
mln::morpho::tree::propagate_if_value(const T & tree, Image< A > & a_, const
way_of_propagation< W > & prop_, const typename A::value & v, const typename
A::value & v_prop) [inline]**

Propagate nodes having the value `v` in the way defined by `way_of_propagation`.

Parameters

tree Component tree used for propagation.
a_ Attributed image where values are propagated.
prop_ Propagate node in ascendant or descendant way.

v [Value](#) that node must have to be propagated.

v_prop [Value](#) to propagate (By default it is the value at the node being propagated).

Definition at line 262 of file propagate_if.hh.

References propagate_if().

9.124.2.11 template<typename T , typename A > void mln::morpho::tree::propagate_node_to_ancestors (typename A::psite n, const T & t, Image< A > & a_, const typename A::value & v)

Propagate a value *v* from a node *n* to its ancestors.

Parameters

[in] *n* Node to propagate.

[in] *t* Component tree used for propagation.

[in] *a_* Attribute image where values are propagated.

[in] *v* [Value](#) to propagate.

Definition at line 170 of file propagate_node.hh.

Referenced by propagate_node_to_ancestors().

9.124.2.12 template<typename T , typename A > void mln::morpho::tree::propagate_node_to_ancestors (typename A::psite n, const T & t, Image< A > & a_) [inline]

Propagate the node's value to its ancestors.

Parameters

[in] *n* Node to propagate.

[in] *t* Component tree used for propagation.

[in, out] *a_* Attribute image where values are propagated.

Definition at line 197 of file propagate_node.hh.

References propagate_node_to_ancestors().

9.124.2.13 template<typename T , typename A > void mln::morpho::tree::propagate_node_to_descendants (typename A::psite n, const T & t, Image< A > & a_, const typename A::value & v, unsigned * nb_leaves = 0) [inline]

Propagate a value *v* from a node *n* to its descendants.

Parameters

[in] *n* Node to propagate.

[in] *t* Component tree used for propagation.

[in] *a_* Attribute image where values are propagated.

[in] *v* Value to propagate.

[out] *nb_leaves* Optional. Store the number of leaves in the component.

Definition at line 120 of file propagate_node.hh.

9.124.2.14 template<typename T , typename A > void mln::morpho::tree::propagate_node_to_descendants (typename A::psite & n, const T & t, Image< A > & a_, unsigned * nb_leaves = 0) [inline]

Propagate the node's value to its descendants.

Parameters

[in] *n* Node to propagate.

[in] *t* Component tree used for propagation.

[in] *a_* Attribute image where values are propagated.

[out] *nb_leaves* Optional. Store the number of leaves in the component.

9.124.2.15 template<typename T , typename F > void mln::morpho::tree::propagate_representative (const T & t, Image< F > & f_) [inline]

Propagate the representative node's value to non-representative points of the component.

Parameters

t Component tree.

f_ Value image.

Definition at line 65 of file propagate_representative.hh.

9.125 mln::morpho::tree::filter Namespace Reference

Namespace for attribute filtering.

Functions

- template<typename T , typename F , typename P >
void **direct** (const T &tree, Image< F > &f_, const Function_v2b< P > &pred_)
Direct non-pruning strategy.
- template<typename T , typename F , typename P >
void **filter** (const T &tree, Image< F > &f_, const Function_v2b< P > &pred_, const typename F::value &v)
Filter the image f_ with a given value.
- template<typename T , typename F , typename P >
void **max** (const T &tree, Image< F > &f_, const Function_v2b< P > &pred_)

Max pruning strategy.

- template<typename T , typename F , typename P >
void **min** (const T &tree, **Image**< F > &f_, const **Function_v2b**< P > &pred_)

Min pruning strategy.

- template<typename T , typename F , typename P >
void **subtractive** (const T &tree, **Image**< F > &f_, const **Function_v2b**< P > &pred_)

Subtractive pruning strategy.

9.125.1 Detailed Description

Namespace for attribute filtering.

9.125.2 Function Documentation

- 9.125.2.1 template<typename T , typename F , typename P > void
mln::morpho::tree::filter::direct (const T & tree, **Image**< F > & f_, const
Function_v2b< P > & pred_) [inline]**

Direct non-pruning strategy.

A node is removed if it does not verify the predicate. The sub-components remain intact.

Parameters

- [in] **tree** Component tree.
- [out] **f_** **Image** to filter.
- [in] **pred_** Filtering criterion.

Definition at line 73 of file direct.hh.

- 9.125.2.2 template<typename T , typename F , typename P > void mln::morpho::tree::filter::filter
(const T & tree, **Image**< F > & f_, const **Function_v2b**< P > & pred_, const
typename F::value & v) [inline]**

Filter the image **f_** with a given value.

The sub-components of nodes that does not match the predicate **pred_** are filled with the given value **v**.

Parameters

- tree** Component tree.
- f_** **Image** function.
- pred_** Predicate.
- v** **Value** to propagate.

Definition at line 73 of file morpho/tree/filter/filter.hh.

References **mln::data::fill()**, and **mln::initialize()**.

9.125.2.3 template<typename T , typename F , typename P > void mln::morpho::tree::filter::max (const T & tree, Image< F > & f_, const Function_v2b< P > & pred_) [inline]

Max pruning strategy.

A node is removed iif all of its children are removed or if it does not verify the predicate `pred_`.

Parameters

- [in] `tree` Component tree.
- [out] `f_` Image to filter.
- [in] `pred_` Filtering criterion.

Definition at line 74 of file morpho/tree/filter/max.hh.

References mln::data::fill(), and mln::initialize().

9.125.2.4 template<typename T , typename F , typename P > void mln::morpho::tree::filter::min (const T & tree, Image< F > & f_, const Function_v2b< P > & pred_) [inline]

Min pruning strategy.

A node is removed iif its parent is removed or if it does not verify the predicate `pred_`.

Parameters

- [in] `tree` Component tree.
- [out] `f_` Image to filter.
- [in] `pred_` Filtering criterion.

Definition at line 75 of file morpho/tree/filter/min.hh.

References mln::data::fill(), and mln::initialize().

**9.125.2.5 template<typename T , typename F , typename P > void
mln::morpho::tree::filter::subtractive (const T & tree, Image< F > & f_, const
Function_v2b< P > & pred_) [inline]**

Subtractive pruning strategy.

The node is removed if it does not verify the predicate. The sub-components values are set to the value of the removed component.

Parameters

- [in] `tree` Component tree.
- [out] `f_` Image to filter.
- [in] `pred_` Filtering criterion.

Definition at line 77 of file subtractive.hh.

References mln::morpho::tree::propagate_if().

9.126 mln::morpho::watershed Namespace Reference

Namespace of morphological watershed routines.

Namespaces

- namespace **watershed**

Namespace of morphological watershed routines implementations.

Functions

- template<typename L , typename I , typename N >
`mln::trait::ch_value< I, L >::ret flooding (const Image< I > &input, const Neighborhood< N > &nbh, L &n_basins)`

Meyer's Watershed Transform (WST) algorithm.

- template<typename L , typename I , typename N >
`mln::trait::ch_value< I, L >::ret flooding (const Image< I > &input, const Neighborhood< N > &nbh)`

Meyer's Watershed Transform (WST) algorithm, with no count of basins.

- template<typename I , typename J >
`mln::trait::ch_value< I, value::rgb8 >::ret superpose (const Image< I > &input, const Image< J > &ws_ima)`

Convert an image to a rgb8 image and draw the watershed lines.

- template<typename I , typename J >
`mln::trait::ch_value< I, value::rgb8 >::ret superpose (const Image< I > &input_, const Image< J > &ws_ima_, const value::rgb8 &wsl_color)`

Convert an image to a rgb8 image and draw the watershed lines.

- template<class T >
`T::image_t topological (T &tree)`

Compute a topological watershed transform from tree.

9.126.1 Detailed Description

Namespace of morphological watershed routines.

9.126.2 Function Documentation

- #### 9.126.2.1 template<typename L , typename I , typename N > mln::trait::ch_value< I, L >::ret `mln::morpho::watershed::flooding (const Image< I > & input, const Neighborhood< N > & nbh, L & n_basins) [inline]`

Meyer's Watershed Transform (WST) algorithm.

Parameters

[in] ***input*** The input image.
 [in] ***nbh*** The connexity of markers.
 [out] ***n_basins*** The number of basins.

- **L** is the type of labels, used to number the watershed itself (with the minimal value), and the basins.
- **I** is the exact type of the input image.
- **N** is the exact type of the neighborhood used to express *input*'s connexity.

Definition at line 381 of file flooding.hh.

**9.126.2.2 template<typename L , typename I , typename N > mln::trait::ch_value< I, L >::ret
 mln::morpho::watershed::flooding (const Image< I > & *input*, const Neighborhood<
 N > & *nbh*)**

Meyer's Watershed Transform (WST) algorithm, with no count of basins.

Parameters

[in] ***input*** The input image.
 [in] ***nbh*** The connexity of markers.

- **L** is the type of labels, used to number the watershed itself (with the minimal value), and the basins.
- **I** is the exact type of the input image.
- **N** is the exact type of the neighborhood used to express *input*'s connexity.

Note that the first parameter, **L**, is not automatically valued from the type of the actual argument during implicit instantiation: you have to explicitly pass this parameter at call sites.

Definition at line 396 of file flooding.hh.

**9.126.2.3 template<typename I , typename J > mln::trait::ch_value< I, value::rgb8 >::ret
 mln::morpho::watershed::superpose (const Image< I > & *input*, const Image< J > &
ws_ima) [inline]**

Convert an image to a rgb8 image and draw the watershed lines.

Definition at line 109 of file morpho/watershed/superpose.hh.

References mln::literal::red, and superpose().

**9.126.2.4 template<typename I , typename J > mln::trait::ch_value< I, value::rgb8 >::ret
 mln::morpho::watershed::superpose (const Image< I > & *input*_, const Image< J >
 & *ws_ima*_ , const value::rgb8 & *wsl_color*) [inline]**

Convert an image to a rgb8 image and draw the watershed lines.

Definition at line 85 of file morpho/watershed/superpose.hh.

References mln::data::convert(), mln::data::fill(), and mln::literal::zero.

Referenced by superpose().

9.126.2.5 template<class T > T::image_t mln::morpho::watershed::topological (T & tree)

Compute a topological watershed transform from *tree*.

Definition at line 675 of file topological.hh.

References mln::data::fill(), mln::p_priority< P, Q >::front(), mln::initialize(), mln::p_priority< P, Q >::pop(), mln::p_priority< P, Q >::push(), and topological().

Referenced by topological().

9.127 mln::morpho::watershed::watershed Namespace Reference

Namespace of morphological watershed routines implementations.

Namespaces

- namespace [generic](#)

Namespace of morphological watershed routines generic implementations.

9.127.1 Detailed Description

Namespace of morphological watershed routines implementations.

9.128 mln::morpho::watershed::watershed::generic Namespace Reference

Namespace of morphological watershed routines generic implementations.

9.128.1 Detailed Description

Namespace of morphological watershed routines generic implementations.

9.129 mln::norm Namespace Reference

Namespace of norms.

Namespaces

- namespace [impl](#)

Implementation namespace of norm namespace.

Functions

- template<unsigned n, typename C >
`mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum l2 (const C(&vec)[n])`
L2-norm of a vector vec.

- template<unsigned n, typename C >
`mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum l1 (const C(&vec)[n])`
L1-norm of a vector vec.

- template<unsigned n, typename C >
`mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum l1_distance (const C(&vec1)[n], const C(&vec2)[n])`
L1-norm distance between vectors vec1 and vec2.

- template<unsigned n, typename C >
`mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum sqr_l2 (const C(&vec)[n])`
Squared L2-norm of a vector vec.

- template<unsigned n, typename C >
`mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum l2_distance (const C(&vec1)[n], const C(&vec2)[n])`
L2-norm distance between vectors vec1 and vec2.

- template<unsigned n, typename C >
`C linfty (const C(&vec)[n])`
L-infinity-norm of a vector vec.

- template<unsigned n, typename C >
`C linfty_distance (const C(&vec1)[n], const C(&vec2)[n])`
L-infinity-norm distance between vectors vec1 and vec2.

9.129.1 Detailed Description

Namespace of norms.

9.129.2 Function Documentation

9.129.2.1 template<unsigned n, typename C > mln::trait::value_< typename mln::trait::op::times< C, C >::ret >::sum mln::norm::l1 (const C(&) vec[n]) [inline]

L1-norm of a vector *vec*.

Definition at line 108 of file 11.hh.

**9.129.2.2 template<unsigned n, typename C> mln::trait::value_< typename
mln::trait::op::times< C, C >::ret >::sum mln::norm::l1_distance (const C(&
vec1[n], const C(&) vec2[n]) [inline]**

L1-norm distance between vectors *vec1* and *vec2*.

Definition at line 124 of file l1.hh.

**9.129.2.3 template<unsigned n, typename C> mln::trait::value_< typename
mln::trait::op::times< C, C >::ret >::sum mln::norm::l2 (const C(&) vec[n])
[inline]**

L2-norm of a vector *vec*.

Definition at line 139 of file l2.hh.

**9.129.2.4 template<unsigned n, typename C> mln::trait::value_< typename
mln::trait::op::times< C, C >::ret >::sum mln::norm::l2_distance (const C(&
vec1[n], const C(&) vec2[n]) [inline]**

L2-norm distance between vectors *vec1* and *vec2*.

Definition at line 173 of file l2.hh.

**9.129.2.5 template<unsigned n, typename C> C mln::norm::linfty (const C(&) vec[n])
[inline]**

L-infinity-norm of a vector *vec*.

Definition at line 113 of file linfty.hh.

**9.129.2.6 template<unsigned n, typename C> C mln::norm::linfty_distance (const C(&
vec1[n], const C(&) vec2[n]) [inline]**

L-infinity-norm distance between vectors *vec1* and *vec2*.

Definition at line 127 of file linfty.hh.

**9.129.2.7 template<unsigned n, typename C> mln::trait::value_< typename
mln::trait::op::times< C, C >::ret >::sum mln::norm::sqr_l2 (const C(&) vec[n])
[inline]**

Squared L2-norm of a vector *vec*.

Definition at line 156 of file l2.hh.

Referenced by mln::geom::mesh_corner_point_area(), and mln::geom::mesh_normal().

9.130 mln::norm::impl Namespace Reference

Implementation namespace of norm namespace.

9.130.1 Detailed Description

Implementation namespace of norm namespace.

9.131 mln::opt Namespace Reference

Namespace of optional routines.

Namespaces

- namespace `impl`

Implementation namespace of opt namespace.

Functions

- template<typename I >
`I::rvalue at (const Image< I > &ima, def::coord ind)`
One dimension Read-only access to the `ima` value located at (`ind`).
- template<typename I >
`I::lvalue at (Image< I > &ima, def::coord ind)`
Read-write access to the `ima` value located at (`ind`).
- template<typename I >
`I::lvalue at (Image< I > &ima, def::coord row, def::coord col)`
Read-write access to the `ima` value located at (`row, col`).
- template<typename I >
`I::rvalue at (const Image< I > &ima, def::coord sli, def::coord row, def::coord col)`
Three dimensions Read-only access to the `ima` value located at (`sli, row, col`).
- template<typename I >
`I::rvalue at (const Image< I > &ima, def::coord row, def::coord col)`
Two dimensions Read-only access to the `ima` value located at (`row, col`).
- template<typename I >
`I::lvalue at (Image< I > &ima, def::coord sli, def::coord row, def::coord col)`
Read-write access to the `ima` value located at (`sli, row, col`).

9.131.1 Detailed Description

Namespace of optional routines.

9.131.2 Function Documentation

9.131.2.1 `template<typename I> I::rvalue mln::opt::at (const Image< I > & ima, def::coord ind) [inline]`

One dimension Read-only access to the `ima` value located at (`ind`).

Definition at line 151 of file at.hh.

Referenced by `mln::transform::hough()`, and `mln::make::image()`.

9.131.2.2 `template<typename I> I::lvalue mln::opt::at (Image< I > & ima, def::coord ind)`

Read-write access to the `ima` value located at (`ind`).

Definition at line 160 of file at.hh.

9.131.2.3 `template<typename I> I::lvalue mln::opt::at (Image< I > & ima, def::coord row, def::coord col)`

Read-write access to the `ima` value located at (`row, col`).

Definition at line 245 of file at.hh.

9.131.2.4 `template<typename I> I::rvalue mln::opt::at (const Image< I > & ima, def::coord sli, def::coord row, def::coord col) [inline]`

Three dimensions Read-only access to the `ima` value located at (`sli, row, col`).

Definition at line 320 of file at.hh.

9.131.2.5 `template<typename I> I::rvalue mln::opt::at (const Image< I > & ima, def::coord row, def::coord col) [inline]`

Two dimensions Read-only access to the `ima` value located at (`row, col`).

Definition at line 236 of file at.hh.

9.131.2.6 `template<typename I> I::lvalue mln::opt::at (Image< I > & ima, def::coord sli, def::coord row, def::coord col)`

Read-write access to the `ima` value located at (`sli, row, col`).

Definition at line 330 of file at.hh.

9.132 `mln::opt::impl` Namespace Reference

Implementation namespace of opt namespace.

9.132.1 Detailed Description

Implementation namespace of opt namespace. Three dimensions.

Two dimensions.

One dimension.

9.133 mln::pw Namespace Reference

Namespace of "point-wise" expression tools.

Classes

- class [image](#)

A generic point-wise image implementation.

9.133.1 Detailed Description

Namespace of "point-wise" expression tools.

9.134 mln::registration Namespace Reference

Namespace of "point-wise" expression tools.

Classes

- class [closest_point_basic](#)

Closest point functor based on map distance.

- class [closest_point_with_map](#)

Closest point functor based on map distance.

Functions

- template<typename P , typename F >
algebra::quat [get_rot](#) (const [p_array](#)< P > &P_, const [vec3d_f](#) &mu_P, const [vec3d_f](#) &mu_Yk, const F &closest_point, const algebra::quat &qR, const [vec3d_f](#) &qT)

FIXME: work only for 3d images.

- template<typename P , typename F >
std::pair< algebra::quat, mln_vec(P)> [icp](#) (const [p_array](#)< P > &P_, const [p_array](#)< P > &X, const F &closest_point, const algebra::quat &initial_rot, const mln_vec(P)&initial_translation)

Base version of the ICP algorithm. It is called in other variants.

- template<typename P , typename F >
`composed< translation< P::dim, float >, rotation< P::dim, float > > icp (const p_array< P > &P_, const p_array< P > &X, const F &closest_point)`
- template<typename P >
`composed< translation< P::dim, float >, rotation< P::dim, float > > registration1 (const box< P > &domain, const p_array< P > &P_, const p_array< P > &X)`
Call ICP once and return the resulting transformation.
- template<typename P >
`composed< translation< P::dim, float >, rotation< P::dim, float > > registration2 (const box< P > &domain, const p_array< P > &P_, const p_array< P > &X)`
Call ICP 10 times.
- template<typename P >
`composed< translation< P::dim, float >, rotation< P::dim, float > > registration3 (const box< P > &domain, const p_array< P > &P_, const p_array< P > &X)`
Call ICP 10 times.

9.134.1 Detailed Description

Namespace of "point-wise" expression tools.

9.134.2 Function Documentation

9.134.2.1 template<typename P , typename F > algebra::quat mln::registration::get_rot (const p_array< P > & P_, const vec3d_f & mu_P, const vec3d_f & mu_Yk, const F & closest_point, const algebra::quat & qR, const vec3d_f & qT)

FIXME: work only for 3d images.

Definition at line 527 of file icp.hh.

References mln::p_array< P >::nsites().

9.134.2.2 template<typename P , typename F > std::pair< algebra::quat, mln_vec(P)> mln::registration::icp (const p_array< P > & P_, const p_array< P > & X, const F & closest_point, const algebra::quat & initial_rot, const mln_vec(P)& initial_translation) [inline]

Base version of the ICP algorithm. It is called in other variants.

Register point in `c` using a function of closest points `closest_point`. This overload allows to specify initial transformations.

Parameters

- [in] `P_` The cloud of points.
- [in] `X` the reference surface.
- [in] `closest_point` The function of closest points.
- [in] `initial_rot` An initial rotation.

[in] ***initial_translation*** An initial translation.

Returns

the rigid transformation which may be used later to create a registered image.

WARNING: the function `closest_point` *MUST* take float/double vector as arguments. Otherwise the resulting transformation may be wrong due to the truncation of the vector coordinate values.

Precondition

P_- and X must not be empty.

Reference article: "A Method for Registration of 3-D Shapes", Paul J. Besl and Neil D. McKay, IEEE, 2, February 1992.

Definition at line 612 of file icp.hh.

References `mln::geom::bbox()`, `mln::literal::black`, `mln::set::compute()`, `mln::duplicate()`, `mln::box< P >::enlarge()`, `mln::data::fill()`, `mln::literal::green`, `mln::io::ppm::save()`, and `mln::literal::white`.

**9.134.2.3 template<typename P , typename F > composed<
translation< $P::dim$,float>,rotation< $P::dim$,float>> mln::registration::icp (const
 $p_array< P > \& P_-$, const $p_array< P > \& X$, const F & closest_point)**

Register point in c using a function of closest points `closest_point`.

Parameters

[in] ***P_-*** The cloud of points.

[in] ***X*** the reference surface.

[in] ***closest_point*** The function of closest points.

Returns

the rigid transformation which may be used later to create a registered image.

**9.134.2.4 template<typename P > composed< translation< $P::dim$, float >, rotation< $P::dim$,
float >> mln::registration::registration1 (const box< P > & domain, const $p_array<$
 $P > \& P_-$, const $p_array< P > \& X$) [inline]**

Call ICP once and return the resulting transformation.

Definition at line 325 of file registration.hh.

**9.134.2.5 template<typename P > composed< translation< $P::dim$, float >, rotation< $P::dim$,
float >> mln::registration::registration2 (const box< P > & domain, const $p_array<$
 $P > \& P_-$, const $p_array< P > \& X$) [inline]**

Call ICP 10 times.

Do the first call to ICP with all sites then work on a subset of which size is decreasing. For each call, a distance criterion is computed on a subset. Sites part of the subset which are too far or too close are removed. Removed sites are *NOT* reused later in the subset.

Definition at line 345 of file registration.hh.

9.134.2.6 template<typename P> composed< translation< P::dim, float >, rotation< P::dim, float > > mln::registration::registration3 (const box< P > & domain, const p_array< P > & P_, const p_array< P > & X) [inline]

Call ICP 10 times.

Do the first call to ICP with all sites then work on a subset. For each call, a distance criterion is computed on a subset. A new subset is computed from the whole set of points according to this distance. It will be used in the next call. Removed Sites *MAY* be reintegrated.

Definition at line 365 of file registration.hh.

9.135 mln::select Namespace Reference

Select namespace (FIXME doc).

Classes

- struct [p_of](#)
Structure p_of.

9.135.1 Detailed Description

Select namespace (FIXME doc).

9.136 mln::set Namespace Reference

Namespace of image processing routines related to pixel sets.

Functions

- template<typename S>
unsigned [card](#) (const [Site_Set](#)< S > &s)
Compute the cardinality of the site set s.
- template<typename A, typename S>
A::result [compute](#) (const [Accumulator](#)< A > &a, const [Site_Set](#)< S > &s)
Compute an accumulator onto a site set.
- template<typename A, typename I>
A::result [compute_with_weights](#) (const [Accumulator](#)< A > &a, const [Image](#)< I > &w)
Compute an accumulator on a site set described by an image.
- template<typename S>
S::site [get](#) (const [Site_Set](#)< S > &s, size_t index)
FIXME.

- template<typename S >
`bool has (const Site_Set< S > &s, const typename S::site &e)`
FIXME.
- template<typename A , typename I >
`mln_meta_accu_result (A, typename I::site) compute_with_weights(const Meta_Accumulator< A > &a`
Compute an accumulator on a site set described by an image.
- template<typename A , typename S >
`mln_meta_accu_result (A, typename S::site) compute(const Meta_Accumulator< A > &a`
Compute an accumulator onto a site set.

9.136.1 Detailed Description

Namespace of image processing routines related to pixel sets.

9.136.2 Function Documentation

9.136.2.1 template<typename S > unsigned mln::set::card (const Site_Set< S > & s) [inline]

Compute the cardinality of the site set `s`.

Definition at line 134 of file set/card.hh.

9.136.2.2 template<typename A , typename S > A::result mln::set::compute (const Accumulator< A > & a, const Site_Set< S > & s) [inline]

Compute an accumulator onto a site set.

Parameters

- [in] `a` An accumulator.
- [in] `s` A site set.

Returns

The accumulator result.

Definition at line 112 of file set/compute.hh.

Referenced by `mln::registration::icp()`.

9.136.2.3 template<typename A , typename I > A::result mln::set::compute_with_weights (const Accumulator< A > & a, const Image< I > & w) [inline]

Compute an accumulator on a site set described by an image.

Parameters

- [in] `a` An accumulator.

[in] *w* An image of weights (a site -> a weight).

Returns

The accumulator result.

Definition at line 217 of file compute_with_weights.hh.

9.136.2.4 template<typename S> S::site mln::set::get (const Site_Set<S> & s, size_t index)

FIXME.

Definition at line 56 of file set/get.hh.

9.136.2.5 template<typename S> bool mln::set::has (const Site_Set<S> & s, const typename S::site & e)

FIXME.

Definition at line 56 of file set/has.hh.

9.136.2.6 template<typename A, typename I> mln::set::mln_meta_accu_result (A, typename I::site) const [inline]

Compute an accumulator on a site set described by an image.

Parameters

[in] *a* A meta-accumulator.

[in] *w* An image of weights (a site -> a weight).

Returns

The accumulator result.

9.136.2.7 template<typename A, typename S> mln::set::mln_meta_accu_result (A, typename S::site) const

Compute an accumulator onto a site set.

Parameters

[in] *a* A meta-accumulator.

[in] *s* A site set.

9.137 mln::subsampling Namespace Reference

Namespace of "point-wise" expression tools.

Functions

- template<typename I >
mln::trait::concrete< I >::ret **antialiased** (const **Image**< I > &input, unsigned factor, const typename I::domain_t &output_domain, unsigned border_thickness)
Antialiased subsampling.
- template<typename I >
mln::trait::concrete< I >::ret **antialiased** (const **Image**< I > &input, unsigned factor)
- template<typename I >
mln::trait::concrete< I >::ret **gaussian_subsampling** (const **Image**< I > &input, float sigma, const typename I::dpsite &first_p, const typename I::site::coord &gap)
Gaussian subsampling FIXME : doxy.
- template<typename I >
mln::trait::concrete< I >::ret **subsampling** (const **Image**< I > &input, const typename I::site::delta &first_p, const typename I::site::coord &gap)
Subsampling FIXME : doxy.

9.137.1 Detailed Description

Namespace of "point-wise" expression tools.

9.137.2 Function Documentation

9.137.2.1 template<typename I > mln::trait::concrete< I >::ret mln::subsampling::antialiased (const Image< I > & input, unsigned factor, const typename I::domain_t & output_domain, unsigned border_thickness) [inline]

Antialiased subsampling.

Parameters

- [in] **input** A gray-level image.
- [in] **factor** Subsampling ratio. Must be divisible by 2 or 3.
- [in] **output_domain** Force output domain.
- [in] **border_thickness** Force output border thickness.

Definition at line 418 of file antialiased.hh.

Referenced by [antialiased\(\)](#).

9.137.2.2 template<typename I > mln::trait::concrete< I >::ret mln::subsampling::antialiased (const Image< I > & input, unsigned factor) [inline]

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 443 of file antialiased.hh.

References [antialiased\(\)](#).

**9.137.2.3 template<typename I > mln::trait::concrete< I >::ret mln::subsampling::gaussian_-
subsampling (const Image< I > & *input*, float *sigma*, const typename I::dpsite &
first_p, const typename I::site::coord & *gap*) [inline]**

Gaussian subsampling FIXME : doxy.

Definition at line 62 of file gaussian_subsampling.hh.

References mln::linear::gaussian(), mln::geom::ncols(), and mln::geom::nrows().

**9.137.2.4 template<typename I > mln::trait::concrete< I >::ret mln::subsampling::subsampling
(const Image< I > & *input*, const typename I::site::delta & *first_p*, const typename
I::site::coord & *gap*) [inline]**

Subsampling FIXME : doxy.

Definition at line 91 of file subsampling.hh.

References mln::geom::ncols(), and mln::geom::nrows().

9.138 mln::tag Namespace Reference

Namespace of image processing routines related to tags.

9.138.1 Detailed Description

Namespace of image processing routines related to tags.

9.139 mln::test Namespace Reference

Namespace of image processing routines related to pixel tests.

Namespaces

- namespace **impl**

Implementation namespace of test namespace.

Functions

- template<typename I >
bool **positive** (const **Image**< I > &*input*)

Test if an image only contains positive values.

- template<typename S , typename F >
bool **predicate** (const **Site_Set**< S > &*pset*, const **Function_v2b**< F > &*f*)

Test if all points of pset verify the predicate f.

- template<typename I , typename J , typename F >
`bool predicate (const Image< I > &lhs, const Image< J > &rhs, const Function_vv2b< F > &f)`
Test if all pixel values of lhs and rhs verify the predicate f.
- template<typename I , typename F >
`bool predicate (const Image< I > &ima, const Function_v2b< F > &f)`
Test if all pixel values of ima verify the predicate f.

9.139.1 Detailed Description

Namespace of image processing routines related to pixel tests.

9.139.2 Function Documentation

9.139.2.1 template<typename I > bool mln::test::positive (const Image< I > & input) [inline]

Test if an image only contains positive values.

Definition at line 54 of file positive.hh.

References predicate(), and mln::literal::zero.

Referenced by mln::morpho::gradient(), mln::morpho::gradient_external(), mln::morpho::gradient_internal(), mln::morpho::top_hat_black(), mln::morpho::elementary::top_hat_black(), mln::morpho::top_hat_self_complementary(), mln::morpho::top_hat_white(), and mln::morpho::elementary::top_hat_white().

9.139.2.2 template<typename S , typename F > bool mln::test::predicate (const Site_Set< S > & pset, const Function_v2b< F > & f) [inline]

Test if all points of pset verify the predicate f.

Parameters

[in] *pset* The point set.

[in] *f* The predicate.

Definition at line 242 of file predicate.hh.

9.139.2.3 template<typename I , typename J , typename F > bool mln::test::predicate (const Image< I > & lhs, const Image< J > & rhs, const Function_vv2b< F > & f) [inline]

Test if all pixel values of lhs and rhs verify the predicate f.

Parameters

[in] *lhs* The image.

[in] *rhs* The image.

[in] f The predicate.

Definition at line 222 of file predicate.hh.

9.139.2.4 template<typename I , typename F > bool mln::test::predicate (const Image< I > & ima, const Function_v2b< F > & f) [inline]

Test if all pixel values of `ima` verify the predicate `f`.

Parameters

[in] ima The image.

[in] f The predicate.

Definition at line 207 of file predicate.hh.

Referenced by `mln::operator<()`, `mln::operator<=()`, `mln::operator==()`, and `positive()`.

9.140 mln::test::impl Namespace Reference

Implementation namespace of test namespace.

9.140.1 Detailed Description

Implementation namespace of test namespace.

9.141 mln::topo Namespace Reference

Namespace of "point-wise" expression tools.

Classes

- class [adj_higher_dim_connected_n_face_bkd_iter](#)
Backward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an `mln::complex<D>`.
- class [adj_higher_dim_connected_n_face_fwd_iter](#)
Forward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an `mln::complex<D>`.
- class [adj_higher_face_bkd_iter](#)
Backward iterator on all the adjacent (n+1)-faces of the n-face of an `mln::complex<D>`.
- class [adj_higher_face_fwd_iter](#)
Forward iterator on all the adjacent (n+1)-faces of the n-face of an `mln::complex<D>`.
- class [adj_lower_dim_connected_n_face_bkd_iter](#)

Backward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>.

- class [adj_lower_dim_connected_n_face_fwd_iter](#)

Forward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>.

- class [adj_lower_face_bkd_iter](#)

Backward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

- class [adj_lower_face_fwd_iter](#)

Forward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

- class [adj_lower_higher_face_bkd_iter](#)

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

- class [adj_lower_higher_face_fwd_iter](#)

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

- class [adj_m_face_bkd_iter](#)

Backward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

- class [adj_m_face_fwd_iter](#)

Forward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

- class [algebraic_face](#)

Algebraic face handle in a complex; the face dimension is dynamic.

- class [algebraic_n_face](#)

Algebraic N-face handle in a complex.

- class [center_only_iter](#)

Iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

- class [centered_bkd_iter_adapter](#)

Forward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

- class [centered_fwd_iter_adapter](#)

Backward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

- class [complex](#)

General complex of dimension D.

- class [face](#)

Face handle in a complex; the face dimension is dynamic.

- class [face_bkd_iter](#)

Backward iterator on all the faces of an mln::complex<D>.

- class [face_fwd_iter](#)

Forward iterator on all the faces of an `mln::complex<D>`.

- struct `is_n_face`

A functor testing whether a `mln::complex_psite` is an N -face.

- struct `is_simple_2d_t`

Test if a point is simple or not.

- class `is_simple_cell`

A predicate for the simplicity of a point based on the collapse property of the attachment.

- class `n_face`

N -face handle in a complex.

- class `n_face_bkd_iter`

Backward iterator on all the faces of an `mln::complex<D>`.

- class `n_face_fwd_iter`

Forward iterator on all the faces of an `mln::complex<D>`.

- class `n_faces_set`

Set of face handles of dimension N .

- class `static_n_face_bkd_iter`

Backward iterator on all the N -faces of a `mln::complex<D>`.

- class `static_n_face_fwd_iter`

Forward iterator on all the N -faces of a `mln::complex<D>`.

Functions

- template<unsigned D, typename G >

`void detach (const complex_psite< D, G > &f, complex_image< D, G, bool > &ima)`

Detach the cell corresponding to f from ima .

- template<unsigned D, typename G >

`bool is_facet (const complex_psite< D, G > &f)`

Is f a facet, i.e., a face not “included in” (adjacent to) a face of higher dimension?

- template<unsigned D>

`algebraic_face< D > make_algebraic_face (const face< D > &f, bool sign)`

Create an algebraic face handle of a D -complex.

- template<unsigned D>

`std::ostream & operator<< (std::ostream &ostr, const face< D > &f)`

Print an `mln::topo::face`.

- template<unsigned N, unsigned D>

`std::ostream & operator<< (std::ostream &ostr, const n_face< N, D > &f)`

Print an `mln::topo::n_face`.

- template<unsigned D>
`std::ostream & operator<< (std::ostream &ostr, const complex< D > &c)`

Pretty print a complex.

- template<unsigned D>
`std::ostream & operator<< (std::ostream &ostr, const algebraic_face< D > &f)`

Print an `mln::topo::algebraic_face`.

- template<unsigned N, unsigned D>

`std::ostream & operator<< (std::ostream &ostr, const algebraic_n_face< N, D > &f)`

Print an `mln::topo::algebraic_n_face`.

- template<unsigned D>
`bool operator== (const complex< D > &lhs, const complex< D > &rhs)`

Compare two complexes for equality.

- template<unsigned D>
`algebraic_face< D > operator- (const face< D > &f)`

Inversion operators.

- template<unsigned D>
`bool operator== (const algebraic_face< D > &lhs, const algebraic_face< D > &rhs)`

Comparison of two instances of `mln::topo::algebraic_face`.

- template<unsigned D>

`bool operator!= (const algebraic_face< D > &lhs, const algebraic_face< D > &rhs)`

Is lhs different from rhs?

- template<unsigned D>

`bool operator< (const algebraic_face< D > &lhs, const algebraic_face< D > &rhs)`

Is lhs “less” than rhs?

- template<unsigned N, unsigned D>

`algebraic_n_face< N, D > operator- (const n_face< N, D > &f)`

Inversion operators.

- template<unsigned N, unsigned D>

`bool operator== (const algebraic_n_face< N, D > &lhs, const algebraic_n_face< N, D > &rhs)`

Comparison of two instances of `mln::topo::algebraic_n_face`.

- template<unsigned N, unsigned D>

`bool operator!= (const algebraic_n_face< N, D > &lhs, const algebraic_n_face< N, D > &rhs)`

Is lhs different from rhs?

- template<unsigned N, unsigned D>

`bool operator< (const algebraic_n_face< N, D > &lhs, const algebraic_n_face< N, D > &rhs)`

Is lhs "less" than rhs?

- template<unsigned D>
`algebraic_n_face< 1, D > edge` (const `n_face< 0, D > &f1`, const `n_face< 0, D > &f2`)
Helpers.

- template<unsigned D>
`bool operator==` (const `face< D > &lhs`, const `face< D > &rhs`)
Comparison of two instances of `mln::topo::face`.

- template<unsigned D>
`bool operator!=` (const `face< D > &lhs`, const `face< D > &rhs`)
Is lhs different from rhs?

- template<unsigned D>
`bool operator<` (const `face< D > &lhs`, const `face< D > &rhs`)
Is lhs "less" than rhs?

- template<unsigned N, unsigned D>
`bool operator==` (const `n_face< N, D > &lhs`, const `n_face< N, D > &rhs`)
Comparison of two instances of `mln::topo::n_face`.

- template<unsigned N, unsigned D>
`bool operator!=` (const `n_face< N, D > &lhs`, const `n_face< N, D > &rhs`)
Is lhs different from rhs?

- template<unsigned N, unsigned D>
`bool operator<` (const `n_face< N, D > &lhs`, const `n_face< N, D > &rhs`)
Is lhs "less" than rhs?

- template<unsigned N, unsigned D>
`n_faces_set< N, D > operator+` (const `algebraic_n_face< N, D > &f1`, const `algebraic_n_face< N, D > &f2`)
Addition.

- template<unsigned N, unsigned D>
`n_faces_set< N, D > operator-` (const `algebraic_n_face< N, D > &f1`, const `algebraic_n_face< N, D > &f2`)
Subtraction.

9.141.1 Detailed Description

Namespace of "point-wise" expression tools.

9.141.2 Function Documentation

9.141.2.1 template<unsigned D, typename G> void mln::topo::detach (const complex_psite< D, G > & f, complex_image< D, G, bool > & ima) [inline]

Detach the cell corresponding to *f* from *ima*.

Precondition

f is a facet (it does not belong to any face of higher dimension).
ima is an image of Boolean values.

Definition at line 58 of file detach.hh.

References mln::make::detachment(), mln::data::fill(), and is_facet().

9.141.2.2 template<unsigned D> algebraic_n_face< 1, D > mln::topo::edge (const n_face< 0, D > & f1, const n_face< 0, D > & f2)

Helpers.

Return the algebraic 1-face (edge) linking the 0-faces (vertices) *f1* and *f2*. If there is no 1-face between *f1* and *f2*, return an invalid 1-face.

Precondition

f1 and *f2* must belong to the same complex.

Note: this routine assumes the complex is not degenerated, i.e,

- it does not check that *f1* and *f2* are the only 0-faces adjacent to an hypothetical 1-face; it just checks that *f1* and *f2* share a common 1-face;
- if there are several adjacent 1-faces shared by *f1* and *f2* (if the complex is ill-formed), there is no guarantee on the returned 1-face (the current implementation return the first 1-face found, but client code should not rely on this implementation-defined behavior).

Definition at line 286 of file algebraic_n_face.hh.

References mln::topo::n_face< N, D >::higher_dim_adj_faces().

9.141.2.3 template<unsigned D, typename G> bool mln::topo::is_facet (const complex_psite< D, G > & f) [inline]

Is *f* a facet, i.e., a face not “included in” (adjacent to) a face of higher dimension?

Definition at line 58 of file is_facet.hh.

Referenced by mln::make::attachment(), mln::make::cell(), detach(), and mln::make::detachment().

9.141.2.4 template<unsigned D> algebraic_face< D > mln::topo::make_algebraic_face (const face< D > & f, bool sign)

Create an algebraic face handle of a D-complex.

Definition at line 211 of file algebraic_face.hh.

9.141.2.5 template<unsigned D> bool mln::topo::operator!= (const algebraic_face< D > & lhs, const algebraic_face< D > & rhs) [inline]

Is *lhs* different from *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 250 of file algebraic_face.hh.

References mln::topo::face< D >::cplx().

9.141.2.6 template<unsigned D> bool mln::topo::operator!= (const face< D > & lhs, const face< D > & rhs) [inline]

Is *lhs* different from *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 394 of file face.hh.

References mln::topo::face< D >::cplx().

9.141.2.7 template<unsigned N, unsigned D> bool mln::topo::operator!= (const algebraic_n_face< N, D > & lhs, const algebraic_n_face< N, D > & rhs) [inline]

Is *lhs* different from *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 250 of file algebraic_n_face.hh.

References mln::topo::n_face< N, D >::cplx().

9.141.2.8 template<unsigned N, unsigned D> bool mln::topo::operator!= (const n_face< N, D > & lhs, const n_face< N, D > & rhs) [inline]

Is *lhs* different from *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 291 of file n_face.hh.

References mln::topo::n_face< N, D >::cplx().

9.141.2.9 template<unsigned N, unsigned D> n_faces_set< N, D > mln::topo::operator+ (const algebraic_n_face< N, D > & f1, const algebraic_n_face< N, D > & f2) [inline]

Addition.

Definition at line 206 of file n_faces_set.hh.

References mln::topo::n_faces_set< N, D >::add().

9.141.2.10 template<unsigned N, unsigned D> algebraic_n_face< N, D > mln::topo::operator- (const n_face< N, D > & f)

Inversion operators.

Definition at line 221 of file algebraic_n_face.hh.

9.141.2.11 template<unsigned N, unsigned D> n_faces_set< N, D > mln::topo::operator- (const algebraic_n_face< N, D > & f1, const algebraic_n_face< N, D > & f2) [inline]

Subtraction.

Definition at line 284 of file n_faces_set.hh.

References mln::topo::n_faces_set< N, D >::add().

9.141.2.12 template<unsigned D> algebraic_face< D > mln::topo::operator- (const face< D > & f)

Inversion operators.

Definition at line 219 of file algebraic_face.hh.

9.141.2.13 template<unsigned N, unsigned D> bool mln::topo::operator< (const n_face< N, D > & lhs, const n_face< N, D > & rhs) [inline]

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting face handles.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 301 of file n_face.hh.

9.141.2.14 template<unsigned D> bool mln::topo::operator< (const face< D > & lhs, const face< D > & rhs) [inline]

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting face handles.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Arguments *lhs* and *rhs* must have the same dimension.

Definition at line 404 of file face.hh.

9.141.2.15 template<unsigned D> bool mln::topo::operator<(const algebraic_face< D > & lhs, const algebraic_face< D > & rhs) [inline]

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting algebraic face handles.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Arguments *lhs* and *rhs* must have the same dimension.

Definition at line 260 of file algebraic_face.hh.

9.141.2.16 template<unsigned N, unsigned D> bool mln::topo::operator<(const algebraic_n_face< N, D > & lhs, const algebraic_n_face< N, D > & rhs) [inline]

Is *lhs* “less” than *rhs*?

This comparison is required by algorithms sorting algebraic face handles.

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 261 of file algebraic_n_face.hh.

9.141.2.17 template<unsigned N, unsigned D> std::ostream & mln::topo::operator<<(std::ostream & ostr, const algebraic_n_face< N, D > & f) [inline]

Print an [mln::topo::algebraic_n_face](#).

Definition at line 273 of file algebraic_n_face.hh.

9.141.2.18 template<unsigned D> std::ostream & mln::topo::operator<<(std::ostream & ostr, const face< D > & f) [inline]

Print an [mln::topo::face](#).

Definition at line 416 of file face.hh.

9.141.2.19 template<unsigned N, unsigned D> std::ostream & mln::topo::operator<<(std::ostream & ostr, const n_face< N, D > & f) [inline]

Print an [mln::topo::n_face](#).

Definition at line 312 of file n_face.hh.

9.141.2.20 template<unsigned D> std::ostream & mln::topo::operator<< (std::ostream & *ostr*, const complex< D > & *c*) [inline]

Pretty print a complex.

Definition at line 670 of file complex.hh.

References mln::topo::complex< D >::print().

9.141.2.21 template<unsigned D> std::ostream & mln::topo::operator<< (std::ostream & *ostr*, const algebraic_face< D > & *f*) [inline]

Print an [mln::topo::algebraic_face](#).

Definition at line 273 of file algebraic_face.hh.

9.141.2.22 template<unsigned N, unsigned D> bool mln::topo::operator== (const algebraic_n_face< N, D > & *lhs*, const algebraic_n_face< N, D > & *rhs*) [inline]

Comparison of two instances of [mln::topo::algebraic_n_face](#).

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 239 of file algebraic_n_face.hh.

References mln::topo::n_face< N, D >::cplx(), mln::topo::n_face< N, D >::face_id(), and mln::topo::algebraic_n_face< N, D >::sign().

9.141.2.23 template<unsigned D> bool mln::topo::operator== (const complex< D > & *lhs*, const complex< D > & *rhs*) [inline]

Compare two complexes for equality.

Definition at line 657 of file complex.hh.

9.141.2.24 template<unsigned D> bool mln::topo::operator== (const face< D > & *lhs*, const face< D > & *rhs*) [inline]

Comparison of two instances of [mln::topo::face](#).

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 384 of file face.hh.

References mln::topo::face< D >::cplx(), mln::topo::face< D >::face_id(), and mln::topo::face< D >::n().

9.141.2.25 template<unsigned D> bool mln::topo::operator==(const algebraic_face< D > & lhs, const algebraic_face< D > & rhs) [inline]

Comparison of two instances of [mln::topo::algebraic_face](#).

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 237 of file [algebraic_face.hh](#).

References [mln::topo::face< D >::cplx\(\)](#), [mln::topo::face< D >::face_id\(\)](#), [mln::topo::face< D >::n\(\)](#), and [mln::topo::algebraic_face< D >::sign\(\)](#).

9.141.2.26 template<unsigned N, unsigned D> bool mln::topo::operator==(const n_face< N, D > & lhs, const n_face< N, D > & rhs) [inline]

Comparison of two instances of [mln::topo::n_face](#).

Is *lhs* equal to *rhs*?

Precondition

Arguments *lhs* and *rhs* must belong to the same [mln::topo::complex](#).

Definition at line 281 of file [n_face.hh](#).

References [mln::topo::n_face< N, D >::cplx\(\)](#), and [mln::topo::n_face< N, D >::face_id\(\)](#).

9.142 mln::trace Namespace Reference

Namespace of routines related to the trace mechanism.

9.142.1 Detailed Description

Namespace of routines related to the trace mechanism.

9.143 mln::trait Namespace Reference

Namespace where traits are defined.

9.143.1 Detailed Description

Namespace where traits are defined. Namespace for image traits.

9.144 mln::transform Namespace Reference

Namespace of transforms.

Functions

- template<typename I , typename N , typename D >
`util::couple< mln::trait::ch_value< I, D >::ret, mln::trait::ch_value< I, typename I::psite >::ret >`
`distance_and_closest_point_geodesic (const Image< I > &input, const Neighborhood< N > &nbh,`
`D max)`
Discrete geodesic distance transform.
- template<typename P , typename N , typename D >
`util::couple< mln_image_from_grid(mln_grid(P), D), mln_image_from_grid(mln_grid(P),`
`unsigned)>` `distance_and_closest_point_geodesic (const p_array< P > &pset, const box< P`
`> &closest_point_domain, const Neighborhood< N > &nbh, D max)`
Discrete geodesic distance transform.
- template<typename I , typename N , typename D >
`util::couple< mln::trait::ch_value< I, D >::ret, I >` `distance_and_influence_zone_geodesic (const`
`Image< I > &input, const Neighborhood< N > &nbh, D max)`
Discrete geodesic distance transform.
- template<typename I , typename N , typename W , typename D >
`mln::trait::ch_value< I, D >::ret` `distance_front (const Image< I > &input, const Neighborhood<`
`N > &nbh, const Weighted_Window< W > &w_win, D max)`
Discrete front distance transform.
- template<typename I , typename N , typename D >
`mln::trait::ch_value< I, D >::ret` `distance_geodesic (const Image< I > &input, const Neighborhood<`
`N > &nbh, D max)`
Discrete geodesic distance transform.
- template<typename I >
`image2d< float >` `hough (const Image< I > &input_)`
Compute the hough transform from a binary image.
- template<typename I , typename N , typename W >
`mln::trait::concrete< I >::ret` `influence_zone_front (const Image< I > &input, const Neighborhood< N > &nbh, const Weighted_Window< W > &w_win)`
Influence zone transform.
- template<typename I , typename N , typename W , typename D >
`mln::trait::concrete< I >::ret` `influence_zone_front (const Image< I > &input, const Neighborhood< N > &nbh, const Weighted_Window< W > &w_win, D max)`
Influence zone transform.
- template<typename I , typename N >
`mln::trait::concrete< I >::ret` `influence_zone_geodesic (const Image< I > &input, const Neighborhood< N > &nbh)`
Geodesic influence zone transform.
- template<typename I , typename N , typename D >
`mln::trait::concrete< I >::ret` `influence_zone_geodesic_saturated (const Image< I > &input, const Neighborhood< N > &nbh, const D &max, const typename I::value &background_value)`
Geodesic influence zone transform.

- template<typename I , typename N , typename D >
`mln::trait::concrete< I >::ret influence_zone_geodesic_saturated (const Image< I > &input, const Neighborhood< N > &nbh, const D &max)`

9.144.1 Detailed Description

Namespace of transforms.

9.144.2 Function Documentation

- 9.144.2.1 template<typename I , typename N , typename D > util::couple<
`mln::trait::ch_value< I, D >::ret, mln::trait::ch_value< I, typename I::psite >::ret >`
`mln::transform::distance_and_closest_point_geodesic (const Image< I > & input,`
`const Neighborhood< N > & nbh, D max) [inline]`**

Discrete geodesic distance transform.

Parameters

- [in] **input** `Image` from which the geodesic distance is computed.
- [in] **nbh** `Neighborhood`
- [in] **max** Max distance of propagation.

Returns

a couple of images. The first one is the distance map and the second one is the closest point image.
The closest point image contains sites.

Postcondition

The returned images have the same domain as `input`.

Definition at line 90 of file `distance_and_closest_point_geodesic.hh`.

References `mln::make::couple()`, and `distance_geodesic()`.

- 9.144.2.2 template<typename P , typename N , typename D > util::couple<
`mln_image_from_grid(mln_grid(P), D), mln_image_from_grid(mln_grid(P),`
`unsigned)> mln::transform::distance_and_closest_point_geodesic (const p_array< P`
`> & pset, const box< P > & closest_point_domain, const Neighborhood< N > & nbh,`
`D max) [inline]`**

Discrete geodesic distance transform.

Parameters

- [in] **pset** an array of sites.
- [in] **closest_point_domain** domain of the returned image.
- [in] **nbh** neighborhood
- [in] **max** max distance of propagation.

Returns

A couple of images. The first one is the distance map and the second one is the closest point image. The closest point image contains site indexes.

Postcondition

The returned image domains are defined on `closest_point_domain`.

Definition at line 110 of file `distance_and_closest_point_geodesic.hh`.

References `mln::geom::bbox()`, `mln::make::couple()`, `distance_geodesic()`, `mln::data::fill()`, and `mln::box< P >::is_valid()`.

9.144.2.3 template<typename I , typename N , typename D > util::couple< mln::trait::ch_value< I, D >::ret, I > mln::transform::distance_and_influence_zone_geodesic (const Image< I > & *input*, const Neighborhood< N > & *ngh*, D *max*) [inline]

Discrete geodesic distance transform.

Parameters

[in] *input* `Image` from which the geodesic distance is computed.

[in] *ngh* `Neighborhood`

[in] *max* Max distance of propagation.

Returns

a couple of images. The first one is the distance map and the second one is the closest point image. The closest point image contains sites.

Postcondition

The returned images have the same domain as *input*.

Definition at line 69 of file `distance_and_influence_zone_geodesic.hh`.

References `mln::make::couple()`, and `distance_geodesic()`.

9.144.2.4 template<typename I , typename N , typename W , typename D > mln::trait::ch_value< I, D >::ret mln::transform::distance_front (const Image< I > & *input*, const Neighborhood< N > & *ngh*, const Weighted_Window< W > & *w_win*, D *max*) [inline]

Discrete front distance transform.

Definition at line 56 of file `transform/distance_front.hh`.

9.144.2.5 template<typename I , typename N , typename D > mln::trait::ch_value< I, D >::ret mln::transform::distance_geodesic (const Image< I > & *input*, const Neighborhood< N > & *ngh*, D *max*) [inline]

Discrete geodesic distance transform.

Definition at line 55 of file `transform/distance_geodesic.hh`.

Referenced by `distance_and_closest_point_geodesic()`, and `distance_and_influence_zone_geodesic()`.

9.144.2.6 template<typename I > image2d< float > mln::transform::hough (const Image< I > & *input_*)

Compute the hough transform from a binary image.

Objects used for computation must be set to 'true'.

Parameters

[in] *input_* A binary image.

Returns

A 2D image of float. Rows are used for the distance and columns are used for the angles. Angles go from 0 to 359. Distance goes from 0 to the maximum distance between the center and a corner. The site having the maximum value indicates through its column index the document inclination.

Definition at line 98 of file hough.hh.

References mln::opt::at(), mln::data::fill(), mln::geom::min_col(), mln::geom::min_row(), mln::geom::ncols(), and mln::geom::nrows().

9.144.2.7 template<typename I , typename N , typename W > mln::trait::concrete< I >::ret mln::transform::influence_zone_front (const Image< I > & *input*, const Neighborhood< N > & *nbh*, const Weighted_Window< W > & *w_win*)

Influence zone transform.

Definition at line 78 of file influence_zone_front.hh.

References influence_zone_front().

9.144.2.8 template<typename I , typename N , typename W , typename D > mln::trait::concrete< I >::ret mln::transform::influence_zone_front (const Image< I > & *input*, const Neighborhood< N > & *nbh*, const Weighted_Window< W > & *w_win*, D *max*)

Influence zone transform.

Definition at line 60 of file influence_zone_front.hh.

References mln::canvas::distance_front().

Referenced by influence_zone_front().

9.144.2.9 template<typename I , typename N > mln::trait::concrete< I >::ret mln::transform::influence_zone_geodesic (const Image< I > & *input*, const Neighborhood< N > & *nbh*)

Geodesic influence zone transform.

Parameters

[in] *input* An image.

[in] *nbh* A neighborhood.

Returns

An image of influence zone.

Definition at line 216 of file influence_zone_geodesic.hh.

9.144.2.10 template<typename I , typename N , typename D > mln::trait::concrete< I >::ret mln::transform::influence_zone_geodesic_saturated (const Image< I > & *input*, const Neighborhood< N > & *nbh*, const D & *max*, const typename I::value & *background_value*)

Geodesic influence zone transform.

Parameters

- [in] *input* An image.
- [in] *nbh* A neighborhood.
- [in] *max* The maximum influence zone distance.
- [in] *background_value* The value used as background (i.e. not propagated).

Returns

An image of influence zone.

Definition at line 73 of file influence_zone_geodesic_saturated.hh.

References mln::canvas::distance_geodesic().

Referenced by influence_zone_geodesic_saturated().

9.144.2.11 template<typename I , typename N , typename D > mln::trait::concrete< I >::ret mln::transform::influence_zone_geodesic_saturated (const Image< I > & *input*, const Neighborhood< N > & *nbh*, const D & *max*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 93 of file influence_zone_geodesic_saturated.hh.

References influence_zone_geodesic_saturated(), and mln::literal::zero.

9.145 mln::util Namespace Reference

Namespace of tools using for more complex algorithm.

Namespaces

- namespace [impl](#)
Implementation namespace of util namespace.

Classes

- class [adjacency_matrix](#)
A class of adjacency matrix.

- class [array](#)
A dynamic array class.
- class [branch](#)
Class of generic branch.
- class [branch_iter](#)
Basic 2D image class.
- class [branch_iter_ind](#)
Basic 2D image class.
- class [couple](#)
Definition of a couple.
- struct [eat](#)
Eat structure.
- class [edge](#)
Edge of a graph G .
- class [fibonacci_heap](#)
Fibonacci heap.
- class [graph](#)
Undirected graph.
- class [greater_point](#)
A “greater than” functor comparing points w.r.t.
- class [greater_psite](#)
A “greater than” functor comparing psites w.r.t.
- class [head](#)
Top structure of the soft heap.
- struct [ignore](#)
Ignore structure.
- struct [ilcell](#)
Element of an item list. Store the data (key) used in [soft_heap](#).
- class [line_graph](#)
Undirected line graph of a graph of type G .
- struct [nil](#)
Nil structure.
- class [node](#)

Meta-data of an element in the heap.

- class [object_id](#)

Base class of an object id.

- struct [ord](#)

Function-object that defines an ordering between objects with type $T : \text{lhs} R \text{rhs}$.

- struct [ord_pair](#)

Ordered pair structure s.a.

- struct [pix](#)

Structure pix.

- class [set](#)

An "efficient" mathematical set class.

- class [site_pair](#)

A pair of sites.

- class [soft_heap](#)

Soft heap.

- class [timer](#)

Timer structure.

- struct [tracked_ptr](#)

Smart pointer for shared data with tracking.

- class [tree](#)

Class of generic tree.

- class [tree_node](#)

Class of generic [tree_node](#) for tree.

- class [vertex](#)

[Vertex](#) of a graph G .

- struct [yes](#)

[Object](#) that always says "yes".

Typedefs

- typedef [object_id](#)< vertex_tag, unsigned > [vertex_id_t](#)

[Vertex](#) id type.

Functions

- template<typename I , typename J >
`void display_branch (const Image< J > &ima_, tree_node< I > *tree_node)`
Display an arborescence from `tree_node`.
- template<typename I , typename J >
`void display_tree (const Image< J > &ima_, tree< I > &tree)`
Display a tree.
- template<typename I >
`I::psite lemmings (const Image< I > &ima, const typename I::psite &pt, const typename I::psite::delta &dpt, const typename I::value &val)`
Launch a lemmings on an image.
- template<typename I >
`greater_point< I > make_greater_point (const Image< I > &ima)`
Helper to build a `mln::util::greater_point`.
- template<typename I >
`greater_psite< I > make_greater_psite (const Image< I > &ima)`
Helper to build a `mln::util::greater_psite`.
- template<typename G >
`bool operator< (const vertex< G > &lhs, const vertex< G > &rhs)`
Less operator. Test whether `lhs.id() < rhs.id()`.
- template<typename G >
`std::ostream & operator<< (std::ostream &ostr, const vertex< G > &v)`
Push the vertex `v` in the output stream `ostr`.
- template<typename T >
`std::ostream & operator<< (std::ostream &ostr, const array< T > &a)`
Operator<<.
- template<typename G >
`bool operator== (const vertex< G > &v1, const vertex< G > &v2)`
Equality operator.
- template<typename T >
`bool operator== (const array< T > &lhs, const array< T > &rhs)`
Operator==.
- template<typename T >
`bool ord_strict (const T &lhs, const T &rhs)`
Routine to test if `lhs` is strictly "less-than" `rhs`.
- template<typename T >
`bool ord_weak (const T &lhs, const T &rhs)`
Routine to test if `lhs` is "less-than or equal-to" `rhs`.

- template<typename T , typename I >
void **tree_fast_to_image** (tree_fast< T > &**tree**, Image< I > &**output_**)
- template<typename T >
tree_fast< T > **tree_to_fast** (tree< T > &**input**)
Facade.
- template<typename T , typename I >
void **tree_to_image** (tree< T > &**tree**, Image< I > &**output_**)
Convert a tree into an image.

9.145.1 Detailed Description

Namespace of tools using for more complex algorithm. Forward declaration.

9.145.2 Typedef Documentation

9.145.2.1 **typedef object_id<vertex_tag, unsigned> mln::util::vertex_id_t**

Vertex id type.

Definition at line 43 of file graph_ids.hh.

9.145.3 Function Documentation

9.145.3.1 **template<typename I , typename J > void mln::util::display_branch (const Image< J > & *ima_*, tree_node< I > * *tree_node*) [inline]**

Display an arborescence from **tree_node**.

Parameters

- [in] **ima_** The domain of output image.
- [in] **tree_node** The root **tree_node** to display.

Definition at line 210 of file tree_to_image.hh.

References mln::data::fill().

9.145.3.2 **template<typename I , typename J > void mln::util::display_tree (const Image< J > & *ima_*, tree< I > & *tree*) [inline]**

Display a tree.

Parameters

- [in] **ima_** The domain of output image.
- [in] **tree** The tree to display.

Definition at line 192 of file tree_to_image.hh.

References mln::util::tree< T >::root().

9.145.3.3 template<typename I> I::psite mln::util::lemmings (const Image< I > & *ima*, const typename I::psite & *pt*, const typename I::psite::delta & *dpt*, const typename I::value & *val*)

Launch a lemmings on an image.

A lemmings is the point *pt* that you put on an image *ima*. This point will move through the image using the delta-point *dpt* while consider his value on the given image.

Returns

The first point that is not in the domain *domain* or which value on the given image is different to the value *val*.

Precondition

The domain *domain* must be contained in the domain of *ima*.

Definition at line 104 of file lemmings.hh.

9.145.3.4 template<typename I> greater_point< I > mln::util::make_greater_point (const Image< I > & *ima*)

Helper to build a [mln::util::greater_point](#).

Definition at line 82 of file greater_point.hh.

9.145.3.5 template<typename I> greater_psite< I > mln::util::make_greater_psite (const Image< I > & *ima*)

Helper to build a [mln::util::greater_psite](#).

Definition at line 82 of file greater_psite.hh.

9.145.3.6 template<typename G> bool mln::util::operator< (const vertex< G > & *lhs*, const vertex< G > & *rhs*) [inline]

Less operator. Test whether *lhs.id()* < *rhs.id()*.

Definition at line 390 of file vertex.hh.

9.145.3.7 template<typename G> std::ostream & mln::util::operator<< (std::ostream & *ostr*, const vertex< G > & *v*) [inline]

Push the vertex *v* in the output stream *ostr*.

Definition at line 372 of file vertex.hh.

9.145.3.8 template<typename T> std::ostream & mln::util::operator<< (std::ostream & *ostr*, const array< T > & *a*)

Operator<<.

Definition at line 796 of file util/array.hh.

References [mln::util::array< T >::nelements\(\)](#).

9.145.3.9 template<typename G> bool mln::util::operator==(const vertex<G> & v1, const vertex<G> & v2) [inline]

Equality operator.

Test whether two vertices have the same id.

Definition at line 380 of file vertex.hh.

References mln::util::vertex< G >::graph(), and mln::util::vertex< G >::id().

9.145.3.10 template<typename T> bool mln::util::operator==(const array<T> & lhs, const array<T> & rhs)

Operator==.

Definition at line 815 of file util/array.hh.

References mln::util::array< T >::std_vector().

9.145.3.11 template<typename T> bool mln::util::ord_strict(const T & lhs, const T & rhs) [inline]

Routine to test if *lhs* is strictly "less-than" *rhs*.

Definition at line 90 of file util/ord.hh.

Referenced by mln::util::ord_pair< T >::change_both(), mln::util::ord_pair< T >::change_first(), and mln::util::ord_pair< T >::change_second().

9.145.3.12 template<typename T> bool mln::util::ord_weak(const T & lhs, const T & rhs) [inline]

Routine to test if *lhs* is "less-than or equal-to" *rhs*.

Definition at line 101 of file util/ord.hh.

Referenced by mln::util::ord_pair< T >::change_both(), mln::util::ord_pair< T >::change_first(), mln::util::ord_pair< T >::change_second(), and mln::box< P >::is_valid().

9.145.3.13 template<typename T, typename I> void mln::util::tree_fast_to_image(tree_fast< T > & tree, Image< I > & output_) [inline]

Convert a tree_fast into an image.

Parameters

[in] *tree* The tree to convert.

[out] *output_* The image containing tree informations.

Definition at line 99 of file tree_fast_to_image.hh.

9.145.3.14 template<typename T> tree_fast< T > mln::util::tree_to_fast(tree< T > & input) [inline]

Facade.

Convert a tree into an tree_fast.

Parameters

[in] ***input*** The tree to convert.

Returns

The tree_fast containing tree informations.

Definition at line 90 of file tree_to_fast.hh.

References mln::util::tree< T >::root().

9.145.3.15 template<typename T , typename I > void mln::util::tree_to_image (tree< T > & tree, Image< I > & output_) [inline]

Convert a tree into an image.

Parameters

[in] ***tree*** The tree to convert.

[out] ***output_*** The image containing tree information.

Definition at line 178 of file tree_to_image.hh.

9.146 mln::util::impl Namespace Reference

Implementation namespace of util namespace.

9.146.1 Detailed Description

Implementation namespace of util namespace.

9.147 mln::value Namespace Reference

Namespace of materials related to pixel value types.

Namespaces

- namespace **impl**

Implementation namespace of value namespace.

Classes

- class **float01**

Class for floating values restricted to the interval [0..1] and discretized with n bits.

- struct [float01_f](#)
Class for floating values restricted to the interval [0..1].
- struct [graylevel](#)
General gray-level class on n bits.
- struct [graylevel_f](#)
General gray-level class on n bits.
- struct [int_s](#)
Signed integer value class.
- struct [int_u](#)
Unsigned integer value class.
- struct [int_u_sat](#)
Unsigned integer value class with saturation behavior.
- struct [Integer](#)
Concept of integer.
- struct [Integer< void >](#)
Category flag type.
- struct [label](#)
Label value class.
- struct [lut_vec](#)
Class that defines FIXME.
- class [proxy](#)
Generic proxy class for an image pixel value.
- struct [rgb](#)
Color class for red-green-blue where every component is n-bit encoded.
- struct [set](#)
Class that defines the set of values of type T.
- class [sign](#)
The sign class represents the value type composed by the set (-1, 0, 1) sign value type is a subset of the int value type.
- struct [stack_image](#)
Stack image class.
- struct [super_value< sign >](#)
Specializations:

- struct [value_array](#)
Generic array class over indexed by a value set with type T.

Typedefs

- [typedef float01_< 16 > float01_16](#)
Alias for 16 bit [float01](#).
- [typedef float01_< 8 > float01_8](#)
Alias for 8 bit [float01](#).
- [typedef graylevel< 16 > gl16](#)
Alias for 16 bit graylevel.
- [typedef graylevel< 8 > gl8](#)
Alias for 8 bit graylevel.
- [typedef graylevel_f glf](#)
Alias for graylevels encoded by float.
- [typedef int_s< 16 > int_s16](#)
Alias for signed 16-bit integers.
- [typedef int_s< 32 > int_s32](#)
Alias for signed 32-bit integers.
- [typedef int_s< 8 > int_s8](#)
Alias for signed 8-bit integers.
- [typedef int_u< 12 > int_u12](#)
Alias for unsigned 12-bit integers.
- [typedef int_u< 16 > int_u16](#)
Alias for unsigned 16-bit integers.
- [typedef mln::value::int_u< 32 > int_u32](#)
Alias for unsigned 32-bit integers.
- [typedef mln::value::int_u< 8 > int_u8](#)
Alias for unsigned 8-bit integers.
- [typedef label< 16 > label_16](#)
Alias for 16-bit integers.
- [typedef label< 32 > label_32](#)
Alias for 32-bit integers.
- [typedef mln::value::label< 8 > label_8](#)

Alias for 8-bit labels.

- `typedef rgb< 16 > rgb16`

Color class for red-green-blue where every component is 16-bit encoded.

- `typedef rgb< 8 > rgb8`

Color class for red-green-blue where every component is 8-bit encoded.

Functions

- `template<typename Dest , typename Src >`
`Dest cast (const Src &src)`

Cast a value src from type Src to type Dest.

- `template<typename V >`
`internal::equiv_< V >::ret equiv (const mln::Value< V > &v)`

Access to the equivalent value.

- `template<unsigned n>`
`rgb< n >::interop operator+ (const rgb< n > &lhs, const rgb< n > &rhs)`

Addition.

- `template<typename H , typename S , typename L >`
`hsl_< H, S, L > operator+ (const hsl_< H, S, L > &lhs, const hsl_< H, S, L > &rhs)`

Addition.

- `template<unsigned n>`
`std::ostream & operator<< (std::ostream &ostr, const label< n > &l)`

Print a label l into the output stream ostr.

- `template<unsigned n>`
`std::ostream & operator<< (std::ostream &ostr, const rgb< n > &c)`

Print an rgb c into the output stream ostr.

- `std::ostream & operator<< (std::ostream &ostr, const graylevel_f &g)`

Op<<.

- `template<typename T >`
`std::ostream & operator<< (std::ostream &ostr, const scalar_< T > &s)`

Print a scalar s in an output stream ostr.

- `template<typename H , typename S , typename L >`
`std::ostream & operator<< (std::ostream &ostr, const hsl_< H, S, L > &c)`

Print an hsl c into the output stream ostr.

- `template<unsigned n>`
`std::ostream & operator<< (std::ostream &ostr, const graylevel< n > &g)`

Op<<.

- template<unsigned n>
`std::ostream & operator<< (std::ostream &ostr, const float01_<n> &f)`
O_p<<.
- `std::ostream & operator<< (std::ostream &ostr, const sign &i)`
Print an signed integer i into the output stream ostr.
- template<unsigned n>
`std::ostream & operator<< (std::ostream &ostr, const int_u_<n> &i)`
Print an unsigned integer i into the output stream ostr.
- template<unsigned n>
`std::ostream & operator<< (std::ostream &ostr, const int_s_<n> &i)`
Print an signed integer i into the output stream ostr.
- template<unsigned n>
`std::ostream & operator<< (std::ostream &ostr, const int_u_sat_<n> &i)`
Print a saturated unsigned integer i into the output stream ostr.
- `bool operator==(const sign &lhs, const sign &rhs)`
Comparaison operator.
- template<typename V >
`V other (const V &val)`
Give an other value than val.
- template<typename H , typename S , typename L >
`hsl_<H, S, L> operator- (const hsl_<H, S, L> &lhs, const hsl_<H, S, L> &rhs)`
Subtraction.
- template<typename H , typename S , typename L , typename S2 >
`hsl_<H, S, L> operator* (const hsl_<H, S, L> &lhs, const mln::value::scalar_<S2> &s)`
Product.
- template<typename H , typename S , typename L , typename S2 >
`hsl_<H, S, L> operator/ (const hsl_<H, S, L> &lhs, const mln::value::scalar_<S2> &s)`
Division.
- template<typename H , typename S , typename L >
`bool operator==(const hsl_<H, S, L> &lhs, const hsl_<H, S, L> &rhs)`
Comparison.
- template<unsigned n>
`rgb<n>::interop operator- (const rgb<n> &lhs, const rgb<n> &rhs)`
Subtraction.

- template<unsigned n, typename S >
`rgb< n >::interop operator*` (const `rgb< n >` &lhs, const `mln::value::scalar_< S >` &s)
Product.
- template<unsigned n, typename S >
`rgb< n >::interop operator/` (const `rgb< n >` &lhs, const `mln::value::scalar_< S >` &s)
Division.
- template<typename I >
`stack_image< 2, const I >` `stack` (const `Image< I >` &ima1, const `Image< I >` &ima2)
Shortcut to build a stack with two images.

9.147.1 Detailed Description

Namespace of materials related to pixel value types.

9.147.2 Typedef Documentation

9.147.2.1 `typedef float01_<16> mln::value::float01_16`

Alias for 16 bit `float01`.

Definition at line 45 of file `float01_16.hh`.

9.147.2.2 `typedef float01_<8> mln::value::float01_8`

Alias for 8 bit `float01`.

Definition at line 45 of file `float01_8.hh`.

9.147.2.3 `typedef graylevel<16> mln::value::gl16`

Alias for 16 bit `graylevel`.

Definition at line 45 of file `gl16.hh`.

9.147.2.4 `typedef graylevel<8> mln::value::gl8`

Alias for 8 bit `graylevel`.

Definition at line 45 of file `gl8.hh`.

9.147.2.5 `typedef graylevel_f mln::value::glf`

Alias for `graylevels` encoded by `float`.

Definition at line 44 of file `glf.hh`.

9.147.2.6 `typedef int_s<16> mln::value::int_s16`

Alias for signed 16-bit integers.

Definition at line 45 of file int_s16.hh.

9.147.2.7 `typedef int_s<32> mln::value::int_s32`

Alias for signed 32-bit integers.

Definition at line 45 of file int_s32.hh.

9.147.2.8 `typedef int_s<8> mln::value::int_s8`

Alias for signed 8-bit integers.

Definition at line 45 of file int_s8.hh.

9.147.2.9 `typedef int_u<12> mln::value::int_u12`

Alias for unsigned 12-bit integers.

Definition at line 45 of file int_u12.hh.

9.147.2.10 `typedef int_u<16> mln::value::int_u16`

Alias for unsigned 16-bit integers.

Definition at line 45 of file int_u16.hh.

9.147.2.11 `typedef mln::value::int_u<32> mln::value::int_u32`

Alias for unsigned 32-bit integers.

Definition at line 45 of file int_u32.hh.

9.147.2.12 `typedef mln::value::int_u<8> mln::value::int_u8`

Alias for unsigned 8-bit integers.

Definition at line 44 of file int_u8.hh.

9.147.2.13 `typedef label<16> mln::value::label_16`

Alias for 16-bit integers.

Definition at line 44 of file label_16.hh.

9.147.2.14 `typedef label<32> mln::value::label_32`

Alias for 32-bit integers.

Definition at line 44 of file label_32.hh.

9.147.2.15 `typedef mln::value::label<8> mln::value::label_8`

Alias for 8-bit labels.

Definition at line 44 of file label_8.hh.

9.147.2.16 `typedef rgb<16> mln::value::rgb16`

Color class for red-green-blue where every component is 16-bit encoded.

Definition at line 45 of file rgb16.hh.

9.147.2.17 `typedef rgb<8> mln::value::rgb8`

Color class for red-green-blue where every component is 8-bit encoded.

Definition at line 45 of file rgb8.hh.

9.147.3 Function Documentation

9.147.3.1 `template<typename Dest , typename Src > Dest mln::value::cast (const Src & src) [inline]`

Cast a value `src` from type `Src` to type `Dest`.

Definition at line 85 of file value/cast.hh.

9.147.3.2 `template<typename V > internal::equiv_< V >::ret mln::value::equiv (const mln::Value< V > & v) [inline]`

Access to the equivalent value.

Definition at line 153 of file equiv.hh.

Referenced by `mln::labeling::superpose()`.

9.147.3.3 `template<unsigned n, typename S > rgb< n >::interop mln::value::operator* (const rgb< n > & lhs, const mln::value::scalar_< S > & s) [inline]`

Product.

Definition at line 717 of file value/rgb.hh.

9.147.3.4 `template<typename H , typename S , typename L , typename S2 > hsl_< H, S, L > mln::value::operator* (const hsl_< H, S, L > & lhs, const mln::value::scalar_< S2 > & s)`

Product.

Definition at line 357 of file hsl.hh.

9.147.3.5 template<unsigned n> rgb<n>::interop mln::value::operator+ (const rgb<n> & lhs, const rgb<n> & rhs) [inline]

Addition.

{

Definition at line 663 of file value/rgb.hh.

9.147.3.6 template<typename H, typename S, typename L> hsl_<H, S, L> mln::value::operator+ (const hsl_<H, S, L> & lhs, const hsl_<H, S, L> & rhs)

Addition.

{

Definition at line 337 of file hsl.hh.

9.147.3.7 template<unsigned n> rgb<n>::interop mln::value::operator- (const rgb<n> & lhs, const rgb<n> & rhs) [inline]

Subtraction.

Definition at line 690 of file value/rgb.hh.

9.147.3.8 template<typename H, typename S, typename L> hsl_<H, S, L> mln::value::operator- (const hsl_<H, S, L> & lhs, const hsl_<H, S, L> & rhs)

Subtraction.

Definition at line 347 of file hsl.hh.

9.147.3.9 template<unsigned n, typename S> rgb<n>::interop mln::value::operator/ (const rgb<n> & lhs, const mln::value::scalar_<S> & s) [inline]

Division.

Definition at line 735 of file value/rgb.hh.

9.147.3.10 template<typename H, typename S, typename L, typename S2> hsl_<H, S, L> mln::value::operator/ (const hsl_<H, S, L> & lhs, const mln::value::scalar_<S2> & s)

Division.

Definition at line 367 of file hsl.hh.

9.147.3.11 template<typename T> std::ostream & mln::value::operator<< (std::ostream & ostr, const scalar_<T> & s) [inline]

Print a scalar s in an output stream ostr.

Definition at line 130 of file scalar.hh.

9.147.3.12 std::ostream & mln::value::operator<< (std::ostream & *ostr*, const sign & *i*) [inline]

Print an signed integer *i* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *i* An sign value

Returns

The modified output stream *ostr*.

Definition at line 184 of file value/sign.hh.

References mln::debug::format().

9.147.3.13 template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & *ostr*, const int_s<n> & *i*) [inline]

Print an signed integer *i* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *i* An signed integer.

Returns

The modified output stream *ostr*.

Definition at line 260 of file int_s.hh.

References mln::debug::format().

9.147.3.14 template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & *ostr*, const graylevel<n> & *g*) [inline]

Op<<.

Definition at line 591 of file graylevel.hh.

9.147.3.15 template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & *ostr*, const int_u<n> & *i*) [inline]

Print an unsigned integer *i* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *i* An unsigned integer.

Returns

The modified output stream `ostr`.

Definition at line 357 of file `int_u.hh`.

References `mln::debug::format()`.

9.147.3.16 `template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & ostr, const int_u_sat<n> & i) [inline]`

Print a saturated unsigned integer `i` into the output stream `ostr`.

Parameters

[in, out] `ostr` An output stream.

[in] `i` A saturated unsigned integer.

Returns

The modified output stream `ostr`.

Definition at line 220 of file `int_u_sat.hh`.

References `mln::debug::format()`.

9.147.3.17 `template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & ostr, const rgb<n> & c) [inline]`

Print an `rgb c` into the output stream `ostr`.

Parameters

[in, out] `ostr` An output stream.

[in] `c` An `rgb`.

Returns

The modified output stream `ostr`.

Definition at line 743 of file `value/rgb.hh`.

References `mln::debug::format()`.

9.147.3.18 `template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & ostr, const float01_<n> & f) [inline]`

Op`<<`.

Definition at line 253 of file `float01_.hh`.

9.147.3.19 template<typename H , typename S , typename L > std::ostream & mln::value::operator<< (std::ostream & ostr, const hsl_< H, S, L > & c) [inline]

Print an hsl *c* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *c* An rgb.

Returns

The modified output stream *ostr*.

Definition at line 326 of file hsl.hh.

References mln::debug::format().

9.147.3.20 template<unsigned n> std::ostream & mln::value::operator<< (std::ostream & ostr, const label< n > & l) [inline]

Print a label *l* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *l* A label.

Returns

The modified output stream *ostr*.

Definition at line 353 of file label.hh.

References mln::debug::format().

9.147.3.21 std::ostream & mln::value::operator<< (std::ostream & ostr, const graylevel_f & g) [inline]

Op<<.

Definition at line 458 of file graylevel_f.hh.

References mln::value::graylevel_f::value().

9.147.3.22 template<typename H , typename S , typename L > bool mln::value::operator== (const hsl_< H, S, L > & lhs, const hsl_< H, S, L > & rhs)

Comparison.

Definition at line 376 of file hsl.hh.

9.147.3.23 bool mln::value::operator== (const sign & lhs, const sign & rhs) [inline]

Comparaison operator.

Definition at line 190 of file value/sign.hh.

9.147.3.24 template<typename V> V mln::value::other (const V & val) [inline]

Give an other value than `val`.

Definition at line 115 of file other.hh.

9.147.3.25 template<typename I> stack_image< 2, const I > mln::value::stack (const Image< I > & ima1, const Image< I > & ima2) [inline]

Shortcut to build a stack with two images.

Definition at line 306 of file stack.hh.

9.148 mln::value::impl Namespace Reference

Implementation namespace of value namespace.

9.148.1 Detailed Description

Implementation namespace of value namespace.

9.149 mln::win Namespace Reference

Namespace of image processing routines related to win.

Classes

- struct [backdiag2d](#)
Diagonal line window defined on the 2D square grid.
- struct [ball](#)
Generic ball window defined on a given grid.
- struct [cube3d](#)
Cube window defined on the 3D grid.
- struct [cuboid3d](#)
Cuboid defined on the 3-D square grid.
- struct [diag2d](#)
Diagonal line window defined on the 2D square grid.

- struct [line](#)
Generic line window defined on a given grid in the given dimension.
- class [multiple](#)
Multiple window.
- class [multiple_size](#)
Definition of a multiple-size window.
- struct [octagon2d](#)
Octagon window defined on the 2D square grid.
- struct [rectangle2d](#)
Rectangular window defined on the 2D square grid.

Typedefs

- typedef [ball< grid::square, def::coord > disk2d](#)
2D disk window; precisely, ball-shaped window defined on the 2D square grid.
- typedef [line< grid::square, 1, def::coord > hline2d](#)
Horizontal line window defined on the 2D square grid.
- typedef [line< grid::tick, 0, def::coord > segment1d](#)
Segment window defined on the 1D grid.
- typedef [line< grid::cube, 0, def::coord > sline3d](#)
Depth line window defined on the 3D cubic grid.
- typedef [ball< grid::cube, def::coord > sphere3d](#)
3D sphere window; precisely, ball-shaped window defined on the 3D cubic grid.
- typedef [line< grid::square, 0, def::coord > vline2d](#)
Vertical line window defined on the 2D square grid.

Functions

- template<typename N1 , typename N2 >
[neighb< typename N1::window::regular > diff](#) (const [Neighborhood< N1 >](#) &nbh1, const [Neighborhood< N2 >](#) &nbh2)
Set difference between a couple of neighborhoods nbh1 and nbh2.
- template<typename W1 , typename W2 >
[mln_regular](#) (W1) diff(const [Window< W1 >](#) &win1
Set difference between a couple of windows win1 and win2.
- template<typename W >
[mln_regular](#) (W) shift(const [Window< W >](#) &win

Shift a window `win` with a delta-point `dp`.

- template<typename W >
`W sym` (const `Window< W >` &`win`)
Give the symmetrical window of `win`.

- template<typename W >
`W sym` (const `Weighted_Window< W >` &`w_win`)
Give the symmetrical weighted window of `w_win`.

9.149.1 Detailed Description

Namespace of image processing routines related to `win`.

9.149.2 Function Documentation

9.149.2.1 template<typename N1 , typename N2 > N2 `neigh< typename N1::window::regular > mln::win::diff` (const `Neighborhood< N1 >` & `nbh1`, const `Neighborhood< N2 >` & `nbh2`)

Set difference between a couple of neighborhoods `nbh1` and `nbh2`.

Definition at line 132 of file `win/diff.hh`.

Referenced by `mln::operator-()`.

9.149.2.2 template<typename W1 , typename W2 > `mln::win::mln_regular` (`W1`) const [inline]

Set difference between a couple of windows `win1` and `win2`.

9.149.2.3 template<typename W > `mln::win::mln_regular` (`W`) const [inline]

Shift a window `win` with a delta-point `dp`.

9.149.2.4 template<typename W > `W mln::win::sym` (const `Window< W >` & `win`) [inline]

Give the symmetrical window of `win`.

Definition at line 59 of file `sym.hh`.

Referenced by `mln::c18()`, `mln::c26()`, `mln::c4_3d()`, `mln::c6()`, `mln::morpho::hit_or_miss_background_-opening()`, `mln::morpho::hit_or_miss_opening()`, `mln::morpho::opening::approx::structural()`, and `mln::morpho::closing::approx::structural()`.

9.149.2.5 template<typename W > `W mln::win::sym` (const `Weighted_Window< W >` & `w_win`) [inline]

Give the symmetrical weighted window of `w_win`.

Definition at line 71 of file sym.hh.

Chapter 10

Class Documentation

10.1 mln::accu::center< P, V > Struct Template Reference

Mass center accumulator.

```
#include <center.hh>
```

Inherits base< V, center< P, V > >.

Public Member Functions

- `bool is_valid () const`
Check whether this accu is able to return a result.
- `unsigned nsites () const`
Return the number of sites taken in consideration.
- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `V to_result () const`
Get the value of the accumulator.
- `void init ()`
Manipulators.

10.1.1 Detailed Description

```
template<typename P, typename V = typename P::vec> struct mln::accu::center< P, V >
```

Mass center accumulator.

Template Parameters

P the type of site.

V the type of vector to be used as result. The default vector type is the one provided by *P*.

Definition at line 55 of file center.hh.

10.1.2 Member Function Documentation

**10.1.2.1 template<typename P , typename V > void mln::accu::center< P, V >::init ()
[inline]**

Manipulators.

Definition at line 116 of file center.hh.

References mln::literal::zero.

**10.1.2.2 template<typename P , typename V > bool mln::accu::center< P, V >::is_valid ()
const [inline]**

Check whether this accu is able to return a result.

Definition at line 160 of file center.hh.

Referenced by mln::accu::center< P, V >::to_result().

**10.1.2.3 template<typename P , typename V > unsigned mln::accu::center< P, V >::nsites ()
const [inline]**

Return the number of sites taken in consideration.

Definition at line 168 of file center.hh.

**10.1.2.4 void mln::Accumulator< center< P, V > >::take_as_init (const T & t)
[inherited]**

Take as initialization the value *t*.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

**10.1.2.5 void mln::Accumulator< center< P, V > >::take_n_times (unsigned n, const T & t)
[inherited]**

Take *n* times the value *t*.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

**10.1.2.6 template<typename P , typename V > V mln::accu::center< P, V >::to_result () const
[inline]**

Get the value of the accumulator.

Definition at line 142 of file center.hh.

References mln::accu::center< P, V >::is_valid().

10.2 mln::accu::convolve< T1, T2, R > Struct Template Reference

Generic convolution accumulator class.

```
#include <convolve.hh>
```

Inherits base< R, convolve< T1, T2, R > >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- R [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.

10.2.1 Detailed Description

```
template<typename T1, typename T2, typename R = typename mln::trait::value_< typename mln::trait::op::times< T1 , T2 >::ret >::sum> struct mln::accu::convolve< T1, T2, R >
```

Generic convolution accumulator class. Parameters T1 and T2 are the type of values to be convolved. Parameter R is the result type.

Definition at line 54 of file accu/convolve.hh.

10.2.2 Member Function Documentation

10.2.2.1 template<typename T1 , typename T2 , typename R > void mln::accu::convolve< T1, T2, R >::init () [inline]

Manipulators.

Definition at line 96 of file accu/convolve.hh.

References mln::literal::zero.

10.2.2.2 template<typename T1 , typename T2 , typename R > bool mln::accu::convolve< T1, T2, R >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 137 of file accu/convolve.hh.

10.2.2.3 void mln::Accumulator< convolve< T1, T2, R > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.2.2.4 void mln::Accumulator< convolve< T1, T2, R > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.2.2.5 template<typename T1 , typename T2 , typename R > R mln::accu::convolve< T1, T2, R >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 129 of file accu/convolve.hh.

10.3 mln::accu::count_adjacent_vertices< F, S > Struct Template Reference

[Accumulator](#) class counting the number of vertices adjacent to a set of mln::p_edges_psite (i.e., a set of edges).

```
#include <count_adjacent_vertices.hh>
```

Inherits base< unsigned, count_adjacent_vertices< F, S > >.

Public Member Functions

- bool [is_valid](#) () const

Return whether this accu can return a result.

- void [take_as_init](#) (const T &t)

Take as initialization the value t .

- void [take_n_times](#) (unsigned n, const T &t)

Take n times the value t .

- unsigned [to_result](#) () const

Get the value of the accumulator.

- void [init \(\)](#)
Manipulators.
- void [set_value \(unsigned c\)](#)
Force the value of the counter to c.

10.3.1 Detailed Description

template<typename F, typename S> struct mln::accu::count_adjacent_vertices< F, S >

Accumulator class counting the number of vertices adjacent to a set of mln::p_edges_psite (i.e., a set of edges). The type to be count is [mln::util::pix< pw::image<F, S> >](#) where F and S are the parameters of this class.

This accumulator is used by mln::closing_area_on_vertices and mln::opening_area_on_vertices.

Definition at line 58 of file accu/count_adjacent_vertices.hh.

10.3.2 Member Function Documentation

10.3.2.1 template<typename F , typename S > void mln::accu::count_adjacent_vertices< F, S >::init () [inline]

Manipulators.

Definition at line 123 of file accu/count_adjacent_vertices.hh.

10.3.2.2 template<typename F , typename S > bool mln::accu::count_adjacent_vertices< F, S >::is_valid () const [inline]

Return whether this accu can return a result.

Definition at line 177 of file accu/count_adjacent_vertices.hh.

10.3.2.3 template<typename F , typename S > void mln::accu::count_adjacent_vertices< F, S >::set_value (unsigned c) [inline]

Force the value of the counter to c.

Definition at line 159 of file accu/count_adjacent_vertices.hh.

10.3.2.4 void mln::Accumulator< count_adjacent_vertices< F, S > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.3.2.5 void mln::Accumulator< count_adjacent_vertices< F, S > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.3.2.6 template<typename F , typename S > unsigned mln::accu::count_adjacent_vertices< F, S >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 151 of file accu/count_adjacent_vertices.hh.

10.4 mln::accu::count_labels< L > Struct Template Reference

Count the number of different labels in an image.

```
#include <count_labels.hh>
```

Inherits base< unsigned, count_labels< L > >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- unsigned [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.
- void [set_value \(unsigned c\)](#)
Force the value of the counter to c.

10.4.1 Detailed Description

template<typename L> struct mln::accu::count_labels< L >

Count the number of different labels in an image. The parameter *L* is the label type to be count.

Definition at line 52 of file count_labels.hh.

10.4.2 Member Function Documentation

10.4.2.1 template<typename L> void mln::accu::count_labels< L >::init() [inline]

Manipulators.

Definition at line 113 of file count_labels.hh.

10.4.2.2 template<typename L> bool mln::accu::count_labels< L >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 163 of file count_labels.hh.

10.4.2.3 template<typename L> void mln::accu::count_labels< L >::set_value(unsigned c) [inline]

Force the value of the counter to c .

Definition at line 155 of file count_labels.hh.

10.4.2.4 void mln::Accumulator< count_labels< L > >::take_as_init(const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.4.2.5 void mln::Accumulator< count_labels< L > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.4.2.6 template<typename L> unsigned mln::accu::count_labels< L >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 146 of file count_labels.hh.

10.5 mln::accu::count_value< V > Struct Template Reference

Define an accumulator that counts the occurrence of a given value.

```
#include <count_value.hh>
```

Inherits base< unsigned, count_value< V > >.

Public Member Functions

- `bool is_valid () const`
Check whether this accu is able to return a result.
- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `unsigned to_result () const`
Get the value of the accumulator.

- `void init ()`
Manipulators.
- `void set_value (unsigned c)`
Force the value of the counter to c.

10.5.1 Detailed Description

`template<typename V> struct mln::accu::count_value< V >`

Define an accumulator that counts the occurrence of a given value.

Definition at line 72 of file count_value.hh.

10.5.2 Member Function Documentation

10.5.2.1 `template<typename V> void mln::accu::count_value< V >::init () [inline]`

Manipulators.

Definition at line 153 of file count_value.hh.

10.5.2.2 `template<typename V> bool mln::accu::count_value< V >::is_valid () const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 216 of file count_value.hh.

10.5.2.3 `template<typename V> void mln::accu::count_value< V >::set_value (unsigned c) [inline]`

Force the value of the counter to c.

Definition at line 208 of file count_value.hh.

10.5.2.4 void mln::Accumulator< count_value< V > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.5.2.5 void mln::Accumulator< count_value< V > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.5.2.6 template<typename V> unsigned mln::accu::count_value< V >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 199 of file count_value.hh.

10.6 mln::accu::histo< V > Struct Template Reference

Generic histogram class over a value set with type V.

```
#include <histo.hh>
```

Inherits base< const std::vector< unsigned > &, histo< V > >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- void [take \(const argument &t\)](#)

Manipulators.

- const std::vector< unsigned > & [vect \(\) const](#)

Get the value of the accumulator.

10.6.1 Detailed Description

template<typename V> struct mln::accu::histo< V >

Generic histogram class over a value set with type V.

Definition at line 56 of file accu/histo.hh.

10.6.2 Member Function Documentation

10.6.2.1 template<typename V> bool mln::accu::histo< V >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 236 of file accu/histo.hh.

10.6.2.2 template<typename V> void mln::accu::histo< V >::take(const argument & t) [inline]

Manipulators.

Definition at line 129 of file accu/histo.hh.

10.6.2.3 void mln::Accumulator< histo< V > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.6.2.4 void mln::Accumulator< histo< V > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.6.2.5 template<typename V> const std::vector< unsigned > & mln::accu::histo< V >::vect() const [inline]

Get the value of the accumulator.

Definition at line 201 of file accu/histo.hh.

10.7 mln::accu::label_used< L > Struct Template Reference

References all the labels used.

```
#include <label_used.hh>
```

Inherits base< const fun::i2v::array< bool > &, label_used< L > >.

Public Member Functions

- void **init** ()

Initialize accumulator attributes.
- bool **is_valid** () const

Check whether this accu is able to return a result.
- void **take_as_init** (const T &t)

Take as initialization the value t.
- void **take_n_times** (unsigned n, const T &t)

Take n times the value t.
- const fun::i2v::array< bool > & **to_result** () const

Get the value of the accumulator.
- void **take** (const argument &)

Manipulators.

10.7.1 Detailed Description

template<typename L> struct mln::accu::label_used< L >

References all the labels used. The parameter *L* is the label type.

Definition at line 53 of file label_used.hh.

10.7.2 Member Function Documentation

10.7.2.1 template<typename L > void mln::accu::label_used< L >::init() [inline]

Initialize accumulator attributes.

Definition at line 110 of file label_used.hh.

10.7.2.2 template<typename L > bool mln::accu::label_used< L >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 150 of file label_used.hh.

10.7.2.3 template<typename L > void mln::accu::label_used< L >::take(const argument & l) [inline]

Manipulators.

Definition at line 118 of file label_used.hh.

**10.7.2.4 void mln::Accumulator< label_used< L > >::take_as_init (const T & t)
[inherited]**

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

**10.7.2.5 void mln::Accumulator< label_used< L > >::take_n_times (unsigned n, const T & t)
[inherited]**

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.7.2.6 template<typename L > const fun::i2v::array< bool > & mln::accu::label_used< L >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 142 of file label_used.hh.

10.8 mln::accu::logic::land Struct Reference

"Logical-and" accumulator.

```
#include <land.hh>
```

Inherits base< bool, land >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- bool [to_result \(\) const](#)

Get the value of the accumulator.

- void [init \(\)](#)

Manipulators.

10.8.1 Detailed Description

"Logical-and" accumulator.

Definition at line 96 of file accu/logic/land.hh.

10.8.2 Member Function Documentation

10.8.2.1 void mln::accu::logic::land::init () [inline]

Manipulators.

Definition at line 136 of file accu/logic/land.hh.

10.8.2.2 bool mln::accu::logic::land::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 185 of file accu/logic/land.hh.

10.8.2.3 void mln::Accumulator< land >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.8.2.4 void mln::Accumulator< land >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.8.2.5 bool mln::accu::logic::land::to_result () const [inline]

Get the value of the accumulator.

Definition at line 178 of file accu/logic/land.hh.

10.9 mln::accu::logic::land_basic Struct Reference

"Logical-and" accumulator.

```
#include <land_basic.hh>
```

Inherits base< bool, land_basic >.

Public Member Functions

- bool [can_stop \(\) const](#)

Test if it is worth for this accumulator to take extra data.

- `bool is_valid () const`

Check whether this accu is able to return a result.

- `void take_as_init (const T &t)`

Take as initialization the value t.

- `void take_n_times (unsigned n, const T &t)`

Take n times the value t.

- `bool to_result () const`

Get the value of the accumulator.

- `void init ()`

Manipulators.

10.9.1 Detailed Description

"Logical-and" accumulator. Conversely to `accu::logic::land`, this version does not have the 'untake' method but features the 'can_stop' method.

Definition at line 99 of file land_basic.hh.

10.9.2 Member Function Documentation

10.9.2.1 `bool mln::accu::logic::land_basic::can_stop () const [inline]`

Test if it is worth for this accumulator to take extra data.

If the result is already 'false' (because this accumulator has already taken a 'false' value), can_stop returns true.

Definition at line 181 of file land_basic.hh.

10.9.2.2 `void mln::accu::logic::land_basic::init () [inline]`

Manipulators.

Definition at line 140 of file land_basic.hh.

10.9.2.3 `bool mln::accu::logic::land_basic::is_valid () const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 174 of file land_basic.hh.

10.9.2.4 void mln::Accumulator< land_basic >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.9.2.5 void mln::Accumulator< land_basic >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.9.2.6 bool mln::accu::logic::land_basic::to_result () const [inline]

Get the value of the accumulator.

Definition at line 167 of file land_basic.hh.

10.10 mln::accu::logic::lor Struct Reference

"Logical-or" accumulator.

```
#include <lór.hh>
```

Inherits base< bool, lor >.

Public Member Functions

- **bool is_valid () const**
Check whether this accu is able to return a result.
- **void take_as_init (const T &t)**
Take as initialization the value t.
- **void take_n_times (unsigned n, const T &t)**
Take n times the value t.
- **bool to_result () const**
Get the value of the accumulator.
- **void init ()**
Manipulators.

10.10.1 Detailed Description

"Logical-or" accumulator.

Definition at line 95 of file accu/logic/lór.hh.

10.10.2 Member Function Documentation

10.10.2.1 void mln::accu::logic::lor::init() [inline]

Manipulators.

Definition at line 134 of file accu/logic/lor.hh.

10.10.2.2 bool mln::accu::logic::lor::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 183 of file accu/logic/lor.hh.

10.10.2.3 void mln::Accumulator< lor >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.10.2.4 void mln::Accumulator< lor >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.10.2.5 bool mln::accu::logic::lor::to_result() const [inline]

Get the value of the accumulator.

Definition at line 176 of file accu/logic/lor.hh.

10.11 mln::accu::logic::lor_basic Struct Reference

"Logical-or" accumulator class.

```
#include <lor_basic.hh>
```

Inherits base< bool, lor_basic >.

Public Member Functions

- bool [can_stop](#) () const

Test if it is worth for this accumulator to take extra data.

- bool [is_valid](#) () const

Check whether this accu is able to return a result.

- void [take_as_init](#) (const T &t)

Take as initialization the value t.

- void [take_n_times](#) (unsigned n, const T &t)

Take n times the value t.

- bool [to_result](#) () const

Get the value of the accumulator.

- void [init](#) ()

Manipulators.

10.11.1 Detailed Description

"Logical-or" accumulator class. Conversely to [accu::logic::lor](#), this version does not have the 'untake' method but features the 'can_stop' method.

Definition at line 98 of file lor_basic.hh.

10.11.2 Member Function Documentation

10.11.2.1 bool mln::accu::logic::lor_basic::can_stop () const [inline]

Test if it is worth for this accumulator to take extra data.

If the result is already 'true' (because this accumulator has already taken a 'true' value), can_stop returns true.

Definition at line 180 of file lor_basic.hh.

10.11.2.2 void mln::accu::logic::lor_basic::init () [inline]

Manipulators.

Definition at line 139 of file lor_basic.hh.

10.11.2.3 bool mln::accu::logic::lor_basic::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 173 of file lor_basic.hh.

10.11.2.4 void mln::Accumulator< lor_basic >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.11.2.5 void mln::Accumulator< lor_basic >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.11.2.6 bool mln::accu::logic::lor_basic::to_result () const [inline]

Get the value of the accumulator.

Definition at line 166 of file lor_basic.hh.

10.12 mln::accu::maj_h< T > Struct Template Reference

Compute the majority value.

```
#include <maj_h.hh>
```

Inherits base< const T &, maj_h< T > >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- const T & [to_result \(\) const](#)

Get the value of the accumulator.

- void [init \(\)](#)

Manipulators.

10.12.1 Detailed Description

```
template<typename T> struct mln::accu::maj_h< T >
```

Compute the majority value. It is based on a histogram. The parameter T is the type of values.

Definition at line 57 of file maj_h.hh.

10.12.2 Member Function Documentation

10.12.2.1 template<typename T> void mln::accu::maj_h< T >::init() [inline]

Manipulators.

Definition at line 129 of file maj_h.hh.

10.12.2.2 template<typename T> bool mln::accu::maj_h< T >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 197 of file maj_h.hh.

10.12.2.3 void mln::Accumulator< maj_h< T > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.12.2.4 void mln::Accumulator< maj_h< T > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.12.2.5 template<typename T> const T & mln::accu::maj_h< T >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 187 of file maj_h.hh.

10.13 mln::accu::math::count< T > Struct Template Reference

Generic counter accumulator.

```
#include <count.hh>
```

Inherits base< unsigned, count< T > >.

Public Member Functions

- bool [is_valid\(\)](#) const

Check whether this accu is able to return a result.

- void [take_as_init\(const T &t\)](#)

Take as initialization the value t.

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t.

- unsigned **to_result** () const

Get the value of the accumulator.

- void **init** ()

Manipulators.

- void **set_value** (unsigned c)

Force the value of the counter to c.

10.13.1 Detailed Description

template<typename T> struct mln::accu::math::count< T >

Generic counter accumulator. The parameter T is the type to be count.

Definition at line 100 of file count.hh.

10.13.2 Member Function Documentation

10.13.2.1 template<typename T> void mln::accu::math::count< T >::init() [inline]

Manipulators.

Definition at line 145 of file count.hh.

10.13.2.2 template<typename T> bool mln::accu::math::count< T >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 203 of file count.hh.

10.13.2.3 template<typename T> void mln::accu::math::count< T >::set_value(unsigned c) [inline]

Force the value of the counter to c .

Definition at line 195 of file count.hh.

10.13.2.4 void mln::Accumulator< count< T > >::take_as_init(const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.13.2.5 void mln::Accumulator< count< T > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.13.2.6 template<typename T> unsigned mln::accu::math::count< T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 187 of file count.hh.

10.14 mln::accu::math::inf< T > Struct Template Reference

Generic inf accumulator class.

```
#include <inf.hh>
```

Inherits base< const T &, inf< T > >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- const T & [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.

10.14.1 Detailed Description

template<typename T> struct mln::accu::math::inf< T >

Generic inf accumulator class. The parameter T is the type of values.

Definition at line 56 of file accu/math/inf.hh.

10.14.2 Member Function Documentation

10.14.2.1 `template<typename T> void mln::accu::math::inf< T >::init() [inline]`

Manipulators.

Definition at line 126 of file accu/math/inf.hh.

10.14.2.2 `template<typename T> bool mln::accu::math::inf< T >::is_valid() const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 164 of file accu/math/inf.hh.

10.14.2.3 `void mln::Accumulator< inf< T > >::take_as_init(const T & t) [inherited]`

Take as initialization the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.14.2.4 `void mln::Accumulator< inf< T > >::take_n_times(unsigned n, const T & t) [inherited]`

Take n times the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.14.2.5 `template<typename T> const T & mln::accu::math::inf< T >::to_result() const [inline]`

Get the value of the accumulator.

Definition at line 156 of file accu/math/inf.hh.

10.15 `mln::accu::math::sum< T, S >` Struct Template Reference

Generic sum accumulator class.

```
#include <sum.hh>
```

Inherits base< const S &, sum< T, S > >.

Public Member Functions

- `bool is_valid() const`

Check whether this accu is able to return a result.

- `void take_as_init(const T &t)`

Take as initialization the value t .

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t.

- const S & **to_result** () const

Get the value of the accumulator.

- void **init** ()

Manipulators.

10.15.1 Detailed Description

```
template<typename T, typename S = typename mln::value::props< T >::sum> struct
mln::accu::math::sum< T, S >
```

Generic sum accumulator class. Parameter T is the type of values that we sum. Parameter S is the type to store the value sum; the default type of S is the summation type (property) of T.

Definition at line 112 of file accu/math/sum.hh.

10.15.2 Member Function Documentation

10.15.2.1 template<typename T , typename S > void mln::accu::math::sum< T, S >::init () [inline]

Manipulators.

Definition at line 161 of file accu/math/sum.hh.

References mln::literal::zero.

10.15.2.2 template<typename T , typename S > bool mln::accu::math::sum< T, S >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 222 of file accu/math/sum.hh.

10.15.2.3 void mln::Accumulator< sum< T, S > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.15.2.4 void mln::Accumulator< sum< T, S > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.15.2.5 template<typename T , typename S > const S & mln::accu::math::sum< T, S >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 206 of file accu/math/sum.hh.

10.16 mln::accu::math::sup< T > Struct Template Reference

Generic sup accumulator class.

```
#include <sup.hh>
```

Inherits base< const T &, sup< T > >.

Public Member Functions

- bool **is_valid** () const

Check whether this accu is able to return a result.

- void **take_as_init** (const T &t)

Take as initialization the value t.

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t.

- const T & **to_result** () const

Get the value of the accumulator.

- void **init** ()

Manipulators.

10.16.1 Detailed Description

template<typename T> struct mln::accu::math::sup< T >

Generic sup accumulator class. The parameter T is the type of values.

Definition at line 56 of file accu/math/sup.hh.

10.16.2 Member Function Documentation

10.16.2.1 template<typename T > void mln::accu::math::sup< T >::init() [inline]

Manipulators.

Definition at line 128 of file accu/math/sup.hh.

10.16.2.2 template<typename T> bool mln::accu::math::sup< T >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 166 of file accu/math/sup.hh.

10.16.2.3 void mln::Accumulator< sup< T > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.16.2.4 void mln::Accumulator< sup< T > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.16.2.5 template<typename T> const T & mln::accu::math::sup< T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 158 of file accu/math/sup.hh.

10.17 mln::accu::max_site< I > Struct Template Reference

Define an accumulator that computes the first site with the maximum value in an image.

```
#include <max_site.hh>
```

Inherits base< I::psite, max_site< I > >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- I::psite [to_result \(\) const](#)

Get the value of the accumulator.

- void **init** ()
Manipulators.

10.17.1 Detailed Description

template<typename I> struct mln::accu::max_site< I >

Define an accumulator that computes the first site with the maximum value in an image.

Definition at line 53 of file max_site.hh.

10.17.2 Member Function Documentation

10.17.2.1 **template<typename I > void mln::accu::max_site< I >::init () [inline]**

Manipulators.

Definition at line 114 of file max_site.hh.

10.17.2.2 **template<typename I > bool mln::accu::max_site< I >::is_valid () const [inline]**

Check whether this accu is able to return a result.

Always true here.

Definition at line 174 of file max_site.hh.

10.17.2.3 **void mln::Accumulator< max_site< I > >::take_as_init (const T & t) [inherited]**

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.17.2.4 **void mln::Accumulator< max_site< I > >::take_n_times (unsigned n, const T & t) [inherited]**

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.17.2.5 **template<typename I > I::psite mln::accu::max_site< I >::to_result () const [inline]**

Get the value of the accumulator.


Definition at line 150 of file max_site.hh.

10.18 mln::accu::meta::center Struct Reference

Meta accumulator for center.

```
#include <center.hh>
```

Inheritance diagram for mln::accu::meta::center:



10.18.1 Detailed Description

Meta accumulator for center.


Definition at line 89 of file center.hh.

10.19 mln::accu::meta::count_adjacent_vertices Struct Reference

Meta accumulator for [count_adjacent_vertices](#).

```
#include <count_adjacent_vertices.hh>
```

Inheritance diagram for mln::accu::meta::count_adjacent_vertices:



10.19.1 Detailed Description

Meta accumulator for [count_adjacent_vertices](#).


Definition at line 98 of file accu/count_adjacent_vertices.hh.

10.20 mln::accu::meta::count_labels Struct Reference

Meta accumulator for [count_labels](#).

```
#include <count_labels.hh>
```

Inheritance diagram for mln::accu::meta::count_labels:



10.20.1 Detailed Description

Meta accumulator for [count_labels](#).


Definition at line 88 of file `count_labels.hh`.

10.21 mln::accu::meta::count_value Struct Reference

FIXME: How to write a meta accumulator with a constructor taking a generic argument? Meta accumulator for [count_value](#).

```
#include <count_value.hh>
```

Inheritance diagram for mln::accu::meta::count_value:



10.21.1 Detailed Description

FIXME: How to write a meta accumulator with a constructor taking a generic argument? Meta accumulator for `count_value`.


Definition at line 116 of file `count_value.hh`.

10.22 mln::accu::meta::histo Struct Reference

Meta accumulator for histo.

```
#include <histo.hh>
```

Inheritance diagram for mln::accu::meta::histo:



10.22.1 Detailed Description

Meta accumulator for histo.


Definition at line 102 of file accu/histo.hh.

10.23 mln::accu::meta::label_used Struct Reference

Meta accumulator for [label_used](#).

```
#include <label_used.hh>
```

Inheritance diagram for mln::accu::meta::label_used:



10.23.1 Detailed Description

Meta accumulator for [label_used](#).


Definition at line 85 of file `label_used.hh`.

10.24 mln::accu::meta::logic::land Struct Reference

Meta accumulator for land.

```
#include <land.hh>
```

Inheritance diagram for mln::accu::meta::logic::land:



10.24.1 Detailed Description

Meta accumulator for land.


Definition at line 76 of file accu/logic/land.hh.

10.25 mln::accu::meta::logic::land_basic Struct Reference

Meta accumulator for [land_basic](#).

```
#include <land_basic.hh>
```

Inheritance diagram for mln::accu::meta::logic::land_basic:



10.25.1 Detailed Description

Meta accumulator for [land_basic](#).


Definition at line 77 of file `land_basic.hh`.

10.26 mln::accu::meta::logic::lor Struct Reference

Meta accumulator for lor.

```
#include <lor.hh>
```

Inheritance diagram for mln::accu::meta::logic::lor:



10.26.1 Detailed Description

Meta accumulator for lor.


Definition at line 76 of file accu/logic/lor.hh.

10.27 mln::accu::meta::logic::lor_basic Struct Reference

Meta accumulator for [lor_basic](#).

```
#include <lor_basic.hh>
```

Inheritance diagram for mln::accu::meta::logic::lor_basic:



10.27.1 Detailed Description

Meta accumulator for [lor_basic](#).


Definition at line 76 of file `lor_basic.hh`.

10.28 mln::accu::meta::maj_h Struct Reference

Meta accumulator for [maj_h](#).

```
#include <maj_h.hh>
```

Inheritance diagram for mln::accu::meta::maj_h:



10.28.1 Detailed Description

Meta accumulator for [maj_h](#).


Definition at line 101 of file `maj_h.hh`.

10.29 mln::accu::meta::math::count Struct Reference

Meta accumulator for count.

```
#include <count.hh>
```

Inheritance diagram for mln::accu::meta::math::count:



10.29.1 Detailed Description

Meta accumulator for count.


Definition at line 77 of file count.hh.

10.30 mln::accu::meta::math::inf Struct Reference

Meta accumulator for inf.

```
#include <inf.hh>
```

Inheritance diagram for mln::accu::meta::math::inf:



10.30.1 Detailed Description

Meta accumulator for inf.


Definition at line 97 of file accu/math/inf.hh.

10.31 mln::accu::meta::math::sum Struct Reference

Meta accumulator for sum.

```
#include <sum.hh>
```

Inheritance diagram for mln::accu::meta::math::sum:



10.31.1 Detailed Description

Meta accumulator for sum.


Definition at line 66 of file accu/math/sum.hh.

10.32 mln::accu::meta::math::sup Struct Reference

Meta accumulator for sup.

```
#include <sup.hh>
```

Inheritance diagram for mln::accu::meta::math::sup:



10.32.1 Detailed Description

Meta accumulator for sup.


Definition at line 98 of file accu/math/sup.hh.

10.33 mln::accu::meta::max_site Struct Reference

Meta accumulator for [max_site](#).

```
#include <max_site.hh>
```

Inheritance diagram for mln::accu::meta::max_site:



10.33.1 Detailed Description

Meta accumulator for [max_site](#).


Definition at line 90 of file `max_site.hh`.

10.34 mln::accu::meta::nil Struct Reference

Meta accumulator for nil.

```
#include <nil.hh>
```

Inheritance diagram for mln::accu::meta::nil:



10.34.1 Detailed Description

Meta accumulator for nil.


Definition at line 77 of file accu/nil.hh.

10.35 mln::accu::meta::p< mA > Struct Template Reference

Meta accumulator for p.

```
#include <p.hh>
```

Inheritance diagram for `mln::accu::meta::p< mA >`:



10.35.1 Detailed Description

```
template<typename mA> struct mln::accu::meta::p< mA >
```

Meta accumulator for `p`.


Definition at line 83 of file `p.hh`.

10.36 mln::accu::meta::pair< A1, A2 > Struct Template Reference

Meta accumulator for `pair`.

```
#include <pair.hh>
```

Inheritance diagram for mln::accu::meta::pair< A1, A2 >:



10.36.1 Detailed Description

```
template<typename A1, typename A2> struct mln::accu::meta::pair< A1, A2 >
```

Meta accumulator for pair.


Definition at line 110 of file pair.hh.

10.37 mln::accu::meta::rms Struct Reference

Meta accumulator for rms.

```
#include <rms.hh>
```

Inheritance diagram for mln::accu::meta::rms:



10.37.1 Detailed Description

Meta accumulator for rms.


Definition at line 88 of file accu/rms.hh.

10.38 mln::accu::meta::shape::bbox Struct Reference

Meta accumulator for bbox.

```
#include <bbox.hh>
```

Inheritance diagram for mln::accu::meta::shape::bbox:



10.38.1 Detailed Description

Meta accumulator for bbox.


Definition at line 94 of file accu/shape/bbox.hh.

10.39 mln::accu::meta::shape::height Struct Reference

Meta accumulator for height.

```
#include <height.hh>
```

Inheritance diagram for mln::accu::meta::shape::height:



10.39.1 Detailed Description

Meta accumulator for height.


Definition at line 121 of file `accu/shape/height.hh`.

10.40 mln::accu::meta::shape::volume Struct Reference

Meta accumulator for volume.

```
#include <volume.hh>
```

Inheritance diagram for mln::accu::meta::shape::volume:



10.40.1 Detailed Description

Meta accumulator for volume.


Definition at line 120 of file accu/shape/volume.hh.

10.41 mln::accu::meta::stat::max Struct Reference

Meta accumulator for max.

```
#include <max.hh>
```

Inheritance diagram for mln::accu::meta::stat::max:



10.41.1 Detailed Description

Meta accumulator for max.


Definition at line 78 of file accu/stat/max.hh.

10.42 mln::accu::meta::stat::max_h Struct Reference

Meta accumulator for max.

```
#include <max_h.hh>
```

Inheritance diagram for mln::accu::meta::stat::max_h:



10.42.1 Detailed Description

Meta accumulator for max.


Definition at line 77 of file `max_h.hh`.

10.43 mln::accu::meta::stat::mean Struct Reference

Meta accumulator for mean.

```
#include <mean.hh>
```

Inheritance diagram for mln::accu::meta::stat::mean:



10.43.1 Detailed Description

Meta accumulator for mean.


Definition at line 65 of file accu/stat/mean.hh.

10.44 mln::accu::meta::stat::median_alt< T > Struct Template Reference

Meta accumulator for [median_alt](#).

```
#include <median_alt.hh>
```

Inheritance diagram for mln::accu::meta::stat::median_alt< T >:



10.44.1 Detailed Description

```
template<typename T> struct mln::accu::meta::stat::median_alt< T >
```

Meta accumulator for [median_alt](#).


Definition at line 122 of file `median_alt.hh`.

10.45 mln::accu::meta::stat::median_h Struct Reference

Meta accumulator for [median_h](#).

```
#include <median_h.hh>
```

Inheritance diagram for mln::accu::meta::stat::median_h:



10.45.1 Detailed Description

Meta accumulator for [median_h](#).


Definition at line 61 of file `median_h.hh`.

10.46 mln::accu::meta::stat::min Struct Reference

Meta accumulator for min.

```
#include <min.hh>
```

Inheritance diagram for mln::accu::meta::stat::min:



10.46.1 Detailed Description

Meta accumulator for min.


Definition at line 78 of file accu/stat/min.hh.

10.47 mln::accu::meta::stat::min_h Struct Reference

Meta accumulator for min.

```
#include <min_h.hh>
```

Inheritance diagram for mln::accu::meta::stat::min_h:



10.47.1 Detailed Description

Meta accumulator for min.


Definition at line 77 of file `min_h.hh`.

10.48 mln::accu::meta::stat::rank Struct Reference

Meta accumulator for rank.

```
#include <rank.hh>
```

Inheritance diagram for mln::accu::meta::stat::rank:



10.48.1 Detailed Description

Meta accumulator for rank.


Definition at line 123 of file `rank.hh`.

10.49 mln::accu::meta::stat::rank_high_quant Struct Reference

Meta accumulator for [rank_high_quant](#).

```
#include <rank_high_quant.hh>
```

Inheritance diagram for mln::accu::meta::stat::rank_high_quant:



10.49.1 Detailed Description

Meta accumulator for [rank_high_quant](#).


Definition at line 102 of file [rank_high_quant.hh](#).

10.50 mln::accu::meta::tuple<n,> Struct Template Reference

Meta accumulator for tuple.

```
#include <tuple.hh>
```

Inheritance diagram for mln::accu::meta::tuple< n, >:



10.50.1 Detailed Description

```
template<unsigned n, BOOST_PP_ENUM_PARAMS_WITH_A_DEFAULT(10, typename T, boost::tuples::null_type)> struct mln::accu::meta::tuple<n, >
```

Meta accumulator for tuple.


Definition at line 111 of file tuple.hh.

10.51 mln::accu::meta::val< mA > Struct Template Reference

Meta accumulator for val.

```
#include <v.hh>
```

Inheritance diagram for `mln::accu::meta::val< mA >`:



10.51.1 Detailed Description

`template<typename mA> struct mln::accu::meta::val< mA >`

Meta accumulator for val.

Definition at line 87 of file v.hh.

10.52 mln::accu::nil< T > Struct Template Reference

Define an accumulator that does nothing.

`#include <nil.hh>`

Inherits base< util::ignore, nil< T > >.

Public Member Functions

- `bool is_valid () const`
Check whether this accu is able to return a result.
- `void take_as_init (const T &t)`

Take as initialization the value t.

- `void take_n_times (unsigned n, const T &t)`

Take n times the value t.

- `util::ignore_to_result () const`

Get the value of the accumulator.

- `void init ()`

Manipulators.

10.52.1 Detailed Description

`template<typename T> struct mln::accu::nil< T >`

Define an accumulator that does nothing.

Definition at line 49 of file accu/nil.hh.

10.52.2 Member Function Documentation

10.52.2.1 `template<typename T> void mln::accu::nil< T >::init () [inline]`

Manipulators.

Definition at line 100 of file accu/nil.hh.

10.52.2.2 `template<typename T> bool mln::accu::nil< T >::is_valid () const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 136 of file accu/nil.hh.

10.52.2.3 `void mln::Accumulator< nil< T > >::take_as_init (const T & t) [inherited]`

Take as initialization the value t.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.52.2.4 `void mln::Accumulator< nil< T > >::take_n_times (unsigned n, const T & t) [inherited]`

Take n times the value t.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.52.2.5 template<typename T > util::ignore mln::accu::nil< T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 128 of file accu/nil.hh.

10.53 mln::accu::p< A > Struct Template Reference

Generic p of accumulators.

```
#include <p.hh>
```

Inherits base< const A::result &, p< A > >.

Public Member Functions

- bool **is_valid () const**
Check whether this accu is able to return a result.
- void **take_as_init (const T &t)**
Take as initialization the value t.
- void **take_n_times (unsigned n, const T &t)**
Take n times the value t.
- const A::result & **to_result () const**
Get the value of the accumulator.
- void **init ()**
Manipulators.

10.53.1 Detailed Description

template<typename A> struct mln::accu::p< A >

Generic p of accumulators. The parameter V is the type of values.

Definition at line 50 of file p.hh.

10.53.2 Member Function Documentation

10.53.2.1 template<typename A > void mln::accu::p< A >::init () [inline]

Manipulators.

Definition at line 115 of file p.hh.

10.53.2.2 template<typename A> bool mln::accu::p< A >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 155 of file p.hh.

10.53.2.3 void mln::Accumulator< p< A > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.53.2.4 void mln::Accumulator< p< A > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.53.2.5 template<typename A> const A::result & mln::accu::p< A >::to_result() const [inline]

Get the value of the accumulator.


Definition at line 147 of file p.hh.

10.54 mln::accu::pair< A1, A2, T > Struct Template Reference

Generic pair of accumulators.

```
#include <pair.hh>
```

Inheritance diagram for `mln::accu::pair< A1, A2, T >`:



Public Member Functions

- `A1::result first () const`
Return the result of the first accumulator.
- `A1 first_accu () const`
Return the first accumulator.
- `bool is_valid () const`
Check whether this accu is able to return a result.
- `A2::result second () const`
Return the result of the second accumulator.
- `A2 second_accu () const`
Return the second accumulator.
- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `void init ()`
Manipulators.

- `std::pair< typename A1::result, typename A2::result > to_result () const`
Get the value of the accumulator.

10.54.1 Detailed Description

`template<typename A1, typename A2, typename T = mln_argument(A1)> struct mln::accu::pair< A1, A2, T >`

Generic pair of accumulators. The parameter T is the type of values.

Definition at line 58 of file pair.hh.

10.54.2 Member Function Documentation

10.54.2.1 `template<typename A1 , typename A2 , typename T > A1::result mln::accu::pair< A1, A2, T >::first () const [inline]`

Return the result of the first accumulator.

Definition at line 191 of file pair.hh.

10.54.2.2 `template<typename A1 , typename A2 , typename T > A1 mln::accu::pair< A1, A2, T >::first_accu () const [inline]`

Return the first accumulator.

Definition at line 209 of file pair.hh.

10.54.2.3 `template<typename A1 , typename A2 , typename T > void mln::accu::pair< A1, A2, T >::init () [inline]`

Manipulators.

Definition at line 136 of file pair.hh.

10.54.2.4 `template<typename A1 , typename A2 , typename T > bool mln::accu::pair< A1, A2, T >::is_valid () const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 226 of file pair.hh.

10.54.2.5 `template<typename A1 , typename A2 , typename T > A2::result mln::accu::pair< A1, A2, T >::second () const [inline]`

Return the result of the second accumulator.

Definition at line 199 of file pair.hh.

10.54.2.6 template<typename A1 , typename A2 , typename T > A2 mln::accu::pair< A1, A2, T >::second_accu () const [inline]

Return the second accumulator.

Definition at line 217 of file pair.hh.

10.54.2.7 void mln::Accumulator< pair< A1, A2, T > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.54.2.8 void mln::Accumulator< pair< A1, A2, T > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.54.2.9 template<typename A1 , typename A2 , typename T > std::pair< typename A1::result, typename A2::result > mln::accu::pair< A1, A2, T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 172 of file pair.hh.

10.55 mln::accu::rms< T, V > Struct Template Reference

Generic root mean square accumulator class.

```
#include <rms.hh>
```

Inherits base< V, rms< T, V > >.

Public Member Functions

- bool **is_valid** () const

Check whether this accu is able to return a result.

- void **take_as_init** (const T &t)

Take as initialization the value t .

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t .

- V **to_result** () const

Get the value of the accumulator.

- `void init()`
Manipulators.

10.55.1 Detailed Description

`template<typename T, typename V> struct mln::accu::rms< T, V >`

Generic root mean square accumulator class. The parameter `T` is the type of the root mean square value.
 Definition at line 52 of file accu/rms.hh.

10.55.2 Member Function Documentation

10.55.2.1 `template<typename T, typename V> void mln::accu::rms< T, V >::init() [inline]`

Manipulators.

Definition at line 112 of file accu/rms.hh.

References `mln::literal::zero`.

10.55.2.2 `template<typename T, typename V> bool mln::accu::rms< T, V >::is_valid() const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 166 of file accu/rms.hh.

10.55.2.3 `void mln::Accumulator< rms< T, V > >::take_as_init(const T & t) [inherited]`

Take as initialization the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.55.2.4 `void mln::Accumulator< rms< T, V > >::take_n_times(unsigned n, const T & t) [inherited]`

Take `n` times the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.55.2.5 `template<typename T, typename V> V mln::accu::rms< T, V >::to_result() const [inline]`

Get the value of the accumulator.

Definition at line 148 of file accu/rms.hh.

10.56 mln::accu::shape::bbox< P > Struct Template Reference

Generic bounding box accumulator class.

```
#include <bbox.hh>
```

Inherits base< const box< P > &, bbox< P > >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- const box< P > & [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.

10.56.1 Detailed Description

```
template<typename P> struct mln::accu::shape::bbox< P >
```

Generic bounding box accumulator class. The parameter P is the type of points.

Definition at line 55 of file accu/shape/bbox.hh.

10.56.2 Member Function Documentation

10.56.2.1 template<typename P > void mln::accu::shape::bbox< P >::init () [inline]

Manipulators.

Definition at line 124 of file accu/shape/bbox.hh.

10.56.2.2 template<typename P > bool mln::accu::shape::bbox< P >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 224 of file accu/shape/bbox.hh.

10.56.2.3 void mln::Accumulator< bbox< P > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.56.2.4 void mln::Accumulator< bbox< P > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.56.2.5 template<typename P> const box< P > & mln::accu::shape::bbox< P >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 215 of file accu/shape/bbox.hh.

Referenced by mln::geom::rotate().

10.57 mln::accu::shape::height< I > Struct Template Reference

Height accumulator.

```
#include <height.hh>
```

Inherits base< unsigned, height< I > >.

Public Types

- **typedef util::pix< I > argument**
The accumulated data type.
- **typedef argument::value value**
The value type associated to the pixel type.

Public Member Functions

- **bool is_valid () const**
Check whether this accu is able to return a result.
- **void take_as_init (const T &t)**
Take as initialization the value t.
- **void take_n_times (unsigned n, const T &t)**
Take n times the value t.
- **unsigned to_result () const**

Get the value of the accumulator.

- void `init ()`
Manipulators.
- void `set_value (unsigned h)`
Force the value of the counter to h.

10.57.1 Detailed Description

template<typename I> struct mln::accu::shape::height< I >

Height accumulator. The parameter `I` is the image type on which the accumulator of pixels is built.

Definition at line 68 of file accu/shape/height.hh.

10.57.2 Member Typedef Documentation

10.57.2.1 template<typename I> typedef util::pix<I> mln::accu::shape::height< I >::argument

The accumulated data type.

The height of component is represented by the height of its root pixel. See `mln::morpho::closing_height` and `mln::morpho::opening_height` for actual uses of this accumulator. **FIXME:** Replaced by `mln::morpho::attribute::height`

Definition at line 78 of file accu/shape/height.hh.

10.57.2.2 template<typename I> typedef argument::value mln::accu::shape::height< I >::value

The value type associated to the pixel type.

Definition at line 80 of file accu/shape/height.hh.

10.57.3 Member Function Documentation

10.57.3.1 template<typename I> void mln::accu::shape::height< I >::init () [inline]

Manipulators.

Definition at line 150 of file accu/shape/height.hh.

10.57.3.2 template<typename I> bool mln::accu::shape::height< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 199 of file accu/shape/height.hh.

10.57.3.3 template<typename I> void mln::accu::shape::height< I >::set_value (unsigned h) [inline]

Force the value of the counter to h .

Definition at line 188 of file accu/shape/height.hh.

10.57.3.4 void mln::Accumulator< height< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.57.3.5 void mln::Accumulator< height< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.57.3.6 template<typename I> unsigned mln::accu::shape::height< I >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 180 of file accu/shape/height.hh.

10.58 `mln::accu::shape::volume< I >` Struct Template Reference

Volume accumulator class.

```
#include <volume.hh>
```

Inherits base< unsigned, volume< I > >.

Public Types

- **typedef util::pix< I > argument**
The accumulated data type.
- **typedef argument::value value**
The value type associated to the pixel type.

Public Member Functions

- **bool is_valid () const**
Check whether this accu is able to return a result.
- **void take_as_init (const T &t)**
Take as initialization the value t .

- void [take_n_times](#) (unsigned n, const T &t)

Take n times the value t.

- unsigned [to_result](#) () const

Get the value of the accumulator.

- void [init](#) ()

Manipulators.

- void [set_value](#) (unsigned v)

Force the value of the counter to v.

10.58.1 Detailed Description

template<typename I> struct mln::accu::shape::volume< I >

Volume accumulator class. The parameter I is the image type on which the accumulator of pixels is built.

Definition at line 66 of file accu/shape/volume.hh.

10.58.2 Member Typedef Documentation

10.58.2.1 template<typename I> typedef util::pix<I> mln::accu::shape::volume< I >::argument

The accumulated data type.

The volume of component is represented by the volume of its root pixel. See mln::morpho::closing_volume and mln::morpho::opening_volume for actual uses of this accumulator. FIXME: Replaced by [mln::morpho::attribute::volume](#)

Definition at line 76 of file accu/shape/volume.hh.

10.58.2.2 template<typename I> typedef argument::value mln::accu::shape::volume< I >::value

The value type associated to the pixel type.

Definition at line 78 of file accu/shape/volume.hh.

10.58.3 Member Function Documentation

10.58.3.1 template<typename I> void mln::accu::shape::volume< I >::init () [inline]

Manipulators.

Definition at line 148 of file accu/shape/volume.hh.

References mln::literal::zero.

10.58.3.2 template<typename I> bool mln::accu::shape::volume< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 215 of file accu/shape/volume.hh.

10.58.3.3 template<typename I> void mln::accu::shape::volume< I >::set_value (unsigned v) [inline]

Force the value of the counter to v .

Definition at line 204 of file accu/shape/volume.hh.

References `mln::literal::zero`.

10.58.3.4 void mln::Accumulator< volume< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.58.3.5 void mln::Accumulator< volume< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.58.3.6 template<typename I> unsigned mln::accu::shape::volume< I >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 196 of file accu/shape/volume.hh.

10.59 mln::accu::site_set::rectangularity< P > Class Template Reference

Compute the rectangularity of a site set.

```
#include <rectangularity.hh>
```

Inherits couple< `accu::shape::bbox< P >`, `accu::math::count< P >`, `float`, `rectangularity< P >` >.

Public Member Functions

- A2::result `area () const`

Return the site set area.

- A1::result **bbox** () const
Return the site set bounding box.
- **rectangularity** ()
Constructor.
- template<typename T >
void **take_as_init** (const T &t)
Take as initialization the value t.
- template<typename T >
void **take_n_times** (unsigned n, const T &t)
Take n times the value t.
- result **to_result** () const
Return the rectangularity value.

10.59.1 Detailed Description

template<typename P> class mln::accu::site_set::rectangularity< P >

Compute the rectangularity of a site set.

Definition at line 51 of file rectangularity.hh.

10.59.2 Constructor & Destructor Documentation

10.59.2.1 template<typename P > mln::accu::site_set::rectangularity< P >::rectangularity () [inline]

Constructor.

Definition at line 91 of file rectangularity.hh.

10.59.3 Member Function Documentation

**10.59.3.1 template<typename P > rectangularity< P >::A2::result
mln::accu::site_set::rectangularity< P >::area () const [inline]**

Return the site set area.

Definition at line 107 of file rectangularity.hh.

**10.59.3.2 template<typename P > rectangularity< P >::A1::result
mln::accu::site_set::rectangularity< P >::bbox () const [inline]**

Return the site set bounding box.

Definition at line 98 of file rectangularity.hh.

10.59.3.3 template<typename E> template<typename T> void mln::Accumulator< E >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

Definition at line 186 of file accumulator.hh.

References mln::mln_exact().

10.59.3.4 template<typename E> template<typename T> void mln::Accumulator< E >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

Definition at line 213 of file accumulator.hh.

References mln::mln_exact().

10.59.3.5 template<typename P> rectangularity< P >::result mln::accu::site_set::rectangularity< P >::to_result () const [inline]

Return the rectangularity value.

Definition at line 116 of file rectangularity.hh.

10.60 mln::accu::stat::deviation< T, S, M > Struct Template Reference

Generic standard deviation accumulator class.

```
#include <deviation.hh>
```

Inherits base< M, deviation< T, S, M > >.

Public Member Functions

- bool **is_valid** () const

Check whether this accu is able to return a result.

- void **take_as_init** (const T &t)

Take as initialization the value t .

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t .

- M **to_result** () const

Get the value of the accumulator.

- void **init** ()

Manipulators.

10.60.1 Detailed Description

```
template<typename T, typename S = typename mln::value::props< T >::sum, typename M = S>
struct mln::accu::stat::deviation< T, S, M >
```

Generic standard deviation accumulator class. Parameter T is the type of values that we sum. Parameter S is the type to store the standard deviation; the default type of S is the summation type (property) of T . Parameter M is the type of the mean value; the default type of M is S .

Definition at line 62 of file deviation.hh.

10.60.2 Member Function Documentation

10.60.2.1 template<typename T , typename S , typename M > void mln::accu::stat::deviation< T,
S, M >::init() [inline]

Manipulators.

Definition at line 132 of file deviation.hh.

10.60.2.2 template<typename T , typename S , typename M > bool mln::accu::stat::deviation< T,
S, M >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 177 of file deviation.hh.

10.60.2.3 void mln::Accumulator< deviation< T, S, M > >::take_as_init(const T & t)
[inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.60.2.4 void mln::Accumulator< deviation< T, S, M > >::take_n_times(unsigned n, const T
 $\& t)$ [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.60.2.5 template<typename T , typename S , typename M > M mln::accu::stat::deviation< T,
S, M >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 159 of file deviation.hh.

10.61 mln::accu::stat::histo3d_rgb< V > Struct Template Reference

Define a histogram as accumulator which returns an [image3d](#).

```
#include <histo3d_rgb.hh>
```

Inherits base< [image3d< unsigned >](#), [histo3d_rgb< V >](#) >.

Public Member Functions

- `bool is_valid () const`

Check whether this accumulator is able to return a result.

- `void take_as_init (const T &t)`

Take as initialization the value t.

- `void take_n_times (unsigned n, const T &t)`

Take n times the value t.

- `histo3d_rgb ()`

Constructors.

- `void init ()`

Manipulators.

- `void take (const argument &t)`

Update the histogram with the RGB pixel t.

- `void take (const histo3d_rgb< V > &other)`

Update the histogram with an other histogram.

- `result to_result () const`

Accessors.

10.61.1 Detailed Description

`template<typename V> struct mln::accu::stat::histo3d_rgb< V >`

Define a histogram as accumulator which returns an [image3d](#). Param V defines the type of the input image value. It is in this space that we count the values. For instance, this histogram works well for [image2d< rgb<2> >](#) or with [image2d< rgb<7> >](#). The number of bins depends directly the values V. For 8 bits there is 256x3 bins. Note that less quantification works too.

Definition at line 167 of file histo3d_rgb.hh.

10.61.2 Constructor & Destructor Documentation

10.61.2.1 template<typename V> mln::accu::stat::histo3d_rgb< V >::histo3d_rgb() [inline]

Constructors.

Infer the size of the resulting `image3d` domain. By evaluating the minimum and the maximum of V, we define the domain of the resulting `image3d`.

Definition at line 244 of file `histo3d_rgb.hh`.

10.61.3 Member Function Documentation

10.61.3.1 template<typename V> void mln::accu::stat::histo3d_rgb< V >::init() [inline]

Manipulators.

Initialize the histogram with zero value. This method must be called just before starting the use of the histogram. If it's not, resulting values won't converge to the density.

Definition at line 268 of file `histo3d_rgb.hh`.

References `mln::data::fill()`, and `mln::literal::zero`.

10.61.3.2 template<typename V> bool mln::accu::stat::histo3d_rgb< V >::is_valid() const [inline]

Check whether this accumulator is able to return a result.

Depends if the resulting `image1d` is valid. We can assume it is quite always the case.

Definition at line 307 of file `histo3d_rgb.hh`.

10.61.3.3 template<typename V> void mln::accu::stat::histo3d_rgb< V >::take(const argument & t) [inline]

Update the histogram with the RGB pixel t.

Parameters

[in] *t* a graylevel pixel of type V.

The end user shouldn't call this method. In place of it, he can go through the data compute interface.

Definition at line 275 of file `histo3d_rgb.hh`.

10.61.3.4 template<typename V> void mln::accu::stat::histo3d_rgb< V >::take(const histo3d_rgb< V > & other) [inline]

Update the histogram with an other histogram.

Parameters

[in] *other* the other histogram.

The end user shouldn't call this method. This is part of data compute interface mechanism.

Definition at line 286 of file histo3d_rgb.hh.

10.61.3.5 void mln::Accumulator< histo3d_rgb< V > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.61.3.6 void mln::Accumulator< histo3d_rgb< V > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.61.3.7 template<typename V> histo3d_rgb< V >::result mln::accu::stat::histo3d_rgb< V >::to_result () const [inline]

Accessors.

Return the histogram as an RGB [image3d](#). This is the machinery to communicate with data compute interface. The end user shouldn't use it.

Definition at line 293 of file histo3d_rgb.hh.

10.62 mln::accu::stat::max< T > Struct Template Reference

Generic max accumulator class.

```
#include <max.hh>
```

Inherits base< const T &, max< T > >.

Public Member Functions

- bool [is_valid](#) () const
Check whether this accu is able to return a result.
- void [set_value](#) (const T &t)
Force the value of the min to t.
- void [take_as_init](#) (const T &t)
Take as initialization the value t.
- void [take_n_times](#) (unsigned n, const T &t)
Take n times the value t.
- const T & [to_result](#) () const
Get the value of the accumulator.

- void `init()`
Manipulators.

10.62.1 Detailed Description

`template<typename T> struct mln::accu::stat::max< T >`

Generic max accumulator class. The parameter `T` is the type of values.

Definition at line 101 of file accu/stat/max.hh.

10.62.2 Member Function Documentation

10.62.2.1 `template<typename T > void mln::accu::stat::max< T >::init() [inline]`

Manipulators.

Definition at line 146 of file accu/stat/max.hh.

10.62.2.2 `template<typename T > bool mln::accu::stat::max< T >::is_valid() const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 196 of file accu/stat/max.hh.

10.62.2.3 `template<typename T > void mln::accu::stat::max< T >::set_value(const T & t) [inline]`

Force the value of the min to `t`.

Definition at line 180 of file accu/stat/max.hh.

10.62.2.4 `void mln::Accumulator< max< T > >::take_as_init(const T & t) [inherited]`

Take as initialization the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.62.2.5 `void mln::Accumulator< max< T > >::take_n_times(unsigned n, const T & t) [inherited]`

Take `n` times the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.62.2.6 template<typename T > const T & mln::accu::stat::max< T >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 188 of file accu/stat/max.hh.

10.63 mln::accu::stat::max_h< V > Struct Template Reference

Generic max function based on histogram over a value set with type V.

```
#include <max_h.hh>
```

Inherits base< const V &, max_h< V > >.

Public Member Functions

- bool `is_valid()` const

Check whether this accu is able to return a result.

- void `take_as_init(const T &t)`

Take as initialization the value t.

- void `take_n_times(unsigned n, const T &t)`

Take n times the value t.

- const argument & `to_result()` const

Get the value of the accumulator.

- void `init()`

Manipulators.

10.63.1 Detailed Description

template<typename V> struct mln::accu::stat::max_h< V >

Generic max function based on histogram over a value set with type V.

Definition at line 100 of file max_h.hh.

10.63.2 Member Function Documentation

10.63.2.1 template<typename V > void mln::accu::stat::max_h< V >::init() [inline]

Manipulators.

Definition at line 280 of file max_h.hh.

10.63.2.2 template<typename V> bool mln::accu::stat::max_h< V >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 323 of file max_h.hh.

10.63.2.3 void mln::Accumulator< max_h< V > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.63.2.4 void mln::Accumulator< max_h< V > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.63.2.5 template<typename V> const max_h< V >::argument & mln::accu::stat::max_h< V >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 304 of file max_h.hh.

10.64 mln::accu::stat::mean< T, S, M > Struct Template Reference

Generic mean accumulator class.

```
#include <mean.hh>
```

Inherits base< M, mean< T, S, M > >.

Public Member Functions

- **accu::math::count< T >::result count () const**

Get the cardinality.

- **bool is_valid () const**

Check whether this accu is able to return a result.

- **accu::math::sum< T >::result sum () const**

Get the sum of values.

- **void take_as_init (const T &t)**

Take as initialization the value t.

- **void take_n_times (unsigned n, const T &t)**

Take n times the value t.

- `M to_result () const`

Get the value of the accumulator.

- `void init ()`

Manipulators.

10.64.1 Detailed Description

```
template<typename T, typename S = typename mln::value::props< T >::sum, typename M = S>
struct mln::accu::stat::mean< T, S, M >
```

Generic mean accumulator class. Parameter T is the type of values that we sum. Parameter S is the type to store the sum of values; the default type of S is the summation type (property) of T. Parameter M is the type of the mean value; the default type of M is S.

Definition at line 119 of file accu/stat/mean.hh.

10.64.2 Member Function Documentation

**10.64.2.1 template<typename T , typename S , typename M > accu::math::count< T >::result
`mln::accu::stat::mean< T, S, M >::count () const [inline]`**

Get the cardinality.

Definition at line 242 of file accu/stat/mean.hh.

**10.64.2.2 template<typename T , typename S , typename M > void mln::accu::stat::mean< T, S,
`M >::init () [inline]`**

Manipulators.

Definition at line 173 of file accu/stat/mean.hh.

**10.64.2.3 template<typename T , typename S , typename M > bool mln::accu::stat::mean< T, S,
`M >::is_valid () const [inline]`**

Check whether this accu is able to return a result.

Always true here.

Definition at line 234 of file accu/stat/mean.hh.

**10.64.2.4 template<typename T , typename S , typename M > accu::math::sum< T >::result
`mln::accu::stat::mean< T, S, M >::sum () const [inline]`**

Get the sum of values.

Definition at line 251 of file accu/stat/mean.hh.

**10.64.2.5 void mln::Accumulator< mean< T, S, M > >::take_as_init (const T & t)
[inherited]**

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.64.2.6 void mln::Accumulator< mean< T, S, M > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.64.2.7 template<typename T, typename S, typename M> M mln::accu::stat::mean< T, S, M >::to_result () const [inline]

Get the value of the accumulator.


Definition at line 216 of file accu/stat/mean.hh.

10.65 mln::accu::stat::median_alt< S > Struct Template Reference

Generic [median_alt](#) function based on histogram over a value set with type S.

```
#include <median_alt.hh>
```

Inheritance diagram for mln::accu::stat::median_alt< S >:



Public Member Functions

- bool [is_valid](#) () const
Check whether this accu is able to return a result.
- void [take_as_init](#) (const T &t)

Take as initialization the value t.

- void **take_n_times** (unsigned n, const T &t)

Take n times the value t.

- const argument & **to_result** () const

Get the value of the accumulator.

- void **take** (const argument &t)

Manipulators.

10.65.1 Detailed Description

template<typename S> struct mln::accu::stat::median_alt< S >

Generic **median_alt** function based on histogram over a value set with type S.

Definition at line 54 of file median_alt.hh.

10.65.2 Member Function Documentation

10.65.2.1 template<typename S > bool mln::accu::stat::median_alt< S >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 282 of file median_alt.hh.

10.65.2.2 template<typename S > void mln::accu::stat::median_alt< S >::take (const argument & t) [inline]

Manipulators.

Definition at line 165 of file median_alt.hh.

10.65.2.3 void mln::Accumulator< median_alt< S > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.65.2.4 void mln::Accumulator< median_alt< S > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.65.2.5 template<typename S > const median_alt< S >::argument & mln::accu::stat::median_alt< S >::to_result () const [inline]

Get the value of the accumulator.


Definition at line 274 of file median_alt.hh.

10.66 mln::accu::stat::median_h< V > Struct Template Reference

Generic median function based on histogram over a value set with type V.

```
#include <median_h.hh>
```

Inheritance diagram for mln::accu::stat::median_h< V >:



Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- const argument & [to_result \(\) const](#)

Get the value of the accumulator.

- void [init \(\)](#)

Manipulators.

10.66.1 Detailed Description

template<typename V> struct mln::accu::stat::meta::deviation::median_h< V >

Generic median function based on histogram over a value set with type V.

Definition at line 82 of file median_h.hh.

10.66.2 Member Function Documentation

10.66.2.1 template<typename V> void mln::accu::stat::meta::deviation::median_h< V >::init() [inline]

Manipulators.

Definition at line 267 of file median_h.hh.

10.66.2.2 template<typename V> bool mln::accu::stat::meta::deviation::median_h< V >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 299 of file median_h.hh.

10.66.2.3 void mln::Accumulator< median_h< V > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.66.2.4 void mln::Accumulator< median_h< V > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.66.2.5 template<typename V> const median_h< V >::argument & mln::accu::stat::meta::deviation::median_h< V >::to_result() const [inline]

Get the value of the accumulator.


Definition at line 281 of file median_h.hh.

10.67 mln::accu::stat::meta::deviation Struct Reference

Meta accumulator for deviation.

```
#include <deviation.hh>
```

Inheritance diagram for mln::accu::stat::meta::deviation:



10.67.1 Detailed Description

Meta accumulator for deviation.

Definition at line 105 of file deviation.hh.

10.68 mln::accu::stat::min< T > Struct Template Reference

Generic min accumulator class.

```
#include <min.hh>
```

Inherits base< const T &, min< T > >.

Public Member Functions

- bool `is_valid () const`
Check whether this accu is able to return a result.
- void `set_value (const T &t)`
Force the value of the min to t.

- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `const T & to_result () const`
Get the value of the accumulator.

- `void init ()`
Manipulators.

10.68.1 Detailed Description

`template<typename T> struct mln::accu::stat::min< T >`

Generic min accumulator class. The parameter T is the type of values.

Definition at line 102 of file accu/stat/min.hh.

10.68.2 Member Function Documentation

10.68.2.1 `template<typename T> void mln::accu::stat::min< T >::init () [inline]`

Manipulators.

Definition at line 147 of file accu/stat/min.hh.

10.68.2.2 `template<typename T> bool mln::accu::stat::min< T >::is_valid () const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 195 of file accu/stat/min.hh.

10.68.2.3 `template<typename T> void mln::accu::stat::min< T >::set_value (const T & t) [inline]`

Force the value of the min to t.

Definition at line 179 of file accu/stat/min.hh.

10.68.2.4 `void mln::Accumulator< min< T > >::take_as_init (const T & t) [inherited]`

Take as initialization the value t.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

**10.68.2.5 void mln::Accumulator< min< T > >::take_n_times (unsigned n, const T & t)
[inherited]**

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

**10.68.2.6 template<typename T> const T & mln::accu::stat::min< T >::to_result () const
[inline]**

Get the value of the accumulator.

Definition at line 187 of file accu/stat/min.hh.

10.69 mln::accu::stat::min_h< V > Struct Template Reference

Generic min function based on histogram over a value set with type V.

```
#include <min_h.hh>
```

Inherits base< const V &, min_h< V > >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- const argument & [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.

10.69.1 Detailed Description

template<typename V> struct mln::accu::stat::min_h< V >

Generic min function based on histogram over a value set with type V.

Definition at line 100 of file min_h.hh.

10.69.2 Member Function Documentation

10.69.2.1 template<typename V> void mln::accu::stat::min_h< V >::init() [inline]

Manipulators.

Definition at line 256 of file min_h.hh.

10.69.2.2 template<typename V> bool mln::accu::stat::min_h< V >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 298 of file min_h.hh.

10.69.2.3 void mln::Accumulator< min_h< V > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.69.2.4 void mln::Accumulator< min_h< V > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.69.2.5 template<typename V> const min_h< V >::argument & mln::accu::stat::min_h< V >::to_result() const [inline]

Get the value of the accumulator.


Definition at line 280 of file min_h.hh.

10.70 mln::accu::stat::min_max< V > Struct Template Reference

Generic min and max accumulator class.

```
#include <min_max.hh>
```

Inheritance diagram for `mln::accu::stat::min_max< V >`:



Public Member Functions

- `min< V >::result first () const`
Return the result of the first accumulator.
- `min< V > first_accu () const`
Return the first accumulator.
- `bool is_valid () const`
Check whether this accu is able to return a result.
- `max< V >::result second () const`
Return the result of the second accumulator.
- `max< V > second_accu () const`
Return the second accumulator.
- template<typename T >
 `void take_as_init (const T &t)`
Take as initialization the value t.
- template<typename T >
 `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `void init ()`
Manipulators.

- std::pair< typename min< V >::result, typename max< V >::result > **to_result** () const
Get the value of the accumulator.

10.70.1 Detailed Description

template<typename V> struct mln::accu::stat::min_max< V >

Generic min and max accumulator class. The parameter V is the type of values.

Definition at line 61 of file accu/stat/min_max.hh.

10.70.2 Member Function Documentation

10.70.2.1 min< V > ::result mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::first () const [inherited]

Return the result of the first accumulator.

10.70.2.2 min< V > mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::first_accu () const [inherited]

Return the first accumulator.

10.70.2.3 void mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::init () [inherited]

Manipulators.

10.70.2.4 bool mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::is_valid () const [inherited]

Check whether this accu is able to return a result.

Always true here.

10.70.2.5 max< V > ::result mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::second () const [inherited]

Return the result of the second accumulator.

10.70.2.6 max< V > mln::accu::pair< min< V > , max< V > , mln_argument(min< V >) >::second_accu () const [inherited]

Return the second accumulator.

10.70.2.7 template<typename E> template<typename T> void mln::Accumulator< E >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

Definition at line 186 of file `accumulator.hh`.

References `mln::mln_exact()`.

10.70.2.8 template<typename E> template<typename T> void mln::Accumulator< E >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

Definition at line 213 of file `accumulator.hh`.

References `mln::mln_exact()`.

10.70.2.9 std::pair<typename min< V > ::result, typename max< V > ::result> mln::accu::pair< min< V >, max< V >, mln_argument(min< V >) >::to_result () const [inherited]

Get the value of the accumulator.

10.71 mln::accu::stat::rank< T > Struct Template Reference

Generic rank accumulator class.

```
#include <rank.hh>
```

Inherits `base< const T &, rank< T > >`.

Public Member Functions

- `bool is_valid () const`

Check whether this accu is able to return a result.

- `unsigned k () const`

Give the rank.

- `void take_as_init (const T &t)`

Take as initialization the value t .

- `void take_n_times (unsigned n, const T &t)`

Take n times the value t .

- `const T & to_result () const`

Get the value of the accumulator.

- `void init()`
Manipulators.

10.71.1 Detailed Description

`template<typename T> struct mln::accu::stat::rank< T >`

Generic rank accumulator class. The parameter `T` is the type of values.

Definition at line 60 of file rank.hh.

10.71.2 Member Function Documentation

10.71.2.1 `template<typename T > void mln::accu::stat::rank< T >::init() [inline]`

Manipulators.

Definition at line 319 of file rank.hh.

10.71.2.2 `template<typename T > bool mln::accu::stat::rank< T >::is_valid() const [inline]`

Check whether this accu is able to return a result.

Always true here.

Definition at line 343 of file rank.hh.

10.71.2.3 `template<typename T > unsigned mln::accu::stat::rank< T >::k() const [inline]`

Give the rank.

Definition at line 178 of file rank.hh.

10.71.2.4 `void mln::Accumulator< rank< T > >::take_as_init(const T & t) [inherited]`

Take as initialization the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with `'_'`).

10.71.2.5 `void mln::Accumulator< rank< T > >::take_n_times(unsigned n, const T & t) [inherited]`

Take `n` times the value `t`.

Dev note: this is a final method; override if needed by `take_as_init_` (ending with `'_'`).

10.71.2.6 template<typename T > const T & mln::accu::stat::rank< T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 333 of file rank.hh.

10.72 mln::accu::stat::rank< bool > Struct Template Reference

rank accumulator class for Boolean.

```
#include <rank_bool.hh>
```

Inherits base< bool, rank< bool > >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void [take_as_init \(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times \(unsigned n, const T &t\)](#)

Take n times the value t.

- bool [to_result \(\) const](#)

Get the value of the accumulator.

- void [init \(\)](#)

Manipulators.

10.72.1 Detailed Description

```
template<> struct mln::accu::stat::rank< bool >
```

rank accumulator class for Boolean.

Definition at line 58 of file rank_bool.hh.

10.72.2 Member Function Documentation

10.72.2.1 void mln::accu::stat::rank< bool >::init () [inline]

Manipulators.

Definition at line 105 of file rank_bool.hh.

10.72.2.2 bool mln::accu::stat::rank< bool >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 157 of file rank_bool.hh.

10.72.2.3 void mln::Accumulator< rank< bool > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.72.2.4 void mln::Accumulator< rank< bool > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.72.2.5 bool mln::accu::stat::rank< bool >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 150 of file rank_bool.hh.

10.73 mln::accu::stat::rank_high_quant< T > Struct Template Reference

Generic rank accumulator class.

```
#include <rank_high_quant.hh>
```

Inherits base< const T &, rank_high_quant< T > >.

Public Member Functions

- bool **is_valid () const**

Check whether this accu is able to return a result.

- void **take_as_init (const T &t)**

Take as initialization the value t .

- void **take_n_times (unsigned n, const T &t)**

Take n times the value t .

- const T & **to_result () const**

Get the value of the accumulator.

- void **init** ()
Manipulators.

10.73.1 Detailed Description

template<typename T> struct mln::accu::stat::rank_high_quant< T >

Generic rank accumulator class. The parameter T is the type of values.

Definition at line 57 of file rank_high_quant.hh.

10.73.2 Member Function Documentation

10.73.2.1 template<typename T > void mln::accu::stat::rank_high_quant< T >::init () [inline]

Manipulators.

Definition at line 148 of file rank_high_quant.hh.

10.73.2.2 template<typename T > bool mln::accu::stat::rank_high_quant< T >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 197 of file rank_high_quant.hh.

10.73.2.3 void mln::Accumulator< rank_high_quant< T > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.73.2.4 void mln::Accumulator< rank_high_quant< T > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.73.2.5 template<typename T > const T & mln::accu::stat::rank_high_quant< T >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 183 of file rank_high_quant.hh.

10.74 mln::accu::stat::var< T > Struct Template Reference

Var accumulator class.

```
#include <var.hh>
```

Inherits base< algebra::mat< T::dim, T::dim, float >, var< T > >.

Public Types

- `typedef algebra::vec< dim, float > mean_t`

Type equipment.

Public Member Functions

- `bool is_valid () const`

Check whether this accu returns a valid result.

- `mean_t mean () const`

Get the mean vector.

- `unsigned n_items () const`

Get the number of items.

- `void take_as_init (const T &t)`

Take as initialization the value t.

- `void take_n_times (unsigned n, const T &t)`

Take n times the value t.

- `result to_result () const`

Get the accumulator result (the var value).

- `result variance () const`

Get the variance matrix.

- `void init ()`

Manipulators.

10.74.1 Detailed Description

`template<typename T> struct mln::accu::stat::var< T >`

Var accumulator class. Parameter T is the type of vectors

Definition at line 58 of file accu/stat/var.hh.

10.74.2 Member Typedef Documentation

10.74.2.1 template<typename T> typedef algebra::vec<dim,float> mln::accu::stat::var< T >::mean_t

Type equipment.

Definition at line 88 of file accu/stat/var.hh.

10.74.3 Member Function Documentation

10.74.3.1 template<typename T> void mln::accu::stat::var< T >::init() [inline]

Manipulators.

Definition at line 118 of file accu/stat/var.hh.

10.74.3.2 template<typename T> bool mln::accu::stat::var< T >::is_valid() const [inline]

Check whether this accu returns a valid result.

Definition at line 213 of file accu/stat/var.hh.

10.74.3.3 template<typename T> var< T >::mean_t mln::accu::stat::var< T >::mean() const [inline]

Get the mean vector.

Definition at line 200 of file accu/stat/var.hh.

References mln::literal::zero.

10.74.3.4 template<typename T> unsigned mln::accu::stat::var< T >::n_items() const [inline]

Get the number of items.

Definition at line 192 of file accu/stat/var.hh.

10.74.3.5 void mln::Accumulator< var< T > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.74.3.6 void mln::Accumulator< var< T > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.74.3.7 `template<typename T> var< T >::result mln::accu::stat::var< T >::to_result() const [inline]`

Get the accumulator result (the var value).

Definition at line 168 of file accu/stat/var.hh.

References `mln::literal::zero`.

10.74.3.8 `template<typename T> var< T >::result mln::accu::stat::var< T >::variance() const [inline]`

Get the variance matrix.

Definition at line 184 of file accu/stat/var.hh.

10.75 `mln::accu::stat::variance< T, S, R >` Struct Template Reference

Variance accumulator class.

```
#include <variance.hh>
```

Inherits base< R, variance< T, S, R > >.

Public Member Functions

- `bool is_valid() const`
Check whether this accu is able to return a result.
- `R mean() const`
Get the mean value.
- `unsigned n_items() const`
Get the number of items.
- `R standard_deviation() const`
Get the standard deviation value.
- `S sum() const`
Get the sum value.
- `void take_as_init(const T &t)`
Take as initialization the value t.
- `void take_n_times(unsigned n, const T &t)`
Take n times the value t.
- `R to_result() const`
Get the accumulator result (the variance value).

- R `var () const`
Get the variance value.

- void `init ()`
Manipulators.

10.75.1 Detailed Description

```
template<typename T, typename S = typename mln::value::props< T >::sum, typename R = S>
struct mln::accu::stat::variance< T, S, R >
```

Variance accumulator class. Parameter `T` is the type of values that we sum. Parameter `S` is the type to store the value sum and the sum of value * value; the default type of `S` is the summation type (property) of `T`. Parameter `R` is the type of the mean and variance values; the default type of `R` is `S`.

Definition at line 61 of file variance.hh.

10.75.2 Member Function Documentation

10.75.2.1 template<typename T, typename S, typename R> void mln::accu::stat::variance< T, S, R >::init () [inline]

Manipulators.

Definition at line 125 of file variance.hh.

References mln::literal::zero.

10.75.2.2 template<typename T, typename S, typename R> bool mln::accu::stat::variance< T, S, R >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 229 of file variance.hh.

10.75.2.3 template<typename T, typename S, typename R> R mln::accu::stat::variance< T, S, R >::mean () const [inline]

Get the mean value.

Definition at line 187 of file variance.hh.

References mln::literal::zero.

10.75.2.4 template<typename T, typename S, typename R> unsigned mln::accu::stat::variance< T, S, R >::n_items () const [inline]

Get the number of items.

Definition at line 205 of file variance.hh.

10.75.2.5 template<typename T , typename S , typename R > R mln::accu::stat::variance< T, S, R >::standard_deviation () const [inline]

Get the standard deviation value.

Definition at line 221 of file variance.hh.

References `mln::accu::stat::variance< T, S, R >::to_result()`.

10.75.2.6 template<typename T , typename S , typename R > S mln::accu::stat::variance< T, S, R >::sum () const [inline]

Get the sum value.

Definition at line 197 of file variance.hh.

10.75.2.7 void mln::Accumulator< variance< T, S, R > >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.75.2.8 void mln::Accumulator< variance< T, S, R > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by `take_as_init_` (ending with '_').

10.75.2.9 template<typename T , typename S , typename R > R mln::accu::stat::variance< T, S, R >::to_result () const [inline]

Get the accumulator result (the variance value).

Definition at line 176 of file variance.hh.

Referenced by `mln::accu::stat::variance< T, S, R >::standard_deviation()`, and `mln::accu::stat::variance< T, S, R >::var()`.

10.75.2.10 template<typename T , typename S , typename R > R mln::accu::stat::variance< T, S, R >::var () const [inline]

Get the variance value.

Definition at line 213 of file variance.hh.

References `mln::accu::stat::variance< T, S, R >::to_result()`.

10.76 `mln::accu::tuple< A, n, >` Struct Template Reference

Generic tuple of accumulators.

```
#include <tuple.hh>
```

Inherits base< boost::tuple< BOOST_PP_REPEAT(10, RESULT_ACCU, Le Ricard ya que ca de vrai!) >, tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >.

Public Member Functions

- bool [is_valid \(\) const](#)
Check whether this accu is able to return a result.
- void [take_as_init \(const T &t\)](#)
Take as initialization the value t.
- void [take_n_times \(unsigned n, const T &t\)](#)
Take n times the value t.
- res [to_result \(\) const](#)
Get the value of the accumulator.
- void [init \(\)](#)
Manipulators.

10.76.1 Detailed Description

```
template<typename A, unsigned n, BOOST_PP_ENUM_PARAMS_WITH_A_DEFAULT(10, typename T, boost::tuples::null_type)> struct mln::accu::tuple< A, n, >
```

Generic tuple of accumulators. The parameter T is the type of values.

Definition at line 74 of file tuple.hh.

10.76.2 Member Function Documentation

10.76.2.1 template<typename A , unsigned n, BOOST_PP_ENUM_PARAMS(10, typename T) > void mln::accu::tuple< A, n, >::init () [inline]

Manipulators.

Definition at line 197 of file tuple.hh.

10.76.2.2 template<typename A , unsigned n, BOOST_PP_ENUM_PARAMS(10, typename T) > bool mln::accu::tuple< A, n, >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 239 of file tuple.hh.

10.76.2.3 void mln::Accumulator< tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >::take_as_init (const T & t) [inherited]

Take as initialization the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.76.2.4 void mln::Accumulator< tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T)> >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t .

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.76.2.5 template<typename A , unsigned n, BOOST_PP_ENUM_PARAMS(10, typename T) > tuple< A, n, BOOST_PP_ENUM_PARAMS(10, T) >::res mln::accu::tuple< A, n, >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 229 of file tuple.hh.

10.77 mln::accu::val< A > Struct Template Reference

Generic val of accumulators.

```
#include <v.hh>
```

Inherits base< const A::result &, val< A > >.

Public Member Functions

- bool **is_valid () const**

Check whether this accu is able to return a result.

- void **take_as_init (const T &t)**

Take as initialization the value t .

- void **take_n_times (unsigned n, const T &t)**

Take n times the value t .

- const A::result & **to_result () const**

Get the value of the accumulator.

- void **init ()**

Manipulators.

10.77.1 Detailed Description

template<typename A> struct mln::accu::val< A >

Generic val of accumulators.

Definition at line 50 of file v.hh.

10.77.2 Member Function Documentation

10.77.2.1 template<typename A > void mln::accu::val< A >::init() [inline]

Manipulators.

Definition at line 119 of file v.hh.

10.77.2.2 template<typename A > bool mln::accu::val< A >::is_valid() const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 177 of file v.hh.

10.77.2.3 void mln::Accumulator< val< A > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.77.2.4 void mln::Accumulator< val< A > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.77.2.5 template<typename A > const A::result & mln::accu::val< A >::to_result() const [inline]

Get the value of the accumulator.


Definition at line 169 of file v.hh.

10.78 mln::Accumulator< E > Struct Template Reference

Base class for implementation of accumulators.

```
#include <accumulator.hh>
```

Inheritance diagram for mln::Accumulator< E >:



Public Member Functions

- template<typename T >
void [take_as_init](#) (const T &t)
Take as initialization the value t.

- template<typename T >
void [take_n_times](#) (unsigned n, const T &t)
Take n times the value t.

10.78.1 Detailed Description

template<typename E> struct mln::Accumulator< E >

Base class for implementation of accumulators. The parameter *E* is the exact type.

See also

[mln::doc::Accumulator](#) for a complete documentation of this class contents.

Definition at line 78 of file accumulator.hh.

10.78.2 Member Function Documentation

10.78.2.1 template<typename E > template<typename T > void mln::Accumulator< E >::take_as_init (const T & t)

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

Definition at line 186 of file accumulator.hh.

References mln::mln_exact().

10.78.2.2 template<typename E > template<typename T > void mln::Accumulator< E >::take_n_times (unsigned n, const T & t)

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

Definition at line 213 of file accumulator.hh.

References mln::mln_exact().

10.79 mln::algebra::h_mat< d, T > Struct Template Reference

N-Dimensional matrix with homogeneous coordinates.

```
#include <h_mat.hh>
```

Inherits mln::algebra::mat< d+1, d+1, T >.

Public Types

- enum

Dimension is the 'natural' one (3 for 3D), not the one of the vector (dim + 1).

Public Member Functions

- `mat< n, m, T > _1 () const`
Return the inverse of the matrix.
- `h_mat ()`
Constructor without argument.
- `h_mat (const mat< d+1, d+1, T > &x)`
Constructor with the underlying matrix.
- `mat< m, n, T > t () const`
Return the transpose of the matrix.

10.79.1 Detailed Description

`template<unsigned d, typename T> struct mln::algebra::h_mat< d, T >`

N-Dimensional matrix with homogeneous coordinates.

Definition at line 49 of file algebra/h_mat.hh.

10.79.2 Member Enumeration Documentation

10.79.2.1 `template<unsigned d, typename T> anonymous enum`

Dimension is the 'natural' one (3 for 3D), not the one of the vector (dim + 1).

Definition at line 52 of file algebra/h_mat.hh.

10.79.3 Constructor & Destructor Documentation

10.79.3.1 `template<unsigned d, typename T> mln::algebra::h_mat< d, T >::h_mat () [inline]`

Constructor without argument.

Definition at line 67 of file algebra/h_mat.hh.

10.79.3.2 `template<unsigned d, typename T> mln::algebra::h_mat< d, T >::h_mat (const mat< d+1, d+1, T > & x) [inline]`

Constructor with the underlying matrix.

Definition at line 74 of file algebra/h_mat.hh.

10.79.4 Member Function Documentation

10.79.4.1 template<unsigned n, unsigned m, typename T> mat< n, m, T > mln::algebra::mat< n, m, T >::_1() const [inline, inherited]

Return the inverse of the matrix.

Only compile on square matrix.

Definition at line 604 of file algebra/mat.hh.

10.79.4.2 template<unsigned n, unsigned m, typename T> mat< m, n, T > mln::algebra::mat< n, m, T >::t() const [inline, inherited]

Return the transpose of the matrix.

Definition at line 538 of file algebra/mat.hh.

10.80 mln::algebra::h_vec< d, C > Class Template Reference

N-Dimensional vector with homogeneous coordinates.

```
#include <h_vec.hh>
```

Inherits mln::algebra::vec< d+1, C >.

Public Types

- enum

Dimension is the 'natural' one (3 for 3D), not the one of the vector (dim + 1).

Public Member Functions

- [h_vec\(\)](#)

Constructor without argument.

- [h_vec\(const vec< d+1, C > &other\)](#)

Constructor with the underlying vector.

- template<typename U>
[operator mat< n, 1, U >\(\)](#) const

Conversion to a matrix.

- [mat< 1, n, T > t\(\)](#) const

Transposition.

- [vec< d, C > to_vec\(\)](#) const

Back to the natural (non-homogeneous) space.

Static Public Attributes

- static const vec< n, T > **origin** = all_to(0)
Origin value.
- static const vec< n, T > **zero** = all_to(0)
Zero value.

10.80.1 Detailed Description

template<unsigned d, typename C> class mln::algebra::h_vec< d, C >

N-Dimensional vector with homogeneous coordinates.

Definition at line 94 of file h_vec.hh.

10.80.2 Member Enumeration Documentation

10.80.2.1 template<unsigned d, typename C> anonymous enum

Dimension is the 'natural' one (3 for 3D), not the one of the vector (dim + 1).

Definition at line 98 of file h_vec.hh.

10.80.3 Constructor & Destructor Documentation

10.80.3.1 template<unsigned d, typename C> mln::algebra::h_vec< d, C >::h_vec () **[inline]**

Constructor without argument.

Definition at line 117 of file h_vec.hh.

References mln::literal::one.

10.80.3.2 template<unsigned d, typename C> mln::algebra::h_vec< d, C >::h_vec (const vec< d+1, C > & other) **[inline]**

Constructor with the underlying vector.

Definition at line 128 of file h_vec.hh.

10.80.4 Member Function Documentation

10.80.4.1 template<unsigned n, typename T> template<typename U> mln::algebra::vec< n, T >::operator mat< n, 1, U > () const **[inline, inherited]**

Conversion to a matrix.

Definition at line 368 of file algebra/mat.hh.

10.80.4.2 template<unsigned n, typename T> mat< 1, n, T > mln::algebra::vec< n, T >::t() const [inline, inherited]

Transposition.

Definition at line 858 of file algebra/mat.hh.

10.80.4.3 template<unsigned d, typename C> vec< d, C > mln::algebra::h_vec< d, C >::to_vec() const [inline]

Back to the natural (non-homogeneous) space.

Definition at line 145 of file h_vec.hh.

10.80.5 Member Data Documentation

10.80.5.1 template<unsigned n, typename T> const vec< n, T > mln::algebra::vec< n, T >::origin = all_to(0) [static, inherited]

Origin value.

Definition at line 247 of file algebra/vec.hh.

10.80.5.2 template<unsigned n, typename T> const vec< n, T > mln::algebra::vec< n, T >::zero = all_to(0) [static, inherited]

Zero value.

Definition at line 244 of file algebra/vec.hh.

10.81 mln::bkd_pixter1d< I > Class Template Reference

Backward pixel iterator on a 1-D image with border.

```
#include <pixter1d.hh>
```

Inherits backward_pixel_iterator_base_< I, bkd_pixter1d< I > >.

Public Types

- `typedef I image`

Image type.

Public Member Functions

- `bkd_pixter1d (I &image)`

Constructor.

- `void next ()`

Go to the next element.

10.81.1 Detailed Description

`template<typename I> class mln::bkd_pixter1d< I >`

Backward pixel iterator on a 1-D image with border.

Definition at line 69 of file pixter1d.hh.

10.81.2 Member Typedef Documentation

10.81.2.1 `template<typename I> typedef I mln::bkd_pixter1d< I >::image`

[Image](#) type.

Definition at line 76 of file pixter1d.hh.

10.81.3 Constructor & Destructor Documentation

10.81.3.1 `template<typename I> mln::bkd_pixter1d< I >::bkd_pixter1d (I & image) [inline]`

Constructor.

Parameters

`[in] image` The image this pixel iterator is bound to.

Definition at line 117 of file pixter1d.hh.

10.81.4 Member Function Documentation

10.81.4.1 `void mln::Iterator< bkd_pixter1d< I > >::next () [inherited]`

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.82 mln::bkd_pixter2d< I > Class Template Reference

Backward pixel iterator on a 2-D image with border.

`#include <pixter2d.hh>`

Inherits backward_pixel_iterator_base< I, bkd_pixter2d< I > >.

Public Types

- `typedef I image`

Image type.

Public Member Functions

- `bkd_pixter2d (I &image)`

Constructor.

- `void next ()`

Go to the next element.

10.82.1 Detailed Description

`template<typename I> class mln::bkd_pixter2d< I >`

Backward pixel iterator on a 2-D image with border.

Definition at line 87 of file pixter2d.hh.

10.82.2 Member Typedef Documentation

10.82.2.1 `template<typename I > typedef I mln::bkd_pixter2d< I >::image`

Image type.

Definition at line 94 of file pixter2d.hh.

10.82.3 Constructor & Destructor Documentation

10.82.3.1 `template<typename I > mln::bkd_pixter2d< I >::bkd_pixter2d (I & image) [inline]`

Constructor.

Parameters

`[in] image` The image this pixel iterator is bound to.

Definition at line 169 of file pixter2d.hh.

10.82.4 Member Function Documentation

10.82.4.1 `void mln::Iterator< bkd_pixter2d< I > >::next () [inherited]`

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.83 mln::bkd_pixter3d< I > Class Template Reference

Backward pixel iterator on a 3-D image with border.

```
#include <pixter3d.hh>
```

Inherits backward_pixel_iterator_base< I, bkd_pixter3d< I > >.

Public Types

- **typedef I image**

Image type.

Public Member Functions

- **bkd_pixter3d (I &image)**

Constructor.

- **void next ()**

Go to the next element.

10.83.1 Detailed Description

```
template<typename I> class mln::bkd_pixter3d< I >
```

Backward pixel iterator on a 3-D image with border.

Definition at line 100 of file pixter3d.hh.

10.83.2 Member Typedef Documentation

10.83.2.1 template<typename I > typedef I mln::bkd_pixter3d< I >::image

Image type.

Definition at line 107 of file pixter3d.hh.

10.83.3 Constructor & Destructor Documentation

10.83.3.1 `template<typename I> mln::bkd_pixter3d< I >::bkd_pixter3d (I & image) [inline]`

Constructor.

Parameters

[in] *image* The image this pixel iterator is bound to.

Definition at line 207 of file pixter3d.hh.

10.83.4 Member Function Documentation

10.83.4.1 `void mln::Iterator< bkd_pixter3d< I > >::next () [inherited]`

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition


The iterator is valid.

10.84 mln::box< P > Class Template Reference

Generic box class: site set containing points of a regular grid.

```
#include <box.hh>
```

Inheritance diagram for mln::box< P >:



Public Types

- enum
Dimension.
- typedef `box_bkd_piter_< P > bkd_piter`
Backward Site_Iterator associated type.
- typedef `P element`
Element associated type.
- typedef `box_fwd_piter_< P > fwd_piter`
Forward Site_Iterator associated type.
- typedef `fwd_piter piter`
Site_Iterator associated type.

- **typedef P psite**
Psite associated type.

- **typedef P site**
Site associated type.

Public Member Functions

- **const box< P > & bbox () const**
Give the bounding box of this site set.

- **box ()**
Constructor without argument.

- **box (const site &pmin, const site &pmax)**
Constructor of a box going from pmin to pmax.

- **void crop_wrt (const box< P > &b)**
Crop this bbox in order to fit in the reference box b.

- **void enlarge (unsigned b)**
Enlarge the box with a border b.

- **void enlarge (unsigned dim, unsigned b)**
Enlarge the box with a border b for dimension dim.

- **bool has (const P &p) const**
Test if p belongs to the box.

- **bool is_empty () const**
Test if this box is empty.

- **bool is_valid () const**
Test that the box owns valid data, i.e., is initialized and with pmin being 'less-than' pmax.

- **unsigned len (unsigned i) const**
Give the length of the i-th side of the box.

- **std::size_t memory_size () const**
Return the size of this site set in memory.

- **void merge (const box< P > &b)**
Merge inplace with another box.

- **unsigned nsites () const**
Give the number of sites of this box.

- `P pcenter () const`
Return the approximated central site of this box.
- `P & pmax ()`
Reference to the maximum point.
- `P pmax () const`
Maximum point.
- `P pmin () const`
Minimum point.
- `P & pmin ()`
Reference to the minimum point.
- `box< P > to_larger (unsigned b) const`
Give a larger box.
- `box` (typename `P::coord ninds`)

Related Functions

(Note that these are not member functions.)

- `template<typename P >
std::ostream & operator<< (std::ostream & ostr, const box< P > & b)`
Print a generic box b into the output stream ostr.

10.84.1 Detailed Description

`template<typename P> class mln::box< P >`

Generic box class: site set containing points of a regular grid. Parameter `P` is the corresponding type of point.

Definition at line 81 of file core/site_set/box.hh.

10.84.2 Member Typedef Documentation

10.84.2.1 `template<typename P> typedef box_bkd_piter_<P> mln::box< P >::bkd_piter`

Backward `Site_Iterator` associated type.

Definition at line 105 of file core/site_set/box.hh.

10.84.2.2 `template<typename P> typedef P mln::box< P >::element`

Element associated type.

Definition at line 90 of file core/site_set/box.hh.

10.84.2.3 template<typename P> typedef box_fwd_piter_<P> mln::box< P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 99 of file core/site_set/box.hh.

10.84.2.4 template<typename P> typedef fwd_piter mln::box< P >::fwd_piter

[Site_Iterator](#) associated type.

Definition at line 102 of file core/site_set/box.hh.

10.84.2.5 template<typename P> typedef P mln::box< P >::psite

Psite associated type.

Definition at line 93 of file core/site_set/box.hh.

10.84.2.6 template<typename P> typedef P mln::box< P >::site

[Site](#) associated type.

Definition at line 96 of file core/site_set/box.hh.

10.84.3 Member Enumeration Documentation**10.84.3.1 template<typename P> anonymous enum**

Dimension.

Definition at line 87 of file core/site_set/box.hh.

10.84.4 Constructor & Destructor Documentation**10.84.4.1 template<typename P> mln::box< P >::box() [inline]**

Constructor without argument.

Definition at line 275 of file core/site_set/box.hh.

10.84.4.2 template<typename P> mln::box< P >::box(const site & pmin, const site & pmax) [inline]

Constructor of a box going from `pmin` to `pmax`.

Definition at line 284 of file core/site_set/box.hh.

References `mln::box< P >::is_valid()`.

10.84.4.3 template<typename P> mln::box< P >::box(typename P::coord ninds) [inline, explicit]

Constructors with different numbers of arguments (sizes) w.r.t. the dimension.

Definition at line 293 of file core/site_set/box.hh.

References mln::literal::origin.

10.84.5 Member Function Documentation

10.84.5.1 const box< P > & mln::Box< box< P > >::bbox() const [inherited]

Give the bounding box of this site set.

Return the bounding box of this site set, so that is itself. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

10.84.5.2 template<typename P> void mln::box< P >::crop_wrt(const box< P > & b) [inline]

Crop this bbox in order to fit in the reference box *b*.

Definition at line 205 of file core/site_set/box.hh.

References mln::box< P >::pmax(), and mln::box< P >::pmin().

Referenced by mln::debug::draw_graph(), and mln::make_debug_graph_image().

10.84.5.3 template<typename P> void mln::box< P >::enlarge(unsigned b) [inline]

Enlarge the box with a border *b*.

Definition at line 337 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

Referenced by mln::registration::icp().

10.84.5.4 template<typename P> void mln::box< P >::enlarge(unsigned dim, unsigned b) [inline]

Enlarge the box with a border *b* for dimension *dim*.

Definition at line 351 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

10.84.5.5 template<typename P> bool mln::box< P >::has(const P & p) const [inline]

Test if *p* belongs to the box.

Parameters

[in] *p* A point site.

Definition at line 325 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

Referenced by mln::morpho::line_gradient().

10.84.5.6 bool mln::Box< box< P > >::is_empty () const [inherited]

Test if this box is empty.

10.84.5.7 template<typename P> bool mln::box< P >::is_valid () const [inline]

Test that the box owns valid data, i.e., is initialized and with pmin being 'less-than' pmax.

Definition at line 195 of file core/site_set/box.hh.

References mln::util::ord_weak().

Referenced by mln::box< P >::box(), mln::transform::distance_and_closest_point_geodesic(), mln::box< P >::enlarge(), mln::box< P >::has(), mln::box< P >::merge(), mln::box< P >::pcenter(), mln::box< P >::pmax(), mln::box< P >::pmin(), and mln::box< P >::to_larger().

10.84.5.8 unsigned mln::Box< box< P > >::len (unsigned i) const [inherited]

Give the length of the i -th side of the box.

Precondition

$i < \text{site}::\text{dim}$

Warning

This method is final for all box classes.

10.84.5.9 template<typename P> std::size_t mln::box< P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 407 of file core/site_set/box.hh.

10.84.5.10 template<typename P> void mln::box< P >::merge (const box< P > & b) [inline]

Merge inplace with another box.

Definition at line 221 of file core/site_set/box.hh.

References mln::box< P >::is_valid(), mln::box< P >::pmax(), and mln::box< P >::pmin().

10.84.5.11 unsigned mln::Box< box< P > >::nsites () const [inherited]

Give the number of sites of this box.

Return the number of sites of this box. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

10.84.5.12 template<typename P> P mln::box< P >::pcenter() const [inline]

Return the approximated central site of this box.

Definition at line 395 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

10.84.5.13 template<typename P> P mln::box< P >::pmax() const [inline]

Maximum point.

Definition at line 259 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

Referenced by mln::box< P >::crop_wrt(), mln::make::image3d(), mln::larger_than(), mln::io::fld::load(), and mln::box< P >::merge().

10.84.5.14 template<typename P> P & mln::box< P >::pmax() [inline]

Reference to the maximum point.

Definition at line 268 of file core/site_set/box.hh.

10.84.5.15 template<typename P> P & mln::box< P >::pmin() [inline]

Reference to the minimum point.

Definition at line 251 of file core/site_set/box.hh.

10.84.5.16 template<typename P> P mln::box< P >::pmin() const [inline]

Minimum point.

Definition at line 242 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

Referenced by mln::box< P >::crop_wrt(), mln::make::image3d(), mln::larger_than(), mln::io::fld::load(), and mln::box< P >::merge().

10.84.5.17 template<typename P> box< P > mln::box< P >::to_larger(unsigned b) const [inline]

Give a larger box.

Definition at line 378 of file core/site_set/box.hh.

References mln::box< P >::is_valid().

10.84.6 Friends And Related Function Documentation

10.84.6.1 template<typename P> std::ostream & operator<<(std::ostream & ostr, const box< P > & b) [related]

Print a generic box *b* into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *b* A generic box.

Returns

The modified output stream *ostr*.


Definition at line 414 of file core/site_set/box.hh.

10.85 mln::Box< E > Struct Template Reference

Base class for implementation classes of boxes.

```
#include <box.hh>
```

Inheritance diagram for mln::Box< E >:



Public Member Functions

- const E & **bbox** () const
Give the bounding box of this site set.
- bool **is_empty** () const
Test if this box is empty.
- unsigned **len** (unsigned i) const
Give the length of the i -th side of the box.
- unsigned **nsites** () const
Give the number of sites of this box.

Related Functions

(Note that these are not member functions.)

- template<typename Sl , typename Sr >
`p_set< typename Sl::site > diff (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Set theoretic difference of lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > inter (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Intersection between a couple of point sets.
- template<typename Sl , typename Sr >
`bool operator< (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Strict inclusion test between site sets lhs and rhs.
- template<typename Bl , typename Br >
`bool operator< (const Box< Bl > &lhs, const Box< Br > &rhs)`
Strict inclusion test between boxes lhs and rhs.
- template<typename S >
`std::ostream & operator<< (std::ostream &ostr, const Site_Set< S > &set)`
Print a site set set into the output stream ostr.
- template<typename Sl , typename Sr >
`bool operator<= (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Inclusion test between site sets lhs and rhs.
- template<typename Bl , typename Br >
`bool operator<= (const Box< Bl > &lhs, const Box< Br > &rhs)`
Inclusion test between boxes lhs and rhs.
- template<typename Sl , typename Sr >
`bool operator== (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Equality test between site sets lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > sym_diff (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Set theoretic symmetrical difference of lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > uni (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Union of a couple of point sets.
- template<typename S >
`p_set< typename S::site > unique (const Site_Set< S > &s)`
Give the unique set of s.

10.85.1 Detailed Description

`template<typename E> struct mln::Box< E >`

Base class for implementation classes of boxes. Boxes are particular site sets useful to bound any set of sites defined on a regular grid.

See also

[mln::doc::Box](#) for a complete documentation of this class contents.

Definition at line 48 of file core/concept/box.hh.

10.85.2 Member Function Documentation

10.85.2.1 template<typename E> const E & mln::Box< E >::bbox() const [inline]

Give the bounding box of this site set.

Return the bounding box of this site set, so that is itself. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

Definition at line 124 of file core/concept/box.hh.

10.85.2.2 template<typename E> bool mln::Box< E >::is_empty() const [inline]

Test if this box is empty.

Definition at line 167 of file core/concept/box.hh.

10.85.2.3 template<typename E> unsigned mln::Box< E >::len(unsigned i) const [inline]

Give the length of the i -th side of the box.

Precondition

$i < \text{site::dim}$

Warning

This method is final for all box classes.

Definition at line 131 of file core/concept/box.hh.

10.85.2.4 template<typename E> unsigned mln::Box< E >::nsites() const [inline]

Give the number of sites of this box.

Return the number of sites of this box. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

Definition at line 153 of file core/concept/box.hh.

Referenced by [mln::morpho::line_gradient\(\)](#).

10.85.3 Friends And Related Function Documentation

10.85.3.1 template<typename Sl , typename Sr > p_set< typename Sl::site > diff (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Set theoretic difference of lhs and rhs.

Definition at line 66 of file set/diff.hh.

10.85.3.2 template<typename Sl , typename Sr > p_set< typename Sl::site > inter (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Intersection between a couple of point sets.

Definition at line 62 of file set/inter.hh.

10.85.3.3 template<typename Sl , typename Sr > bool operator< (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Strict inclusion test between site sets lhs and rhs.

Parameters

[in] **lhs** A site set (strictly included?).

[in] **rhs** Another site set (includer?).

Definition at line 479 of file operators.hh.

10.85.3.4 template<typename Bl , typename Br > bool operator< (const Box< Bl > & lhs, const Box< Br > & rhs) [related]

Strict inclusion test between boxes lhs and rhs.

Parameters

[in] **lhs** A box (strictly included?).

[in] **rhs** Another box (includer?).

Definition at line 193 of file core/concept/box.hh.

10.85.3.5 template<typename S > std::ostream & operator<< (std::ostream & ostr, const Site_Set< S > & set) [related, inherited]

Print a site set set into the output stream ostr.

Parameters

[in, out] **ostr** An output stream.

[in] **set** A site set.

Returns

The modified output stream ostr.

Definition at line 505 of file operators.hh.

10.85.3.6 template<typename Sl , typename Sr > bool operator<= (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Inclusion test between site sets lhs and rhs.

Parameters

- [in] **lhs** A site set (included?).
- [in] **rhs** Another site set (includer?).

Definition at line 491 of file operators.hh.

10.85.3.7 template<typename Bl , typename Br > bool operator<= (const Box< Bl > & lhs, const Box< Br > & rhs) [related]

Inclusion test between boxes lhs and rhs.

Parameters

- [in] **lhs** A box (included?).
- [in] **rhs** Another box (includor?).

Definition at line 178 of file core/concept/box.hh.

10.85.3.8 template<typename Sl , typename Sr > bool operator== (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Equality test between site sets lhs and rhs.

Parameters

- [in] **lhs** A site set.
- [in] **rhs** Another site set.

Definition at line 467 of file operators.hh.

10.85.3.9 template<typename Sl , typename Sr > p_set< typename Sl::site > sym_diff (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Set theoretic symmetrical difference of lhs and rhs.

Definition at line 65 of file sym_diff.hh.

10.85.3.10 template<typename Sl , typename Sr > p_set< typename Sl::site > uni (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related, inherited]

Union of a couple of point sets.

Definition at line 61 of file uni.hh.

10.85.3.11 template<typename S> p_set< typename S::site > unique (const Site_Set< S > & s) [related, inherited]

Give the unique set of s.

Definition at line 61 of file unique.hh.

10.86 mln::box_runend_piter< P > Class Template Reference

A generic backward iterator on points by lines.

```
#include <box_runend_piter.hh>
```

Inherits site_set_iterator_base< box< P >, box_runend_piter< P > >.

Public Member Functions

- [box_runend_piter \(const box< P > &b\)](#)

Constructor.

- [void next \(\)](#)

Go to the next element.

- [unsigned run_length \(\) const](#)

Give the lenght of the run.

10.86.1 Detailed Description

```
template<typename P> class mln::box_runend_piter< P >
```

A generic backward iterator on points by lines. The parameter P is the type of points.

Definition at line 49 of file box_runend_piter.hh.

10.86.2 Constructor & Destructor Documentation

10.86.2.1 template<typename P> mln::box_runend_piter< P >::box_runend_piter (const box< P > & b) [inline]

Constructor.

Parameters

[in] **b** A box.

Definition at line 105 of file box_runend_piter.hh.

10.86.3 Member Function Documentation

10.86.3.1 void mln::Site_Iterator< box_runend_piter< P > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.86.3.2 template<typename P> unsigned mln::box_runend_piter< P >::run_length() const [inline]

Give the lenght of the run.

Definition at line 167 of file box_runend_piter.hh.

10.87 mln::box_runstart_piter< P > Class Template Reference

A generic forward iterator on points by lines.

```
#include <box_runstart_piter.hh>
```

Inherits site_set_iterator_base< box< P >, box_runstart_piter< P > >.

Public Member Functions

- [box_runstart_piter](#) (const [box< P >](#) &b)

Constructor

- [void next](#) ()

Go to the next element.

- [unsigned run_length](#) () const

Give the lenght of the run.

10.87.1 Detailed Description

template<typename P> class mln::box_runstart_piter< P >

A generic forward iterator on points by lines. The parameter *P* is the type of points.

Definition at line 49 of file box_runstart_piter.hh.

10.87.2 Constructor & Destructor Documentation

10.87.2.1 template<typename P> mln::box_runstart_piter<P>::box_runstart_piter (const box<P> & b) [inline]

Constructor.

Parameters

[in] **b** A box.

Definition at line 105 of file box_runstart_piter.hh.

10.87.3 Member Function Documentation

10.87.3.1 void mln::Site_Iterator<box_runstart_piter<P>>::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.87.3.2 template<typename P> unsigned mln::box_runstart_piter<P>::run_length () const [inline]

Give the lenght of the run.


Definition at line 167 of file box_runstart_piter.hh.

10.88 mln::Browsing< E > Struct Template Reference

Base class for implementation classes that are browsings.

```
#include <browsing.hh>
```

Inheritance diagram for mln::Browsing< E >:



10.88.1 Detailed Description

template<typename E> struct mln::Browsing< E >

Base class for implementation classes that are browsings.

See also

[mln::doc::Browsing](#) for a complete documentation of this class contents.


Definition at line 56 of file `browsing.hh`.

10.89 mln::canvas::browsing::backdiagonal2d_t Struct Reference

[Browsing](#) in a certain direction.

```
#include <backdiagonal2d.hh>
```

Inheritance diagram for `mln::canvas::browsing::backdiagonal2d_t`:



10.89.1 Detailed Description

[Browsing](#) in a certain direction. This canvas browse all the point of an image 'input' of type 'I' and of dimension 'dim' in the direction 'dir'.

The functor should provide (In addition to 'input', 'I', 'dim' and 'dir') three methods :

- `init()` : Will be called at the beginning.
- `next()` : Will be called at each point 'p' (also provided by the functor).
- `final()`: Will be called at the end.

F shall features :

```
{
--- as types:
I;
--- as attributes:
dim;
dir; // and test dir < dim
input;
```

```
p;  
--- as methods:  
void init();  
void next();  
void final();  
}
```

Example :

-----> | 4 7 9 | 2 5 8 | 1 3 6

Definition at line 83 of file backdiagonal2d.hh.

10.90 mln::canvas::browsing::breadth_first_search_t Struct Reference

Breadth-first search algorithm for graph, on vertices.

```
#include <breadth_first_search.hh>
```

Inherits graph_first_search_t< breadth_first_search_t, std::queue >.

10.90.1 Detailed Description

Breadth-first search algorithm for graph, on vertices.

Definition at line 79 of file breadth_first_search.hh.

10.91 mln::canvas::browsing::depth_first_search_t Struct Reference

Breadth-first search algorithm for graph, on vertices.

```
#include <depth_first_search.hh>
```

Inherits graph_first_search_t< depth_first_search_t, std::stack >.

10.91.1 Detailed Description

Breadth-first search algorithm for graph, on vertices.


Definition at line 80 of file depth_first_search.hh.

10.92 mln::canvas::browsing::diagonal2d_t Struct Reference

[Browsing](#) in a certain direction.

```
#include <diagonal2d.hh>
```

Inheritance diagram for `mln::canvas::browsing::diagonal2d_t`:



10.92.1 Detailed Description

[Browsing](#) in a certain direction. This canvas browse all the point of an image 'input' of type 'I' and of dimension 'dim' in the direction 'dir'.

The functor should provide (In addition to 'input', 'I', 'dim' and 'dir') three methods :

- `init()` : Will be called at the beginning.
- `next()` : Will be called at each point 'p' (also provided by the functor).
- `final()`: Will be called at the end.

F shall features :

```
{
--- as types:
I;
--- as attributes:
dim;
dir; // and test dir < dim
input;
```

```
p;
--- as methods:
void init();
void next();
void final();
}
```

Example :

```
| 1 3 6 | 2 5 8 | 4 7 9 L----->
```


Definition at line 82 of file diagonal2d.hh.

10.93 mln::canvas::browsing::dir_struct_elt_incr_update_t Struct Reference

[Browsing](#) in a certain direction with a segment.

```
#include <dir_struct_elt_incr_update.hh>
```

Inheritance diagram for mln::canvas::browsing::dir_struct_elt_incr_update_t:



10.93.1 Detailed Description

[Browsing](#) in a certain direction with a segment. This canvas browse all the point of an image 'input' of type 'I', of dimension 'dim' in the direction 'dir' with considering weigh the 'length' nearest points.

The functor should provide (In addition to 'input', 'I', 'dim', 'dir' and 'length') six methods :

- `init()` : Will be called at the beginning.
- `init_line()` : Will be called at the beginning of each line.
- `add_point(q)` : Will be called for taking the new point '`q`' into account.
- `remove_point(q)`: Will be called for untaking the new point '`q`' into account.
- `next()` : Will be called at each point '`p`' (also provided by the functor).
- `final()` : Will be called at the end.

`F` shall features :

```
{
--- as types:
I;
--- as attributes:
dim;
dir; // and test dir < dim
input;
p;
length;
--- as methods:
void init();
void init_line();
void add_point(q)
void remove_point(q)
void next();
void final();
}
```


Definition at line 86 of file `dir_struct_elt_incr_update.hh`.

10.94 mln::canvas::browsing::directional_t Struct Reference

[Browsing](#) in a certain direction.

```
#include <directional.hh>
```

Inheritance diagram for mln::canvas::browsing::directional_t:



10.94.1 Detailed Description

[Browsing](#) in a certain direction. This canvas browse all the point of an image 'input' of type 'I' and of dimension 'dim' in the direction 'dir'.

The functor should provide (In addition to 'input', 'I', 'dim' and 'dir') three methods :

- init() : Will be called at the beginning.
- next() : Will be called at each point 'p' (also provided by the functor).
- final(): Will be called at the end.

F shall features :

```
{
--- as types:
I;
--- as attributes:
dim;
dir; // and test dir < dim
input;
```

```
p;
--- as methods:
void init();
void next();
void final();
}
```

Example :

```
1 0 0 2 0 0 3 0 0
4 0 0 5 0 0 6 0 0
7 0 0 8 0 0 9 0 0
```


Definition at line 90 of file directional.hh.

10.95 mln::canvas::browsing::fwd_t Struct Reference

Canvas for forward browsing.

```
#include <fwd.hh>
```

Inheritance diagram for mln::canvas::browsing::fwd_t:



10.95.1 Detailed Description

Canvas for forward browsing. This canvas browse all the points of an image 'input' of type 'I' from left to right and from top to bottom

The functor should provide (In addition of 'I' and 'input') three methods :

- init() : Will be called at the beginning.
- next() : Will be called at each point 'p' (also provided by the functor).
- final(): Will be called at the end.

F shall feature:

```
{  
--- as typedef:  
I;  
--as attributes:  
input;  
p;  
--- as method:  
void init();  
void next();  
void final();  
}
```


Definition at line 72 of file fwd.hh.

10.96 mln::canvas::browsing::hyper_directional_t Struct Reference

[Browsing](#) in a certain direction.

```
#include <hyper_directional.hh>
```

Inheritance diagram for `mln::canvas::browsing::hyper_directional_t`:



10.96.1 Detailed Description

Browsing in a certain direction. This canvas browse all the point of an image 'input' of type 'I' and of dimension 'dim' in the direction 'dir'.

The functor should provide (In addition to 'input', 'I', 'dim' and 'dir') three methods :

- `init()` : Will be called at the beginning.
- `next()` : Will be called at each point 'p' (also provided by the functor).
- `final()`: Will be called at the end.

F shall features :

```
{
--- as types:
I;
--- as attributes:
dim;
dir; // and test dir < dim
input;
```

```
p;
--- as methods:
void init();
void next();
void final();
}
```


Definition at line 74 of file hyper_directional.hh.

10.97 mln::canvas::browsing::snake_fwd_t Struct Reference

[Browsing](#) in a snake-way, forward.

```
#include <snake_fwd.hh>
```

Inheritance diagram for mln::canvas::browsing::snake_fwd_t:



10.97.1 Detailed Description

[Browsing](#) in a snake-way, forward. This canvas browse all the point of an image 'input' like this :

-----> <-----' '----->

The functor should provide (In addition to 'input') four methods :

- init() : Will be called at the beginning.

- down() : Will be called after each moving down. (will also be called once at the first point).

- fwd() : Will be called after each moving right.

- bwd() : Will ba called after each moving left.

This methods should acces to the current working point 'p' also provided by the functor.

Warning: This canvas works only on 2D.

F shall feature:

```
{
--- as attributes:
input;
p;
--- as methods:
void init();
void down();
void fwd();
void bwd();
}
```


Definition at line 84 of file snake_fwd.hh.

10.98 mln::canvas::browsing::snake_generic_t Struct Reference

Multidimentional [Browsing](#) in a given-way.

```
#include <snake_generic.hh>
```

Inheritance diagram for mln::canvas::browsing::snake_generic_t:



10.98.1 Detailed Description

Multidimensional [Browsing](#) in a given-way. F shall feature:

```
{
--- as attributes:
input;
p;
--- as methods:
void init();
void *() moves[];
dpsite dps[];
}
```

`init` is called before browsing

The snake follow dimension using the delta point site of `dps`. `dps[0]` = delta psite following the global dimension (forward) `dps[1]` = delta psite following the 2nd dimension to follow (forward). `dps[2]` = delta psite following the 2nd dimension to follow (backward). `dps[3]` = delta psite following the 3rd dimension to follow (forward). `dps[3]` = delta psite following the 3rd dimension to follow (backward).

`moves` contains pointer to f's members. These members will be call in each time the snake progress in the

correct dimension :

moves[i] is called at each move following the delta psite dps[i]


Definition at line 76 of file snake_generic.hh.

10.99 mln::canvas::browsing::snake_vert_t Struct Reference

[Browsing](#) in a snake-way, forward.

```
#include <snake_vert.hh>
```

Inheritance diagram for mln::canvas::browsing::snake_vert_t:



10.99.1 Detailed Description

[Browsing](#) in a snake-way, forward. This canvas browse all the point of an image 'input' like this :

| \ | | | | / | \ |

The functor should provide (In addition to 'input') four methods :

- `init()` : Will be called at the beginning.
- `down()` : Will be called after each moving down.
- `up()` : Will be called after each moving up.

- `fwd()` : Will be called after each moving right. (will also be called once at the first point).

This methods should acces to the current working point 'p' also provided by the functor.

Warning: This canvas works only on 2D.

F shall feature:

```
{
--- as attributes:
input;
p;
--- as methods:
void init();
void down();
void up();
void fwd();
}
```

Definition at line 83 of file snake_vert.hh.

10.100 mln::canvas::chamfer< F > Struct Template Reference

Compute chamfer distance.

```
#include <chamfer.hh>
```

10.100.1 Detailed Description

```
template<typename F> struct mln::canvas::chamfer< F >
```

Compute chamfer distance.

Definition at line 47 of file canvas/chamfer.hh.

10.101 mln::category< R(*)(A) > Struct Template Reference

Category declaration for a unary C function.

```
#include <c.hh>
```

10.101.1 Detailed Description

```
template<typename R, typename A> struct mln::category< R(*)(A) >
```

Category declaration for a unary C function.

Definition at line 51 of file c.hh.

10.102 mln::complex_image< D, G, V > Class Template Reference

[Image](#) based on a complex.

```
#include <complex_image.hh>
```

Inherits `image_primary< V, p_complex< D, G >, complex_image< D, G, V > >`.

Public Types

- `typedef G geom`
The geometry type of the complex.
- `typedef V & lvalue`
Return type of read-write access.
- `typedef const V & rvalue`
Return type of read-only access.
- `typedef complex_image< D, tag::psite_< G >, tag::value_< V > > skeleton`
Skeleton.
- `typedef V value`
Value associated type.

Public Member Functions

- `rvalue operator() (const complex_psite< D, G > &p) const`
Read-only access of face value at point site p.
- `lvalue operator() (const complex_psite< D, G > &p)`
Read-write access of face value at point site p.
- `complex_image ()`
Constructors.
- `const p_complex< D, G > & domain () const`
Accessors.
- `const metal::vec< D+1, std::vector< mlc_unbool(V) > > & values () const`
Return the array of values associated to the faces.

Static Public Attributes

- `static const unsigned dim = D`
The dimension of the complex.

10.102.1 Detailed Description

template<unsigned D, typename G, typename V> class mln::complex_image< D, G, V >

[Image](#) based on a complex. Values attached to each face of the complex.

Template Parameters

D The dimension of the complex.

G The geometry type of the complex.

V The value type of the image.

Definition at line 164 of file mln/core/image/complex_image.hh.

10.102.2 Member Typedef Documentation

10.102.2.1 template<unsigned D, typename G, typename V> typedef G mln::complex_image< D, G, V >::geom

The geometry type of the complex.

Definition at line 172 of file mln/core/image/complex_image.hh.

10.102.2.2 template<unsigned D, typename G, typename V> typedef V& mln::complex_image< D, G, V >::lvalue

Return type of read-write access.

Definition at line 177 of file mln/core/image/complex_image.hh.

10.102.2.3 template<unsigned D, typename G, typename V> typedef const V& mln::complex_image< D, G, V >::rvalue

Return type of read-only access.

Definition at line 180 of file mln/core/image/complex_image.hh.

10.102.2.4 template<unsigned D, typename G, typename V> typedef complex_image< D, tag::psite_<G>, tag::value_<V> > mln::complex_image< D, G, V >::skeleton

Skeleton.

Definition at line 183 of file mln/core/image/complex_image.hh.

10.102.2.5 template<unsigned D, typename G, typename V> typedef V mln::complex_image< D, G, V >::value

[Value](#) associated type.

Definition at line 174 of file mln/core/image/complex_image.hh.

10.102.3 Constructor & Destructor Documentation

10.102.3.1 template<unsigned D, typename G , typename V > mln::complex_image< D, G, V >::complex_image () [inline]

Constructors.

Definition at line 276 of file mln/core/image/complex_image.hh.

10.102.4 Member Function Documentation

10.102.4.1 template<unsigned D, typename G , typename V > const p_complex< D, G > & mln::complex_image< D, G, V >::domain () const [inline]

Accessors.

Return the domain of psites od the image.

Definition at line 343 of file mln/core/image/complex_image.hh.

10.102.4.2 template<unsigned D, typename G, typename V > complex_image< D, G, V >::value mln::complex_image< D, G, V >::operator() (const complex_psite< D, G > & p) [inline]

Read-write access of face value at point site p.

Definition at line 326 of file mln/core/image/complex_image.hh.

References mln::complex_psite< D, G >::face_id(), and mln::complex_psite< D, G >::n().

10.102.4.3 template<unsigned D, typename G, typename V > complex_image< D, G, V >::rvalue mln::complex_image< D, G, V >::operator() (const complex_psite< D, G > & p) const [inline]

Read-only access of face value at point site p.

Definition at line 317 of file mln/core/image/complex_image.hh.

References mln::complex_psite< D, G >::face_id(), and mln::complex_psite< D, G >::n().

10.102.4.4 template<unsigned D, typename G , typename V > const metal::vec< D+1, std::vector< mlc_unbool(V) > > & mln::complex_image< D, G, V >::values () const [inline]

Return the array of values associated to the faces.

Definition at line 335 of file mln/core/image/complex_image.hh.

10.102.5 Member Data Documentation

10.102.5.1 template<unsigned D, typename G, typename V> const unsigned mln::complex_image< D, G, V >::dim = D [static]

The dimension of the complex.

Definition at line 170 of file mln/core/image/complex_image.hh.

10.103 mln::complex_neighborhood_bkd_piter< I, G, N > Class Template Reference

Backward iterator on complex neighborhood.

```
#include <complex_neighborhood_piter.hh>
```

Inherits site_relative_iterator_base< N, complex_neighborhood_bkd_piter< I, G, N > >.

Public Types

- **typedef N::complex_bkd_iter iter_type**
The type of the underlying complex iterator.
- **typedef N::psite psite**
The [Pseudo_Site](#) type.

Public Member Functions

- **void next ()**
Go to the next element.
- **complex_neighborhood_bkd_piter ()**
Construction.
- **const iter_type & iter () const**
Accessors.

10.103.1 Detailed Description

```
template<typename I, typename G, typename N> class mln::complex_neighborhood_bkd_piter< I,  
G, N >
```

Backward iterator on complex neighborhood.

Definition at line 124 of file complex_neighborhood_piter.hh.

10.103.2 Member Typedef Documentation

10.103.2.1 template<typename I, typename G, typename N> **typedef N::complex_bkd_iter mln::complex_neighborhood_bkd_piter< I, G, N >::iter_type**

The type of the underlying complex iterator.

Definition at line 135 of file complex_neighborhood_piter.hh.

10.103.2.2 template<typename I, typename G, typename N> typedef N ::psite mln::complex_neighborhood_bkd_piter< I, G, N >::psite

The [Pseudo_Site](#) type.

Definition at line 133 of file complex_neighborhood_piter.hh.

10.103.3 Constructor & Destructor Documentation

10.103.3.1 template<typename I , typename G , typename N > mln::complex_neighborhood_bkd_piter< I, G, N >::complex_neighborhood_bkd_piter () [inline]

Construction.

Definition at line 305 of file complex_neighborhood_piter.hh.

10.103.4 Member Function Documentation

10.103.4.1 template<typename I , typename G , typename N > const N::complex_bkd_iter & mln::complex_neighborhood_bkd_piter< I, G, N >::iter () const [inline]

Accessors.

Definition at line 382 of file complex_neighborhood_piter.hh.

10.103.4.2 void mln::Site_Iterator< complex_neighborhood_bkd_piter< I, G, N > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.104 mln::complex_neighborhood_fwd_piter< I, G, N > Class Template Reference

Forward iterator on complex neighborhood.

```
#include <complex_neighborhood_piter.hh>
```

Inherits site_relative_iterator_base< N, complex_neighborhood_fwd_piter< I, G, N > >.

Public Types

- typedef N::complex_fwd_iter [iter_type](#)

The type of the underlying complex iterator.

- **typedef N::psite psite**
The [Pseudo_Site](#) type.

Public Member Functions

- **void next ()**
Go to the next element.
- **complex_neighborhood_fwd_piter ()**
Construction.
- **const iter_type & iter () const**
Accessors.

10.104.1 Detailed Description

template<typename I, typename G, typename N> class mln::complex_neighborhood_fwd_piter< I, G, N >

Forward iterator on complex neighborhood.

Definition at line 53 of file complex_neighborhood_piter.hh.

10.104.2 Member Typedef Documentation

**10.104.2.1 template<typename I, typename G, typename N> typedef N::complex_fwd_iter
mln::complex_neighborhood_fwd_piter< I, G, N >::iter_type**

The type of the underlying complex iterator.

Definition at line 64 of file complex_neighborhood_piter.hh.

**10.104.2.2 template<typename I, typename G, typename N> typedef N ::psite
mln::complex_neighborhood_fwd_piter< I, G, N >::psite**

The [Pseudo_Site](#) type.

Definition at line 62 of file complex_neighborhood_piter.hh.

10.104.3 Constructor & Destructor Documentation

**10.104.3.1 template<typename I , typename G , typename N > mln::complex_-
neighborhood_fwd_piter< I, G, N >::complex_neighborhood_fwd_piter ()
[inline]**

Construction.

Definition at line 198 of file complex_neighborhood_piter.hh.

10.104.4 Member Function Documentation

10.104.4.1 template<typename I , typename G , typename N > const N::complex_fwd_iter & mln::complex_neighborhood_fwd_piter< I, G, N >::iter() const [inline]

Accessors.

Definition at line 275 of file complex_neighborhood_piter.hh.

10.104.4.2 void mln::Site_Iterator< complex_neighborhood_fwd_piter< I, G, N > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.105 mln::complex_psite< D, G > Class Template Reference

Point site associated to a [mln::p_complex](#).

```
#include <complex_psite.hh>
Inherits pseudo_site_base_< const G::site &, complex_psite< D, G > >.
```

Public Member Functions

- **complex_psite()**
Construction and assignment.
- **complex_psite(const p_complex< D, G > &pc, const topo::face< D > &face)**
- **bool is_valid()** const
Psite manipulators.
- **void invalidate()**
Invalidate this psite.
- **const target & site_set()** const
Site set manipulators.
- **void change_target(const target &new_target)**
Set the target site_set.

- const [topo::face](#)< D > & [face](#) () const
Face handle manipulators.
- unsigned [n](#) () const
Return the dimension of the face of this psite.
- unsigned [face_id](#) () const
Return the id of the face of this psite.

10.105.1 Detailed Description

`template<unsigned D, typename G> class mln::complex_psite< D, G >`

[Point](#) site associated to a [mln::p_complex](#).

Template Parameters

D The dimension of the complex this psite belongs to.

G The geometry of the complex.

Definition at line 60 of file `complex_psite.hh`.

10.105.2 Constructor & Destructor Documentation

10.105.2.1 template<unsigned D, typename G> mln::complex_psite< D, G >::complex_psite() [inline]

Construction and assignment.

Definition at line 203 of file `complex_psite.hh`.

References `mln::complex_psite< D, G >::invalidate()`.

10.105.2.2 template<unsigned D, typename G> mln::complex_psite< D, G >::complex_psite(const p_complex< D, G > & pc, const topo::face< D > & face) [inline]

Precondition

`pc.cplx() == face.cplx()`.

Definition at line 211 of file `complex_psite.hh`.

References `mln::topo::face< D >::cplx()`, `mln::p_complex< D, G >::cplx()`, and `mln::complex_psite< D, G >::is_valid()`.

10.105.3 Member Function Documentation

10.105.3.1 template<unsigned D, typename G> void mln::complex_psite< D, G >::change_target(const target & new_target) [inline]

Set the target `site_set`.

Definition at line 280 of file complex_psite.hh.

References mln::p_complex< D, G >::cplx(), and mln::complex_psite< D, G >::invalidate().

10.105.3.2 template<unsigned D, typename G> const topo::face< D > & mln::complex_psite< D, G >::face() const [inline]

Face handle manipulators.

Return the face handle of this point site.

Definition at line 301 of file complex_psite.hh.

Referenced by mln::operator!=(), and mln::operator==().

10.105.3.3 template<unsigned D, typename G> unsigned mln::complex_psite< D, G >::face_id() const [inline]

Return the id of the face of this psite.

Definition at line 317 of file complex_psite.hh.

Referenced by mln::complex_image< D, G, V >::operator()().

10.105.3.4 template<unsigned D, typename G> void mln::complex_psite< D, G >::invalidate() [inline]

Invalidate this psite.

Definition at line 251 of file complex_psite.hh.

Referenced by mln::complex_psite< D, G >::change_target(), and mln::complex_psite< D, G >::complex_psite().

10.105.3.5 template<unsigned D, typename G> bool mln::complex_psite< D, G >::is_valid() const [inline]

Psite manipulators.

Is this psite valid?

Definition at line 239 of file complex_psite.hh.

Referenced by mln::complex_psite< D, G >::complex_psite(), and mln::p_complex< D, G >::has().

10.105.3.6 template<unsigned D, typename G> unsigned mln::complex_psite< D, G >::n() const [inline]

Return the dimension of the face of this psite.

Definition at line 309 of file complex_psite.hh.

Referenced by mln::make::cell(), and mln::complex_image< D, G, V >::operator()().

10.105.3.7 template<unsigned D, typename G> const p_complex< D, G > & mln::complex_psites< D, G >::site_set() const [inline]

[Site](#) set manipulators.

Return the [mln::p_complex](#) this site is built on. (shortcut for *target()).

Precondition

Member face_ is valid.

Definition at line 259 of file complex_psites.hh.

Referenced by [mln::p_complex< D, G >::has\(\)](#), [mln::operator!=\(\)](#), and [mln::operator==\(\)](#).

10.106 mln::complex_window_bkd_piter< I, G, W > Class Template Reference

Backward iterator on complex window.

```
#include <complex_window_piter.hh>
```

Inherits [site_relative_iterator_base< W, complex_window_bkd_piter< I, G, W > >](#).

Public Types

- [typedef W::complex_bkd_iter iter_type](#)
The type of the underlying complex iterator.
- [typedef W::psite psite](#)
The [Pseudo_Site](#) type.

Public Member Functions

- [void next\(\)](#)
Go to the next element.
- [complex_window_bkd_piter\(\)](#)
Construction.
- [const iter_type & iter\(\) const](#)
Accessors.

10.106.1 Detailed Description

```
template<typename I, typename G, typename W> class mln::complex_window_bkd_piter< I, G, W >
```

Backward iterator on complex window.

Definition at line 124 of file complex_window_piter.hh.

10.106.2 Member Typedef Documentation

**10.106.2.1 template<typename I, typename G, typename W> typedef W::complex_bkd_iter
mln::complex_window_bkd_piter< I, G, W >::iter_type**

The type of the underlying complex iterator.

Definition at line 135 of file complex_window_piter.hh.

**10.106.2.2 template<typename I, typename G, typename W> typedef W ::psite
mln::complex_window_bkd_piter< I, G, W >::psite**

The [Pseudo_Site](#) type.

Definition at line 133 of file complex_window_piter.hh.

10.106.3 Constructor & Destructor Documentation

**10.106.3.1 template<typename I, typename G, typename W> mln::complex_-
window_bkd_piter< I, G, W >::complex_window_bkd_piter ()
[inline]**

Construction.

Definition at line 305 of file complex_window_piter.hh.

10.106.4 Member Function Documentation

**10.106.4.1 template<typename I, typename G, typename W> const W::complex_bkd_iter &
mln::complex_window_bkd_piter< I, G, W >::iter () const [inline]**

Accessors.

Definition at line 384 of file complex_window_piter.hh.

**10.106.4.2 void mln::Site_Iterator< complex_window_bkd_piter< I, G, W > >::next ()
[inherited]**

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.107 mln::complex_window_fwd_piter< I, G, W > Class Template Reference

Forward iterator on complex window.

```
#include <complex_window_piter.hh>
```

Inherits site_relative_iterator_base< W, complex_window_fwd_piter< I, G, W > >.

Public Types

- **typedef W::complex_fwd_iter iter_type**
The type of the underlying complex iterator.
- **typedef W::psite psite**
The [Pseudo_Site](#) type.

Public Member Functions

- **void next ()**
Go to the next element.
- **complex_window_fwd_piter ()**
Construction.
- **const iter_type & iter () const**
Accessors.

10.107.1 Detailed Description

```
template<typename I, typename G, typename W> class mln::complex_window_fwd_piter< I, G, W >
```

Forward iterator on complex window.

Definition at line 54 of file complex_window_piter.hh.

10.107.2 Member Typedef Documentation

10.107.2.1 template<typename I, typename G, typename W> typedef W::complex_fwd_iter mln::complex_window_fwd_piter< I, G, W >::iter_type

The type of the underlying complex iterator.

Definition at line 65 of file complex_window_piter.hh.

10.107.2.2 template<typename I, typename G, typename W> typedef W ::psite mln::complex_window_fwd_piter< I, G, W >::psite

The [Pseudo_Site](#) type.

Definition at line 63 of file complex_window_piter.hh.

10.107.3 Constructor & Destructor Documentation

10.107.3.1 template<typename I , typename G , typename W > mln::complex_- window_fwd_piter< I, G, W >::complex_window_fwd_piter () [inline]

Construction.

Definition at line 197 of file complex_window_piter.hh.

10.107.4 Member Function Documentation

10.107.4.1 template<typename I , typename G , typename W > const W::complex_fwd_iter & mln::complex_window_fwd_piter< I, G, W >::iter () const [inline]

Accessors.

Definition at line 275 of file complex_window_piter.hh.

10.107.4.2 void mln::Site_Iterator< complex_window_fwd_piter< I, G, W > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.108 mln::decorated_image< I, D > Struct Template Reference

[Image](#) that can have additional features.

```
#include <decorated_image.hh>
```

Inherits decorated_image_impl_< I, decorated_image< I, D > >, and image_identity< I, I::domain_t, decorated_image< I, D > >.

Public Types

- [typedef impl_::lvalue lvalue](#)

Return type of read-write access.

- `typedef I::psite psite`
Type of the psite.
- `typedef I::rvalue rvalue`
Return type of read-only access.
- `typedef decorated_image< tag::image_< I >, tag::data_< D > > skeleton`
Skeleton.

Public Member Functions

- `decorated_image()`
Ctors.
- `D & decoration()`
Give the decoration.
- `const D & decoration() const`
Give the decoration.
- `operator decorated_image< const I, D > () const`
Const promotion via conversion.
- `rvalue operator() (const psite &p) const`
Read-only access of pixel value at point site p.
- `lvalue operator() (const psite &p)`
Read-write access of pixel value at point site p.
- `~decorated_image()`
Dtor.

10.108.1 Detailed Description

`template<typename I, typename D> struct mln::decorated_image< I, D >`

`Image` that can have additional features.

Definition at line 81 of file `decorated_image.hh`.

10.108.2 Member Typedef Documentation

10.108.2.1 `template<typename I, typename D> typedef impl::lvalue mln::decorated_image< I, D >::lvalue`

Return type of read-write access.

Definition at line 95 of file decorated_image.hh.

10.108.2.2 template<typename I, typename D> typedef I ::psite mln::decorated_image< I, D >::psite

Type of the psite.

Definition at line 90 of file decorated_image.hh.

10.108.2.3 template<typename I, typename D> typedef I ::rvalue mln::decorated_image< I, D >::rvalue

Return type of read-only access.

Definition at line 93 of file decorated_image.hh.

10.108.2.4 template<typename I, typename D> typedef decorated_image< tag::image_<I>, tag::data_<D> > mln::decorated_image< I, D >::skeleton

Skeleton.

Definition at line 108 of file decorated_image.hh.

10.108.3 Constructor & Destructor Documentation

10.108.3.1 template<typename I , typename D > mln::decorated_image< I, D >::decorated_image() [inline]

Ctors.

Definition at line 161 of file decorated_image.hh.

10.108.3.2 template<typename I , typename D > mln::decorated_image< I, D >::~decorated_image() [inline]

Dtor.

Definition at line 184 of file decorated_image.hh.

10.108.4 Member Function Documentation

10.108.4.1 template<typename I , typename D > const D & mln::decorated_image< I, D >::decoration() const [inline]

Give the decoration.

Definition at line 249 of file decorated_image.hh.

10.108.4.2 template<typename I , typename D > D & mln::decorated_image< I, D >::decoration() [inline]

Give the decoration.

Definition at line 257 of file decorated_image.hh.

**10.108.4.3 template<typename I , typename D > mln::decorated_image< I, D >::operator
decorated_image< const I, D >() const [inline]**

Const promotion via conversion.

Definition at line 239 of file decorated_image.hh.

**10.108.4.4 template<typename I , typename D > decorated_image< I, D >::rvalue
mln::decorated_image< I, D >::operator() (const psite & p) const [inline]**

Read-only access of pixel value at point site p.

Definition at line 197 of file decorated_image.hh.

**10.108.4.5 template<typename I , typename D > decorated_image< I, D >::lvalue
mln::decorated_image< I, D >::operator() (const psite & p) [inline]**

Read-write access of pixel value at point site p.

Definition at line 206 of file decorated_image.hh.

10.109 mln::Delta_Point_Site< void > Struct Template Reference

Delta point site category flag type.

```
#include <delta_point_site.hh>
```

10.109.1 Detailed Description

template<> struct mln::Delta_Point_Site< void >

Delta point site category flag type.

Definition at line 70 of file delta_point_site.hh.

10.110 mln::doc::Accumulator< E > Struct Template Reference

Documentation class for [mln::Accumulator](#).

```
#include <accumulator.hh>
```

Public Types

- **typedef void argument**

The argument type of elements to accumulate.

Public Member Functions

- void [init \(\)](#)
Initialize the accumulator.
- void [take \(const E &other\)](#)
Take into account another accumulator `other`.
- void [take \(const argument &t\)](#)
Take into account a argument `t` (an element).

10.110.1 Detailed Description

template<typename E> struct mln::doc::Accumulator< E >

Documentation class for [mln::Accumulator](#).

See also

[mln::Accumulator](#)

Definition at line 36 of file doc/accumulator.hh.

10.110.2 Member Typedef Documentation

10.110.2.1 template<typename E > typedef void mln::doc::Accumulator< E >::argument

The argument type of elements to accumulate.

Definition at line 39 of file doc/accumulator.hh.

10.110.3 Member Function Documentation

10.110.3.1 template<typename E > void mln::doc::Accumulator< E >::init ()

Initialize the accumulator.

10.110.3.2 template<typename E > void mln::doc::Accumulator< E >::take (const E & other)

Take into account another accumulator `other`.

10.110.3.3 template<typename E > void mln::doc::Accumulator< E >::take (const argument & t)


Take into account a argument `t` (an element).

10.111 mln::doc::Box< E > Struct Template Reference

Documentation class for [mln::Box](#).

```
#include <box.hh>
```

Inheritance diagram for mln::doc::Box< E >:



Public Types

- **typedef void bkd_piter**
Backward Site_Iterator associated type.
- **typedef void fwd_piter**
Forward Site_Iterator associated type.
- **typedef void psite**
PSite associated type.
- **typedef void site**
Site associated type.

Public Member Functions

- **const E & bbox () const**
Return the bounding box of this point set.
- **bool has (const psite &p) const**
Test if p belongs to this site set.

- `unsigned nsites () const`
Return the number of points of this box.
- `const site & pmax () const`
Give the box "maximum" point.
- `const site & pmin () const`
Give the box "minimum" point.

10.111.1 Detailed Description

`template<typename E> struct mln::doc::Box< E >`

Documentation class for [mln::Box](#).

See also

[mln::Box](#)

Definition at line 36 of file core/concept/doc/box.hh.

10.111.2 Member Typedef Documentation

10.111.2.1 `template<typename E > typedef void mln::doc::Site_Set< E >::bkd_piter [inherited]`

Backward [Site_Iterator](#) associated type.

Definition at line 53 of file mln/core/concept/doc/site_set.hh.

10.111.2.2 `template<typename E > typedef void mln::doc::Site_Set< E >::fwd_piter [inherited]`

Forward [Site_Iterator](#) associated type.

Definition at line 49 of file mln/core/concept/doc/site_set.hh.

10.111.2.3 `template<typename E > typedef void mln::doc::Site_Set< E >::psite [inherited]`

PSite associated type.

Definition at line 45 of file mln/core/concept/doc/site_set.hh.

10.111.2.4 `template<typename E > typedef void mln::doc::Site_Set< E >::site [inherited]`

[Site](#) associated type.

Definition at line 41 of file mln/core/concept/doc/site_set.hh.

10.111.3 Member Function Documentation

10.111.3.1 template<typename E> const E& mln::doc::Box< E >::bbox() const

Return the bounding box of this point set.

Return the bounding box of this point set, so that is itself. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

10.111.3.2 template<typename E> bool mln::doc::Site_Set< E >::has(const psite & p) const [inherited]

Test if p belongs to this site set.

Parameters

[in] *p* A psite.

Returns

True if p is an element of the site set.

10.111.3.3 template<typename E> unsigned mln::doc::Box< E >::nsites() const

Return the number of points of this box.

Return the number of points of this box. This method is declared by the [mln::Site_Set](#) concept.

Warning

This method is final for all box classes.

10.111.3.4 template<typename E> const site& mln::doc::Box< E >::pmax() const

Give the box "maximum" point.

Return the "maximum" point w.r.t. the ordering between points. For instance, with [mln::box2d](#), this maximum is the bottom right point of the box.

10.111.3.5 template<typename E> const site& mln::doc::Box< E >::pmin() const

Give the box "minimum" point.


Return the "minimum" point w.r.t. the ordering between points. For instance, with [mln::box2d](#), this minimum is the top left point of the box.

10.112 mln::doc::Dpoint< E > Struct Template Reference

Documentation class for [mln:Dpoint](#).

```
#include <dpoint.hh>
```

Inheritance diagram for mln::doc::Dpoint< E >:



Public Types

- enum { [dim](#) }
- typedef void [coord](#)
- typedef void [dpoint](#)

Dpsite associated type.

- typedef void [point](#)

Site associated type.

Public Member Functions

- [coord operator\[\]](#) (unsigned i) const
Read-only access to the i -th coordinate value.

10.112.1 Detailed Description

template<typename E> struct mln::doc::Dpoint< E >

Documentation class for [mln:Dpoint](#).

See also

[mln:Dpoint](#)

Definition at line 36 of file [concept/doc/dpoint.hh](#).

10.112.2 Member Typedef Documentation

10.112.2.1 template<typename E > typedef void mln::doc::Dpoint< E >::coord

Coordinate associated type.

Definition at line 56 of file concept/doc/dpoint.hh.

10.112.2.2 template<typename E > typedef void mln::doc::Dpoint< E >::dpoint

Dpsite associated type.

Invariant

This type has to derive from [mln::Dpoint](#).

Definition at line 52 of file concept/doc/dpoint.hh.

10.112.2.3 template<typename E > typedef void mln::doc::Dpoint< E >::point

Site associated type.

Invariant

This type has to derive from [mln::Point](#).

Definition at line 47 of file concept/doc/dpoint.hh.

10.112.3 Member Enumeration Documentation

10.112.3.1 template<typename E > anonymous enum

Enumerator:

dim Dimension of the space.

Invariant

$\text{dim} > 0$

Definition at line 42 of file concept/doc/dpoint.hh.

10.112.4 Member Function Documentation

10.112.4.1 template<typename E > coord mln::doc::Dpoint< E >::operator[](unsigned *i*) const

Read-only access to the *i*-th coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

$i < \dim$

Returns


The value of the i -th coordinate.

10.113 mln::doc::Fastest_Image< E > Struct Template Reference

Documentation class for the concept of images that have the speed property set to "fastest".

```
#include <image_fastest.hh>
```

Inheritance diagram for mln::doc::Fastest_Image< E >:



Public Types

- **typedef void bkd_piter**
Backward point iterator associated type.
- **typedef void coord**
Coordinate associated type.
- **typedef void dpoint**
Dpsite associated type.
- **typedef void fwd_piter**
Forward point iterator associated type.
- **typedef void lvalue**
Type returned by the read-write pixel value operator.

- **typedef void point**
Site associated type.
- **typedef void pset**
Point set associated type.
- **typedef void psite**
Point_Site associated type.
- **typedef void rvalue**
Type returned by the read pixel value operator.
- **typedef void skeleton**
Associate type that describes how this type of image is constructed.
- **typedef void value**
Value associated type.
- **typedef void vset**
Value set associated type.

Public Member Functions

- **const box< point > & bbox () const**
Give a bounding box of the image domain.
- **unsigned border ()**
Give the border thickness.
- **const value * buffer () const**
Give a hook to the value buffer.
- **int delta_index (const dpoint &dp)**
Give the offset corresponding to the delta-point dp.
- **const pset & domain () const**
Give the definition domain of the image.
- **bool has (const psite &p) const**
Test if the image owns the point site p.
- **bool has (const psite &p) const**
Test if p belongs to the image domain.
- **bool is_valid () const**
Test if the image have been initialized.

- `unsigned nelements () const`
Give the number of pixels of the image including those of the virtual border.
- `unsigned nsites () const`
Give the number of points of the image domain.
- `lvalue operator() (const psite &p)`
Read-write access to the image value located at p.
- `rvalue operator() (const psite &p) const`
Read-only access to the image value located at p.
- `rvalue operator[] (unsigned o) const`
Read-only access to the image value at offset o.
- `lvalue operator[] (unsigned o)`
Read-write access to the image value at offset o.
- `point point_at_index (unsigned o) const`
Give the point at offset o.
- `const vset & values () const`
Give the set of values of the image.

10.113.1 Detailed Description

`template<typename E> struct mln::doc::Fastest_Image< E >`

Documentation class for the concept of images that have the speed property set to "fastest".

Definition at line 36 of file concept/doc/image_fastest.hh.

10.113.2 Member Typedef Documentation

10.113.2.1 `template<typename E > typedef void mln::doc::Image< E >::bkd_piter [inherited]`

Backward point iterator associated type.

Invariant

This type has to derive from `mln::Site_Iterator`.

Definition at line 147 of file core/concept/doc/image.hh.

10.113.2.2 `template<typename E > typedef void mln::doc::Image< E >::coord [inherited]`

Coordinate associated type.

Definition at line 131 of file core/concept/doc/image.hh.

10.113.2.3 template<typename E > typedef void mln::doc::Image< E >::dpoint [inherited]

Dpsite associated type.

Invariant

This type has to derive from [mln::Dpoint](#).

Definition at line 136 of file core/concept/doc/image.hh.

10.113.2.4 template<typename E > typedef void mln::doc::Image< E >::fwd_piter [inherited]

Forward point iterator associated type.

Invariant

This type has to derive from [mln::Site_Iterator](#).

Definition at line 142 of file core/concept/doc/image.hh.

10.113.2.5 template<typename E > typedef void mln::doc::Image< E >::lvalue [inherited]

Type returned by the read-write pixel value operator.

Definition at line 52 of file core/concept/doc/image.hh.

10.113.2.6 template<typename E > typedef void mln::doc::Image< E >::point [inherited]

[Site](#) associated type.

Invariant

This type has to derive from [mln::Point](#).

Definition at line 121 of file core/concept/doc/image.hh.

10.113.2.7 template<typename E > typedef void mln::doc::Image< E >::pset [inherited]

[Point](#) set associated type.

Invariant

This type has to derive from [mln::Site_Set](#).

Definition at line 116 of file core/concept/doc/image.hh.

10.113.2.8 template<typename E > typedef void mln::doc::Image< E >::psite [inherited]

[Point_Site](#) associated type.

Invariant

This type has to derive from [mln::Point_Site](#).

Definition at line 126 of file core/concept/doc/image.hh.

10.113.2.9 template<typename E> typedef void mln::doc::Image< E >::rvalue [inherited]

Type returned by the read pixel value operator.

Definition at line 48 of file core/concept/doc/image.hh.

10.113.2.10 template<typename E> typedef void mln::doc::Image< E >::skeleton [inherited]

Associate type that describes how this type of image is constructed.

Definition at line 64 of file core/concept/doc/image.hh.

10.113.2.11 template<typename E> typedef void mln::doc::Image< E >::value [inherited]

[Value](#) associated type.

Invariant

This type is neither qualified by const, nor by reference.

Definition at line 44 of file core/concept/doc/image.hh.

10.113.2.12 template<typename E> typedef void mln::doc::Image< E >::vset [inherited]

[Value](#) set associated type.

Invariant

This type has to derive from [mln::Value_Set](#).

Definition at line 57 of file core/concept/doc/image.hh.

10.113.3 Member Function Documentation**10.113.3.1 template<typename E> const box<point>& mln::doc::Image< E >::bbox() const [inherited]**

Give a bounding box of the image domain.

This bounding box may be larger than the smallest bounding box (the optimal one). Practically an image type is not obliged to update its bounding box so that it is always optimal.

Returns

A bounding box of the image domain.

10.113.3.2 template<typename E> unsigned mln::doc::Fastest_Image< E >::border()

Give the border thickness.

Precondition

The image has to be initialized.

10.113.3.3 template<typename E> const value* mln::doc::Fastest_Image< E >::buffer() const

Give a hook to the value buffer.

Precondition

The image has to be initialized.

10.113.3.4 template<typename E> int mln::doc::Fastest_Image< E >::delta_index(const dpoint & dp)

Give the offset corresponding to the delta-point *dp*.

Parameters

[in] *dp* A delta-point.

Precondition

The image has to be initialized.

10.113.3.5 template<typename E> const pset& mln::doc::Image< E >::domain() const [inherited]

Give the definition domain of the image.

Returns

A reference to the domain point set.

10.113.3.6 template<typename E> bool mln::doc::Image< E >::has(const psite & p) const [inherited]

Test if the image owns the point site *p*.

Returns

True if accessing the image value at *p* is possible, that is, does not abort the execution.

**10.113.3.7 template<typename E> bool mln::doc::Image< E >::has (const psite & p) const
[inherited]**

Test if p belongs to the image domain.

Parameters

[in] *p* A point site.

Returns

True if p belongs to the image domain.

Invariant

has(p) is true => has(p) is also true.

**10.113.3.8 template<typename E> bool mln::doc::Image< E >::is_valid () const
[inherited]**

Test if the image have been initialized.

10.113.3.9 template<typename E> unsigned mln::doc::Fastest_Image< E >::nelements () const

Give the number of pixels of the image including those of the virtual border.

Precondition

The image has to be initialized.

**10.113.3.10 template<typename E> unsigned mln::doc::Image< E >::nsites () const
[inherited]**

Give the number of points of the image domain.

10.113.3.11 template<typename E> lvalue mln::doc::Image< E >::operator() (const psite & p) [inherited]

Read-write access to the image value located at p.

Parameters

[in] *p* A point site.

Precondition

The image has to own the site p.

Returns

The value at p (assignable).

10.113.3.12 template<typename E> rvalue mln::doc::Image< E >::operator() (const psite & p) const [inherited]

Read-only access to the image value located at p.

Parameters

[in] *p* A point site.

Precondition

The image has to own the site p.

Returns

The value at p (not assignable).

10.113.3.13 template<typename E> rvalue mln::doc::Fastest_Image< E >::operator[] (unsigned o) const

Read-only access to the image value at offset o.

Parameters

[in] *o* An offset.

Precondition

o < nelements()

Returns

The value at o (not assignable).

10.113.3.14 template<typename E> lvalue mln::doc::Fastest_Image< E >::operator[] (unsigned o)

Read-write access to the image value at offset o.

Parameters

[in] *o* An offset.

Precondition

o < nelements()

Returns

The value at o (assignable).

10.113.3.15 template<typename E > point mln::doc::Fastest_Image< E >::point_at_index (unsigned *o*) const

Give the point at offset *o*.

Parameters

[in] *o* An offset.

Precondition

The image has to be initialized.

o < `nelements()`

10.113.3.16 template<typename E > const vset& mln::doc::Image< E >::values () const [inherited]

Give the set of values of the image.

Returns


A reference to the value set.

10.114 mln::doc::Generalized_Pixel< E > Struct Template Reference

Documentation class for mln::Generalized_Pixel.

```
#include <generalized_pixel.hh>
```

Inheritance diagram for mln::doc::Generalized_Pixel< E >:



Public Types

- `typedef void image`

Image associated type (with possible const qualification).

- **typedef void rvalue**
Read-only value associated type.
- **typedef void value**
Value associated type.

Public Member Functions

- **image & ima () const**
Give the image of this generalized pixel.
- **rvalue val () const**
Give the value of this generalized pixel.

10.114.1 Detailed Description

template<typename E> struct mln::doc::Generalized_Pixel< E >

Documentation class for mln::Generalized_Pixel.

See also

[mln::Generalized_Pixel](#)

Definition at line 45 of file doc/generalized_pixel.hh.

10.114.2 Member Typedef Documentation

10.114.2.1 template<typename E > typedef void mln::doc::Generalized_Pixel< E >::image

[Image](#) associated type (with possible const qualification).

Definition at line 49 of file doc/generalized_pixel.hh.

10.114.2.2 template<typename E > typedef void mln::doc::Generalized_Pixel< E >::rvalue

Read-only value associated type.

Definition at line 55 of file doc/generalized_pixel.hh.

10.114.2.3 template<typename E > typedef void mln::doc::Generalized_Pixel< E >::value

[Value](#) associated type.

Definition at line 52 of file doc/generalized_pixel.hh.

10.114.3 Member Function Documentation

10.114.3.1 template<typename E > image& mln::doc::Generalized_Pixel< E >::ima () const

Give the image of this generalized pixel.

The constness of a pixel object is not transmitted to the underlying image.

10.114.3.2 template<typename E > rvalue mln::doc::Generalized_Pixel< E >::val () const

Give the value of this generalized pixel.

Returns

A read-only value.


Reimplemented in [mln::doc::Pixel_Iterator< E >](#).

10.115 mln::doc::Image< E > Struct Template Reference

Documentation class for [mln::Image](#).

```
#include <image.hh>
```

Inheritance diagram for mln::doc::Image< E >:



Public Types

- **typedef void bkd_piter**
Backward point iterator associated type.
- **typedef void coord**

Coordinate associated type.

- **typedef void dpoint**
Dpsite associated type.
- **typedef void fwd_piter**
Forward point iterator associated type.
- **typedef void lvalue**
Type returned by the read-write pixel value operator.
- **typedef void point**
Site associated type.
- **typedef void pset**
Point set associated type.
- **typedef void psite**
Point_Site associated type.
- **typedef void rvalue**
Type returned by the read pixel value operator.
- **typedef void skeleton**
Associate type that describes how this type of image is constructed.
- **typedef void value**
Value associated type.
- **typedef void vset**
Value set associated type.

Public Member Functions

- **const box< point > & bbox () const**
Give a bounding box of the image domain.
- **const pset & domain () const**
Give the definition domain of the image.
- **bool has (const psite &p) const**
Test if the image owns the point site p.
- **bool has (const psite &p) const**
Test if p belongs to the image domain.
- **bool is_valid () const**
Test if the image have been initialized.

- `unsigned nsites () const`
Give the number of points of the image domain.
- `rvalue operator() (const psite &p) const`
Read-only access to the image value located at p.
- `lvalue operator() (const psite &p)`
Read-write access to the image value located at p.
- `const vset & values () const`
Give the set of values of the image.

10.115.1 Detailed Description

template<typename E> struct mln::doc::Image< E >

Documentation class for [mln::Image](#).

See also

[mln::Image](#)

Definition at line 36 of file core/concept/doc/image.hh.

10.115.2 Member Typedef Documentation

10.115.2.1 template<typename E > typedef void mln::doc::Image< E >::bkd_piter

Backward point iterator associated type.

Invariant

This type has to derive from [mln::Site_Iterator](#).

Definition at line 147 of file core/concept/doc/image.hh.

10.115.2.2 template<typename E > typedef void mln::doc::Image< E >::coord

Coordinate associated type.

Definition at line 131 of file core/concept/doc/image.hh.

10.115.2.3 template<typename E > typedef void mln::doc::Image< E >::dpoint

Dpsite associated type.

Invariant

This type has to derive from [mln::Dpoint](#).

Definition at line 136 of file core/concept/doc/image.hh.

10.115.2.4 template<typename E > typedef void mln::doc::Image< E >::fwd_piter

Forward point iterator associated type.

Invariant

This type has to derive from [mln::Site_Iterator](#).

Definition at line 142 of file core/concept/doc/image.hh.

10.115.2.5 template<typename E > typedef void mln::doc::Image< E >::lvalue

Type returned by the read-write pixel value operator.

Definition at line 52 of file core/concept/doc/image.hh.

10.115.2.6 template<typename E > typedef void mln::doc::Image< E >::point

[Site](#) associated type.

Invariant

This type has to derive from [mln::Point](#).

Definition at line 121 of file core/concept/doc/image.hh.

10.115.2.7 template<typename E > typedef void mln::doc::Image< E >::pset

[Point](#) set associated type.

Invariant

This type has to derive from [mln::Site_Set](#).

Definition at line 116 of file core/concept/doc/image.hh.

10.115.2.8 template<typename E > typedef void mln::doc::Image< E >::psite

[Point_Site](#) associated type.

Invariant

This type has to derive from [mln::Point_Site](#).

Definition at line 126 of file core/concept/doc/image.hh.

10.115.2.9 template<typename E > typedef void mln::doc::Image< E >::rvalue

Type returned by the read pixel value operator.

Definition at line 48 of file core/concept/doc/image.hh.

10.115.2.10 template<typename E > typedef void mln::doc::Image< E >::skeleton

Associate type that describes how this type of image is constructed.

Definition at line 64 of file core/concept/doc/image.hh.

10.115.2.11 template<typename E > typedef void mln::doc::Image< E >::value

[Value](#) associated type.

Invariant

This type is neither qualified by const, nor by reference.

Definition at line 44 of file core/concept/doc/image.hh.

10.115.2.12 template<typename E > typedef void mln::doc::Image< E >::vset

[Value](#) set associated type.

Invariant

This type has to derive from [mln::Value_Set](#).

Definition at line 57 of file core/concept/doc/image.hh.

10.115.3 Member Function Documentation**10.115.3.1 template<typename E > const box<point>& mln::doc::Image< E >::bbox () const**

Give a bounding box of the image domain.

This bounding box may be larger than the smallest bounding box (the optimal one). Practically an image type is not obliged to update its bounding box so that it is always optimal.

Returns

A bounding box of the image domain.

10.115.3.2 template<typename E > const pset& mln::doc::Image< E >::domain () const

Give the definition domain of the image.

Returns

A reference to the domain point set.

10.115.3.3 template<typename E > bool mln::doc::Image< E >::has (const psite & p) const

Test if the image owns the point site p.

Returns

True if accessing the image value at p is possible, that is, does not abort the execution.

10.115.3.4 template<typename E> bool mln::doc::Image< E >::has (const psite & p) const

Test if p belongs to the image domain.

Parameters

[in] *p* A point site.

Returns

True if p belongs to the image domain.

Invariant

has(p) is true => has(p) is also true.

10.115.3.5 template<typename E> bool mln::doc::Image< E >::is_valid () const

Test if the image have been initialized.

10.115.3.6 template<typename E> unsigned mln::doc::Image< E >::nsites () const

Give the number of points of the image domain.

10.115.3.7 template<typename E> rvalue mln::doc::Image< E >::operator() (const psite & p) const

Read-only access to the image value located at p.

Parameters

[in] *p* A point site.

Precondition

The image has to own the site p.

Returns

The value at p (not assignable).

10.115.3.8 template<typename E> lvalue mln::doc::Image< E >::operator() (const psite & p)

Read-write access to the image value located at p.

Parameters

[in] *p* A point site.

Precondition

The image has to own the site p.

Returns

The value at p (assignable).

10.115.3.9 template<typename E > const vset& mln::doc::Image< E >::values() const

Give the set of values of the image.

Returns


A reference to the value set.

10.116 mln::doc::Iterator< E > Struct Template Reference

Documentation class for [mln::Iterator](#).

```
#include <iterator.hh>
```

Inheritance diagram for mln::doc::Iterator< E >:



Public Member Functions

- void [invalidate\(\)](#)
Invalidate the iterator.
- bool [is_valid\(\)](#) const
Returns true if the iterator is valid, that is, designates an element.
- void [start\(\)](#)
Start an iteration.

10.116.1 Detailed Description

template<typename E> struct mln::doc::Iterator< E >

Documentation class for [mln::Iterator](#).

See also

[mln::Iterator](#)

Definition at line 36 of file doc/iterator.hh.

10.116.2 Member Function Documentation

10.116.2.1 template<typename E> void mln::doc::Iterator< E >::invalidate()

Invalidate the iterator.

10.116.2.2 template<typename E> bool mln::doc::Iterator< E >::is_valid() const

Returns true if the iterator is valid, that is, designates an element.

10.116.2.3 template<typename E> void mln::doc::Iterator< E >::start()

Start an iteration.


Make the iterator designate the first element if it exists. If this first element does not exist, the iterator is not valid.

10.117 mln::doc::Neighborhood< E > Struct Template Reference

Documentation class for [mln::Neighborhood](#).

```
#include <neighborhood.hh>
```

Inheritance diagram for mln::doc::Neighborhood< E >:



Public Types

- [typedef void bkd_niter](#)

Site_Iterator type associated to this neighborhood to browse neighbors in a backward way.

- [typedef void dpoint](#)

Dpsite associated type.

- [typedef void fwd_niter](#)

Site_Iterator type associated to this neighborhood to browse neighbors in a forward way.

- **typedef void niter**
Site_Iterator type associated to this neighborhood to browse neighbors.
- **typedef void point**
Site associated type.

10.117.1 Detailed Description

template<typename E> struct mln::doc::Neighborhood< E >

Documentation class for [mln::Neighborhood](#).

See also

[mln::Neighborhood](#)

Definition at line 37 of file core/concept/doc/neighborhood.hh.

10.117.2 Member Typedef Documentation

10.117.2.1 template<typename E > typedef void mln::doc::Neighborhood< E >::bkd_niter

Site_Iterator type associated to this neighborhood to browse neighbors in a backward way.

Definition at line 52 of file core/concept/doc/neighborhood.hh.

10.117.2.2 template<typename E > typedef void mln::doc::Neighborhood< E >::dpoint

Dpsite associated type.

Definition at line 55 of file core/concept/doc/neighborhood.hh.

10.117.2.3 template<typename E > typedef void mln::doc::Neighborhood< E >::fwd_niter

Site_Iterator type associated to this neighborhood to browse neighbors in a forward way.

Definition at line 47 of file core/concept/doc/neighborhood.hh.

10.117.2.4 template<typename E > typedef void mln::doc::Neighborhood< E >::niter

Site_Iterator type associated to this neighborhood to browse neighbors.

Definition at line 42 of file core/concept/doc/neighborhood.hh.

10.117.2.5 template<typename E > typedef void mln::doc::Neighborhood< E >::point

Site associated type.


Definition at line 58 of file core/concept/doc/neighborhood.hh.

10.118 mln::doc::Object< E > Struct Template Reference

Documentation class for [mln::Object](#).

```
#include <object.hh>
```

Inheritance diagram for mln::doc::Object< E >:



10.118.1 Detailed Description

template<typename E> struct mln::doc::Object< E >

Documentation class for [mln::Object](#).

See also

[mln::Object](#)


Definition at line 46 of file doc/object.hh.

10.119 mln::doc::Pixel_Iterator< E > Struct Template Reference

Documentation class for [mln::Iterator](#).

```
#include <pixel_iterator.hh>
```

Inheritance diagram for `mln::doc::Pixel_Iterator< E >`:



Public Types

- `typedef void image`
`Image` associated type (with possible `const` qualification).
- `typedef void lvalue`
`Type returned by the read-write dereference operator.`
- `typedef void rvalue`
`Read-only value associated type.`
- `typedef void value`
`Value` associated type.

Public Member Functions

- `image & ima () const`
`Give the image of this generalized pixel.`
- `void invalidate ()`
`Invalidate the iterator.`
- `bool is_valid () const`
`Returns true if the iterator is valid, that is, designates an element.`
- `void start ()`
`Start an iteration.`

- **`lvalue val () const`**
Give the pixel value.

10.119.1 Detailed Description

`template<typename E> struct mln::doc::Pixel_Iterator< E >`

Documentation class for [mln::Iterator](#).

See also

[mln::Pixel_Iterator](#)

Definition at line 36 of file doc/pixel_iterator.hh.

10.119.2 Member Typedef Documentation

10.119.2.1 `template<typename E > typedef void mln::doc::Generalized_Pixel< E >::image [inherited]`

[Image](#) associated type (with possible const qualification).

Definition at line 49 of file doc/generalized_pixel.hh.

10.119.2.2 `template<typename E > typedef void mln::doc::Pixel_Iterator< E >::lvalue`

Type returned by the read-write dereference operator.

Definition at line 41 of file doc/pixel_iterator.hh.

10.119.2.3 `template<typename E > typedef void mln::doc::Generalized_Pixel< E >::rvalue [inherited]`

Read-only value associated type.

Definition at line 55 of file doc/generalized_pixel.hh.

10.119.2.4 `template<typename E > typedef void mln::doc::Generalized_Pixel< E >::value [inherited]`

[Value](#) associated type.

Definition at line 52 of file doc/generalized_pixel.hh.

10.119.3 Member Function Documentation

10.119.3.1 `template<typename E > image& mln::doc::Generalized_Pixel< E >::ima () const [inherited]`

Give the image of this generalized pixel.

The constness of a pixel object is not transmitted to the underlying image.

10.119.3.2 template<typename E > void mln::doc::Iterator< E >::invalidate () [inherited]

Invalidate the iterator.

10.119.3.3 template<typename E > bool mln::doc::Iterator< E >::is_valid () const [inherited]

Returns true if the iterator is valid, that is, designates an element.

10.119.3.4 template<typename E > void mln::doc::Iterator< E >::start () [inherited]

Start an iteration.

Make the iterator designate the first element if it exists. If this first element does not exist, the iterator is not valid.

10.119.3.5 template<typename E > lvalue mln::doc::Pixel_Iterator< E >::val () const

Give the pixel value.

Returns

The current pixel value; this value cannot be modified.

Reimplemented from [mln::doc::Generalized_Pixel< E >](#).

10.120 mln::doc::Point_Site< E > Struct Template Reference

Documentation class for [mln::Point_Site](#).

```
#include <point_site.hh>
```

Public Types

- enum { [dim](#) }
- typedef void [coord](#)
- typedef void [dpoint](#)

Dsite associated type.

- typedef void [mesh](#)

Mesh associated type.

- typedef void [point](#)

Site associated type.

Public Member Functions

- `coord operator[] (unsigned i) const`
Read-only access to the i -th coordinate value.
- `const point & to_point () const`
Give a reference to the corresponding point.

10.120.1 Detailed Description

`template<typename E> struct mln::doc::Point_Site< E >`

Documentation class for [mln::Point_Site](#).

See also

[mln::Point_Site](#)

Definition at line 37 of file doc/point_site.hh.

10.120.2 Member Typedef Documentation

10.120.2.1 `template<typename E > typedef void mln::doc::Point_Site< E >::coord`

Coordinate associated type.

Definition at line 62 of file doc/point_site.hh.

10.120.2.2 `template<typename E > typedef void mln::doc::Point_Site< E >::dpoint`

Dpsite associated type.

Invariant

This type has to derive from [mln::Dpoint](#).

Definition at line 58 of file doc/point_site.hh.

10.120.2.3 `template<typename E > typedef void mln::doc::Point_Site< E >::mesh`

Mesh associated type.

Invariant

This type has to derive from [mln::Mesh](#).

Definition at line 48 of file doc/point_site.hh.

10.120.2.4 template<typename E > typedef void mln::doc::Point_Site< E >::point

[Site](#) associated type.

Invariant

This type has to derive from [mln::Point](#).

Definition at line 53 of file doc/point_site.hh.

10.120.3 Member Enumeration Documentation**10.120.3.1 template<typename E > anonymous enum**

Enumerator:

dim Dimension of the space.

Invariant

$\text{dim} > 0$

Definition at line 43 of file doc/point_site.hh.

10.120.4 Member Function Documentation**10.120.4.1 template<typename E > coord mln::doc::Point_Site< E >::operator[](unsigned *i*) const**

Read-only access to the *i*-th coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

$i < \text{dim}$

Returns

The value of the *i*-th coordinate.

10.120.4.2 template<typename E > const point& mln::doc::Point_Site< E >::to_point() const

Give a reference to the corresponding point.

This method allows for iterators to refer to a point.

Returns


A point constant reference.

10.121 mln::doc::Site_Iterator< E > Struct Template Reference

Documentation class for [mln::Site_Iterator](#).

```
#include <point_iterator.hh>
```

Inheritance diagram for mln::doc::Site_Iterator< E >:



Public Types

- [typedef void psite](#)
Point_Site associated type.

Public Member Functions

- [void invalidate \(\)](#)
Invalidate the iterator.
- [bool is_valid \(\) const](#)
Returns true if the iterator is valid, that is, designates an element.
- [operator psite \(\) const](#)
Conversion into a point-site.
- [void start \(\)](#)
Start an iteration.

10.121.1 Detailed Description

template<typename E> struct mln::doc::Site_Iterator< E >

Documentation class for [mln::Site_Iterator](#).

See also

[mln::Site_Iterator](#)

Definition at line 37 of file point_iterator.hh.

10.121.2 Member Typedef Documentation

10.121.2.1 template<typename E > typedef void mln::doc::Site_Iterator< E >::psite

[Point_Site](#) associated type.

Invariant

This type has to derive from [mln::Point_Site](#).

Definition at line 43 of file point_iterator.hh.

10.121.3 Member Function Documentation

10.121.3.1 template<typename E > void mln::doc::Iterator< E >::invalidate () [inherited]

Invalidate the iterator.

10.121.3.2 template<typename E > bool mln::doc::Iterator< E >::is_valid () const [inherited]

Returns true if the iterator is valid, that is, designates an element.

10.121.3.3 template<typename E > mln::doc::Site_Iterator< E >::operator psite () const

Conversion into a point-site.

Returns

A point site.

10.121.3.4 template<typename E > void mln::doc::Iterator< E >::start () [inherited]

Start an iteration.


Make the iterator designate the first element if it exists. If this first element does not exist, the iterator is not valid.

10.122 mln::doc::Site_Set< E > Struct Template Reference

Documentation class for [mln::Site_Set](#).

```
#include <site_set.hh>
```

Inheritance diagram for mln::doc::Site_Set< E >:



Public Types

- `typedef void bkd_piter`

Backward Site_Iterator associated type.

- `typedef void fwd_piter`

Forward Site_Iterator associated type.

- `typedef void psite`

PSite associated type.

- `typedef void site`

Site associated type.

Public Member Functions

- `bool has (const psite &p) const`

Test if p belongs to this site set.

10.122.1 Detailed Description

template<typename E> struct mln::doc::Site_Set< E >

Documentation class for [mln::Site_Set](#).

See also

[mln::Site_Set](#)

Definition at line 37 of file mln/core/concept/doc/site_set.hh.

10.122.2 Member Typedef Documentation

10.122.2.1 template<typename E > typedef void mln::doc::Site_Set< E >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 53 of file mln/core/concept/doc/site_set.hh.

10.122.2.2 template<typename E > typedef void mln::doc::Site_Set< E >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 49 of file mln/core/concept/doc/site_set.hh.

10.122.2.3 template<typename E > typedef void mln::doc::Site_Set< E >::psite

PSite associated type.

Definition at line 45 of file mln/core/concept/doc/site_set.hh.

10.122.2.4 template<typename E > typedef void mln::doc::Site_Set< E >::site

[Site](#) associated type.

Definition at line 41 of file mln/core/concept/doc/site_set.hh.

10.122.3 Member Function Documentation

10.122.3.1 template<typename E > bool mln::doc::Site_Set< E >::has (const psite & p) const

Test if *p* belongs to this site set.

Parameters

[in] *p* A psite.

Returns


True if *p* is an element of the site set.

10.123 mln::doc::Value_Iterator< E > Struct Template Reference

Documentation class for [mln::Value_Iterator](#).

```
#include <value_iterator.hh>
```

Inheritance diagram for mln::doc::Value_Iterator< E >:



Public Types

- `typedef void value`
Value associated type.

Public Member Functions

- `void invalidate ()`
Invalidate the iterator.
- `bool is_valid () const`
Returns true if the iterator is valid, that is, designates an element.
- `operator value () const`
Conversion into a value.
- `void start ()`
Start an iteration.

10.123.1 Detailed Description

template<typename E> struct mln::doc::Value_Iterator< E >

Documentation class for [mln::Value_Iterator](#).

See also

[mln::Value_Iterator](#)

Definition at line 37 of file doc/value_iterator.hh.

10.123.2 Member Typedef Documentation

10.123.2.1 template<typename E > typedef void mln::doc::Value_Iterator< E >::value

[Value](#) associated type.

Definition at line 41 of file doc/value_iterator.hh.

10.123.3 Member Function Documentation

10.123.3.1 template<typename E > void mln::doc::Iterator< E >::invalidate () [inherited]

Invalidate the iterator.

10.123.3.2 template<typename E > bool mln::doc::Iterator< E >::is_valid () const [inherited]

Returns true if the iterator is valid, that is, designates an element.

10.123.3.3 template<typename E > mln::doc::Value_Iterator< E >::operator value () const

Conversion into a value.

Returns

A value.

10.123.3.4 template<typename E > void mln::doc::Iterator< E >::start () [inherited]

Start an iteration.


Make the iterator designate the first element if it exists. If this first element does not exist, the iterator is not valid.

10.124 mln::doc::Value_Set< E > Struct Template Reference

Documentation class for [mln::Value_Set](#).

```
#include <value_set.hh>
```

Inheritance diagram for mln::doc::Value_Set< E >:



Public Types

- **typedef void bkd_viter**
Backward [Value_Iterator](#) associated type.
- **typedef void fwd_viter**
Forward [Value_Iterator](#) associated type.
- **typedef void value**
[Value](#) associated type.

Public Member Functions

- **bool has (const [value](#) &v) const**
Test if v belongs to this set of values.
- **unsigned index_of (const [value](#) &v) const**
Give the index of value v in this set.
- **unsigned nvalues () const**
Give the number of values in this set.
- **[value](#) operator[] (unsigned i) const**
Give the i-th value of this set.

10.124.1 Detailed Description

template<typename E> struct mln::doc::Value_Set< E >

Documentation class for [mln::Value_Set](#).

See also

[mln::Value_Set](#)

Definition at line 37 of file doc/value_set.hh.

10.124.2 Member Typedef Documentation

10.124.2.1 template<typename E > typedef void mln::doc::Value_Set< E >::bkd_viter

Backward [Value_Iterator](#) associated type.

Definition at line 49 of file doc/value_set.hh.

10.124.2.2 template<typename E > typedef void mln::doc::Value_Set< E >::fwd_viter

Forward [Value_Iterator](#) associated type.

Definition at line 45 of file doc/value_set.hh.

10.124.2.3 template<typename E > typedef void mln::doc::Value_Set< E >::value

[Value](#) associated type.

Definition at line 41 of file doc/value_set.hh.

10.124.3 Member Function Documentation

10.124.3.1 template<typename E > bool mln::doc::Value_Set< E >::has (const value & v) const

Test if v belongs to this set of values.

Parameters

[in] v A value.

Returns

True if v is an element of the set of values.

10.124.3.2 template<typename E > unsigned mln::doc::Value_Set< E >::index_of (const value & v) const

Give the index of value v in this set.

10.124.3.3 template<typename E > unsigned mln::doc::Value_Set< E >::nvalues () const

Give the number of values in this set.

10.124.3.4 template<typename E> value mln::doc::Value_Set< E >::operator[](unsigned i) const


Give the i -th value of this set.

10.125 mln::doc::Weighted_Window< E > Struct Template Reference

Documentation class for [mln::Weighted_Window](#).

```
#include <weighted_window.hh>
```

Inheritance diagram for mln::doc::Weighted_Window< E >:



Public Types

- **typedef void bkd_qiter**
Site_Iterator type associated to this weighted_window to browse its points in a backward way.
- **typedef void dpoint**
Dpsite associated type.
- **typedef void fwd_qiter**
Site_Iterator type associated to this weighted_window to browse its points in a forward way.
- **typedef void point**
Site associated type.
- **typedef void weight**
Weight associated type.
- **typedef void window**
Window associated type.

Public Member Functions

- `unsigned delta () const`

Give the maximum coordinate gap between the window center and a window point.

- `bool is_centered () const`

Test if the weighted_window is centered.

- `bool is_empty () const`

Test if the weighted window is empty.

- `E & sym ()`

Apply a central symmetry to the target weighted window.

- `const window & win () const`

Give the corresponding window.

10.125.1 Detailed Description

`template<typename E> struct mln::doc::Weighted_Window< E >`

Documentation class for [mln::Weighted_Window](#). A weighted_window is the definition of a set of points located around a central point, with a weight associated to each point.

See also

[mln::Weighted_Window](#)

Definition at line 40 of file doc/weighted_window.hh.

10.125.2 Member Typedef Documentation

10.125.2.1 template<typename E > typedef void mln::doc::Weighted_Window< E >::bkd_qiter

[Site_Iterator](#) type associated to this weighted_window to browse its points in a backward way.

Definition at line 51 of file doc/weighted_window.hh.

10.125.2.2 template<typename E > typedef void mln::doc::Weighted_Window< E >::dpoint

Dpsite associated type.

Definition at line 57 of file doc/weighted_window.hh.

10.125.2.3 template<typename E > typedef void mln::doc::Weighted_Window< E >::fwd_qiter

[Site_Iterator](#) type associated to this weighted_window to browse its points in a forward way.

Definition at line 46 of file doc/weighted_window.hh.

10.125.2.4 template<typename E> typedef void mln::doc::Weighted_Window< E >::point

[Site](#) associated type.

Definition at line 54 of file doc/weighted_window.hh.

10.125.2.5 template<typename E> typedef void mln::doc::Weighted_Window< E >::weight

Weight associated type.

Definition at line 60 of file doc/weighted_window.hh.

10.125.2.6 template<typename E> typedef void mln::doc::Weighted_Window< E >::window

[Window](#) associated type.

Definition at line 63 of file doc/weighted_window.hh.

10.125.3 Member Function Documentation

10.125.3.1 template<typename E> unsigned mln::doc::Weighted_Window< E >::delta() const

Give the maximum coordinate gap between the window center and a window point.

10.125.3.2 template<typename E> bool mln::doc::Weighted_Window< E >::is_centered() const

Test if the weighted_window is centered.

A weighted window is centered if the origin belongs to it.

10.125.3.3 template<typename E> bool mln::doc::Weighted_Window< E >::is_empty() const

Test if the weighted window is empty.

A weighted_window of null size is empty.

10.125.3.4 template<typename E> E& mln::doc::Weighted_Window< E >::sym()

Apply a central symmetry to the target weighted window.

10.125.3.5 template<typename E> const window& mln::doc::Weighted_Window< E >::win() const


Give the corresponding window.

10.126 mln::doc::Window< E > Struct Template Reference

Documentation class for [mln::Window](#).

```
#include <window.hh>
```

Inheritance diagram for mln::doc::Window< E >:



Public Types

- **typedef void bkd_qiter**
Site_Iterator type associated to this window to browse its points in a backward way.
- **typedef void fwd_qiter**
Site_Iterator type associated to this window to browse its points in a forward way.
- **typedef void qiter**
Site_Iterator type associated to this window to browse its points.

10.126.1 Detailed Description

template<typename E> struct mln::doc::Window< E >

Documentation class for [mln::Window](#). A window is the definition of a set of points located around a central point.

See also

[mln::Window](#)

Definition at line 40 of file concept/doc/window.hh.

10.126.2 Member Typedef Documentation

10.126.2.1 template<typename E > typedef void mln::doc::Window< E >::bkd_qiter

[Site_Iterator](#) type associated to this window to browse its points in a backward way.

Definition at line 55 of file concept/doc/window.hh.

10.126.2.2 template<typename E > typedef void mln::doc::Window< E >::fwd_qiter

[Site_Iterator](#) type associated to this window to browse its points in a forward way.

Definition at line 50 of file concept/doc/window.hh.

10.126.2.3 template<typename E > typedef void mln::doc::Window< E >::qiter

[Site_Iterator](#) type associated to this window to browse its points.

Definition at line 45 of file concept/doc/window.hh.

10.127 mln::Dpoint< E > Struct Template Reference

Base class for implementation of delta-point classes.

```
#include <dpoint.hh>
```

Inherits mln::Delta_Point_Site< E >.

Public Member Functions

- const E & [to_dpoint](#) () const

It is a [Dpoint](#) so it returns itself.

10.127.1 Detailed Description

template<typename E> struct mln::Dpoint< E >

Base class for implementation of delta-point classes. A delta-point is a vector defined by a couple of points.

Given two points, A and B, the vector AB is mapped into the delta-point D = AB. Practically one can write:
 $D = B - A$.

See also

[mln::doc::Dpoint](#) for a complete documentation of this class contents.

Definition at line 63 of file concept/dpoint.hh.

10.127.2 Member Function Documentation

**10.127.2.1 template<typename E > const E & mln::Dpoint< E >::to_dpoint () const
[inline]**

It is a [Dpoint](#) so it returns itself.


Definition at line 88 of file concept/dpoint.hh.

10.128 mln::dpoint< G, C > Struct Template Reference

Generic delta-point class.

```
#include <dpoint.hh>
```

Inheritance diagram for mln::dpoint< G, C >:



Public Types

- enum { `dim` = `G::dim` }
- typedef `C coord`
Coordinate associated type.
- typedef `G grid`
Grid associated type.
- typedef `point< G, C > psite`
Psite associated type.
- typedef `point< G, C > site`
Site associated type.
- typedef `algebra::vec< G::dim, C > vec`
Algebra vector (vec) associated type.

Public Member Functions

- **dpoint ()**
Constructor without argument.
- template<typename C2 >
dpoint (const algebra::vec< dim, C2 > &v)
Constructor from an algebra vector.
- template<typename F >
dpoint (const Function_v2v< F > &f)
Constructor; coordinates are set by function f.
- template<typename Q >
operator mln::algebra::vec< dpoint< G, C >::dim, Q > () const
Conversion towards a algebra::vec.
- C **operator[]** (unsigned i) const
Read-only access to the i-th coordinate value.
- C & **operator[]** (unsigned i)
Read-write access to the i-th coordinate value.
- void **set_all** (C c)
Set all coordinates to the value c.
- **vec to_vec () const**
Explicit conversion.
- **dpoint (C ind)**
- **dpoint (const literal::zero_t &)**
Constructors/assignments with literals.

10.128.1 Detailed Description

template<typename G, typename C> struct mln::dpoint< G, C >

Generic delta-point class. Parameters are G the dimension of the space and C the coordinate type in this space.

Definition at line 58 of file dpoint.hh.

10.128.2 Member Typedef Documentation

10.128.2.1 template<typename G, typename C> typedef C mln::dpoint< G, C >::coord

Coordinate associated type.

Definition at line 76 of file dpoint.hh.

10.128.2.2 template<typename G, typename C> typedef G mln::dpoint< G, C >::grid

Grid associated type.

Definition at line 67 of file dpoint.hh.

10.128.2.3 template<typename G, typename C> typedef point<G,C> mln::dpoint< G, C >::psite

Psite associated type.

Definition at line 70 of file dpoint.hh.

10.128.2.4 template<typename G, typename C> typedef point<G,C> mln::dpoint< G, C >::site

[Site](#) associated type.

Definition at line 73 of file dpoint.hh.

10.128.2.5 template<typename G, typename C> typedef algebra::vec<G::dim, C> mln::dpoint< G, C >::vec

Algebra vector (vec) associated type.

Definition at line 79 of file dpoint.hh.

10.128.3 Member Enumeration Documentation**10.128.3.1 template<typename G, typename C> anonymous enum**

Enumerator:

dim Dimension of the space.

Invariant

$\text{dim} > 0$

Definition at line 64 of file dpoint.hh.

10.128.4 Constructor & Destructor Documentation**10.128.4.1 template<typename G , typename C > mln::dpoint< G, C >::dpoint() [inline]**

Constructor without argument.

Definition at line 152 of file dpoint.hh.

10.128.4.2 template<typename G , typename C > template<typename C2 > mln::dpoint< G, C >::dpoint(const algebra::vec< dim, C2 > & v) [inline]

Constructor from an algebra vector.

Definition at line 159 of file dpoint.hh.

References mln::dpoint< G, C >::dim.

10.128.4.3 template<typename G , typename C> mln::dpoint< G, C >::dpoint (C *ind*) [inline]

Constructors with different numbers of arguments (coordinates) w.r.t. the dimension.

Definition at line 176 of file dpoint.hh.

10.128.4.4 template<typename G , typename C> mln::dpoint< G, C >::dpoint (const literal::zero_t &) [inline]

Constructors/assignments with literals.

Definition at line 203 of file dpoint.hh.

10.128.4.5 template<typename G , typename C> template<typename F> mln::dpoint< G, C >::dpoint (const Function_v2v< F > & f) [inline]

Constructor; coordinates are set by function *f*.

Definition at line 238 of file dpoint.hh.

10.128.5 Member Function Documentation

10.128.5.1 template<typename G , typename C> template<typename Q> mln::dpoint< G, C >::operator mln::algebra::vec< dpoint< G, C >::dim, Q >() const [inline]

Conversion towards a algebra::vec.

Definition at line 257 of file dpoint.hh.

References mln::dpoint< G, C >::to_vec().

10.128.5.2 template<typename G , typename C> C & mln::dpoint< G, C >::operator[](unsigned *i*) [inline]

Read-write access to the *i*-th coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

i < dim

Definition at line 144 of file dpoint.hh.

References mln::dpoint< G, C >::dim.

10.128.5.3 template<typename G , typename C> C mln::dpoint< G, C >::operator[](unsigned *i*) const [inline]

Read-only access to the *i*-th coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

i < dim

Definition at line 136 of file dpoint.hh.

References mln::dpoint< G, C >::dim.

10.128.5.4 template<typename G , typename C> void mln::dpoint< G, C >::set_all (C c) [inline]

Set all coordinates to the value *c*.

Definition at line 248 of file dpoint.hh.

Referenced by mln::win::line< M, i, C >::line().

10.128.5.5 template<typename G , typename C > dpoint< G, C >::vec mln::dpoint< G, C >::to_vec () const [inline]

Explicit conversion.

Definition at line 265 of file dpoint.hh.

References mln::dpoint< G, C >::dim.


Referenced by mln::dpoint< G, C >::operator mln::algebra::vec< dpoint< G, C >::dim, Q >().

10.129 mln::dpoints_bkd_pixter< I > Class Template Reference

A generic backward iterator on the pixels of a dpoint-based window or neighborhood.

```
#include <dpoints_pixter.hh>
```

Inheritance diagram for mln::dpoints_bkd_pixter< I >:



Public Member Functions

- const I::value & [center_val \(\) const](#)
The value around which this iterator moves.

- template<typename Dps, typename Pref>
[dpoints_bkd_pixter](#)(const Generalized_Pixel< Pref > &pxl_ref, const Dps &dps)
Constructor (using a generalized pixel).

- template<typename Dps, typename Pref>
[dpoints_bkd_pixter](#)(I &image, const Dps &dps, const Pref &p_ref)
Constructor (using an image).

- void [next \(\)](#)
Go to the next element.

- void [start \(\)](#)
Manipulation.

- void **invalidate** ()

Invalidate the iterator.
- bool **is_valid** () const

Test the iterator validity.
- void **update** ()

Force this iterator to update its location to take into account that its center point may have moved.

10.129.1 Detailed Description

template<typename I> class mln::dpoints_bkd_pixter< I >

A generic backward iterator on the pixels of a dpoint-based window or neighborhood. Parameter *I* is the image type.

Definition at line 140 of file dpoints_pixter.hh.

10.129.2 Constructor & Destructor Documentation

**10.129.2.1 template<typename I > template<typename Dps , typename Pref >
mln::dpoints_bkd_pixter< I >::dpoints_bkd_pixter (I & *image*, const Dps & *dps*,
const Pref & *p_ref*) [inline]**

Constructor (using an image).

Parameters

- [in] *image* The image to iterate over.
- [in] *dps* An object (neighborhood or window) that can provide a set of delta-points.
- [in] *p_ref* Center (resp. reference) point of the neighborhood (resp. window).

Definition at line 338 of file dpoints_pixter.hh.

**10.129.2.2 template<typename I > template<typename Dps , typename Pref >
mln::dpoints_bkd_pixter< I >::dpoints_bkd_pixter (const Generalized_Pixel< Pref
> & *pxl_ref*, const Dps & *dps*) [inline]**

Constructor (using a generalized pixel).

Parameters

- [in] *pxl_ref* Center (generalized) pixel to iterate around.
- [in] *dps* An object (neighborhood or window) that can provide a set of delta-points.

Definition at line 352 of file dpoints_pixter.hh.

10.129.3 Member Function Documentation

10.129.3.1 template<typename I> const I::value & mln::dpoints_bkd_pixter< I >::center_val() const [inline]

The value around which this iterator moves.

Definition at line 367 of file dpoints_pixter.hh.

10.129.3.2 template<typename I> void mln::dpoints_bkd_pixter< I >::invalidate() [inline]

Invalidate the iterator.

Definition at line 436 of file dpoints_pixter.hh.

10.129.3.3 template<typename I> bool mln::dpoints_bkd_pixter< I >::is_valid() const [inline]

Test the iterator validity.

Definition at line 428 of file dpoints_pixter.hh.

Referenced by mln::dpoints_bkd_pixter< I >::update().

10.129.3.4 void mln::Iterator< dpoints_bkd_pixter< I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.129.3.5 template<typename I> void mln::dpoints_bkd_pixter< I >::start() [inline]

Manipulation.

Start an iteration.

Definition at line 409 of file dpoints_pixter.hh.

References mln::dpoints_bkd_pixter< I >::update().

10.129.3.6 template<typename I> void mln::dpoints_bkd_pixter< I >::update() [inline]

Force this iterator to update its location to take into account that its center point may have moved.

Definition at line 395 of file dpoints_pixter.hh.

References mln::dpoints_bkd_pixter< I >::is_valid().


Referenced by mln::dpoints_bkd_pixter< I >::start().

10.130 mln::dpoints_fwd_pixter< I > Class Template Reference

A generic forward iterator on the pixels of a dpoint-based window or neighborhood.

```
#include <dpoints_pixter.hh>
```

Inheritance diagram for mln::dpoints_fwd_pixter< I >:



Public Member Functions

- const I::value & [center_val](#) () const

The value around which this iterator moves.

- template<typename Dps, typename Pref>

[dpoints_fwd_pixter](#) (const Generalized_Pixel< Pref > &pxl_ref, const Dps &dps)

Constructor (using a generalized pixel).

- template<typename Dps, typename Pref>

[dpoints_fwd_pixter](#) (I &image, const Dps &dps, const Pref &p_ref)

Constructor (using an image).

- void [next](#) ()

Go to the next element.

- void **start** ()
Manipulation.
- void **invalidate** ()
Invalidate the iterator.
- bool **is_valid** () const
Test the iterator validity.
- void **update** ()
Force this iterator to update its location to take into account that its center point may have moved.

10.130.1 Detailed Description

template<typename I> class mln::dpoints_fwd_pixter< I >

A generic forward iterator on the pixels of a dpoint-based window or neighborhood. Parameter **I** is the image type.

Definition at line 57 of file dpoints_pixter.hh.

10.130.2 Constructor & Destructor Documentation

**10.130.2.1 template<typename I > template<typename Dps , typename Pref >
 mln::dpoints_fwd_pixter< I >::dpoints_fwd_pixter (I & *image*, const Dps & *dps*,
 const Pref & *p_ref*) [inline]**

Constructor (using an image).

Parameters

- [in] ***image*** The image to iterate over.
- [in] ***dps*** An object (neighborhood or window) that can provide a set of delta-points.
- [in] ***p_ref*** Center (resp. reference) point of the neighborhood (resp. window).

Definition at line 224 of file dpoints_pixter.hh.

**10.130.2.2 template<typename I > template<typename Dps , typename Pref >
 mln::dpoints_fwd_pixter< I >::dpoints_fwd_pixter (const Generalized_Pixel< Pref
 > & *pxl_ref*, const Dps & *dps*) [inline]**

Constructor (using a generalized pixel).

Parameters

- [in] ***pxl_ref*** Center (generalized) pixel to iterate around.
- [in] ***dps*** An object (neighborhood or window) that can provide a set of delta-points.

Definition at line 241 of file dpoints_pixter.hh.

10.130.3 Member Function Documentation

10.130.3.1 template<typename I> const mln::dpoints_fwd_pixter< I >::center_val() const [inline]

The value around which this iterator moves.

Definition at line 256 of file dpoints_pixter.hh.

10.130.3.2 template<typename I> void mln::dpoints_fwd_pixter< I >::invalidate() [inline]

Invalidate the iterator.

Definition at line 325 of file dpoints_pixter.hh.

10.130.3.3 template<typename I> bool mln::dpoints_fwd_pixter< I >::is_valid() const [inline]

Test the iterator validity.

Definition at line 317 of file dpoints_pixter.hh.

Referenced by mln::dpoints_fwd_pixter< I >::update().

10.130.3.4 void mln::Iterator< dpoints_fwd_pixter< I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.130.3.5 template<typename I> void mln::dpoints_fwd_pixter< I >::start() [inline]

Manipulation.

Start an iteration.

Definition at line 298 of file dpoints_pixter.hh.

References mln::dpoints_fwd_pixter< I >::update().

10.130.3.6 template<typename I> void mln::dpoints_fwd_pixter< I >::update() [inline]

Force this iterator to update its location to take into account that its center point may have moved.

Definition at line 284 of file dpoints_pixter.hh.

References mln::dpoints_fwd_pixter< I >::is_valid().

Referenced by mln::dpoints_fwd_pixter< I >::start().

10.131 mln::Edge< E > Struct Template Reference

edge category flag type.

```
#include <edge.hh>
```

10.131.1 Detailed Description

```
template<typename E> struct mln::Edge< E >
```

edge category flag type.

Definition at line 52 of file edge.hh.

10.132 mln::edge_image< P, V, G > Class Template Reference

[Image](#) based on graph edges.

```
#include <edge_image.hh>
```

Inherits `image_base< fun::i2v::array< V >, p_edges< G, internal::efsite_selector< P, G >::site_function_t >, edge_image< P, V, G > >`.

Public Types

- `typedef graph_elt_neighborhood< G, p_edges< G, site_function_t > > edge_nbh_t`
Neighborhood type.
- `typedef graph_elt_window< G, p_edges< G, site_function_t > > edge_win_t`
Edge Window type.
- `typedef G graph_t`
The type of the underlying graph.
- `typedef edge_nbh_t nbh_t`
Default Neighborhood type.
- `typedef internal::efsite_selector< P, G >::site_function_t site_function_t`
Function mapping graph elements to sites.
- `typedef edge_image< tag::psite_< P >, tag::value_< V >, tag::graph_< G > > skeleton`
Skeleton type.
- `typedef edge_win_t win_t`
Default Window type.

Public Member Functions

- `edge_image ()`
Constructors.

- rvalue `operator()` (unsigned e_id) const
Value accessors/operators overloads.

10.132.1 Detailed Description

`template<typename P, typename V, typename G = util::graph> class mln::edge_image< P, V, G >`

[Image](#) based on graph edges.

Definition at line 123 of file core/image/edge_image.hh.

10.132.2 Member Typedef Documentation

10.132.2.1 `template<typename P, typename V, typename G = util::graph> typedef graph_elt_neighborhood<G,p_edges<G,site_function_t> > mln::edge_image< P, V, G >::edge_nbh_t`

[Neighborhood](#) type.

Definition at line 153 of file core/image/edge_image.hh.

10.132.2.2 `template<typename P, typename V, typename G = util::graph> typedef graph_elt_window<G,p_edges<G,site_function_t> > mln::edge_image< P, V, G >::edge_win_t`

[Edge Window](#) type.

Definition at line 151 of file core/image/edge_image.hh.

10.132.2.3 `template<typename P, typename V, typename G = util::graph> typedef G mln::edge_image< P, V, G >::graph_t`

The type of the underlying graph.

Definition at line 138 of file core/image/edge_image.hh.

10.132.2.4 `template<typename P, typename V, typename G = util::graph> typedef edge_nbh_t mln::edge_image< P, V, G >::nbh_t`

Default [Neighborhood](#) type.

Definition at line 159 of file core/image/edge_image.hh.

10.132.2.5 template<typename P, typename V, typename G = util::graph> typedef internal::efsite_selector<P,G>::site_function_t mln::edge_image< P, V, G >::site_function_t

Function mapping graph elements to sites.

Definition at line 147 of file core/image/edge_image.hh.

10.132.2.6 template<typename P, typename V, typename G = util::graph> typedef edge_image< tag::psite_<P>, tag::value_<V>, tag::graph_<G> > mln::edge_image< P, V, G >::skeleton

Skeleton type.

Definition at line 143 of file core/image/edge_image.hh.

10.132.2.7 template<typename P, typename V, typename G = util::graph> typedef edge_win_t mln::edge_image< P, V, G >::win_t

Default [Window](#) type.

Definition at line 156 of file core/image/edge_image.hh.

10.132.3 Constructor & Destructor Documentation

10.132.3.1 template<typename P , typename V , typename G > mln::edge_image< P, V, G >::edge_image() [inline]

Constructors.

Definition at line 248 of file core/image/edge_image.hh.

10.132.4 Member Function Documentation

10.132.4.1 template<typename P , typename V , typename G > edge_image< P, V, G >::rvalue mln::edge_image< P, V, G >::operator() (unsigned e_id) const

[Value](#) accessors/operators overloads.

Definition at line 302 of file core/image/edge_image.hh.

10.133 mln::extended< I > Struct Template Reference

Makes an image become restricted by a point set.

```
#include <extended.hh>
```

Inherits [image_domain_morpher< I, box< I::site >, extended< I > >](#).

Public Types

- [typedef tag::image_< I > skeleton](#)

Skeleton.

- `typedef I::value value`

Value type.

Public Member Functions

- `const box< typename I::site > & domain () const`

Give the definition domain.

- `extended ()`

Constructor without argument.

- `extended (I &ima, const box< typename I::site > &b)`

Constructor.

10.133.1 Detailed Description

`template<typename I> struct mln::extended< I >`

Makes an image become restricted by a point set.

Definition at line 92 of file extended.hh.

10.133.2 Member Typedef Documentation

10.133.2.1 `template<typename I> typedef tag::image_<I> mln::extended< I >::skeleton`

Skeleton.

Definition at line 102 of file extended.hh.

10.133.2.2 `template<typename I> typedef I ::value mln::extended< I >::value`

Value type.

Definition at line 99 of file extended.hh.

10.133.3 Constructor & Destructor Documentation

10.133.3.1 `template<typename I> mln::extended< I >::extended () [inline]`

Constructor without argument.

Definition at line 169 of file extended.hh.

10.133.3.2 template<typename I> mln::extended< I >::extended (I & ima, const box< typename I::site > & b) [inline]

Constructor.

Definition at line 175 of file extended.hh.

10.133.4 Member Function Documentation

10.133.4.1 template<typename I> const box< typename I::site > & mln::extended< I >::domain () const [inline]

Give the definition domain.

Definition at line 192 of file extended.hh.

10.134 mln::extension_fun< I, F > Class Template Reference

Extends the domain of an image with a function.

```
#include <extension_fun.hh>
```

Inherits image_identity< I, I::domain_t, extension_fun< I, F > >.

Public Types

- **typedef I::value rvalue**
Return type of read-only access.
- **typedef extension_fun< tag::image_< I >, tag::function_< F > > skeleton**
Skeleton.
- **typedef I::value value**
Image value type.

Public Member Functions

- **const F & extension () const**
Give the extension function.
- **extension_fun (I &ima, const F &fun)**
Constructor from an image ima and a function fun.
- **extension_fun ()**
Constructor without argument.
- **template<typename P >
 bool has (const P &p) const**
Test if p is valid.

- internal::morpher_lvalue_< I >::ret [operator\(\)](#) (const typename I::psite &p)

Read-write access to the image value located at site p.

- I::value [operator\(\)](#) (const typename I::psite &p) const

Read-only access to the image value located at site p;

10.134.1 Detailed Description

template<typename I, typename F> class mln::extension_fun< I, F >

Extends the domain of an image with a function.

Definition at line 99 of file extension_fun.hh.

10.134.2 Member Typedef Documentation

10.134.2.1 template<typename I, typename F> typedef I ::value mln::extension_fun< I, F >::rvalue

Return type of read-only access.

Definition at line 112 of file extension_fun.hh.

10.134.2.2 template<typename I, typename F> typedef extension_fun< tag::image_<I>, tag::function_<F> > mln::extension_fun< I, F >::skeleton

Skeleton.

Definition at line 106 of file extension_fun.hh.

10.134.2.3 template<typename I, typename F> typedef I ::value mln::extension_fun< I, F >::value

[Image](#) value type.

Definition at line 109 of file extension_fun.hh.

10.134.3 Constructor & Destructor Documentation

10.134.3.1 template<typename I, typename F> mln::extension_fun< I, F >::extension_fun () [inline]

Constructor without argument.

Definition at line 178 of file extension_fun.hh.

10.134.3.2 template<typename I , typename F > mln::extension_fun< I, F >::extension_fun (I & ima, const F & fun) [inline]

Constructor from an image `ima` and a function `fun`.

Definition at line 184 of file `extension_fun.hh`.

10.134.4 Member Function Documentation

10.134.4.1 template<typename I , typename F > const F & mln::extension_fun< I, F >::extension() const [inline]

Give the extension function.

Definition at line 243 of file `extension_fun.hh`.

10.134.4.2 template<typename I , typename F > template<typename P > bool mln::extension_fun< I, F >::has(const P & p) const [inline]

Test if `p` is valid.

It returns always true, assuming that the function is valid for any `p`.

Definition at line 201 of file `extension_fun.hh`.

10.134.4.3 template<typename I , typename F > internal::morpher_lvalue_< I >::ret mln::extension_fun< I, F >::operator() (const typename I::psite & p) [inline]

Read-write access to the image value located at site `p`.

Definition at line 223 of file `extension_fun.hh`.

10.134.4.4 template<typename I , typename F > I::value mln::extension_fun< I, F >::operator() (const typename I::psite & p) const [inline]

Read-only access to the image value located at site `p`:

Definition at line 209 of file `extension_fun.hh`.

10.135 mln::extension_ima< I, J > Class Template Reference

Extends the domain of an image with an image.

```
#include <extension_ima.hh>
```

Inherits `image_identity< I, I::domain_t, extension_ima< I, J > >`.

Public Types

- `typedef I::value rvalue`

Return type of read-only access.

- **typedef** `extension_ima< tag::image_< I >, tag::ext_< J > > skeleton`
Skeleton.
- **typedef** `I::value value`
Image value type.

Public Member Functions

- **const J & extension () const**
Read-only access to the extension domain (image).
- **extension_ima (I &ima, const J &ext)**
Constructor from an image ima and a function ext.
- **extension_ima ()**
Constructor without argument.
- **template<typename P >
 bool has (const P &p) const**
Test if p is valid.
- **internal::morpher_lvalue_< I >::ret operator() (const typename I::psite &p)**
Read-write access to the image value located at site p.
- **I::value operator() (const typename I::psite &p) const**
Read-only access to the image value located at site p;.

10.135.1 Detailed Description

template<typename I, typename J> class mln::extension_ima< I, J >

Extends the domain of an image with an image.

Definition at line 97 of file extension_ima.hh.

10.135.2 Member Typedef Documentation

10.135.2.1 **template<typename I, typename J> typedef I ::value mln::extension_ima< I, J >::rvalue**

Return type of read-only access.

Definition at line 111 of file extension_ima.hh.

10.135.2.2 template<typename I, typename J> typedef extension_ima< tag::image_<I>, tag::ext_<J> > mln::extension_ima< I, J >::skeleton

Skeleton.

Definition at line 105 of file extension_ima.hh.

10.135.2.3 template<typename I, typename J> typedef I ::value mln::extension_ima< I, J >::value

[Image](#) value type.

Definition at line 108 of file extension_ima.hh.

10.135.3 Constructor & Destructor Documentation

10.135.3.1 template<typename I , typename J > mln::extension_ima< I, J >::extension_ima () [inline]

Constructor without argument.

Definition at line 173 of file extension_ima.hh.

10.135.3.2 template<typename I , typename J > mln::extension_ima< I, J >::extension_ima (I & ima, const J & ext) [inline]

Constructor from an image `ima` and a function `ext`.

Definition at line 179 of file extension_ima.hh.

10.135.4 Member Function Documentation

10.135.4.1 template<typename I , typename J > const J & mln::extension_ima< I, J >::extension () const [inline]

Read-only access to the extension domain (image).

Definition at line 244 of file extension_ima.hh.

10.135.4.2 template<typename I , typename J > template<typename P > bool mln::extension_ima< I, J >::has (const P & p) const [inline]

Test if `p` is valid.

Definition at line 196 of file extension_ima.hh.

10.135.4.3 template<typename I , typename J > internal::morpher_lvalue_< I >::ret mln::extension_ima< I, J >::operator() (const typename I::psite & p) [inline]

Read-write access to the image value located at site `p`.

Definition at line 223 of file extension_ima.hh.

**10.135.4.4 template<typename I , typename J > I::value mln::extension_ima< I, J >::operator()
(const typename I::psite & p) const [inline]**

Read-only access to the image value located at site p;.

Definition at line 208 of file extension_ima.hh.

10.136 mln::extension_val< I > Class Template Reference

Extends the domain of an image with a value.

```
#include <extension_val.hh>
```

Inherits image_identity< I, I::domain_t, extension_val< I > >.

Public Types

- **typedef I::value rvalue**
Return type of read-only access.
- **typedef extension_val< tag::image_< I > > skeleton**
Skeleton.
- **typedef I::value value**
Image value type.

Public Member Functions

- **void change_extension (const typename I::value &val)**
Change the value of the extension domain.
- **const I::value & extension () const**
Read-only access to the value of the extension domain.
- **extension_val (I &ima, const typename I::value &val)**
Constructor from an image ima and a value val.
- **extension_val ()**
Constructor without argument.
- **template<typename P >
bool has (const P &p) const**
Test if p is valid. It returns always true.
- **internal::morpher_lvalue_< I >::ret operator() (const typename I::psite &p)**
Read-write access to the image value located at site p.
- **I::value operator() (const typename I::psite &p) const**
Read-only access to the image value located at site p;.

10.136.1 Detailed Description

template<typename I> class mln::extension_val< I >

Extends the domain of an image with a value.

Definition at line 98 of file extension_val.hh.

10.136.2 Member Typedef Documentation

10.136.2.1 template<typename I> typedef I ::value mln::extension_val< I >::rvalue

Return type of read-only access.

Definition at line 110 of file extension_val.hh.

10.136.2.2 template<typename I> typedef extension_val< tag::image_<I> > mln::extension_val< I >::skeleton

Skeleton.

Definition at line 104 of file extension_val.hh.

10.136.2.3 template<typename I> typedef I ::value mln::extension_val< I >::value

[Image](#) value type.

Definition at line 107 of file extension_val.hh.

10.136.3 Constructor & Destructor Documentation

10.136.3.1 template<typename I> mln::extension_val< I >::extension_val() [inline]

Constructor without argument.

Definition at line 176 of file extension_val.hh.

10.136.3.2 template<typename I> mln::extension_val< I >::extension_val(I & ima, const typename I::value & val) [inline]

Constructor from an image *ima* and a value *val*.

Definition at line 182 of file extension_val.hh.

10.136.4 Member Function Documentation

10.136.4.1 template<typename I> void mln::extension_val< I >::change_extension(const typename I::value & val) [inline]

Change the value of the extension domain.

Definition at line 247 of file extension_val.hh.

10.136.4.2 template<typename I> const I::value & mln::extension_val< I >::extension () const [inline]

Read-only access to the value of the extension domain.

Definition at line 238 of file extension_val.hh.

10.136.4.3 template<typename I> template<typename P> bool mln::extension_val< I >::has (const P & p) const [inline]

Test if p is valid. It returns always true.

Definition at line 199 of file extension_val.hh.

10.136.4.4 template<typename I> internal::morpher_lvalue_< I >::ret mln::extension_val< I >::operator() (const typename I::psite & p) [inline]

Read-write access to the image value located at site p .

Definition at line 220 of file extension_val.hh.

10.136.4.5 template<typename I> I::value mln::extension_val< I >::operator() (const typename I::psite & p) const [inline]

Read-only access to the image value located at site p .

Definition at line 207 of file extension_val.hh.

10.137 mln::faces_psite< N, D, P > Class Template Reference

[Point](#) site associated to a [mln::p_faces](#).

```
#include <faces_psite.hh>
```

Inherits [pseudo_site_base_< const P &, faces_psite< N, D, P > >](#).

Public Member Functions

- [faces_psite \(\)](#)
Construction and assignment.
- [faces_psite \(const p_faces< N, D, P > &pf, const topo::n_face< N, D > &face\)](#)
- [bool is_valid \(\) const](#)
Psite manipulators.
- [void invalidate \(\)](#)
Invalidate this psite.

- [const target & site_set \(\) const](#)
Site set manipulators.

- void `change_target` (const `target` &`new_target`)
Set the target site_set.
- `topo::n_face< N, D > face` () const
Face handle manipulators.
- unsigned `n` () const
Return the dimension of the face of this psite.
- unsigned `face_id` () const
Return the id of the face of this psite.

10.137.1 Detailed Description

`template<unsigned N, unsigned D, typename P> class mln::faces_psite< N, D, P >`

Point site associated to a `mln::p_faces`.

Template Parameters

N The dimension of the face associated to this psite.

D The dimension of the complex this psite belongs to.

P The type of point associated to this psite.

Definition at line 56 of file `faces_psite.hh`.

10.137.2 Constructor & Destructor Documentation

10.137.2.1 template<unsigned N, unsigned D, typename P> mln::faces_psite< N, D, P >::faces_psite () [inline]

Construction and assignment.

Definition at line 190 of file `faces_psite.hh`.

References `mln::faces_psite< N, D, P >::invalidate()`.

10.137.2.2 template<unsigned N, unsigned D, typename P> mln::faces_psite< N, D, P >::faces_psite (const `p_faces< N, D, P >` & `pf`, const `topo::n_face< N, D >` & `face`) [inline]

Precondition

`pf.cplx() == face.cplx()`.

Definition at line 201 of file `faces_psite.hh`.

10.137.3 Member Function Documentation

10.137.3.1 template<unsigned N, unsigned D, typename P> void mln::faces_psite< N, D, P >::change_target(const target & new_target) [inline]

Set the target site_set.

Definition at line 265 of file faces_psite.hh.

References mln::p_faces< N, D, P >::cplx(), and mln::faces_psite< N, D, P >::invalidate().

10.137.3.2 template<unsigned N, unsigned D, typename P> topo::n_face< N, D > mln::faces_psite< N, D, P >::face() const [inline]

Face handle manipulators.

Return the face handle of this point site.

Definition at line 289 of file faces_psite.hh.

Referenced by mln::operator!=(), and mln::operator==().

10.137.3.3 template<unsigned N, unsigned D, typename P> unsigned mln::faces_psite< N, D, P >::face_id() const [inline]

Return the id of the face of this psite.

Definition at line 305 of file faces_psite.hh.

10.137.3.4 template<unsigned N, unsigned D, typename P> void mln::faces_psite< N, D, P >::invalidate() [inline]

Invalidate this psite.

Definition at line 239 of file faces_psite.hh.

Referenced by mln::faces_psite< N, D, P >::change_target(), and mln::faces_psite< N, D, P >::faces_psite().

10.137.3.5 template<unsigned N, unsigned D, typename P> bool mln::faces_psite< N, D, P >::is_valid() const [inline]

Psite manipulators.

Is this psite valid?

Definition at line 230 of file faces_psite.hh.

10.137.3.6 template<unsigned N, unsigned D, typename P> unsigned mln::faces_psite< N, D, P >::n() const [inline]

Return the dimension of the face of this psite.

Definition at line 297 of file faces_psite.hh.

10.137.3.7 template<unsigned N, unsigned D, typename P> const p_faces< N, D, P > & mln::faces_psite< N, D, P >::site_set() const [inline]

[Site](#) set manipulators.

Return the [p_faces](#) this site is built on. (shortcut for *target()).

Precondition

Member `face_` is valid.

Definition at line 247 of file `faces_psite.hh`.

Referenced by `mln::operator!=()`, and `mln::operator==()`.

10.138 mln::flat_image< T, S > Struct Template Reference

[Image](#) with a single value.

```
#include <flat_image.hh>
```

Inherits `image_primary< T, S, flat_image< T, S > >`.

Public Types

- `typedef T & lvalue`
Return type of read-write access.
- `typedef const T & rvalue`
Return type of read-only access.
- `typedef flat_image< tag::value_< T >, tag::domain_< S > > skeleton`
Skeleton.
- `typedef T value`
Value associated type.

Public Member Functions

- `const S & domain() const`
Give the definition domain.
- `flat_image(const T & val, const S & pset)`
Constructor.
- `flat_image()`
Constructor without argument.
- `bool has(const typename S::psite & p) const`
Test if p is valid: always return true.

- const T & [operator\(\)](#) (const typename S::psite &p) const
Read-only access to the image value located at point p.

- T & [operator\(\)](#) (const typename S::psite &p)
Read-write access to the image value located at point p.

10.138.1 Detailed Description

template<typename T, typename S> struct mln::flat_image< T, S >

[Image](#) with a single value.

Definition at line 105 of file flat_image.hh.

10.138.2 Member Typedef Documentation

10.138.2.1 template<typename T, typename S> typedef T& mln::flat_image< T, S >::lvalue

Return type of read-write access.

Definition at line 118 of file flat_image.hh.

10.138.2.2 template<typename T, typename S> typedef const T& mln::flat_image< T, S >::rvalue

Return type of read-only access.

Definition at line 115 of file flat_image.hh.

10.138.2.3 template<typename T, typename S> typedef flat_image< tag::value_< T >, tag::domain_< S > > mln::flat_image< T, S >::skeleton

Skeleton.

Definition at line 108 of file flat_image.hh.

10.138.2.4 template<typename T, typename S> typedef T mln::flat_image< T, S >::value

[Value](#) associated type.

Definition at line 112 of file flat_image.hh.

10.138.3 Constructor & Destructor Documentation

10.138.3.1 template<typename T , typename S > mln::flat_image< T, S >::flat_image() [inline]

Constructor without argument.

Definition at line 191 of file flat_image.hh.

10.138.3.2 template<typename T , typename S > mln::flat_image< T, S >::flat_image (const T & val, const S & pset) [inline]

Constructor.

Definition at line 197 of file flat_image.hh.

10.138.4 Member Function Documentation

10.138.4.1 template<typename T , typename S > const S & mln::flat_image< T, S >::domain () const [inline]

Give the definition domain.

Definition at line 214 of file flat_image.hh.

10.138.4.2 template<typename T , typename S > bool mln::flat_image< T, S >::has (const typename S::psite & p) const [inline]

Test if p is valid: always return true.

Definition at line 222 of file flat_image.hh.

10.138.4.3 template<typename T , typename S > const T & mln::flat_image< T, S >::operator() (const typename S::psite & p) const [inline]

Read-only access to the image value located at point p.

Definition at line 230 of file flat_image.hh.

10.138.4.4 template<typename T , typename S > T & mln::flat_image< T, S >::operator() (const typename S::psite & p) [inline]

Read-write access to the image value located at point p.

Definition at line 239 of file flat_image.hh.

10.139 mln::fun::from_accu< A > Struct Template Reference

Wrap an accumulator into a function.

```
#include <from_accu.hh>
```

Inherits mln::fun::unary_param< from_accu< A >, A * >.

10.139.1 Detailed Description

template<typename A> struct mln::fun::from_accu< A >

Wrap an accumulator into a function.


Definition at line 49 of file from_accu.hh.

10.140 mln::fun::n2v::white_gaussian< V > Struct Template Reference

Generate a White Gaussian Noise.

```
#include <white_gaussian.hh>
```

Inheritance diagram for mln::fun::n2v::white_gaussian< V >:



10.140.1 Detailed Description

```
template<typename V> struct mln::fun::n2v::white_gaussian< V >
```

Generate a White Gaussian Noise. Reference: <http://www.dspguru.com/dsp/howtos/how-to-generate-white-gaussian-noise>


Definition at line 56 of file white_gaussian.hh.

10.141 mln::fun::p2b::antilogy Struct Reference

A p2b function always returning false.

```
#include <antilogy.hh>
```

Inheritance diagram for mln::fun::p2b::antilogy:



10.141.1 Detailed Description

A [p2b](#) function always returning `false`. A simpler name would be ‘`false`’, but this is not a valid C++ identifier, as `false` is a keyword of the language.


Definition at line 50 of file `antilogy.hh`.

10.142 mln::fun::p2b::tautology Struct Reference

A [p2b](#) function always returning `true`.

```
#include <tautology.hh>
```

Inheritance diagram for mln::fun::p2b::tautology:



10.142.1 Detailed Description

A `p2b` function always returning `true`. A simpler name would be ‘`true`’, but this is not a valid C++ identifier, as `true` is a keyword of the language.


Definition at line 50 of file `tautology.hh`.

10.143 mln::fun::v2b::lnot< V > Struct Template Reference

Functor computing logical-not on a value.

```
#include <lnot.hh>
```

Inheritance diagram for mln::fun::v2b::lnot< V >:



10.143.1 Detailed Description

```
template<typename V> struct mln::fun::v2b::lnot< V >
```

Functor computing logical-not on a value.


Definition at line 47 of file lnot.hh.

10.144 mln::fun::v2b::threshold< V > Struct Template Reference

Threshold function.

```
#include <threshold.hh>
```

Inheritance diagram for mln::fun::v2b::threshold< V >:



10.144.1 Detailed Description

```
template<typename V> struct mln::fun::v2b::threshold< V >
```

Threshold function. $f(v) = (v \geq \text{threshold})$.


Definition at line 48 of file fun/v2b/threshold.hh.

10.145 mln::fun::v2v::ch_function_value< F, V > Class Template Reference

Wrap a function [v2v](#) and convert its result to another type.

```
#include <ch_function_value.hh>
```

Inheritance diagram for mln::fun::v2v::ch_function_value< F, V >:



10.145.1 Detailed Description

```
template<typename F, typename V> class mln::fun::v2v::ch_function_value< F, V >
```

Wrap a function [v2v](#) and convert its result to another type.


Definition at line 52 of file fun/v2v/ch_function_value.hh.

10.146 `mln::fun::v2v::component< T, i >` Struct Template Reference

Functor that accesses the i-th component of a value.

```
#include <component.hh>
```

Inheritance diagram for `mln::fun::v2v::component< T, i >`:



10.146.1 Detailed Description

```
template<typename T, unsigned i> struct mln::fun::v2v::component< T, i >
```

Functor that accesses the i-th component of a value.


Definition at line 51 of file component.hh.

10.147 `mln::fun::v2v::l1_norm< V, R >` Struct Template Reference

L1-norm.

```
#include <norm.hh>
```

Inheritance diagram for mln::fun::v2v::l1_norm< V, R >:



10.147.1 Detailed Description

```
template<typename V, typename R> struct mln::fun::v2v::l1_norm< V, R >
```

L1-norm. V is the type of input values; R is the result type.

See also

[mln::norm::l1](#).


Definition at line 57 of file v2v/norm.hh.

10.148 mln::fun::v2v::l2_norm< V, R > Struct Template Reference

L2-norm.

```
#include <norm.hh>
```

Inheritance diagram for mln::fun::v2v::l2_norm< V, R >:



10.148.1 Detailed Description

```
template<typename V, typename R> struct mln::fun::v2v::l2_norm< V, R >
```

L2-norm. V is the type of input values; R is the result type.

See also

[mln::norm::l2](#).


Definition at line 69 of file v2v/norm.hh.

10.149 mln::fun::v2v::linear< V, T, R > Struct Template Reference

Linear function. $f(v) = a * v + b$. V is the type of input values; T is the type used to compute the result; R is the result type.

```
#include <linear.hh>
```

Inheritance diagram for mln::fun::v2v::linear< V, T, R >:



10.149.1 Detailed Description

```
template<typename V, typename T = V, typename R = T> struct mln::fun::v2v::linear< V, T, R >
```

Linear function. $f(v) = a * v + b$. V is the type of input values; T is the type used to compute the result; R is the result type. By default, T is V and R is T .


Definition at line 55 of file v2v/linear.hh.

10.150 mln::fun::v2v::linfty_norm< V, R > Struct Template Reference

L-infty norm.

```
#include <norm.hh>
```

Inheritance diagram for `mln::fun::v2v::linsky_norm< V, R >`:



10.150.1 Detailed Description

`template<typename V, typename R> struct mln::fun::v2v::linsky_norm< V, R >`

L-infty norm. V is the type of input values; R is the result type.

See also

[mln::norm::linsky](#).


Definition at line 81 of file v2v/norm.hh.

10.151 mln::fun::v2v::rgb8_to_rgn< n > Struct Template Reference

Convert a rgb8 value to a rgn, $n < 8$.

```
#include <rgb8_to_rgn.hh>
```

Inheritance diagram for mln::fun::v2v::rgb8_to_rgn< n >:



Public Member Functions

- `result operator() (const argument &c) const`

Convert a rg8 value to a rgn, n < 8.

10.151.1 Detailed Description

`template<unsigned n> struct mln::fun::v2v::rgb8_to_rgn< n >`

Convert a rg8 value to a rgn, n < 8.

Parameters

- `n` defines the output quantification used for the transformation.

Definition at line 56 of file `rgb8_to_rgn.h`.

10.151.2 Member Function Documentation

10.151.2.1 template<unsigned n> rgb8_to_rgn<n>::result mln::fun::v2v::rgb8_to_rgn<n>::operator() (const argument & c) const

Convert a rg8 value to a rgn, n < 8.

Parameters

[in] *v* the rg8 value to convert.

Conversion is done by computing the size by which we divide each rg component.

Parameters

n defines the output quantification used for the transformation.

Definition at line 83 of file rg8_to_rgn.hh.


References mln::value::rgb<n>::red().

10.152 mln::fun::v2w2v::cos< V > Struct Template Reference

Cosinus bijective functor.

```
#include <cos.hh>
```

Inheritance diagram for mln::fun::v2w2v::cos< V >:



10.152.1 Detailed Description

```
template<typename V> struct mln::fun::v2w2v::cos< V >
```

Cosinus bijective functor. V is the type of input values and the result type.

See also

[mln::math::cos](#).


Definition at line 59 of file [fun/v2w2v/cos.hh](#).

10.153 mln::fun::v2w_w2v::l1_norm< V, R > Struct Template Reference

L1-norm.

```
#include <norm.hh>
```

Inheritance diagram for mln::fun::v2w_w2v::l1_norm< V, R >:



10.153.1 Detailed Description

```
template<typename V, typename R> struct mln::fun::v2w_w2v::l1_norm< V, R >
```

L1-norm. V is the type of input values; R is the result type.

See also

[mln::norm::l1](#).


Definition at line 56 of file v2w_w2v/norm.hh.

10.154 mln::fun::v2w_w2v::l2_norm< V, R > Struct Template Reference

L2-norm.

```
#include <norm.hh>
```

Inheritance diagram for mln::fun::v2w_w2v::l2_norm< V, R >:



10.154.1 Detailed Description

```
template<typename V, typename R> struct mln::fun::v2w_w2v::l2_norm< V, R >
```

L2-norm. V is the type of input values; R is the result type.

See also

[mln::norm::l2](#).


Definition at line 69 of file v2w_w2v/norm.hh.

10.155 mln::fun::v2w_w2v::lfinity_norm< V, R > Struct Template Reference

L-infty norm.

```
#include <norm.hh>
```

Inheritance diagram for mln::fun::v2w_w2v::lfinity_norm< V, R >:



10.155.1 Detailed Description

```
template<typename V, typename R> struct mln::fun::v2w_w2v::lfinity_norm< V, R >
```

L-infty norm. V is the type of input values; R is the result type.

See also

[mln::norm::lfinity](#).


Definition at line 82 of file v2w_w2v/norm.hh.

10.156 mln::fun::vv2b::eq< L, R > Struct Template Reference

Functor computing equal between two values.

```
#include <eq.hh>
```

Inheritance diagram for mln::fun::vv2b::eq< L, R >:



10.156.1 Detailed Description

```
template<typename L, typename R = L> struct mln::fun::vv2b::eq< L, R >
```

Functor computing equal between two values.


Definition at line 48 of file fun/vv2b(eq.hh).

10.157 mln::fun::vv2b::ge< L, R > Struct Template Reference

Functor computing "greater or equal than" between two values.

```
#include <ge.hh>
```

Inheritance diagram for mln::fun::vv2b::ge< L, R >:



10.157.1 Detailed Description

```
template<typename L, typename R = L> struct mln::fun::vv2b::ge< L, R >
```

Functor computing "greater or equal than" between two values.


Definition at line 48 of file ge.hh.

10.158 mln::fun::vv2b::gt< L, R > Struct Template Reference

Functor computing "greater than" between two values.

```
#include <gt.hh>
```

Inheritance diagram for mln::fun::vv2b::gt< L, R >:



10.158.1 Detailed Description

```
template<typename L, typename R = L> struct mln::fun::vv2b::gt< L, R >
```

Functor computing "greater than" between two values.


Definition at line 48 of file gt.hh.

10.159 mln::fun::vv2b::implies< L, R > Struct Template Reference

Functor computing logical-implies between two values.

```
#include <implies.hh>
```

Inheritance diagram for `mln::fun::vv2b::implies< L, R >`:



10.159.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2b::implies< L, R >`

Functor computing logical-implies between two values.


Definition at line 48 of file `implies.hh`.

10.160 mln::fun::vv2b::le< L, R > Struct Template Reference

Functor computing "lower or equal than" between two values.

`#include <le.hh>`

Inheritance diagram for mln::fun::vv2b::le< L, R >:



10.160.1 Detailed Description

```
template<typename L, typename R = L> struct mln::fun::vv2b::le< L, R >
```

Functor computing "lower or equal than" between two values.


Definition at line 48 of file le.hh.

10.161 mln::fun::vv2b::lt< L, R > Struct Template Reference

Functor computing "lower than" between two values.

```
#include <lt.hh>
```

Inheritance diagram for `mln::fun::vv2b::lt< L, R >`:



10.161.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2b::lt< L, R >`

Functor computing "lower than" between two values.


Definition at line 48 of file `lt.hh`.

10.162 mln::fun::vv2v::diff_abs< V > Struct Template Reference

A functor computing the diff_absimum of two values.

```
#include <diff_abs.hh>
```

Inheritance diagram for mln::fun::vv2v::diff_abs< V >:



10.162.1 Detailed Description

`template<typename V> struct mln::fun::vv2v::diff_abs< V >`

A functor computing the diff_absimum of two values.


Definition at line 50 of file `fun/vv2v/diff_abs.hh`.

10.163 mln::fun::vv2v::land< L, R > Struct Template Reference

Functor computing logical-and between two values.

```
#include <land.hh>
```

Inheritance diagram for `mln::fun::vv2v::land< L, R >`:



10.163.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2v::land< L, R >`

Functor computing logical-and between two values.


Definition at line 48 of file `fun/vv2v/land.hh`.

10.164 `mln::fun::vv2v::land_not< L, R >` Struct Template Reference

Functor computing logical and-not between two values.

```
#include <land_not.hh>
```

Inheritance diagram for mln::fun::vv2v::land_not< L, R >:



10.164.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2v::land_not< L, R >`

Functor computing logical and-not between two values.


Definition at line 49 of file `land_not.hh`.

10.165 mln::fun::vv2v::lor< L, R > Struct Template Reference

Functor computing logical-or between two values.

```
#include <l(or.hh>
```

Inheritance diagram for `mln::fun::vv2v::lor< L, R >`:



10.165.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2v::lor< L, R >`

Functor computing logical-or between two values.


Definition at line 48 of file `fun/vv2v/lor.hh`.

10.166 mln::fun::vv2v::lxor< L, R > Struct Template Reference

Functor computing logical-xor between two values.

`#include <lxor.hh>`

Inheritance diagram for mln::fun::vv2v::lxor< L, R >:



10.166.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2v::lxor< L, R >`

Functor computing logical-xor between two values.


Definition at line 48 of file `lxor.hh`.

10.167 mln::fun::vv2v::max< V > Struct Template Reference

A functor computing the maximum of two values.

```
#include <max.hh>
```

Inheritance diagram for `mln::fun::vv2v::max< V >`:



10.167.1 Detailed Description

`template<typename V> struct mln::fun::vv2v::max< V >`

A functor computing the maximum of two values.


Definition at line 49 of file `fun/vv2v/max.hh`.

10.168 mln::fun::vv2v::min< L, R > Struct Template Reference

A functor computing the minimum of two values.

```
#include <min.hh>
```

Inheritance diagram for mln::fun::vv2v::min< L, R >:



10.168.1 Detailed Description

`template<typename L, typename R = L> struct mln::fun::vv2v::min< L, R >`

A functor computing the minimum of two values.


Definition at line 50 of file `fun/vv2v/min.hh`.

10.169 mln::fun::vv2v::vec< V > Struct Template Reference

A functor computing the vecimum of two values.

```
#include <vec.hh>
```

Inheritance diagram for `mln::fun::vv2v::vec< V >`:



10.169.1 Detailed Description

`template<typename V> struct mln::fun::vv2v::vec< V >`

A functor computing the vecimum of two values.

Definition at line 50 of file `fun/vv2v/vec.hh`.

10.170 mln::fun::x2p::closest_point< P > Struct Template Reference

FIXME: doxygen + concept checking.

```
#include <closest_point.hh>
```

10.170.1 Detailed Description

template<typename P> struct mln::fun::x2p::closest_point< P >

FIXME: doxygen + concept checking.


Definition at line 45 of file closest_point.hh.

10.171 mln::fun::x2v::bilinear< I > Struct Template Reference

Represent a bilinear interpolation of values from an underlying image.

#include <bilinear.hh>

Inheritance diagram for mln::fun::x2v::bilinear< I >:



Public Member Functions

- template<typename T >
I::value **operator()** (const algebra::vec< 3, T > &v) const
Bilinear filtering on 3d images. Work on slices.

- template<typename T >
I::value **operator()** (const algebra::vec< 2, T > &v) const
Bilinear filtering on 2d images.

10.171.1 Detailed Description

template<typename I> struct mln::fun::x2v::bilinear< I >

Represent a bilinear interpolation of values from an underlying image.

Definition at line 52 of file bilinear.hh.

10.171.2 Member Function Documentation

10.171.2.1 template<typename I > template<typename T > I::value mln::fun::x2v::bilinear< I >::operator() (const algebra::vec< 2, T > & v) const

Bilinear filtering on 2d images.

Definition at line 86 of file bilinear.hh.

10.171.2.2 template<typename I> template<typename T> I::value mln::fun::x2v::bilinear< I >::operator() (const algebra::vec< 3, T > & v) const

Bilinear filtering on 3d images. Work on slices.


Definition at line 132 of file bilinear.hh.

10.172 mln::fun::x2v::trilinear< I > Struct Template Reference

Represent a trilinear interpolation of values from an underlying image.

```
#include <trilinear.hh>
```

Inheritance diagram for mln::fun::x2v::trilinear< I >:



10.172.1 Detailed Description

template<typename I> struct mln::fun::x2v::trilinear< I >

Represent a trilinear interpolation of values from an underlying image.

Definition at line 53 of file trilinear.hh.

10.173 mln::fun::x2x::composed< T2, T1 > Struct Template Reference

Represent a composition of two transformations.

```
#include <composed.hh>
```

Public Member Functions

- **composed ()**
Constructor without argument.
- **composed (const T2 &f, const T1 &g)**
Constructor with the two transformation to be composed.

10.173.1 Detailed Description

template<typename T2, typename T1> struct mln::fun::x2x::composed< T2, T1 >

Represent a composition of two transformations.

Definition at line 144 of file composed.hh.

10.173.2 Constructor & Destructor Documentation

10.173.2.1 template<typename T2, typename T1> mln::fun::x2x::composed< T2, T1 >::composed () [inline]

Constructor without argument.

Definition at line 153 of file composed.hh.

10.173.2.2 template<typename T2, typename T1> mln::fun::x2x::composed< T2, T1 >::composed (const T2 & f, const T1 & g) [inline]

Constructor with the two transformation to be composed.


Definition at line 156 of file composed.hh.

10.174 mln::fun::x2x::linear< I > Struct Template Reference

Represent a linear interpolation of values from an underlying image.

```
#include <linear.hh>
```

Inheritance diagram for mln::fun::x2x::linear< I >:



Public Member Functions

- **linear (const I &ima)**

Constructor with the underlying image.

- **template<typename C >**

I::value **operator()** (const algebra::vec< 1, C > &v) const

Return the interpolated value in the underlying image at the given 'point' v.

Public Attributes

- **const I & ima**

Underlying image.

10.174.1 Detailed Description

template<typename I> struct mln::fun::x2x::linear< I >

Represent a linear interpolation of values from an underlying image.

Definition at line 53 of file x2v/linear.hh.

10.174.2 Constructor & Destructor Documentation

10.174.2.1 template<typename I > mln::fun::x2x::linear< I >::linear (const I & ima)

Constructor with the underlying image.

Definition at line 77 of file x2v/linear.hh.

10.174.3 Member Function Documentation

10.174.3.1 template<typename I > template<typename C > I::value mln::fun::x2x::linear< I >::operator() (const algebra::vec< 1, C > & v) const

Return the interpolated value in the underlying image at the given 'point' v.

Definition at line 85 of file x2v/linear.hh.

10.174.4 Member Data Documentation

10.174.4.1 template<typename I > const I& mln::fun::x2x::linear< I >::ima

Underlying image.


Definition at line 70 of file x2v/linear.hh.

10.175 mln::fun::x2x::rotation< n, C > Struct Template Reference

Represent a rotation function.

```
#include <rotation.hh>
```

Inheritance diagram for mln::fun::x2x::rotation< n, C >:



Public Types

- **typedef C `data_t`**
Type of the underlying data stored in vectors and matrices.
- **typedef `rotation< n, C > invert`**
Type of the inverse function.

Public Member Functions

- **`invert inv () const`**
Return the inverse function.
- **`algebra::vec< n, C > operator() (const algebra::vec< n, C > &v) const`**
Perform the rotation of the given vector.

- **rotation ()**
Constructor without argument.
- **rotation (const algebra::quat &q)**
Constructor with quaternion.
- **rotation (const algebra::h_mat< n, C > &m)**
Constructor with h_mat.
- **rotation (C alpha, const algebra::vec< n, C > &axis)**
Constructor with radian alpha and a facultative direction (rotation axis).
- **void set_alpha (C alpha)**
Set a new grade alpha.
- **void set_axis (const algebra::vec< n, C > &axis)**
Set a new rotation axis.

10.175.1 Detailed Description

template<unsigned n, typename C> struct mln::fun::x2x::rotation< n, C >

Represent a rotation function.

Definition at line 147 of file rotation.hh.

10.175.2 Member Typedef Documentation

10.175.2.1 template<unsigned n, typename C> typedef C mln::fun::x2x::rotation< n, C >::data_t

Type of the underlying data stored in vectors and matrices.

Definition at line 152 of file rotation.hh.

10.175.2.2 template<unsigned n, typename C> typedef rotation<n,C> mln::fun::x2x::rotation< n, C >::invert

Type of the inverse function.

Definition at line 155 of file rotation.hh.

10.175.3 Constructor & Destructor Documentation

10.175.3.1 template<unsigned n, typename C> mln::fun::x2x::rotation< n, C >::rotation () [inline]

Constructor without argument.

Definition at line 192 of file rotation.hh.

10.175.3.2 template<unsigned n, typename C> mln::fun::x2x::rotation< n, C >::rotation (*C alpha, const algebra::vec< n, C > & axis*) [inline]

Constructor with radian alpha and a facultative direction (rotation axis).

Definition at line 198 of file rotation.hh.

10.175.3.3 template<unsigned n, typename C> mln::fun::x2x::rotation< n, C >::rotation (*const algebra::quat & q*) [inline]

Constructor with quaternion.

Definition at line 208 of file rotation.hh.

References mln::make::h_mat().

10.175.3.4 template<unsigned n, typename C> mln::fun::x2x::rotation< n, C >::rotation (*const algebra::h_mat< n, C > & m*) [inline]

Constructor with h_mat.

Definition at line 238 of file rotation.hh.

10.175.4 Member Function Documentation

10.175.4.1 template<unsigned n, typename C> rotation< n, C > mln::fun::x2x::rotation< n, C >::inv () const [inline]

Return the inverse function.

Definition at line 265 of file rotation.hh.

10.175.4.2 template<unsigned n, typename C> algebra::vec< n, C > mln::fun::x2x::rotation< n, C >::operator() (*const algebra::vec< n, C > & v*) const [inline]

Perform the rotation of the given vector.

Definition at line 247 of file rotation.hh.

10.175.4.3 template<unsigned n, typename C> void mln::fun::x2x::rotation< n, C >::set_alpha (*C alpha*) [inline]

Set a new grade alpha.

Definition at line 274 of file rotation.hh.

10.175.4.4 template<unsigned n, typename C> void mln::fun::x2x::rotation< n, C >::set_axis (*const algebra::vec< n, C > & axis*) [inline]

Set a new rotation axis.


Definition at line 283 of file rotation.hh.

10.176 mln::fun::x2x::translation< n, C > Struct Template Reference

Translation function-object.

```
#include <translation.hh>
```

Inheritance diagram for mln::fun::x2x::translation< n, C >:



Public Types

- **typedef C `data_t`**
Type of the underlying data stored in vectors and matrices.
- **typedef `translation< n, C > invert`**
Type of the inverse function.

Public Member Functions

- **`invert inv () const`**

Return the inverse function.

- algebra::vec< n, C > **operator()** (const algebra::vec< n, C > &v) const

Perform the translation of the given vector.

- void **set_t** (const algebra::vec< n, C > &t)

Set a net translation vector.

- const algebra::vec< n, C > & **t** () const

Return the translation vector.

- **translation** (const algebra::vec< n, C > &t)

Constructor with the translation vector.

- **translation** ()

Constructor without argument.

10.176.1 Detailed Description

template<unsigned n, typename C> struct mln::fun::x2x::translation< n, C >

Translation function-object.

Definition at line 52 of file x2x/translation.hh.

10.176.2 Member Typedef Documentation

10.176.2.1 template<unsigned n, typename C> typedef C mln::fun::x2x::translation< n, C >::data_t

Type of the underlying data stored in vectors and matrices.

Definition at line 59 of file x2x/translation.hh.

10.176.2.2 template<unsigned n, typename C> typedef translation<n,C> mln::fun::x2x::translation< n, C >::invert

Type of the inverse function.

Definition at line 62 of file x2x/translation.hh.

10.176.3 Constructor & Destructor Documentation

10.176.3.1 template<unsigned n, typename C> mln::fun::x2x::translation< n, C >::translation () [inline]

Constructor without argument.

Definition at line 93 of file x2x/translation.hh.

10.176.3.2 template<unsigned n, typename C> mln::fun::x2x::translation<n, C>::translation (const algebra::vec<n, C> & t) [inline]

Constructor with the translation vector.

Definition at line 99 of file x2x/translation.hh.

10.176.4 Member Function Documentation

10.176.4.1 template<unsigned n, typename C> translation<n, C> mln::fun::x2x::translation<n, C>::inv () const [inline]

Return the inverse function.

Definition at line 124 of file x2x/translation.hh.

10.176.4.2 template<unsigned n, typename C> algebra::vec<n, C> mln::fun::x2x::translation<n, C>::operator() (const algebra::vec<n, C> & v) const [inline]

Perform the translation of the given vector.

Definition at line 108 of file x2x/translation.hh.

10.176.4.3 template<unsigned n, typename C> void mln::fun::x2x::translation<n, C>::set_t (const algebra::vec<n, C> & t) [inline]

Set a net translation vector.

Definition at line 134 of file x2x/translation.hh.

10.176.4.4 template<unsigned n, typename C> const algebra::vec<n, C> & mln::fun::x2x::translation<n, C>::t () const [inline]

Return the translation vector.

Definition at line 143 of file x2x/translation.hh.

10.177 mln::fun_image< F, I > Struct Template Reference

[Image](#) read through a function.

```
#include <fun_image.hh>
```

Inherits image_value_morpher< I, F::result, fun_image< F, I > >.

Public Types

- **typedef F::result lvalue**
Return type of read-write access.
- **typedef F::result rvalue**

Return type of read-only access.

- **typedef fun_image< tag::value_< typename F::result >, tag::image_< I > > skeleton**
Skeleton.
- **typedef F::result value**
Value associated type.

Public Member Functions

- **fun_image ()**
Constructor.
- **fun_image (const Function_v2v< F > &f, const Image< I > &ima)**
Constructor.
- **fun_image (const Image< I > &ima)**
Constructor.
- **F::result operator() (const typename I::psite &p) const**
Read-only access of pixel value at point site p.
- **F::result operator() (const typename I::psite &p)**
Mutable access is for reading only.

10.177.1 Detailed Description

template<typename F, typename I> struct mln::fun_image< F, I >

Image read through a function.

Definition at line 101 of file fun_image.hh.

10.177.2 Member Typedef Documentation

10.177.2.1 template<typename F, typename I> typedef F ::result mln::fun_image< F, I >::lvalue

Return type of read-write access.

Definition at line 111 of file fun_image.hh.

10.177.2.2 template<typename F, typename I> typedef F ::result mln::fun_image< F, I >::rvalue

Return type of read-only access.

Definition at line 108 of file fun_image.hh.

10.177.2.3 template<typename F, typename I> typedef fun_image< tag::value_<typename F :::result>, tag::image_<I> > mln::fun_image< F, I >::skeleton

Skeleton.

Definition at line 115 of file fun_image.hh.

10.177.2.4 template<typename F, typename I> typedef F :::result mln::fun_image< F, I >::value

Value associated type.

Definition at line 105 of file fun_image.hh.

10.177.3 Constructor & Destructor Documentation

10.177.3.1 template<typename F , typename I > mln::fun_image< F, I >::fun_image () [inline]

Constructor.

Definition at line 177 of file fun_image.hh.

10.177.3.2 template<typename F , typename I > mln::fun_image< F, I >::fun_image (const Function_v2v< F > & f, const Image< I > & ima) [inline]

Constructor.

Definition at line 184 of file fun_image.hh.

10.177.3.3 template<typename F , typename I > mln::fun_image< F, I >::fun_image (const Image< I > & ima) [inline]

Constructor.

Definition at line 191 of file fun_image.hh.

10.177.4 Member Function Documentation

10.177.4.1 template<typename F , typename I > F::result mln::fun_image< F, I >::operator0 (const typename I::psite & p) const [inline]

Read-only access of pixel value at point site *p*.

Definition at line 209 of file fun_image.hh.

10.177.4.2 template<typename F , typename I > F::result mln::fun_image< F, I >::operator0 (const typename I::psite & p) [inline]

Mutable access is for reading only.

Definition at line 218 of file fun_image.hh.

10.178 mln::Function< E > Struct Template Reference

Base class for implementation of function-objects.

```
#include <function.hh>
```

Inherits [mln::Object< E >](#).

Inherited by [mln::Function_n2v< E >](#), [mln::Function_v2v< E >](#), [mln::Function_vv2b< E >](#), and [mln::Function_vv2v< E >](#).

Protected Member Functions

- [Function \(\)](#)

An operator() has to be provided.

10.178.1 Detailed Description

```
template<typename E> struct mln::Function< E >
```

Base class for implementation of function-objects. The parameter *E* is the exact type.

Definition at line 64 of file function.hh.

10.178.2 Constructor & Destructor Documentation

10.178.2.1 template<typename E > mln::Function< E >::Function () [inline, protected]

An operator() has to be provided.

Its signature depends on the particular function-object one considers.

Definition at line 219 of file function.hh.

10.179 mln::Function< void > Struct Template Reference

[Function](#) category flag type.

```
#include <function.hh>
```

10.179.1 Detailed Description

```
template<> struct mln::Function< void >
```

[Function](#) category flag type.


Definition at line 51 of file function.hh.

10.180 mln::Function_n2v< E > Struct Template Reference

Base class for implementation of function-objects from Nil to value.

```
#include <function.hh>
```

Inheritance diagram for mln::Function_n2v< E >:



10.180.1 Detailed Description

```
template<typename E> struct mln::Function_n2v< E >
```

Base class for implementation of function-objects from Nil to value. The parameter *E* is the exact type.


Definition at line 99 of file function.hh.

10.181 mln::Function_v2b< E > Struct Template Reference

Base class for implementation of function-objects from a value to a Boolean.

```
#include <function.hh>
```

Inheritance diagram for mln::Function_v2b< E >:



10.181.1 Detailed Description

template<typename E> struct mln::Function_v2b< E >

Base class for implementation of function-objects from a value to a Boolean. The parameter *E* is the exact type.

Definition at line 150 of file function.hh.

10.182 mln::Function_v2v< E > Struct Template Reference

Base class for implementation of function-objects from value to value.

```
#include <function.hh>
```

Inherits [mln::Function< E >](#).

Inherited by [mln::fun::C< R\(*\)\(A\)>](#), [mln::fun::v2v::dec< T >](#), [mln::fun::v2v::id< T >](#), [mln::fun::v2v::inc< T >](#), [mln::fun::x2v::bilinear< I >](#), [mln::fun::x2v::trilinear< I >](#), [mln::fun::x2x::internal::helper_composed< T2, T1, E, false >](#), [mln::fun::x2x::internal::helper_composed< T2, T1, E, true >](#), [mln::fun::x2x::linear< I >](#), [mln::fun::x2x::neighbor< I >](#), and [mln::Function_v2b< E > \[virtual\]](#).

10.182.1 Detailed Description

```
template<typename E> struct mln::Function_v2v< E >
```


Base class for implementation of function-objects from value to value. The parameter E is the exact type.
Definition at line 124 of file function.hh.

10.183 mln::Function_vv2b< E > Struct Template Reference

Base class for implementation of function-objects from a couple of values to a Boolean.

```
#include <function.hh>
```

Inheritance diagram for mln::Function_vv2b< E >:



10.183.1 Detailed Description

```
template<typename E> struct mln::Function_vv2b< E >
```

Base class for implementation of function-objects from a couple of values to a Boolean. The parameter E is the exact type.


Definition at line 202 of file function.hh.

10.184 mln::Function_vv2v< E > Struct Template Reference

Base class for implementation of function-objects from a couple of values to a value.

```
#include <function.hh>
```

Inheritance diagram for mln::Function_vv2v< E >:



10.184.1 Detailed Description

template<typename E> struct mln::Function_vv2v< E >

Base class for implementation of function-objects from a couple of values to a value. The parameter *E* is the exact type.

Definition at line 177 of file function.hh.

10.185 mln::fwd_pixter1d< I > Class Template Reference

Forward pixel iterator on a 1-D image with border.

```
#include <pixter1d.hh>
```

Inherits forward_pixel_iterator_base_< I, fwd_pixter1d< I > >.

Public Types

- **typedef I image**

Image type.

Public Member Functions

- **fwd_pixter1d (I &image)**

Constructor.

- **void next ()**

Go to the next element.

10.185.1 Detailed Description

`template<typename I> class mln::fwd_pixter1d< I >`

Forward pixel iterator on a 1-D image with border.

Definition at line 45 of file pixter1d.hh.

10.185.2 Member Typedef Documentation

10.185.2.1 template<typename I> typedef I mln::fwd_pixter1d< I >::image

[Image](#) type.

Definition at line 52 of file pixter1d.hh.

10.185.3 Constructor & Destructor Documentation

**10.185.3.1 template<typename I> mln::fwd_pixter1d< I >::fwd_pixter1d (I & *image*)
[inline]**

Constructor.

Parameters

[in] *image* The image this pixel iterator is bound to.

Definition at line 96 of file pixter1d.hh.

10.185.4 Member Function Documentation

10.185.4.1 void mln::Iterator< fwd_pixter1d< I > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.186 mln::fwd_pixter2d< I > Class Template Reference

Forward pixel iterator on a 2-D image with border.

```
#include <pixter2d.hh>
Inherits forward_pixel_iterator_base_< I, fwd_pixter2d< I > >.
```

Public Types

- **typedef I image**
Image type.

Public Member Functions

- **fwd_pixter2d (I &image)**
Constructor.
- **void next ()**
Go to the next element.

10.186.1 Detailed Description

template<typename I> class mln::fwd_pixter2d< I >

Forward pixel iterator on a 2-D image with border.

Definition at line 47 of file pixter2d.hh.

10.186.2 Member Typedef Documentation

10.186.2.1 template<typename I > typedef I mln::fwd_pixter2d< I >::image

Image type.

Definition at line 54 of file pixter2d.hh.

10.186.3 Constructor & Destructor Documentation

10.186.3.1 template<typename I > mln::fwd_pixter2d< I >::fwd_pixter2d (I & *image*) [inline]

Constructor.

Parameters

[in] *image* The image this pixel iterator is bound to.

Definition at line 130 of file pixter2d.hh.

10.186.4 Member Function Documentation

10.186.4.1 void mln::Iterator< fwd_pixter2d< I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.187 mln::fwd_pixter3d< I > Class Template Reference

Forward pixel iterator on a 3-D image with border.

```
#include <pixter3d.hh>
```

Inherits forward_pixel_iterator_base_< I, fwd_pixter3d< I > >.

Public Types

- `typedef I image`

Image type.

Public Member Functions

- `fwd_pixter3d (I &image)`

Constructor.

- `void next ()`

Go to the next element.

10.187.1 Detailed Description

```
template<typename I> class mln::fwd_pixter3d< I >
```

Forward pixel iterator on a 3-D image with border.

Definition at line 48 of file pixter3d.hh.

10.187.2 Member Typedef Documentation

10.187.2.1 template<typename I > typedef I mln::fwd_pixter3d< I >::image

Image type.

Definition at line 55 of file pixter3d.hh.

10.187.3 Constructor & Destructor Documentation

10.187.3.1 template<typename I> mln::fwd_pixter3d< I >::fwd_pixter3d (I & *image*) [inline]

Constructor.

Parameters

[in] *image* The image this pixel iterator is bound to.

Definition at line 154 of file pixter3d.hh.

10.187.4 Member Function Documentation

10.187.4.1 void mln::Iterator< fwd_pixter3d< I > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition


The iterator is valid.

10.188 mln::Gdpoint< E > Struct Template Reference

FIXME: Doc!

```
#include <gdpoint.hh>
```

Inheritance diagram for mln::Gdpoint< E >:



10.188.1 Detailed Description

`template<typename E> struct mln::Gdpoint< E >`

FIXME: Doc!

Definition at line 95 of file gdpoint.hh.

10.189 mln::Gdpoint< void > Struct Template Reference

Delta point site category flag type.

`#include <gdpoint.hh>`

10.189.1 Detailed Description

`template<> struct mln::Gdpoint< void >`

Delta point site category flag type.

Definition at line 87 of file gdpoint.hh.

10.190 `mln::geom::complex_geometry< D, P >` Class Template Reference

A functor returning the sites of the faces of a complex where the locations of each 0-face is stored.

```
#include <complex_geometry.hh>
```

Public Member Functions

- `unsigned add_location (const P &p)`
Populate the set of locations.
- `complex_geometry ()`
Build a complex geometry object.
- `site operator() (const mln::topo::face< D > &f) const`
Retrieve the site associated to f.

10.190.1 Detailed Description

```
template<unsigned D, typename P> class mln::geom::complex_geometry< D, P >
```

A functor returning the sites of the faces of a complex where the locations of each 0-face is stored. Faces of higher dimensions are computed.

Template Parameters

D The dimension of the complex.

P The type of the location of a 0-face.

Locations of 0-face are usually points (hence the P above), but can possibly be any (default-constructible) values.

The functor returns a std::vector of locations: 0-faces are singletons, 1-faces are (usually) pairs, faces of higher dimensions are arrays of locations.

Note that for consistency reasons w.r.t. the return type of operator(), returned sites are always *arrays* of locations attached to 0-faces; hence the returned singletons (of locations) for 0-faces.

Definition at line 88 of file geom/complex_geometry.hh.

10.190.2 Constructor & Destructor Documentation

```
10.190.2.1 template<unsigned D, typename P> mln::geom::complex_geometry< D, P >::complex_geometry( ) [inline]
```

Build a complex geometry object.

Definition at line 132 of file geom/complex_geometry.hh.

10.190.3 Member Function Documentation

10.190.3.1 template<unsigned D, typename P> unsigned mln::geom::complex_geometry< D, P >::add_location(const P & p) [inline]

Populate the set of locations.

Append a new location *p*. Return the index of the newly created location (which should semantically match the id of the corresponding 0-face in the complex).

Definition at line 140 of file geom/complex_geometry.hh.

10.190.3.2 template<unsigned D, typename P> util::multi_site< P > mln::geom::complex_geometry< D, P >::operator() (const mln::topo::face< D > & f) const [inline]

Retrieve the site associated to *f*.

Definition at line 151 of file geom/complex_geometry.hh.


References mln::topo::face< D >::face_id(), and mln::topo::face< D >::n().

10.191 mln::Gpoint< E > Struct Template Reference

Base class for implementation of point classes.

```
#include <gpoint.hh>
```

Inheritance diagram for mln::Gpoint< E >:



Related Functions

(Note that these are not member functions.)

- template<typename P , typename D >
`P operator+ (const Gpoint< P > &p, const Gdpoint< D > &dp)`
Add a delta-point rhs to a grid point lhs.
- template<typename P , typename D >
`P & operator+= (Gpoint< P > &p, const Gdpoint< D > &dp)`
Shift a point by a delta-point dp.
- template<typename L , typename R >
`L::delta operator- (const Gpoint< L > &lhs, const Gpoint< R > &rhs)`
Difference between a couple of grid point lhs and rhs.
- template<typename P , typename D >
`P & operator-= (Gpoint< P > &p, const Gdpoint< D > &dp)`

Shift a point by the negate of a delta-point dp .

- template<typename P , typename D >
P **operator/** (const Gpoint< P > &p, const value::scalar_< D > &dp)

Divide a point by a scalar s .

- template<typename P >
std::ostream & **operator<<** (std::ostream &ostr, const Gpoint< P > &p)

Print a grid point p into the output stream $ostr$.

- template<typename L , typename R >
bool **operator==** (const Gpoint< L > &lhs, const Gpoint< R > &rhs)

Equality comparison between a couple of grid point lhs and rhs .

10.191.1 Detailed Description

template<typename E> struct mln::Gpoint< E >

Base class for implementation of point classes. A point is an element of a space.

For instance, **mln::point2d** is the type of elements defined on the discrete square grid of the 2D plane.

Definition at line 115 of file gpoint.hh.

10.191.2 Friends And Related Function Documentation

10.191.2.1 template<typename P , typename D > P operator+ (const Gpoint< P > & p, const Gdpoint< D > & dp) [related]

Add a delta-point rhs to a grid point lhs .

Parameters

[in] **p** A grid point.

[in] **dp** A delta-point.

The type of dp has to compatible with the type of p .

Returns

A point (temporary object).

See also

mln::Gdpoint

Definition at line 385 of file gpoint.hh.

10.191.2.2 template<typename P , typename D > P & operator+=(Gpoint< P > & p, const Gdpoint< D > & dp) [related]

Shift a point by a delta-point dp.

Parameters

- [in, out] *p* The targeted point.
- [in] *dp* A delta-point.

Returns

A reference to the point *p* once translated by *dp*.

Precondition

The type of *dp* has to be compatible with the type of *p*.

Definition at line 428 of file gpoint.hh.

10.191.2.3 template<typename L , typename R > L::delta operator- (const Gpoint< L > & lhs, const Gpoint< R > & rhs) [related]

Difference between a couple of grid point *lhs* and *rhs*.

Parameters

- [in] *lhs* A first grid point.
- [in] *rhs* A second grid point.

Warning

There is no type promotion in Milena so the client has to make sure that both points are defined with the same type of coordinates.

Precondition

Both *lhs* and *rhs* have to be defined on the same topology and with the same type of coordinates; otherwise this test does not compile.

Postcondition

The result, *dp*, is such as *lhs* == *rhs* + *dp*.

Returns

A delta point (temporary object).

See also

[mln::Gdpoint](#)

Definition at line 374 of file gpoint.hh.

10.191.2.4 template<typename P , typename D > P & operator-= (Gpoint< P > & p, const Gdpoint< D > & dp) [related]

Shift a point by the negate of a delta-point dp.

Parameters

- [in, out] *p* The targeted point.
- [in] *dp* A delta-point.

Returns

A reference to the point p once translated by - dp.

Precondition

The type of dp has to be compatible with the type of p.

Definition at line 436 of file gpoint.hh.

10.191.2.5 template<typename P , typename D > P operator/ (const Gpoint< P > & p, const value::scalar_< D > & dp) [related]

Divise a point by a scalar s.

Parameters

- [in, out] *p* The targeted point.
- [in] *dp* A scalar.

Returns

A reference to the point p once divided by s.

10.191.2.6 template<typename P > std::ostream & operator<< (std::ostream & ostr, const Gpoint< P > & p) [related]

Print a grid point p into the output stream ostr.

Parameters

- [in, out] *ostr* An output stream.
- [in] *p* A grid point.

Returns

The modified output stream ostr.

Definition at line 417 of file gpoint.hh.

References mln::debug::format().

10.191.2.7 template<typename L , typename R > bool operator==(const Gpoint< L > & lhs, const Gpoint< R > & rhs) [related]

Equality comparison between a couple of grid point *lhs* and *rhs*.

Parameters

- [in] *lhs* A first grid point.
- [in] *rhs* A second grid point.

Precondition

Both *lhs* and *rhs* have to be defined on the same topology; otherwise this test does not compile.

Returns

True if both grid points have the same coordinates, otherwise false.


Definition at line 365 of file gpoint.hh.

10.192 mln::Graph< E > Struct Template Reference

Base class for implementation of graph classes.

```
#include <graph.hh>
```

Inheritance diagram for mln::Graph< E >:



10.192.1 Detailed Description

template<typename E> struct mln::Graph< E >

Base class for implementation of graph classes.

See also

`mln::doc::Graph` for a complete documentation of this class contents.

Definition at line 57 of file `mln/core/concept/graph.hh`.

10.193 `mln::graph::attribute::card_t` Struct Reference

Compute the cardinality of every component in a graph.

```
#include <card.hh>
```

Public Types

- **typedef `util::array<unsigned> result`**

Type of the computed value.

10.193.1 Detailed Description

Compute the cardinality of every component in a graph.

Returns

An array with the cardinality for each component. Components are labeled from 0.

Definition at line 61 of file `graph/attribute/card.hh`.

10.193.2 Member Typedef Documentation

10.193.2.1 **typedef `util::array<unsigned> mln::graph::attribute::card_t::result`**

Type of the computed value.

Definition at line 64 of file `graph/attribute/card.hh`.

10.194 `mln::graph::attribute::representative_t` Struct Reference

Compute the representative vertex of every component in a graph.

```
#include <representative.hh>
```

Public Types

- **typedef `util::array<unsigned> result`**

Type of the computed value.

10.194.1 Detailed Description

Compute the representative vertex of every component in a graph.

Returns

An array with the representative for each component. Components are labeled from 0.

Definition at line 63 of file representative.hh.

10.194.2 Member Typedef Documentation

10.194.2.1 `typedef util::array<unsigned> mln::graph::attribute::representative_t::result`

Type of the computed value.


Definition at line 66 of file representative.hh.

10.195 mln::graph_elt_mixed_neighborhood< G, S, S2 > Struct Template Reference

Elementary neighborhood on graph class.

```
#include <graph_elt_mixed_neighborhood.hh>
```

Inheritance diagram for mln::graph_elt_mixed_neighborhood< G, S, S2 >:



Public Types

- `typedef neighb_bkd_niter< graph_elt_mixed_window< G, S, S2 > > bkd_niter`
Backward site iterator associated type.

- **typedef neighb_fwd_niter< graph_elt_mixed_window< G, S, S2 > > fwd_niter**
Forward site iterator associated type.
- **typedef fwd_niter niter**
Site iterator associated type.

10.195.1 Detailed Description

template<typename G, typename S, typename S2> struct mln::graph_elt_mixed_neighborhood< G, S, S2 >

Elementary neighborhood on graph class.

Template Parameters

- G* is a graph type.
- S* is a site set type.
- S2* is the site set type of the neighbors.

Definition at line 48 of file graph_elt_mixed_neighborhood.hh.

10.195.2 Member Typedef Documentation

10.195.2.1 typedef neighb_bkd_niter<graph_elt_mixed_window< G, S, S2 > > mln::neighb< graph_elt_mixed_window< G, S, S2 > >::bkd_niter [inherited]

Backward site iterator associated type.

Definition at line 87 of file mln/core/neighb.hh.

10.195.2.2 typedef neighb_fwd_niter<graph_elt_mixed_window< G, S, S2 > > mln::neighb< graph_elt_mixed_window< G, S, S2 > >::fwd_niter [inherited]

Forward site iterator associated type.

Definition at line 84 of file mln/core/neighb.hh.

10.195.2.3 typedef fwd_niter mln::neighb< graph_elt_mixed_window< G, S, S2 > >::niter [inherited]

Site iterator associated type.


Definition at line 90 of file mln/core/neighb.hh.

10.196 mln::graph_elt_mixed_window< G, S, S2 > Class Template Reference

Elementary window on graph class.

```
#include <graph_elt_mixed_window.hh>
```

Inheritance diagram for mln::graph_elt_mixed_window< G, S, S2 >:



Public Types

- **typedef super_::target target**
Associated types.
- **typedef target::psite psite**
The type of psite corresponding to the window.
- **typedef S::psite center_t**
Type of the window center element.
- **typedef target::graph_element graph_element**
Type of the graph element pointed by this iterator.
- **typedef graph_window_piter< target, self_, nbh_fwd_iter_ > fwd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef graph_window_piter< target, self_, nbh_bkd_iter_ > bkd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef fwd_qiter qiter**
The default qiter type.

- **typedef S2::fun_t::result site**
Associated types.

Public Member Functions

- bool `is_valid () const`
Return true by default.

- bool `is_empty () const`
Interface of the concept Window.

- bool `is_centered () const`
Is the window centered?

- bool `is_symmetric () const`
Is the window symmetric?

- unsigned `delta () const`
Return the maximum coordinate gap between the window center and a window point.

- `self_ & sym ()`
Apply a central symmetry to the target window.

10.196.1 Detailed Description

```
template<typename G, typename S, typename S2> class mln::graph_elt_mixed_window< G, S, S2 >
```

Elementary window on graph class. `G` is the graph type. `S` is an image site set from where the center is extracted. `S2` is an image site set from where the neighbors are extracted.

Definition at line 109 of file graph_elt_mixed_window.hh.

10.196.2 Member Typedef Documentation

10.196.2.1 template<typename G , typename S , typename S2 > typedef graph_window_piter<target,self_,nbh_bkd_iter_> mln::graph_elt_mixed_window< G, S, S2 >::bkd_qiter

`Site_Iterator` type to browse the psites of the window w.r.t.

the reverse ordering of vertices.

Definition at line 139 of file graph_elt_mixed_window.hh.

10.196.2.2 template<typename G , typename S , typename S2 > typedef S ::psite mln::graph_elt_mixed_window< G, S, S2 >::center_t

Type of the window center element.

Definition at line 128 of file graph_elt_mixed_window.hh.

10.196.2.3 template<typename G , typename S , typename S2 > typedef graph_window_piter<target,self_,nbh_fwd_iter_> mln::graph_elt_mixed_window< G, S, S2 >::fwd_qiter

`Site_Iterator` type to browse the psites of the window w.r.t.
the ordering of vertices.

Definition at line 135 of file `graph_elt_mixed_window.hh`.

10.196.2.4 template<typename G , typename S , typename S2 > typedef target ::graph_element mln::graph_elt_mixed_window< G, S, S2 >::graph_element

Type of the graph element pointed by this iterator.

Definition at line 131 of file `graph_elt_mixed_window.hh`.

10.196.2.5 template<typename G , typename S , typename S2 > typedef target ::psite mln::graph_elt_mixed_window< G, S, S2 >::psite

The type of psite corresponding to the window.

Definition at line 125 of file `graph_elt_mixed_window.hh`.

10.196.2.6 template<typename G , typename S , typename S2 > typedef fwd_qiter mln::graph_elt_mixed_window< G, S, S2 >::qiter

The default qiter type.

Definition at line 142 of file `graph_elt_mixed_window.hh`.

10.196.2.7 typedef S2::fun_t::result mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 > >::site [inherited]

Associated types.

The type of site corresponding to the window.

Definition at line 48 of file `graph_window_base.hh`.

10.196.2.8 template<typename G , typename S , typename S2 > typedef super_::target mln::graph_elt_mixed_window< G, S, S2 >::target

Associated types.

Definition at line 123 of file `graph_elt_mixed_window.hh`.

10.196.3 Member Function Documentation

10.196.3.1 unsigned mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 > >::delta () const [inherited]

Return the maximum coordinate gap between the window center and a window point.

10.196.3.2 bool mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 >>::is_centered () const [inherited]

Is the window centered?

10.196.3.3 bool mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 >>::is_empty () const [inherited]

Interface of the concept Window.

Is the window is empty?

10.196.3.4 bool mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 >>::is_symmetric () const [inherited]

Is the window symmetric?

10.196.3.5 bool mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 >>::is_valid () const [inherited]

Return true by default.

10.196.3.6 self_& mln::graph_window_base< S2::fun_t::result , graph_elt_mixed_window< G, S, S2 >>::sym () [inherited]


Apply a central symmetry to the target window.

10.197 mln::graph_elt_neighborhood< G, S > Struct Template Reference

Elementary neighborhood on graph class.

```
#include <graph_elt_neighborhood.hh>
```

Inheritance diagram for mln::graph_elt_neighborhood< G, S >:



Public Types

- `typedef neighb_bkd_niter< graph_elt_window< G, S > > bkd_niter`
Backward site iterator associated type.
- `typedef neighb_fwd_niter< graph_elt_window< G, S > > fwd_niter`
Forward site iterator associated type.
- `typedef fwd_niter niter`
Site iterator associated type.

10.197.1 Detailed Description

`template<typename G, typename S> struct mln::graph_elt_neighborhood< G, S >`

Elementary neighborhood on graph class.

Template Parameters

`G` is a graph type.

`S` is a site set type.

Definition at line 47 of file `graph_elt_neighborhood.hh`.

10.197.2 Member Typedef Documentation

10.197.2.1 `typedef neighb_bkd_niter<graph_elt_window< G, S > > mln::neighb< graph_elt_window< G, S > >::bkd_niter [inherited]`

Backward site iterator associated type.

Definition at line 87 of file mln/core/neighb.hh.

10.197.2.2 `typedef neighb_fwd_niter<graph_elt_window< G, S > > mln::neighb< graph_elt_window< G, S > >::fwd_niter [inherited]`

Forward site iterator associated type.

Definition at line 84 of file mln/core/neighb.hh.

10.197.2.3 `typedef fwd_niter mln::neighb< graph_elt_window< G, S > >::niter [inherited]`

Site iterator associated type.


Definition at line 90 of file mln/core/neighb.hh.

10.198 `mln::graph_elt_neighborhood_if< G, S, I >` Struct Template Reference

Elementary neighborhood_if on graph class.

```
#include <graph_elt_neighborhood_if.hh>
```

Inheritance diagram for `mln::graph_elt_neighborhood_if< G, S, I >`:



Public Types

- **typedef neighb_bkd_niter< graph_elt_window_if< G, S, I > > bkd_niter**
Backward site iterator associated type.
- **typedef neighb_fwd_niter< graph_elt_window_if< G, S, I > > fwd_niter**
Forward site iterator associated type.
- **typedef fwd_niter niter**
Site iterator associated type.

Public Member Functions

- **graph_elt_neighborhood_if ()**
Constructors @{ Construct an invalid neighborhood.
- **graph_elt_neighborhood_if (const Image< I > &mask)**
- **const I & mask () const**
- @}

10.198.1 Detailed Description

template<typename G, typename S, typename I> struct mln::graph_elt_neighborhood_if< G, S, I >

Elementary neighborhood_if on graph class.

Definition at line 43 of file graph_elt_neighborhood_if.hh.

10.198.2 Member Typedef Documentation

10.198.2.1 **typedef neighb_bkd_niter<graph_elt_window_if< G, S, I > > mln::neighb< graph_elt_window_if< G, S, I > >::bkd_niter [inherited]**

Backward site iterator associated type.

Definition at line 87 of file mln/core/neighb.hh.

10.198.2.2 **typedef neighb_fwd_niter<graph_elt_window_if< G, S, I > > mln::neighb< graph_elt_window_if< G, S, I > >::fwd_niter [inherited]**

Forward site iterator associated type.

Definition at line 84 of file mln/core/neighb.hh.

10.198.2.3 `typedef fwd_niter mln::neighb< graph_elt_window_if< G, S, I > >::niter [inherited]`

Site iterator associated type.

Definition at line 90 of file mln/core/neighb.hh.

10.198.3 Constructor & Destructor Documentation

10.198.3.1 `template<typename G , typename S , typename I > mln::graph_elt_neighborhood_if< G, S, I >::graph_elt_neighborhood_if() [inline]`

Constructors @ { Construct an invalid neighborhood.

Definition at line 67 of file graph_elt_neighborhood_if.hh.

10.198.3.2 `template<typename G , typename S , typename I > mln::graph_elt_neighborhood_if< G, S, I >::graph_elt_neighborhood_if(const Image< I > & mask) [inline]`

Parameters

`[in] mask` A graph image of Boolean.

Definition at line 74 of file graph_elt_neighborhood_if.hh.

10.198.4 Member Function Documentation

10.198.4.1 `template<typename G , typename S , typename I > const I & mln::graph_elt_neighborhood_if< G, S, I >::mask() const [inline]`

@ }

Return the graph image used as mask.


Definition at line 83 of file graph_elt_neighborhood_if.hh.

10.199 `mln::graph_elt_window< G, S >` Class Template Reference

Elementary window on graph class.

```
#include <graph_elt_window.hh>
```

Inheritance diagram for mln::graph_elt_window< G, S >:



Public Types

- **typedef S target**
Associated types.
- **typedef S::psite psite**
The type of psite corresponding to the window.
- **typedef S::psite center_t**
Type of the window center element.
- **typedef S::graph_element graph_element**
Type of the graph element pointed by this iterator.
- **typedef graph_window_piter< S, self_, nbh_fwd_iter_ > fwd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef graph_window_piter< S, self_, nbh_bkd_iter_ > bkd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef fwd_qiter qiter**
The default qiter type.
- **typedef S::fun_t::result site**
Associated types.

Public Member Functions

- bool `is_valid () const`

Return true by default.

- bool `is_empty () const`

Interface of the concept Window.

- bool `is_centered () const`

Is the window centered?

- bool `is_symmetric () const`

Is the window symmetric?

- unsigned `delta () const`

Return the maximum coordinate gap between the window center and a window point.

- `self_ & sym ()`

Apply a central symmetry to the target window.

10.199.1 Detailed Description

`template<typename G, typename S> class mln::graph_elt_window< G, S >`

Elementary window on graph class. `G` is the graph type. `S` is an image site set from where the center is extracted. `S2` is an image site set from where the neighbors are extracted.

Definition at line 111 of file `graph_elt_window.hh`.

10.199.2 Member Typedef Documentation

10.199.2.1 `template<typename G , typename S > typedef graph_window_piter<S,self_,nbh_bkd_iter_> mln::graph_elt_window< G, S >::bkd_qiter`

`Site_Iterator` type to browse the psites of the window w.r.t.

the reverse ordering of vertices.

Definition at line 142 of file `graph_elt_window.hh`.

10.199.2.2 `template<typename G , typename S > typedef S ::psite mln::graph_elt_window< G, S >::center_t`

Type of the window center element.

Definition at line 131 of file `graph_elt_window.hh`.

10.199.2.3 template<typename G , typename S > typedef graph_window_piter<S,self_,nbh_fwd_iter_> mln::graph_elt_window< G, S >::fwd_qiter

`Site_Iterator` type to browse the psites of the window w.r.t.

the ordering of vertices.

Definition at line 138 of file `graph_elt_window.hh`.

10.199.2.4 template<typename G , typename S > typedef S ::graph_element mln::graph_elt_window< G, S >::graph_element

Type of the graph element pointed by this iterator.

Definition at line 134 of file `graph_elt_window.hh`.

10.199.2.5 template<typename G , typename S > typedef S ::psite mln::graph_elt_window< G, S >::psite

The type of psite corresponding to the window.

Definition at line 128 of file `graph_elt_window.hh`.

10.199.2.6 template<typename G , typename S > typedef fwd_qiter mln::graph_elt_window< G, S >::qiter

The default qiter type.

Definition at line 145 of file `graph_elt_window.hh`.

10.199.2.7 typedef S::fun_t::result mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::site [inherited]

Associated types.

The type of site corresponding to the window.

Definition at line 48 of file `graph_window_base.hh`.

10.199.2.8 template<typename G , typename S > typedef S mln::graph_elt_window< G, S >::target

Associated types.

Definition at line 125 of file `graph_elt_window.hh`.

10.199.3 Member Function Documentation

10.199.3.1 unsigned mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::delta () const [inherited]

Return the maximum coordinate gap between the window center and a window point.

10.199.3.2 bool mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::is_centered () const [inherited]

Is the window centered?

10.199.3.3 bool mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::is_empty () const [inherited]

Interface of the concept Window.

Is the window is empty?

10.199.3.4 bool mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::is_symmetric () const [inherited]

Is the window symmetric?

10.199.3.5 bool mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::is_valid () const [inherited]

Return true by default.

10.199.3.6 self_& mln::graph_window_base< S::fun_t::result , graph_elt_window< G, S > >::sym () [inherited]


Apply a central symmetry to the target window.

10.200 mln::graph_elt_window_if< G, S, I > Class Template Reference

Custom window on graph class.

```
#include <graph_elt_window_if.hh>
```

Inheritance diagram for mln::graph_elt_window_if< G, S, I >:



Public Types

- **typedef I mask_t**
The type of the image used as mask.
- **typedef S target**
`@{ }`
- **typedef target::psite psite**
The type of psite corresponding to the window.
- **typedef graph_window_if_piter< target, self_, nbh_fwd_iter_ > fwd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef graph_window_if_piter< target, self_, nbh_bkd_iter_ > bkd_qiter**
Site_Iterator type to browse the psites of the window w.r.t.
- **typedef fwd_qiter qiter**
The default qiter type.
- **typedef S::fun_t::result site**
Associated types.

Public Member Functions

- void `change_mask` (const `Image< I >` &`mask`)
Change mask image.
- `graph_elt_window_if` ()
Constructor.
- `graph_elt_window_if` (const `Image< I >` &`mask`)
- bool `is_valid` () const
Return true by default.
- const `I & mask` () const
Return the graph image used as mask.
- bool `is_empty` () const
Interface of the concept Window.
- bool `is_centered` () const
Is the window centered?
- bool `is_symmetric` () const
Is the window symmetric?
- unsigned `delta` () const
Return the maximum coordinate gap between the window center and a window point.
- `self_ & sym` ()
Apply a central symmetry to the target window.

10.200.1 Detailed Description

`template<typename G, typename S, typename I> class mln::graph_elt_window_if< G, S, I >`

Custom window on graph class. It is defined thanks to a mask.

`G` is the graph type. `S` is the image site set. `I` is the graph image the type used as mask.

Definition at line 105 of file `graph_elt_window_if.hh`.

10.200.2 Member Typedef Documentation

10.200.2.1 `template<typename G , typename S , typename I > typedef graph_window_if_piter<target,self_,nbh_bkd_iter_> mln::graph_elt_window_if< G, S, I >::bkd_qiter`

`Site_Iterator` type to browse the psites of the window w.r.t.

the reverse ordering of vertices.

Definition at line 147 of file `graph_elt_window_if.hh`.

10.200.2.2 template<typename G , typename S , typename I > typedef graph_window_if_piter<target,self_,nbh_fwd_iter_> mln::graph_elt_window_if< G, S, I >::fwd_qiter

[Site_Iterator](#) type to browse the psites of the window w.r.t.

the ordering of vertices.

Definition at line 143 of file graph_elt_window_if.hh.

10.200.2.3 template<typename G , typename S , typename I > typedef I mln::graph_elt_window_if< G, S, I >::mask_t

The type of the image used as mask.

Definition at line 119 of file graph_elt_window_if.hh.

10.200.2.4 template<typename G , typename S , typename I > typedef target ::psite mln::graph_elt_window_if< G, S, I >::psite

The type of psite corresponding to the window.

Definition at line 139 of file graph_elt_window_if.hh.

10.200.2.5 template<typename G , typename S , typename I > typedef fwd_qiter mln::graph_elt_window_if< G, S, I >::qiter

The default qiter type.

Definition at line 150 of file graph_elt_window_if.hh.

10.200.2.6 typedef S::fun_t::result mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::site [inherited]

Associated types.

The type of site corresponding to the window.

Definition at line 48 of file graph_window_base.hh.

10.200.2.7 template<typename G , typename S , typename I > typedef S mln::graph_elt_window_if< G, S, I >::target

@ }

Associated types. The image domain on which this window iterates on.

Definition at line 136 of file graph_elt_window_if.hh.

10.200.3 Constructor & Destructor Documentation

10.200.3.1 template<typename G , typename S , typename I > mln::graph_elt_window_if< G, S, I >::graph_elt_window_if() [inline]

Constructor.

@{ Default. Construct an invalid window.

Definition at line 174 of file graph_elt_window_if.hh.

10.200.3.2 template<typename G , typename S , typename I > mln::graph_elt_window_if< G, S, I >::graph_elt_window_if(const Image< I > & mask) [inline]

Parameters

[in] *mask* A graph image of bool.

See also

[vertex_image](#), [edge_image](#).

Definition at line 181 of file graph_elt_window_if.hh.

10.200.4 Member Function Documentation

10.200.4.1 template<typename G , typename S , typename I > void mln::graph_elt_window_if< G, S, I >::change_mask(const Image< I > & mask) [inline]

Change mask image.

Definition at line 199 of file graph_elt_window_if.hh.

References mln::graph_elt_window_if< G, S, I >::is_valid().

10.200.4.2 unsigned mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::delta() const [inherited]

Return the maximum coordinate gap between the window center and a window point.

10.200.4.3 bool mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::is_centered() const [inherited]

Is the window centered?

10.200.4.4 bool mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::is_empty() const [inherited]

Interface of the concept Window.

Is the window is empty?

10.200.4.5 bool mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::is_symmetric () const [inherited]

Is the window symmetric?

10.200.4.6 template<typename G , typename S , typename I > bool mln::graph_elt_window_if< G, S, I >::is_valid () const [inline]

Return true by default.

Reimplemented from [mln::graph_window_base< S::fun_t::result, graph_elt_window_if< G, S, I > >](#).

Definition at line 208 of file [graph_elt_window_if.hh](#).

Referenced by [mln::graph_elt_window_if< G, S, I >::change_mask\(\)](#).

10.200.4.7 template<typename G , typename S , typename I > const I & mln::graph_elt_window_if< G, S, I >::mask () const [inline]

Return the graph image used as mask.

Definition at line 190 of file [graph_elt_window_if.hh](#).


10.200.4.8 self_& mln::graph_window_base< S::fun_t::result , graph_elt_window_if< G, S, I > >::sym () [inherited]

Apply a central symmetry to the target window.

10.201 mln::graph_window_base< P, E > Class Template Reference

```
#include <graph_window_base.hh>
```

Inheritance diagram for [mln::graph_window_base< P, E >](#):



Public Types

- **typedef P site**
Associated types.

Public Member Functions

- **bool [is_valid \(\) const](#)**

Return true by default.

- `bool is_empty () const`
Interface of the concept [Window](#).
- `bool is_centered () const`
Is the window centered?
- `bool is_symmetric () const`
Is the window symmetric?
- `unsigned delta () const`
Return the maximum coordinate gap between the window center and a window point.
- `self_ & sym ()`
Apply a central symmetry to the target window.

10.201.1 Detailed Description

`template<typename P, typename E> class mln::graph_window_base< P, E >`

Template Parameters

P [Site](#) type.

Definition at line 40 of file `graph_window_base.hh`.

10.201.2 Member Typedef Documentation

10.201.2.1 `template<typename P, typename E> typedef P mln::graph_window_base< P, E >::site`

Associated types.

The type of site corresponding to the window.

Definition at line 48 of file `graph_window_base.hh`.

10.201.3 Member Function Documentation

10.201.3.1 `template<typename P , typename E > unsigned mln::graph_window_base< P, E >::delta () const [inline]`

Return the maximum coordinate gap between the window center and a window point.

Definition at line 128 of file `graph_window_base.hh`.

10.201.3.2 `template<typename P , typename E > bool mln::graph_window_base< P, E >::is_centered () const [inline]`

Is the window centered?

Definition at line 112 of file `graph_window_base.hh`.

10.201.3.3 template<typename P , typename E > bool mln::graph_window_base< P, E >::is_empty() const [inline]

Interface of the concept [Window](#).

Is the window is empty?

Definition at line 104 of file `graph_window_base.hh`.

10.201.3.4 template<typename P , typename E > bool mln::graph_window_base< P, E >::is_symmetric() const [inline]

Is the window symmetric?

Definition at line 120 of file `graph_window_base.hh`.

10.201.3.5 template<typename P , typename E > bool mln::graph_window_base< P, E >::is_valid() const [inline]

Return true by default.

Reimplemented in [mln::graph_elt_window_if< G, S, I >](#).

Definition at line 153 of file `graph_window_base.hh`.

10.201.3.6 template<typename P , typename E > graph_window_base< P, E > & mln::graph_window_base< P, E >::sym() [inline]

Apply a central symmetry to the target window.

Definition at line 137 of file `graph_window_base.hh`.

10.202 `mln::graph_window_if_piter< S, W, I >` Class Template Reference

Forward iterator on line graph window.

```
#include <graph_window_if_piter.hh>
```

Inherits `site_relative_iterator_base< W, graph_window_if_piter< S, W, I > >`, and `is_masked_impl_selector< S, W::mask_t::domain_t, graph_window_if_piter< S, W, I > >`.

Public Types

- `typedef S::fun_t::result P`

Associated types.

Public Member Functions

- `void next()`

Go to the next element.

- **graph_window_if_piter ()**
Construction.

- **const S::graph_element & element () const**
Return the graph element pointed by this iterator.

- **unsigned id () const**
Return the graph element id.

10.202.1 Detailed Description

template<typename S, typename W, typename I> class mln::graph_window_if_piter< S, W, I >

Forward iterator on line graph window.

Definition at line 47 of file graph_window_if_piter.hh.

10.202.2 Member Typedef Documentation

10.202.2.1 template<typename S , typename W , typename I > typedef S::fun_t ::result mln::graph_window_if_piter< S, W, I >::P

Associated types.

Definition at line 60 of file graph_window_if_piter.hh.

10.202.3 Constructor & Destructor Documentation

10.202.3.1 template<typename S , typename W , typename I > mln::graph_window_if_piter< S, W, I >::graph_window_if_piter () [inline]

Construction.

Definition at line 122 of file graph_window_if_piter.hh.

10.202.4 Member Function Documentation

10.202.4.1 template<typename S , typename W , typename I > const S::graph_element & mln::graph_window_if_piter< S, W, I >::element () const [inline]

Return the graph element pointed by this iterator.

Definition at line 213 of file graph_window_if_piter.hh.

10.202.4.2 template<typename S , typename W , typename I > unsigned mln::graph_window_if_piter< S, W, I >::id () const [inline]

Return the graph element id.

FIXME: we do not want to have this member since there is an automatic conversion to the graph element. C++ does not seem to use this conversion operator.

Definition at line 221 of file graph_window_if_piter.hh.

10.202.4.3 void mln::Site_Iterator< graph_window_if_piter< S, W, I > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.203 mln::graph_window_piter< S, W, I > Class Template Reference

Forward iterator on line graph window.

```
#include <graph_window_piter.hh>
```

Inherits site_relative_iterator_base< W, graph_window_piter< S, W, I >, W::center_t >, and impl_selector< W::center_t, W::psite, graph_window_piter< S, W, I > >.

Public Types

- **typedef S::fun_t::result P**
Associated types
Type of the window elements.
- **typedef W::center_t center_t**
Type of the window center.
- **typedef W::graph_element graph_element**
Type of the graph element pointed by this iterator.

Public Member Functions

- **void change_target_site_set (const S &s)**
Change the target site set.
- **void next ()**
Go to the next element.
- **const S & target_site_set () const**

Return the target site set.

- `graph_window_piter ()`
Construction.
- template<typename Pref >
`graph_window_piter (const Window< W > &win, const Pref &p_ref)`
To be used in case the center and neighbor sites have the same type and belong to the same site set.
- template<typename Pref >
`graph_window_piter (const Window< W > &win, const Site_Set< S > &target_site_set, const Pref &p_ref)`
To be used in case center and neighbors sites do not have the same type and do not belong to the same site set.
- const `graph_element & element () const`
Return the graph element pointed by this iterator.
- unsigned `id () const`
Return the graph element id.

10.203.1 Detailed Description

`template<typename S, typename W, typename I> class mln::graph_window_piter< S, W, I >`

Forward iterator on line graph window.

Template Parameters

`S` is the site set type.

`W` is the window type.

`I` is the underlying iterator type.

Definition at line 99 of file `graph_window_piter.hh`.

10.203.2 Member Typedef Documentation

**10.203.2.1 template<typename S , typename W , typename I > typedef W::center_t
`mln::graph_window_piter< S, W, I >::center_t`**

Type of the window center.

Definition at line 120 of file `graph_window_piter.hh`.

**10.203.2.2 template<typename S , typename W , typename I > typedef W::graph_element
`mln::graph_window_piter< S, W, I >::graph_element`**

Type of the graph element pointed by this iterator.

Definition at line 122 of file `graph_window_piter.hh`.

10.203.2.3 template<typename S , typename W , typename I > typedef S::fun_t ::result mln::graph_window_piter< S, W, I >::P

Associated types

Type of the window elements.

Definition at line 118 of file graph_window_piter.hh.

10.203.3 Constructor & Destructor Documentation

10.203.3.1 template<typename S , typename W , typename I > mln::graph_window_piter< S, W, I >::graph_window_piter() [inline]

Construction.

Definition at line 226 of file graph_window_piter.hh.

10.203.3.2 template<typename S , typename W , typename I > template<typename Pref > mln::graph_window_piter< S, W, I >::graph_window_piter (const Window< W > & win, const Pref & p_ref) [inline]

To be used in case the center and neighbor sites have the same type and belong to the same site set.

Parameters

win The underlying window.

p_ref [Window](#) center.

Definition at line 235 of file graph_window_piter.hh.

10.203.3.3 template<typename S , typename W , typename I > template<typename Pref > mln::graph_window_piter< S, W, I >::graph_window_piter (const Window< W > & win, const Site_Set< S > & target_site_set, const Pref & p_ref) [inline]

To be used in case center and neighbors sites do not have the same type and do not belong to the same site set.

Parameters

win The underlying window.

target_site_set [Site](#) set in which neighbor sites are extracted.

p_ref [Window](#) center.

Definition at line 249 of file graph_window_piter.hh.

10.203.4 Member Function Documentation

10.203.4.1 template<typename S , typename W , typename I > void mln::graph_window_piter< S, W, I >::change_target_site_set (const S & s) [inline]

Change the target site set.

[Window](#) elements different from the center come from the target site set.

Definition at line 357 of file graph_window_piter.hh.

10.203.4.2 template<typename S , typename W , typename I > const graph_window_piter< S, W, I >::graph_element & mln::graph_window_piter< S, W, I >::element() const [inline]

Return the graph element pointed by this iterator.

Definition at line 341 of file graph_window_piter.hh.

10.203.4.3 template<typename S , typename W , typename I > unsigned mln::graph_window_piter< S, W, I >::id() const [inline]

Return the graph element id.

FIXME: we do not want to have this member since there is an automatic conversion to the graph element. C++ does not seem to use this conversion operator.

Definition at line 349 of file graph_window_piter.hh.

10.203.4.4 void mln::Site_Iterator< graph_window_piter< S, W, I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.203.4.5 template<typename S , typename W , typename I > const S & mln::graph_window_piter< S, W, I >::target_site_set() const [inline]

Return the target site set.

[Window](#) elements different from the center come from the target site set.


Definition at line 366 of file graph_window_piter.hh.

10.204 mln::hexa< I > Struct Template Reference

hexagonal image class.

```
#include <hexa.hh>
```

Inheritance diagram for mln::hexa< I >:



Public Types

- **typedef hexa_bkd_piter_< box2d > bkd_piter**
FIXME : should it be in box2d_h? Backward Site_Iterator associated type.
- **typedef hexa_fwd_piter_< box2d > fwd_piter**
FIXME : should it be in box2d_h? Forward Site_Iterator associated type.
- **typedef I::lvalue lvalue**
Lvalue associated type.
- **typedef point2d_h psite**
Point site type.
- **typedef I::rvalue rvalue**
Return type of read-only access.
- **typedef hexa< tag::image_< I > > skeleton**
Skeleton.
- **typedef I::value value**
Value associated type.

Public Member Functions

- **const box2d_h & domain () const**

Give the definition domain.

- `bool has (const psite &p) const`

Test if p belongs to the image domain.

- `hexa (I &ima)`

Constructor with an base image.

- `hexa ()`

Constructor without argument.

- `lvalue operator() (const point2d_h &p)`

Read-write access of pixel value at hexa point site p.

- `rvalue operator() (const point2d_h &p) const`

Read-only access of pixel value at hexa point site p.

10.204.1 Detailed Description

template<typename I> struct mln::hexa< I >

hexagonal image class. The parameter I is the type of the base image. This image class which handles hexagonal grid.

```
Ex : 1 3 5 7 9 11 0 2 4 6 8 10 ----- 0 XX| | | | |XX ----- 2 XX| | | | |XX
----- 4 XX| | | | |XX ----- 6 XX| | | | |XX ----- 8 XX| | | | |
|XX -----
```

Definition at line 116 of file hexa.hh.

10.204.2 Member Typedef Documentation

10.204.2.1 template<typename I> typedef hexa_bkd_piter_<box2d> mln::hexa< I >::bkd_piter

FIXME : should it be in box2d_h? Backward [Site_Iterator](#) associated type.

Definition at line 140 of file hexa.hh.

10.204.2.2 template<typename I> typedef hexa_fwd_piter_<box2d> mln::hexa< I >::fwd_piter

FIXME : should it be in box2d_h? Forward [Site_Iterator](#) associated type.

Definition at line 136 of file hexa.hh.

10.204.2.3 template<typename I> typedef I ::lvalue mln::hexa< I >::lvalue

Lvalue associated type.

Definition at line 126 of file hexa.hh.

10.204.2.4 template<typename I> typedef point2d_h mln::hexa< I >::psite

[Point](#) site type.

Reimplemented in [mln::image2d_h< V >](#).

Definition at line 132 of file hexa.hh.

10.204.2.5 template<typename I> typedef I ::rvalue mln::hexa< I >::rvalue

Return type of read-only access.

Definition at line 129 of file hexa.hh.

10.204.2.6 template<typename I> typedef hexa< tag::image_<I> > mln::hexa< I >::skeleton

Skeleton.

Definition at line 120 of file hexa.hh.

10.204.2.7 template<typename I> typedef I ::value mln::hexa< I >::value

[Value](#) associated type.

Definition at line 123 of file hexa.hh.

10.204.3 Constructor & Destructor Documentation**10.204.3.1 template<typename I> mln::hexa< I >::hexa() [inline]**

Constructor without argument.

Definition at line 215 of file hexa.hh.

10.204.3.2 template<typename I> mln::hexa< I >::hexa(I & *ima*) [inline]

Constructor with an base image.

Definition at line 222 of file hexa.hh.

10.204.4 Member Function Documentation**10.204.4.1 template<typename I> const box2d_h & mln::hexa< I >::domain() const [inline]**

Give the definition domain.

Definition at line 250 of file hexa.hh.

10.204.4.2 template<typename I> bool mln::hexa< I >::has(const psite & *p*) const [inline]

Test if *p* belongs to the image domain.

Definition at line 259 of file hexa.hh.

Referenced by mln::hexa< I >::operator()().

10.204.4.3 template<typename I> hexa< I >::rvalue mln::hexa< I >::operator() (const point2d_h & p) const [inline]

Read-only access of pixel value at hexa point site p.

Definition at line 230 of file hexa.hh.

References mln::hexa< I >::has().

10.204.4.4 template<typename I> hexa< I >::lvalue mln::hexa< I >::operator() (const point2d_h & p) [inline]

Read-write access of pixel value at hexa point site p.

Definition at line 240 of file hexa.hh.

References mln::hexa< I >::has().

10.205 mln::histo::array< T > Struct Template Reference

Generic histogram class over a value set with type T.

```
#include <array.hh>
```

10.205.1 Detailed Description

template<typename T> struct mln::histo::array< T >

Generic histogram class over a value set with type T.


Definition at line 48 of file histo/array.hh.

10.206 mln::Image< E > Struct Template Reference

Base class for implementation of image classes.

```
#include <image.hh>
```

Inheritance diagram for mln::Image< E >:



10.206.1 Detailed Description

template<typename E> struct mln::Image< E >

Base class for implementation of image classes.

See also

[mln::doc::Image](#) for a complete documentation of this class contents.

Definition at line 73 of file core/concept/image.hh.

10.207 mln::image1d< T > Struct Template Reference

Basic 1D image class.

#include <image1d.hh>

Inherits [image_primary< T, box1d, image1d< T > >](#).

Public Types

- **typedef T & lvalue**
Return type of read-write access.
- **typedef const T & rvalue**
Return type of read-only access.
- **typedef image1d< tag::value_< T > > skeleton**
Skeleton.
- **typedef T value**
Value associated type.

Public Member Functions

- **const box1d & bbox () const**
Give the bounding box domain.
- **unsigned border () const**
Give the border thickness.
- **const T * buffer () const**
Give a hook to the value buffer.
- **T * buffer ()**
Give a hook to the value buffer.
- **int delta_index (const dpoint1d &dp) const**

Give the offset corresponding to the delta-point dp .

- const **box1d** & **domain** () const

Give the definition domain.

- const **T** & **element** (unsigned **i**) const

Read-only access to the i -th image value (including the border).

- **T** & **element** (unsigned **i**)

Read-write access to the i -th image value (including the border).

- bool **has** (const **point1d** &**p**) const

Test if p is valid.

- **image1d** ()

Constructor without argument.

- **image1d** (const **box1d** &**b**, unsigned **bdr**=**border**::**thickness**)

Constructor with a box and the border thickness.

- **image1d** (unsigned **ninds**, unsigned **bdr**=**border**::**thickness**)

Constructor with the number of indices and the border thickness.

- unsigned **nelements** () const

Give the number of cells (points including border ones).

- unsigned **ninds** () const

Give the number of indexes.

- **T** & **operator()** (const **point1d** &**p**)

Read-write access to the image value located at point p .

- const **T** & **operator()** (const **point1d** &**p**) const

Read-only access to the image value located at point p .

- **point1d** **point_at_index** (unsigned **i**) const

Give the point corresponding to the offset i .

- const **box1d** & **vbbox** () const

virtual box, i.e., box including the virtual border

10.207.1 Detailed Description

template<typename T> struct mln::image1d< T >

Basic 1D image class. The parameter **T** is the type of pixel values. This image class stores data in memory and has a virtual border with constant thickness before and after data.

Definition at line 155 of file image1d.hh.

10.207.2 Member Typedef Documentation

10.207.2.1 template<typename T> typedef T& mln::image1d< T >::lvalue

Return type of read-write access.

Definition at line 167 of file image1d.hh.

10.207.2.2 template<typename T> typedef const T& mln::image1d< T >::rvalue

Return type of read-only access.

Definition at line 164 of file image1d.hh.

10.207.2.3 template<typename T> typedef image1d< tag::value_< T > > mln::image1d< T >::skeleton

Skeleton.

Definition at line 170 of file image1d.hh.

10.207.2.4 template<typename T> typedef T mln::image1d< T >::value

Value associated type.

Definition at line 161 of file image1d.hh.

10.207.3 Constructor & Destructor Documentation

10.207.3.1 template<typename T > mln::image1d< T >::image1d() [inline]

Constructor without argument.

Definition at line 371 of file image1d.hh.

10.207.3.2 template<typename T > mln::image1d< T >::image1d(unsigned ninds, unsigned bdr = border::thickness) [inline]

Constructor with the number of indices and the border thickness.

Definition at line 384 of file image1d.hh.

References mln::make::box1d().

10.207.3.3 template<typename T > mln::image1d< T >::image1d(const box1d & b, unsigned bdr = border::thickness) [inline]

Constructor with a box and the border thickness.

Definition at line 377 of file image1d.hh.

10.207.4 Member Function Documentation

10.207.4.1 template<typename T > const box1d & mln::image1d< T >::bbox() const [inline]

Give the bounding box domain.

Definition at line 411 of file image1d.hh.

10.207.4.2 template<typename T > unsigned mln::image1d< T >::border() const [inline]

Give the border thickness.

Definition at line 429 of file image1d.hh.

10.207.4.3 template<typename T > const T * mln::image1d< T >::buffer() const [inline]

Give a hook to the value buffer.

Definition at line 520 of file image1d.hh.

10.207.4.4 template<typename T > T * mln::image1d< T >::buffer() [inline]

Give a hook to the value buffer.

Definition at line 529 of file image1d.hh.

10.207.4.5 template<typename T > int mln::image1d< T >::delta_index(const dpoint1d & dp) const [inline]

Give the offset corresponding to the delta-point dp.

Definition at line 538 of file image1d.hh.

10.207.4.6 template<typename T > const box1d & mln::image1d< T >::domain() const [inline]

Give the definition domain.

Definition at line 402 of file image1d.hh.

10.207.4.7 template<typename T > const T & mln::image1d< T >::element(unsigned i) const [inline]

Read-only access to the *i*-th image value (including the border).

Definition at line 502 of file image1d.hh.

References mln::image1d< T >::nelements().

**10.207.4.8 template<typename T > T & mln::image1d< T >::element (unsigned *i*)
[inline]**

Read-write access to the *i*-th image value (including the border).

Definition at line 511 of file image1d.hh.

References mln::image1d< T >::nelements().

**10.207.4.9 template<typename T > bool mln::image1d< T >::has (const point1d & *p*) const
[inline]**

Test if *p* is valid.

Definition at line 447 of file image1d.hh.

Referenced by mln::image1d< T >::operator()().

**10.207.4.10 template<typename T > unsigned mln::image1d< T >::nelements () const
[inline]**

Give the number of cells (points including border ones).

Definition at line 438 of file image1d.hh.

Referenced by mln::image1d< T >::element(), and mln::image1d< T >::point_at_index().

10.207.4.11 template<typename T > unsigned mln::image1d< T >::ninds () const [inline]

Give the number of indexes.

Definition at line 483 of file image1d.hh.

10.207.4.12 template<typename T > const T & mln::image1d< T >::operator() (const point1d & *p*) const [inline]

Read-only access to the image value located at point *p*.

Definition at line 456 of file image1d.hh.

References mln::image1d< T >::has().

**10.207.4.13 template<typename T > T & mln::image1d< T >::operator() (const point1d & *p*)
[inline]**

Read-write access to the image value located at point *p*.

Definition at line 465 of file image1d.hh.

References mln::image1d< T >::has().

**10.207.4.14 template<typename T > point1d mln::image1d< T >::point_at_index (unsigned *i*)
const [inline]**

Give the point corresponding to the offset *o*.

Definition at line 548 of file image1d.hh.

References mln::image1d< T >::nelements().

10.207.4.15 template<typename T > const box1d & mln::image1d< T >::vbbox () const [inline]

virtual box, i.e., box including the virtual border

Definition at line 420 of file image1d.hh.

10.208 mln::image2d< T > Class Template Reference

Basic 2D image class.

```
#include <image2d.hh>
```

Inherits image_primary< T, mln::box2d, image2d< T > >.

Public Types

- **typedef T & lvalue**
Return type of read-write access.
- **typedef const T & rvalue**
Return type of read-only access.
- **typedef image2d< tag::value_< T > > skeleton**
Skeleton.
- **typedef T value**
Value associated type.

Public Member Functions

- **const box2d & bbox () const**
Give the bounding box domain.
- **unsigned border () const**
Give the border thickness.
- **const T * buffer () const**
Give a hook to the value buffer.
- **T * buffer ()**
Give a hook to the value buffer.
- **int delta_index (const dpoint2d &dp) const**
Give the delta-index corresponding to the delta-point dp.

- const `box2d` & `domain` () const
Give the definition domain.
- `T` & `element` (unsigned `i`)
Read-write access to the image value located at index `i`.
- const `T` & `element` (unsigned `i`) const
Read-only access to the image value located at index `i`.
- bool `has` (const `point2d` &`p`) const
Test if `p` is valid.
- `image2d` (int `nrows`, int `ncols`, unsigned `bdr=border::thickness`)
Constructor with the numbers of rows and columns and the border thickness.
- `image2d` ()
Constructor without argument.
- `image2d` (const `box2d` &`b`, unsigned `bdr=border::thickness`)
Constructor with a box and the border thickness (default is 3).
- unsigned `ncols` () const
Give the number of columns.
- unsigned `nelements` () const
Give the number of elements (points including border ones).
- unsigned `nrows` () const
Give the number of rows.
- const `T` & `operator()` (const `point2d` &`p`) const
Read-only access to the image value located at point `p`.
- `T` & `operator()` (const `point2d` &`p`)
Read-write access to the image value located at point `p`.
- `point2d` `point_at_index` (unsigned `i`) const
Give the point corresponding to the index `i`.

10.208.1 Detailed Description

`template<typename T> class mln::image2d< T >`

Basic 2D image class. The parameter `T` is the type of pixel values. This image class stores data in memory and has a virtual border with constant thickness around data.

Definition at line 136 of file core/image/image2d.hh.

10.208.2 Member Typedef Documentation

10.208.2.1 template<typename T> typedef T& mln::image2d< T >::lvalue

Return type of read-write access.

Definition at line 148 of file core/image/image2d.hh.

10.208.2.2 template<typename T> typedef const T& mln::image2d< T >::rvalue

Return type of read-only access.

Definition at line 145 of file core/image/image2d.hh.

10.208.2.3 template<typename T> typedef image2d< tag::value_< T > > mln::image2d< T >::skeleton

Skeleton.

Definition at line 152 of file core/image/image2d.hh.

10.208.2.4 template<typename T> typedef T mln::image2d< T >::value

Value associated type.

Definition at line 142 of file core/image/image2d.hh.

10.208.3 Constructor & Destructor Documentation

10.208.3.1 template<typename T> mln::image2d< T >::image2d() [inline]

Constructor without argument.

Definition at line 394 of file core/image/image2d.hh.

10.208.3.2 template<typename T> mln::image2d< T >::image2d(int *nrows*, int *ncols*, unsigned *bdr* = *border*::thickness) [inline]

Constructor with the numbers of rows and columns and the border thickness.

Definition at line 400 of file core/image/image2d.hh.

References mln::make::box2d().

10.208.3.3 template<typename T> mln::image2d< T >::image2d(const box2d & *b*, unsigned *bdr* = *border*::thickness) [inline]

Constructor with a box and the border thickness (default is 3).

Definition at line 407 of file core/image/image2d.hh.

10.208.4 Member Function Documentation

10.208.4.1 template<typename T > const box2d & mln::image2d< T >::bbox () const [inline]

Give the bounding box domain.

Definition at line 433 of file core/image/image2d.hh.

10.208.4.2 template<typename T > unsigned mln::image2d< T >::border () const [inline]

Give the border thickness.

Definition at line 520 of file core/image/image2d.hh.

10.208.4.3 template<typename T > const T * mln::image2d< T >::buffer () const [inline]

Give a hook to the value buffer.

Definition at line 556 of file core/image/image2d.hh.

10.208.4.4 template<typename T > T * mln::image2d< T >::buffer () [inline]

Give a hook to the value buffer.

Definition at line 565 of file core/image/image2d.hh.

10.208.4.5 template<typename T > int mln::image2d< T >::delta_index (const dpoint2d & dp) const [inline]

Give the delta-index corresponding to the delta-point dp.

Definition at line 574 of file core/image/image2d.hh.

10.208.4.6 template<typename T > const box2d & mln::image2d< T >::domain () const [inline]

Give the definition domain.

Definition at line 424 of file core/image/image2d.hh.

Referenced by mln::morpho::line_gradient(), mln::make_debug_graph_image(), and mln::io::txt::save().

10.208.4.7 template<typename T > const T & mln::image2d< T >::element (unsigned i) const [inline]

Read-only access to the image value located at index i.

Definition at line 538 of file core/image/image2d.hh.

References mln::image2d< T >::nelements().

**10.208.4.8 template<typename T > T & mln::image2d< T >::element (unsigned i)
[inline]**

Read-write access to the image value located at index *i*.

Definition at line 547 of file core/image/image2d.hh.

References mln::image2d< T >::nelements().

**10.208.4.9 template<typename T > bool mln::image2d< T >::has (const point2d & p) const
[inline]**

Test if *p* is valid.

Definition at line 451 of file core/image/image2d.hh.

Referenced by mln::image2d< T >::operator()(), and mln::debug::put_word().

10.208.4.10 template<typename T > unsigned mln::image2d< T >::ncols () const [inline]

Give the number of columns.

Definition at line 508 of file core/image/image2d.hh.

**10.208.4.11 template<typename T > unsigned mln::image2d< T >::nelements () const
[inline]**

Give the number of elements (points including border ones).

Definition at line 529 of file core/image/image2d.hh.

Referenced by mln::image2d< T >::element(), and mln::image2d< T >::point_at_index().

10.208.4.12 template<typename T > unsigned mln::image2d< T >::nrows () const [inline]

Give the number of rows.

Definition at line 499 of file core/image/image2d.hh.

**10.208.4.13 template<typename T > T & mln::image2d< T >::operator() (const point2d & p)
[inline]**

Read-write access to the image value located at point *p*.

Definition at line 469 of file core/image/image2d.hh.

References mln::image2d< T >::has().

**10.208.4.14 template<typename T > const T & mln::image2d< T >::operator() (const point2d
& p) const [inline]**

Read-only access to the image value located at point *p*.

Definition at line 460 of file core/image/image2d.hh.

References mln::image2d< T >::has().

10.208.4.15 template<typename T > point2d mln::image2d< T >::point_at_index (unsigned i) const [inline]

Give the point corresponding to the index *i*.

Definition at line 584 of file core/image/image2d.hh.


References mln::image2d< T >::nelements().

10.209 mln::image2d_h< V > Struct Template Reference

2d image based on an hexagonal mesh.

```
#include <image2d_h.hh>
```

Inheritance diagram for mln::image2d_h< V >:



Public Types

- **typedef hexa_bkd_piter_< box2d > bkd_piter**
FIXME : should it be in box2d_h? Backward Site_Iterator associated type.
- **typedef hexa_fwd_piter_< box2d > fwd_piter**
FIXME : should it be in box2d_h? Forward Site_Iterator associated type.
- **typedef image2d< V >::lvalue lvalue**
Lvalue associated type.
- **typedef point2d_h psite**
Point site type.

- **typedef image2d< V >::rvalue rvalue**
Return type of read-only access.
- **typedef hexa< tag::image_< image2d< V > >> skeleton**
Skeleton.
- **typedef image2d< V >::value value**
Value associated type.

Public Member Functions

- **const box2d_h & domain () const**
Give the definition domain.
- **bool has (const psite &p) const**
Test if p belongs to the image domain.
- **image2d_h (int nrows, int ncols, unsigned bdr=border::thickness)**
Constructor with the numbers of rows and columns border thickness.
- **lvalue operator() (const point2d_h &p)**
Read-write access of pixel value at hexa point site p.
- **rvalue operator() (const point2d_h &p) const**
Read-only access of pixel value at hexa point site p.

10.209.1 Detailed Description

template<typename V> struct mln::image2d_h< V >

2d image based on an hexagonal mesh.

Definition at line 50 of file image2d_h.hh.

10.209.2 Member Typedef Documentation

10.209.2.1 typedef hexa_bkd_piter_<box2d> mln::hexa< image2d< V > >::bkd_piter [inherited]

FIXME : should it be in box2d_h? Backward Site_Iterator associated type.

Definition at line 140 of file hexa.hh.

10.209.2.2 typedef hexa_fwd_piter_<box2d> mln::hexa< image2d< V > >::fwd_piter [inherited]

FIXME : should it be in box2d_h? Forward Site_Iterator associated type.

Definition at line 136 of file hexa.hh.

10.209.2.3 `typedef image2d< V > ::lvalue mln::hexa< image2d< V > >::lvalue [inherited]`

Lvalue associated type.

Definition at line 126 of file hexa.hh.

10.209.2.4 `template<typename V > typedef point2d_h mln::image2d_h< V >::psite`

Point site type.

Reimplemented from [mln::hexa< image2d< V > >](#).

Definition at line 56 of file image2d_h.hh.

10.209.2.5 `typedef image2d< V > ::rvalue mln::hexa< image2d< V > >::rvalue [inherited]`

Return type of read-only access.

Definition at line 129 of file hexa.hh.

10.209.2.6 `typedef hexa< tag::image_<image2d< V > > > mln::hexa< image2d< V > >::skelton [inherited]`

Skeleton.

Definition at line 120 of file hexa.hh.

10.209.2.7 `typedef image2d< V > ::value mln::hexa< image2d< V > >::value [inherited]`

Value associated type.

Definition at line 123 of file hexa.hh.

10.209.3 Constructor & Destructor Documentation**10.209.3.1 `template<typename V > mln::image2d_h< V >::image2d_h(int nrows, int ncols, unsigned bdr = border::thickness) [inline]`**

Constructor with the numbers of rows and columns border thickness.

image2d_h(3,6) will build this hexa image :

1 3 5 0 2 4 ----- 0| x x x | 2| x x x | 4| x x x

Definition at line 82 of file image2d_h.hh.

10.209.4 Member Function Documentation**10.209.4.1 `const box2d_h& mln::hexa< image2d< V > >::domain() const [inherited]`**

Give the definition domain.

10.209.4.2 bool mln::hexa< image2d< V > >::has (const psite & p) const [inherited]

Test if p belongs to the image domain.

10.209.4.3 rvalue mln::hexa< image2d< V > >::operator() (const point2d_h & p) const [inherited]

Read-only access of pixel value at hexa point site p.

10.209.4.4 lvalue mln::hexa< image2d< V > >::operator() (const point2d_h & p) [inherited]


Read-write access of pixel value at hexa point site p.

10.210 mln::image3d< T > Struct Template Reference

Basic 3D image class.

```
#include <image3d.hh>
```

Inheritance diagram for mln::image3d< T >:



Public Types

- **typedef T & lvalue**
Return type of read-write access.
- **typedef const T & rvalue**
Return type of read-only access.
- **typedef image3d< tag::value_< T > > skeleton**
Skeleton.
- **typedef T value**

Value associated type.

Public Member Functions

- `const box3d & bbox () const`
Give the bounding box domain.
- `unsigned border () const`
Give the border thickness.
- `const T * buffer () const`
Give a hook to the value buffer.
- `T * buffer ()`
Give a hook to the value buffer.
- `int delta_index (const dpoint3d &dp) const`
*Fast *Image* method.*
- `const box3d & domain () const`
Give the definition domain.
- `const T & element (unsigned i) const`
*Read-only access to the image value located at index *i*.*
- `T & element (unsigned i)`
*Read-write access to the image value located at index *i*.*
- `bool has (const point3d &p) const`
*Test if *p* is valid.*
- `image3d (const box3d &b, unsigned bdr=border::thickness)`
Constructor with a box and the border thickness (default is 3).
- `image3d ()`
Constructor without argument.
- `image3d (int nslis, int nrows, int ncols, unsigned bdr=border::thickness)`
Constructor with the numbers of indexes and the border thickness.
- `unsigned ncols () const`
Give the number of columns.
- `unsigned nelements () const`
Give the number of cells (points including border ones).
- `unsigned nrows () const`
Give the number of rows.

- `unsigned nslis () const`
Give the number of slices.
- `const T & operator() (const point3d &p) const`
Read-only access to the image value located at point p.
- `T & operator() (const point3d &p)`
Read-write access to the image value located at point p.
- `point3d point_at_index (unsigned o) const`
Give the point corresponding to the offset o.
- `const box3d & vbox () const`
virtual box, i.e., box including the virtual border

10.210.1 Detailed Description

`template<typename T> struct mln::image3d< T >`

Basic 3D image class. The parameter T is the type of pixel values. This image class stores data in memory and has a virtual border with constant thickness around data.

Definition at line 130 of file core/image/image3d.hh.

10.210.2 Member Typedef Documentation

10.210.2.1 template<typename T> typedef T& mln::image3d< T >::lvalue

Return type of read-write access.

Definition at line 153 of file core/image/image3d.hh.

10.210.2.2 template<typename T> typedef const T& mln::image3d< T >::rvalue

Return type of read-only access.

Definition at line 150 of file core/image/image3d.hh.

10.210.2.3 template<typename T> typedef image3d< tag::value_< T > > mln::image3d< T >::skeleton

Skeleton.

Definition at line 157 of file core/image/image3d.hh.

10.210.2.4 template<typename T> typedef T mln::image3d< T >::value

`Value` associated type.

Definition at line 147 of file core/image/image3d.hh.

10.210.3 Constructor & Destructor Documentation

10.210.3.1 template<typename T> mln::image3d< T >::image3d() [inline]

Constructor without argument.

Definition at line 389 of file core/image/image3d.hh.

10.210.3.2 template<typename T> mln::image3d< T >::image3d(const box3d & b, unsigned bdr = border::thickness) [inline]

Constructor with a box and the border thickness (default is 3).

Definition at line 395 of file core/image/image3d.hh.

10.210.3.3 template<typename T> mln::image3d< T >::image3d(int nslis, int nrows, int ncols, unsigned bdr = border::thickness) [inline]

Constructor with the numbers of indexes and the border thickness.

Definition at line 402 of file core/image/image3d.hh.

References mln::make::box3d().

10.210.4 Member Function Documentation

10.210.4.1 template<typename T> const box3d & mln::image3d< T >::bbox() const [inline]

Give the bounding box domain.

Definition at line 428 of file core/image/image3d.hh.

10.210.4.2 template<typename T> unsigned mln::image3d< T >::border() const [inline]

Give the border thickness.

Definition at line 446 of file core/image/image3d.hh.

10.210.4.3 template<typename T> const T * mln::image3d< T >::buffer() const [inline]

Give a hook to the value buffer.

Definition at line 554 of file core/image/image3d.hh.

10.210.4.4 template<typename T> T * mln::image3d< T >::buffer() [inline]

Give a hook to the value buffer.

Definition at line 563 of file core/image/image3d.hh.

10.210.4.5 template<typename T > int mln::image3d< T >::delta_index (const dpoint3d & dp) const [inline]

Fast [Image](#) method.

Give the offset corresponding to the delta-point *dp*.

Definition at line 572 of file core/image/image3d.hh.

10.210.4.6 template<typename T > const box3d & mln::image3d< T >::domain () const [inline]

Give the definition domain.

Definition at line 419 of file core/image/image3d.hh.

Referenced by mln::accu::stat::operator==().

10.210.4.7 template<typename T > const T & mln::image3d< T >::element (unsigned i) const [inline]

Read-only access to the image value located at index *i*.

Definition at line 491 of file core/image/image3d.hh.

References mln::image3d< T >::nelements().

10.210.4.8 template<typename T > T & mln::image3d< T >::element (unsigned i) [inline]

Read-write access to the image value located at index *i*.

Definition at line 500 of file core/image/image3d.hh.

References mln::image3d< T >::nelements().

10.210.4.9 template<typename T > bool mln::image3d< T >::has (const point3d & p) const [inline]

Test if *p* is valid.

Definition at line 464 of file core/image/image3d.hh.

Referenced by mln::image3d< T >::operator()().

10.210.4.10 template<typename T > unsigned mln::image3d< T >::ncols () const [inline]

Give the number of columns.

Definition at line 545 of file core/image/image3d.hh.

10.210.4.11 template<typename T > unsigned mln::image3d< T >::nelements () const [inline]

Give the number of cells (points including border ones).

Definition at line 455 of file core/image/image3d.hh.

Referenced by `mln::image3d< T >::element()`, and `mln::image3d< T >::point_at_index()`.

10.210.4.12 template<typename T> unsigned mln::image3d< T >::nrows() const [inline]

Give the number of rows.

Definition at line 536 of file core/image/image3d.hh.

10.210.4.13 template<typename T> unsigned mln::image3d< T >::nslis() const [inline]

Give the number of slices.

Definition at line 527 of file core/image/image3d.hh.

10.210.4.14 template<typename T> T & mln::image3d< T >::operator()(const point3d & p) [inline]

Read-write access to the image value located at point `p`.

Definition at line 482 of file core/image/image3d.hh.

References `mln::image3d< T >::has()`.

10.210.4.15 template<typename T> const T & mln::image3d< T >::operator()(const point3d & p) const [inline]

Read-only access to the image value located at point `p`.

Definition at line 473 of file core/image/image3d.hh.

References `mln::image3d< T >::has()`.

10.210.4.16 template<typename T> point3d mln::image3d< T >::point_at_index(unsigned o) const [inline]

Give the point corresponding to the offset `o`.

Definition at line 583 of file core/image/image3d.hh.

References `mln::image3d< T >::nelements()`.

10.210.4.17 template<typename T> const box3d & mln::image3d< T >::vbbox() const [inline]

virtual box, i.e., box including the virtual border

Definition at line 437 of file core/image/image3d.hh.

10.211 mln::image_if< I, F > Struct Template Reference

[Image](#) which domain is restricted by a function 'site -> Boolean'.

```
#include <image_if.hh>

Inherits image_domain_morpher< I, p_if< I::domain_t, F >, image_if< I, F > >.
```

Public Types

- **typedef image_if< tag::image_< I >, tag::function_< F > > skeleton**
Skeleton.

Public Member Functions

- **const p_if< typename I::domain_t, F > & domain () const**
Give the definition domain.
- **image_if (I &ima, const F &f)**
*Constructor from an image *ima* and a predicate *f*.*
- **image_if ()**
Constructor without argument.
- **operator image_if< const I, F > () const**
Const promotion via conversion.

10.211.1 Detailed Description

template<typename I, typename F> struct mln::image_if< I, F >

Image which domain is restricted by a function 'site -> Boolean'.

Definition at line 93 of file image_if.hh.

10.211.2 Member Typedef Documentation

10.211.2.1 template<typename I, typename F> typedef image_if< tag::image_<I>, tag::function_<F> > mln::image_if< I, F >::skeleton

Skeleton.

Definition at line 98 of file image_if.hh.

10.211.3 Constructor & Destructor Documentation

10.211.3.1 template<typename I , typename F > mln::image_if< I, F >::image_if () **[inline]**

Constructor without argument.

Definition at line 188 of file image_if.hh.

10.211.3.2 template<typename I , typename F > mln::image_if< I, F >::image_if(I & *ima*, const F & *f*) [inline]

Constructor from an image *ima* and a predicate *f*.

Definition at line 194 of file image_if.hh.

10.211.4 Member Function Documentation

10.211.4.1 template<typename I , typename F > const p_if< typename I::domain_t, F > & mln::image_if< I, F >::domain() const [inline]

Give the definition domain.

Definition at line 211 of file image_if.hh.

10.211.4.2 template<typename I , typename F > mln::image_if< I, F >::operator image_if< const I, F >() const [inline]

Const promotion via conversion.

Definition at line 219 of file image_if.hh.

10.212 mln::interpolated< I, F > Struct Template Reference

Makes the underlying image being accessed with floating coordinates.

```
#include <interpolated.hh>
```

Inherits image_identity< I, I::domain_t, interpolated< I, F > >.

Public Types

- **typedef I::lvalue lvalue**

Return type of read-write access.

- **typedef I::psite psite**

Point_Site associated type.

- **typedef I::rvalue rvalue**

Return type of read-only access.

- **typedef interpolated< tag::image_< I >, F > skeleton**

Skeleton.

- **typedef I::value value**

Value associated type.

Public Member Functions

- template<typename C >
bool **has** (const mln::algebra::vec< I::psite::dim, C > &v) const

Test if a pixel value is accessible at v.

- **interpolated** (I &ima)

Constructors.

- bool **is_valid** () const

Test if this image has been initialized.

10.212.1 Detailed Description

template<typename I, template< class > class F> struct mln::interpolated< I, F >

Makes the underlying image being accessed with floating coordinates.

Definition at line 84 of file interpolated.hh.

10.212.2 Member Typedef Documentation

**10.212.2.1 template<typename I , template< class > class F> typedef I ::lvalue
mln::interpolated< I, F >::lvalue**

Return type of read-write access.

Definition at line 98 of file interpolated.hh.

10.212.2.2 template<typename I , template< class > class F> typedef I ::psite mln::interpolated< I, F >::psite

[Point_Site](#) associated type.

Definition at line 92 of file interpolated.hh.

**10.212.2.3 template<typename I , template< class > class F> typedef I ::rvalue
mln::interpolated< I, F >::rvalue**

Return type of read-only access.

Definition at line 101 of file interpolated.hh.

10.212.2.4 template<typename I , template< class > class F> typedef interpolated< tag::image_<I>, F > mln::interpolated< I, F >::skeleton

Skeleton.

Definition at line 104 of file interpolated.hh.

10.212.2.5 template<typename I , template< class > class F> typedef I ::value mln::interpolated< I, F >::value

[Value](#) associated type.

Definition at line 95 of file interpolated.hh.

10.212.3 Constructor & Destructor Documentation

10.212.3.1 template<typename I , template< class > class F> mln::interpolated< I, F >::interpolated (I & *ima*) [inline]

Constructors.

FIXME: don't we want a 'const' here?

Definition at line 156 of file interpolated.hh.

10.212.4 Member Function Documentation

10.212.4.1 template<typename I , template< class > class F> template<typename C > bool mln::interpolated< I, F >::has (const mln::algebra::vec< I::psite::dim, C > & *v*) const [inline]

Test if a pixel value is accessible at v.

Definition at line 189 of file interpolated.hh.

10.212.4.2 template<typename I , template< class > class F> bool mln::interpolated< I, F >::is_valid () const [inline]

Test if this image has been initialized.

Definition at line 180 of file interpolated.hh.

10.213 mln::io::dicom::dicom_header Struct Reference

Store dicom file header.

```
#include <get_header.hh>
```

10.213.1 Detailed Description

Store dicom file header.

Definition at line 59 of file dicom/get_header.hh.

10.214 mln::io::dump::dump_header Struct Reference

Store dump file header.

```
#include <get_header.hh>
```

10.214.1 Detailed Description

Store dump file header.

Definition at line 53 of file dump/get_header.hh.

10.215 mln::io::fld::fld_header Struct Reference

Define the header structure of an AVS field data file.

```
#include <header.hh>
```

10.215.1 Detailed Description

Define the header structure of an AVS field data file.

Definition at line 45 of file header.hh.

10.216 mln::io::raw::raw_header Struct Reference

Store raw file header.

```
#include <get_header.hh>
```

10.216.1 Detailed Description

Store raw file header.


Definition at line 53 of file raw/get_header.hh.

10.217 mln::Iterator< E > Struct Template Reference

Base class for implementation classes that are iterators.

```
#include <iterator.hh>
```

Inheritance diagram for mln::Iterator< E >:



Public Member Functions

- void next ()

Go to the next element.

10.217.1 Detailed Description

```
template<typename E> struct mln::Iterator< E >
```

Base class for implementation classes that are iterators.

See also

[mln::doc::Iterator](#) for a complete documentation of this class contents.

Definition at line 75 of file iterator.hh.

10.217.2 Member Function Documentation

10.217.2.1 template<typename E > void mln::Iterator< E >::next()

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.


Definition at line 102 of file iterator.hh.

10.218 mln::labeled_image< I > Class Template Reference

Morpher providing an improved interface for labeled image.

```
#include <labeled_image.hh>
```

Inheritance diagram for mln::labeled_image< I >:



Public Types

- **typedef accu::shape::bbox< typename I::psite >::result bbox_t**
Type of the bounding component bounding boxes.
- **typedef labeled_image< tag::image_< I > > skeleton**
Skeleton.

Public Member Functions

- **const bbox_t & bbox (const typename I::value &label) const**
Return the bounding box of the component label.
- **const util::array< bbox_t > & bboxes () const**
Return the component bounding boxes.
- **I::value nlables () const**
Return the number of labels.;
- **p_if< mln_box(I), fun::eq_v2b_expr_< pw::value_< I >, pw::cst_< typename I::value > > > > subdomain (const typename I::value &label) const**
Return the domain of the component with label label.
- **labeled_image ()**
Constructors
Constructor without argument.
- **labeled_image (const I &ima, const typename I::value &nlables)**
Constructor from an image ima and the number of labels nlables.
- **labeled_image (const I &ima, const typename I::value &nlables, const util::array< mln_box(I)> &bboxes)**
Constructor from an image ima, the number of labels nlables and the object bounding boxes.
- **void relabel (const Function_v2v< F > &f)**
Relabel according to a function.
- **void relabel (const Function_v2b< F > &f)**
Labels may be removed.

Protected Member Functions

- **void update_data (const fun::i2v::array< typename I::value > &relabel_fun)**
Update bounding boxes information.

10.218.1 Detailed Description

template<typename I> class mln::labeled_image< I >

Morpher providing an improved interface for labeled image.

Template Parameters

I The label image type.

This image type allows to access every site set at a given label.

This image type guarantees that labels are contiguous (from 1 to n).

Definition at line 105 of file labeled_image.hh.

10.218.2 Member Typedef Documentation

10.218.2.1 typedef accu::shape::bbox<typename I ::psite>::result mln::labeled_image_base< I, labeled_image< I > >::bbox_t [inherited]

Type of the bounding component bounding boxes.

Definition at line 124 of file labeled_image_base.hh.

10.218.2.2 template<typename I> typedef labeled_image< tag::image_<I> > mln::labeled_image< I >::skeleton

Skeleton.

Definition at line 113 of file labeled_image.hh.

10.218.3 Constructor & Destructor Documentation

10.218.3.1 template<typename I > mln::labeled_image< I >::labeled_image() [inline]

Constructors

Constructor without argument.

Definition at line 193 of file labeled_image.hh.

10.218.3.2 template<typename I > mln::labeled_image< I >::labeled_image(const I & ima, const typename I::value & nlabels) [inline]

Constructor from an image *ima* and the number of labels *nlabels*.

Definition at line 199 of file labeled_image.hh.

10.218.3.3 template<typename I > mln::labeled_image< I >::labeled_image(const I & ima, const typename I::value & nlabels, const util::array< mln_box(I)> & bboxes) [inline]

Constructor from an image *ima*, the number of labels *nlabels* and the object bounding boxes.

Definition at line 206 of file labeled_image.hh.

References mln::data::compute().

10.218.4 Member Function Documentation

10.218.4.1 const bbox_t& mln::labeled_image_base< I, labeled_image< I > >::bbox (const typename I::value & *label*) const [inherited]

Return the bounding box of the component *label*.

10.218.4.2 const util::array<bbox_t>& mln::labeled_image_base< I, labeled_image< I > >::bboxes () const [inherited]

Return the component bounding boxes.

10.218.4.3 I ::value mln::labeled_image_base< I, labeled_image< I > >::nlabels () const [inherited]

Return the number of labels;

10.218.4.4 void mln::labeled_image_base< I, labeled_image< I > >::relabel (const Function_v2b< F > & *f*) [inherited]

Labels may be removed.

This overload make sure the labeling is still contiguous.

10.218.4.5 void mln::labeled_image_base< I, labeled_image< I > >::relabel (const Function_v2v< F > & *f*) [inherited]

Relabel according to a function.

Merge or delete labels according to the given function. This method ensures that the labeling remains contiguous.

10.218.4.6 p_if<mln_box(I), fun::eq_v2b_expr<pw::value<I>, pw::cst_<typename I ::value>> > mln::labeled_image_base< I, labeled_image< I > >::subdomain (const typename I::value & *label*) const [inherited]

Return the domain of the component with label *label*.

10.218.4.7 void mln::labeled_image_base< I, labeled_image< I > >::update_data (const fun::i2v::array< typename I::value > & *relabel_fun*) [protected, inherited]


Update bounding boxes information.

10.219 mln::labeled_image_base< I, E > Class Template Reference

Base class Morpher providing an improved interface for labeled image.

```
#include <labeled_image_base.hh>
```

Inheritance diagram for mln::labeled_image_base< I, E >:



Public Types

- **typedef accu::shape::bbox< typename I::psite >::result bbox_t**
Type of the bounding component bounding boxes.

Public Member Functions

- **const bbox_t & bbox**(const typename I::value &**label**) const
*Return the bounding box of the component **label**.*
- **const util::array< bbox_t > & bboxes**() const
Return the component bounding boxes.
- **I::value nlabels**() const
Return the number of labels;.
- **p_if< mln_box(I), fun::eq_v2b_expr< pw::value_< I >, pw::cst_< typename I::value > > > subdomain**(const typename I::value &**label**) const
*Return the domain of the component with label **label**.*
- **labeled_image_base**()

Constructors
Constructor without argument.

- template<typename F >
void **relabel** (const **Function_v2v**< F > &f)
Relabel according to a function.

- template<typename F >
void **relabel** (const **Function_v2b**< F > &f)
Labels may be removed.

Protected Member Functions

- void **update_data** (const **fun::i2v::array**< typename I::value > &relabel_fun)
Update bounding boxes information.

10.219.1 Detailed Description

template<typename I, typename E> class mln::labeled_image_base< I, E >

Base class Morpher providing an improved interface for labeled image.

Template Parameters

I The label image type.

This image type allows to access every site set at a given label.

This image type guarantees that labels are contiguous (from 1 to n).

Definition at line 116 of file labeled_image_base.hh.

10.219.2 Member Typedef Documentation

10.219.2.1 template<typename I, typename E> typedef accu::shape::bbox<typename I ::psite>::result mln::labeled_image_base< I, E >::bbox_t

Type of the bounding component bounding boxes.

Definition at line 124 of file labeled_image_base.hh.

10.219.3 Constructor & Destructor Documentation

10.219.3.1 template<typename I , typename E > mln::labeled_image_base< I, E >::labeled_image_base() [inline]

Constructors

Constructor without argument.

Definition at line 217 of file labeled_image_base.hh.

10.219.4 Member Function Documentation

10.219.4.1 template<typename I, typename E > const labeled_image_base< I, E >::bbox_t & mln::labeled_image_base< I, E >::bbox (const typename I::value & *label*) const

Return the bounding box of the component *label*.

Definition at line 305 of file labeled_image_base.hh.

Referenced by mln::labeled_image_base< I, E >::subdomain().

10.219.4.2 template<typename I , typename E > const util::array< typename labeled_image_base< I, E >::bbox_t > & mln::labeled_image_base< I, E >::bboxes () const

Return the component bounding boxes.

Definition at line 313 of file labeled_image_base.hh.

10.219.4.3 template<typename I , typename E > I::value mln::labeled_image_base< I, E >::nlabs () const [inline]

Return the number of labels;.

Definition at line 273 of file labeled_image_base.hh.

10.219.4.4 template<typename I , typename E > template<typename F > void mln::labeled_image_base< I, E >::relabel (const Function_v2b< F > & *f*) [inline]

Labels may be removed.

This overload make sure the labeling is still contiguous.

Definition at line 252 of file labeled_image_base.hh.

References mln::labeling::relabel_inplace(), mln::make::relabelfun(), and mln::labeled_image_base< I, E >::update_data().

10.219.4.5 template<typename I , typename E > template<typename F > void mln::labeled_image_base< I, E >::relabel (const Function_v2v< F > & *f*) [inline]

Relabel according to a function.

Merge or delete labels according to the given function. This method ensures that the labeling remains contiguous.

Definition at line 226 of file labeled_image_base.hh.

References mln::labeling::relabel_inplace(), mln::make::relabelfun(), and mln::labeled_image_base< I, E >::update_data().

10.219.4.6 template<typename I, typename E > p_if< mln_box(I), fun::eq_v2b_expr_< pw::value_< I >, pw::est_< typename I::value >>> mln::labeled_image_base< I, E >::subdomain (const typename I::value & *label*) const

Return the domain of the component with label *label*.

Definition at line 322 of file labeled_image_base.hh.

References mln::labeled_image_base< I, E >::bbox().

10.219.4.7 template<typename I, typename E > void mln::labeled_image_base< I, E >::update_data (const fun::i2v::array< typename I::value > & *relabel_fun*) [protected]

Update bounding boxes information.

Definition at line 281 of file labeled_image_base.hh.

References mln::util::array< T >::size().

Referenced by mln::labeled_image_base< I, E >::relabel().

10.220 mln::lazy_image< I, F, B > Struct Template Reference

[Image](#) values are computed on the fly.

```
#include <lazy_image.hh>
```

Inherits image_identity< mln::trait::ch_value< I, F::result >::ret, I::domain_t, lazy_image< I, F, B > >.

Public Types

- **typedef F::result lvalue**
Return type of read-write access.
- **typedef F::result rvalue**
Return type of read access.
- **typedef lazy_image< tag::image_< I >, F, B > skeleton**
Skeleton.

Public Member Functions

- **const box< typename I::psite > & domain () const**
Return domain of lazyd_image.
- **bool has (const typename I::psite &) const**
Test if a pixel value is accessible at p.
- **lazy_image (const F &fun, const B &box)**
Constructors.

- [lazy_image \(\)](#)

Constructors.

- [F::result operator\(\) \(const typename F::input &x\) const](#)

Read-only access of pixel value at F::input x.

- [lvalue operator\(\) \(const typename I::psite &p\)](#)

Read and "write if possible" access of pixel value at point site p.

- [F::result operator\(\) \(const typename F::input &x\) const](#)

Read and "write if possible" access of pixel value at F::input x.

- [rvalue operator\(\) \(const typename I::psite &p\) const](#)

Read-only access of pixel value at point site p.

10.220.1 Detailed Description

template<typename I, typename F, typename B> struct mln::lazy_image< I, F, B >

Image values are computed on the fly. The parameter **I** is the type of image. The parameter **F** is the type of function. The parameter **B** is the type of box.

This image class take a functor **fun** and a box **box**. Access to **ima(p)** where **p** include **box** return **fun(b)** lazily.

Definition at line 92 of file **lazy_image.hh**.

10.220.2 Member Typedef Documentation

10.220.2.1 template<typename I, typename F, typename B> typedef F ::result mln::lazy_image< I, F, B >::lvalue

Return type of read-write access.

Definition at line 104 of file **lazy_image.hh**.

10.220.2.2 template<typename I, typename F, typename B> typedef F ::result mln::lazy_image< I, F, B >::rvalue

Return type of read access.

Definition at line 101 of file **lazy_image.hh**.

10.220.2.3 template<typename I, typename F, typename B> typedef lazy_image< tag::image_<I>, F, B > mln::lazy_image< I, F, B >::skeleton

Skeleton.

Definition at line 107 of file **lazy_image.hh**.

10.220.3 Constructor & Destructor Documentation

10.220.3.1 template<typename I, typename F, typename B> mln::lazy_image< I, F, B >::lazy_image()

Constructors.

10.220.3.2 template<typename I , typename F, typename B> mln::lazy_image< I, F, B >::lazy_image(const F & fun, const B & box) [inline]

Constructors.

Definition at line 161 of file lazy_image.hh.

10.220.4 Member Function Documentation

10.220.4.1 template<typename I , typename F, typename B > const box< typename I::psite > & mln::lazy_image< I, F, B >::domain() const [inline]

Return domain of lazyd_image.

Definition at line 226 of file lazy_image.hh.

10.220.4.2 template<typename I, typename F , typename B > bool mln::lazy_image< I, F, B >::has(const typename I::psite & p) const [inline]

Test if a pixel value is accessible at p.

Definition at line 175 of file lazy_image.hh.

10.220.4.3 template<typename I, typename F, typename B > lazy_image< I, F, B >::rvalue mln::lazy_image< I, F, B >::operator() (const typename I::psite & p) const [inline]

Read-only access of pixel value at point site p.

Definition at line 210 of file lazy_image.hh.

10.220.4.4 template<typename I , typename F, typename B > F::result mln::lazy_image< I, F, B >::operator()(const typename F::input & x) [inline]

Read and "write if possible" access of pixel value at F::input x.

Definition at line 197 of file lazy_image.hh.

10.220.4.5 template<typename I , typename F, typename B > F::result mln::lazy_image< I, F, B >::operator()(const typename F::input & x) const [inline]

Read-only access of pixel value at F::input x.

Definition at line 183 of file lazy_image.hh.

**10.220.4.6 template<typename I, typename F, typename B> lazy_image< I, F, B >::lvalue
mln::lazy_image< I, F, B >::operator() (const typename I::psite & p) [inline]**

Read and "write if possible" access of pixel value at point site p.


Definition at line 218 of file lazy_image.hh.

10.221 mln::Literal< E > Struct Template Reference

Base class for implementation classes of literals.

```
#include <literal.hh>
```

Inheritance diagram for mln::Literal< E >:



10.221.1 Detailed Description

```
template<typename E> struct mln::Literal< E >
```

Base class for implementation classes of literals.

See also

[mln::doc::Literal](#) for a complete documentation of this class contents.


Definition at line 56 of file [literal.hh](#).

10.222 mln::literal::black_t Struct Reference

Type of literal black.

```
#include <black.hh>
```

Inheritance diagram for mln::literal::black_t:



10.222.1 Detailed Description

Type of literal black.


Definition at line 43 of file [black.hh](#).

10.223 mln::literal::blue_t Struct Reference

Type of literal blue.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::blue_t:



10.223.1 Detailed Description

Type of literal blue.


Definition at line 53 of file colors.hh.

10.224 mln::literal::brown_t Struct Reference

Type of literal brown.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::brown_t:



10.224.1 Detailed Description

Type of literal brown.


Definition at line 58 of file colors.hh.

10.225 mln::literal::cyan_t Struct Reference

Type of literal cyan.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::cyan_t:



10.225.1 Detailed Description

Type of literal cyan.


Definition at line 93 of file colors.hh.

10.226 mln::literal::green_t Struct Reference

Type of literal green.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::green_t:



10.226.1 Detailed Description

Type of literal green.


Definition at line 48 of file colors.hh.

10.227 mln::literal::identity_t Struct Reference

Type of literal identity.

```
#include <identity.hh>
```

Inheritance diagram for mln::literal::identity_t:



10.227.1 Detailed Description

Type of literal identity.


Definition at line 43 of file `identity.hh`.

10.228 mln::literal::light_gray_t Struct Reference

Type of literal grays.

```
#include <grays.hh>
```

Inheritance diagram for mln::literal::light_gray_t:



10.228.1 Detailed Description

Type of literal grays.


Definition at line 43 of file `grays.hh`.

10.229 mln::literal::lime_t Struct Reference

Type of literal lime.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::lime_t:



10.229.1 Detailed Description

Type of literal lime.


Definition at line 63 of file colors.hh.

10.230 mln::literal::magenta_t Struct Reference

Type of literal magenta.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::magenta_t:



10.230.1 Detailed Description

Type of literal magenta.


Definition at line 98 of file colors.hh.

10.231 mln::literal::max_t Struct Reference

Type of literal max.

```
#include <max.hh>
```

Inheritance diagram for mln::literal::max_t:



10.231.1 Detailed Description

Type of literal max.


Definition at line 44 of file `literal/max.hh`.

10.232 mln::literal::min_t Struct Reference

Type of literal min.

```
#include <min.hh>
```

Inheritance diagram for mln::literal::min_t:



10.232.1 Detailed Description

Type of literal min.


Definition at line 44 of file `literal/min.hh`.

10.233 mln::literal::olive_t Struct Reference

Type of literal olive.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::olive_t:



10.233.1 Detailed Description

Type of literal olive.


Definition at line 108 of file colors.hh.

10.234 mln::literal::one_t Struct Reference

Type of literal one.

```
#include <one.hh>
```

Inheritance diagram for mln::literal::one_t:



10.234.1 Detailed Description

Type of literal one.


Definition at line 44 of file one.hh.

10.235 mln::literal::orange_t Struct Reference

Type of literal orange.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::orange_t:



10.235.1 Detailed Description

Type of literal orange.


Definition at line 68 of file colors.hh.

10.236 mln::literal::origin_t Struct Reference

Type of literal origin.

```
#include <origin.hh>
```

Inheritance diagram for mln::literal::origin_t:



10.236.1 Detailed Description

Type of literal origin.


Definition at line 44 of file `origin.hh`.

10.237 mln::literal::pink_t Struct Reference

Type of literal pink.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::pink_t:



10.237.1 Detailed Description

Type of literal pink.


Definition at line 73 of file colors.hh.

10.238 mln::literal::purple_t Struct Reference

Type of literal purple.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::purple_t:



10.238.1 Detailed Description

Type of literal purple.


Definition at line 78 of file colors.hh.

10.239 mln::literal::red_t Struct Reference

Type of literal red.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::red_t:



10.239.1 Detailed Description

Type of literal red.


Definition at line 43 of file colors.hh.

10.240 mln::literal::teal_t Struct Reference

Type of literal teal.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::teal_t:



10.240.1 Detailed Description

Type of literal teal.


Definition at line 83 of file colors.hh.

10.241 mln::literal::violet_t Struct Reference

Type of literal violet.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::violet_t:



10.241.1 Detailed Description

Type of literal violet.


Definition at line 88 of file colors.hh.

10.242 mln::literal::white_t Struct Reference

Type of literal white.

```
#include <white.hh>
```

Inheritance diagram for mln::literal::white_t:



10.242.1 Detailed Description

Type of literal white.


Definition at line 43 of file `white.hh`.

10.243 mln::literal::yellow_t Struct Reference

Type of literal yellow.

```
#include <colors.hh>
```

Inheritance diagram for mln::literal::yellow_t:



10.243.1 Detailed Description

Type of literal yellow.


Definition at line 103 of file colors.hh.

10.244 mln::literal::zero_t Struct Reference

Type of literal zero.

```
#include <zero.hh>
```

Inheritance diagram for mln::literal::zero_t:



10.244.1 Detailed Description

Type of literal zero.


Definition at line 46 of file `zero.hh`.

10.245 mln::Mesh< E > Struct Template Reference

Base class for implementation classes of meshes.

```
#include <mesh.hh>
```

Inheritance diagram for mln::Mesh< E >:



10.245.1 Detailed Description

template<typename E> struct mln::Mesh< E >

Base class for implementation classes of meshes.

See also

[mln::doc::Mesh](#) for a complete documentation of this class contents.


Definition at line 45 of file [mesh.hh](#).

10.246 mln::Meta_Accumulator< E > Struct Template Reference

Base class for implementation of meta accumulators.

```
#include <meta_accumulator.hh>
```

Inheritance diagram for mln::Meta_Accumulator< E >:



10.246.1 Detailed Description

template<typename E> struct mln::Meta_Accumulator< E >

Base class for implementation of meta accumulators. The parameter *E* is the exact type.

See also

[mln::doc::Meta_Accumulator](#) for a complete documentation of this class contents.


Definition at line 103 of file `meta_accumulator.hh`.

10.247 mln::Meta_Function< E > Struct Template Reference

Base class for implementation of meta functions.

```
#include <meta_function.hh>
```

Inheritance diagram for `mln::Meta_Function< E >`:



10.247.1 Detailed Description

`template<typename E> struct mln::Meta_Function< E >`

Base class for implementation of meta functions. The parameter *E* is the exact type.

See also

[mln::doc::Meta_Function](#) for a complete documentation of this class contents.


Definition at line 78 of file `meta_function.hh`.

10.248 mln::Meta_Function_v2v< E > Struct Template Reference

Base class for implementation of function-objects from value to value.

```
#include <meta_function.hh>
```

Inheritance diagram for mln::Meta_Function_v2v< E >:



10.248.1 Detailed Description

```
template<typename E> struct mln::Meta_Function_v2v< E >
```

Base class for implementation of function-objects from value to value. The parameter *E* is the exact type.


Definition at line 98 of file meta_function.hh.

10.249 mln::Meta_Function_vv2v< E > Struct Template Reference

Base class for implementation of function-objects from value to value.

```
#include <meta_function.hh>
```

Inheritance diagram for mln::Meta_Function_vv2v< E >:



10.249.1 Detailed Description

```
template<typename E> struct mln::Meta_Function_vv2v< E >
```

Base class for implementation of function-objects from value to value. The parameter *E* is the exact type.
Definition at line 120 of file meta_function.hh.

10.250 mln::metal::ands< E1, E2, E3, E4, E5, E6, E7, E8 > Struct Template Reference

Ands type.

```
#include <ands.hh>
```

10.250.1 Detailed Description

```
template<typename E1, typename E2, typename E3, typename E4 = true_, typename E5 = true_,  
typename E6 = true_, typename E7 = true_, typename E8 = true_> struct mln::metal::ands< E1,  
E2, E3, E4, E5, E6, E7, E8 >
```

Ands type.

Definition at line 51 of file ands.hh.

10.251 mln::metal::converts_to< T, U > Struct Template Reference

"converts-to" check.

```
#include <converts_to.hh>
```

Inherited by mln::metal::converts_to< T *, U * >.

10.251.1 Detailed Description

```
template<typename T, typename U> struct mln::metal::converts_to< T, U >
```

"converts-to" check.


Definition at line 78 of file converts_to.hh.

10.252 mln::metal::equal< T1, T2 > Struct Template Reference

Definition of a static 'equal' test.

```
#include <equal.hh>
```

Inheritance diagram for `mln::metal::equal< T1, T2 >`:



10.252.1 Detailed Description

template<typename T1, typename T2> struct mln::metal::equal< T1, T2 >

Definition of a static 'equal' test. Check whether type T1 is exactly type T2.

Definition at line 49 of file equal.hh.

10.253 `mln::metal::goes_to< T, U >` Struct Template Reference

"goes-to" check.

```
#include <goes_to.hh>
```

10.253.1 Detailed Description

template<typename T, typename U> struct mln::metal::goes_to< T, U >

"goes-to" check. FIXME: Doc!

Definition at line 53 of file goes_to.hh.

10.254 `mln::metal::is< T, U >` Struct Template Reference

"is" check.

```
#include <is.hh>
```

10.254.1 Detailed Description

template<typename T, typename U> struct mln::metal::is< T, U >

"is" check. Check whether T inherits from U.

Definition at line 64 of file is.hh.

10.255 `mln::metal::is_a< T, M >` Struct Template Reference

"is_a" check.

```
#include <is_a.hh>
```

10.255.1 Detailed Description

`template<typename T, template< class > class M> struct mln::metal::is_a< T, M >`

"is_a" check. Check whether T inherits from _CONCEPT_ M.

Definition at line 95 of file `is_a.hh`.

10.256 `mln::metal::is_not< T, U >` Struct Template Reference

"is_not" check.

```
#include <is_not.hh>
```

10.256.1 Detailed Description

`template<typename T, typename U> struct mln::metal::is_not< T, U >`

"is_not" check. FIXME: Doc!

Definition at line 52 of file `is_not.hh`.

10.257 `mln::metal::is_not_a< T, M >` Struct Template Reference

"is_not_a" static Boolean expression.

```
#include <is_not_a.hh>
```

10.257.1 Detailed Description

`template<typename T, template< class > class M> struct mln::metal::is_not_a< T, M >`

"is_not_a" static Boolean expression.

Definition at line 48 of file `is_not_a.hh`.

10.258 `mln::mixed_neighb< W >` Class Template Reference

Adapter class from window to neighborhood.

```
#include <mixed_neighb.hh>
```

Inherits `neighb_base< W, mixed_neighb< W > >`, and `mlc_is_aW`.

Public Types

- `typedef mixed_neighb_bkd_niter< W > bkd_niter`
Backward site iterator associated type.
- `typedef mixed_neighb_fwd_niter< W > fwd_niter`
Forward site iterator associated type.
- `typedef fwd_niter niter`
Site iterator associated type.

Public Member Functions

- `mixed_neighb()`
Constructor without argument.
- `mixed_neighb(const W &win)`
Constructor from a window `win`.

10.258.1 Detailed Description

`template<typename W> class mln::mixed_neighb< W >`

Adapter class from window to neighborhood.

Definition at line 79 of file `mixed_neighb.hh`.

10.258.2 Member Typedef Documentation

10.258.2.1 `template<typename W> typedef mixed_neighb_bkd_niter<W> mln::mixed_neighb< W >::bkd_niter`

Backward site iterator associated type.

Definition at line 91 of file `mixed_neighb.hh`.

10.258.2.2 `template<typename W> typedef mixed_neighb_fwd_niter<W> mln::mixed_neighb< W >::fwd_niter`

Forward site iterator associated type.

Definition at line 88 of file `mixed_neighb.hh`.

10.258.2.3 `template<typename W> typedef fwd_niter mln::mixed_neighb< W >::niter`

`Site` iterator associated type.

Definition at line 94 of file `mixed_neighb.hh`.

10.258.3 Constructor & Destructor Documentation

10.258.3.1 template<typename W> mln::mixed_neighb<W>::mixed_neighb() [inline]

Constructor without argument.

Definition at line 158 of file mixed_neighb.hh.

10.258.3.2 template<typename W> mln::mixed_neighb<W>::mixed_neighb(const W & win) [inline]

Constructor from a window `win`.

Definition at line 164 of file mixed_neighb.hh.

10.259 mln::morpho::attribute::card< I > Class Template Reference

Cardinality accumulator class.

```
#include <card.hh>
```

Inherits base< unsigned, card< I > >.

Public Member Functions

- bool `is_valid()` const
Check whether this accu is able to return a result.
- void `take_as_init(const T &t)`
Take as initialization the value `t`.
- void `take_n_times(unsigned n, const T &t)`
Take `n` times the value `t`.
- unsigned `to_result()` const
Get the value of the accumulator.
- void `init()`
Manipulators.

10.259.1 Detailed Description

template<typename I> class mln::morpho::attribute::card< I >

Cardinality accumulator class.

Definition at line 80 of file morpho/attribute/card.hh.

10.259.2 Member Function Documentation

10.259.2.1 template<typename I> void mln::morpho::attribute::card< I >::init () [inline]

Manipulators.

Definition at line 128 of file morpho/attribute/card.hh.

10.259.2.2 template<typename I> bool mln::morpho::attribute::card< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 197 of file morpho/attribute/card.hh.

10.259.2.3 void mln::Accumulator< card< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.259.2.4 void mln::Accumulator< card< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.259.2.5 template<typename I> unsigned mln::morpho::attribute::card< I >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 189 of file morpho/attribute/card.hh.

10.260 mln::morpho::attribute::count_adjacent_vertices< I > Struct Template Reference

Count_Adjacent_Vertices accumulator class.

```
#include <count_adjacent_vertices.hh>
```

Inherits base< unsigned, count_adjacent_vertices< I > >.

Public Member Functions

- bool [is_valid \(\) const](#)

Check whether this accu is able to return a result.

- void `take_as_init` (const T &t)
Take as initialization the value t.
- void `take_n_times` (unsigned n, const T &t)
Take n times the value t.
- unsigned `to_result` () const
Get the value of the accumulator.
- void `init` ()
Manipulators.

10.260.1 Detailed Description

`template<typename I> struct mln::morpho::attribute::count_adjacent_vertices< I >`

Count_Adjacent_Vertices accumulator class. The parameter I is the image type on which the accumulator of pixels is built.

Definition at line 83 of file morpho/attribute/count_adjacent_vertices.hh.

10.260.2 Member Function Documentation

10.260.2.1 template<typename I> void mln::morpho::attribute::count_adjacent_vertices< I >::init () [inline]

Manipulators.

Definition at line 132 of file morpho/attribute/count_adjacent_vertices.hh.

10.260.2.2 template<typename I> bool mln::morpho::attribute::count_adjacent_vertices< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Definition at line 185 of file morpho/attribute/count_adjacent_vertices.hh.

10.260.2.3 void mln::Accumulator< count_adjacent_vertices< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.260.2.4 void mln::Accumulator< count_adjacent_vertices< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.260.2.5 template<typename I> unsigned mln::morpho::attribute::count_adjacent_vertices< I >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 169 of file morpho/attribute/count_adjacent_vertices.hh.

10.261 mln::morpho::attribute::height< I > Struct Template Reference

Height accumulator class.

```
#include <height.hh>
```

Inherits base<unsigned, height< I >>.

Public Member Functions

- unsigned [base_level\(\)](#) const

Get base & current level of the accumulator.

- bool [is_valid\(\)](#) const

Check whether this accu is able to return a result.

- void [take_as_init\(const T &t\)](#)

Take as initialization the value t.

- void [take_n_times\(unsigned n, const T &t\)](#)

Take n times the value t.

- unsigned [to_result\(\)](#) const

Get the value of the accumulator.

- void [init\(\)](#)

Manipulators.

10.261.1 Detailed Description

template<typename I> struct mln::morpho::attribute::height< I >

Height accumulator class. The parameter I is the image type on which the accumulator of pixels is built.

Definition at line 80 of file morpho/attribute/height.hh.

10.261.2 Member Function Documentation

10.261.2.1 template<typename I> unsigned mln::morpho::attribute::height< I >::base_level () const [inline]

Get base & current level of the accumulator.

Definition at line 214 of file morpho/attribute/height.hh.

10.261.2.2 template<typename I> void mln::morpho::attribute::height< I >::init () [inline]

Manipulators.

Definition at line 131 of file morpho/attribute/height.hh.

10.261.2.3 template<typename I> bool mln::morpho::attribute::height< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 231 of file morpho/attribute/height.hh.

Referenced by mln::morpho::attribute::height< I >::to_result().

10.261.2.4 void mln::Accumulator< height< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.261.2.5 void mln::Accumulator< height< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.261.2.6 template<typename I> unsigned mln::morpho::attribute::height< I >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 204 of file morpho/attribute/height.hh.

References mln::morpho::attribute::height< I >::is_valid().

10.262 mln::morpho::attribute::sharpness< I > Struct Template Reference

Sharpness accumulator class.

```
#include <sharpness.hh>
Inherits base< double, sharpness< I > >.
```

Public Member Functions

- `unsigned area () const`
Give the area of the component.
- `unsigned height () const`
Give the height.
- `bool is_valid () const`
Check whether this accu is able to return a result.
- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `double to_result () const`
Get the value of the accumulator.
- `unsigned volume () const`
Give the volume of the component.
- `void init ()`
Manipulators.

10.262.1 Detailed Description

`template<typename I> struct mln::morpho::attribute::sharpness< I >`

Sharpness accumulator class. The parameter `I` is the image type on which the accumulator of pixels is built.

Definition at line 80 of file sharpness.hh.

10.262.2 Member Function Documentation

10.262.2.1 `template<typename I> unsigned mln::morpho::attribute::sharpness< I >::area () const [inline]`

Give the area of the component.

Definition at line 190 of file sharpness.hh.

10.262.2.2 template<typename I> unsigned mln::morpho::attribute::sharpness< I >::height () const [inline]

Give the height.

Definition at line 206 of file sharpness.hh.

10.262.2.3 template<typename I> void mln::morpho::attribute::sharpness< I >::init () [inline]

Manipulators.

Definition at line 134 of file sharpness.hh.

10.262.2.4 template<typename I> bool mln::morpho::attribute::sharpness< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 214 of file sharpness.hh.

10.262.2.5 void mln::Accumulator< sharpness< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.262.2.6 void mln::Accumulator< sharpness< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.262.2.7 template<typename I> double mln::morpho::attribute::sharpness< I >::to_result () const [inline]

Get the value of the accumulator.

Definition at line 175 of file sharpness.hh.

10.262.2.8 template<typename I> unsigned mln::morpho::attribute::sharpness< I >::volume () const [inline]

Give the volume of the component.

Definition at line 198 of file sharpness.hh.

10.263 mln::morpho::attribute::sum< I, S > Class Template Reference

Suminality accumulator class.

```
#include <sum.hh>
```

Inherits base< S, sum< I, S > >.

Public Member Functions

- bool `is_valid () const`
Check whether this accu is able to return a result.
- void `set_value (const argument &v)`
Set the return value of the accumalator.
- void `take_as_init (const T &t)`
Take as initialization the value t.
- void `take_n_times (unsigned n, const T &t)`
Take n times the value t.
- S `to_result () const`
Get the value of the accumulator.
- void `untake (const argument &v)`
Untake a value from the accumulator.
- void `init ()`
Manipulators.

10.263.1 Detailed Description

```
template<typename I, typename S = typename mln::value::props< typename I ::value >::sum>
class mln::morpho::attribute::sum< I, S >
```

Suminality accumulator class.

Definition at line 80 of file morpho/attribute/sum.hh.

10.263.2 Member Function Documentation

10.263.2.1 template<typename I, typename S > void mln::morpho::attribute::sum< I, S >::init () [inline]

Manipulators.

Definition at line 137 of file morpho/attribute/sum.hh.

References mln::literal::zero.

10.263.2.2 template<typename I , typename S > bool mln::morpho::attribute::sum< I, S >::is_valid() const [inline]

Check whether this accu is able to return a result.

Return always true.

Definition at line 229 of file morpho/attribute/sum.hh.

10.263.2.3 template<typename I , typename S > void mln::morpho::attribute::sum< I, S >::set_value(const argument & v) [inline]

Set the return value of the accumalator.

Definition at line 205 of file morpho/attribute/sum.hh.

10.263.2.4 void mln::Accumulator< sum< I, S > >::take_as_init(const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.263.2.5 void mln::Accumulator< sum< I, S > >::take_n_times(unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.263.2.6 template<typename I , typename S > S mln::morpho::attribute::sum< I, S >::to_result() const [inline]

Get the value of the accumulator.

Definition at line 221 of file morpho/attribute/sum.hh.

10.263.2.7 template<typename I , typename S > void mln::morpho::attribute::sum< I, S >::untake(const argument & v) [inline]

Untake a value from the accumulator.

Definition at line 189 of file morpho/attribute/sum.hh.

10.264 mln::morpho::attribute::volume< I > Struct Template Reference

Volume accumulator class.

```
#include <volume.hh>
```

Inherits base< unsigned, volume< I > >.

Public Member Functions

- `unsigned area () const`
Give the area.
- `bool is_valid () const`
Check whether this accu is able to return a result.
- `void take_as_init (const T &t)`
Take as initialization the value t.
- `void take_n_times (unsigned n, const T &t)`
Take n times the value t.
- `unsigned to_result () const`
Get the value of the accumulator.

- `void init ()`
Manipulators.

10.264.1 Detailed Description

`template<typename I> struct mln::morpho::attribute::volume< I >`

Volume accumulator class. The parameter `I` is the image type on which the accumulator of pixels is built.
 Definition at line 78 of file morpho/attribute/volume.hh.

10.264.2 Member Function Documentation

10.264.2.1 template<typename I > unsigned mln::morpho::attribute::volume< I >::area () const [inline]

Give the area.

Definition at line 202 of file morpho/attribute/volume.hh.

10.264.2.2 template<typename I > void mln::morpho::attribute::volume< I >::init () [inline]

Manipulators.

Definition at line 130 of file morpho/attribute/volume.hh.

10.264.2.3 template<typename I > bool mln::morpho::attribute::volume< I >::is_valid () const [inline]

Check whether this accu is able to return a result.

Always true here.

Definition at line 210 of file morpho/attribute/volume.hh.

10.264.2.4 void mln::Accumulator< volume< I > >::take_as_init (const T & t) [inherited]

Take as initialization the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.264.2.5 void mln::Accumulator< volume< I > >::take_n_times (unsigned n, const T & t) [inherited]

Take n times the value t.

Dev note: this is a final method; override if needed by take_as_init_ (ending with '_').

10.264.2.6 template<typename I> unsigned mln::morpho::attribute::volume< I >::to_result () const [inline]

Get the value of the accumulator.


Definition at line 194 of file morpho/attribute/volume.hh.

10.265 mln::neighb< W > Class Template Reference

Adapter class from window to neighborhood.

```
#include <neighb.hh>
```

Inheritance diagram for mln::neighb< W >:



Public Types

- **typedef neighb_bkd_niter< W > bkd_niter**
Backward site iterator associated type.
- **typedef neighb_fwd_niter< W > fwd_niter**
Forward site iterator associated type.
- **typedef fwd_niter niter**
Site iterator associated type.

Public Member Functions

- [neighb \(\)](#)

Constructor without argument.

- [neighb \(const W &win\)](#)

Constructor from a window win.

10.265.1 Detailed Description

template<typename W> class mln::neighb< W >

Adapter class from window to neighborhood.

Definition at line 76 of file mln/core/neighb.hh.

10.265.2 Member Typedef Documentation

10.265.2.1 template<typename W> typedef neighb_bkd_niter<W> mln::neighb< W >::bkd_niter

Backward site iterator associated type.

Definition at line 87 of file mln/core/neighb.hh.

10.265.2.2 template<typename W> typedef neighb_fwd_niter<W> mln::neighb< W >::fwd_niter

Forward site iterator associated type.

Definition at line 84 of file mln/core/neighb.hh.

10.265.2.3 template<typename W> typedef fwd_niter mln::neighb< W >::niter

[Site](#) iterator associated type.

Definition at line 90 of file mln/core/neighb.hh.

10.265.3 Constructor & Destructor Documentation

10.265.3.1 template<typename W> mln::neighb< W >::neighb() [inline]

Constructor without argument.

Definition at line 150 of file mln/core/neighb.hh.

10.265.3.2 template<typename W> mln::neighb< W >::neighb(const W & win) [inline]

Constructor from a window win.


Definition at line 156 of file mln/core/neighb.hh.

10.266 mln::Neighborhood< E > Struct Template Reference

Base class for implementation classes that are neighborhoods.

```
#include <neighborhood.hh>
```

Inheritance diagram for mln::Neighborhood< E >:



10.266.1 Detailed Description

```
template<typename E> struct mln::Neighborhood< E >
```

Base class for implementation classes that are neighborhoods.

See also

[mln::doc::Neighborhood](#) for a complete documentation of this class contents.

Definition at line 66 of file core/concept/neighborhood.hh.

10.267 mln::Neighborhood< void > Struct Template Reference

[Neighborhood](#) category flag type.

```
#include <neighborhood.hh>
```

10.267.1 Detailed Description

```
template<> struct mln::Neighborhood< void >
```

[Neighborhood](#) category flag type.

Definition at line 54 of file core/concept/neighborhood.hh.

10.268 mln::Object< E > Struct Template Reference

Base class for almost every class defined in Milena.

```
#include <object.hh>
```

Inherited by mln::Base< E >, mln::Browsing< E >, mln::Delta_Point_Site< E >, mln::Function< E >, mln::Gdpoint< E >, mln::Graph< E >, mln::Image< E >, mln::io::off::internal::off_loader< I, E >, mln::io::off::internal::off_saver< I, E >, mln::Iterator< E >, mln::Literal< E >, mln::Mesh< E >, mln::Meta_Accumulator< E >, mln::Meta_Function< E >, mln::Neighborhood< E >, mln::Point_Site< E >, mln::Proxy< E >, mln::Site< E >, mln::Site_Set< E >, mln::Value< E >, mln::value::HSL< E >, mln::Value_Set< E >, mln::Weighted_Window< E >, and mln::Window< E >.

10.268.1 Detailed Description

template<typename E> struct mln::Object< E >

Base class for almost every class defined in Milena. The parameter *E* is the exact type.

Definition at line 171 of file object.hh.

10.269 mln::p2p_image< I, F > Struct Template Reference

FIXME: Doc!

```
#include <p2p_image.hh>
```

Inherits image_domain_morpher< I, I::domain_t, p2p_image< I, F > >.

Public Types

- **typedef p2p_image< tag::image_< I >, tag::function_< F > > skeleton**
Skeleton.

Public Member Functions

- **const I::domain_t & domain () const**
Give the definition domain.
- **const F & fun () const**
Give the p2p function.
- **I::rvalue operator() (const typename I::psite &p) const**
Read-only access to the image value located at point p.
- **internal::morpher_lvalue_< I >::ret operator() (const typename I::psite &p)**
Read-write access to the image value located at point p.
- **p2p_image (I &ima, const F &f)**
Constructor from an image ima and a predicate f.
- **p2p_image ()**
Constructor without argument.

10.269.1 Detailed Description

```
template<typename I, typename F> struct mln::p2p_image< I, F >
```

FIXME: Doc!

Definition at line 90 of file p2p_image.hh.

10.269.2 Member Typedef Documentation

10.269.2.1 template<typename I, typename F> typedef p2p_image< tag::image_<I>, tag::function_<F> > mln::p2p_image< I, F >::skeleton

Skeleton.

Definition at line 95 of file p2p_image.hh.

10.269.3 Constructor & Destructor Documentation

10.269.3.1 template<typename I , typename F > mln::p2p_image< I, F >::p2p_image() [inline]

Constructor without argument.

Definition at line 178 of file p2p_image.hh.

10.269.3.2 template<typename I , typename F > mln::p2p_image< I, F >::p2p_image(I & ima, const F & f) [inline]

Constructor from an image *ima* and a predicate *f*.

Definition at line 184 of file p2p_image.hh.

10.269.4 Member Function Documentation

10.269.4.1 template<typename I , typename F > const I::domain_t & mln::p2p_image< I, F >::domain() const [inline]

Give the definition domain.

Definition at line 201 of file p2p_image.hh.

10.269.4.2 template<typename I , typename F > const F & mln::p2p_image< I, F >::fun() const [inline]

Give the p2p function.

Definition at line 210 of file p2p_image.hh.

10.269.4.3 template<typename I , typename F > I::rvalue mln::p2p_image< I, F >::operator() (const typename I::psite & p) const [inline]

Read-only access to the image value located at point p.

Definition at line 219 of file p2p_image.hh.

10.269.4.4 template<typename I , typename F > internal::morpher_lvalue_< I >::ret mln::p2p_image< I, F >::operator() (const typename I::psite & p) [inline]

Read-write access to the image value located at point p.

Definition at line 229 of file p2p_image.hh.

10.270 mln::p_array< P > Class Template Reference

Multi-set of sites.

```
#include <p_array.hh>
```

Inherits site_set_base_< P, p_array< P > >.

Public Types

- **typedef p_indexed_bkd_piter< self_ > bkd_piter**
Backward Site_Iterator associated type.
- **typedef P element**
Element associated type.
- **typedef p_indexed_fwd_piter< self_ > fwd_piter**
Forward Site_Iterator associated type.
- **typedef P i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_indexed_psite< self_ > psite**
Psite associated type.

Public Member Functions

- **p_array< P > & append (const P &p)**
Append a point p.
- **p_array< P > & append (const p_array< P > &other)**
Append an array other of points.

- void **change** (const **psite** &p, const **P** &new_p)

Change site p into new_p.

- void **clear** ()

Clear this set.

- bool **has** (const **util::index** &i) const

Test if index i belongs to this site set.

- bool **has** (const **psite** &p) const

Test if p belongs to this site set.

- void **insert** (const **P** &p)

Insert a point p (equivalent as 'append').

- bool **is_valid** () const

Test this set validity so returns always true.

- std::size_t **memory_size** () const

Return the size of this site set in memory.

- unsigned **nsites** () const

Give the number of sites.

- const **P** & **operator[]** (const **util::index** &i) const

Return the i-th element.

- **P** & **operator[]** (unsigned i)

Return the i-th site (mutable).

- const **P** & **operator[]** (unsigned i) const

Return the i-th site (constant).

- **p_array** ()

Constructor.

- **p_array** (const **std::vector< P >** &vect)

Constructor from a vector vect.

- void **reserve** (size_type n)

Reserve n cells.

- void **resize** (size_t size)

Update the size of this array.

- const **std::vector< P >** & **std_vector** () const

Return the corresponding std::vector of points.

10.270.1 Detailed Description

`template<typename P> class mln::p_array< P >`

Multi-set of sites. [Site](#) set class based on std::vector.

Definition at line 84 of file p_array.hh.

10.270.2 Member Typedef Documentation

10.270.2.1 template<typename P> typedef p_indexed_bkd_piter<self_> mln::p_array< P >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 100 of file p_array.hh.

10.270.2.2 template<typename P> typedef P mln::p_array< P >::element

Element associated type.

Definition at line 91 of file p_array.hh.

10.270.2.3 template<typename P> typedef p_indexed_fwd_piter<self_> mln::p_array< P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 97 of file p_array.hh.

10.270.2.4 template<typename P> typedef P mln::p_array< P >::i_element

Insertion element associated type.

Definition at line 141 of file p_array.hh.

10.270.2.5 template<typename P> typedef fwd_piter mln::p_array< P >::piter

[Site_Iterator](#) associated type.

Definition at line 103 of file p_array.hh.

10.270.2.6 template<typename P> typedef p_indexed_psite<self_> mln::p_array< P >::psite

Psite associated type.

Definition at line 94 of file p_array.hh.

10.270.3 Constructor & Destructor Documentation

10.270.3.1 `template<typename P> mln::p_array<P>::p_array() [inline]`

Constructor.

Definition at line 340 of file p_array.hh.

10.270.3.2 `template<typename P> mln::p_array<P>::p_array(const std::vector<P> & vect) [inline]`

Constructor from a vector `vect`.

Definition at line 346 of file p_array.hh.

10.270.4 Member Function Documentation

10.270.4.1 `template<typename P> p_array<P> & mln::p_array<P>::append(const P & p) [inline]`

Append a point `p`.

Definition at line 408 of file p_array.hh.

Referenced by `mln::convert::to_p_array()`.

10.270.4.2 `template<typename P> p_array<P> & mln::p_array<P>::append(const p_array<P> & other) [inline]`

Append an array `other` of points.

Definition at line 425 of file p_array.hh.

References `mln::p_array<P>::std_vector()`.

10.270.4.3 `template<typename P> void mln::p_array<P>::change(const psite & p, const P & new_p) [inline]`

Change site `p` into `new_p`.

Definition at line 472 of file p_array.hh.

References `mln::p_array<P>::has()`.

10.270.4.4 `template<typename P> void mln::p_array<P>::clear() [inline]`

Clear this set.

Definition at line 436 of file p_array.hh.

10.270.4.5 `template<typename P> bool mln::p_array<P>::has(const psite & p) const [inline]`

Test if `p` belongs to this site set.

Definition at line 362 of file p_array.hh.

Referenced by mln::p_array< P >::change(), and mln::p_array< P >::operator[]().

10.270.4.6 template<typename P> bool mln::p_array< P >::has (const util::index & i) const [inline]

Test is index *i* belongs to this site set.

Definition at line 375 of file p_array.hh.

References mln::p_array< P >::nsites().

10.270.4.7 template<typename P> void mln::p_array< P >::insert (const P & p) [inline]

Insert a point *p* (equivalent as 'append').

Definition at line 417 of file p_array.hh.

10.270.4.8 template<typename P> bool mln::p_array< P >::is_valid () const [inline]

Test this set validity so returns always true.

Definition at line 383 of file p_array.hh.

10.270.4.9 template<typename P> std::size_t mln::p_array< P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 481 of file p_array.hh.

References mln::p_array< P >::nsites().

10.270.4.10 template<typename P> unsigned mln::p_array< P >::nsites () const [inline]

Give the number of sites.

Definition at line 400 of file p_array.hh.

Referenced by mln::registration::get_rot(), mln::p_array< P >::has(), mln::p_array< P >::memory_size(), and mln::p_array< P >::operator[]().

10.270.4.11 template<typename P> P & mln::p_array< P >::operator[](unsigned i) [inline]

Return the *i*-th site (mutable).

Definition at line 463 of file p_array.hh.

References mln::p_array< P >::nsites().

10.270.4.12 template<typename P> const P & mln::p_array< P >::operator[](const util::index & i) const [inline]

Return the i-th element.

Definition at line 391 of file p_array.hh.

References mln::p_array< P >::has().

10.270.4.13 template<typename P> const P & mln::p_array< P >::operator[](unsigned i) const [inline]

Return the i-th site (constant).

Definition at line 454 of file p_array.hh.

References mln::p_array< P >::nsites().

10.270.4.14 template<typename P> void mln::p_array< P >::reserve(size_type n) [inline]

Reserve n cells.

Definition at line 354 of file p_array.hh.

Referenced by mln::convert::to_p_array().

10.270.4.15 template<typename P> void mln::p_array< P >::resize(size_t size) [inline]

Update the size of this array.

Definition at line 445 of file p_array.hh.

10.270.4.16 template<typename P> const std::vector< P > & mln::p_array< P >::std_vector() const [inline]

Return the corresponding std::vector of points.

Definition at line 489 of file p_array.hh.

Referenced by mln::p_array< P >::append().

10.271 mln::p_centered< W > Class Template Reference

[Site](#) set corresponding to a window centered on a site.

```
#include <p_centered.hh>
```

Inherits site_set_base_< W::psite, p_centered< W > >, and mlc_is_aW.

Public Types

- `typedef p_centered_piter< W > bkd_piter`

Backward Site_Iterator associated type.

- **typedef psite element**
Element associated type.
- **typedef p_centered_piter< W > fwd_piter**
Forward [Site_Iterator](#) associated type.
- **typedef fwd_piter piter**
[Site_Iterator](#) associated type.
- **typedef W::psite psite**
Psite associated type.
- **typedef W::site site**
[Site](#) associated type.

Public Member Functions

- **const W::psite & center () const**
Give the center of this site set.
- **template<typename P >
bool has (const P &p) const**
Test if p belongs to the box.
- **bool is_valid () const**
Test if this site set is initialized.
- **std::size_t memory_size () const**
Return the size of this site set in memory.
- **p_centered (const W &win, const typename W::psite &c)**
Constructor from a window win and a center c.
- **p_centered ()**
Constructor without argument.
- **const W & window () const**
Give the window this site set is defined upon.

10.271.1 Detailed Description

template<typename W> class mln::p_centered< W >

[Site](#) set corresponding to a window centered on a site.

Definition at line 77 of file p_centered.hh.

10.271.2 Member Typedef Documentation

10.271.2.1 `template<typename W> typedef p_centered_piter<W> mln::p_centered<W>::bkd_piter`

Backward [Site_Iterator](#) associated type.

Definition at line 97 of file p_centered.hh.

10.271.2.2 `template<typename W> typedef psite mln::p_centered<W>::element`

Element associated type.

Definition at line 90 of file p_centered.hh.

10.271.2.3 `template<typename W> typedef p_centered_piter<W> mln::p_centered<W>::fwd_piter`

Forward [Site_Iterator](#) associated type.

Definition at line 94 of file p_centered.hh.

10.271.2.4 `template<typename W> typedef fwd_piter mln::p_centered<W>::piter`

[Site_Iterator](#) associated type.

Definition at line 100 of file p_centered.hh.

10.271.2.5 `template<typename W> typedef W ::psite mln::p_centered<W>::psite`

Psite associated type.

Definition at line 83 of file p_centered.hh.

10.271.2.6 `template<typename W> typedef W ::site mln::p_centered<W>::site`

[Site](#) associated type.

Definition at line 86 of file p_centered.hh.

10.271.3 Constructor & Destructor Documentation

10.271.3.1 `template<typename W> mln::p_centered<W>::p_centered() [inline]`

Constructor without argument.

Definition at line 182 of file p_centered.hh.

10.271.3.2 `template<typename W> mln::p_centered<W>::p_centered(const W & win, const typename W::psite & c) [inline]`

Constructor from a window `win` and a center `c`.

Definition at line 188 of file p_centered.hh.

References mln::p_centered< W >::is_valid().

10.271.4 Member Function Documentation

10.271.4.1 template<typename W> const W::psite & mln::p_centered< W >::center() const [inline]

Give the center of this site set.

Definition at line 216 of file p_centered.hh.

10.271.4.2 template<typename W> template<typename P> bool mln::p_centered< W >::has(const P & p) const [inline]

Test if p belongs to the box.

Definition at line 199 of file p_centered.hh.

References mln::p_centered< W >::is_valid().

10.271.4.3 template<typename W> bool mln::p_centered< W >::is_valid() const [inline]

Test if this site set is initialized.

Definition at line 175 of file p_centered.hh.

Referenced by mln::p_centered< W >::has(), and mln::p_centered< W >::p_centered().

10.271.4.4 template<typename W> std::size_t mln::p_centered< W >::memory_size() const [inline]

Return the size of this site set in memory.

Definition at line 208 of file p_centered.hh.

10.271.4.5 template<typename W> const W & mln::p_centered< W >::window() const [inline]

Give the window this site set is defined upon.

Definition at line 224 of file p_centered.hh.

10.272 mln::p_complex< D, G > Class Template Reference

A complex psite set based on the N-faces of a complex of dimension D (a D-complex).

```
#include <p_complex.hh>
```

Inherits site_set_base_< complex_psite< D, G >, p_complex< D, G > >.

Public Types

- `typedef super_::site element`
Associated types.
- `typedef complex_psite< D, G > psite`
Point_Site associated type.
- `typedef p_complex_fwd_piter_< D, G > fwd_piter`
Forward Site_Iterator associated type.
- `typedef p_complex_bkd_piter_< D, G > bkd_piter`
Backward Site_Iterator associated type.
- `typedef fwd_piter piter`
Site_Iterator associated type.

Public Member Functions

- `bool has (const psite &p) const`
Does this site set has p?
- `bool is_valid () const`
Is this site set valid?
- `unsigned nfakes () const`
Return the number of faces in the complex.
- `unsigned nfakes_of_dim (unsigned n) const`
Return the number of n-faces in the complex.
- `unsigned nsites () const`
Return The number of sites of the set, i.e., the number of faces.
- `p_complex (const topo::complex< D > &cplx, const G &geom)`
Construct a complex psite set from a complex.
- `topo::complex< D > & cplx () const`
Accessors.
- `topo::complex< D > & cplx ()`
Return the complex associated to the `p_complex` domain (mutable version).
- `const G & geom () const`
Return the geometry of the complex.

10.272.1 Detailed Description

template<unsigned D, typename G> class mln::p_complex< D, G >

A complex psite set based on the N-faces of a complex of dimension D (a D-complex).

Template Parameters

D The dimension of the complex.

G A function object type, associating localization information (geometry) to each face of the complex.

See also

[mln::geom::complex_geometry](#). A complex psite set based on the N-faces of a complex.

Definition at line 116 of file p_complex.hh.

10.272.2 Member Typedef Documentation

10.272.2.1 template<unsigned D, typename G> typedef p_complex_bkd_piter_<D, G> mln::p_complex< D, G >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 141 of file p_complex.hh.

10.272.2.2 template<unsigned D, typename G> typedef super_ ::site mln::p_complex< D, G >::element

Associated types.

Element associated type.

Definition at line 132 of file p_complex.hh.

10.272.2.3 template<unsigned D, typename G> typedef p_complex_fwd_piter_<D, G> mln::p_complex< D, G >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 138 of file p_complex.hh.

10.272.2.4 template<unsigned D, typename G> typedef fwd_piter mln::p_complex< D, G >::piter

[Site_Iterator](#) associated type.

Definition at line 144 of file p_complex.hh.

10.272.2.5 template<unsigned D, typename G> typedef complex_psite<D, G> mln::p_complex< D, G >::psite

[Point_Site](#) associated type.

Definition at line 135 of file p_complex.hh.

10.272.3 Constructor & Destructor Documentation

10.272.3.1 template<unsigned D, typename G> mln::p_complex< D, G >::p_complex (const topo::complex< D > & *cplx*, const G & *geom*) [inline]

Construct a complex psite set from a complex.

Parameters

cplx The complex upon which the complex psite set is built.

geom FIXME

Definition at line 231 of file p_complex.hh.

10.272.4 Member Function Documentation

10.272.4.1 template<unsigned D, typename G> topo::complex< D > & mln::p_complex< D, G >::cplx () const

Accessors.

Return the complex associated to the [p_complex](#) domain (const version)

Definition at line 293 of file p_complex.hh.

References mln::p_complex< D, G >::is_valid().

Referenced by mln::complex_psite< D, G >::change_target(), mln::complex_psite< D, G >::complex_psite(), and mln::operator==().

10.272.4.2 template<unsigned D, typename G> topo::complex< D > & mln::p_complex< D, G >::cplx ()

Return the complex associated to the [p_complex](#) domain (mutable version).

Definition at line 301 of file p_complex.hh.

References mln::p_complex< D, G >::is_valid().

10.272.4.3 template<unsigned D, typename G> const G & mln::p_complex< D, G >::geom () const

Return the geometry of the complex.

Definition at line 309 of file p_complex.hh.

10.272.4.4 template<unsigned D, typename G> bool mln::p_complex< D, G >::has (const psite & *p*) const [inline]

Does this site set has *p*?

Definition at line 271 of file p_complex.hh.

References `mln::complex_psite< D, G >::is_valid()`, `mln::p_complex< D, G >::is_valid()`, and `mln::complex_psite< D, G >::site_set()`.

10.272.4.5 template<unsigned D, typename G> bool mln::p_complex< D, G >::is_valid() const [inline]

Is this site set valid?

Definition at line 263 of file `p_complex.hh`.

Referenced by `mln::p_complex< D, G >::cplx()`, and `mln::p_complex< D, G >::has()`.

10.272.4.6 template<unsigned D, typename G> unsigned mln::p_complex< D, G >::nffaces() const [inline]

Return the number of faces in the complex.

Definition at line 247 of file `p_complex.hh`.

Referenced by `mln::p_complex< D, G >::nsites()`.

10.272.4.7 template<unsigned D, typename G> unsigned mln::p_complex< D, G >::nffaces_of_dim(unsigned n) const [inline]

Return the number of *n-faces* in the complex.

Definition at line 255 of file `p_complex.hh`.

10.272.4.8 template<unsigned D, typename G> unsigned mln::p_complex< D, G >::nsites() const [inline]

Return The number of sites of the set, i.e., the number of *faces*.

(Required by the [mln::Site_Set](#) concept, since the property `trait::site_set::nsites::known` of this site set is set to ‘known’.)

Definition at line 239 of file `p_complex.hh`.

References `mln::p_complex< D, G >::nffaces()`.

10.273 `mln::p_edges< G, F >` Class Template Reference

[Site](#) set mapping graph edges and image sites.

```
#include <p_edges.hh>
```

Inherits `site_set_base_< F::result, p_edges< G, F > >`.

Public Types

- `typedef util::edge< G > edge`

Type of graph edge.

- **typedef F fun_t**
Function associated type.
- **typedef util::edge< G > graph_element**
Type of graph element this site set focuses on.
- **typedef G graph_t**
Graph associated type.

- **typedef super_::site element**
Associated types.
- **typedef p_edges_psite< G, F > psite**
Point_Site associated type.
- **typedef p_graph_piter< self_, mln_edge_fwd_iter(G) > fwd_piter**
Forward Site_Iterator associated type.
- **typedef p_graph_piter< self_, mln_edge_bkd_iter(G) > bkd_piter**
Backward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.

Public Member Functions

- **bool has (const psite &p) const**
Does this site set has site p?
- **template<typename G2 >**
bool has (const util::edge< G2 > &e) const
Does this site set has edge e?
- **void invalidate ()**
Invalidate this site set.
- **bool is_valid () const**
Is this site set valid?
- **std::size_t memory_size () const**
*Does this site set has vertex_id? *FIXME: causes ambiguities while calling has(mln::neighb_fwd_niter<>); bool has(unsigned vertex_id) const;**
- **unsigned nedges () const**
Return The number of edges in the graph.
- **unsigned nsites () const**
Return The number of points (sites) of the set, i.e., the number of edges.

- **p_edges ()**
Constructors
Default constructor.
- **p_edges (const Graph< G > &gr)**
Construct a graph edge psite set from a graph.
- **p_edges (const Graph< G > &gr, const Function< F > &f)**
Construct a graph edge psite set from a graph and a function.
- template<typename F2 >
p_edges (const Graph< G > &gr, const Function< F2 > &f)
Construct a graph edge psite set from a graph and a function.

- **const G & graph () const**
Accessors.
- **const F & function () const**
Return the mapping function.

10.273.1 Detailed Description

```
template<typename G, typename F = util::internal::id2element<G,util::edge<G>>> class
mln::p_edges< G, F >
```

[Site](#) set mapping graph edges and image sites.

Definition at line 70 of file p_edges.hh.

10.273.2 Member Typedef Documentation

**10.273.2.1 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef p_graph_piter< self_, mln_edge_bkd_iter(G) > mln::p_edges< G, F >::bkd_piter**

Backward [Site_Iterator](#) associated type.

Definition at line 128 of file p_edges.hh.

**10.273.2.2 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef util::edge<G> mln::p_edges< G, F >::edge**

Type of graph edge.

Definition at line 86 of file p_edges.hh.

**10.273.2.3 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef super_ ::site mln::p_edges< G, F >::element**

Associated types.

Element associated type.

Definition at line 119 of file p_edges.hh.

**10.273.2.4 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef F mln::p_edges< G, F >::fun_t**

Function associated type.

Definition at line 83 of file p_edges.hh.

**10.273.2.5 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef p_graph_piter< self_, mln::edge_fwd_iter(G) > mln::p_edges< G, F >::fwd_piter**

Forward [Site_Iterator](#) associated type.

Definition at line 125 of file p_edges.hh.

**10.273.2.6 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef util::edge<G> mln::p_edges< G, F >::graph_element**

Type of graph element this site set focuses on.

Definition at line 89 of file p_edges.hh.

**10.273.2.7 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef G mln::p_edges< G, F >::graph_t**

[Graph](#) associated type.

Definition at line 80 of file p_edges.hh.

**10.273.2.8 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef fwd_piter mln::p_edges< G, F >::piter**

[Site_Iterator](#) associated type.

Definition at line 131 of file p_edges.hh.

**10.273.2.9 template<typename G, typename F = util::internal::id2element<G,util::edge<G>>>
typedef p_edges_psite<G, F> mln::p_edges< G, F >::psite**

[Point_Site](#) associated type.

Definition at line 122 of file p_edges.hh.

10.273.3 Constructor & Destructor Documentation

10.273.3.1 template<typename G , typename F > mln::p_edges< G, F >::p_edges () [inline]

Constructors

Default constructor.

Definition at line 203 of file p_edges.hh.

10.273.3.2 template<typename G , typename F > mln::p_edges< G, F >::p_edges (const Graph< G > & gr) [inline]

Construct a graph edge psite set from a graph.

Parameters

gr The graph upon which the graph edge psite set is built.

Definition at line 209 of file p_edges.hh.

References `mln::p_edges< G, F >::is_valid()`.

10.273.3.3 template<typename G , typename F > mln::p_edges< G, F >::p_edges (const Graph< G > & gr, const Function< F > & f) [inline]

Construct a graph edge psite set from a graph and a function.

Parameters

gr The graph upon which the graph edge psite set is built.

f the function mapping edges and sites.

Definition at line 221 of file p_edges.hh.

References `mln::p_edges< G, F >::is_valid()`.

10.273.3.4 template<typename G , typename F > template<typename F2 > mln::p_edges< G, F >::p_edges (const Graph< G > & gr, const Function< F2 > & f) [inline]

Construct a graph edge psite set from a graph and a function.

Parameters

gr The graph upon which the graph edge psite set is built.

f the function mapping edges and sites. It must be convertible towards the function type *F*.

Definition at line 231 of file p_edges.hh.

References `mln::p_edges< G, F >::is_valid()`.

10.273.4 Member Function Documentation

10.273.4.1 template<typename G , typename F > const F & mln::p_edges< G, F >::function () const [inline]

Return the mapping function.

Definition at line 324 of file p_edges.hh.

10.273.4.2 template<typename G , typename F > const G & mln::p_edges< G, F >::graph () const [inline]

Accessors.

Return the graph associated to this site set

Definition at line 315 of file p_edges.hh.

References mln::p_edges< G, F >::is_valid().

Referenced by mln::operator==().

10.273.4.3 template<typename G , typename F > bool mln::p_edges< G, F >::has (const psite & p) const [inline]

Does this site set has site *p*?

Definition at line 276 of file p_edges.hh.

References mln::p_edges< G, F >::is_valid().

10.273.4.4 template<typename G , typename F > template<typename G2 > bool mln::p_edges< G, F >::has (const util::edge< G2 > & e) const [inline]

Does this site set has edge *e*?

Definition at line 286 of file p_edges.hh.

References mln::util::edge< G >::graph(), mln::util::edge< G >::is_valid(), and mln::p_edges< G, F >::is_valid().

10.273.4.5 template<typename G , typename F > void mln::p_edges< G, F >::invalidate () [inline]

Invalidate this site set.

Definition at line 268 of file p_edges.hh.

10.273.4.6 template<typename G , typename F > bool mln::p_edges< G, F >::is_valid () const [inline]

Is this site set valid?

Definition at line 260 of file p_edges.hh.

Referenced by mln::p_edges< G, F >::graph(), mln::p_edges< G, F >::has(), and mln::p_edges< G, F >::p_edges().

10.273.4.7 template<typename G , typename F > std::size_t mln::p_edges< G, F >::memory_size() const [inline]

Does this site set has *vertex_id*? FIXME: causes ambiguities while calling has(mln::neighb_fwd_niter<>);
bool has(unsigned vertex_id) const;

Definition at line 305 of file p_edges.hh.

10.273.4.8 template<typename G , typename F > unsigned mln::p_edges< G, F >::nedges() const [inline]

Return The number of edges in the graph.

Definition at line 252 of file p_edges.hh.

Referenced by mln::p_edges< G, F >::nsites().

10.273.4.9 template<typename G , typename F > unsigned mln::p_edges< G, F >::nsites() const [inline]

Return The number of points (sites) of the set, i.e., the number of *edges*.

Definition at line 244 of file p_edges.hh.

References mln::p_edges< G, F >::nedges().

10.274 mln::p_faces< N, D, P > Struct Template Reference

A complex psite set based on a the N-faces of a complex of dimension D (a D-complex).

```
#include <p_faces.hh>
```

Inherits site_set_base_< faces_psite< N, D, P >, p_faces< N, D, P > >.

Public Types

- **typedef super_::site element**
Associated types.
- **typedef faces_psite< N, D, P > psite**
Point_Site associated type.
- **typedef p_faces_fwd_piter_< N, D, P > fwd_piter**
Forward Site_Iterator associated type.
- **typedef p_faces_bkd_piter_< N, D, P > bkd_piter**
Backward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.

Public Member Functions

- `bool is_valid () const`
Is this site set valid?
- `unsigned nfacs () const`
Return The number of faces in the complex.
- `unsigned nsites () const`
Return The number of sites of the set, i.e., the number of faces.
- `p_faces (const topo::complex< D > &cplx)`
Construct a faces psite set from an mln::complex.
- `p_faces (const p_complex< D, P > &pc)`
Construct a faces psite set from an mln::p_complex.

- `topo::complex< D > & cplx () const`
Accessors.
- `topo::complex< D > & cplx ()`
Return the complex associated to the `p_faces` domain (mutable version).

10.274.1 Detailed Description

`template<unsigned N, unsigned D, typename P> struct mln::p_faces< N, D, P >`

A complex psite set based on a the N-faces of a complex of dimension D (a D-complex).

Definition at line 77 of file p_faces.hh.

10.274.2 Member Typedef Documentation

10.274.2.1 `template<unsigned N, unsigned D, typename P> typedef p_faces_bkd_piter_<N, D, P> mln::p_faces< N, D, P >::bkd_piter`

Backward [Site_Iterator](#) associated type.

Definition at line 110 of file p_faces.hh.

10.274.2.2 `template<unsigned N, unsigned D, typename P> typedef super_ ::site mln::p_faces< N, D, P >::element`

Associated types.

Element associated type.

Definition at line 99 of file p_faces.hh.

10.274.2.3 template<unsigned N, unsigned D, typename P> typedef p_faces_fwd_piter_<N, D, P> mln::p_faces< N, D, P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 106 of file p_faces.hh.

10.274.2.4 template<unsigned N, unsigned D, typename P> typedef fwd_piter mln::p_faces< N, D, P >::fwd_piter

[Site_Iterator](#) associated type.

Definition at line 113 of file p_faces.hh.

10.274.2.5 template<unsigned N, unsigned D, typename P> typedef faces_psites<N, D, P> mln::p_faces< N, D, P >::psite

[Point_Site](#) associated type.

Definition at line 102 of file p_faces.hh.

10.274.3 Constructor & Destructor Documentation

10.274.3.1 template<unsigned N, unsigned D, typename P> mln::p_faces< N, D, P >::p_faces (const topo::complex< D > & cplx) [inline]

Construct a faces psite set from an mln::complex.

Parameters

cplx The complex upon which the complex psite set is built.

Definition at line 192 of file p_faces.hh.

10.274.3.2 template<unsigned N, unsigned D, typename P> mln::p_faces< N, D, P >::p_faces (const p_complex< D, P > & pc) [inline]

Construct a faces psite set from an [mln::p_complex](#).

Parameters

pc The complex upon which the complex psite set is built.

Definition at line 201 of file p_faces.hh.

10.274.4 Member Function Documentation

10.274.4.1 template<unsigned N, unsigned D, typename P> topo::complex< D > & mln::p_faces< N, D, P >::cplx () const

Accessors.

Return the complex associated to the `p_faces` domain (const version).

Definition at line 257 of file `p_faces.hh`.

References `mln::p_faces< N, D, P >::is_valid()`.

Referenced by `mln::faces_psite< N, D, P >::change_target()`, and `mln::operator==()`.

10.274.4.2 template<unsigned N, unsigned D, typename P> topo::complex< D > & mln::p_faces< N, D, P >::cplx()

Return the complex associated to the `p_faces` domain (mutable version).

Definition at line 265 of file `p_faces.hh`.

References `mln::p_faces< N, D, P >::is_valid()`.

10.274.4.3 template<unsigned N, unsigned D, typename P> bool mln::p_faces< N, D, P >::is_valid() const [inline]

Is this site set valid?

Definition at line 227 of file `p_faces.hh`.

Referenced by `mln::p_faces< N, D, P >::cplx()`.

10.274.4.4 template<unsigned N, unsigned D, typename P> unsigned mln::p_faces< N, D, P >::nfacs() const [inline]

Return The number of faces in the complex.

Definition at line 219 of file `p_faces.hh`.

Referenced by `mln::p_faces< N, D, P >::nsites()`.

10.274.4.5 template<unsigned N, unsigned D, typename P> unsigned mln::p_faces< N, D, P >::nsites() const [inline]

Return The number of sites of the set, i.e., the number of *faces*.

(Required by the `mln::Site_Set` concept, since the property trait::site_set::nsites::known of this site set is set to ‘known’.)

Definition at line 211 of file `p_faces.hh`.

References `mln::p_faces< N, D, P >::nfacs()`.

10.275 mln::p_graph_piter< S, I > Class Template Reference

Generic iterator on point sites of a `mln::S`.

```
#include <p_graph_piter.hh>
```

Inherits `site_set_iterator_base< S, p_graph_piter< S, I > >`.

Public Member Functions

- const S::graph_t & [graph \(\) const](#)
Return the graph associated to the target S.
- unsigned [id \(\) const](#)
Return the graph element id.
- [mln_q_subject \(iter\) element\(\)](#)
Return the underlying graph element.
- void [next \(\)](#)
Go to the next element.
- [p_graph_piter \(\)](#)
Constructors.

10.275.1 Detailed Description

`template<typename S, typename I> class mln::p_graph_piter< S, I >`

Generic iterator on point sites of a mln::S.

Definition at line 55 of file p_graph_piter.hh.

10.275.2 Constructor & Destructor Documentation

10.275.2.1 template<typename S , typename I > mln::p_graph_piter< S, I >::p_graph_piter () [inline]

Constructors.

Definition at line 151 of file p_graph_piter.hh.

10.275.3 Member Function Documentation

10.275.3.1 template<typename S , typename I > const S::graph_t & mln::p_graph_piter< S, I >::graph () const [inline]

Return the graph associated to the target S.

Definition at line 212 of file p_graph_piter.hh.

10.275.3.2 template<typename S , typename I > unsigned mln::p_graph_piter< S, I >::id () const [inline]

Return the graph element id.

Definition at line 228 of file p_graph_piter.hh.

10.275.3.3 template<typename S , typename I > mln::p_graph_piter< S, I >::mln_q_subject (iter)

Return the underlying graph element.

10.275.3.4 void mln::Site_Iterator< p_graph_piter< S, I > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.276 mln::p_if< S, F > Class Template Reference

[Site](#) set restricted w.r.t.

```
#include <p_if.hh>
```

Inherits site_set_base_< S::psite, p_if< S, F > >.

Public Types

- **typedef p_if_piter_< typename S::bkd_piter, S, F > bkd_piter**
Backward Site_Iterator associated type.
- **typedef S::element element**
Element associated type.
- **typedef p_if_piter_< typename S::fwd_piter, S, F > fwd_piter**
Forward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef S::psite psite**
Psite associated type.

Public Member Functions

- **bool has (const psite &p) const**
Test if p belongs to the subset.
- **bool is_valid () const**

Test if this site set is valid.

- std::size_t **memory_size** () const
Return the size of this site set in memory.
- const S & **overset** () const
Give the primary overset.
- **p_if** ()
Constructor without argument.
- **p_if** (const S &s, const F &f)
Constructor with a site set s and a predicate f.
- bool **pred** (const psite &p) const
Test predicate on point site p.
- const F & **predicate** () const
Give the predicate function.

10.276.1 Detailed Description

template<typename S, typename F> class mln::p_if< S, F >

Site set restricted w.r.t. a predicate.

Parameter S is a site set type; parameter F is a function from point to Boolean.

Definition at line 83 of file p_if.hh.

10.276.2 Member Typedef Documentation

10.276.2.1 template<typename S, typename F> typedef p_if_piter_<typename S ::bkd_piter, S, F> mln::p_if< S, F >::bkd_piter

Backward **Site_Iterator** associated type.

Definition at line 100 of file p_if.hh.

10.276.2.2 template<typename S, typename F> typedef S ::element mln::p_if< S, F >::element

Element associated type.

Definition at line 90 of file p_if.hh.

10.276.2.3 template<typename S, typename F> typedef p_if_piter_<typename S ::fwd_piter, S, F> mln::p_if< S, F >::fwd_piter

Forward **Site_Iterator** associated type.

Definition at line 97 of file p_if.hh.

10.276.2.4 template<typename S, typename F> typedef fwd_piter mln::p_if< S, F >::piter

[Site_Iterator](#) associated type.

Definition at line 103 of file p_if.hh.

10.276.2.5 template<typename S, typename F> typedef S ::psite mln::p_if< S, F >::psite

Psite associated type.

Definition at line 94 of file p_if.hh.

10.276.3 Constructor & Destructor Documentation**10.276.3.1 template<typename S , typename F > mln::p_if< S, F >::p_if(const S & s, const F & f) [inline]**

Constructor with a site set *s* and a predicate *f*.

Definition at line 190 of file p_if.hh.

10.276.3.2 template<typename S , typename F > mln::p_if< S, F >::p_if() [inline]

Constructor without argument.

Definition at line 198 of file p_if.hh.

10.276.4 Member Function Documentation**10.276.4.1 template<typename S , typename F > bool mln::p_if< S, F >::has(const psite & p) const [inline]**

Test if *p* belongs to the subset.

Definition at line 159 of file p_if.hh.

References mln::p_if< S, F >::has().

Referenced by mln::p_if< S, F >::has().

10.276.4.2 template<typename S , typename F > bool mln::p_if< S, F >::is_valid() const [inline]

Test if this site set is valid.

Definition at line 167 of file p_if.hh.

10.276.4.3 template<typename S , typename F > std::size_t mln::p_if< S, F >::memory_size() const [inline]

Return the size of this site set in memory.

Definition at line 213 of file p_if.hh.

10.276.4.4 template<typename S , typename F > const S & mln::p_if< S, F >::overset() const [inline]

Give the primary overset.

Definition at line 175 of file p_if.hh.

10.276.4.5 template<typename S , typename F > bool mln::p_if< S, F >::pred(const psite & p) const [inline]

Test predicate on point site p.

Definition at line 183 of file p_if.hh.

10.276.4.6 template<typename S , typename F > const F & mln::p_if< S, F >::predicate() const [inline]

Give the predicate function.

Definition at line 205 of file p_if.hh.

10.277 mln::p_image< I > Class Template Reference

[Site](#) set based on an image of Booleans.

```
#include <p_image.hh>
```

Inherits site_set_base_< I::psite, p_image< I > >.

Public Types

- **typedef S::bkd_piter bkd_piter**
Backward Site_Iterator associated type.
- **typedef I::psite element**
Element associated type.
- **typedef S::fwd_piter fwd_piter**
Forward Site_Iterator associated type.
- **typedef psite i_element**
Insertion element associated type.
- **typedef S::piter piter**
Site_Iterator associated type.
- **typedef I::psite psite**
Psite associated type.
- **typedef psite r_element**
Removal element associated type.

- `typedef internal::p_image_site_set< I >::ret S`
Equivalent site_set type.

Public Member Functions

- `void clear ()`
Clear this set.
- `bool has (const psite &) const`
Test if the psite p belongs to this site set.
- `void insert (const psite &p)`
Insert a site p .
- `bool is_valid () const`
Test if this site set is valid, i.e., initialized.
- `std::size_t memory_size () const`
Return the size of this site set in memory.
- `unsigned nsites () const`
Give the number of sites.
- `operator typename internal::p_image_site_set< I >::ret () const`
Conversion towards the equivalent site set.
- `p_image ()`
Constructor without argument.
- `p_image (const I &ima)`
Constructor.
- `void remove (const psite &p)`
Remove a site p .
- `void toggle (const psite &p)`
Change the status in/out of a site p .

10.277.1 Detailed Description

`template<typename I> class mln::p_image< I >`

`Site` set based on an image of Booleans.

Definition at line 88 of file p_image.hh.

10.277.2 Member Typedef Documentation

10.277.2.1 template<typename I> typedef S ::bkd_piter mln::p_image< I >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 110 of file p_image.hh.

10.277.2.2 template<typename I> typedef I ::psite mln::p_image< I >::element

Element associated type.

Definition at line 100 of file p_image.hh.

10.277.2.3 template<typename I> typedef S ::fwd_piter mln::p_image< I >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 107 of file p_image.hh.

10.277.2.4 template<typename I> typedef psite mln::p_image< I >::i_element

Insertion element associated type.

Definition at line 136 of file p_image.hh.

10.277.2.5 template<typename I> typedef S ::piter mln::p_image< I >::piter

[Site_Iterator](#) associated type.

Definition at line 113 of file p_image.hh.

10.277.2.6 template<typename I> typedef I ::psite mln::p_image< I >::psite

Psite associated type.

Definition at line 104 of file p_image.hh.

10.277.2.7 template<typename I> typedef psite mln::p_image< I >::r_element

Removal element associated type.

Definition at line 142 of file p_image.hh.

10.277.2.8 template<typename I> typedef internal::p_image_site_set<I>::ret mln::p_image< I >::S

Equivalent site_set type.

Definition at line 93 of file p_image.hh.

10.277.3 Constructor & Destructor Documentation

10.277.3.1 template<typename I> mln::p_image<I>::p_image() [inline]

Constructor without argument.

Definition at line 182 of file p_image.hh.

10.277.3.2 template<typename I> mln::p_image<I>::p_image(const I & ima) [inline]

Constructor.

Definition at line 189 of file p_image.hh.

References mln::p_image<I>::clear().

10.277.4 Member Function Documentation

10.277.4.1 template<typename I> void mln::p_image<I>::clear() [inline]

Clear this set.

Definition at line 283 of file p_image.hh.

References mln::data::fill_with_value(), and mln::p_image<I>::is_valid().

Referenced by mln::p_image<I>::p_image().

10.277.4.2 template<typename I> bool mln::p_image<I>::has(const psite & p) const [inline]

Test is the psite p belongs to this site set.

Definition at line 199 of file p_image.hh.

References mln::p_image<I>::is_valid().

10.277.4.3 template<typename I> void mln::p_image<I>::insert(const psite & p) [inline]

Insert a site p .

Definition at line 224 of file p_image.hh.

References mln::p_image<I>::is_valid().

10.277.4.4 template<typename I> bool mln::p_image<I>::is_valid() const [inline]

Test if this site set is valid, i.e., initialized.

Definition at line 208 of file p_image.hh.

Referenced by mln::p_image<I>::clear(), mln::p_image<I>::has(), mln::p_image<I>::insert(), mln::p_image<I>::memory_size(), mln::p_image<I>::remove(), and mln::p_image<I>::toggle().

10.277.4.5 template<typename I> std::size_t mln::p_image< I >::memory_size() const [inline]

Return the size of this site set in memory.

Definition at line 273 of file p_image.hh.

References `mln::p_image< I >::is_valid()`.

10.277.4.6 template<typename I> unsigned mln::p_image< I >::nsites() const [inline]

Give the number of sites.

Definition at line 216 of file p_image.hh.

10.277.4.7 template<typename I> mln::p_image< I >::operator typename internal::p_image_site_set< I >::ret() const [inline]

Conversion towards the equivalent site set.

Definition at line 174 of file p_image.hh.

10.277.4.8 template<typename I> void mln::p_image< I >::remove(const psite & p) [inline]

Remove a site `p`.

Definition at line 237 of file p_image.hh.

References `mln::p_image< I >::is_valid()`.

10.277.4.9 template<typename I> void mln::p_image< I >::toggle(const psite & p) [inline]

Change the status in/out of a site `p`.

Definition at line 251 of file p_image.hh.

References `mln::p_image< I >::is_valid()`.

10.278 `mln::p_indexed_bkd_piter< S >` Class Template Reference

Backward iterator on sites of an indexed site set.

```
#include <p_array.hh>
```

Inherits `site_set_iterator_base< S, p_indexed_bkd_piter< S > >`.

Public Member Functions

- int `index()` const

Return the current index.

- [void next \(\)](#)
Go to the next element.
- [p_indexed_bkd_piter \(const S &s\)](#)
Constructor.
- [p_indexed_bkd_piter \(\)](#)
Constructor with no argument.

10.278.1 Detailed Description

`template<typename S> class mln::p_indexed_bkd_piter< S >`

Backward iterator on sites of an indexed site set.

Definition at line 276 of file p_array.hh.

10.278.2 Constructor & Destructor Documentation

10.278.2.1 template<typename S > mln::p_indexed_bkd_piter< S >::p_indexed_bkd_piter () [inline]

Constructor with no argument.

Definition at line 686 of file p_array.hh.

10.278.2.2 template<typename S > mln::p_indexed_bkd_piter< S >::p_indexed_bkd_piter (const S & s) [inline]

Constructor.

Definition at line 692 of file p_array.hh.

10.278.3 Member Function Documentation

10.278.3.1 template<typename S > int mln::p_indexed_bkd_piter< S >::index () const [inline]

Return the current index.

Definition at line 733 of file p_array.hh.

10.278.3.2 void mln::Site_Iterator< p_indexed_bkd_piter< S > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.279 `mln::p_indexed_fwd_piter< S >` Class Template Reference

Forward iterator on sites of an indexed site set.

```
#include <p_array.hh>
```

Inherits site_set_iterator_base< S, p_indexed_fwd_piter< S > >.

Public Member Functions

- int `index` () const
Return the current index.
- void `next` ()
Go to the next element.
- `p_indexed_fwd_piter` (const S &s)
Constructor.
- `p_indexed_fwd_piter` ()
Constructor with no argument.

10.279.1 Detailed Description

```
template<typename S> class mln::p_indexed_fwd_piter< S >
```

Forward iterator on sites of an indexed site set.

Definition at line 235 of file p_array.hh.

10.279.2 Constructor & Destructor Documentation

10.279.2.1 template<typename S > mln::p_indexed_fwd_piter< S >::p_indexed_fwd_piter () [inline]

Constructor with no argument.

Definition at line 629 of file p_array.hh.

10.279.2.2 template<typename S > mln::p_indexed_fwd_piter< S >::p_indexed_fwd_piter (const S & s) [inline]

Constructor.

Definition at line 635 of file p_array.hh.

10.279.3 Member Function Documentation

10.279.3.1 template<typename S > int mln::p_indexed_fwd_piter< S >::index() const [inline]

Return the current index.

Definition at line 676 of file p_array.hh.

10.279.3.2 void mln::Site_Iterator< p_indexed_fwd_piter< S > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.280 mln::p_indexed_psite< S > Class Template Reference

Psite class for indexed site sets such as [p_array](#).

```
#include <p_array.hh>
```

Inherits `pseudo_site_base_< const S::element &, p_indexed_psite< S > >`.

10.280.1 Detailed Description

template<typename S> class mln::p_indexed_psite< S >

Psite class for indexed site sets such as [p_array](#)..

Definition at line 183 of file p_array.hh.

10.281 mln::p_key< K, P > Class Template Reference

Priority queue class.

```
#include <p_key.hh>
```

Inherits `site_set_base_< P, p_key< K, P > >`.

Public Types

- `typedef p_double_piter< self_, mln_bkd_eiter(util::set< K >), typename p_set< P >::bkd_piter > bkd_piter`

Backward Site_Iterator associated type.

- **typedef P element**
Element associated type.
- **typedef p_double_piter< self_, mln_fwd_eiter(util::set< K >), typename p_set< P >::fwd_piter > fwd_piter**
Forward Site_Iterator associated type.
- **typedef std::pair< K, P > i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_double_psite< self_, p_set< P > > psite**
Psite associated type.
- **typedef P r_element**
Removal element associated type.

Public Member Functions

- **void change_key (const K &k, const K &new_k)**
Change the key k into a new value new_k.
- **template<typename F > void change_keys (const Function_v2v< F > &f)**
Change the keys by applying the function f.
- **void clear ()**
Clear this site set.
- **bool exists_key (const K &key) const**
Test if the priority exists.
- **bool has (const psite &) const**
Test is the psite p belongs to this site set.
- **bool has (const P &p) const**
Test is the psite p belongs to this site set.
- **void insert (const i_element &k_p)**
Insert a pair k_p (key k, site p).
- **void insert (const K &k, const P &p)**
Insert a pair (key k, site p).
- **bool is_valid () const**
Test this set validity so returns always true.

- const K & **key** (const P &p) const
Give the key associated with site p.
- const **util::set< K > & keys** () const
Give the set of keys.
- std::size_t **memory_size** () const
Return the size of this site set in memory.
- unsigned **nsites** () const
Give the number of sites.
- const **p_set< P > & operator()** (const K &key) const
Give the queue with the priority priority.
- **p_key** ()
Constructor.
- void **remove** (const P &p)
Remove a site p.
- void **remove_key** (const K &k)
Remove all sites with key k.

10.281.1 Detailed Description

template<typename K, typename P> class mln::p_key< K, P >

Priority queue class.

Definition at line 72 of file p_key.hh.

10.281.2 Member Typedef Documentation

10.281.2.1 template<typename K , typename P > typedef p_double_piter<self_, mln_bkd_eiter(util::set<K>), typename p_set<P>::bkd_piter> mln::p_key< K, P >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 93 of file p_key.hh.

10.281.2.2 template<typename K , typename P > typedef P mln::p_key< K, P >::element

Element associated type.

Definition at line 79 of file p_key.hh.

10.281.2.3 template<typename K , typename P > typedef p_double_piter<self_, mln_fwd_eiter(util::set<K>), typename p_set<P>::fwd_piter> mln::p_key< K, P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 88 of file p_key.hh.

10.281.2.4 template<typename K , typename P > typedef std::pair<K,P> mln::p_key< K, P >::i_element

Insertion element associated type.

Definition at line 118 of file p_key.hh.

10.281.2.5 template<typename K , typename P > typedef fwd_piter mln::p_key< K, P >::piter

[Site_Iterator](#) associated type.

Definition at line 96 of file p_key.hh.

10.281.2.6 template<typename K , typename P > typedef p_double_psite< self_, p_set<P> > mln::p_key< K, P >::psite

Psite associated type.

Definition at line 83 of file p_key.hh.

10.281.2.7 template<typename K , typename P > typedef P mln::p_key< K, P >::r_element

Removal element associated type.

Definition at line 132 of file p_key.hh.

10.281.3 Constructor & Destructor Documentation

10.281.3.1 template<typename K , typename P > mln::p_key< K, P >::p_key() [inline]

Constructor.

Definition at line 208 of file p_key.hh.

10.281.4 Member Function Documentation

10.281.4.1 template<typename K , typename P > void mln::p_key< K, P >::change_key (const K & k, const K & new_k) [inline]

Change the key `k` into a new value `new_k`.

Definition at line 382 of file p_key.hh.

References `mln::p_set< P >::nsites()`.

10.281.4.2 template<typename K , typename P > template<typename F > void mln::p_key< K, P >::change_keys (const Function_v2v< F > & f) [inline]

Change the keys by applying the function *f*.

Definition at line 428 of file p_key.hh.

References mln::util::set< T >::insert().

10.281.4.3 template<typename K , typename P > void mln::p_key< K, P >::clear () [inline]

Clear this site set.

Definition at line 462 of file p_key.hh.

10.281.4.4 template<typename K , typename P > bool mln::p_key< K, P >::exists_key (const K & key) const [inline]

Test if the priority exists.

Definition at line 520 of file p_key.hh.

Referenced by mln::p_key< K, P >::operator()().

10.281.4.5 template<typename K , typename P > bool mln::p_key< K, P >::has (const P & p) const [inline]

Test is the psite *p* belongs to this site set.

Definition at line 227 of file p_key.hh.

10.281.4.6 template<typename K , typename P > bool mln::p_key< K, P >::has (const psite &) const [inline]

Test is the psite *p* belongs to this site set.

Definition at line 217 of file p_key.hh.

Referenced by mln::p_key< K, P >::insert().

10.281.4.7 template<typename K , typename P > void mln::p_key< K, P >::insert (const i_element & k_p) [inline]

Insert a pair *k_p* (key *k*, site *p*).

Definition at line 301 of file p_key.hh.

10.281.4.8 template<typename K , typename P > void mln::p_key< K, P >::insert (const K & k, const P & p) [inline]

Insert a pair (key *k*, site *p*).

Definition at line 268 of file p_key.hh.

References mln::p_key< K, P >::has().

10.281.4.9 template<typename K , typename P > bool mln::p_key< K, P >::is_valid () const [inline]

Test this set validity so returns always true.

Definition at line 236 of file p_key.hh.

10.281.4.10 template<typename K , typename P > const K & mln::p_key< K, P >::key (const P & p) const [inline]

Give the key associated with site p.

Definition at line 501 of file p_key.hh.

10.281.4.11 template<typename K , typename P > const util::set< K > & mln::p_key< K, P >::keys () const [inline]

Give the set of keys.

Definition at line 511 of file p_key.hh.

10.281.4.12 template<typename K , typename P > std::size_t mln::p_key< K, P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 475 of file p_key.hh.

10.281.4.13 template<typename K , typename P > unsigned mln::p_key< K, P >::nsites () const [inline]

Give the number of sites.

Definition at line 245 of file p_key.hh.

10.281.4.14 template<typename K , typename P > const p_set< P > & mln::p_key< K, P >::operator() (const K & key) const [inline]

Give the queue with the priority priority.

This method always works: if the priority is not in this set, an empty queue is returned.

Definition at line 489 of file p_key.hh.

References mln::p_key< K, P >::exists_key().

10.281.4.15 template<typename K , typename P > void mln::p_key< K, P >::remove (const P & p) [inline]

Remove a site p.

Definition at line 309 of file p_key.hh.

10.281.4.16 template<typename K , typename P > void mln::p_key< K, P >::remove_key (const K & k) [inline]

Remove all sites with key k.

Definition at line 351 of file p_key.hh.

References mln::p_set< P >::nsites().

10.282 mln::p_line2d Class Reference

2D discrete line of points.

```
#include <p_line2d.hh>
```

Inherits site_set_base_< point2d, p_line2d >.

Public Types

- **typedef p_indexed_bkd_piter< self_ > bkd_piter**
Backward Site_Iterator associated type.
- **typedef point2d element**
Element associated type.
- **typedef p_indexed_fwd_piter< self_ > fwd_piter**
Forward Site_Iterator associated type.
- **typedef p_indexed_fwd_piter< self_ > piter**
Site_Iterator associated type.
- **typedef p_indexed_psite< self_ > psite**
Psite associated type.
- **typedef const box2d & bbox**
Box (qualified) associated type.

Public Member Functions

- **const box2d & bbox () const**
Give the exact bounding box.
- **const point2d & begin () const**
Give the point that begins the line.
- **const point2d & end () const**
Give the point that ends the line.
- **bool has (const util::index &i) const**

Test if index i belongs to this point set.

- bool `has` (const `psite` &`p`) const

Test if p belongs to this point set.

- bool `is_valid` () const

Test if this line is valid, i.e., initialized.

- std::size_t `memory_size` () const

Return the size of this site set in memory.

- unsigned `nsites` () const

Give the number of points.

- const `point2d` & `operator[]` (unsigned i) const

Return the i -th point of the line.

- `p_line2d` (const `point2d` &`beg`, const `point2d` &`end`, bool `is_end_excluded=false`)

Constructor from point `beg` to point `end`.

- `p_line2d` ()

Constructor without argument.

- const std::vector< `point2d` > & `std_vector` () const

Return the corresponding std::vector of points.

10.282.1 Detailed Description

2D discrete line of points. It is based on `p_array`.

Definition at line 79 of file `p_line2d.hh`.

10.282.2 Member Typedef Documentation

10.282.2.1 `typedef p_indexed_bkd_piter<self>` mln::p_line2d::bkd_piter

Backward `Site_Iterator` associated type.

Definition at line 97 of file `p_line2d.hh`.

10.282.2.2 `typedef point2d` mln::p_line2d::element

Element associated type.

Definition at line 85 of file `p_line2d.hh`.

10.282.2.3 `typedef p_indexed_fwd_piter<self>` mln::p_line2d::fwd_piter

Forward `Site_Iterator` associated type.

Definition at line 94 of file `p_line2d.hh`.

10.282.2.4 `typedef p_indexed_fwd_piter<self_> mln::p_line2d::piter`

[Site_Iterator](#) associated type.

Definition at line 91 of file p_line2d.hh.

10.282.2.5 `typedef p_indexed_psite<self_> mln::p_line2d::psite`

Psite associated type.

Definition at line 88 of file p_line2d.hh.

10.282.2.6 `typedef const box2d& mln::p_line2d::q_box`

[Box](#) (qualified) associated type.

Definition at line 132 of file p_line2d.hh.

10.282.3 Constructor & Destructor Documentation**10.282.3.1 `mln::p_line2d::p_line2d() [inline]`**

Constructor without argument.

Definition at line 161 of file p_line2d.hh.

References `is_valid()`.

10.282.3.2 `mln::p_line2d::p_line2d(const point2d & beg, const point2d & end, bool is_end_excluded = false) [inline]`

Constructor from point `beg` to point `end`.

Definition at line 167 of file p_line2d.hh.

References `is_valid()`.

10.282.4 Member Function Documentation**10.282.4.1 `const box2d & mln::p_line2d::bbox() const [inline]`**

Give the exact bounding box.

Definition at line 273 of file p_line2d.hh.

References `is_valid()`.

10.282.4.2 `const point2d & mln::p_line2d::begin() const [inline]`

Give the point that begins the line.

Definition at line 307 of file p_line2d.hh.

References `is_valid()`.

Referenced by mln::debug::draw_graph().

10.282.4.3 const point2d & mln::p_line2d::end () const [inline]

Give the point that ends the line.

Definition at line 315 of file p_line2d.hh.

References is_valid(), and nsites().

Referenced by mln::debug::draw_graph().

10.282.4.4 bool mln::p_line2d::has (const psite & p) const [inline]

Test if p belongs to this point set.

Definition at line 240 of file p_line2d.hh.

10.282.4.5 bool mln::p_line2d::has (const util::index & i) const [inline]

Test if index i belongs to this point set.

Definition at line 251 of file p_line2d.hh.

References nsites().

10.282.4.6 bool mln::p_line2d::is_valid () const [inline]

Test if this line is valid, i.e., initialized.

Definition at line 258 of file p_line2d.hh.

References mln::implies().

Referenced by bbox(), begin(), end(), and p_line2d().

10.282.4.7 std::size_t mln::p_line2d::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 323 of file p_line2d.hh.

10.282.4.8 unsigned mln::p_line2d::nsites () const [inline]

Give the number of points.

Definition at line 266 of file p_line2d.hh.

Referenced by end(), has(), and operator[]().

10.282.4.9 const point2d & mln::p_line2d::operator[](unsigned i) const [inline]

Return the i-th point of the line.

Definition at line 299 of file p_line2d.hh.

References nsites().

10.282.4.10 const std::vector< point2d > & mln::p_line2d::std_vector() const [inline]

Return the corresponding std::vector of points.

Definition at line 281 of file p_line2d.hh.

10.283 mln::p Mutable_array_of< S > Class Template Reference

[p Mutable_array_of](#) is a mutable array of site sets.

```
#include <p Mutable_array_of.hh>
```

Inherits site_set_base< S::site, p Mutable_array_of< S > >.

Public Types

- **typedef p_double_piter< self_, mln_bkd_eiter(array_), typename S::bkd_piter > bkd_piter**
Backward Site_Iterator associated type.
- **typedef S element**
Element associated type.
- **typedef p_double_piter< self_, mln_fwd_eiter(array_), typename S::fwd_piter > fwd_piter**
Forward Site_Iterator associated type.
- **typedef S i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_double_psite< self_, element > psite**
Psite associated type.

Public Member Functions

- **void clear()**
Clear this set.
- **bool has (const psite &p) const**
Test if p belongs to this point set.
- **void insert (const S &s)**
Insert a site set s.
- **bool is_valid () const**

Test this set validity so returns always true.

- std::size_t **memory_size** () const
Return the size of this site set in memory.
- unsigned **nelements** () const
Give the number of elements (site sets) of this composite.
- S & **operator[]** (unsigned i)
Return the i -th site set (mutable version).
- const S & **operator[]** (unsigned i) const
Return the i -th site set (const version).
- **pMutableArray_of** ()
Constructor without arguments.
- void **reserve** (unsigned n)
Reserve memory for n elements.

10.283.1 Detailed Description

template<typename S> class mln::pMutableArray_of< S >

pMutableArray_of is a mutable array of site sets. Parameter S is the type of the contained site sets.
 Definition at line 76 of file pMutableArray_of.hh.

10.283.2 Member Typedef Documentation

10.283.2.1 **template<typename S > typedef pDoublePiter<self_, mln::bkd_eiter(array_), typename S ::bkd_piter> mln::pMutableArray_of< S >::bkd_piter**

Backward **Site_Iterator** associated type.

Definition at line 99 of file pMutableArray_of.hh.

10.283.2.2 **template<typename S > typedef S mln::pMutableArray_of< S >::element**

Element associated type.

Definition at line 85 of file pMutableArray_of.hh.

10.283.2.3 **template<typename S > typedef pDoublePiter<self_, mln::fwd_eiter(array_), typename S ::fwd_piter> mln::pMutableArray_of< S >::fwd_piter**

Forward **Site_Iterator** associated type.

Definition at line 94 of file pMutableArray_of.hh.

10.283.2.4 template<typename S > typedef S mln::pMutableArray_of< S >::i_element

Insertion element associated type.

Definition at line 121 of file p.MutableArray_of.hh.

10.283.2.5 template<typename S > typedef fwd_piter mln::pMutableArray_of< S >::piter

[Site_Iterator](#) associated type.

Definition at line 102 of file p.MutableArray_of.hh.

**10.283.2.6 template<typename S > typedef p_double_psite<self_, element>
mln::pMutableArray_of< S >::psite**

Psite associated type.

Definition at line 89 of file p.MutableArray_of.hh.

10.283.3 Constructor & Destructor Documentation**10.283.3.1 template<typename S > mln::pMutableArray_of< S >::pMutableArray_of()
[inline]**

Constructor without arguments.

Definition at line 175 of file p.MutableArray_of.hh.

10.283.4 Member Function Documentation**10.283.4.1 template<typename S > void mln::pMutableArray_of< S >::clear() [inline]**

Clear this set.

Definition at line 241 of file p.MutableArray_of.hh.

**10.283.4.2 template<typename S > bool mln::pMutableArray_of< S >::has(const psite & p)
const [inline]**

Test if p belongs to this point set.

Definition at line 190 of file p.MutableArray_of.hh.

**10.283.4.3 template<typename S > void mln::pMutableArray_of< S >::insert(const S & s)
[inline]**

Insert a site set s .

Precondition

s is valid.

Definition at line 206 of file p.MutableArray_of.hh.

10.283.4.4 template<typename S> bool mln::p Mutable_array_of< S >::is_valid () const [inline]

Test this set validity so returns always true.

Definition at line 198 of file p Mutable_array_of.hh.

10.283.4.5 template<typename S> std::size_t mln::p Mutable_array_of< S >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 258 of file p Mutable_array_of.hh.

10.283.4.6 template<typename S> unsigned mln::p Mutable_array_of< S >::nelements () const [inline]

Give the number of elements (site sets) of this composite.

Definition at line 233 of file p Mutable_array_of.hh.

10.283.4.7 template<typename S> S & mln::p Mutable_array_of< S >::operator[] (unsigned i) [inline]

Return the i -th site set (mutable version).

Definition at line 224 of file p Mutable_array_of.hh.

10.283.4.8 template<typename S> const S & mln::p Mutable_array_of< S >::operator[] (unsigned i) const [inline]

Return the i -th site set (const version).

Definition at line 215 of file p Mutable_array_of.hh.

10.283.4.9 template<typename S> void mln::p Mutable_array_of< S >::reserve (unsigned n) [inline]

Reserve memory for n elements.

Definition at line 182 of file p Mutable_array_of.hh.

10.284 mln::p_n_faces_bkd_piter< D, G > Class Template Reference

Backward iterator on the n-faces sites of an mln::p_complex<D, G>.

```
#include <p_n_faces_piter.hh>
```

Inherits p_complex_piter_base_< topo::n_face_bkd_iter< D >, p_complex< D, G >, G::site, p_n_faces_bkd_piter< D, G > >.

Public Member Functions

- void `next()`

Go to the next element.

- `p_n_faces_bkd_piter()`

Construction and assignment.

- unsigned `n() const`

Accessors.

10.284.1 Detailed Description

`template<unsigned D, typename G> class mln::p_n_faces_bkd_piter< D, G >`

Backward iterator on the n-faces sites of an `mln::p_complex<D, G>`.

Definition at line 92 of file `p_n_faces_piter.hh`.

10.284.2 Constructor & Destructor Documentation

10.284.2.1 `template<unsigned D, typename G> mln::p_n_faces_bkd_piter< D, G >::p_n_faces_bkd_piter() [inline]`

Construction and assignment.

Definition at line 169 of file `p_n_faces_piter.hh`.

10.284.3 Member Function Documentation

10.284.3.1 `template<unsigned D, typename G> unsigned mln::p_n_faces_bkd_piter< D, G >::n() const [inline]`

Accessors.

Shortcuts to face_’s accessors.

Definition at line 186 of file `p_n_faces_piter.hh`.

10.284.3.2 `void mln::Site_Iterator< p_n_faces_bkd_piter< D, G > >::next() [inherited]`

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the `next_` method.

Precondition

The iterator is valid.

10.285 mln::p_n_faces_fwd_piter< D, G > Class Template Reference

Forward iterator on the n-faces sites of an mln::p_complex<D, G>.

```
#include <p_n_faces_piter.hh>
```

Inherits p_complex_piter_base_< topo::n_face_fwd_iter< D >, p_complex< D, G >, G::site, p_n_faces_fwd_piter< D, G > .

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [p_n_faces_fwd_piter \(\)](#)

Construction and assignment.

- unsigned [n \(\) const](#)

Accessors.

10.285.1 Detailed Description

```
template<unsigned D, typename G> class mln::p_n_faces_fwd_piter< D, G >
```

Forward iterator on the n-faces sites of an mln::p_complex<D, G>.

Definition at line 56 of file p_n_faces_piter.hh.

10.285.2 Constructor & Destructor Documentation

10.285.2.1 template<unsigned D, typename G > mln::p_n_faces_fwd_piter< D, G >::p_n_faces_fwd_piter () [inline]

Construction and assignment.

Definition at line 132 of file p_n_faces_piter.hh.

10.285.3 Member Function Documentation

10.285.3.1 template<unsigned D, typename G > unsigned mln::p_n_faces_fwd_piter< D, G >::n () const [inline]

Accessors.

Shortcuts to face_’s accessors.

Definition at line 149 of file p_n_faces_piter.hh.

10.285.3.2 void mln::Site_Iterator< p_n_faces_fwd_piter< D, G > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.286 mln::p_priority< P, Q > Class Template Reference

Priority queue.

```
#include <p_priority.hh>
```

Inherits site_set_base_< Q::site, p_priority< P, Q > >.

Public Types

- **typedef p_double_piter< self_, mln_fwd_eiter(util::set< P >), typename Q::bkd_piter > bkd_piter**
Backward Site_Iterator associated type.
- **typedef Q::element element**
Element associated type.
- **typedef p_double_piter< self_, mln_bkd_eiter(util::set< P >), typename Q::fwd_piter > fwd_piter**
Forward Site_Iterator associated type.
- **typedef std::pair< P, element > i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_double_psite< self_, Q > psite**
Psite associated type.

Public Member Functions

- **void clear()**
Clear the queue.
- **bool exists_priority (const P &priority) const**
Test if the priority exists.

- const Q::element & **front** () const

Give an element with highest priority.

- bool **has** (const psite &) const

Test is the psite p belongs to this site set.

- const P **highest_priority** () const

Give the highest priority.

- void **insert** (const i_element &p_e)

Insert a pair p_e (priority p, element e).

- void **insert** (const p_priority< P, Q > &other)

Insert elements from another priority queue.

- bool **is_valid** () const

Test this set validity so returns always true.

- const P **lowest_priority** () const

Give the lowest priority.

- std::size_t **memory_size** () const

Return the size of this site set in memory.

- unsigned **nsites** () const

Give the number of sites.

- const Q & **operator()** (const P &priority) const

Give the queue with the priority priority.

- **p_priority** ()

Constructor.

- void **pop** ()

Pop (remove) from the queue an element with highest priority.

- Q::element **pop_front** ()

Return an element with highest priority and remove it from the set.

- const util::set< P > & **priorities** () const

Give the set of priorities.

- void **push** (const P &priority, const element &e)

Push in the queue with priority the element e.

10.286.1 Detailed Description

template<typename P, typename Q> class mln::p_priority< P, Q >

Priority queue. The parameter *P* is the type of the priorities (for instance `unsigned`).

The parameter *Q* is a type of queue (for instance `p_queue<point2d>`).

Definition at line 76 of file `p_priority.hh`.

10.286.2 Member Typedef Documentation

**10.286.2.1 template<typename P, typename Q> typedef p_double_piter< self_,
mln_fwd_eiter(util::set<P>), typename Q ::bkd_piter > mln::p_priority< P, Q
>::bkd_piter**

Backward [Site_Iterator](#) associated type.

Definition at line 98 of file `p_priority.hh`.

**10.286.2.2 template<typename P, typename Q> typedef Q ::element mln::p_priority< P, Q
>::element**

Element associated type.

Definition at line 84 of file `p_priority.hh`.

**10.286.2.3 template<typename P, typename Q> typedef p_double_piter< self_,
mln_bkd_eiter(util::set<P>), typename Q ::fwd_piter > mln::p_priority< P, Q
>::fwd_piter**

Forward [Site_Iterator](#) associated type.

Definition at line 93 of file `p_priority.hh`.

**10.286.2.4 template<typename P, typename Q> typedef std::pair<P, element> mln::p_priority<
P, Q >::i_element**

Insertion element associated type.

Definition at line 121 of file `p_priority.hh`.

10.286.2.5 template<typename P, typename Q> typedef fwd_piter mln::p_priority< P, Q >::piter

[Site_Iterator](#) associated type.

Definition at line 101 of file `p_priority.hh`.

**10.286.2.6 template<typename P, typename Q> typedef p_double_psite<self_, Q>
mln::p_priority< P, Q >::psite**

Psites associated type.

Definition at line 88 of file `p_priority.hh`.

10.286.3 Constructor & Destructor Documentation

10.286.3.1 template<typename P , typename Q > mln::p_priority< P, Q >::p_priority () [inline]

Constructor.

Definition at line 202 of file p_priority.hh.

10.286.4 Member Function Documentation

10.286.4.1 template<typename P , typename Q > void mln::p_priority< P, Q >::clear () [inline]

Clear the queue.

Definition at line 316 of file p_priority.hh.

10.286.4.2 template<typename P , typename Q > bool mln::p_priority< P, Q >::exists_priority (const P & priority) const [inline]

Test if the priority exists.

Definition at line 366 of file p_priority.hh.

Referenced by mln::p_priority< P, Q >::operator()().

10.286.4.3 template<typename P , typename Q > const Q::element & mln::p_priority< P, Q >::front () const [inline]

Give an element with highest priority.

If several elements have this priority, the least recently inserted is chosen.

Precondition

! is_empty()

Definition at line 294 of file p_priority.hh.

References mln::p_priority< P, Q >::highest_priority().

Referenced by mln::morpho::meyer_wst(), and mln::morpho::watershed::topological().

10.286.4.4 template<typename P , typename Q > bool mln::p_priority< P, Q >::has (const psite &) const [inline]

Test is the psite p belongs to this site set.

Definition at line 211 of file p_priority.hh.

10.286.4.5 template<typename P , typename Q > const P mln::p_priority< P, Q >::highest_priority () const [inline]

Give the highest priority.

Precondition

```
! is_empty()
```

Definition at line 375 of file p_priority.hh.

Referenced by mln::p_priority< P, Q >::front(), and mln::p_priority< P, Q >::pop().

10.286.4.6 template<typename P , typename Q > void mln::p_priority< P, Q >::insert (const i_element & p_e) [inline]

Insert a pair p_e (priority p , element e).

Definition at line 251 of file p_priority.hh.

References mln::p_priority< P, Q >::push().

10.286.4.7 template<typename P , typename Q > void mln::p_priority< P, Q >::insert (const p_priority< P, Q > & other) [inline]

Insert elements from another priority queue.

Definition at line 259 of file p_priority.hh.

10.286.4.8 template<typename P , typename Q > bool mln::p_priority< P, Q >::is_valid () const [inline]

Test this set validity so returns always true.

Definition at line 221 of file p_priority.hh.

10.286.4.9 template<typename P , typename Q > const P mln::p_priority< P, Q >::lowest_priority () const [inline]

Give the lowest priority.

Precondition

```
! is_empty()
```

Definition at line 384 of file p_priority.hh.

10.286.4.10 template<typename P , typename Q > std::size_t mln::p_priority< P, Q >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 328 of file p_priority.hh.

10.286.4.11 template<typename P , typename Q > unsigned mln::p_priority< P, Q >::nsites () const [inline]

Give the number of sites.

Definition at line 230 of file p_priority.hh.

Referenced by mln::p_priority< P, Q >::operator()().

**10.286.4.12 template<typename P , typename Q > const Q & mln::p_priority< P, Q >::operator()
(const P & priority) const [inline]**

Give the queue with the priority priority.

This method always works: if the priority is not in this set, an empty queue is returned.

Definition at line 341 of file p_priority.hh.

References mln::p_priority< P, Q >::exists_priority(), and mln::p_priority< P, Q >::nsites().

**10.286.4.13 template<typename P , typename Q > void mln::p_priority< P, Q >::pop()
[inline]**

Pop (remove) from the queue an element with highest priority.

If several elements have this priority, the least recently inserted is chosen.

Precondition

! is_empty()

Definition at line 277 of file p_priority.hh.

References mln::p_priority< P, Q >::highest_priority().

Referenced by mln::morpho::meyer_wst(), and mln::morpho::watershed::topological().

**10.286.4.14 template<typename P , typename Q > Q::element mln::p_priority< P, Q
>::pop_front() [inline]**

Return an element with highest priority and remove it from the set.

If several elements have this priority, the least recently inserted is chosen.

Precondition

! is_empty()

Definition at line 304 of file p_priority.hh.

**10.286.4.15 template<typename P , typename Q > const util::set< P > & mln::p_priority< P, Q
>::priorities() const [inline]**

Give the set of priorities.

Definition at line 357 of file p_priority.hh.

**10.286.4.16 template<typename P , typename Q > void mln::p_priority< P, Q >::push(const P
& priority, const element & e) [inline]**

Push in the queue with priority the element e.

Definition at line 239 of file p_priority.hh.

Referenced by mln::p_priority< P, Q >::insert(), mln::morpho::meyer_wst(), and mln::morpho::watershed::topological().

10.287 mln::p_queue< P > Class Template Reference

Queue of sites (based on std::deque).

```
#include <p_queue.hh>
```

Inherits site_set_base< P, p_queue< P > >.

Public Types

- **typedef p_indexed_bkd_piter< self_ > bkd_piter**
Backward Site Iterator associated type.
- **typedef P element**
Element associated type.
- **typedef p_indexed_fwd_piter< self_ > fwd_piter**
Forward Site Iterator associated type.
- **typedef P i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site Iterator associated type.
- **typedef p_indexed_psite< self_ > psite**
Psite associated type.

Public Member Functions

- **void clear ()**
Clear the queue.
- **const P & front () const**
Give the front site p of the queue; p is the least recently inserted site.
- **bool has (const psite &p) const**
Test if p belongs to this site set.
- **bool has (const util::index &i) const**
Test if index i belongs to this site set.
- **void insert (const P &p)**
Insert a site p (equivalent as 'push').

- `bool is_valid () const`
This set is always valid so it returns true.
- `std::size_t memory_size () const`
Return the size of this site set in memory.
- `unsigned nsites () const`
Give the number of sites.
- `const P & operator[] (unsigned i) const`
Return the i -th site.
- `p_queue ()`
Constructor without argument.
- `void pop ()`
Pop (remove) the front site p from the queue; p is the least recently inserted site.
- `P pop_front ()`
Pop (remove) the front site p from the queue; p is the least recently inserted site and give the front site p of the queue; p is the least recently inserted site.
- `void push (const P &p)`
Push a site p in the queue.
- `const std::deque< P > & std_deque () const`
Return the corresponding std::deque of sites.

10.287.1 Detailed Description

`template<typename P> class mln::p_queue< P >`

Queue of sites (based on `std::deque`). The parameter `P` shall be a site or pseudo-site type.

Definition at line 74 of file `p_queue.hh`.

10.287.2 Member Typedef Documentation

10.287.2.1 `template<typename P> typedef p_indexed_bkd_piter<self_> mln::p_queue< P >::bkd_piter`

Backward `Site_Iterator` associated type.

Definition at line 90 of file `p_queue.hh`.

10.287.2.2 `template<typename P> typedef P mln::p_queue< P >::element`

Element associated type.

Definition at line 80 of file `p_queue.hh`.

10.287.2.3 template<typename P> typedef p_indexed_fwd_piter<self_> mln::p_queue< P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 87 of file p_queue.hh.

10.287.2.4 template<typename P> typedef P mln::p_queue< P >::i_element

Insertion element associated type.

Definition at line 118 of file p_queue.hh.

10.287.2.5 template<typename P> typedef fwd_piter mln::p_queue< P >::piter

[Site_Iterator](#) associated type.

Definition at line 93 of file p_queue.hh.

10.287.2.6 template<typename P> typedef p_indexed_psite<self_> mln::p_queue< P >::psite

Psite associated type.

Definition at line 84 of file p_queue.hh.

10.287.3 Constructor & Destructor Documentation

10.287.3.1 template<typename P> mln::p_queue< P >::p_queue() [inline]

Constructor without argument.

Definition at line 163 of file p_queue.hh.

10.287.4 Member Function Documentation

10.287.4.1 template<typename P> void mln::p_queue< P >::clear() [inline]

Clear the queue.

Definition at line 244 of file p_queue.hh.

10.287.4.2 template<typename P> const P & mln::p_queue< P >::front() const [inline]

Give the front site p of the queue; p is the least recently inserted site.

Definition at line 224 of file p_queue.hh.

Referenced by `mln::p_queue< P >::pop_front()`, and `mln::geom::impl::seeds2tiling()`.

10.287.4.3 template<typename P> bool mln::p_queue< P >::has(const util::index & i) const [inline]

Test if index i belongs to this site set.

Definition at line 183 of file p_queue.hh.

References mln::p_queue< P >::nsites().

10.287.4.4 template<typename P> bool mln::p_queue< P >::has (const psite & p) const [inline]

Test if p belongs to this site set.

Definition at line 170 of file p_queue.hh.

References mln::p_queue< P >::nsites().

10.287.4.5 template<typename P> void mln::p_queue< P >::insert (const P & p) [inline]

Insert a site p (equivalent as 'push').

Definition at line 261 of file p_queue.hh.

References mln::p_queue< P >::push().

10.287.4.6 template<typename P> bool mln::p_queue< P >::is_valid () const [inline]

This set is always valid so it returns true.

Definition at line 191 of file p_queue.hh.

10.287.4.7 template<typename P> std::size_t mln::p_queue< P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 277 of file p_queue.hh.

References mln::p_queue< P >::nsites().

10.287.4.8 template<typename P> unsigned mln::p_queue< P >::nsites () const [inline]

Give the number of sites.

Definition at line 199 of file p_queue.hh.

Referenced by mln::p_queue< P >::has(), mln::p_queue< P >::memory_size(), and mln::p_queue< P >::operator[]().

10.287.4.9 template<typename P> const P & mln::p_queue< P >::operator[](unsigned i) const [inline]

Return the i-th site.

Definition at line 252 of file p_queue.hh.

References mln::p_queue< P >::nsites().

10.287.4.10 template<typename P> void mln::p_queue< P >::pop() [inline]

Pop (remove) the front site p from the queue; p is the least recently inserted site.

Definition at line 215 of file p_queue.hh.

Referenced by mln::p_queue< P >::pop_front(), and mln::geom::impl::seeds2tiling().

10.287.4.11 template<typename P> P mln::p_queue< P >::pop_front() [inline]

Pop (remove) the front site p from the queue; p is the least recently inserted site and give the front site p of the queue; p is the least recently inserted site.

Definition at line 233 of file p_queue.hh.

References mln::p_queue< P >::front(), and mln::p_queue< P >::pop().

10.287.4.12 template<typename P> void mln::p_queue< P >::push(const P & p) [inline]

Push a site p in the queue.

Definition at line 207 of file p_queue.hh.

Referenced by mln::p_queue< P >::insert(), and mln::geom::impl::seeds2tiling().

10.287.4.13 template<typename P> const std::deque< P > & mln::p_queue< P >::std_deque() const [inline]

Return the corresponding std::deque of sites.

Definition at line 269 of file p_queue.hh.

10.288 mln::p_queue_fast< P > Class Template Reference

Queue of sites class (based on [p_array](#).

```
#include <p_queue_fast.hh>
```

Inherits site_set_base_< P, p_queue_fast< P > >.

Public Types

- **typedef p_indexed_bkd_piter< self_ > bkd_piter**
Backward Site Iterator associated type.
- **typedef P element**
Element associated type.
- **typedef p_indexed_fwd_piter< self_ > fwd_piter**
Forward Site Iterator associated type.
- **typedef P i_element**
Insertion element associated type.

- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_indexed_psite< self_ > psite**
Psite associated type.

Public Member Functions

- **void clear ()**
Clear the queue.
- **bool compute_has (const P &p) const**
Test if p belongs to this site set.
- **bool empty () const**
Test if the queue is empty.
- **const P & front () const**
Give the front site p of the queue; p is the least recently inserted site.
- **bool has (const util::index &i) const**
Test if index i belongs to this site set.
- **bool has (const psite &p) const**
Test if p belongs to this site set.
- **void insert (const P &p)**
Insert a site p (equivalent as 'push').
- **bool is_valid () const**
This set is always valid so it returns true.
- **std::size_t memory_size () const**
Return the size of this site set in memory.
- **unsigned nsites () const**
Give the number of sites.
- **const P & operator[] (unsigned i) const**
Return the i-th site.
- **p_queue_fast ()**
Constructor without argument.
- **void pop ()**
Pop (remove) the front site p from the queue; p is the least recently inserted site.

- const P & [pop_front](#) ()

Pop (remove) the front site p from the queue; p is the least recently inserted site and give the front site p of the queue; p is the least recently inserted site.

- void [purge](#) ()

Purge the queue to save (free) some memory.

- void [push](#) (const P &p)

Push a site p in the queue.

- void [reserve](#) (typename p_array< P >::size_type n)

Reserve n cells.

- const std::vector< P > & [std_vector](#) () const

Return the corresponding std::vector of sites.

10.288.1 Detailed Description

template<typename P> class mln::p_queue_fast< P >

Queue of sites class (based on [p_array](#).).

This container is efficient; FIXME: explain...

The parameter P shall be a site or pseudo-site type.

Definition at line 72 of file p_queue_fast.hh.

10.288.2 Member Typedef Documentation

10.288.2.1 template<typename P> typedef p_indexed_bkd_piter<self_> mln::p_queue_fast< P >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 87 of file p_queue_fast.hh.

10.288.2.2 template<typename P> typedef P mln::p_queue_fast< P >::element

Element associated type.

Definition at line 78 of file p_queue_fast.hh.

10.288.2.3 template<typename P> typedef p_indexed_fwd_piter<self_> mln::p_queue_fast< P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 84 of file p_queue_fast.hh.

10.288.2.4 template<typename P> typedef P mln::p_queue_fast< P >::i_element

Insertion element associated type.

Definition at line 121 of file `p_queue_fast.hh`.

10.288.2.5 template<typename P> typedef fwd_piter mln::p_queue_fast< P >::piter

[Site_Iterator](#) associated type.

Definition at line 90 of file `p_queue_fast.hh`.

10.288.2.6 template<typename P> typedef p_indexed_psite<self_> mln::p_queue_fast< P >::psite

Psite associated type.

Definition at line 81 of file `p_queue_fast.hh`.

10.288.3 Constructor & Destructor Documentation

10.288.3.1 template<typename P> mln::p_queue_fast< P >::p_queue_fast() [inline]

Constructor without argument.

Definition at line 170 of file `p_queue_fast.hh`.

10.288.4 Member Function Documentation

10.288.4.1 template<typename P> void mln::p_queue_fast< P >::clear() [inline]

Clear the queue.

Definition at line 297 of file `p_queue_fast.hh`.

10.288.4.2 template<typename P> bool mln::p_queue_fast< P >::compute_has(const P & p) const [inline]

Test if `p` belongs to this site set.

Definition at line 222 of file `p_queue_fast.hh`.

10.288.4.3 template<typename P> bool mln::p_queue_fast< P >::empty() const [inline]

Test if the queue is empty.

Definition at line 250 of file `p_queue_fast.hh`.

10.288.4.4 template<typename P> const P & mln::p_queue_fast< P >::front() const [inline]

Give the front site `p` of the queue; `p` is the least recently inserted site.

Definition at line 277 of file p_queue_fast.hh.

Referenced by mln::p_queue_fast< P >::pop_front().

10.288.4.5 template<typename P> bool mln::p_queue_fast< P >::has (const psite & p) const [inline]

Test if p belongs to this site set.

Definition at line 201 of file p_queue_fast.hh.

References mln::p_queue_fast< P >::nsites().

10.288.4.6 template<typename P> bool mln::p_queue_fast< P >::has (const util::index & i) const [inline]

Test if index i belongs to this site set.

Definition at line 214 of file p_queue_fast.hh.

References mln::p_queue_fast< P >::nsites().

10.288.4.7 template<typename P> void mln::p_queue_fast< P >::insert (const P & p) [inline]

Insert a site p (equivalent as 'push').

Definition at line 314 of file p_queue_fast.hh.

References mln::p_queue_fast< P >::push().

10.288.4.8 template<typename P> bool mln::p_queue_fast< P >::is_valid () const [inline]

This set is always valid so it returns true.

Definition at line 233 of file p_queue_fast.hh.

10.288.4.9 template<typename P> std::size_t mln::p_queue_fast< P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 330 of file p_queue_fast.hh.

10.288.4.10 template<typename P> unsigned mln::p_queue_fast< P >::nsites () const [inline]

Give the number of sites.

Definition at line 241 of file p_queue_fast.hh.

Referenced by mln::p_queue_fast< P >::has(), and mln::p_queue_fast< P >::operator[]().

10.288.4.11 template<typename P> const P & mln::p_queue_fast< P >::operator[](unsigned i) const [inline]

Return the i -th site.

Definition at line 305 of file p_queue_fast.hh.

References `mln::p_queue_fast< P >::nsites()`.

10.288.4.12 template<typename P> void mln::p_queue_fast< P >::pop() [inline]

Pop (remove) the front site p from the queue; p is the least recently inserted site.

Definition at line 268 of file p_queue_fast.hh.

Referenced by `mln::p_queue_fast< P >::pop_front()`.

10.288.4.13 template<typename P> const P & mln::p_queue_fast< P >::pop_front() [inline]

Pop (remove) the front site p from the queue; p is the least recently inserted site and give the front site p of the queue; p is the least recently inserted site.

Definition at line 286 of file p_queue_fast.hh.

References `mln::p_queue_fast< P >::front()`, and `mln::p_queue_fast< P >::pop()`.

10.288.4.14 template<typename P> void mln::p_queue_fast< P >::purge() [inline]

Purge the queue to save (free) some memory.

Definition at line 187 of file p_queue_fast.hh.

10.288.4.15 template<typename P> void mln::p_queue_fast< P >::push(const P & p) [inline]

Push a site p in the queue.

Definition at line 259 of file p_queue_fast.hh.

Referenced by `mln::p_queue_fast< P >::insert()`.

10.288.4.16 template<typename P> void mln::p_queue_fast< P >::reserve(typename p_array< P >::size_type n) [inline]

Reserve n cells.

Definition at line 179 of file p_queue_fast.hh.

10.288.4.17 template<typename P> const std::vector< P > & mln::p_queue_fast< P >::std_vector() const [inline]

Return the corresponding std::vector of sites.

Definition at line 322 of file p_queue_fast.hh.

10.289 mln::p_run< P > Class Template Reference

[Point](#) set class in run.

```
#include <p_run.hh>
```

Inherits site_set_base_< P, p_run< P > >.

Public Types

- **typedef p_run_bkd_piter_< P > bkd_piter**
Backward Site_Iterator associated type.
- **typedef P element**
Element associated type.
- **typedef p_run_fwd_piter_< P > fwd_piter**
Forward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_run_psite< P > psite**
Psite associated type.
- **typedef mln::box< P > q_box**
Box associated type.

Public Member Functions

- **mln::box< P > bbox () const**
Give the exact bounding box.
- **P end () const**
Return (compute) the ending point.
- **bool has (const P &p) const**
Test if p belongs to this point set.
- **bool has (const psite &p) const**
Test if p belongs to this point set.
- **bool has_index (unsigned short i) const**
Test if index i belongs to this point set.
- **void init (const P &start, unsigned short len)**
Set the starting point.
- **bool is_valid () const**

Test if this run is valid, i.e., with length > 0.

- `unsigned short length () const`
Give the length of the run.
- `std::size_t memory_size () const`
Return the size of this site set in memory.
- `unsigned nsites () const`
Give the number of sites.
- `P operator[](unsigned short i) const`
Return the i -th point.
- `p_run()`
Constructor without argument.
- `p_run(const P &start, unsigned short len)`
Constructor.
- `p_run(const P &start, const P &end)`
Constructor.
- `const P & start () const`
Return the starting point.

10.289.1 Detailed Description

`template<typename P> class mln::p_run< P >`

`Point` set class in run. This is a mathematical set of points (not a multi-set). The parameter `P` shall be a `Point` type.

Definition at line 86 of file p_run.hh.

10.289.2 Member Typedef Documentation

10.289.2.1 template<typename P> typedef p_run_bkd_piter_<P> mln::p_run< P >::bkd_piter

Backward `Site_Iterator` associated type.

Definition at line 101 of file p_run.hh.

10.289.2.2 template<typename P> typedef P mln::p_run< P >::element

Element associated type.

Definition at line 91 of file p_run.hh.

10.289.2.3 template<typename P> typedef p_run_fwd_piter_<P> mln::p_run< P >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 98 of file p_run.hh.

10.289.2.4 template<typename P> typedef fwd_piter mln::p_run< P >::piter

[Site_Iterator](#) associated type.

Definition at line 104 of file p_run.hh.

10.289.2.5 template<typename P> typedef p_run_psite<P> mln::p_run< P >::psite

Psite associated type.

Definition at line 95 of file p_run.hh.

10.289.2.6 template<typename P> typedef mln::box<P> mln::p_run< P >::q_box

[Box](#) associated type.

Definition at line 149 of file p_run.hh.

10.289.3 Constructor & Destructor Documentation

10.289.3.1 template<typename P> mln::p_run< P >::p_run() [inline]

Constructor without argument.

Definition at line 223 of file p_run.hh.

10.289.3.2 template<typename P> mln::p_run< P >::p_run(const P & start, unsigned short len) [inline]

Constructor.

Definition at line 230 of file p_run.hh.

References mln::p_run< P >::init().

10.289.3.3 template<typename P> mln::p_run< P >::p_run(const P & start, const P & end) [inline]

Constructor.

Definition at line 238 of file p_run.hh.

10.289.4 Member Function Documentation

10.289.4.1 `template<typename P> mln::box< P > mln::p_run< P >::bbox() const [inline]`

Give the exact bounding box.

Definition at line 267 of file `p_run.hh`.

References `mln::p_run< P >::end()`.

10.289.4.2 `template<typename P> P mln::p_run< P >::end() const [inline]`

Return (compute) the ending point.

Definition at line 348 of file `p_run.hh`.

References `mln::point< G, C >::last_coord()`.

Referenced by `mln::p_run< P >::bbox()`.

10.289.4.3 `template<typename P> bool mln::p_run< P >::has(const psite & p) const [inline]`

Test if `p` belongs to this point set.

Definition at line 276 of file `p_run.hh`.

10.289.4.4 `template<typename P> bool mln::p_run< P >::has(const P & p) const [inline]`

Test if `p` belongs to this point set.

Definition at line 289 of file `p_run.hh`.

References `mln::p_run< P >::is_valid()`.

10.289.4.5 `template<typename P> bool mln::p_run< P >::has_index(unsigned short i) const [inline]`

Test if index `i` belongs to this point set.

Definition at line 302 of file `p_run.hh`.

10.289.4.6 `template<typename P> void mln::p_run< P >::init(const P & start, unsigned short len) [inline]`

Set the starting point.

Definition at line 249 of file `p_run.hh`.

Referenced by `mln::p_run< P >::p_run()`.

10.289.4.7 template<typename P> bool mln::p_run<P>::is_valid() const [inline]

Test if this run is valid, i.e., with length > 0.

Definition at line 259 of file p_run.hh.

Referenced by mln::p_run<P>::has(), mln::p_run<P>::length(), mln::p_run<P>::nsites(), and mln::p_run<P>::operator[]().

10.289.4.8 template<typename P> unsigned short mln::p_run<P>::length() const [inline]

Give the length of the run.

Definition at line 319 of file p_run.hh.

References mln::p_run<P>::is_valid().

10.289.4.9 template<typename P> std::size_t mln::p_run<P>::memory_size() const [inline]

Return the size of this site set in memory.

Definition at line 358 of file p_run.hh.

10.289.4.10 template<typename P> unsigned mln::p_run<P>::nsites() const [inline]

Give the number of sites.

Definition at line 310 of file p_run.hh.

References mln::p_run<P>::is_valid().

10.289.4.11 template<typename P> P mln::p_run<P>::operator[](unsigned short i) const [inline]

Return the i -th point.

Definition at line 328 of file p_run.hh.

References mln::p_run<P>::is_valid(), and mln::point<G, C>::last_coord().

10.289.4.12 template<typename P> const P& mln::p_run<P>::start() const [inline]

Return the starting point.

Definition at line 340 of file p_run.hh.

10.290 mln::p_set<P> Class Template Reference

Mathematical set of sites (based on [util::set](#)).

```
#include <p_set.hh>
```

Inherits site_set_base_<P, p_set<P>>.

Public Types

- **typedef p_indexed_bkd_piter< self_ > bkd_piter**
Backward Site_Iterator associated type.
- **typedef P element**
Element associated type.
- **typedef p_indexed_fwd_piter< self_ > fwd_piter**
Forward Site_Iterator associated type.
- **typedef P i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef p_indexed_psite< self_ > psite**
Psite associated type.
- **typedef P r_element**
Removal element associated type.

Public Member Functions

- **void clear ()**
Clear this set.
- **bool has (const psite &p) const**
Test if psite p belongs to this point set.
- **bool has (const util::index &i) const**
Test if index i belongs to this point set.
- **bool has (const P &p) const**
Test if p belongs to this point set.
- **void insert (const P &p)**
Insert a site p.
- **bool is_valid () const**
Test this set validity so returns always true.
- **std::size_t memory_size () const**
Return the size of this site set in memory.
- **unsigned nsites () const**
Give the number of sites.

- const P & `operator[]` (unsigned i) const
Return the i -th site.
- `p_set()`
Constructor.
- void `remove` (const P &p)
Remove a site p .
- const std::vector< P > & `std_vector()` const
Return the corresponding std::vector of sites.
- const util::set< P > & `util_set()` const
Return the corresponding util::set of sites.

10.290.1 Detailed Description

`template<typename P> class mln::p_set< P >`

Mathematical set of sites (based on `util::set`). This is a mathematical set of sites (not a multi-set).

The parameter P shall be a site or pseudo-site type.

Definition at line 70 of file p_set.hh.

10.290.2 Member Typedef Documentation

10.290.2.1 `template<typename P> typedef p_indexed_bkd_piter<self_> mln::p_set< P >::bkd_piter`

Backward `Site_Iterator` associated type.

Definition at line 85 of file p_set.hh.

10.290.2.2 `template<typename P> typedef P mln::p_set< P >::element`

Element associated type.

Definition at line 76 of file p_set.hh.

10.290.2.3 `template<typename P> typedef p_indexed_fwd_piter<self_> mln::p_set< P >::fwd_piter`

Forward `Site_Iterator` associated type.

Definition at line 82 of file p_set.hh.

10.290.2.4 `template<typename P> typedef P mln::p_set< P >::i_element`

Insertion element associated type.

Definition at line 113 of file p_set.hh.

10.290.2.5 template<typename P> typedef fwd_piter mln::p_set< P >::piter

[Site_Iterator](#) associated type.

Definition at line 88 of file p_set.hh.

10.290.2.6 template<typename P> typedef p_indexed_psite<self_> mln::p_set< P >::psite

Psite associated type.

Definition at line 79 of file p_set.hh.

10.290.2.7 template<typename P> typedef P mln::p_set< P >::r_element

Removal element associated type.

Definition at line 119 of file p_set.hh.

10.290.3 Constructor & Destructor Documentation**10.290.3.1 template<typename P> mln::p_set< P >::p_set() [inline]**

Constructor.

Definition at line 152 of file p_set.hh.

10.290.4 Member Function Documentation**10.290.4.1 template<typename P> void mln::p_set< P >::clear() [inline]**

Clear this set.

Definition at line 219 of file p_set.hh.

10.290.4.2 template<typename P> bool mln::p_set< P >::has(const psite & p) const [inline]

Test if psite *p* belongs to this point set.

Definition at line 167 of file p_set.hh.

10.290.4.3 template<typename P> bool mln::p_set< P >::has(const P & p) const [inline]

Test if *p* belongs to this point set.

Definition at line 159 of file p_set.hh.

10.290.4.4 template<typename P> bool mln::p_set< P >::has(const util::index & i) const [inline]

Test if index *i* belongs to this point set.

Definition at line 179 of file p_set.hh.

References mln::p_set< P >::nsites().

10.290.4.5 template<typename P> void mln::p_set< P >::insert (const P & p) [inline]

Insert a site p.

Definition at line 203 of file p_set.hh.

Referenced by mln::convert::to_p_set().

10.290.4.6 template<typename P> bool mln::p_set< P >::is_valid () const [inline]

Test this set validity so returns always true.

Definition at line 187 of file p_set.hh.

10.290.4.7 template<typename P> std::size_t mln::p_set< P >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 236 of file p_set.hh.

10.290.4.8 template<typename P> unsigned mln::p_set< P >::nsites () const [inline]

Give the number of sites.

Definition at line 195 of file p_set.hh.

Referenced by mln::p_key< K, P >::change_key(), mln::p_set< P >::has(), mln::p_set< P >::operator[](), and mln::p_key< K, P >::remove_key().

10.290.4.9 template<typename P> const P & mln::p_set< P >::operator[] (unsigned i) const [inline]

Return the *i*-th site.

Definition at line 227 of file p_set.hh.

References mln::p_set< P >::nsites().

10.290.4.10 template<typename P> void mln::p_set< P >::remove (const P & p) [inline]

Remove a site p.

Definition at line 211 of file p_set.hh.

10.290.4.11 template<typename P> const std::vector< P > & mln::p_set< P >::std_vector () const [inline]

Return the corresponding std::vector of sites.

Definition at line 244 of file p_set.hh.

10.290.4.12 template<typename P> const util::set< P > & mln::p_set< P >::util_set() const [inline]

Return the corresponding [util::set](#) of sites.

Definition at line 252 of file p_set.hh.

10.291 mln::p_set_of< S > Class Template Reference

[p_set_of](#) is a set of site sets.

```
#include <p_set_of.hh>
```

Inherits [site_set_base< S::site, p_set_of< S > >](#), and [site_set_impl< S >](#).

Public Types

- [typedef p_double_piter< self_, mln_bkd_eiter\(set_\)>, typename S::bkd_piter > bkd_piter](#)
Backward Site_Iterator associated type.
- [typedef S element](#)
Element associated type.
- [typedef p_double_piter< self_, mln_fwd_eiter\(set_\)>, typename S::fwd_piter > fwd_piter](#)
Forward Site_Iterator associated type.
- [typedef S i_element](#)
Insertion element associated type.
- [typedef fwd_piter piter](#)
Site_Iterator associated type.
- [typedef p_double_psite< self_, element > psite](#)
Psite associated type.

Public Member Functions

- [void clear\(\)](#)
Clear this set.
- [bool has\(const psite &p\) const](#)
Test if p belongs to this point set.
- [void insert\(const S &s\)](#)
Insert a site set s.
- [bool is_valid\(\) const](#)
Test if this set of runs is valid.

- `std::size_t memory_size () const`
Return the size of this site set in memory.
- `unsigned nelements () const`
Give the number of elements (site sets) of this composite.
- `const S & operator[] (unsigned i) const`
Return the i -th site set.
- `p_set_of ()`
Constructor without arguments.

10.291.1 Detailed Description

`template<typename S> class mln::p_set_of< S >`

`p_set_of` is a set of site sets. Parameter `S` is the type of the contained site sets.

Definition at line 71 of file `p_set_of.hh`.

10.291.2 Member Typedef Documentation

10.291.2.1 `template<typename S > typedef p_double_piter<self_, mln_bkd_eiter(set_), typename S ::bkd_piter> mln::p_set_of< S >::bkd_piter`

Backward `Site_Iterator` associated type.

Definition at line 95 of file `p_set_of.hh`.

10.291.2.2 `template<typename S > typedef S mln::p_set_of< S >::element`

Element associated type.

Definition at line 81 of file `p_set_of.hh`.

10.291.2.3 `template<typename S > typedef p_double_piter<self_, mln_fwd_eiter(set_), typename S ::fwd_piter> mln::p_set_of< S >::fwd_piter`

Forward `Site_Iterator` associated type.

Definition at line 90 of file `p_set_of.hh`.

10.291.2.4 `template<typename S > typedef S mln::p_set_of< S >::i_element`

Insertion element associated type.

Definition at line 113 of file `p_set_of.hh`.

10.291.2.5 template<typename S > typedef fwd_piter mln::p_set_of< S >::piter

[Site_Iterator](#) associated type.

Definition at line 98 of file p_set_of.hh.

10.291.2.6 template<typename S > typedef p_double_psite<self_, element> mln::p_set_of< S >::psite

Psite associated type.

Definition at line 85 of file p_set_of.hh.

10.291.3 Constructor & Destructor Documentation

10.291.3.1 template<typename S > mln::p_set_of< S >::p_set_of() [inline]

Constructor without arguments.

Definition at line 160 of file p_set_of.hh.

10.291.4 Member Function Documentation

10.291.4.1 template<typename S > void mln::p_set_of< S >::clear() [inline]

Clear this set.

Definition at line 211 of file p_set_of.hh.

10.291.4.2 template<typename S > bool mln::p_set_of< S >::has(const psite & p) const [inline]

Test if p belongs to this point set.

Definition at line 167 of file p_set_of.hh.

10.291.4.3 template<typename S > void mln::p_set_of< S >::insert(const S & s) [inline]

Insert a site set s.

Definition at line 183 of file p_set_of.hh.

10.291.4.4 template<typename S > bool mln::p_set_of< S >::is_valid() const [inline]

Test if this set of runs is valid.

Definition at line 175 of file p_set_of.hh.

10.291.4.5 template<typename S > std::size_t mln::p_set_of< S >::memory_size() const [inline]

Return the size of this site set in memory.

Definition at line 220 of file p_set_of.hh.

10.291.4.6 template<typename S> unsigned mln::p_set_of< S >::elements() const [inline]

Give the number of elements (site sets) of this composite.

Definition at line 203 of file p_set_of.hh.

10.291.4.7 template<typename S> const S & mln::p_set_of< S >::operator[](unsigned i) const [inline]

Return the i -th site set.

Definition at line 194 of file p_set_of.hh.

10.292 mln::p_transformed< S, F > Class Template Reference

[Site](#) set transformed through a function.

```
#include <p_transformed.hh>
```

Inherits [site_set_base< S::psite, p_transformed< S, F > >](#).

Public Types

- **typedef p_transformed_piter< typename S::bkd_piter, S, F > bkd_piter**
Backward Site_Iterator associated type.
- **typedef S::element element**
Element associated type.
- **typedef p_transformed_piter< typename S::fwd_piter, S, F > fwd_piter**
Forward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.
- **typedef S::psite psite**
Psite associated type.

Public Member Functions

- **const F & function()** const
Return the transformation function.
- **bool has(const psite &p)** const
Test if p belongs to the subset.

- `bool is_valid () const`
Test if this site set is valid.
- `std::size_t memory_size () const`
Return the size of this site set in memory.
- `p_transformed ()`
Constructor without argument.
- `p_transformed (const S &s, const F &f)`
Constructor with a site set s and a predicate f.
- `const S & primary_set () const`
Return the primary set.

10.292.1 Detailed Description

`template<typename S, typename F> class mln::p_transformed< S, F >`

[Site](#) set transformed through a function. Parameter S is a site set type; parameter F is a function from site to site.

Definition at line 82 of file p_transformed.hh.

10.292.2 Member Typedef Documentation

10.292.2.1 `template<typename S, typename F> typedef p_transformed_piter<typename S ::bkd_piter, S, F> mln::p_transformed< S, F >::bkd_piter`

Backward [Site_Iterator](#) associated type.

Definition at line 101 of file p_transformed.hh.

10.292.2.2 `template<typename S, typename F> typedef S ::element mln::p_transformed< S, F >::element`

Element associated type.

Definition at line 91 of file p_transformed.hh.

10.292.2.3 `template<typename S, typename F> typedef p_transformed_piter<typename S ::fwd_piter, S, F> mln::p_transformed< S, F >::fwd_piter`

Forward [Site_Iterator](#) associated type.

Definition at line 98 of file p_transformed.hh.

10.292.2.4 template<typename S, typename F> typedef fwd_piter mln::p_transformed< S, F >::piter

[Site_Iterator](#) associated type.

Definition at line 104 of file p_transformed.hh.

10.292.2.5 template<typename S, typename F> typedef S ::psite mln::p_transformed< S, F >::psite

Psite associated type.

Definition at line 95 of file p_transformed.hh.

10.292.3 Constructor & Destructor Documentation

10.292.3.1 template<typename S , typename F > mln::p_transformed< S, F >::p_transformed (const S & s, const F & f) [inline]

Constructor with a site set *s* and a predicate *f*.

Definition at line 163 of file p_transformed.hh.

10.292.3.2 template<typename S , typename F > mln::p_transformed< S, F >::p_transformed () [inline]

Constructor without argument.

Definition at line 157 of file p_transformed.hh.

10.292.4 Member Function Documentation

10.292.4.1 template<typename S , typename F > const F & mln::p_transformed< S, F >::function () const [inline]

Return the transformation function.

Definition at line 206 of file p_transformed.hh.

10.292.4.2 template<typename S , typename F > bool mln::p_transformed< S, F >::has (const psite & p) const [inline]

Test if *p* belongs to the subset.

Definition at line 172 of file p_transformed.hh.

10.292.4.3 template<typename S , typename F > bool mln::p_transformed< S, F >::is_valid () const [inline]

Test if this site set is valid.

Definition at line 182 of file p_transformed.hh.

10.292.4.4 template<typename S , typename F > std::size_t mln::p_transformed< S, F >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 190 of file p_transformed.hh.

10.292.4.5 template<typename S , typename F > const S & mln::p_transformed< S, F >::primary_set () const [inline]

Return the primary set.

Definition at line 198 of file p_transformed.hh.

Referenced by mln::p_transformed_piter< Pi, S, F >::change_target().

10.293 mln::p_transformed_piter< Pi, S, F > Struct Template Reference

[Iterator](#) on p_transformed<S,F>.

```
#include <p_transformed_piter.hh>
```

Inherits mln::internal::site_set_iterator_base< p_transformed< S, F >,p_transformed_piter< Pi, S, F > >.

Public Member Functions

- void [change_target](#) (const [p_transformed](#)< S, F > &s)
Change the set site targeted by this iterator.
- void [next](#) ()
Go to the next element.
- [p_transformed_piter](#) (const [p_transformed](#)< S, F > &s)
Constructor from a site set.
- [p_transformed_piter](#) ()
Constructor without argument.

10.293.1 Detailed Description

template<typename Pi, typename S, typename F> struct mln::p_transformed_piter< Pi, S, F >

[Iterator](#) on p_transformed<S,F>. Parameter S is a site set type; parameter F is a function from point to Boolean.

See also

[mln::p_transformed](#)

Definition at line 50 of file p_transformed_piter.hh.

10.293.2 Constructor & Destructor Documentation

10.293.2.1 template<typename Pi , typename S , typename F > mln::p_transformed_piter< Pi, S, F >::p_transformed_piter () [inline]

Constructor without argument.

Definition at line 93 of file p_transformed_piter.hh.

10.293.2.2 template<typename Pi , typename S , typename F > mln::p_transformed_piter< Pi, S, F >::p_transformed_piter (const p_transformed< S, F > & s) [inline]

Constructor from a site set.

Definition at line 99 of file p_transformed_piter.hh.

References mln::p_transformed_piter< Pi, S, F >::change_target().

10.293.3 Member Function Documentation

10.293.3.1 template<typename Pi , typename S , typename F > void mln::p_transformed_piter< Pi, S, F >::change_target (const p_transformed< S, F > & s) [inline]

Change the set site targeted by this iterator.

Definition at line 143 of file p_transformed_piter.hh.

References mln::p_transformed< S, F >::primary_set().

Referenced by mln::p_transformed_piter< Pi, S, F >::p_transformed_piter().

10.293.3.2 template<typename E > void mln::Site_Iterator< E >::next () [inline, inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

Definition at line 92 of file site_iterator.hh.

10.294 mln::p_vaccess< V, S > Class Template Reference

[Site](#) set in which sites are grouped by their associated value.

```
#include <p_vaccess.hh>
```

Inherits site_set_base_< S::site, p_vaccess< V, S > >, and site_set_impl< S >.

Public Types

- **typedef p_double_piter< self_>**, typename vset::bkd_viter, typename S::bkd_piter > **bkd_piter**
Backward Site Iterator associated type.
- **typedef S::element element**
Element associated type.
- **typedef p_double_piter< self_>**, typename vset::fwd_viter, typename S::fwd_piter > **fwd_piter**
Forward Site Iterator associated type.
- **typedef std::pair< V, element > i_element**
Insertion element associated type.
- **typedef fwd_piter piter**
Site Iterator associated type.
- **typedef S pset**
Inner site set associated type.
- **typedef p_double_psite< self_>, S > psite**
Psite associated type.
- **typedef V value**
Value associated type.
- **typedef mln::value::set< V > vset**
Value_Set associated type.

Public Member Functions

- **bool has (const psite &p) const**
Test if p belongs to this site set.
- **bool has (const V &v, const typename S::psite &p) const**
Test if the couple (value v, psite p) belongs to this site set.
- **void insert (const i_element &v_e)**
Insert a pair v_e (value v, element e).
- **void insert (const V &v, const element &e)**
Insert e at value v.
- **bool is_valid () const**
Test if this site set is valid.
- **std::size_t memory_size () const**
Return the size of this site set in memory.

- const S & [operator\(\)](#) (const V &v) const
Return the site set at value v.
- [p_vaccess \(\)](#)
Constructor.
- const [mln::value::set< V >](#) & [values \(\) const](#)
Give the set of values.

10.294.1 Detailed Description

template<typename V, typename S> class mln::p_vaccess< V, S >

[Site](#) set in which sites are grouped by their associated value.

Definition at line 70 of file p_vaccess.hh.

10.294.2 Member Typedef Documentation

10.294.2.1 template<typename V , typename S > typedef p_double_piter<self_, typename vset ::bkd_viter, typename S ::bkd_piter> mln::p_vaccess< V, S >::bkd_piter

Backward [Site_Iterator](#) associated type.

Definition at line 94 of file p_vaccess.hh.

10.294.2.2 template<typename V , typename S > typedef S ::element mln::p_vaccess< V, S >::element

Element associated type.

Definition at line 117 of file p_vaccess.hh.

10.294.2.3 template<typename V , typename S > typedef p_double_piter<self_, typename vset ::fwd_viter, typename S ::fwd_piter> mln::p_vaccess< V, S >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 91 of file p_vaccess.hh.

10.294.2.4 template<typename V , typename S > typedef std::pair<V, element> mln::p_vaccess< V, S >::i_element

Insertion element associated type.

Definition at line 120 of file p_vaccess.hh.

10.294.2.5 template<typename V , typename S > typedef fwd_piter mln::p_vaccess< V, S >::piter

[Site_Iterator](#) associated type.

Definition at line 97 of file p_vaccess.hh.

10.294.2.6 template<typename V , typename S > **typedef S mln::p_vaccess< V, S >::pset**

Inner site set associated type.

Definition at line 85 of file p_vaccess.hh.

10.294.2.7 template<typename V , typename S > **typedef p_double_psite<self_ , S> mln::p_vaccess< V, S >::psite**

Psite associated type.

Definition at line 88 of file p_vaccess.hh.

10.294.2.8 template<typename V , typename S > **typedef V mln::p_vaccess< V, S >::value**

[Value](#) associated type.

Definition at line 78 of file p_vaccess.hh.

10.294.2.9 template<typename V , typename S > **typedef mln::value::set<V> mln::p_vaccess< V, S >::vset**

[Value_Set](#) associated type.

Definition at line 81 of file p_vaccess.hh.

10.294.3 Constructor & Destructor Documentation

10.294.3.1 template<typename V , typename S > **mln::p_vaccess< V, S >::p_vaccess () [inline]**

Constructor.

Definition at line 163 of file p_vaccess.hh.

10.294.4 Member Function Documentation

10.294.4.1 template<typename V , typename S > **bool mln::p_vaccess< V, S >::has (const V & v, const typename S::psite & p) const [inline]**

Test if the couple (value v, psite p) belongs to this site set.

Definition at line 189 of file p_vaccess.hh.

10.294.4.2 template<typename V , typename S > **bool mln::p_vaccess< V, S >::has (const psite & p) const [inline]**

Test if p belongs to this site set.

Definition at line 180 of file p_vaccess.hh.

10.294.4.3 template<typename V , typename S > void mln::p_vaccess< V, S >::insert (const i_element & v_e) [inline]

Insert a pair v_e (value v, element e).

Definition at line 216 of file p_vaccess.hh.

10.294.4.4 template<typename V , typename S > void mln::p_vaccess< V, S >::insert (const V & v, const element & e) [inline]

Insert e at value v.

Definition at line 206 of file p_vaccess.hh.

10.294.4.5 template<typename V , typename S > bool mln::p_vaccess< V, S >::is_valid () const [inline]

Test if this site set is valid.

Definition at line 197 of file p_vaccess.hh.

10.294.4.6 template<typename V , typename S > std::size_t mln::p_vaccess< V, S >::memory_size () const [inline]

Return the size of this site set in memory.

Definition at line 242 of file p_vaccess.hh.

10.294.4.7 template<typename V , typename S > const S & mln::p_vaccess< V, S >::operator() (const V & v) const [inline]

Return the site set at value v.

Definition at line 234 of file p_vaccess.hh.

10.294.4.8 template<typename V , typename S > const mln::value::set< V > & mln::p_vaccess< V, S >::values () const [inline]

Give the set of values.

Definition at line 254 of file p_vaccess.hh.

10.295 mln::p_vertices< G, F > Class Template Reference

[Site](#) set based mapping graph vertices to sites.

```
#include <p_vertices.hh>
```

Inherits site_set_base_< F::result, p_vertices< G, F > >.

Public Types

- **typedef F fun_t**
Function associated type.
- **typedef util::vertex< G > graph_element**
Type of graph element this site set focuses on.
- **typedef G graph_t**
Graph associated type.
- **typedef util::vertex< G > vertex**
Type of graph vertex.

- **typedef super_::site element**
Associated types.
- **typedef p_vertices_psite< G, F > psite**
Point_Site associated type.
- **typedef p_graph_piter< self_, mln_vertex_fwd_iter(G) > fwd_piter**
Forward Site_Iterator associated type.
- **typedef p_graph_piter< self_, mln_vertex_bkd_iter(G) > bkd_piter**
Backward Site_Iterator associated type.
- **typedef fwd_piter piter**
Site_Iterator associated type.

Public Member Functions

- **bool has (const psite &p) const**
Does this site set has p?
- **template<typename G2 >**
bool has (const util::vertex< G2 > &v) const
Does this site set has v?
- **void invalidate ()**
Invalidate this site set.
- **bool is_valid () const**
Test this site set validity.
- **std::size_t memory_size () const**
*Does this site set has vertex_id? FIXME: causes ambiguities while calling has(mln::neighb_fwd_niter<>);
 bool has(unsigned vertex_id) const;.*
- **unsigned nsites () const**

Return The number of points (sites) of the set, i.e., the number of vertices.

- `unsigned nvertices () const`

Return The number of vertices in the graph.

- `p_vertices (const Graph< G > &gr)`

Construct a graph psite set from a graph of points.

- `p_vertices (const Graph< G > &gr, const Function< F > &f)`

Construct a graph psite set from a graph of points.

- `template<typename F2 >`

- `p_vertices (const p_vertices< G, F2 > &other)`

Copy constructor.

- `p_vertices ()`

Constructor without argument.

- `template<typename F2 >`

- `p_vertices (const Graph< G > &gr, const Function< F2 > &f)`

Construct a graph psite set from a graph of points.

- `F::result operator() (const psite &p) const`

Return the value associated to an element of this site set.

- `const G & graph () const`

Accessors.

- `const F & function () const`

Return the association function.

10.295.1 Detailed Description

```
template<typename G, typename F = util::internal::id2element<G,util::vertex<G> >> class
mln::p_vertices< G, F >
```

[Site](#) set based mapping graph vertices to sites.

Definition at line 71 of file p_vertices.hh.

10.295.2 Member Typedef Documentation

```
10.295.2.1 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>
>> typedef p_graph_piter< self_, mln_vertex_bkd_iter(G) > mln::p_vertices< G, F
>::bkd_piter
```

Backward [Site_Iterator](#) associated type.

Definition at line 132 of file p_vertices.hh.

10.295.2.2 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef super_ ::site mln::p_vertices< G, F >::element

Associated types.

Element associated type.

Definition at line 123 of file p_vertices.hh.

10.295.2.3 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef F mln::p_vertices< G, F >::fun_t

Function associated type.

Definition at line 84 of file p_vertices.hh.

10.295.2.4 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef p_graph_piter< self_, mln_vertex_fwd_iter(G) > mln::p_vertices< G, F >::fwd_piter

Forward [Site_Iterator](#) associated type.

Definition at line 129 of file p_vertices.hh.

10.295.2.5 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef util::vertex<G> mln::p_vertices< G, F >::graph_element

Type of graph element this site set focuses on.

Definition at line 91 of file p_vertices.hh.

10.295.2.6 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef G mln::p_vertices< G, F >::graph_t

[Graph](#) associated type.

Definition at line 81 of file p_vertices.hh.

10.295.2.7 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef fwd_piter mln::p_vertices< G, F >::piter

[Site_Iterator](#) associated type.

Definition at line 135 of file p_vertices.hh.

10.295.2.8 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef p_vertices_psite<G,F> mln::p_vertices< G, F >::psite

[Point_Site](#) associated type.

Definition at line 126 of file p_vertices.hh.

10.295.2.9 template<typename G, typename F = util::internal::id2element<G,util::vertex<G>>> typedef util::vertex<G> mln::p_vertices< G, F >::vertex

Type of graph vertex.

Definition at line 87 of file p_vertices.hh.

10.295.3 Constructor & Destructor Documentation

10.295.3.1 template<typename G , typename F > mln::p_vertices< G, F >::p_vertices () [inline]

Constructor without argument.

Definition at line 220 of file p_vertices.hh.

10.295.3.2 template<typename G , typename F > mln::p_vertices< G, F >::p_vertices (const Graph< G > & gr) [inline]

Construct a graph psite set from a graph of points.

Parameters

gr The graph upon which the graph psite set is built. The identity function is used.

Definition at line 226 of file p_vertices.hh.

References mln::p_vertices< G, F >::is_valid().

10.295.3.3 template<typename G , typename F > mln::p_vertices< G, F >::p_vertices (const Graph< G > & gr, const Function< F > & f) [inline]

Construct a graph psite set from a graph of points.

Parameters

gr The graph upon which the graph psite set is built.

f the function which maps a vertex to a site.

Definition at line 238 of file p_vertices.hh.

References mln::p_vertices< G, F >::is_valid().

10.295.3.4 template<typename G , typename F > template<typename F2 > mln::p_vertices< G, F >::p_vertices (const Graph< G > & gr, const Function< F2 > & f) [inline]

Construct a graph psite set from a graph of points.

Parameters

gr The graph upon which the graph psite set is built.

f the function which maps a vertex to a site. It must be convertible to the function type *F*.

Definition at line 248 of file p_vertices.hh.

References mln::p_vertices< G, F >::is_valid().

10.295.3.5 template<typename G , typename F > template<typename F2 > mln::p_vertices< G, F >::p_vertices (const p_vertices< G, F2 > & other) [inline]

Copy constructor.

Definition at line 260 of file p_vertices.hh.

References mln::p_vertices< G, F >::function(), mln::p_vertices< G, F >::graph(), and mln::p_vertices< G, F >::is_valid().

10.295.4 Member Function Documentation

10.295.4.1 template<typename G , typename F > const F & mln::p_vertices< G, F >::function () const [inline]

Return the association function.

Definition at line 385 of file p_vertices.hh.

Referenced by mln::p_vertices< G, F >::p_vertices().

10.295.4.2 template<typename G , typename F > const G & mln::p_vertices< G, F >::graph () const [inline]

Accessors.

Return the graph associated to this site set (const version)

Definition at line 376 of file p_vertices.hh.

References mln::p_vertices< G, F >::is_valid().

Referenced by mln::debug::draw_graph(), mln::operator==(), and mln::p_vertices< G, F >::p_vertices().

10.295.4.3 template<typename G , typename F > bool mln::p_vertices< G, F >::has (const psite & p) const [inline]

Does this site set has *p*?

Definition at line 304 of file p_vertices.hh.

References mln::p_vertices< G, F >::is_valid().

10.295.4.4 template<typename G , typename F > template<typename G2 > bool mln::p_vertices< G, F >::has (const util::vertex< G2 > & v) const [inline]

Does this site set has *v*?

Definition at line 314 of file p_vertices.hh.

References mln::util::vertex< G >::graph(), mln::util::vertex< G >::is_valid(), and mln::p_vertices< G, F >::is_valid().

**10.295.4.5 template<typename G , typename F > void mln::p_vertices< G, F >::invalidate ()
[inline]**

Invalidate this site set.

Definition at line 296 of file p_vertices.hh.

**10.295.4.6 template<typename G , typename F > bool mln::p_vertices< G, F >::is_valid ()
const [inline]**

Test this site set validity.

Definition at line 288 of file p_vertices.hh.

Referenced by mln::p_vertices< G, F >::graph(), mln::p_vertices< G, F >::has(), and mln::p_vertices< G, F >::p_vertices().

**10.295.4.7 template<typename G , typename F > std::size_t mln::p_vertices< G, F
>::memory_size () const [inline]**

Does this site set has *vertex_id*? FIXME: causes ambiguities while calling has(mln::neighb_fwd_niter<>); bool has(unsigned vertex_id) const;

Definition at line 339 of file p_vertices.hh.

**10.295.4.8 template<typename G , typename F > unsigned mln::p_vertices< G, F >::nsites ()
const [inline]**

Return The number of points (sites) of the set, i.e., the number of *vertices*.

Required by the mln::Point_Set concept.

Definition at line 272 of file p_vertices.hh.

References mln::p_vertices< G, F >::nvertices().

10.295.4.9 template<typename G , typename F > unsigned mln::p_vertices< G, F >::nvertices () const [inline]

Return The number of vertices in the graph.

Definition at line 280 of file p_vertices.hh.

Referenced by mln::p_vertices< G, F >::nsites().

**10.295.4.10 template<typename G , typename F > F::result mln::p_vertices< G, F >::operator()
(const psite & p) const [inline]**

Return the value associated to an element of this site set.


Definition at line 349 of file p_vertices.hh.

10.296 `mln::pixel< I >` Struct Template Reference

Generic pixel class.

```
#include <pixel.hh>
```

Inheritance diagram for `mln::pixel< I >`:



Public Member Functions

- void `change_to` (const typename I::psite &p)
Change the pixel to the one at point p.
- bool `is_valid` () const
Test if this pixel is valid.
- `pixel` (I &image)
Constructor.
- `pixel` (I &image, const typename I::psite &p)
Constructor.

10.296.1 Detailed Description

`template<typename I> struct mln::pixel< I >`

Generic pixel class. The parameter is `I` the type of the image it belongs to.

Definition at line 50 of file `core/pixel.hh`.

10.296.2 Constructor & Destructor Documentation

10.296.2.1 template<typename I> mln::pixel< I >::pixel(I & *image*) [inline]

Constructor.

Definition at line 75 of file core/pixel.hh.

10.296.2.2 template<typename I> mln::pixel< I >::pixel(I & *image*, const typename I::psite & *p*) [inline]

Constructor.

Definition at line 82 of file core/pixel.hh.

References mln::pixel< I >::change_to().

10.296.3 Member Function Documentation

10.296.3.1 template<typename I> void mln::pixel< I >::change_to(const typename I::psite & *p*) [inline]

Change the pixel to the one at point p.

Definition at line 92 of file core/pixel.hh.

Referenced by mln::pixel< I >::pixel().

10.296.3.2 template<typename I> bool mln::pixel< I >::is_valid() const [inline]

Test if this pixel is valid.


Definition at line 101 of file core/pixel.hh.

10.297 mln::Pixel_Iterator< E > Struct Template Reference

Base class for the implementation of pixel iterator classes.

```
#include <pixel_iterator.hh>
```

Inheritance diagram for mln::Pixel_Iterator< E >:



Public Member Functions

- void [next \(\)](#)

Go to the next element.

10.297.1 Detailed Description

template<typename E> struct mln::Pixel_Iterator< E >

Base class for the implementation of pixel iterator classes. An iterator on pixels is an iterator that is bound to a particular image and that browses over a set of image pixels.

See also

[mln::doc::Pixel_Iterator](#) for a complete documentation of this class contents.

Definition at line 51 of file `pixel_iterator.hh`.

10.297.2 Member Function Documentation

10.297.2.1 template<typename E > void mln::Iterator< E >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the `next_` method.

Precondition

The iterator is valid.

Definition at line 102 of file `iterator.hh`.

10.298 `mln::plain< I >` Class Template Reference

Prevents an image from sharing its data.

```
#include <plain.hh>
```

Inherits `image_identity< I, I::domain_t, plain< I > >`.

Public Types

- `typedef plain< tag::image_< I > > skeleton`
Skeleton.

Public Member Functions

- `operator I () const`
Conversion into an image with type `I`.
- `plain< I > & operator=(const I &ima)`
Assignment operator from an image `ima`.
- `plain< I > & operator=(const plain< I > &rhs)`
Assignment operator.
- `plain (const plain< I > &rhs)`
Copy constructor.
- `plain ()`
Constructor without argument.
- `plain (const I &ima)`
Copy constructor from an image `ima`.

10.298.1 Detailed Description

`template<typename I> class mln::plain< I >`

Prevents an image from sharing its data. While assigned to another image, its data is duplicated.

Definition at line 82 of file `plain.hh`.

10.298.2 Member Typedef Documentation

10.298.2.1 `template<typename I> typedef plain< tag::image_<I> > mln::plain< I >::skeleton`

`Skeleton.`

Definition at line 93 of file `plain.hh`.

10.298.3 Constructor & Destructor Documentation

10.298.3.1 template<typename I> mln::plain< I >::plain() [inline]

Constructor without argument.

Definition at line 141 of file plain.hh.

10.298.3.2 template<typename I> mln::plain< I >::plain(const plain< I > & rhs) [inline]

Copy constructor.

Definition at line 147 of file plain.hh.

10.298.3.3 template<typename I> mln::plain< I >::plain(const I & ima) [inline]

Copy constructor from an image *ima*.

Definition at line 156 of file plain.hh.

10.298.4 Member Function Documentation

10.298.4.1 template<typename I> mln::plain< I >::operator I() const [inline]

Conversion into an image with type *I*.

Definition at line 197 of file plain.hh.

References mln::duplicate().

10.298.4.2 template<typename I> plain< I > & mln::plain< I >::operator=(const plain< I > & rhs) [inline]

Assignment operator.

Definition at line 174 of file plain.hh.

10.298.4.3 template<typename I> plain< I > & mln::plain< I >::operator=(const I & ima) [inline]

Assignment operator from an image *ima*.


Definition at line 187 of file plain.hh.

10.299 mln::Point< P > Struct Template Reference

Base class for implementation of point classes.

```
#include <point.hh>
```

Inheritance diagram for `mln::Point< P >`:



Public Types

- `typedef P point`
The associated point type is itself.

Public Member Functions

- `const P & to_point() const`
It is a `Point` so it returns itself.

Related Functions

(Note that these are not member functions.)

- `template<typename P, typename D>`
`P & operator+=(Point< P > &p, const Dpoint< D > &dp)`
Shift a point by a delta-point dp.

- template<typename P , typename D >
 $P \& \text{operator-}=(\text{Point}< P > \&p, \text{const Dpoint}< D > \&dp)$
Shift a point by the negate of a delta-point dp.
- template<typename P , typename D >
 $P \& \text{operator}/(\text{Point}< P > \&p, \text{const value::Scalar}< D > \&dp)$
Divide a point by a scalar s.

10.299.1 Detailed Description

template<typename P> struct mln::Point< P >

Base class for implementation of point classes. A point is an element of a space.

For instance, [mln::point2d](#) is the type of elements defined on the discrete square grid of the 2D plane.

Definition at line 62 of file concept/point.hh.

10.299.2 Member Typedef Documentation

10.299.2.1 template<typename P> typedef P mln::Point< P >::point

The associated point type is itself.

Definition at line 66 of file concept/point.hh.

10.299.3 Member Function Documentation

10.299.3.1 template<typename P> const P & mln::Point< P >::to_point() const [inline]

It is a [Point](#) so it returns itself.

Definition at line 130 of file concept/point.hh.

10.299.4 Friends And Related Function Documentation

10.299.4.1 template<typename P , typename D > P & operator+=(Point< P > & p, const Dpoint< D > & dp) [related]

Shift a point by a delta-point dp.

Parameters

[in, out] *p* The targeted point.

[in] *dp* A delta-point.

Returns

A reference to the point p once translated by dp.

Precondition

The type of `dp` has to be compatible with the type of `p`.

Definition at line 137 of file concept/point.hh.

10.299.4.2 template<typename P , typename D > P & operator-= (Point< P > & p, const Dpoint< D > & dp) [related]

Shift a point by the negate of a delta-point `dp`.

Parameters

[in, out] `p` The targeted point.

[in] `dp` A delta-point.

Returns

A reference to the point `p` once translated by `- dp`.

Precondition

The type of `dp` has to be compatible with the type of `p`.

Definition at line 149 of file concept/point.hh.

10.299.4.3 template<typename P , typename D > P & operator/ (Point< P > & p, const value::Scalar< D > & dp) [related]

Divise a point by a scalar `s`.

Parameters

[in, out] `p` The targeted point.

[in] `dp` A scalar.

Returns

A reference to the point `p` once divided by `s`.


Definition at line 163 of file concept/point.hh.

10.300 mln::point< G, C > Struct Template Reference

Generic point class.

```
#include <point.hh>
```

Inheritance diagram for mln::point< G, C >:



Public Types

- enum { `dim` = `G::dim` }
- typedef `C coord`
Coordinate associated type.
- typedef `dpoint< G, C > delta`
Delta associated type.
- typedef `dpoint< G, C > dpsite`
DPSite associated type.
- typedef `G grid`
Grid associated type.
- typedef `mln::algebra::h_vec< G::dim, float > h_vec`

Algebra hexagonal vector (hvec) associated type.

- `typedef mln::algebra::vec< G::dim, float > vec`
Algebra vector (vec) associated type.

Public Member Functions

- `const C & last_coord () const`
Read-only access to the last coordinate.
- `C & last_coord ()`
Read-write access to the last coordinate.
- `point< G, C > & operator+= (const delta &dp)`
Shifting by dp.
- `point< G, C > & operator-= (const delta &dp)`
Shifting by the inverse of dp.
- `C & operator[] (unsigned i)`
*Read-write access to the *i*-th coordinate value.*
- `const C & operator[] (unsigned i) const`
*Read-only access to the *i*-th coordinate value.*
- `template<typename F > point (const Function_v2v< F > &f)`
Constructor; coordinates are set by function f.
- `point ()`
Constructor without argument.
- `template<typename C2 > point (const mln::algebra::vec< dim, C2 > &v)`
Constructor from an algebra vector.
- `void set_all (C c)`
Set all coordinates to the value c.
- `h_vec to_h_vec () const`
Transform to point in homogeneous coordinate system.
- `vec to_vec () const`
Explicit conversion towards mln::algebra::vec.
- `point (C ind)`
- `point (const literal::origin_t &)`
Constructors/assignments with literals.

Static Public Member Functions

- static const `point< G, C > & minus_infty ()`
Point with all coordinates set to the minimum value.
- static const `point< G, C > & plus_infty ()`
Point with all coordinates set to the maximum value.

Static Public Attributes

- static const `point< G, C > origin = all_to(0)`
Origin point (all coordinates are 0).

10.300.1 Detailed Description

`template<typename G, typename C> struct mln::point< G, C >`

Generic point class. Parameters are `n` the dimension of the space and `C` the coordinate type in this space.
Definition at line 108 of file point.hh.

10.300.2 Member Typedef Documentation

10.300.2.1 `template<typename G, typename C> typedef C mln::point< G, C >::coord`

Coordinate associated type.

Definition at line 131 of file point.hh.

10.300.2.2 `template<typename G, typename C> typedef dpoint<G,C> mln::point< G, C >::delta`

Delta associated type.

Definition at line 125 of file point.hh.

10.300.2.3 `template<typename G, typename C> typedef dpoint<G,C> mln::point< G, C >::dpsite`

DPSite associated type.

Definition at line 128 of file point.hh.

10.300.2.4 `template<typename G, typename C> typedef G mln::point< G, C >::grid`

Grid associated type.

Definition at line 122 of file point.hh.

10.300.2.5 template<typename G, typename C> typedef mln::algebra::h_vec<G::dim, float> mln::point< G, C >::h_vec

Algebra hexagonal vector (hvec) associated type.

Definition at line 137 of file point.hh.

10.300.2.6 template<typename G, typename C> typedef mln::algebra::vec<G::dim, float> mln::point< G, C >::vec

Algebra vector (vec) associated type.

Definition at line 134 of file point.hh.

10.300.3 Member Enumeration Documentation

10.300.3.1 template<typename G, typename C> anonymous enum

Enumerator:

dim Dimension of the space.

Invariant

$\text{dim} > 0$

Definition at line 119 of file point.hh.

10.300.4 Constructor & Destructor Documentation

10.300.4.1 template<typename G , typename C > mln::point< G, C >::point() [inline]

Constructor without argument.

Definition at line 420 of file point.hh.

10.300.4.2 template<typename G , typename C > template<typename C2 > mln::point< G, C >::point(const mln::algebra::vec< dim, C2 > & v) [inline]

Constructor from an algebra vector.

Definition at line 427 of file point.hh.

10.300.4.3 template<typename G , typename C> mln::point< G, C >::point(C ind) [inline, explicit]

Constructors with different numbers of arguments (coordinates) w.r.t. the dimension.

Definition at line 443 of file point.hh.

10.300.4.4 template<typename G , typename C> mln::point< G, C >::point(const literal::origin_t &) [inline]

Constructors/assignments with literals.

Definition at line 481 of file point.hh.

10.300.4.5 template<typename G , typename C > template<typename F > mln::point< G, C >::point (const Function_v2v< F > & f) [inline]

Constructor; coordinates are set by function f.

Definition at line 471 of file point.hh.

10.300.5 Member Function Documentation

10.300.5.1 template<typename G , typename C > const C & mln::point< G, C >::last_coord () const [inline]

Read-only access to the last coordinate.

Definition at line 402 of file point.hh.

Referenced by mln::p_run< P >::end(), mln::p_run< P >::operator[](), and mln::debug::put_word().

10.300.5.2 template<typename G , typename C > C & mln::point< G, C >::last_coord () [inline]

Read-write access to the last coordinate.

Definition at line 410 of file point.hh.

10.300.5.3 template<typename G , typename C > const point< G, C > & mln::point< G, C >::minus_infy () [inline, static]

[Point](#) with all coordinates set to the minimum value.

Definition at line 627 of file point.hh.

10.300.5.4 template<typename G , typename C > point< G, C > & mln::point< G, C >::operator+= (const delta & dp) [inline]

Shifting by dp.

Definition at line 544 of file point.hh.

10.300.5.5 template<typename G , typename C > point< G, C > & mln::point< G, C >::operator-= (const delta & dp) [inline]

Shifting by the inverse of dp.

Definition at line 554 of file point.hh.

10.300.5.6 template<typename G , typename C > C & mln::point< G, C >::operator[] (unsigned i) [inline]

Read-write access to the $i - t$ h coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

i < dim

Definition at line 393 of file point.hh.

10.300.5.7 template<typename G , typename C > const C & mln::point< G, C >::operator[] (unsigned *i*) const [inline]

Read-only access to the *i*-th coordinate value.

Parameters

[in] *i* The coordinate index.

Precondition

i < dim

Definition at line 385 of file point.hh.

10.300.5.8 template<typename G , typename C > const point< G, C > & mln::point< G, C >::plus_infty () [inline, static]

[Point](#) with all coordinates set to the maximum value.

Definition at line 618 of file point.hh.

10.300.5.9 template<typename G , typename C> void mln::point< G, C >::set_all (C *c*) [inline]

Set all coordinates to the value *c*.

Definition at line 533 of file point.hh.

10.300.5.10 template<typename G , typename C > point< G, C >::h_vec mln::point< G, C >::to_h_vec () const [inline]

Transform to point in homogene coordinate system.

Definition at line 592 of file point.hh.

10.300.5.11 template<typename G , typename C > point< G, C >::vec mln::point< G, C >::to_vec () const [inline]

Explicit conversion towards mln::algebra::vec.

Definition at line 571 of file point.hh.

10.300.6 Member Data Documentation

10.300.6.1 template<typename G, typename C> const point< G, C > mln::point< G, C >::origin = all_to(0) [static]

Origin point (all coordinates are 0).


Definition at line 192 of file point.hh.

10.301 mln::Point_Site< E > Struct Template Reference

Base class for implementation classes of the notion of "point site".

```
#include <point_site.hh>
```

Inheritance diagram for mln::Point_Site< E >:



Related Functions

(Note that these are not member functions.)

- `template<typename L, typename R > L::dpoint operator- (const Point_Site< L > &lhs, const Point_Site< R > &rhs)`

Difference between a couple of point site lhs and rhs.

- template<typename P >
`std::ostream & operator<< (std::ostream &os, const Point_Site< P > &p)`
Print a point site p into the output stream ostr.
- template<typename L , typename R >
`bool operator== (const Point_Site< L > &lhs, const Point_Site< R > &rhs)`
Equality comparison between a couple of point site lhs and rhs.
- template<typename P , typename D >
`P::point operator+ (const Point_Site< P > &p, const Delta_Point_Site< D > &dp)`
Add a delta-point rhs to a point site lhs.
- template<typename P , typename D >
`P::point operator- (const Point_Site< P > &p, const Delta_Point_Site< D > &dp)`
`}`

10.301.1 Detailed Description

template<typename E> struct mln::Point_Site< E >

Base class for implementation classes of the notion of "point site". A point site ("psite" for short) is an object that allows an efficient access to data associated with a point. A point site is either a point or designates a point.

When a point site is not really a point, it is automatically convertible to the point it designates.

Let us take the example of a 2D image encoded as an array of runs of values. With a point, a pair (row index, column index), retrieving the corresponding pixel value would mean to browse the array of runs to find the value location. That would not be efficient. Conversely, a point site dedicated to this image structure allows for value access in constant time; precisely the proper point site is a pair (index of run, index within the run).

Definition at line 106 of file point_site.hh.

10.301.2 Friends And Related Function Documentation

10.301.2.1 template<typename P , typename D > P::point operator+ (const Point_Site< P > & p, const Delta_Point_Site< D > & dp) [related]

Add a delta-point rhs to a point site lhs.

Parameters

- [in] **p** A point site.
- [in] **dp** A delta-point.

The type of dp has to compatible with the type of p.

Returns

A point (temporary object).

See also

[mln::Delta_Point_Site](#)

Definition at line 282 of file point_site.hh.

10.301.2.2 template<typename P , typename D > P::point operator- (const Point_Site< P > & p, const Delta_Point_Site< D > & dp) [related]

}

Substract a delta-point *dp* to a point site *p*.

Parameters

[in] *p* A point site.

[in] *dp* A delta-point.

The type of *dp* has to compatible with the type of *p*.

Returns

A point (temporary object).

See also

[mln::Dpoint](#)

[mln::Delta_Point_Site](#)

Definition at line 296 of file point_site.hh.

10.301.2.3 template<typename L , typename R > L::dpoint operator- (const Point_Site< L > & lhs, const Point_Site< R > & rhs) [related]

Difference between a couple of point site *lhs* and *rhs*.

Parameters

[in] *lhs* A first point site.

[in] *rhs* A second point site.

Warning

There is no type promotion in Milena so the client has to make sure that both points are defined with the same type of coordinates.

Precondition

Both *lhs* and *rhs* have to be defined on the same topology and with the same type of coordinates; otherwise this test does not compile.

Postcondition

The result, *dp*, is such as *lhs* == *rhs* + *dp*.

Returns

A delta point (temporary object).

See also

`mln::Delta_Point_Site`

Definition at line 267 of file `point_site.hh`.

10.301.2.4 template<typename P> std::ostream & operator<< (std::ostream & ostr, const Point_Site<P> & p) [related]

Print a point site `p` into the output stream `ostr`.

Parameters

[in, out] `ostr` An output stream.

[in] `p` A point site.

Returns

The modified output stream `ostr`.

Definition at line 311 of file `point_site.hh`.

10.301.2.5 template<typename L, typename R> bool operator==(const Point_Site<L> & lhs, const Point_Site<R> & rhs) [related]

Equality comparison between a couple of point site `lhs` and `rhs`.

Parameters

[in] `lhs` A first point site.

[in] `rhs` A second point site.

Precondition

Both `lhs` and `rhs` have to be defined on the same topology; otherwise this test does not compile.

Returns

True if both point sites have the same coordinates, otherwise false.

Definition at line 251 of file `point_site.hh`.

10.302 mln::Point_Site< void > Struct Template Reference

[Point](#) site category flag type.

```
#include <point_site.hh>
```

10.302.1 Detailed Description

template<> struct mln::Point_Site< void >

[Point](#) site category flag type.

Definition at line 80 of file point_site.hh.

10.303 mln::Proxy< E > Struct Template Reference

Base class for implementation classes of the notion of "proxy".

#include <proxy.hh>

Inherits [mln::Object< E >](#).

Inherited by [mln::Accumulator< E >](#), [mln::internal::graph_iter_base< G, Elt, E >](#), [mln::internal::nbh_iterator_base< G, C, Elt, E >](#), and [mln::Site_Proxy< E >](#).

10.303.1 Detailed Description

template<typename E> struct mln::Proxy< E >

Base class for implementation classes of the notion of "proxy".

Definition at line 232 of file core/concept/proxy.hh.

10.304 mln::Proxy< void > Struct Template Reference

[Proxy](#) category flag type.

#include <proxy.hh>

10.304.1 Detailed Description

template<> struct mln::Proxy< void >

[Proxy](#) category flag type.


Definition at line 222 of file core/concept/proxy.hh.

10.305 mln::Pseudo_Site< E > Struct Template Reference

Base class for implementation classes of the notion of "pseudo site".

#include <pseudo_site.hh>

Inheritance diagram for mln::Pseudo_Site< E >:



10.305.1 Detailed Description

`template<typename E> struct mln::Pseudo_Site< E >`

Base class for implementation classes of the notion of "pseudo site". *FIXME: Explain...*

Definition at line 64 of file `pseudo_site.hh`.

10.306 mln::Pseudo_Site< void > Struct Template Reference

[Pseudo_Site](#) category flag type.

`#include <pseudo_site.hh>`

10.306.1 Detailed Description

`template<> struct mln::Pseudo_Site< void >`

[Pseudo_Site](#) category flag type.

Definition at line 52 of file `pseudo_site.hh`.

10.307 mln::pw::image< F, S > Class Template Reference

A generic point-wise image implementation.

`#include <image.hh>`

Inherits `image_base< F, S, image< F, S > >`.

Public Types

- `typedef image< tag::function_< F >, tag::domain_< S > > skeleton`
Skeleton.

Public Member Functions

- [image \(\)](#)
Constructor without argument.
- [image \(const Function_v2v< F > &f, const Site_Set< S > &ps\)](#)
Constructor.

10.307.1 Detailed Description

template<typename F, typename S> class mln::pw::image< F, S >

A generic point-wise image implementation. Parameter F is a function restricting the domain. Parameter S is the domain type.

Definition at line 92 of file pw/image.hh.

10.307.2 Member Typedef Documentation

10.307.2.1 template<typename F, typename S> typedef image< tag::function_<F>, tag::domain_<S> > mln::pw::image< F, S >::skeleton

Skeleton.

Definition at line 99 of file pw/image.hh.

10.307.3 Constructor & Destructor Documentation

10.307.3.1 template<typename F , typename S > mln::pw::image< F, S >::image () [inline]

Constructor without argument.

Definition at line 169 of file pw/image.hh.

10.307.3.2 template<typename F , typename S > mln::pw::image< F, S >::image (const Function_v2v< F > & f, const Site_Set< S > & ps) [inline]

Constructor.

Definition at line 175 of file pw/image.hh.

10.308 mln::registration::closest_point_basic< P > Class Template Reference

Closest point functor based on map distance.

```
#include <icp.hh>
```

10.308.1 Detailed Description

```
template<typename P> class mln::registration::closest_point_basic< P >
```

Closest point functor based on map distance.

Definition at line 240 of file icp.hh.

10.309 mln::registration::closest_point_with_map< P > Class Template Reference

Closest point functor based on map distance.

```
#include <icp.hh>
```

10.309.1 Detailed Description

```
template<typename P> class mln::registration::closest_point_with_map< P >
```

Closest point functor based on map distance.


Definition at line 145 of file icp.hh.

10.310 mln::Regular_Grid< E > Struct Template Reference

Base class for implementation classes of regular grids.

```
#include <regular_grid.hh>
```

Inheritance diagram for mln::Regular_Grid< E >:



10.310.1 Detailed Description

```
template<typename E> struct mln::Regular_Grid< E >
```

Base class for implementation classes of regular grids.

Definition at line 42 of file regular_grid.hh.

10.311 `mln::safe_image< I >` Class Template Reference

Makes an image accessible at undefined location.

```
#include <safe.hh>
```

Inherits `image_identity< I, I::domain_t, safe_image< I > >`.

Public Types

- `typedef safe_image< tag::image_< I > > skeleton`
Skeleton.

Public Member Functions

- `operator safe_image< const I > () const`
Const promotion via conversion.

10.311.1 Detailed Description

`template<typename I> class mln::safe_image< I >`

Makes an image accessible at undefined location.

Definition at line 83 of file `safe.hh`.

10.311.2 Member Typedef Documentation

10.311.2.1 `template<typename I> typedef safe_image< tag::image_<I> > mln::safe_image< I >::skeleton`

Skeleton.

Definition at line 88 of file `safe.hh`.

10.311.3 Member Function Documentation

10.311.3.1 `template<typename I> mln::safe_image< I >::operator safe_image< const I > () const [inline]`

Const promotion via conversion.

Definition at line 195 of file `safe.hh`.

10.312 `mln::select::p_of< P >` Struct Template Reference

Structure `p_of`.

```
#include <pix.hh>
```

10.312.1 Detailed Description

```
template<typename P> struct mln::select::p_of< P >
```

Structure [p_of](#).


Definition at line 52 of file `util/pix.hh`.

10.313 mln::Site< E > Struct Template Reference

Base class for classes that are explicitly sites.

```
#include <site.hh>
```

Inheritance diagram for `mln::Site< E >`:



10.313.1 Detailed Description

```
template<typename E> struct mln::Site< E >
```

Base class for classes that are explicitly sites.

Definition at line 55 of file `site.hh`.

10.314 mln::Site< void > Struct Template Reference

[Site](#) category flag type.

```
#include <site.hh>
```

10.314.1 Detailed Description

```
template<> struct mln::Site< void >
```

[Site](#) category flag type.


Definition at line 46 of file site.hh.

10.315 mln::Site_Iterator< E > Struct Template Reference

Base class for implementation of classes of iterator on points.

```
#include <site_iterator.hh>
```

Inheritance diagram for mln::Site_Iterator< E >:



Public Member Functions

- void [next \(\)](#)
Go to the next element.

10.315.1 Detailed Description

template<typename E> struct mln::Site_Iterator< E >

Base class for implementation of classes of iterator on points. An iterator on points is an iterator that browse over a set of points.

See also

[mln::doc::Site_Iterator](#) for a complete documentation of this class contents.

Definition at line 53 of file site_iterator.hh.

10.315.2 Member Function Documentation

10.315.2.1 template<typename E > void mln::Site_Iterator< E >::next () [inline]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

Definition at line 92 of file site_iterator.hh.

10.316 mln::Site_Proxy< E > Struct Template Reference

Base class for implementation classes of the notion of "site proxy".

#include <site_proxy.hh>

Inherits [mln::Proxy< E >](#).

Inherited by [mln::Pseudo_Site< E >](#), and [mln::Site_Iterator< E >](#).

10.316.1 Detailed Description

template<typename E> struct mln::Site_Proxy< E >

Base class for implementation classes of the notion of "site proxy". **FIXME:** Explain...

Definition at line 61 of file site_proxy.hh.

10.317 mln::Site_Proxy< void > Struct Template Reference

[Site_Proxy](#) category flag type.

```
#include <site_proxy.hh>
```

10.317.1 Detailed Description

```
template<> struct mln::Site_Proxy< void >
```

[Site_Proxy](#) category flag type.


Definition at line 49 of file site_proxy.hh.

10.318 mln::Site_Set< E > Struct Template Reference

Base class for implementation classes of site sets.

```
#include <site_set.hh>
```

Inheritance diagram for mln::Site_Set< E >:



Related Functions

(Note that these are not member functions.)

- template<typename Sl , typename Sr >
`p_set< typename Sl::site > diff (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Set theoretic difference of lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > inter (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Intersection between a couple of point sets.
- template<typename Sl , typename Sr >
`bool operator< (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Strict inclusion test between site sets lhs and rhs.
- template<typename S >
`std::ostream & operator<< (std::ostream &ostr, const Site_Set< S > &set)`
Print a site set set into the output stream ostr.
- template<typename Sl , typename Sr >
`bool operator<= (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Inclusion test between site sets lhs and rhs.
- template<typename Sl , typename Sr >
`bool operator== (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Equality test between site sets lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > sym_diff (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Set theoretic symmetrical difference of lhs and rhs.
- template<typename Sl , typename Sr >
`p_set< typename Sl::site > uni (const Site_Set< Sl > &lhs, const Site_Set< Sr > &rhs)`
Union of a couple of point sets.
- template<typename S >
`p_set< typename S::site > unique (const Site_Set< S > &s)`
Give the unique set of s.

10.318.1 Detailed Description

`template<typename E> struct mln::Site_Set< E >`

Base class for implementation classes of site sets.

See also

[mln::doc::Site_Set](#) for a complete documentation of this class contents.

Definition at line 65 of file mln/core/concept/site_set.hh.

10.318.2 Friends And Related Function Documentation

10.318.2.1 template<typename Sl , typename Sr > p_set< typename Sl::site > diff (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Set theoretic difference of `lhs` and `rhs`.

Definition at line 66 of file set/diff.hh.

10.318.2.2 template<typename Sl , typename Sr > p_set< typename Sl::site > inter (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Intersection between a couple of point sets.

Definition at line 62 of file set/inter.hh.

10.318.2.3 template<typename Sl , typename Sr > bool operator< (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Strict inclusion test between site sets `lhs` and `rhs`.

Parameters

[in] **lhs** A site set (strictly included?).

[in] **rhs** Another site set (includer?).

Definition at line 479 of file operators.hh.

10.318.2.4 template<typename S > std::ostream & operator<< (std::ostream & ostr, const Site_Set< S > & set) [related]

Print a site set `set` into the output stream `ostr`.

Parameters

[in, out] **ostr** An output stream.

[in] **set** A site set.

Returns

The modified output stream `ostr`.

Definition at line 505 of file operators.hh.

10.318.2.5 template<typename Sl , typename Sr > bool operator<= (const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Inclusion test between site sets `lhs` and `rhs`.

Parameters

[in] **lhs** A site set (included?).

[in] **rhs** Another site set (includer?).

Definition at line 491 of file operators.hh.

10.318.2.6 template<typename Sl , typename Sr > bool operator==(const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Equality test between site sets lhs and rhs.

Parameters

[in] **lhs** A site set.

[in] **rhs** Another site set.

Definition at line 467 of file operators.hh.

10.318.2.7 template<typename Sl , typename Sr > p_set< typename Sl::site > sym_diff(const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Set theoretic symmetrical difference of lhs and rhs.

Definition at line 65 of file sym_diff.hh.

10.318.2.8 template<typename Sl , typename Sr > p_set< typename Sl::site > uni(const Site_Set< Sl > & lhs, const Site_Set< Sr > & rhs) [related]

Union of a couple of point sets.

Definition at line 61 of file uni.hh.

10.318.2.9 template<typename S > p_set< typename S::site > unique(const Site_Set< S > & s) [related]

Give the unique set of s.

Definition at line 61 of file unique.hh.

10.319 mln::Site_Set< void > Struct Template Reference

[Site_Set](#) category flag type.

```
#include <site_set.hh>
```

10.319.1 Detailed Description

template<> struct mln::Site_Set< void >

[Site_Set](#) category flag type.

Definition at line 54 of file mln/core/concept/site_set.hh.

10.320 mln::slice_image< I > Struct Template Reference

2D image extracted from a slice of a 3D image.

```
#include <slice_image.hh>
Inherits image_domain_morpher< I, box2d, slice_image< I > >.
```

Public Types

- **typedef slice_image< tag::image_< I > > skeleton**
Skeleton.

Public Member Functions

- **const box2d & domain () const**
Give the definition domain.
- **operator slice_image< const I > () const**
Const promotion via conversion.
- **I::rvalue operator() (const point2d &p) const**
Read-only access to the image value located at point p.
- **internal::morpher_lvalue_< I >::ret operator() (const point2d &p)**
Read-write access to the image value located at point p.
- **def::coord sli () const**
Give the slice number.
- **slice_image ()**
Constructor without argument.
- **slice_image (I &ima, def::coord sli)**
Constructor from an image ima and a predicate f.

10.320.1 Detailed Description

template<typename I> struct mln::slice_image< I >

2D image extracted from a slice of a 3D image.

Definition at line 95 of file slice_image.hh.

10.320.2 Member Typedef Documentation

10.320.2.1 template<typename I> typedef slice_image< tag::image_<I> > mln::slice_image< I >::skeleton

Skeleton.

Definition at line 100 of file slice_image.hh.

10.320.3 Constructor & Destructor Documentation

10.320.3.1 template<typename I> mln::slice_image< I >::slice_image() [inline]

Constructor without argument.

Definition at line 193 of file slice_image.hh.

10.320.3.2 template<typename I> mln::slice_image< I >::slice_image(I & ima, def::coord sli) [inline]

Constructor from an image `ima` and a predicate `f`.

Definition at line 199 of file slice_image.hh.

10.320.4 Member Function Documentation

10.320.4.1 template<typename I> const box2d & mln::slice_image< I >::domain() const [inline]

Give the definition domain.

Definition at line 216 of file slice_image.hh.

10.320.4.2 template<typename I> mln::slice_image< I >::operator slice_image< const I >() const [inline]

Const promotion via conversion.

Definition at line 255 of file slice_image.hh.

10.320.4.3 template<typename I> internal::morpher_lvalue_< I >::ret mln::slice_image< I >::operator()(const point2d & p) [inline]

Read-write access to the image value located at point `p`.

Definition at line 245 of file slice_image.hh.

10.320.4.4 template<typename I> I::rvalue mln::slice_image< I >::operator()(const point2d & p) const [inline]

Read-only access to the image value located at point `p`.

Definition at line 234 of file slice_image.hh.

10.320.4.5 template<typename I> def::coord mln::slice_image< I >::sli() const [inline]

Give the slice number.

Definition at line 225 of file slice_image.hh.

10.321 mln::sub_image< I, S > Class Template Reference

[Image](#) having its domain restricted by a site set.

```
#include <sub_image.hh>
```

Inherits [image_domain_morpher< I, S, sub_image< I, S > >](#).

Public Types

- [typedef sub_image< tag::image_< I >, tag::domain_< S > > skeleton](#)
Skeleton.

Public Member Functions

- [const S & domain \(\) const](#)
Give the definition domain.
- [operator sub_image< const I, S > \(\) const](#)
Const promotion via conversion.
- [sub_image \(\)](#)
Constructor without argument.
- [sub_image \(const I &ima, const S &pset\)](#)
Constructor.

10.321.1 Detailed Description

```
template<typename I, typename S> class mln::sub_image< I, S >
```

[Image](#) having its domain restricted by a site set.

Definition at line 102 of file [sub_image.hh](#).

10.321.2 Member Typedef Documentation

10.321.2.1 template<typename I, typename S> typedef sub_image< tag::image_<I>, tag::domain_<S> > mln::sub_image< I, S >::skeleton

Skeleton.

Definition at line 108 of file [sub_image.hh](#).

10.321.3 Constructor & Destructor Documentation

10.321.3.1 template<typename I , typename S > mln::sub_image< I, S >::sub_image() [inline]

Constructor without argument.

Definition at line 182 of file sub_image.hh.

10.321.3.2 template<typename I , typename S > mln::sub_image< I, S >::sub_image(const I & ima, const S & pset) [inline]

Constructor.

Definition at line 188 of file sub_image.hh.

10.321.4 Member Function Documentation

10.321.4.1 template<typename I , typename S > const S & mln::sub_image< I, S >::domain() const [inline]

Give the definition domain.

Definition at line 205 of file sub_image.hh.

10.321.4.2 template<typename I , typename S > mln::sub_image< I, S >::operator sub_image< const I, S >() const [inline]

Const promotion via conversion.

Definition at line 212 of file sub_image.hh.

10.322 `mln::sub_image_if< I, S >` Struct Template Reference

[Image](#) having its domain restricted by a site set and a function.

```
#include <sub_image_if.hh>
```

Inherits `image_domain_morpher< I, p_if< S, fun::p2b::has< I > >, sub_image_if< I, S > >`.

Public Types

- `typedef sub_image_if< tag::image_< I >, tag::domain_< S > > skeleton`
Skeleton.

Public Member Functions

- `const p_if< S, fun::p2b::has< I > > & domain()` const
Give the definition domain.

- [sub_image_if\(\)](#)
Constructor without argument.
- [sub_image_if\(I &ima, const S &s\)](#)
Constructor.

10.322.1 Detailed Description

`template<typename I, typename S> struct mln::sub_image_if< I, S >`

[Image](#) having its domain restricted by a site set and a function.

Definition at line 101 of file `sub_image_if.hh`.

10.322.2 Member Typedef Documentation

10.322.2.1 `template<typename I, typename S> typedef sub_image_if< tag::image_<I>, tag::domain_<S> > mln::sub_image_if< I, S >::skeleton`

Skeleton.

Definition at line 106 of file `sub_image_if.hh`.

10.322.3 Constructor & Destructor Documentation

10.322.3.1 `template<typename I , typename S > mln::sub_image_if< I, S >::sub_image_if() [inline]`

Constructor without argument.

Definition at line 181 of file `sub_image_if.hh`.

10.322.3.2 `template<typename I , typename S > mln::sub_image_if< I, S >::sub_image_if(I & ima, const S & s) [inline]`

Constructor.

Definition at line 187 of file `sub_image_if.hh`.

10.322.4 Member Function Documentation

10.322.4.1 `template<typename I , typename S > const p_if< S, fun::p2b::has< I > > & mln::sub_image_if< I, S >::domain() const [inline]`

Give the definition domain.

Definition at line 204 of file `sub_image_if.hh`.

10.323 mln::thru_image< I, F > Class Template Reference

Morph image values through a function.

```
#include <thru_image.hh>
```

Public Member Functions

- `operator thru_image< const I, F > () const`
Const promotion via conversion.

10.323.1 Detailed Description

```
template<typename I, typename F> class mln::thru_image< I, F >
```

Morph image values through a function.

Definition at line 156 of file thru_image.hh.

10.323.2 Member Function Documentation

10.323.2.1 template<typename I , typename F > mln::thru_image< I, F >::operator thru_image< const I, F > () const [inline]

Const promotion via conversion.

Definition at line 239 of file thru_image.hh.

10.324 mln::thrubin_image< I1, I2, F > Class Template Reference

Morphes values from two images through a binary function.

```
#include <thrubin_image.hh>
```

Inherits `image_value_morpher< I1, F::result, thrubin_image< I1, I2, F > >`.

Public Types

- `typedef I1::psite psite`
Point_Site associated type.
- `typedef value rvalue`
Return type of read-only access.
- `typedef thrubin_image< tag::image_< I1 >, tag::image_< I2 >, F > skeleton`
Skeleton.
- `typedef F::result value`
Value associated type.

Public Member Functions

- `operator thrubin_image< const I1, const I2, F > () const`

Const promotion via conversion.

10.324.1 Detailed Description

`template<typename I1, typename I2, typename F> class mln::thrubin_image< I1, I2, F >`

Morphes values from two images through a binary function.

Definition at line 82 of file thrubin_image.hh.

10.324.2 Member Typedef Documentation

- 10.324.2.1 `template<typename I1, typename I2, typename F> typedef I1 ::psite
mln::thrubin_image< I1, I2, F >::psite`**

`Point_Site` associated type.

Definition at line 94 of file thrubin_image.hh.

- 10.324.2.2 `template<typename I1, typename I2, typename F> typedef value
mln::thrubin_image< I1, I2, F >::rvalue`**

Return type of read-only access.

Definition at line 100 of file thrubin_image.hh.

- 10.324.2.3 `template<typename I1, typename I2, typename F> typedef thrubin_-
image<tag::image_<I1>, tag::image_<I2>, F> mln::thrubin_image< I1, I2, F
>::skeleton`**

Skeleton.

Definition at line 91 of file thrubin_image.hh.

- 10.324.2.4 `template<typename I1, typename I2, typename F> typedef F ::result
mln::thrubin_image< I1, I2, F >::value`**

`Value` associated type.

Definition at line 97 of file thrubin_image.hh.

10.324.3 Member Function Documentation

- 10.324.3.1 `template<typename I1 , typename I2 , typename F > mln::thrubin_image< I1, I2, F
>::operator thrubin_image< const I1, const I2, F > () const [inline]`**

Const promotion via conversion.

Definition at line 186 of file thrubin_image.hh.

10.325 mln::topo::adj_higher_dim_connected_n_face_bkd_iter< D > Class Template Reference

Backward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>.

```
#include <adj_higher_dim_connected_n_face_iter.hh>
```

Inherits backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_bkd_iter< D > >, and mln::topo::internal::adj_higher_dim_connected_n_face_iterator< D >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_higher_dim_connected_n_face_bkd_iter \(\)](#)

Construction.

10.325.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_higher_dim_connected_n_face_bkd_iter< D >
```

Backward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>.

Template Parameters

- D* The dimension of the complex this iterator belongs to.

Definition at line 104 of file adj_higher_dim_connected_n_face_iter.hh.

10.325.2 Constructor & Destructor Documentation

```
10.325.2.1 template<unsigned D> mln::topo::adj_higher_dim_connected_n_face_bkd_iter< D >::adj_higher_dim_connected_n_face_bkd_iter( ) [inline]
```

Construction.

Definition at line 196 of file adj_higher_dim_connected_n_face_iter.hh.

10.325.3 Member Function Documentation

10.325.3.1 void mln::Iterator< adj_higher_dim_connected_n_face_bkd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.326 mln::topo::adj_higher_dim_connected_n_face_fwd_iter< D > Class Template Reference

Forward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>.

```
#include <adj_higher_dim_connected_n_face_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_dim_connected_n_face_fwd_iter< D > >, and mln::topo::internal::adj_higher_dim_connected_n_face_iterator< D >.

Public Member Functions

- void [next \(\)](#)
Go to the next element.

- [adj_higher_dim_connected_n_face_fwd_iter \(\)](#)
Construction.

10.326.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_higher_dim_connected_n_face_fwd_iter< D >
```

Forward iterator on all the n-faces sharing an adjacent (n+1)-face with a (reference) n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 65 of file adj_higher_dim_connected_n_face_iter.hh.

10.326.2 Constructor & Destructor Documentation

10.326.2.1 template<unsigned D> mln::topo::adj_higher_dim_connected_n_face_fwd_iter< D >::adj_higher_dim_connected_n_face_fwd_iter() [inline]

Construction.

Definition at line 162 of file adj_higher_dim_connected_n_face_iter.hh.

10.326.3 Member Function Documentation

10.326.3.1 void mln::Iterator< adj_higher_dim_connected_n_face_fwd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.327 mln::topo::adj_higher_face_bkd_iter< D > Class Template Reference

Backward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_higher_face_iter.hh>
```

Inherits backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_bkd_iter< D > >.

Public Member Functions

- void [next\(\)](#)

Go to the next element.

- [adj_higher_face_bkd_iter\(\)](#)

Construction.

10.327.1 Detailed Description

template<unsigned D> class mln::topo::adj_higher_face_bkd_iter< D >

Backward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 106 of file adj_higher_face_iter.hh.

10.327.2 Constructor & Destructor Documentation

10.327.2.1 template<unsigned D> mln::topo::adj_higher_face_bkd_iter< D >::adj_higher_face_bkd_iter () [inline]

Construction.

Definition at line 167 of file adj_higher_face_iter.hh.

10.327.3 Member Function Documentation

10.327.3.1 void mln::Iterator< adj_higher_face_bkd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.328 mln::topo::adj_higher_face_fwd_iter< D > Class Template Reference

Forward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_higher_face_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_higher_face_fwd_iter< D > >.

Public Member Functions

- void **next ()**

Go to the next element.

- **adj_higher_face_fwd_iter ()**

Construction.

10.328.1 Detailed Description

template<unsigned D> class mln::topo::adj_higher_face_fwd_iter< D >

Forward iterator on all the adjacent (n+1)-faces of the n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 72 of file adj_higher_face_iter.hh.

10.328.2 Constructor & Destructor Documentation

10.328.2.1 template<unsigned D> mln::topo::adj_higher_face_fwd_iter< D >::adj_higher_face_fwd_iter () [inline]

Construction.

Definition at line 139 of file adj_higher_face_iter.hh.

10.328.3 Member Function Documentation

10.328.3.1 void mln::Iterator< adj_higher_face_fwd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.329 mln::topo::adj_lower_dim_connected_n_face_bkd_iter< D > Class Template Reference

Backward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>.

```
#include <adj_lower_dim_connected_n_face_iter.hh>
```

Inherits backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_bkd_iter< D > >, and mln::topo::internal::adj_lower_dim_connected_n_face_iterator< D >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_lower_dim_connected_n_face_bkd_iter\(\)](#)
Construction.

10.329.1 Detailed Description

`template<unsigned D> class mln::topo::adj_lower_dim_connected_n_face_bkd_iter< D >`

Backward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an `mln::complex<D>`.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 104 of file `adj_lower_dim_connected_n_face_iter.hh`.

10.329.2 Constructor & Destructor Documentation

10.329.2.1 template<unsigned D> mln::topo::adj_lower_dim_connected_n_face_bkd_iter< D >::adj_lower_dim_connected_n_face_bkd_iter() [inline]

Construction.

Definition at line 196 of file `adj_lower_dim_connected_n_face_iter.hh`.

10.329.3 Member Function Documentation

10.329.3.1 void mln::Iterator< adj_lower_dim_connected_n_face_bkd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the `next_` method.

Precondition

The iterator is valid.

10.330 mln::topo::adj_lower_dim_connected_n_face_fwd_iter< D > Class Template Reference

Forward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an `mln::complex<D>`.

```
#include <adj_lower_dim_connected_n_face_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_dim_connected_n_face_fwd_iter< D > >, and mln::topo::internal::adj_lower_dim_connected_n_face_iterator< D >.

Public Member Functions

- void [next \(\)](#)
Go to the next element.
- [adj_lower_dim_connected_n_face_fwd_iter \(\)](#)
Construction.

10.330.1 Detailed Description

template<unsigned D> class mln::topo::adj_lower_dim_connected_n_face_fwd_iter< D >

Forward iterator on all the n-faces sharing an adjacent (n-1)-face with a (reference) n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 65 of file adj_lower_dim_connected_n_face_iter.hh.

10.330.2 Constructor & Destructor Documentation

10.330.2.1 template<unsigned D> mln::topo::adj_lower_dim_connected_n_face_fwd_iter< D >::adj_lower_dim_connected_n_face_fwd_iter() [inline]

Construction.

Definition at line 162 of file adj_lower_dim_connected_n_face_iter.hh.

10.330.3 Member Function Documentation

10.330.3.1 void mln::Iterator< adj_lower_dim_connected_n_face_fwd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.331 mln::topo::adj_lower_face_bkd_iter< D > Class Template Reference

Backward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_lower_face_iter.hh>
```

Inherits backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_bkd_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_lower_face_bkd_iter \(\)](#)

Construction.

10.331.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_lower_face_bkd_iter< D >
```

Backward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

Template Parameters

- D** The dimension of the complex this iterator belongs to.

Definition at line 108 of file adj_lower_face_iter.hh.

10.331.2 Constructor & Destructor Documentation

```
10.331.2.1 template<unsigned D> mln::topo::adj_lower_face_bkd_iter< D >::adj_lower_face_bkd_iter( ) [inline]
```

Construction.

Definition at line 169 of file adj_lower_face_iter.hh.

10.331.3 Member Function Documentation

```
10.331.3.1 void mln::Iterator< adj_lower_face_bkd_iter< D > >::next( ) [inherited]
```

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.332 mln::topo::adj_lower_face_fwd_iter< D > Class Template Reference

Forward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_lower_face_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_lower_face_fwd_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_lower_face_fwd_iter \(\)](#)

Construction.

10.332.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_lower_face_fwd_iter< D >
```

Forward iterator on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 73 of file adj_lower_face_iter.hh.

10.332.2 Constructor & Destructor Documentation

10.332.2.1 template<unsigned D> mln::topo::adj_lower_face_fwd_iter< D >::adj_lower_face_fwd_iter () [inline]

Construction.

Definition at line 141 of file adj_lower_face_iter.hh.

10.332.3 Member Function Documentation

10.332.3.1 void mln::Iterator< adj_lower_face_fwd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.333 mln::topo::adj_lower_higher_face_bkd_iter< D > Class Template Reference

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_lower_higher_face_iter.hh>
```

Inherits complex_relative_iterator_sequence< adj_higher_face_bkd_iter< D >, adj_lower_face_bkd_iter< D >, adj_lower_higher_face_bkd_iter< D >>.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_lower_higher_face_bkd_iter \(\)](#)

Construction.

10.333.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_lower_higher_face_bkd_iter< D >
```

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 102 of file adj_lower_higher_face_iter.hh.

10.333.2 Constructor & Destructor Documentation

10.333.2.1 template<unsigned D> mln::topo::adj_lower_higher_face_bkd_iter< D >::adj_lower_higher_face_bkd_iter() [inline]

Construction.

Definition at line 152 of file adj_lower_higher_face_iter.hh.

10.333.3 Member Function Documentation

10.333.3.1 void mln::Iterator< adj_lower_higher_face_bkd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.334 mln::topo::adj_lower_higher_face_fwd_iter< D > Class Template Reference

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

```
#include <adj_lower_higher_face_iter.hh>
```

Inherits complex_relative_iterator_sequence< adj_lower_face_fwd_iter< D >, adj_higher_face_fwd_iter< D >, adj_lower_higher_face_fwd_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_lower_higher_face_fwd_iter \(\)](#)

Construction.

10.334.1 Detailed Description

```
template<unsigned D> class mln::topo::adj_lower_higher_face_fwd_iter< D >
```

Forward iterator on all the adjacent (n-1)-faces and (n+1)-faces of the n-face of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 71 of file adj_lower_higher_face_iter.hh.

10.334.2 Constructor & Destructor Documentation

10.334.2.1 template<unsigned D> mln::topo::adj_lower_higher_face_fwd_iter< D >::adj_lower_higher_face_fwd_iter () [inline]

Construction.

Definition at line 133 of file adj_lower_higher_face_iter.hh.

10.334.3 Member Function Documentation

10.334.3.1 void mln::Iterator< adj_lower_higher_face_fwd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.335 mln::topo::adj_m_face_bkd_iter< D > Class Template Reference

Backward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

```
#include <adj_m_face_iter.hh>
```

Inherits backward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_bkd_iter< D > >, and mln::topo::internal::adj_m_face_iterator< D >.

Public Member Functions

- void **next ()**

Go to the next element.

- **adj_m_face_bkd_iter ()**

Construction.

- template<typename Fref >
adj_m_face_bkd_iter (const Fref &f_ref, unsigned m)

Constructs an iterator, with f_ref as reference face, and a target dimension equal to m.

10.335.1 Detailed Description

template<unsigned D> class mln::topo::adj_m_face_bkd_iter< D >

Backward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

Template Parameters

D The dimension of the complex this iterator belongs to.

The dimension parameter (*m_*) must be lower or equal to D.

If *m_* is equal to the dimension of the reference face, then the iterated set is empty.

Definition at line 118 of file adj_m_face_iter.hh.

10.335.2 Constructor & Destructor Documentation

10.335.2.1 template<unsigned D> mln::topo::adj_m_face_bkd_iter< D >::adj_m_face_bkd_iter() [inline]

Construction.

Construct an iterator, with an invalid reference face, and a target dimension equal to 0.

Definition at line 223 of file adj_m_face_iter.hh.

10.335.2.2 template<unsigned D> template<typename Fref > mln::topo::adj_m_face_bkd_iter< D >::adj_m_face_bkd_iter(const Fref & f_ref, unsigned m) [inline]

Constructs an iterator, with *f_ref* as reference face, and a target dimension equal to *m*.

Definition at line 230 of file adj_m_face_iter.hh.

10.335.3 Member Function Documentation

10.335.3.1 void mln::Iterator< adj_m_face_bkd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.336 mln::topo::adj_m_face_fwd_iter< D > Class Template Reference

Forward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

```
#include <adj_m_face_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, adj_m_face_fwd_iter< D > >, and mln::topo::internal::adj_m_face_iterator< D >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [adj_m_face_fwd_iter \(\)](#)

Construction.

- template<typename Fref >

[adj_m_face_fwd_iter \(const Fref &f_ref, unsigned m\)](#)

Constructs an iterator, with f_ref as reference face, and a target dimension equal to m.

10.336.1 Detailed Description

template<unsigned D> class mln::topo::adj_m_face_fwd_iter< D >

Forward iterator on all the m-faces transitively adjacent to a (reference) n-face in a complex.

Template Parameters

D The dimension of the complex this iterator belongs to.

The dimension parameter (*m_*) must be lower or equal to D.

If *m_* is equal to the dimension of the reference face, then the iterated set is empty.

Definition at line 70 of file adj_m_face_iter.hh.

10.336.2 Constructor & Destructor Documentation

10.336.2.1 template<unsigned D> mln::topo::adj_m_face_fwd_iter< D >::adj_m_face_fwd_iter () [inline]

Construction.

Construct an iterator, with an invalid reference face, and a target dimension equal to 0.

Definition at line 194 of file adj_m_face_iter.hh.

10.336.2.2 template<unsigned D> template<typename Fref > mln::topo::adj_m_face_fwd_iter< D >::adj_m_face_fwd_iter (const Fref & f_ref, unsigned m) [inline]

Constructs an iterator, with *f_ref* as reference face, and a target dimension equal to *m*.

Definition at line 201 of file adj_m_face_iter.hh.

10.336.3 Member Function Documentation

10.336.3.1 void mln::Iterator< adj_m_face_fwd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition


The iterator is valid.

10.337 mln::topo::algebraic_face< D > Class Template Reference

Algebraic face handle in a complex; the face dimension is dynamic.

```
#include <algebraic_face.hh>
```

Inheritance diagram for mln::topo::algebraic_face< D >:



Public Member Functions

- [algebraic_face\(\)](#)
Build a non-initialized algebraic face handle.
- [algebraic_face\(complex< D > &complex, unsigned n, unsigned face_id, bool sign\)](#)
Build an algebraic face handle from complex and face_id.
- template<unsigned N>
 [algebraic_face\(const algebraic_n_face< N, D > &f\)](#)
Build a face handle from an mln::topo::algebraic_n_face.
- [algebraic_face\(const face< D > &f, bool sign\)](#)
Build an algebraic face handle from an mln::face.

- void **invalidate** ()

Invalidate this handle.
- bool **is_valid** () const

Is this handle valid?
- bool **sign** () const

Accessors.
- void **set_sign** (bool **sign**)

Set the sign of this face.
- **complex< D > cplx** () const

Accessors.
- unsigned **n** () const

Return the dimension of the face.
- unsigned **face_id** () const

Return the id of the face.
- void **set_cplx** (const **complex< D >** &**cplx**)

Set the complex the face belongs to.
- void **set_n** (unsigned **n**)

Set the dimension of the face.
- void **inc_n** ()

Increment the dimension of the face.
- void **dec_n** ()

Decrement the dimension of the face.
- void **set_face_id** (unsigned **face_id**)

Set the id of the face.
- void **inc_face_id** ()

Increment the id of the face.
- void **dec_face_id** ()

Decrement the id of the face.
- template<unsigned N>
 face_data< N, D > & **data** () const

Return the `mln::topo::face_data` pointed by this handle.
- std::vector< **algebraic_face< D >** > > **lower_dim_adj_faces** () const

Return an array of face handles pointing to adjacent (n-1)-faces.
- std::vector< **algebraic_face< D >** > > **higher_dim_adj_faces** () const

Return an array of face handles pointing to adjacent (n+1)-faces.

10.337.1 Detailed Description

template<unsigned D> class mln::topo::algebraic_face< D >

Algebraic face handle in a complex; the face dimension is dynamic. Contrary to an [mln::topo::algebraic_n_face](#), the dimension of an [mln::topo::algebraic_face](#) is not fixed.

Definition at line 60 of file algebraic_face.hh.

10.337.2 Constructor & Destructor Documentation

10.337.2.1 template<unsigned D> mln::topo::algebraic_face< D >::algebraic_face () [inline]

Build a non-initialized algebraic face handle.

Definition at line 157 of file algebraic_face.hh.

10.337.2.2 template<unsigned D> mln::topo::algebraic_face< D >::algebraic_face (complex< D > & complex, unsigned n, unsigned face_id, bool sign) [inline]

Build an algebraic face handle from *complex* and *face_id*.

Definition at line 164 of file algebraic_face.hh.

10.337.2.3 template<unsigned D> mln::topo::algebraic_face< D >::algebraic_face (const face< D > & f, bool sign) [inline]

Build an algebraic face handle from an mln::face.

Definition at line 174 of file algebraic_face.hh.

References mln::topo::face< D >::n().

10.337.2.4 template<unsigned D> template<unsigned N> mln::topo::algebraic_face< D >::algebraic_face (const algebraic_n_face< N, D > & f) [inline]

Build a face handle from an [mln::topo::algebraic_n_face](#).

Definition at line 184 of file algebraic_face.hh.

10.337.3 Member Function Documentation

10.337.3.1 template<unsigned D> complex< D > mln::topo::face< D >::cplx () const [inline, inherited]

Accessors.

Return the complex the face belongs to.

Definition at line 224 of file face.hh.

Referenced by [mln::complex_psite< D, G >::complex_psite\(\)](#), [mln::topo::operator!=\(\)](#), and [mln::topo::operator==\(\)](#).

10.337.3.2 template<unsigned D> template<unsigned N> face_data< N, D > & mln::topo::face< D >::data() const [inline, inherited]

Return the mln::topo::face_data pointed by this handle.

Definition at line 305 of file face.hh.

References mln::topo::face< D >::is_valid().

10.337.3.3 template<unsigned D> void mln::topo::face< D >::dec_face_id() [inline, inherited]

Decrement the id of the face.

Definition at line 296 of file face.hh.

10.337.3.4 template<unsigned D> void mln::topo::face< D >::dec_n() [inline, inherited]

Decrement the dimension of the face.

Definition at line 272 of file face.hh.

10.337.3.5 template<unsigned D> unsigned mln::topo::face< D >::face_id() const [inline, inherited]

Return the id of the face.

Definition at line 240 of file face.hh.

Referenced by mln::geom::complex_geometry< D, P >::operator()(), and mln::topo::operator==().

10.337.3.6 template<unsigned D> std::vector< algebraic_face< D > > mln::topo::face< D >::higher_dim_adj_faces() const [inline, inherited]

Return an array of face handles pointing to adjacent (n+1)-faces.

Definition at line 370 of file face.hh.

10.337.3.7 template<unsigned D> void mln::topo::face< D >::inc_face_id() [inline, inherited]

Increment the id of the face.

Definition at line 288 of file face.hh.

10.337.3.8 template<unsigned D> void mln::topo::face< D >::inc_n() [inline, inherited]

Increment the dimension of the face.

Definition at line 264 of file face.hh.

10.337.3.9 template<unsigned D> void mln::topo::face< D >::invalidate() [inline, inherited]

Invalidate this handle.

Definition at line 215 of file face.hh.

References mln::topo::face< D >::set_face_id(), and mln::topo::face< D >::set_n().

10.337.3.10 template<unsigned D> bool mln::topo::face< D >::is_valid() const [inline, inherited]

Is this handle valid?

Definition at line 207 of file face.hh.

Referenced by mln::topo::face< D >::data().

10.337.3.11 template<unsigned D> std::vector< algebraic_face< D > > mln::topo::face< D >::lower_dim_adj_faces() const [inline, inherited]

Return an array of face handles pointing to adjacent (n-1)-faces.

Definition at line 357 of file face.hh.

10.337.3.12 template<unsigned D> unsigned mln::topo::face< D >::n() const [inline, inherited]

Return the dimension of the face.

Definition at line 232 of file face.hh.

Referenced by mln::topo::algebraic_face< D >::algebraic_face(), mln::geom::complex_geometry< D, P >::operator()(), and mln::topo::operator==().

10.337.3.13 template<unsigned D> void mln::topo::face< D >::set_cplx(const complex< D > & cplx) [inline, inherited]

Set the complex the face belongs to.

Definition at line 248 of file face.hh.

10.337.3.14 template<unsigned D> void mln::topo::face< D >::set_face_id(unsigned face_id) [inline, inherited]

Set the id of the face.

Definition at line 280 of file face.hh.

Referenced by mln::topo::face< D >::invalidate().

10.337.3.15 template<unsigned D> void mln::topo::face< D >::set_n(unsigned n) [inline, inherited]

Set the dimension of the face.

Definition at line 256 of file face.hh.

Referenced by mln::topo::face< D >::invalidate().

10.337.3.16 template<unsigned D> void mln::topo::algebraic_face< D >::set_sign (bool sign) [inline]

Set the sign of this face.

Definition at line 203 of file algebraic_face.hh.

10.337.3.17 template<unsigned D> bool mln::topo::algebraic_face< D >::sign () const [inline]

Accessors.

Return the sign of this face.

Definition at line 195 of file algebraic_face.hh.


Referenced by mln::topo::operator==().

10.338 mln::topo::algebraic_n_face< N, D > Class Template Reference

Algebraic N-face handle in a complex.

```
#include <algebraic_n_face.hh>
```

Inheritance diagram for mln::topo::algebraic_n_face< N, D >:



Public Member Functions

- [algebraic_n_face \(\)](#)
Build a non-initialized algebraic face handle.
- [algebraic_n_face \(complex< D > &complex, unsigned face_id, bool sign\)](#)

Build an algebraic face handle from complex and face_id.

- `algebraic_n_face (const n_face< N, D > &f, bool sign)`

Build an algebraic face handle from an mln::n_face.

- `void invalidate ()`

Invalidate this handle.

- `bool is_valid () const`

Is this handle valid?

- `bool sign () const`

Accessors.

- `void set_sign (bool sign)`

Set the sign of this face.

- `complex< D > cplx () const`

Accessors.

- `unsigned face_id () const`

Return the id of the face.

- `void set_cplx (const complex< D > &cplx)`

Set the complex the face belongs to.

- `unsigned n () const`

Return the dimension of the face.

- `void set_face_id (unsigned face_id)`

Set the id of the face.

- `void inc_face_id ()`

Increment the id of the face.

- `void dec_face_id ()`

Decrement the id of the face.

- `face_data< N, D > & data () const`

Return the mln::topo::face_data pointed by this handle.

- `std::vector< algebraic_n_face< N-1, D > > lower_dim_adj_faces () const`

Return an array of face handles pointing to adjacent (n-1)-faces.

- `std::vector< algebraic_n_face< N+1, D > > higher_dim_adj_faces () const`

Return an array of face handles pointing to adjacent (n+1)-faces.

10.338.1 Detailed Description

template<unsigned N, unsigned D> class mln::topo::algebraic_n_face< N, D >

Algebraic N-face handle in a complex. Contrary to an [mln::topo::algebraic_face](#), the dimension of an [mln::topo::algebraic_n_face](#) is fixed.

Definition at line 50 of file algebraic_n_face.hh.

10.338.2 Constructor & Destructor Documentation

10.338.2.1 template<unsigned N, unsigned D> mln::topo::algebraic_n_face< N, D >::algebraic_n_face() [inline]

Build a non-initialized algebraic face handle.

Definition at line 166 of file algebraic_n_face.hh.

References [mln::topo::n_face< N, D >::is_valid\(\)](#).

10.338.2.2 template<unsigned N, unsigned D> mln::topo::algebraic_n_face< N, D >::algebraic_n_face(complex< D > & complex, unsigned face_id, bool sign) [inline]

Build an algebraic face handle from *complex* and *face_id*.

Definition at line 176 of file algebraic_n_face.hh.

10.338.2.3 template<unsigned N, unsigned D> mln::topo::algebraic_n_face< N, D >::algebraic_n_face(const n_face< N, D > & f, bool sign) [inline]

Build an algebraic face handle from an [mln::n_face](#).

Definition at line 186 of file algebraic_n_face.hh.

10.338.3 Member Function Documentation

10.338.3.1 template<unsigned N, unsigned D> complex< D > mln::topo::n_face< N, D >::cplx() const [inline, inherited]

Accessors.

Return the complex the face belongs to.

Definition at line 195 of file n_face.hh.

Referenced by [mln::topo::n_faces_set< N, D >::add\(\)](#), [mln::topo::operator!=\(\)](#), and [mln::topo::operator==\(\)](#).

10.338.3.2 template<unsigned N, unsigned D> face_data< N, D > & mln::topo::n_face< N, D >::data() const [inline, inherited]

Return the [mln::topo::face_data](#) pointed by this handle.

Definition at line 251 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

**10.338.3.3 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::dec_face_id()
[inline, inherited]**

Decrement the id of the face.

Definition at line 243 of file n_face.hh.

**10.338.3.4 template<unsigned N, unsigned D> unsigned mln::topo::n_face< N, D >::face_id()
const [inline, inherited]**

Return the id of the face.

Definition at line 211 of file n_face.hh.

Referenced by mln::topo::operator==().

**10.338.3.5 template<unsigned N, unsigned D> std::vector< algebraic_n_face< N+1, D >
> mln::topo::n_face< N, D >::higher_dim_adj_faces() const [inline,
inherited]**

Return an array of face handles pointing to adjacent (n+1)-faces.

Definition at line 270 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

Referenced by mln::topo::edge().

**10.338.3.6 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::inc_face_id()
[inline, inherited]**

Increment the id of the face.

Definition at line 235 of file n_face.hh.

**10.338.3.7 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::invalidate()
[inline, inherited]**

Invalidate this handle.

Definition at line 187 of file n_face.hh.

References mln::topo::n_face< N, D >::set_face_id().

**10.338.3.8 template<unsigned N, unsigned D> bool mln::topo::n_face< N, D >::is_valid()
const [inline, inherited]**

Is this handle valid?

Definition at line 179 of file n_face.hh.

Referenced by mln::topo::algebraic_n_face< N, D >::algebraic_n_face(), mln::topo::n_face< N, D >::data(), mln::topo::n_face< N, D >::higher_dim_adj_faces(), mln::topo::n_face< N, D >::lower_dim_adj_faces(), and mln::topo::n_face< N, D >::n_face().

10.338.3.9 template<unsigned N, unsigned D> std::vector< algebraic_n_face< N-1, D > > mln::topo::n_face< N, D >::lower_dim_adj_faces () const [inline, inherited]

Return an array of face handles pointing to adjacent (n-1)-faces.

Definition at line 260 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

10.338.3.10 template<unsigned N, unsigned D> unsigned mln::topo::n_face< N, D >::n () const [inline, inherited]

Return the dimension of the face.

Definition at line 203 of file n_face.hh.

10.338.3.11 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::set_cplx (const complex< D > & cplx) [inline, inherited]

Set the complex the face belongs to.

Definition at line 219 of file n_face.hh.

10.338.3.12 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::set_face_id (unsigned face_id) [inline, inherited]

Set the id of the face.

Definition at line 227 of file n_face.hh.

Referenced by mln::topo::n_face< N, D >::invalidate().

10.338.3.13 template<unsigned N, unsigned D> void mln::topo::algebraic_n_face< N, D >::set_sign (bool sign) [inline]

Set the sign of this face.

Definition at line 205 of file algebraic_n_face.hh.

10.338.3.14 template<unsigned N, unsigned D> bool mln::topo::algebraic_n_face< N, D >::sign () const [inline]

Accessors.

Return the sign of this face.

Definition at line 197 of file algebraic_n_face.hh.

Referenced by mln::topo::operator==().

10.339 mln::topo::center_only_iter< D > Class Template Reference

[Iterator](#) on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

```
#include <center_only_iter.hh>
```

Inherits forward_complex_relative_iterator_base< topo::face< D >, algebraic_face< D >, center_only_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [center_only_iter \(\)](#)

Construction.

10.339.1 Detailed Description

```
template<unsigned D> class mln::topo::center_only_iter< D >
```

[Iterator](#) on all the adjacent (n-1)-faces of the n-face of an mln::complex<D>.

Template Parameters

- D** The dimension of the complex this iterator belongs to.

[mln::topo::center_only_iter](#) inherits from [mln::topo::internal::forward_complex_relative_iterator_base](#), but it could inherit from [mln::topo::internal::backward_complex_relative_iterator_base](#) as well, since it always contains a single element, the center/reference face (and the traversal order is meaningless).

This iterator is essentially used to implement other iterators.

See also

[mln::topo::centered_iter_adapter](#)
[mln::complex_lower_window](#)
[mln::complex_higher_window](#)
[mln::complex_lower_higher_window](#)

Definition at line 73 of file center_only_iter.hh.

10.339.2 Constructor & Destructor Documentation

10.339.2.1 template<unsigned D> mln::topo::center_only_iter< D >::center_only_iter() [inline]

Construction.

Definition at line 107 of file center_only_iter.hh.

10.339.3 Member Function Documentation

10.339.3.1 void mln::Iterator< center_only_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.340 mln::topo::centered_bkd_iter_adapter< D, I > Class Template Reference

Forward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

```
#include <centered_iter_adapter.hh>
```

Inherits complex_relative_iterator_sequence< I, center_only_iter< D >, centered_bkd_iter_adapter< D, I > >.

Public Member Functions

- void [next\(\)](#)

Go to the next element.

- [centered_bkd_iter_adapter\(\)](#)

Construction.

10.340.1 Detailed Description

```
template<unsigned D, typename I> class mln::topo::centered_bkd_iter_adapter< D, I >
```

Forward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

Template Parameters

D The dimension of the complex this iterator belongs to.

I The adapted complex relative iterator.

Definition at line 91 of file `centered_iter_adapter.hh`.

10.340.2 Constructor & Destructor Documentation

10.340.2.1 template<unsigned D, typename I> mln::topo::centered_bkd_iter_adapter< D, I >::centered_bkd_iter_adapter() [inline]

Construction.

Definition at line 141 of file centered_iter_adapter.hh.

10.340.3 Member Function Documentation

10.340.3.1 void mln::Iterator< centered_bkd_iter_adapter< D, I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.341 mln::topo::centered_fwd_iter_adapter< D, I > Class Template Reference

Backward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

```
#include <centered_iter_adapter.hh>
```

Inherits complex_relative_iterator_sequence< center_only_iter< D >, I, centered_fwd_iter_adapter< D, I > >.

Public Member Functions

- void [next\(\)](#)

Go to the next element.

- [centered_fwd_iter_adapter\(\)](#)

Construction.

10.341.1 Detailed Description

```
template<unsigned D, typename I> class mln::topo::centered_fwd_iter_adapter< D, I >
```

Backward complex relative iterator adapters adding the central (reference) point to the set of iterated faces.

Template Parameters

D The dimension of the complex this iterator belongs to.

I The adapted complex relative iterator.

Definition at line 57 of file centered_iter_adapter.hh.

10.341.2 Constructor & Destructor Documentation

10.341.2.1 template<unsigned D, typename I > mln::topo::centered_fwd_iter_adapter< D, I >::centered_fwd_iter_adapter() [inline]

Construction.

Definition at line 122 of file centered_iter_adapter.hh.

10.341.3 Member Function Documentation

10.341.3.1 void mln::Iterator< centered_fwd_iter_adapter< D, I > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.342 mln::topo::complex< D > Class Template Reference

General complex of dimension D.

```
#include <complex.hh>
```

Public Types

- **typedef face_bkd_iter< D > bkd_citer**
Backward mln::Iterator type iterating on all faces.
- **typedef face_fwd_iter< D > fwd_citer**
Forward mln::Iterator type iterating on all faces.

Public Member Functions

- **const void * addr() const**
Get the address of the data of this complex.

- `complex ()`
Complex construction.
- `n_face< 0u, D > add_face ()`
Add a 0-face to the complex.
- template<unsigned N>
`n_face< N+1, D > add_face (const n_faces_set< N, D > &adjacent_faces)`
Add a (N+1)-face to the complex (with N >= 0).

- unsigned `nfakes () const`
Static manipulators.
- template<unsigned N>
 unsigned `nfakes_of_static_dim () const`
Return the number of N-faces.

- unsigned `nfakes_of_dim (unsigned n) const`
Dynamic manipulators.

- void `print (std::ostream &ostr) const`
Pretty-printing.
- template<unsigned N>
 void `print_faces (std::ostream &ostr) const`
Print the faces of dimension N.

10.342.1 Detailed Description

`template<unsigned D> class mln::topo::complex< D >`

General complex of dimension D.

Definition at line 87 of file complex.hh.

10.342.2 Member Typedef Documentation

10.342.2.1 `template<unsigned D> typedef face_bkd_iter<D> mln::topo::complex< D >::bkd_citer`

Backward `mln::Iterator` type iterating on all faces.

Definition at line 93 of file complex.hh.

10.342.2.2 template<unsigned D> typedef face_fwd_iter<D> mln::topo::complex< D >::fwd_citer

Forward [mln::Iterator](#) type iterating on all faces.

Definition at line 91 of file complex.hh.

10.342.3 Constructor & Destructor Documentation

10.342.3.1 template<unsigned D> mln::topo::complex< D >::complex() [inline]

Complex construction.

Create a new D-complex.

Definition at line 471 of file complex.hh.

10.342.4 Member Function Documentation

10.342.4.1 template<unsigned D> n_face< 0u, D > mln::topo::complex< D >::add_face() [inline]

Add a 0-face to the complex.

Definition at line 480 of file complex.hh.

10.342.4.2 template<unsigned D> template<unsigned N> n_face< N+1, D > mln::topo::complex< D >::add_face(const n_faces_set< N, D > & adjacent_faces) [inline]

Add a (N+1)-face to the complex (with N >= 0).

Parameters

adjacent_faces The (N-1)-faces adjacent to the new N-face.

Definition at line 493 of file complex.hh.

References [mln::topo::n_faces_set< N, D >::faces\(\)](#).

10.342.4.3 template<unsigned D> const void * mln::topo::complex< D >::addr() const [inline]

Get the address of the data of this complex.

This address is a concise and useful information to print and track the actual content of this complex.

Definition at line 699 of file complex.hh.

10.342.4.4 template<unsigned D> unsigned mln::topo::complex< D >::nfaces() const [inline]

Static manipulators.

These methods use statically-known input.

Return the total number of faces, whatever their dimension.

Definition at line 579 of file complex.hh.

10.342.4.5 template<unsigned D> unsigned mln::topo::complex< D >::nfaces_of_dim (unsigned n) const [inline]

Dynamic manipulators.

These methods use input known as run time.

Return the number of *n-faces*.

Warning, this function has a complexity linear in term of N, since each `n_faces_set` is checked (the present implementation does not provide a direct access to `n_faces_set` through a dynamic value of the dimension).

Definition at line 601 of file complex.hh.

10.342.4.6 template<unsigned D> template<unsigned N> unsigned mln::topo::complex< D >::nfaces_of_static_dim () const [inline]

Return the number of N-faces.

Definition at line 588 of file complex.hh.

10.342.4.7 template<unsigned D> void mln::topo::complex< D >::print (std::ostream & ostr) const [inline]

Pretty-printing.

Print the complex.

Definition at line 679 of file complex.hh.

Referenced by `mln::topo::operator<<()`.

10.342.4.8 template<unsigned D> template<unsigned N> void mln::topo::complex< D >::print_faces (std::ostream & ostr) const [inline]

Print the faces of dimension N.


Definition at line 688 of file complex.hh.

10.343 mln::topo::face< D > Class Template Reference

Face handle in a complex; the face dimension is dynamic.

```
#include <face.hh>
```

Inheritance diagram for `mln::topo::face< D >`:



Public Member Functions

- `face ()`
Build a non-initialized face handle.
- `face (complex< D > &cplx, unsigned n, unsigned face_id)`
Build a face handle from complex and face_id.
- template<unsigned N>
`face (const n_face< N, D > &f)`
Build a face handle from an `mln::topo::n_face`.
- `void invalidate ()`
Invalidate this handle.
- `bool is_valid () const`
Is this handle valid?
- `complex< D > cplx () const`
Accessors.
- `unsigned n () const`
Return the dimension of the face.
- `unsigned face_id () const`
Return the id of the face.
- `void set_cplx (const complex< D > &cplx)`
Set the complex the face belongs to.
- `void set_n (unsigned n)`
Set the dimension of the face.
- `void inc_n ()`

Increment the dimension of the face.

- void [dec_n\(\)](#)

Decrement the dimension of the face.

- void [set_face_id\(unsigned face_id\)](#)

Set the id of the face.

- void [inc_face_id\(\)](#)

Increment the id of the face.

- void [dec_face_id\(\)](#)

Decrement the id of the face.

- template<unsigned N>

[face_data< N, D > & data\(\)](#) const

Return the mln::topo::face_data pointed by this handle.

- std::vector< [algebraic_face< D >](#) > [lower_dim_adj_faces\(\)](#) const

Return an array of face handles pointing to adjacent (n-1)-faces.

- std::vector< [algebraic_face< D >](#) > [higher_dim_adj_faces\(\)](#) const

Return an array of face handles pointing to adjacent (n+1)-faces.

10.343.1 Detailed Description

template<unsigned D> class mln::topo::face< D >

Face handle in a complex; the face dimension is dynamic. Contrary to an [mln::topo::n_face](#), the dimension of an [mln::topo::face](#) is not fixed.

Definition at line 64 of file face.hh.

10.343.2 Constructor & Destructor Documentation

10.343.2.1 template<unsigned D> mln::topo::face< D >::face() [inline]

Build a non-initialized face handle.

Definition at line 178 of file face.hh.

10.343.2.2 template<unsigned D> mln::topo::face< D >::face(complex< D > & complex, unsigned n, unsigned face_id) [inline]

Build a face handle from *complex* and *face_id*.

Definition at line 187 of file face.hh.

10.343.2.3 template<unsigned D> template<unsigned N> mln::topo::face< D >::face(const n_face< N, D > & f) [inline]

Build a face handle from an [mln::topo::n_face](#).

Definition at line 197 of file face.hh.

10.343.3 Member Function Documentation

10.343.3.1 template<unsigned D> complex< D > mln::topo::face< D >::cplx() const [inline]

Accessors.

Return the complex the face belongs to.

Definition at line 224 of file face.hh.

Referenced by mln::complex_psite< D, G >::complex_psite(), mln::topo::operator!=(), and mln::topo::operator==().

10.343.3.2 template<unsigned D> template<unsigned N> face_data< N, D > & mln::topo::face< D >::data() const [inline]

Return the mln::topo::face_data pointed by this handle.

Definition at line 305 of file face.hh.

References mln::topo::face< D >::is_valid().

10.343.3.3 template<unsigned D> void mln::topo::face< D >::dec_face_id() [inline]

Decrement the id of the face.

Definition at line 296 of file face.hh.

10.343.3.4 template<unsigned D> void mln::topo::face< D >::dec_n() [inline]

Decrement the dimension of the face.

Definition at line 272 of file face.hh.

10.343.3.5 template<unsigned D> unsigned mln::topo::face< D >::face_id() const [inline]

Return the id of the face.

Definition at line 240 of file face.hh.

Referenced by mln::geom::complex_geometry< D, P >::operator()(), and mln::topo::operator==().

10.343.3.6 template<unsigned D> std::vector< algebraic_face< D > > mln::topo::face< D >::higher_dim_adj_faces() const [inline]

Return an array of face handles pointing to adjacent (n+1)-faces.

Definition at line 370 of file face.hh.

10.343.3.7 template<unsigned D> void mln::topo::face< D >::inc_face_id() [inline]

Increment the id of the face.

Definition at line 288 of file face.hh.

10.343.3.8 template<unsigned D> void mln::topo::face< D >::inc_n() [inline]

Increment the dimension of the face.

Definition at line 264 of file face.hh.

10.343.3.9 template<unsigned D> void mln::topo::face< D >::invalidate() [inline]

Invalidate this handle.

Definition at line 215 of file face.hh.

References mln::topo::face< D >::set_face_id(), and mln::topo::face< D >::set_n().

10.343.3.10 template<unsigned D> bool mln::topo::face< D >::is_valid() const [inline]

Is this handle valid?

Definition at line 207 of file face.hh.

Referenced by mln::topo::face< D >::data().

10.343.3.11 template<unsigned D> std::vector< algebraic_face< D > > mln::topo::face< D >::lower_dim_adj_faces() const [inline]

Return an array of face handles pointing to adjacent (n-1)-faces.

Definition at line 357 of file face.hh.

10.343.3.12 template<unsigned D> unsigned mln::topo::face< D >::n() const [inline]

Return the dimension of the face.

Definition at line 232 of file face.hh.

Referenced by mln::topo::algebraic_face< D >::algebraic_face(), mln::geom::complex_geometry< D, P >::operator()(), and mln::topo::operator==().

10.343.3.13 template<unsigned D> void mln::topo::face< D >::set_cplx(const complex< D > & cplx) [inline]

Set the complex the face belongs to.

Definition at line 248 of file face.hh.

10.343.3.14 template<unsigned D> void mln::topo::face< D >::set_face_id (unsigned face_id) [inline]

Set the id of the face.

Definition at line 280 of file face.hh.

Referenced by mln::topo::face< D >::invalidate().

10.343.3.15 template<unsigned D> void mln::topo::face< D >::set_n (unsigned n) [inline]

Set the dimension of the face.

Definition at line 256 of file face.hh.

Referenced by mln::topo::face< D >::invalidate().

10.344 mln::topo::face_bkd_iter< D > Class Template Reference

Backward iterator on all the faces of an mln::complex<D>.

```
#include <face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, face_bkd_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [face_bkd_iter \(\)](#)

Construction and assignment.

- void [start \(\)](#)

Manipulation.

10.344.1 Detailed Description

template<unsigned D> class mln::topo::face_bkd_iter< D >

Backward iterator on all the faces of an mln::complex<D>.

Template Parameters

- D** The dimension of the complex this iterator belongs to.

Definition at line 112 of file face_iter.hh.

10.344.2 Constructor & Destructor Documentation

10.344.2.1 template<unsigned D> mln::topo::face_bkd_iter< D >::face_bkd_iter() [inline]

Construction and assignment.

Definition at line 207 of file face_iter.hh.

10.344.3 Member Function Documentation

10.344.3.1 void mln::Iterator< face_bkd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.344.3.2 template<unsigned D> void mln::topo::face_bkd_iter< D >::start() [inline]

Manipulation.

Start an iteration.

Definition at line 224 of file face_iter.hh.

10.345 mln::topo::face_fwd_iter< D > Class Template Reference

Forward iterator on all the faces of an mln::complex<D>.

```
#include <face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, face_fwd_iter< D > >.

Public Member Functions

- void [next\(\)](#)

Go to the next element.

- [face_fwd_iter\(\)](#)

Construction and assignment.

- void [start\(\)](#)

Manipulation.

10.345.1 Detailed Description

template<unsigned D> class mln::topo::face_fwd_iter< D >

Forward iterator on all the faces of an mln::complex<D>.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 69 of file face_iter.hh.

10.345.2 Constructor & Destructor Documentation

10.345.2.1 template<unsigned D> mln::topo::face_fwd_iter< D >::face_fwd_iter () [inline]

Construction and assignment.

Definition at line 155 of file face_iter.hh.

10.345.3 Member Function Documentation

10.345.3.1 void mln::Iterator< face_fwd_iter< D > >::next () [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.345.3.2 template<unsigned D> void mln::topo::face_fwd_iter< D >::start () [inline]

Manipulation.

Test if the iterator is valid.


Definition at line 172 of file face_iter.hh.

10.346 mln::topo::is_n_face< N > Struct Template Reference

A functor testing whether a [mln::complex_psitem](#) is an *N*-face.

```
#include <is_n_face.hh>
```

Inheritance diagram for mln::topo::is_n_face< N >:



10.346.1 Detailed Description

`template<unsigned N> struct mln::topo::is_n_face< N >`

A functor testing whether a `mln::complex_psite` is an N -face.

Definition at line 48 of file `is_n_face.hh`.

10.347 mln::topo::is_simple_2d_t< N > Struct Template Reference

Test if a point is simple or not.

```
#include <is_simple_2d.hh>
```

10.347.1 Detailed Description

```
template<typename N> struct mln::topo::is_simple_2d_t< N >
```

Test if a point is simple or not. A point of an object is simple if in its c8 neiborhood, there is exactly one connected component of the object, and only one connected component of the background Examples : (| == object, - = background)

- - | | P | Here p is simple in the c4 and c8 case. | | |

- | - | P | Here p is never simple. | | |


Definition at line 66 of file is_simple_2d.hh.

10.348 mln::topo::is_simple_cell< I > Class Template Reference

A predicate for the simplicity of a point based on the collapse property of the attachment.

```
#include <is_simple_cell.hh>
```

Inheritance diagram for mln::topo::is_simple_cell< I >:



Public Types

- **typedef mln::complex_psite< D, G > psite**
Psite type.
- **typedef bool result**
Result type of the functor.

Public Member Functions

- **typedef mln_geom (I) G**
Geometry of the image.

- `bool operator()` (`const mln::complex_psite< I::dim, mln_geom(I)> &p`) const
Based on the algorithm A2 from couprie.08.pami.
- `void set_image` (`const mln::Image< I > &ima`)
Set the underlying image.

Static Public Attributes

- `static const unsigned D = I::dim`
Dimension of the image (and therefore of the complex).

10.348.1 Detailed Description

`template<typename I> class mln::topo::is_simple_cell< I >`

A predicate for the simplicity of a point based on the collapse property of the attachment. The functor does not actually take a cell as input, but a face that is expected to be a D-facet.

Definition at line 57 of file `is_simple_cell.hh`.

10.348.2 Member Typedef Documentation

10.348.2.1 `template<typename I > typedef mln::complex_psite<D, G> mln::topo::is_simple_cell< I >::psite`

Psite type.

Definition at line 65 of file `is_simple_cell.hh`.

10.348.2.2 `template<typename I > typedef bool mln::topo::is_simple_cell< I >::result`

Result type of the functor.

Reimplemented from `mln::Function_v2b< is_simple_cell< I > >`.

Definition at line 68 of file `is_simple_cell.hh`.

10.348.3 Member Function Documentation

10.348.3.1 `template<typename I > typedef mln::topo::is_simple_cell< I >::mln_geom (I)`

Geometry of the image.

10.348.3.2 `template<typename I > bool mln::topo::is_simple_cell< I >::operator() (const mln::complex_psite< I::dim, mln_geom(I)> & p) const [inline]`

Based on the algorithm A2 from `couprie.08.pami`.

Definition at line 115 of file `is_simple_cell.hh`.

References mln::make::attachment().

10.348.3.3 template<typename I> void mln::topo::is_simple_cell< I >::set_image (const mln::Image< I > & ima) [inline]

Set the underlying image.

Definition at line 107 of file is_simple_cell.hh.

10.348.4 Member Data Documentation

10.348.4.1 template<typename I> const unsigned mln::topo::is_simple_cell< I >::D = I::dim [static]

Dimension of the image (and therefore of the complex).


Definition at line 61 of file is_simple_cell.hh.

10.349 mln::topo::n_face< N, D > Class Template Reference

N-face handle in a complex.

```
#include <n_face.hh>
```

Inheritance diagram for mln::topo::n_face< N, D >:



Public Member Functions

- void [invalidate \(\)](#)
Invalidate this handle.
- bool [is_valid \(\) const](#)
Is this handle valid?
- [n_face \(\)](#)
Build a non-initialized face handle.

- **n_face** (`complex< D > &complex`, `unsigned face_id`)

Build a face handle from complex and face_id.

- **complex< D > cplx () const**
Accessors.
- **unsigned face_id () const**
Return the id of the face.
- **void set_cplx (const complex< D > &cplx)**
Set the complex the face belongs to.
- **unsigned n () const**
Return the dimension of the face.
- **void set_face_id (unsigned face_id)**
Set the id of the face.
- **void inc_face_id ()**
Increment the id of the face.
- **void dec_face_id ()**
Decrement the id of the face.
- **face_data< N, D > & data () const**
Return the mln::topo::face_data pointed by this handle.
- **std::vector< algebraic_n_face< N-1, D > > lower_dim_adj_faces () const**
Return an array of face handles pointing to adjacent (n-1)-faces.
- **std::vector< algebraic_n_face< N+1, D > > higher_dim_adj_faces () const**
Return an array of face handles pointing to adjacent (n+1)-faces.

10.349.1 Detailed Description

`template<unsigned N, unsigned D> class mln::topo::n_face< N, D >`

N-face handle in a complex. Contrary to an `mln::topo::face`, the dimension of an `mln::topo::n_face` is fixed.

Definition at line 61 of file `n_face.hh`.

10.349.2 Constructor & Destructor Documentation

10.349.2.1 `template<unsigned N, unsigned D> mln::topo::n_face< N, D >::n_face () [inline]`

Build a non-initialized face handle.

Definition at line 159 of file `n_face.hh`.

References `mln::topo::n_face< N, D >::is_valid()`.

10.349.2.2 template<unsigned N, unsigned D> mln::topo::n_face< N, D >::n_face (complex< D > & *complex*, unsigned *face_id*) [inline]

Build a face handle from *complex* and *face_id*.

Definition at line 169 of file n_face.hh.

10.349.3 Member Function Documentation

10.349.3.1 template<unsigned N, unsigned D> complex< D > mln::topo::n_face< N, D >::cplx () const [inline]

Accessors.

Return the complex the face belongs to.

Definition at line 195 of file n_face.hh.

Referenced by mln::topo::n_faces_set< N, D >::add(), mln::topo::operator!=(), and mln::topo::operator==().

10.349.3.2 template<unsigned N, unsigned D> face_data< N, D > & mln::topo::n_face< N, D >::data () const [inline]

Return the mln::topo::face_data pointed by this handle.

Definition at line 251 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

10.349.3.3 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::dec_face_id () [inline]

Decrement the id of the face.

Definition at line 243 of file n_face.hh.

10.349.3.4 template<unsigned N, unsigned D> unsigned mln::topo::n_face< N, D >::face_id () const [inline]

Return the id of the face.

Definition at line 211 of file n_face.hh.

Referenced by mln::topo::operator==().

10.349.3.5 template<unsigned N, unsigned D> std::vector< algebraic_n_face< N+1, D > > mln::topo::n_face< N, D >::higher_dim_adj_faces () const [inline]

Return an array of face handles pointing to adjacent (n+1)-faces.

Definition at line 270 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

Referenced by mln::topo::edge().

10.349.3.6 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::inc_face_id () [inline]

Increment the id of the face.

Definition at line 235 of file n_face.hh.

10.349.3.7 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::invalidate () [inline]

Invalidate this handle.

Definition at line 187 of file n_face.hh.

References mln::topo::n_face< N, D >::set_face_id().

10.349.3.8 template<unsigned N, unsigned D> bool mln::topo::n_face< N, D >::is_valid () const [inline]

Is this handle valid?

Definition at line 179 of file n_face.hh.

Referenced by mln::topo::algebraic_n_face< N, D >::algebraic_n_face(), mln::topo::n_face< N, D >::data(), mln::topo::n_face< N, D >::higher_dim_adj_faces(), mln::topo::n_face< N, D >::lower_dim_adj_faces(), and mln::topo::n_face< N, D >::n_face().

10.349.3.9 template<unsigned N, unsigned D> std::vector< algebraic_n_face< N-1, D > > mln::topo::n_face< N, D >::lower_dim_adj_faces () const [inline]

Return an array of face handles pointing to adjacent (n-1)-faces.

Definition at line 260 of file n_face.hh.

References mln::topo::n_face< N, D >::is_valid().

10.349.3.10 template<unsigned N, unsigned D> unsigned mln::topo::n_face< N, D >::n () const [inline]

Return the dimension of the face.

Definition at line 203 of file n_face.hh.

10.349.3.11 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::set_cplx (const complex< D > & cplx) [inline]

Set the complex the face belongs to.

Definition at line 219 of file n_face.hh.

10.349.3.12 template<unsigned N, unsigned D> void mln::topo::n_face< N, D >::set_face_id (unsigned face_id) [inline]

Set the id of the face.

Definition at line 227 of file n_face.hh.

Referenced by mln::topo::n_face< N, D >::invalidate().

10.350 mln::topo::n_face_bkd_iter< D > Class Template Reference

Backward iterator on all the faces of an mln::complex<D>.

```
#include <n_face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, n_face_bkd_iter< D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [n_face_bkd_iter \(\)](#)

Construction and assignment.

- void [start \(\)](#)

Manipulation.

- unsigned [n \(\) const](#)

Accessors.

10.350.1 Detailed Description

template<unsigned D> class mln::topo::n_face_bkd_iter< D >

Backward iterator on all the faces of an mln::complex<D>.

Template Parameters

- D** The dimension of the complex this iterator belongs to.

Definition at line 127 of file n_face_iter.hh.

10.350.2 Constructor & Destructor Documentation

10.350.2.1 template<unsigned D> mln::topo::n_face_bkd_iter< D >::n_face_bkd_iter () [inline]

Construction and assignment.

Definition at line 256 of file n_face_iter.hh.

10.350.3 Member Function Documentation

10.350.3.1 template<unsigned D> unsigned mln::topo::n_face_bkd_iter< D >::n() const [inline]

Accessors.

Shortcuts to face_’s accessors.

Definition at line 308 of file n_face_iter.hh.

Referenced by mln::topo::n_face_bkd_iter< D >::start().

10.350.3.2 void mln::Iterator< n_face_bkd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.350.3.3 template<unsigned D> void mln::topo::n_face_bkd_iter< D >::start() [inline]

Manipulation.

Start an iteration.

Definition at line 275 of file n_face_iter.hh.

References mln::topo::n_face_bkd_iter< D >::n().

10.351 mln::topo::n_face_fwd_iter< D > Class Template Reference

Forward iterator on all the faces of an mln::complex<D>.

```
#include <n_face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, n_face_fwd_iter< D > >.

Public Member Functions

- void [next\(\)](#)

Go to the next element.

- [n_face_fwd_iter\(\)](#)

Construction and assignment.

- void [start \(\)](#)
Manipulation.

- unsigned [n \(\) const](#)
Accessors.

10.351.1 Detailed Description

`template<unsigned D> class mln::topo::n_face_fwd_iter< D >`

Forward iterator on all the faces of an `mln::complex<D>`.

Template Parameters

D The dimension of the complex this iterator belongs to.

Definition at line 72 of file `n_face_iter.hh`.

10.351.2 Constructor & Destructor Documentation

10.351.2.1 template<unsigned D> mln::topo::n_face_fwd_iter< D >::n_face_fwd_iter() [inline]

Construction and assignment.

Definition at line 183 of file `n_face_iter.hh`.

10.351.3 Member Function Documentation

10.351.3.1 template<unsigned D> unsigned mln::topo::n_face_fwd_iter< D >::n() const [inline]

Accessors.

Shortcuts to `face_`'s accessors.

Definition at line 235 of file `n_face_iter.hh`.

10.351.3.2 void mln::Iterator< n_face_fwd_iter< D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the `next_` method.

Precondition

The iterator is valid.

10.351.3.3 template<unsigned D> void mln::topo::n_face_fwd_iter< D >::start() [inline]

Manipulation.

Test if the iterator is valid.

Definition at line 202 of file n_face_iter.hh.

10.352 mln::topo::n_faces_set< N, D > Class Template Reference

Set of face handles of dimension N.

```
#include <n_faces_set.hh>
```

Public Types

- **typedef std::vector< algebraic_n_face< N, D > > faces_type**

The type of the set of face handles.

Public Member Functions

- **void add (const algebraic_n_face< N, D > &f)**

Append an algebraic face f to the set.

- **void reserve (size_t n)**

Reserve n cells in the set.

- **const faces_type & faces () const**

Accessors.

10.352.1 Detailed Description

```
template<unsigned N, unsigned D> class mln::topo::n_faces_set< N, D >
```

Set of face handles of dimension N.

Definition at line 56 of file n_faces_set.hh.

10.352.2 Member Typedef Documentation

10.352.2.1 template<unsigned N, unsigned D> typedef std::vector< algebraic_n_face<N, D> > mln::topo::n_faces_set< N, D >::faces_type

The type of the set of face handles.

Definition at line 70 of file n_faces_set.hh.

10.352.3 Member Function Documentation

10.352.3.1 template<unsigned N, unsigned D> void mln::topo::n_faces_set< N, D >::add (const algebraic_n_face< N, D > & f) [inline]

Append an algebraic face f to the set.

Definition at line 171 of file n_faces_set.hh.

References mln::topo::n_face< N, D >::cplx().

Referenced by mln::topo::operator+(), and mln::topo::operator-().

10.352.3.2 template<unsigned N, unsigned D> const std::vector< algebraic_n_face< N, D > >> & mln::topo::n_faces_set< N, D >::faces () const [inline]

Accessors.

Return the set of handles.

Definition at line 190 of file n_faces_set.hh.

Referenced by mln::topo::complex< D >::add_face().

10.352.3.3 template<unsigned N, unsigned D> void mln::topo::n_faces_set< N, D >::reserve (size_t n) [inline]

Reserve n cells in the set.

This methods does not change the content of $faces_{_}$; it only pre-allocate memory. Method reserve is provided for efficiency purpose, and its use is completely optional.

Definition at line 182 of file n_faces_set.hh.

10.353 mln::topo::skeleton::is_simple_point< N > Struct Template Reference

```
#include <is_simple_point.hh>
```

10.353.1 Detailed Description

template<typename N> struct mln::topo::skeleton::is_simple_point< N >

Tell if a point is simple or not. A point of an object is simple if in its c8 neiborhood, there is exactly one connected component of the object, and only one connected component of the background Examples : (| == object, - = background)

```
- - |
| P | Here p is simple in the c4 and c8 case.
| | |

- | -
| P | Here p is never simple.
| | |
```

Definition at line 68 of file is_simple_point.hh.

10.354 mln::topo::static_n_face_bkd_iter< N, D > Class Template Reference

Backward iterator on all the N-faces of a mln::complex<D>.

```
#include <static_n_face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, static_n_face_bkd_iter< N, D > >.

Public Member Functions

- void [next \(\)](#)

Go to the next element.

- [static_n_face_bkd_iter \(\)](#)

Construction and assignment.

- void [start \(\)](#)

Manipulation.

10.354.1 Detailed Description

```
template<unsigned N, unsigned D> class mln::topo::static_n_face_bkd_iter< N, D >
```

Backward iterator on all the N-faces of a mln::complex<D>.

Template Parameters

N The dimension of the face associated to this iterator.

D The dimension of the complex this iterator belongs to.

Definition at line 101 of file static_n_face_iter.hh.

10.354.2 Constructor & Destructor Documentation

```
10.354.2.1 template<unsigned N, unsigned D> mln::topo::static_n_face_bkd_iter< N, D >::static_n_face_bkd_iter( ) [inline]
```

Construction and assignment.

Definition at line 194 of file static_n_face_iter.hh.

10.354.3 Member Function Documentation

10.354.3.1 void mln::Iterator< static_n_face_bkd_iter< N, D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.354.3.2 template<unsigned N, unsigned D> void mln::topo::static_n_face_bkd_iter< N, D >::start() [inline]

Manipulation.

Start an iteration.

Definition at line 217 of file static_n_face_iter.hh.

10.355 mln::topo::static_n_face_fwd_iter< N, D > Class Template Reference

Forward iterator on all the N-faces of a mln::complex<D>.

```
#include <static_n_face_iter.hh>
```

Inherits complex_set_iterator_base< topo::face< D >, static_n_face_fwd_iter< N, D > >.

Public Member Functions

- void **next**()

Go to the next element.

- **static_n_face_fwd_iter**()

Construction and assignment.

- void **start**()

Manipulation.

10.355.1 Detailed Description

template<unsigned N, unsigned D> class mln::topo::static_n_face_fwd_iter< N, D >

Forward iterator on all the N-faces of a mln::complex<D>.

Template Parameters

N The dimension of the face associated to this iterator.

D The dimension of the complex this iterator belongs to.

Definition at line 55 of file static_n_face_iter.hh.

10.355.2 Constructor & Destructor Documentation

10.355.2.1 template<unsigned N, unsigned D> mln::topo::static_n_face_fwd_iter< N, D >::static_n_face_fwd_iter() [inline]

Construction and assignment.

Definition at line 145 of file static_n_face_iter.hh.

10.355.3 Member Function Documentation

10.355.3.1 void mln::Iterator< static_n_face_fwd_iter< N, D > >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

10.355.3.2 template<unsigned N, unsigned D> void mln::topo::static_n_face_fwd_iter< N, D >::start() [inline]

Manipulation.

Test if the iterator is valid.

Definition at line 168 of file static_n_face_iter.hh.

10.356 mln::tr_image< S, I, T > Struct Template Reference

Transform an image by a given transformation.

```
#include <tr_image.hh>
```

Inherits image_identity< I, S, tr_image< S, I, T > >.

Public Types

- typedef I::value **lvalue**

Return type of read-write access.

- **typedef I::psite psite**
Point_Site associated type.
- **typedef I::value rvalue**
Return type of read-only access.
- **typedef I::site site**
Site associated type.
- **typedef tr_image< S, tag::image_< I >, T > skeleton**
Skeleton.
- **typedef I::value value**
Value associated type.

Public Member Functions

- **const S & domain () const**
Return the domain morpher.
- **bool has (const vec_t &v) const**
Test if a pixel value is accessible at v.
- **bool is_valid () const**
Test if this image has been initialized.
- **I::value operator() (const psite &p) const**
Read-only access of pixel value at point site p.
- **void set_tr (T &tr)**
Set the transformation.
- **const T & tr () const**
Return the underlying transformation.
- **tr_image (const S &s, const I &ima, const T &tr)**
Constructors.

10.356.1 Detailed Description

template<typename S, typename I, typename T> struct mln::tr_image< S, I, T >

Transform an image by a given transformation.

Definition at line 83 of file tr_image.hh.

10.356.2 Member Typedef Documentation

10.356.2.1 template<typename S, typename I, typename T> typedef I ::value mln::tr_image< S, I, T >::lvalue

Return type of read-write access.

Definition at line 101 of file tr_image.hh.

10.356.2.2 template<typename S, typename I, typename T> typedef I ::psite mln::tr_image< S, I, T >::psite

[Point_Site](#) associated type.

Definition at line 92 of file tr_image.hh.

10.356.2.3 template<typename S, typename I, typename T> typedef I ::value mln::tr_image< S, I, T >::rvalue

Return type of read-only access.

Definition at line 104 of file tr_image.hh.

10.356.2.4 template<typename S, typename I, typename T> typedef I ::site mln::tr_image< S, I, T >::site

[Site](#) associated type.

Definition at line 95 of file tr_image.hh.

10.356.2.5 template<typename S, typename I, typename T> typedef tr_image< S, tag::image_<I>, T > mln::tr_image< S, I, T >::skeleton

Skeleton.

Definition at line 107 of file tr_image.hh.

10.356.2.6 template<typename S, typename I, typename T> typedef I ::value mln::tr_image< S, I, T >::value

[Value](#) associated type.

Definition at line 98 of file tr_image.hh.

10.356.3 Constructor & Destructor Documentation

10.356.3.1 template<typename S , typename I , typename T > mln::tr_image< S, I, T >::tr_image (const S & s, const I & ima, const T & tr) [inline]

Constructors.

Definition at line 174 of file tr_image.hh.

10.356.4 Member Function Documentation

10.356.4.1 template<typename S , typename I , typename T > const S & mln::tr_image< S, I, T >::domain() const [inline]

Return the domain morpher.

Definition at line 247 of file tr_image.hh.

10.356.4.2 template<typename S , typename I , typename T > bool mln::tr_image< S, I, T >::has(const vec_t & v) const [inline]

Test if a pixel value is accessible at v.

Definition at line 200 of file tr_image.hh.

10.356.4.3 template<typename S , typename I , typename T > bool mln::tr_image< S, I, T >::is_valid() const [inline]

Test if this image has been initialized.

Definition at line 191 of file tr_image.hh.

10.356.4.4 template<typename S , typename I , typename T > I::value mln::tr_image< S, I, T >::operator()(const psite & p) const [inline]

Read-only access of pixel value at point site p.

Mutable access is only OK for reading (not writing).

Definition at line 213 of file tr_image.hh.

10.356.4.5 template<typename S , typename I , typename T > void mln::tr_image< S, I, T >::set_tr(T & tr) [inline]

Set the transformation.

Definition at line 231 of file tr_image.hh.

10.356.4.6 template<typename S , typename I , typename T > const T & mln::tr_image< S, I, T >::tr() const [inline]

Return the underlying transformation.

Definition at line 239 of file tr_image.hh.

10.357 mln::unproject_image< I, D, F > Struct Template Reference

Un-projects an image.

```
#include <unproject_image.hh>
```

Inherits image_domain_morpher< I, D, unproject_image< I, D, F > >.

Public Member Functions

- const D & [domain\(\)](#) const
Give the definition domain.
- internal::morpher_lvalue_< I >::ret [operator\(\)](#) (const typename D::psite &p)
Read-write access to the image value located at point p.
- I::rvalue [operator\(\)](#) (const typename D::psite &p) const
Read-only access to the image value located at point p.
- [unproject_image\(\)](#)
Constructor without argument.
- [unproject_image\(I &ima, const D &dom, const F &f\)](#)
Constructor from an image ima, a domain dom, and a function f.

10.357.1 Detailed Description

template<typename I, typename D, typename F> struct mln::unproject_image< I, D, F >

Un-projects an image.

Definition at line 96 of file unproject_image.hh.

10.357.2 Constructor & Destructor Documentation

10.357.2.1 template<typename I , typename D , typename F > mln::unproject_image< I, D, F >::unproject_image() [inline]

Constructor without argument.

Definition at line 182 of file unproject_image.hh.

10.357.2.2 template<typename I , typename D , typename F > mln::unproject_image< I, D, F >::unproject_image(I & ima, const D & dom, const F & f) [inline]

Constructor from an image ima, a domain dom, and a function f.

Definition at line 188 of file unproject_image.hh.

10.357.3 Member Function Documentation

10.357.3.1 template<typename I , typename D , typename F > const D & mln::unproject_image< I, D, F >::domain() const [inline]

Give the definition domain.

Definition at line 205 of file unproject_image.hh.

10.357.3.2 template<typename I , typename D , typename F > internal::morpher_lvalue_< I >::ret mln::unproject_image< I, D, F >::operator() (const typename D::psite & p) [inline]

Read-write access to the image value located at point p.

Definition at line 225 of file unproject_image.hh.

10.357.3.3 template<typename I , typename D , typename F > I::rvalue mln::unproject_image< I, D, F >::operator() (const typename D::psite & p) const [inline]

Read-only access to the image value located at point p.

Definition at line 214 of file unproject_image.hh.

10.358 mln::util::adjacency_matrix< V > Class Template Reference

A class of adjacency matrix.

```
#include <adjacency_matrix.hh>
```

Inherits adjacency_matrix_impl_selector< V, mln::metal::equal< mln::trait::value_< V >::quant, trait::value::quant::low >::eval >.

Public Member Functions

- [adjacency_matrix \(\)](#)
Constructors.
- [adjacency_matrix \(const V &nElements\)](#)
Construct an adjacency matrix with nElements elements maximum.

10.358.1 Detailed Description

template<typename V = def::coord> class mln::util::adjacency_matrix< V >

A class of adjacency matrix. Support low and high quantification value types. In case of low quantification value type, it uses an [image2d](#) to store adjacency information. In case of high quantification value type, it uses a [util::set](#) to store the adjacency information.

Definition at line 136 of file adjacency_matrix.hh.

10.358.2 Constructor & Destructor Documentation

10.358.2.1 template<typename V > mln::util::adjacency_matrix< V >::adjacency_matrix ()

Constructors.

```
@{
```

Default

Definition at line 308 of file adjacency_matrix.hh.

10.358.2.2 template<typename V> mln::util::adjacency_matrix<V>::adjacency_matrix (const V & nelements)

Construct an adjacency matrix with `nelements` elements maximum.


Definition at line 315 of file adjacency_matrix.hh.

10.359 mln::util::array< T > Class Template Reference

A dynamic array class.

```
#include <array.hh>
```

Inheritance diagram for mln::util::array< T >:



Public Types

- **typedef T element**
Element associated type.
- **typedef T result**
Returned value types.
- **typedef array_fwd_iter< T > fwd_eiter**
Iterator types
Forward iterator associated type.
- **typedef array_bkd_iter< T > bkd_eiter**
Backward iterator associated type.

- **typedef fwd_eiter eiter**
Iterator associated type.

Public Member Functions

- **array< T > & append (const T &elt)**
Add the element elt at the end of this array.
- **template<typename U >**
array< T > & append (const array< U > &other)
Add the elements of other at the end of this array.
- **void clear ()**
Empty the array.
- **void fill (const T &value)**
Fill the whole array with value value.
- **bool is_empty () const**
Test if the array is empty.
- **ro_result last () const**
Return the last element.
- **mutable_result last ()**
Return the last element.
- **std::size_t memory_size () const**
Return the size of this array in memory.
- **unsigned nelements () const**
Return the number of elements of the array.
- **ro_result operator() (unsigned i) const**
Return the i-th element of the array.
- **mutable_result operator() (unsigned i)**
Return the i-th element of the array.
- **ro_result operator[] (unsigned i) const**
Return the i-th element of the array.
- **mutable_result operator[] (unsigned i)**
Return the i-th element of the array.
- **void reserve (unsigned n)**
Reserve memory for n elements.
- **void resize (unsigned n)**

Resize this array to n elements.

- void `resize` (unsigned n, const T &value)

Resize this array to n elements with value as value.

- unsigned `size` () const

Return the number of elements of the array.

- const std::vector< T > & `std_vector` () const

Return the corresponding std::vector of elements.

- `array` ()

Constructors

Constructor without arguments.

- `array` (unsigned n)

Construct a new array and resize it to elements.

- `array` (unsigned n, const T &value)

Construct a new array, resize it to elements and fill it with default_value.

10.359.1 Detailed Description

`template<typename T> class mln::util::array< T >`

A dynamic array class. Elements are stored by copy. Implementation is lazy.

The parameter T is the element type, which shall not be const-qualified.

Definition at line 99 of file util/array.hh.

10.359.2 Member Typedef Documentation

10.359.2.1 template<typename T> typedef array_bkd_iter<T> mln::util::array< T >::bkd_eiter

Backward iterator associated type.

Definition at line 124 of file util/array.hh.

10.359.2.2 template<typename T> typedef fwd_eiter mln::util::array< T >::eiter

Iterator associated type.

Definition at line 127 of file util/array.hh.

10.359.2.3 `template<typename T> typedef T mln::util::array< T >::element`

Element associated type.

Definition at line 107 of file util/array.hh.

10.359.2.4 `template<typename T> typedef array_fwd_iter<T> mln::util::array< T >::fwd_eiter`

[Iterator](#) types

Forward iterator associated type.

Definition at line 121 of file util/array.hh.

10.359.2.5 `template<typename T> typedef T mln::util::array< T >::result`

Returned value types.

Related to the [Function_v2v](#) concept.

Definition at line 112 of file util/array.hh.

10.359.3 Constructor & Destructor Documentation

10.359.3.1 `template<typename T> mln::util::array< T >::array() [inline]`

Constructors

Constructor without arguments.

Definition at line 427 of file util/array.hh.

10.359.3.2 `template<typename T> mln::util::array< T >::array(unsigned n) [inline]`

Construct a new array and resize it to

elements.

Definition at line 433 of file util/array.hh.

10.359.3.3 `template<typename T> mln::util::array< T >::array(unsigned n, const T & value) [inline]`

Construct a new array, resize it to

elements and fill it with `default_value`.

Definition at line 440 of file util/array.hh.

10.359.4 Member Function Documentation

10.359.4.1 `template<typename T> array< T > & mln::util::array< T >::append(const T & elt) [inline]`

Add the element `elt` at the end of this array.

Definition at line 472 of file util/array.hh.

Referenced by mln::io::dicom::get_header(), and mln::io::plot::load().

10.359.4.2 template<typename T> template<typename U> array< T > & mln::util::array< T >::append(const array< U > & other) [inline]

Add the elements of `other` at the end of this array.

Definition at line 482 of file util/array.hh.

References mln::util::array< T >::is_empty(), and mln::util::array< T >::std_vector().

10.359.4.3 template<typename T> void mln::util::array< T >::clear() [inline]

Empty the array.

All elements contained in the array are destroyed.

Postcondition

`is_empty() == true`

Definition at line 495 of file util/array.hh.

References mln::util::array< T >::is_empty().

Referenced by mln::io::plot::load().

10.359.4.4 template<typename T> void mln::util::array< T >::fill(const T & value) [inline]

Fill the whole array with value `value`.

Definition at line 504 of file util/array.hh.

10.359.4.5 template<typename T> bool mln::util::array< T >::is_empty() const [inline]

Test if the array is empty.

Definition at line 578 of file util/array.hh.

References mln::util::array< T >::nelements().

Referenced by mln::util::array< T >::append(), mln::util::array< T >::clear(), mln::make::image3d(), and mln::io::pnms::load().

10.359.4.6 template<typename T> array< T >::ro_result mln::util::array< T >::last() const [inline]

Return the last element.

Definition at line 562 of file util/array.hh.

References mln::util::array< T >::nelements().

10.359.4.7 template<typename T > array< T >::mutable_result mln::util::array< T >::last () [inline]

Return the last element.

Definition at line 570 of file util/array.hh.

References mln::util::array< T >::nelements().

10.359.4.8 template<typename T > std::size_t mln::util::array< T >::memory_size () const [inline]

Return the size of this array in memory.

Definition at line 602 of file util/array.hh.

References mln::util::array< T >::nelements().

10.359.4.9 template<typename T > unsigned mln::util::array< T >::nelements () const [inline]

Return the number of elements of the array.

Definition at line 520 of file util/array.hh.

Referenced by mln::labeling::fill_holes(), mln::make::image3d(), mln::util::array< T >::is_empty(), mln::util::array< T >::last(), mln::io::pnms::load(), mln::util::array< T >::memory_size(), mln::util::operator<<(), mln::util::array< T >::operator[](), mln::io::plot::save(), and mln::util::array< T >::size().

10.359.4.10 template<typename T > array< T >::ro_result mln::util::array< T >::operator() (unsigned i) const [inline]

Return the i -th element of the array.

Precondition

$i < \text{nelements}()$

Definition at line 528 of file util/array.hh.

10.359.4.11 template<typename T > array< T >::mutable_result mln::util::array< T >::operator() (unsigned i) [inline]

Return the i -th element of the array.

Precondition

$i < \text{nelements}()$

Definition at line 536 of file util/array.hh.

10.359.4.12 template<typename T > array< T >::ro_result mln::util::array< T >::operator[] (unsigned i) const [inline]

Return the i -th element of the array.

Precondition

$i < \text{nelements}()$

Definition at line 544 of file util/array.hh.

References mln::util::array< T >::nelements().

10.359.4.13 template<typename T > array< T >::mutable_result mln::util::array< T >::operator[] (unsigned i) [inline]

Return the i -th element of the array.

Precondition

$i < \text{nelements}()$

Definition at line 553 of file util/array.hh.

References mln::util::array< T >::nelements().

10.359.4.14 template<typename T > void mln::util::array< T >::reserve (unsigned n) [inline]

Reserve memory for n elements.

Definition at line 448 of file util/array.hh.

10.359.4.15 template<typename T > void mln::util::array< T >::resize (unsigned n) [inline]

Resize this array to n elements.

Definition at line 456 of file util/array.hh.

Referenced by mln::labeling::impl::generic::compute(), mln::labeling::impl::compute_fastest(), mln::io::raw::get_header(), and mln::io::dump::get_header().

10.359.4.16 template<typename T> void mln::util::array< T >::resize (unsigned n, const T & value) [inline]

Resize this array to n elements with value as value.

Definition at line 464 of file util/array.hh.

10.359.4.17 template<typename T > unsigned mln::util::array< T >::size () const [inline]

Return the number of elements of the array.

Added for compatibility with fun::i2v::array.

See also[nelements](#)

Definition at line 512 of file util/array.hh.

References mln::util::array< T >::nelements().

Referenced by mln::labeling::impl::generic::compute(), mln::labeling::impl::compute_fastest(), mln::value::lut_vec< S, T >::lut_vec(), and mln::labeled_image_base< I, E >::update_data().

10.359.4.18 template<typename T > const std::vector< T > & mln::util::array< T >::std_vector() const [inline]

Return the corresponding std::vector of elements.

Definition at line 586 of file util/array.hh.

Referenced by mln::util::array< T >::append(), mln::value::lut_vec< S, T >::lut_vec(), and mln::util::operator==().

10.360 mln::util::branch< T > Class Template Reference

Class of generic branch.

```
#include <tree.hh>
```

Public Member Functions

- [tree_node< T > & apex\(\)](#)
The getter of the apex.
- [branch \(tree< T > & tree, tree_node< T > & apex\)](#)
Constructor.
- [tree< T > & util_tree\(\)](#)
The getter of the tree.

10.360.1 Detailed Description

```
template<typename T> class mln::util::branch< T >
```

Class of generic branch.

Definition at line 249 of file tree.hh.

10.360.2 Constructor & Destructor Documentation

10.360.2.1 template<typename T > mln::util::branch< T >::branch (util::tree< T > & tree, util::tree_node< T > & apex) [inline]

Constructor.

Parameters

- [in] **tree** The tree of the branch.
- [in] **apex** The apex of the branch.

Definition at line 537 of file tree.hh.

10.360.3 Member Function Documentation

10.360.3.1 template<typename T> util::tree_node< T > & mln::util::branch< T >::apex() [inline]

The getter of the apex.

Returns

The [tree_node](#) appex of the current branch.

Definition at line 548 of file tree.hh.

10.360.3.2 template<typename T> mln::util::tree< T > & mln::util::branch< T >::util_tree() [inline]

The getter of the tree.

Returns

The tree of the current branch.

Definition at line 556 of file tree.hh.

10.361 mln::util::branch_iter< T > Class Template Reference

Basic 2D image class.

```
#include <branch_iter.hh>
```

Public Member Functions

- `unsigned deepness() const`
Give how deep is the iterator in the branch.
- `void invalidate()`
Invalidate the iterator.
- `bool is_valid() const`
Test the iterator validity.
- `void next()`
Go to the next point.

- `operator util::tree_node< T > & () const`

Conversion to node.

- `void start ()`

Start an iteration.

10.361.1 Detailed Description

`template<typename T> class mln::util::branch_iter< T >`

Basic 2D image class. The parameter `T` is the type of node's data. `branch_iter` is used to pre-order walk a branch.

Definition at line 52 of file `branch_iter.hh`.

10.361.2 Member Function Documentation

10.361.2.1 template<typename T > unsigned mln::util::branch_iter< T >::deepness () const [inline]

Give how deep is the iterator in the branch.

Definition at line 119 of file `branch_iter.hh`.

References `mln::util::branch_iter< T >::is_valid()`, and `mln::util::tree_node< T >::parent()`.

10.361.2.2 template<typename T > void mln::util::branch_iter< T >::invalidate () [inline]

Invalidate the iterator.

Definition at line 143 of file `branch_iter.hh`.

Referenced by `mln::util::branch_iter< T >::next()`.

10.361.2.3 template<typename T > bool mln::util::branch_iter< T >::is_valid () const [inline]

Test the iterator validity.

Definition at line 135 of file `branch_iter.hh`.

Referenced by `mln::util::branch_iter< T >::deepness()`.

10.361.2.4 template<typename T > void mln::util::branch_iter< T >::next() [inline]

Go to the next point.

Definition at line 162 of file `branch_iter.hh`.

References `mln::util::branch_iter< T >::invalidate()`.

10.361.2.5 template<typename T > mln::util::branch_iter< T >::operator util::tree_node< T > & () const [inline]

Conversion to node.

Definition at line 101 of file branch_iter.hh.

10.361.2.6 template<typename T > void mln::util::branch_iter< T >::start() [inline]

Start an iteration.

Definition at line 152 of file branch_iter.hh.

10.362 mln::util::branch_iter_ind< T > Class Template Reference

Basic 2D image class.

```
#include <branch_iter_ind.hh>
```

Public Member Functions

- `unsigned deepness () const`

Give how deep is the iterator in the branch.

- `void invalidate ()`

Invalidate the iterator.

- `bool is_valid () const`

Test the iterator validity.

- `void next ()`

Go to the next point.

- `operator util::tree_node< T > & () const`

Conversion to node.

- `void start ()`

Start an iteration.

10.362.1 Detailed Description

template<typename T> class mln::util::branch_iter_ind< T >

Basic 2D image class. The parameter `T` is the type of node's data. `branch_iter_ind` is used to pre-order walk a branch.

Definition at line 66 of file branch_iter_ind.hh.

10.362.2 Member Function Documentation

10.362.2.1 template<typename T> unsigned mln::util::branch_iter_ind< T >::deepness() const [inline]

Give how deep is the iterator in the branch.

Definition at line 131 of file `branch_iter_ind.hh`.

References `mln::util::branch_iter_ind< T >::is_valid()`, and `mln::util::tree_node< T >::parent()`.

10.362.2.2 template<typename T> void mln::util::branch_iter_ind< T >::invalidate() [inline]

Invalidate the iterator.

Definition at line 155 of file `branch_iter_ind.hh`.

Referenced by `mln::util::branch_iter_ind< T >::next()`.

10.362.2.3 template<typename T> bool mln::util::branch_iter_ind< T >::is_valid() const [inline]

Test the iterator validity.

Definition at line 147 of file `branch_iter_ind.hh`.

Referenced by `mln::util::branch_iter_ind< T >::deepness()`.

10.362.2.4 template<typename T> void mln::util::branch_iter_ind< T >::next() [inline]

Go to the next point.

Definition at line 174 of file `branch_iter_ind.hh`.

References `mln::util::branch_iter_ind< T >::invalidate()`.

10.362.2.5 template<typename T> mln::util::branch_iter_ind< T >::operator util::tree_node< T > &() const [inline]

Conversion to node.

Definition at line 113 of file `branch_iter_ind.hh`.

10.362.2.6 template<typename T> void mln::util::branch_iter_ind< T >::start() [inline]

Start an iteration.


Definition at line 164 of file `branch_iter_ind.hh`.

10.363 `mln::util::couple< T, U >` Class Template Reference

Definition of a couple.

```
#include <couple.hh>
```

Inheritance diagram for mln::util::couple< T, U >:



Public Member Functions

- void [change_both](#) (const T &first, const U &second)
Replace both members of the couple by val.
- void [change_first](#) (const T &val)
Replace the first member of the couple by val.
- void [change_second](#) (const U &val)
Replace the second member of the couple by val.
- const T & [first](#) () const
Get the first member of the couple.
- const U & [second](#) () const
Get the second member of the couple.

10.363.1 Detailed Description

```
template<typename T, typename U> class mln::util::couple< T, U >
```

Definition of a couple.

Definition at line 48 of file util/couple.hh.

10.363.2 Member Function Documentation

10.363.2.1 template<typename T , typename U > void mln::util::couple< T, U >::change_both (const T & *first*, const U & *second*) [inline]

Replace both members of the couple by *val*.

Definition at line 182 of file util/couple.hh.

10.363.2.2 template<typename T , typename U > void mln::util::couple< T, U >::change_first (const T & *val*) [inline]

Replace the first member of the couple by *val*.

Definition at line 166 of file util/couple.hh.

10.363.2.3 template<typename T , typename U > void mln::util::couple< T, U >::change_second (const U & *val*) [inline]

Replace the second member of the couple by *val*.

Definition at line 174 of file util/couple.hh.

10.363.2.4 template<typename T , typename U > const T & mln::util::couple< T, U >::first () const [inline]

Get the first member of the couple.

Definition at line 134 of file util/couple.hh.

10.363.2.5 template<typename T , typename U > const U & mln::util::couple< T, U >::second () const [inline]

Get the second member of the couple.


Definition at line 150 of file util/couple.hh.

10.364 mln::util::eat Struct Reference

Eat structure.

```
#include <eat.hh>
```

Inheritance diagram for mln::util::eat:



10.364.1 Detailed Description

Eat structure.

Definition at line 46 of file eat.hh.

10.365 mln::util::edge< G > Class Template Reference

[Edge](#) of a graph G.

```
#include <edge.hh>
```

Inherits mln::util::internal::edge_impl_< G >.

Public Types

- typedef [Edge< void > category](#)
Object category.
- typedef G [graph_t](#)
Graph associated type.
- typedef [edge_id_t id_t](#)
The edge type id.
- typedef [edge_id_t::value_t id_value_t](#)
The underlying type used to store edge ids.

Public Member Functions

- `edge ()`
Constructors.

- `bool is_valid () const`
Misc.
- `void invalidate ()`
Invalidate that vertex.
- `edge_id_t id () const`
Return the edge id.
- `void update_id (const edge_id_t &id)`
Set id_ with id;.
- `operator edge_id_t () const`
Conversion to the edge id.
- `const G & graph () const`
Return a reference to the graph holding this edge.
- `void change_graph (const G &g)`
Set g_ with g;.

- `vertex_id_t v_other (const vertex_id_t &id_v) const`
Vertex and edges oriented.

- `vertex_id_t v1 () const`
Edge oriented.
- `vertex_id_t v2 () const`
Return the highest vertex id adjacent to this edge.
- `size_t nmax_nbh_edges () const`
Return the number max of adjacent edges.
- `edge_id_t ith_nbh_edge (unsigned i) const`
Return the i th adjacent edge.

10.365.1 Detailed Description

`template<typename G> class mln::util::edge< G >`

`Edge` of a graph `G`.

Definition at line 69 of file `edge.hh`.

10.365.2 Member Typedef Documentation

10.365.2.1 template<typename G> typedef Edge<void> mln::util::edge< G >::category

[Object](#) category.

Definition at line 73 of file edge.hh.

10.365.2.2 template<typename G> typedef G mln::util::edge< G >::graph_t

[Graph](#) associated type.

Definition at line 82 of file edge.hh.

10.365.2.3 template<typename G> typedef edge_id_t mln::util::edge< G >::id_t

The edge type id.

Definition at line 79 of file edge.hh.

10.365.2.4 template<typename G> typedef edge_id_t::value_t mln::util::edge< G >::id_value_t

The underlying type used to store edge ids.

Definition at line 76 of file edge.hh.

10.365.3 Constructor & Destructor Documentation

10.365.3.1 template<typename G> mln::util::edge< G >::edge() [inline]

Constructors.

Definition at line 227 of file edge.hh.

References `mln::util::edge< G >::invalidate()`.

10.365.4 Member Function Documentation

10.365.4.1 template<typename G> void mln::util::edge< G >::change_graph(const G & g) [inline]

Set `g_` with `g`;

Definition at line 290 of file edge.hh.

10.365.4.2 template<typename G> const G & mln::util::edge< G >::graph() const [inline]

Return a reference to the graph holding this edge.

Definition at line 282 of file edge.hh.

Referenced by `mln::p_edges< G, F >::has()`, and `mln::util::line_graph< G >::has()`.

10.365.4.3 template<typename G> edge_id_t mln::util::edge< G >::id() const [inline]

Return the edge id.

Definition at line 259 of file edge.hh.

Referenced by mln::util::line_graph< G >::has().

10.365.4.4 template<typename G> void mln::util::edge< G >::invalidate() [inline]

Invalidate that vertex.

Definition at line 306 of file edge.hh.

Referenced by mln::util::edge< G >::edge().

10.365.4.5 template<typename G> bool mln::util::edge< G >::is_valid() const [inline]

Misc.

Return whether is points to a known edge.

Definition at line 298 of file edge.hh.

Referenced by mln::p_edges< G, F >::has().

10.365.4.6 template<typename G> edge_id_t mln::util::edge< G >::ith_nbh_edge(unsigned i) const [inline]

Return the *i* th adjacent edge.

Definition at line 351 of file edge.hh.

10.365.4.7 template<typename G> size_t mln::util::edge< G >::nmax_nbh_edges() const [inline]

Return the number max of adjacent edges.

Definition at line 342 of file edge.hh.

10.365.4.8 template<typename G> mln::util::edge< G >::operator edge_id_t() const [inline]

Conversion to the edge id.

Definition at line 274 of file edge.hh.

10.365.4.9 template<typename G> void mln::util::edge< G >::update_id(const edge_id_t & id) [inline]

Set id_ with *id*;

Definition at line 267 of file edge.hh.

10.365.4.10 template<typename G> vertex_id_t mln::util::edge< G >::v1() const [inline]

[Edge](#) oriented.

Return the lowest vertex id adjacent to this edge.

Definition at line 324 of file edge.hh.

Referenced by mln::util::edge< G >::v_other().

10.365.4.11 template<typename G> vertex_id_t mln::util::edge< G >::v2() const [inline]

Return the highest vertex id adjacent to this edge.

Definition at line 333 of file edge.hh.

Referenced by mln::util::edge< G >::v_other().

10.365.4.12 template<typename G> vertex_id_t mln::util::edge< G >::v_other(const vertex_id_t & id_v) const [inline]

[Vertex](#) and edges oriented.

Return the vertex id of this edge which is different from `id_v`.

Definition at line 315 of file edge.hh.


References mln::util::edge< G >::v1(), and mln::util::edge< G >::v2().

10.366 mln::util::fibonacci_heap< P, T > Class Template Reference

Fibonacci heap.

```
#include <fibonacci_heap.hh>
```

Inheritance diagram for mln::util::fibonacci_heap< P, T >:



Public Member Functions

- `void clear ()`
Clear all elements in the heap and make the heap empty.
- `fibonacci_heap ()`
Default constructor.
- `fibonacci_heap (const fibonacci_heap< P, T > &node)`
Copy constructor Be ware that once this heap is constructed, the argument node is cleared and all its elements are part of this new heap.
- `const T & front () const`
Return the minimum value in the heap.
- `bool is_empty () const`
Is it empty?
- `bool is_valid () const`
return false if it is empty.
- `unsigned nelements () const`
Return the number of elements.
- `fibonacci_heap< P, T > & operator= (fibonacci_heap< P, T > &rhs)`
Assignment operator.
- `T pop_front ()`

Return and remove the minimum value in the heap.

- void **push** (const P &priority, const T &value)
Push a new element in the heap.
- void **push** (**fibonacci_heap**< P, T > &other_heap)
Take other_heap's elements and insert them in this heap.

10.366.1 Detailed Description

template<typename P, typename T> class mln::util::fibonacci_heap< P, T >

Fibonacci heap.

Definition at line 117 of file fibonacci_heap.hh.

10.366.2 Constructor & Destructor Documentation

10.366.2.1 template<typename P , typename T > mln::util::fibonacci_heap< P, T >::fibonacci_heap() [inline]

Default constructor.

Definition at line 472 of file fibonacci_heap.hh.

10.366.2.2 template<typename P , typename T > mln::util::fibonacci_heap< P, T >::fibonacci_heap(const fibonacci_heap< P, T > & node) [inline]

Copy constructor Be ware that once this heap is constructed, the argument *node* is cleared and all its elements are part of this new heap.

Definition at line 480 of file fibonacci_heap.hh.

10.366.3 Member Function Documentation

10.366.3.1 template<typename P , typename T > void mln::util::fibonacci_heap< P, T >::clear() [inline]

Clear all elements in the heap and make the heap empty.

Definition at line 723 of file fibonacci_heap.hh.

References mln::util::fibonacci_heap< P, T >::pop_front().

10.366.3.2 template<typename P , typename T > const T & mln::util::fibonacci_heap< P, T >::front() const [inline]

Return the minimum value in the heap.

Definition at line 569 of file fibonacci_heap.hh.

10.366.3.3 template<typename P , typename T > bool mln::util::fibonacci_heap< P, T >::is_empty() const [inline]

Is it empty?

Definition at line 705 of file fibonacci_heap.hh.

Referenced by mln::util::fibonacci_heap< P, T >::pop_front(), and mln::util::fibonacci_heap< P, T >::push().

10.366.3.4 template<typename P , typename T > bool mln::util::fibonacci_heap< P, T >::is_valid() const [inline]

return false if it is empty.

Definition at line 714 of file fibonacci_heap.hh.

Referenced by mln::util::fibonacci_heap< P, T >::pop_front().

10.366.3.5 template<typename P , typename T > unsigned mln::util::fibonacci_heap< P, T >::elements() const [inline]

Return the number of elements.

Definition at line 745 of file fibonacci_heap.hh.

10.366.3.6 template<typename P , typename T > fibonacci_heap< P, T > & mln::util::fibonacci_heap< P, T >::operator=(fibonacci_heap< P, T > & rhs) [inline]

Assignment operator.

Be ware that this operator do *not* copy the data from `rhs` to this heap. It moves all elements which means that afterwards, `rhs` is cleared and all its elements are part of this new heap.

Definition at line 754 of file fibonacci_heap.hh.

10.366.3.7 template<typename P , typename T > T mln::util::fibonacci_heap< P, T >::pop_front() [inline]

Return and remove the minimum value in the heap.

Definition at line 578 of file fibonacci_heap.hh.

References mln::util::fibonacci_heap< P, T >::is_empty(), mln::util::fibonacci_heap< P, T >::is_valid(), and mln::util::fibonacci_heap< P, T >::push().

Referenced by mln::util::fibonacci_heap< P, T >::clear().

10.366.3.8 template<typename P , typename T > void mln::util::fibonacci_heap< P, T >::push(const P & priority, const T & value) [inline]

Push a new element in the heap.

See also

[insert](#)

Definition at line 508 of file fibonacci_heap.hh.

Referenced by `mln::util::fibonacci_heap< P, T >::pop_front()`.

10.366.3.9 template<typename P , typename T > void mln::util::fibonacci_heap< P, T >::push (fibonacci_heap< P, T > & other_heap) [inline]

Take `other_heap`'s elements and insert them in this heap.

After this call `other_heap` is cleared.

Definition at line 520 of file fibonacci_heap.hh.

References `mln::util::fibonacci_heap< P, T >::is_empty()`.

10.367 mln::util::graph Class Reference

Undirected graph.

#include <graph.hh>

Inherits `graph_base< graph >`.

Public Types

- `typedef std::set< edge_data_t > edges_set_t`
A set to test the presence of a given edge.
- `typedef std::vector< edge_data_t > edges_t`
The type of the set of edges.
- `typedef std::vector< vertex_data_t > vertices_t`
The type of the set of vertices.
- `typedef mln::internal::vertex_fwd_iterator< graph > vertex_fwd_iter`
Iterator types
Vertex iterators.
- `typedef mln::internal::vertex_nbh_edge_fwd_iterator< graph > vertex_nbh_edge_fwd_iter`
Vertex centered edge iterators.
- `typedef mln::internal::vertex_nbh_vertex_fwd_iterator< graph > vertex_nbh_vertex_fwd_iter`
Vertex centered vertex iterators.
- `typedef mln::internal::edge_fwd_iterator< graph > edge_fwd_iter`

Edge iterators.

- `typedef mln::internal::edge_nbh_edge_fwd_iterator< graph > edge_nbh_edge_fwd_iter`
Edge centered edge iterators.

Public Member Functions

- `graph ()`
- `graph (unsigned nvertices)`
Construct a graph with nvertices vertices.
- `bool has_v (const vertex_id_t &id_v) const`
Check whether a vertex id id_v exists in the graph.
- `edge_id_t v_ith_nbh_edge (const vertex_id_t &id_v, unsigned i) const`
Returns the i th edge adjacent to the vertex id_v.
- `vertex_id_t v_ith_nbh_vertex (const vertex_id_t &id_v, unsigned i) const`
Returns the i th vertex adjacent to the vertex id_v.
- `size_t v_nmax () const`
Return the number of vertices in the graph.
- `size_t v_nmax_nbh_edges (const vertex_id_t &id_v) const`
Return the number of adjacent edges of vertex id_v.
- `size_t v_nmax_nbh_vertices (const vertex_id_t &id_v) const`
Return the number of adjacent vertices of vertex id_v.
- `unsigned add_vertex ()`
Vertex oriented.
- `std::pair< vertex_id_t, vertex_id_t > add_vertices (unsigned n)`
Add n vertices to the graph.
- `vertex_t vertex (vertex_id_t id_v) const`
Return the vertex whose id is v.
- `edge_id_t add_edge (const vertex_id_t &id_v1, const vertex_id_t &id_v2)`
Edge oriented.
- `edge_t edge (const edge_id_t &e) const`
Return the edge whose id is e.
- `const std::vector< util::ord_pair< vertex_id_t > > & edges () const`
Return the list of all edges.

- `size_t e_nmax () const`
Return the number of edges in the graph.
- `bool has_e (const edge_id_t &id_e) const`
Return whether `id_e` is in the graph.
- `edge_t edge (const vertex_t &v1, const vertex_t &v2) const`
Return the corresponding edge id if exists.
- `vertex_id_t v1 (const edge_id_t &id_e) const`
Return the first vertex associated to the edge `id_e`.
- `vertex_id_t v2 (const edge_id_t &id_e) const`
Return the second vertex associated to edge `id_e`.
- `size_t e_nmax_nbh_edges (const edge_id_t &id_e) const`
Return the number max of adjacent edge, given an edge `id_e`.
- `edge_id_t e_ith_nbh_edge (const edge_id_t &id_e, unsigned i) const`
Return the `i` th edge adjacent to the edge `id_e`.
- template<typename G2 >
`bool is_subgraph_of (const G2 &g) const`
*Return whether this graph is a subgraph. Return true if `g` and `*this` have the same graph_id.*

10.367.1 Detailed Description

Undirected graph.

Definition at line 87 of file mln/util/graph.hh.

10.367.2 Member Typedef Documentation

10.367.2.1 `typedef mln::internal::edge_fwd_iterator<graph> mln::util::graph::edge_fwd_iter`

`Edge` iterators.

Definition at line 129 of file mln/util/graph.hh.

10.367.2.2 `typedef mln::internal::edge_nbh_edge_fwd_iterator<graph> mln::util::graph::edge_nbh_edge_fwd_iter`

`Edge` centered edge iterators.

Definition at line 136 of file mln/util/graph.hh.

10.367.2.3 `typedef std::set<edge_data_t> mln::util::graph::edges_set_t`

A set to test the presence of a given edge.

Definition at line 102 of file mln/util/graph.hh.

10.367.2.4 `typedef std::vector<edge_data_t> mln::util::graph::edges_t`

The type of the set of edges.

Definition at line 100 of file mln/util/graph.hh.

10.367.2.5 `typedef mln::internal::vertex_fwd_iterator<graph> mln::util::graph::vertex_fwd_iter`

[Iterator](#) types

[Vertex](#) iterators.

Definition at line 108 of file mln/util/graph.hh.

10.367.2.6 `typedef mln::internal::vertex_nbh_edge_fwd_iterator<graph> mln::util::graph::vertex_nbh_edge_fwd_iter`

[Vertex](#) centered edge iterators.

Definition at line 115 of file mln/util/graph.hh.

10.367.2.7 `typedef mln::internal::vertex_nbh_vertex_fwd_iterator<graph> mln::util::graph::vertex_nbh_vertex_fwd_iter`

[Vertex](#) centered vertex iterators.

Definition at line 122 of file mln/util/graph.hh.

10.367.2.8 `typedef std::vector<vertex_data_t> mln::util::graph::vertices_t`

The type of the set of vertices.

Definition at line 97 of file mln/util/graph.hh.

10.367.3 Constructor & Destructor Documentation

10.367.3.1 `mln::util::graph::graph() [inline]`

Constructor.

Definition at line 282 of file mln/util/graph.hh.

10.367.3.2 `mln::util::graph::graph(unsigned nvertices) [inline]`

Construct a graph with `nvertices` vertices.

Definition at line 288 of file mln/util/graph.hh.

10.367.4 Member Function Documentation

10.367.4.1 `edge_id_t mln::util::graph::add_edge (const vertex_id_t & id_v1, const vertex_id_t & id_v2) [inline]`

[Edge](#) oriented.

Add an edge.

Returns

The id of the new edge if it does not exist yet; otherwise, return `mln_max (unsigned)`.

Definition at line 386 of file `mln/util/graph.hh`.

References `edge()`, and `has_v()`.

Referenced by `mln::make::voronoi()`.

10.367.4.2 `unsigned mln::util::graph::add_vertex () [inline]`

[Vertex](#) oriented.

Shortcuts factoring the insertion of vertices and edges. Add a vertex.

Returns

The id of the new vertex.

Definition at line 299 of file `mln/util/graph.hh`.

References `v_nmax()`.

Referenced by `mln::make::voronoi()`.

10.367.4.3 `std::pair<vertex_id_t, vertex_id_t> mln::util::graph::add_vertices (unsigned n) [inline]`

Add `n` vertices to the graph.

Returns

A range of vertex ids.

Definition at line 310 of file `mln/util/graph.hh`.

References `v_nmax()`.

10.367.4.4 `edge_id_t mln::util::graph::e_ith_nbh_edge (const edge_id_t & id_e, unsigned i) const [inline]`

Return the `i` th edge adjacent to the edge `id_e`.

Definition at line 503 of file `mln/util/graph.hh`.

References `e_nmax()`, `e_nmax_nbh_edges()`, `has_e()`, `v1()`, `v2()`, `v_ith_nbh_edge()`, and `v_nmax_nbh_edges()`.

10.367.4.5 size_t mln::util::graph::e_nmax() const [inline]

Return the number of edges in the graph.

Definition at line 443 of file mln/util/graph.hh.

Referenced by e_ith_nbh_edge(), and edge().

10.367.4.6 size_t mln::util::graph::e_nmax_nbh_edges(const edge_id_t & id_e) const [inline]

Return the number max of adjacent edge, given an edge `id_e`.

Definition at line 495 of file mln/util/graph.hh.

References has_e(), v1(), v2(), and v_nmax_nbh_edges().

Referenced by e_ith_nbh_edge().

10.367.4.7 graph::edge_t mln::util::graph::edge(const edge_id_t & e) const [inline]

Return the edge whose id is `e`.

Definition at line 435 of file mln/util/graph.hh.

References e_nmax().

Referenced by add_edge().

10.367.4.8 graph::edge_t mln::util::graph::edge(const vertex_t & v1, const vertex_t & v2) const [inline]

Return the corresponding edge id if exists.

If it is not, returns an invalid edge.

Definition at line 457 of file mln/util/graph.hh.

References has_v().

10.367.4.9 const std::vector< util::ord_pair< vertex_id_t > > & mln::util::graph::edges() const [inline]

Return the list of all edges.

Definition at line 428 of file mln/util/graph.hh.

10.367.4.10 bool mln::util::graph::has_e(const edge_id_t & id_e) const [inline]

Return whether `id_e` is in the graph.

Definition at line 450 of file mln/util/graph.hh.

Referenced by e_ith_nbh_edge(), e_nmax_nbh_edges(), v1(), and v2().

10.367.4.11 bool mln::util::graph::has_v (const vertex_id_t & id_v) const [inline]

Check whether a vertex id `id_v` exists in the graph.

Definition at line 338 of file mln/util/graph.hh.

Referenced by `add_edge()`, `edge()`, `v_ith_nbh_edge()`, `v_ith_nbh_vertex()`, `v_nmax_nbh_edges()`, `v_nmax_nbh_vertices()`, and `vertex()`.

10.367.4.12 template<typename G2> bool mln::util::graph::is_subgraph_of (const G2 & g) const [inline]

Return whether this graph is a subgraph Return true if `g` and `*this` have the same `graph_id`.

Definition at line 519 of file mln/util/graph.hh.

10.367.4.13 vertex_id_t mln::util::graph::v1 (const edge_id_t & id_e) const [inline]

Return the first vertex associated to the edge `id_e`.

Definition at line 479 of file mln/util/graph.hh.

References `has_e()`.

Referenced by `e_ith_nbh_edge()`, and `e_nmax_nbh_edges()`.

10.367.4.14 vertex_id_t mln::util::graph::v2 (const edge_id_t & id_e) const [inline]

Return the second vertex associated to edge `id_e`.

Definition at line 487 of file mln/util/graph.hh.

References `has_e()`.

Referenced by `e_ith_nbh_edge()`, and `e_nmax_nbh_edges()`.

10.367.4.15 edge_id_t mln::util::graph::v_ith_nbh_edge (const vertex_id_t & id_v, unsigned i) const [inline]

Returns the `i` th edge adjacent to the vertex `id_v`.

Definition at line 353 of file mln/util/graph.hh.

References `has_v()`, and `v_nmax_nbh_edges()`.

Referenced by `e_ith_nbh_edge()`, and `v_ith_nbh_vertex()`.

10.367.4.16 vertex_id_t mln::util::graph::v_ith_nbh_vertex (const vertex_id_t & id_v, unsigned i) const [inline]

Returns the `i` th vertex adjacent to the vertex `id_v`.

Definition at line 371 of file mln/util/graph.hh.

References `has_v()`, and `v_ith_nbh_edge()`.

10.367.4.17 size_t mln::util::graph::v_nmax() const [inline]

Return the number of vertices in the graph.

Definition at line 331 of file mln/util/graph.hh.

Referenced by add_vertex(), and add_vertices().

10.367.4.18 size_t mln::util::graph::v_nmax_nbh_edges(const vertex_id_t & id_v) const [inline]

Return the number of adjacent edges of vertex `id_v`.

Definition at line 345 of file mln/util/graph.hh.

References has_v().

Referenced by e_ith_nbh_edge(), e_nmax_nbh_edges(), v_ith_nbh_edge(), and v_nmax_nbh_vertices().

10.367.4.19 size_t mln::util::graph::v_nmax_nbh_vertices(const vertex_id_t & id_v) const [inline]

Return the number of adjacent vertices of vertex `id_v`.

Definition at line 363 of file mln/util/graph.hh.

References has_v(), and v_nmax_nbh_edges().

10.367.4.20 graph::vertex_t mln::util::graph::vertex(vertex_id_t id_v) const [inline]

Return the vertex whose id is v .

Definition at line 322 of file mln/util/graph.hh.

References has_v().

10.368 mln::util::greater_point< I > Class Template Reference

A “greater than” functor comparing points w.r.t.

```
#include <greater_point.hh>
```

Public Member Functions

- bool `operator()` (const point &x, const point &y)

Is x greater than y?

10.368.1 Detailed Description**template<typename I> class mln::util::greater_point< I >**

A “greater than” functor comparing points w.r.t. the values they refer to in an image.

This functor used in useful to implement ordered queues of points.

Definition at line 42 of file greater_point.hh.

10.368.2 Member Function Documentation

10.368.2.1 template<typename I> bool mln::util::greater_point< I >::operator() (const point & x, const point & y)

Is x greater than y ?

Definition at line 74 of file greater_point.hh.

10.369 mln::util::greater_psite< I > Class Template Reference

A “greater than” functor comparing psites w.r.t.

```
#include <greater_psite.hh>
```

Public Member Functions

- bool [operator\(\)](#) (const psite & x , const psite & y)

Is x greater than y ?

10.369.1 Detailed Description

template<typename I> class mln::util::greater_psite< I >

A “greater than” functor comparing psites w.r.t. the values they refer to in an image.

This functor used in useful to implement ordered queues of psites.

Definition at line 42 of file greater_psite.hh.

10.369.2 Member Function Documentation

10.369.2.1 template<typename I> bool mln::util::greater_psite< I >::operator() (const psite & x, const psite & y)

Is x greater than y ?

Definition at line 74 of file greater_psite.hh.

10.370 mln::util::head< T, R > Class Template Reference

Top structure of the soft heap.

```
#include <soft_heap.hh>
```

10.370.1 Detailed Description

```
template<typename T, typename R> class mln::util::head< T, R >
```

Top structure of the soft heap.


Definition at line 138 of file soft_heap.hh.

10.371 mln::util::ignore Struct Reference

Ignore structure.

```
#include <ignore.hh>
```

Inheritance diagram for mln::util::ignore:



10.371.1 Detailed Description

Ignore structure.

Definition at line 46 of file ignore.hh.

10.372 mln::util::ilcell< T > Struct Template Reference

Element of an item list. Store the data (key) used in [soft_heap](#).

```
#include <soft_heap.hh>
```

10.372.1 Detailed Description

template<typename T> struct mln::util::ilcell< T >

Element of an item list. Store the data (key) used in [soft_heap](#).

Definition at line 76 of file [soft_heap.hh](#).

10.373 mln::util::line_graph< G > Class Template Reference

Undirected line graph of a graph of type `G`.

#include <[line_graph.hh](#)>

Inherits `graph_base< line_graph< G > >`.

Public Types

- `typedef std::vector< edge_data_t > edges_t`

The type of the set of edges.

- `typedef std::vector< vertex_data_t > vertices_t`

The type of the set of vertices.

- `typedef mln::internal::vertex_fwd_iterator< line_graph< G > > vertex_fwd_iter`

Iterator types

Vertex iterators.

- `typedef mln::internal::edge_fwd_iterator< line_graph< G > > edge_fwd_iter`

Edge iterators.

- `typedef mln::internal::edge_nbh_edge_fwd_iterator< line_graph< G > > edge_nbh_edge_fwd_iter`

Edge nbh edge iterators.

- `typedef mln::internal::vertex_nbh_vertex_fwd_iterator< line_graph< G > > vertex_nbh_vertex_fwd_iter`

Vertex nbh vertex iterators.

- `typedef mln::internal::vertex_nbh_edge_fwd_iterator< line_graph< G > > vertex_nbh_edge_fwd_iter`

Vertex nbh edge iterators.

Public Member Functions

- template<typename G2>
bool **has** (const [util::vertex](#)< G2 > &v) const
Check whether a vertex v exists in the line graph.
- bool **has_v** (const [vertex_id_t](#) &id_v) const
Check whether a vertex id id_v exists in the line graph.
- [edge_id_t v_ith_nbh_edge](#) (const [vertex_id_t](#) &id_v, unsigned i) const
Returns the i th edge adjacent to the vertex id_v.
- [vertex_id_t v_ith_nbh_vertex](#) (const [vertex_id_t](#) &id_v, unsigned i) const
Returns the i th vertex adjacent to the vertex id_v.
- size_t **v_nmax** () const
Return the number of vertices in the graph.
- size_t **v_nmax_nbh_edges** (const [vertex_id_t](#) &id_v) const
Return the number of adjacent edges of vertex id_v.
- size_t **v_nmax_nbh_vertices** (const [vertex_id_t](#) &id_v) const
Return the number of adjacent vertices of vertex id_v.
- vertex_t **vertex** (const [vertex_id_t](#) &id_v) const
Vertex oriented.
- [edge_t edge](#) (const [edge_id_t](#) &e) const
Edge oriented.
- size_t **e_nmax** () const
Return the number of edges in the graph.
- bool **has_e** (const [edge_id_t](#) &id_e) const
Return whether id_e is in the line graph.
- template<typename G2>
bool **has** (const [util::edge](#)< G2 > &e) const
Return whether e is in the line graph.
- [vertex_id_t v1](#) (const [edge_id_t](#) &id_e) const
Return the first vertex associated to the edge id_e.
- [vertex_id_t v2](#) (const [edge_id_t](#) &id_e) const
Return the second vertex associated to edge id_e.
- size_t **e_nmax_nbh_edges** (const [edge_id_t](#) &id_e) const
Return the number max of adjacent edge, given an edge id_e.
- [edge_id_t e_ith_nbh_edge](#) (const [edge_id_t](#) &id_e, unsigned i) const

Return the i th edge adjacent to the edge id_e .

- template<typename G2 >
bool **is_subgraph_of** (const G2 &g) const

*Return whether this graph is a subgraph Return true if g and *this have the same graph_id.*

- const G & **graph** () const

Return the underlying graph.

10.373.1 Detailed Description

template<typename G> class mln::util::line_graph< G >

Undirected line graph of a graph of type G.

Definition at line 82 of file line_graph.hh.

10.373.2 Member Typedef Documentation

10.373.2.1 template<typename G> typedef mln::internal::edge_fwd_iterator< line_graph<G> > mln::util::line_graph< G >::edge_fwd_iter

Edge iterators.

Definition at line 114 of file line_graph.hh.

10.373.2.2 template<typename G> typedef mln::internal::edge_nbh_edge_fwd_iterator< line_graph<G> > mln::util::line_graph< G >::edge_nbh_edge_fwd_iter

Edge nbh edge iterators.

Definition at line 123 of file line_graph.hh.

10.373.2.3 template<typename G> typedef std::vector<edge_data_t> mln::util::line_graph< G >::edges_t

The type of the set of edges.

Definition at line 98 of file line_graph.hh.

10.373.2.4 template<typename G> typedef mln::internal::vertex_fwd_iterator< line_graph<G> > mln::util::line_graph< G >::vertex_fwd_iter

Iterator types

Vertex iterators.

Definition at line 105 of file line_graph.hh.

10.373.2.5 template<typename G> typedef mln::internal::vertex_nbh_edge_fwd_iterator< line_graph<G>> mln::util::line_graph< G >::vertex_nbh_edge_fwd_iter

Vertex nbh edge iterators.

Definition at line 141 of file line_graph.hh.

10.373.2.6 template<typename G> typedef mln::internal::vertex_nbh_vertex_fwd_iterator< line_graph<G>> mln::util::line_graph< G >::vertex_nbh_vertex_fwd_iter

Vertex nbh vertex iterators.

Definition at line 132 of file line_graph.hh.

10.373.2.7 template<typename G> typedef std::vector<vertex_data_t> mln::util::line_graph< G >::vertices_t

The type of the set of vertices.

Definition at line 95 of file line_graph.hh.

10.373.3 Member Function Documentation

10.373.3.1 template<typename G> edge_id_t mln::util::line_graph< G >::e_ith_nbh_edge (const edge_id_t & id_e, unsigned i) const [inline]

Return the *i* th edge adjacent to the edge *id_e*.

Definition at line 460 of file line_graph.hh.

References mln::util::line_graph< G >::e_nmax(), mln::util::line_graph< G >::e_nmax_nbh_edges(), mln::util::line_graph< G >::has_e(), mln::util::line_graph< G >::v1(), mln::util::line_graph< G >::v2(), mln::util::line_graph< G >::v_ith_nbh_edge(), and mln::util::line_graph< G >::v_nmax_nbh_edges().

10.373.3.2 template<typename G> size_t mln::util::line_graph< G >::e_nmax () const [inline]

Return the number of edges in the graph.

Definition at line 408 of file line_graph.hh.

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge(), and mln::util::line_graph< G >::edge().

10.373.3.3 template<typename G> size_t mln::util::line_graph< G >::e_nmax_nbh_edges (const edge_id_t & id_e) const [inline]

Return the number max of adjacent edge, given an edge *id_e*.

Definition at line 451 of file line_graph.hh.

References mln::util::line_graph< G >::has_e(), mln::util::line_graph< G >::v1(), mln::util::line_graph< G >::v2(), and mln::util::line_graph< G >::v_nmax_nbh_edges().

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge().

10.373.3.4 template<typename G> line_graph<G>::edge_t mln::util::line_graph<G>::edge (const edge_id_t & e) const [inline]

[Edge](#) oriented.

Return the edge whose id is *e*.

Definition at line 399 of file line_graph.hh.

References mln::util::line_graph<G>::e_nmax().

10.373.3.5 template<typename G> const G & mln::util::line_graph<G>::graph () const [inline]

Return the underlying graph.

Definition at line 485 of file line_graph.hh.

10.373.3.6 template<typename G> template<typename G2> bool mln::util::line_graph<G>::has (const util::vertex<G2> & v) const [inline]

Check whether a vertex *v* exists in the line graph.

Definition at line 345 of file line_graph.hh.

References mln::util::vertex<G>::graph(), mln::util::line_graph<G>::has_v(), and mln::util::vertex<G>::id().

10.373.3.7 template<typename G> template<typename G2> bool mln::util::line_graph<G>::has (const util::edge<G2> & e) const [inline]

Return whether *e* is in the line graph.

Definition at line 425 of file line_graph.hh.

References mln::util::edge<G>::graph(), mln::util::line_graph<G>::has_e(), and mln::util::edge<G>::id().

10.373.3.8 template<typename G> bool mln::util::line_graph<G>::has_e (const util::edge_id_t & id_e) const [inline]

Return whether *id_e* is in the line graph.

Definition at line 416 of file line_graph.hh.

Referenced by mln::util::line_graph<G>::e_ith_nbh_edge(), mln::util::line_graph<G>::e_nmax_nbh_edges(), mln::util::line_graph<G>::has(), mln::util::line_graph<G>::v1(), and mln::util::line_graph<G>::v2().

10.373.3.9 template<typename G> bool mln::util::line_graph<G>::has_v (const vertex_id_t & id_v) const [inline]

Check whether a vertex *id_v* exists in the line graph.

Definition at line 336 of file line_graph.hh.

Referenced by mln::util::line_graph< G >::has(), mln::util::line_graph< G >::v_ith_nbh_edge(), mln::util::line_graph< G >::v_ith_nbh_vertex(), mln::util::line_graph< G >::v_nmax_nbh_edges(), mln::util::line_graph< G >::v_nmax_nbh_vertices(), and mln::util::line_graph< G >::vertex().

10.373.3.10 template<typename G> template<typename G2> bool mln::util::line_graph< G >::is_subgraph_of(const G2 & g) const [inline]

Return whether this graph is a subgraph Return true if g and *this have the same graph_id.

Definition at line 477 of file line_graph.hh.

10.373.3.11 template<typename G> vertex_id_t mln::util::line_graph< G >::v1(const edge_id_t & id_e) const [inline]

Return the first vertex associated to the edge id_e.

Definition at line 433 of file line_graph.hh.

References mln::util::line_graph< G >::has_e().

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge(), and mln::util::line_graph< G >::e_nmax_nbh_edges().

10.373.3.12 template<typename G> vertex_id_t mln::util::line_graph< G >::v2(const edge_id_t & id_e) const [inline]

Return the second vertex associated to edge id_e.

Definition at line 442 of file line_graph.hh.

References mln::util::line_graph< G >::has_e().

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge(), and mln::util::line_graph< G >::e_nmax_nbh_edges().

10.373.3.13 template<typename G> edge_id_t mln::util::line_graph< G >::v_ith_nbh_edge(const vertex_id_t & id_v, unsigned i) const [inline]

Returns the i th edge adjacent to the vertex id_v.

Definition at line 363 of file line_graph.hh.

References mln::util::line_graph< G >::has_v(), mln::util::line_graph< G >::v_nmax(), and mln::util::line_graph< G >::v_nmax_nbh_edges().

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge(), and mln::util::line_graph< G >::v_ith_nbh_vertex().

10.373.3.14 template<typename G> vertex_id_t mln::util::line_graph< G >::v_ith_nbh_vertex(const vertex_id_t & id_v, unsigned i) const [inline]

Returns the i th vertex adjacent to the vertex id_v.

Definition at line 383 of file line_graph.hh.

References mln::util::line_graph< G >::has_v(), and mln::util::line_graph< G >::v_ith_nbh_edge().

10.373.3.15 template<typename G> size_t mln::util::line_graph< G >::v_nmax() const [inline]

Return the number of vertices in the graph.

Definition at line 328 of file line_graph.hh.

Referenced by mln::util::line_graph< G >::v_ith_nbh_edge().

10.373.3.16 template<typename G> size_t mln::util::line_graph< G >::v_nmax_nbh_edges(const vertex_id_t & id_v) const [inline]

Return the number of adjacent edges of vertex `id_v`.

Definition at line 354 of file line_graph.hh.

References mln::util::line_graph< G >::has_v().

Referenced by mln::util::line_graph< G >::e_ith_nbh_edge(), mln::util::line_graph< G >::e_nmax_nbh_edges(), mln::util::line_graph< G >::v_ith_nbh_edge(), and mln::util::line_graph< G >::v_nmax_nbh_vertices().

10.373.3.17 template<typename G> size_t mln::util::line_graph< G >::v_nmax_nbh_vertices(const vertex_id_t & id_v) const [inline]

Return the number of adjacent vertices of vertex `id_v`.

Definition at line 374 of file line_graph.hh.

References mln::util::line_graph< G >::has_v(), and mln::util::line_graph< G >::v_nmax_nbh_edges().

10.373.3.18 template<typename G> line_graph< G >::vertex_t mln::util::line_graph< G >::vertex(const vertex_id_t & id_v) const [inline]

[Vertex](#) oriented.

Shortcuts factoring the insertion of vertices and edges.

Return the vertex whose id is `v`.

Definition at line 318 of file line_graph.hh.


References mln::util::line_graph< G >::has_v().

10.374 mln::util::nil Struct Reference

Nil structure.

```
#include <nil.hh>
```

Inheritance diagram for `mln::util::nil`:



10.374.1 Detailed Description

Nil structure.

Definition at line 46 of file `util/nil.hh`.

10.375 `mln::util::node< T, R >` Class Template Reference

Meta-data of an element in the heap.

```
#include <soft_heap.hh>
```

10.375.1 Detailed Description

```
template<typename T, typename R> class mln::util::node< T, R >
```

Meta-data of an element in the heap.


Definition at line 97 of file `soft_heap.hh`.

10.376 `mln::util::object_id< Tag, V >` Class Template Reference

Base class of an object id.

```
#include <object_id.hh>
```

Inheritance diagram for mln::util::object_id< Tag, V >:



Public Types

- `typedef V value_t`

The underlying type id.

Public Member Functions

- `object_id ()`
Constructors.

10.376.1 Detailed Description

`template<typename Tag, typename V> class mln::util::object_id< Tag, V >`

Base class of an object id.

Template Parameters

Tag the tag type

Equiv the equivalent value.

Definition at line 66 of file `object_id.hh`.

10.376.2 Member Typedef Documentation

10.376.2.1 `template<typename Tag, typename V> typedef V mln::util::object_id< Tag, V >::value_t`

The underlying type id.

Definition at line 70 of file `object_id.hh`.

10.376.3 Constructor & Destructor Documentation

10.376.3.1 `template<typename Tag, typename V> mln::util::object_id< Tag, V >::object_id() [inline]`

Constructors.

Definition at line 120 of file `object_id.hh`.

10.377 `mln::util::ord< T >` Struct Template Reference

Function-object that defines an ordering between objects with type `T`: *lhs R rhs*.

```
#include <ord.hh>
```

10.377.1 Detailed Description

`template<typename T> struct mln::util::ord< T >`

Function-object that defines an ordering between objects with type `T`: *lhs R rhs*. Its meaning is "lhs less-than rhs."


Definition at line 48 of file `util/ord.hh`.

10.378 `mln::util::ord_pair< T >` Struct Template Reference

Ordered pair structure s.a.

```
#include <ord_pair.hh>
```

Inheritance diagram for `mln::util::ord_pair< T >`:



Public Member Functions

- void `change_both` (const T &first, const T &second)
Replace both members of the pair by val, while keeping the relative order.
- void `change_first` (const T &val)
Replace the first member of the pair by val, while keeping the relative order.
- void `change_second` (const T &val)
Replace the second member of the pair by val, while keeping the relative order.
- const T & `first` () const
Get the first (lowest) member of the pair.
- const T & `second` () const
Get the second (highest) member of the pair.

10.378.1 Detailed Description

`template<typename T> struct mln::util::ord_pair< T >`

Ordered pair structure s.a. `this->first <= this->second`; ordered pairs are partially ordered using lexicographical ordering.

Definition at line 50 of file `ord_pair.hh`.

10.378.2 Member Function Documentation

10.378.2.1 `template<typename T> void mln::util::ord_pair< T >::change_both (const T & first, const T & second) [inline]`

Replace both members of the pair by *val*, while keeping the relative order.

Postcondition

first_ \leq *second_* (with \leq being the `mln::util::ord_weak` relationship).

Definition at line 211 of file `ord_pair.hh`.

References `mln::util::ord_strict()`, and `mln::util::ord_weak()`.

10.378.2.2 `template<typename T> void mln::util::ord_pair< T >::change_first (const T & val) [inline]`

Replace the first member of the pair by *val*, while keeping the relative order.

Postcondition

first_ \leq *second_* (with \leq being the `mln::util::ord_weak` relationship).

Definition at line 181 of file `ord_pair.hh`.

References `mln::util::ord_strict()`, and `mln::util::ord_weak()`.

10.378.2.3 `template<typename T> void mln::util::ord_pair< T >::change_second (const T & val) [inline]`

Replace the second member of the pair by *val*, while keeping the relative order.

Postcondition

first_ \leq *second_* (with \leq being the `mln::util::ord_weak` relationship).

Definition at line 196 of file `ord_pair.hh`.

References `mln::util::ord_strict()`, and `mln::util::ord_weak()`.

10.378.2.4 `template<typename T> const T & mln::util::ord_pair< T >::first () const [inline]`

Get the first (lowest) member of the pair.

Definition at line 149 of file `ord_pair.hh`.

10.378.2.5 `template<typename T> const T & mln::util::ord_pair< T >::second () const [inline]`

Get the second (highest) member of the pair.

Definition at line 165 of file `ord_pair.hh`.

10.379 mln::util::pix< I > Struct Template Reference

Structure pix.

```
#include <pix.hh>
```

Public Types

- **typedef I::psite psite**
Point_Site associated type.
- **typedef I::value value**
Value associated type.

Public Member Functions

- **const I & ima () const**
The getter of the image associate to pix structure.
- **const I::psite & p () const**
The getter of psite associate to pix structure.
- **pix (const Image< I > &ima, const typename I::psite &p)**
Constructor.
- **I::rvalue v () const**
The getter of value associate to pix structure.

10.379.1 Detailed Description

```
template<typename I> struct mln::util::pix< I >
```

Structure pix.

Definition at line 69 of file util/pix.hh.

10.379.2 Member Typedef Documentation

10.379.2.1 template<typename I> typedef I ::psite mln::util::pix< I >::psite

Point_Site associated type.

Definition at line 73 of file util/pix.hh.

10.379.2.2 template<typename I> typedef I ::value mln::util::pix< I >::value

Value associated type.

Definition at line 76 of file util/pix.hh.

10.379.3 Constructor & Destructor Documentation

10.379.3.1 template<typename I> mln::util::pix< I >::pix (const Image< I > & *ima*, const typename I::psite & *p*) [inline]

Constructor.

Parameters

[in] *ima* The image.

[in] *p* The p_site.

Definition at line 121 of file util/pix.hh.

10.379.4 Member Function Documentation

10.379.4.1 template<typename I> const I & mln::util::pix< I >::ima () const [inline]

The getter of the image associate to pix structure.

Returns

The image *ima*_.

Definition at line 131 of file util/pix.hh.

10.379.4.2 template<typename I> const I::psite & mln::util::pix< I >::p () const [inline]

The getter of psite associate to pix structure.

Returns

The psite *p*_.

Definition at line 140 of file util/pix.hh.

10.379.4.3 template<typename I> I::rvalue mln::util::pix< I >::v () const [inline]

The getter of value associate to pix structure.

Returns

The value of pix.


Definition at line 150 of file util/pix.hh.

10.380 mln::util::set< T > Class Template Reference

An "efficient" mathematical set class.

```
#include <set.hh>
```

Inheritance diagram for `mln::util::set< T >`:



Public Types

- `typedef set_bkd_iter< T > bkd_eiter`
Backward iterator associated type.
- `typedef fwd_eiter eiter`
Iterator associated type.
- `typedef T element`
Element associated type.
- `typedef set_fwd_iter< T > fwd_eiter`
Forward iterator associated type.

Public Member Functions

- `void clear()`
Empty the set.
- `const T first_element() const`
Return the first element of the set.
- `bool has(const T &elt) const`
Test if the object `elt` belongs to the set.
- `set< T > & insert(const T &elt)`

Insert an element `elt` into the set.

- template<typename U>
`set< T > & insert (const set< U > &other)`

Insert the elements of `other` into the set.

- bool `is_empty` () const

Test if the set is empty.

- const T `last_element` () const

Return the last element of the set.

- std::size_t `memory_size` () const

Return the size of this set in memory.

- unsigned `nElements` () const

Return the number of elements of the set.

- const T & `operator[]` (unsigned i) const

Return the i-th element of the set.

- `set< T > & remove (const T &elt)`

Remove an element `elt` into the set.

- `set()`

Constructor without arguments.

- const std::vector< T > & `std_vector` () const

Give access to the set elements.

10.380.1 Detailed Description

`template<typename T> class mln::util::set< T >`

An "efficient" mathematical set class. This set class is designed to store a mathematical set and to present it to the user as a linear array (std::vector).

Elements are stored by copy. Implementation is lazy.

The set has two states: frozen or not. There is an automatic switch of state when the user modifies its contents (insert, remove, or clear) or access to its contents (`op[i]`).

The parameter `T` is the element type, which shall not be const-qualified.

The unicity of set elements is handled by the `mln::util::ord` mechanism.

See also

[mln::util::ord](#)

Definition at line 81 of file util/set.hh.

10.380.2 Member Typedef Documentation

10.380.2.1 `template<typename T> typedef set_bkd_iter<T> mln::util::set< T >::bkd_eiter`

Backward iterator associated type.

Definition at line 93 of file util/set.hh.

10.380.2.2 `template<typename T> typedef fwd_eiter mln::util::set< T >::eiter`

Iterator associated type.

Definition at line 96 of file util/set.hh.

10.380.2.3 `template<typename T> typedef T mln::util::set< T >::element`

Element associated type.

Definition at line 86 of file util/set.hh.

10.380.2.4 `template<typename T> typedef set_fwd_iter<T> mln::util::set< T >::fwd_eiter`

Forward iterator associated type.

Definition at line 90 of file util/set.hh.

10.380.3 Constructor & Destructor Documentation

10.380.3.1 `template<typename T > mln::util::set< T >::set() [inline]`

Constructor without arguments.

Definition at line 348 of file util/set.hh.

10.380.4 Member Function Documentation

10.380.4.1 `template<typename T > void mln::util::set< T >::clear() [inline]`

Empty the set.

All elements contained in the set are destroyed so the set is emptied.

Postcondition

`is_empty() == true`

Definition at line 390 of file util/set.hh.

References `mln::util::set< T >::is_empty()`.

10.380.4.2 `template<typename T > const T mln::util::set< T >::first_element() const [inline]`

Return the first element of the set.

Precondition

not `is_empty()`

Definition at line 427 of file util/set.hh.

References `mln::util::set< T >::is_empty()`.

10.380.4.3 template<typename T> bool mln::util::set< T >::has (const T & elt) const [inline]

Test if the object `elt` belongs to the set.

Parameters

[in] `elt` A possible element of the set.

Returns

True if `elt` is in the set.

Definition at line 445 of file util/set.hh.

10.380.4.4 template<typename T> set< T > & mln::util::set< T >::insert (const T & elt) [inline]

Insert an element `elt` into the set.

Parameters

[in] `elt` The element to be inserted.

If `elt` is already in the set, this method is a no-op.

Returns

The set itself after insertion.

Definition at line 356 of file util/set.hh.

Referenced by `mln::p_key< K, P >::change_keys()`.

10.380.4.5 template<typename T> template<typename U> set< T > & mln::util::set< T >::insert (const set< U > & other) [inline]

Insert the elements of `other` into the set.

Parameters

[in] `other` The set containing the elements to be inserted.

Returns

The set itself after insertion.

Definition at line 367 of file util/set.hh.

References `mln::util::set< T >::is_empty()`, and `mln::util::set< T >::std_vector()`.

10.380.4.6 template<typename T > bool mln::util::set< T >::is_empty () const [inline]

Test if the set is empty.

Definition at line 453 of file util/set.hh.

References mln::util::set< T >::nelements().

Referenced by mln::util::set< T >::clear(), mln::util::set< T >::first_element(), mln::util::set< T >::insert(), and mln::util::set< T >::last_element().

10.380.4.7 template<typename T > const T mln::util::set< T >::last_element () const [inline]

Return the last element of the set.

Precondition

not [is_empty\(\)](#)

Definition at line 436 of file util/set.hh.

References mln::util::set< T >::is_empty().

10.380.4.8 template<typename T > std::size_t mln::util::set< T >::memory_size () const [inline]

Return the size of this set in memory.

Definition at line 494 of file util/set.hh.

References mln::util::set< T >::nelements().

10.380.4.9 template<typename T > unsigned mln::util::set< T >::nelements () const [inline]

Return the number of elements of the set.

Definition at line 409 of file util/set.hh.

Referenced by mln::util::set< T >::is_empty(), mln::util::set< T >::memory_size(), and mln::util::set< T >::operator[]().

10.380.4.10 template<typename T > const T & mln::util::set< T >::operator[](unsigned i) const [inline]

Return the i-th element of the set.

Parameters

[in] *i* Index of the element to retrieve.

Precondition

i < [nelements\(\)](#)

The element is returned by reference and is constant.

Definition at line 417 of file util/set.hh.

References mln::util::set< T >::elements().

10.380.4.11 template<typename T> set< T > & mln::util::set< T >::remove (const T & elt) [inline]

Remove an element *elt* into the set.

Parameters

[in] *elt* The element to be inserted.

If *elt* is already in the set, this method is a no-op.

Returns

The set itself after suppression.

Definition at line 380 of file util/set.hh.

10.380.4.12 template<typename T> const std::vector< T > & mln::util::set< T >::std_vector () const [inline]

Give access to the set elements.

The complexity of this method is O(1).

Postcondition

The set is frozen.

Returns

An array (std::vector) of elements.

Definition at line 461 of file util/set.hh.


Referenced by mln::util::set< T >::insert().

10.381 mln::util::site_pair< P > Class Template Reference

A pair of sites.

```
#include <site_pair.hh>
```

Inheritance diagram for `mln::util::site_pair< P >`:



Public Member Functions

- `const P & first () const`
Return the first site.
- `const util::ord_pair< P > & pair () const`
Return the underlying pair.
- `const P & second () const`
Return the second site.

10.381.1 Detailed Description

`template<typename P> class mln::util::site_pair< P >`

A pair of sites. It can be used as site.

Definition at line 52 of file `site_pair.hh`.

10.381.2 Member Function Documentation

10.381.2.1 `template<typename P > const P & mln::util::site_pair< P >::first () const [inline]`

Return the first site.

Definition at line 142 of file `site_pair.hh`.

10.381.2.2 template<typename P> const util::ord_pair< P > & mln::util::site_pair< P >::pair() const [inline]

Return the underlying pair.

Definition at line 158 of file site_pair.hh.

10.381.2.3 template<typename P> const P & mln::util::site_pair< P >::second() const [inline]

Return the second site.


Definition at line 150 of file site_pair.hh.

10.382 mln::util::soft_heap< T, R > Class Template Reference

Soft heap.

```
#include <soft_heap.hh>
```

Inheritance diagram for mln::util::soft_heap< T, R >:



Public Types

- **typedef T element**
Element associated type.

Public Member Functions

- **void clear()**

Clear the heap.

- bool `is_empty () const`

Return true if there is at least one element.

- bool `is_valid () const`

Return true if there is at least one element.

- int `nelements () const`

Return the number of element in the heap.

- T `pop_front ()`

Returns the element with the lowest priority and remove it from the heap.

- void `push (soft_heap< T, R > &sh)`

Merge sh with this heap.

- void `push (const T &element)`

Add a new element element.

- `soft_heap (unsigned r=20)`

Default constructor.

- `~soft_heap ()`

Destructor.

10.382.1 Detailed Description

`template<typename T, typename R> class mln::util::soft_heap< T, R >`

Soft heap. T key, the data to store in the heap. For instance a point 2d. R rank, for instance int_u8
Definition at line 178 of file soft_heap.hh.

10.382.2 Member Typedef Documentation

10.382.2.1 `template<typename T, typename R> typedef T mln::util::soft_heap< T, R >::element`

Element associated type.

Definition at line 185 of file soft_heap.hh.

10.382.3 Constructor & Destructor Documentation

10.382.3.1 `template<typename T , typename R > mln::util::soft_heap< T, R >::soft_heap (unsigned r = 20) [inline]`

Default constructor.

A corruption threshold `r` can be specified. This threshold means that if nodes have a rank higher than this threshold they can be "corrupted" and therefore their rank can be reduced.

Definition at line 619 of file `soft_heap.hh`.

10.382.3.2 `template<typename T, typename R> mln::util::soft_heap< T, R >::~soft_heap() [inline]`

Destructor.

Definition at line 631 of file `soft_heap.hh`.

10.382.4 Member Function Documentation

10.382.4.1 `template<typename T, typename R> void mln::util::soft_heap< T, R >::clear() [inline]`

Clear the heap.

Definition at line 771 of file `soft_heap.hh`.

10.382.4.2 `template<typename T, typename R> bool mln::util::soft_heap< T, R >::is_empty() const [inline]`

Return true if there is at least one element.

Definition at line 753 of file `soft_heap.hh`.

10.382.4.3 `template<typename T, typename R> bool mln::util::soft_heap< T, R >::is_valid() const [inline]`

Return true if there is at least one element.

Definition at line 744 of file `soft_heap.hh`.

Referenced by `mln::util::soft_heap< T, R >::pop_front()`.

10.382.4.4 `template<typename T, typename R> int mln::util::soft_heap< T, R >::nelements() const [inline]`

Return the number of element in the heap.

Definition at line 762 of file `soft_heap.hh`.

Referenced by `mln::util::soft_heap< T, R >::push()`.

10.382.4.5 `template<typename T, typename R> T mln::util::soft_heap< T, R >::pop_front() [inline]`

Returns the element with the lowest priority and remove it from the heap.

Definition at line 675 of file `soft_heap.hh`.

References `mln::util::soft_heap< T, R >::is_valid()`.

10.382.4.6 `template<typename T, typename R> void mln::util::soft_heap< T, R >::push (const T & element) [inline]`

Add a new element `element`.

Definition at line 646 of file `soft_heap.hh`.

10.382.4.7 `template<typename T, typename R> void mln::util::soft_heap< T, R >::push (soft_heap< T, R > & sh) [inline]`

Merge `sh` with this heap.

Be ware that after this call, `sh` will be empty. This heap will hold the elements which were part of `sh`.

Definition at line 658 of file `soft_heap.hh`.


References `mln::util::soft_heap< T, R >::nelements()`.

10.383 mln::util::timer Class Reference

Timer structure.

```
#include <timer.hh>
```

Inheritance diagram for `mln::util::timer`:



10.383.1 Detailed Description

Timer structure.

Definition at line 45 of file mln/util/timer.hh.

10.384 mln::util::tracked_ptr< T > Struct Template Reference

Smart pointer for shared data with tracking.

```
#include <tracked_ptr.hh>
```

Public Member Functions

- `operator bool () const`

Coercion towards Boolean (for arithmetical tests).

- `bool operator! () const`

Negation (for arithmetical tests).

- `T * operator-> ()`

Mimics the behavior of op-> for a pointer in the mutable case.

- `const T * operator-> () const`

Mimics the behavior of op-> for a pointer in the const case.

- `tracked_ptr< T > & operator= (T *ptr)`

Assignment.

- `tracked_ptr< T > & operator= (const tracked_ptr< T > &rhs)`

Assignment.

- `~tracked_ptr ()`

Destructor.

- `tracked_ptr ()`

Constructors.

- `tracked_ptr (const tracked_ptr< T > &rhs)`

Copy constructor.

10.384.1 Detailed Description

```
template<typename T> struct mln::util::tracked_ptr< T >
```

Smart pointer for shared data with tracking.

Definition at line 52 of file tracked_ptr.hh.

10.384.2 Constructor & Destructor Documentation

10.384.2.1 template<typename T> mln::util::tracked_ptr< T >::tracked_ptr() [inline]

Constructors.

Definition at line 140 of file tracked_ptr.hh.

10.384.2.2 template<typename T> mln::util::tracked_ptr< T >::tracked_ptr(const tracked_ptr< T > & rhs) [inline]

Copy constructor.

Definition at line 164 of file tracked_ptr.hh.

10.384.2.3 template<typename T> mln::util::tracked_ptr< T >::~tracked_ptr() [inline]

Destructor.

Definition at line 216 of file tracked_ptr.hh.

10.384.3 Member Function Documentation

10.384.3.1 template<typename T> mln::util::tracked_ptr< T >::operator bool() const [inline]

Coercion towards Boolean (for arithmetical tests).

Definition at line 106 of file tracked_ptr.hh.

10.384.3.2 template<typename T> bool mln::util::tracked_ptr< T >::operator! () const [inline]

Negation (for arithmetical tests).

Definition at line 114 of file tracked_ptr.hh.

10.384.3.3 template<typename T> T * mln::util::tracked_ptr< T >::operator-> () [inline]

Mimics the behavior of op-> for a pointer in the mutable case.

Invariant

Pointer proxy exists.

Definition at line 131 of file tracked_ptr.hh.

10.384.3.4 template<typename T> const T * mln::util::tracked_ptr< T >::operator-> () const [inline]

Mimics the behavior of op-> for a pointer in the const case.

Invariant

Pointer proxy exists.

Definition at line 122 of file tracked_ptr.hh.

10.384.3.5 template<typename T > tracked_ptr< T > & mln::util::tracked_ptr< T >::operator= (T * ptr) [inline]

Assignment.

Definition at line 195 of file tracked_ptr.hh.

10.384.3.6 template<typename T > tracked_ptr< T > & mln::util::tracked_ptr< T >::operator= (const tracked_ptr< T > & rhs) [inline]

Assignment.

Definition at line 176 of file tracked_ptr.hh.

10.385 mln::util::tree< T > Class Template Reference

Class of generic tree.

```
#include <tree.hh>
```

Public Member Functions

- void [add_tree_down](#) (T &elt)
Bind a new tree downer the current.
- void [add_tree_up](#) (T &elt)
Bind a new tree upper the current.
- bool [check_consistency](#) ()
Check the consistency of the tree.
- [branch< T > main_branch](#) ()
Convert the tree into brach.
- [tree_node< T > * root](#) ()
The getter of the root.
- [tree](#) ()
Constructor.
- [tree \(tree_node< T > *root\)](#)
Constructor.

10.385.1 Detailed Description

template<typename T> class mln::util::tree< T >

Class of generic tree.

Definition at line 187 of file tree.hh.

10.385.2 Constructor & Destructor Documentation

10.385.2.1 template<typename T > mln::util::tree< T >::tree() [inline]

Constructor.

Definition at line 285 of file tree.hh.

10.385.2.2 template<typename T > mln::util::tree< T >::tree (tree_node< T > * root) [inline]

Constructor.

Parameters

[in] *root* The root of the tree.

Definition at line 292 of file tree.hh.

10.385.3 Member Function Documentation

10.385.3.1 template<typename T > void mln::util::tree< T >::add_tree_down (T & elt) [inline]

Bind a new tree downer the current.

Parameters

[in] *elt* The new value of the new tree_node of the new tree add downer the current.

Definition at line 328 of file tree.hh.

10.385.3.2 template<typename T > void mln::util::tree< T >::add_tree_up (T & elt) [inline]

Bind a new tree upper the current.

Parameters

[in] *elt* The new value of the new tree_node of the new tree add upper the current.

Definition at line 317 of file tree.hh.

References mln::util::tree_node< T >::children().

**10.385.3.3 template<typename T> bool mln::util::tree< T >::check_consistency()
[inline]**

Check the consistency of the tree.

Returns

true if no error, else false.

Definition at line 338 of file tree.hh.

References mln::util::tree< T >::root().

**10.385.3.4 template<typename T> branch< T > mln::util::tree< T >::main_branch()
[inline]**

Convert the tree into brach.

Returns

The root's [tree_node](#) of the the current tree.

Definition at line 309 of file tree.hh.

References mln::util::tree< T >::root().

**10.385.3.5 template<typename T> tree_node< T > * mln::util::tree< T >::root()
[inline]**

The getter of the root.

Returns

The root's [tree_node](#) of the the current tree.

Definition at line 301 of file tree.hh.

Referenced by mln::util::tree< T >::check_consistency(), mln::util::display_tree(), mln::util::tree< T >::main_branch(), and mln::util::tree_to_fast().

10.386 mln::util::tree_node< T > Class Template Reference

Class of generic [tree_node](#) for tree.

```
#include <tree.hh>
```

Public Member Functions

- [tree_node< T > * add_child \(T elt\)](#)
Create a [tree_node](#) with elt which become the child of the current [tree_node](#).
- [tree_node< T > * add_child \(tree_node< T > *tree_node\)](#)

Bind `tree_node` to the current `tree_node` and become its child.

- `bool check_consistency ()`
Check the consistency of the `tree_node`.
- `children_t & children ()`
The getter of the children.
- `const children_t & children () const`
The getter of the children.
- `tree_node< T > * delete_tree_node ()`
Delete the current `tree_node`.
- `T & elt ()`
The getter of the element.
- `const T & elt () const`
The const getter of the element.
- `tree_node< T > * parent ()`
The getter of the parent.
- `void print (std::ostream &ostr, int level=0)`
Print on `ostr` the arborescence with the current `tree_node` as root.
- `tree_node< T > * search (T &elt)`
Search the `tree_node` with value `elt` in the arborescence of the current `tree_node`.
- `int search_rec (tree_node< T > **res, T &elt)`
The using method for method search.
- `void set_parent (tree_node< T > *parent)`
Bind `tree_node` to the current `tree_node` and become its parent.
- `tree_node ()`
Constructor.
- `tree_node (T elt)`
Constructor.

10.386.1 Detailed Description

`template<typename T> class mln::util::tree_node< T >`

Class of generic `tree_node` for tree.

Definition at line 58 of file tree.hh.

10.386.2 Constructor & Destructor Documentation

10.386.2.1 template<typename T> mln::util::tree_node< T >::tree_node() [inline]

Constructor.

Definition at line 345 of file tree.hh.

10.386.2.2 template<typename T> mln::util::tree_node< T >::tree_node(T elt) [inline]

Constructor.

Parameters

[in] *elt* The element of [tree_node](#).

Definition at line 352 of file tree.hh.

10.386.3 Member Function Documentation

10.386.3.1 template<typename T> tree_node< T > * mln::util::tree_node< T >::add_child(T elt) [inline]

Create a [tree_node](#) with *elt* which become the child of the current [tree_node](#).

Parameters

[in] *elt* The element of the new child to add.

Returns

The new [tree_node](#) created.

Definition at line 394 of file tree.hh.

10.386.3.2 template<typename T> tree_node< T > * mln::util::tree_node< T >::add_child(tree_node< T > * tree_node) [inline]

Bind [tree_node](#) to the current [tree_node](#) and become its child.

Parameters

[in] *tree_node* The new child [tree_node](#).

Returns

The child [tree_node](#).

Definition at line 407 of file tree.hh.

References [mln::util::tree_node< T >::children\(\)](#), and [mln::util::tree_node< T >::parent\(\)](#).

10.386.3.3 template<typename T > bool mln::util::tree_node< T >::check_consistency() [inline]

Check the consistency of the [tree_node](#).

Returns

true if no error, else false.

Definition at line 519 of file tree.hh.

10.386.3.4 template<typename T > const std::vector< tree_node< T > * > & mln::util::tree_node< T >::children() const [inline]

The getter of the children.

Returns

The children of the [tree_node](#) in const.

Definition at line 386 of file tree.hh.

10.386.3.5 template<typename T > std::vector< tree_node< T > * > & mln::util::tree_node< T >::children() [inline]

The getter of the children.

Returns

The children of the [tree_node](#).

Definition at line 378 of file tree.hh.

Referenced by [mln::util::tree_node< T >::add_child\(\)](#), and [mln::util::tree< T >::add_tree_up\(\)](#).

10.386.3.6 template<typename T > tree_node< T > * mln::util::tree_node< T >::delete_tree_node() [inline]

Delete the current [tree_node](#).

Definition at line 427 of file tree.hh.

10.386.3.7 template<typename T > const T & mln::util::tree_node< T >::elt() const [inline]

The const getter of the element.

Returns

The element of the [tree_node](#) in const.

Definition at line 361 of file tree.hh.

10.386.3.8 template<typename T > T & mln::util::tree_node< T >::elt() [inline]

The getter of the element.

Returns

The element of the [tree_node](#).

Definition at line 369 of file tree.hh.

Referenced by [mln::util::tree_node< T >::print\(\)](#).

10.386.3.9 template<typename T > tree_node< T > * mln::util::tree_node< T >::parent() [inline]

The getter of the parent.

Returns

The parent of the [tree_node](#).

Definition at line 477 of file tree.hh.

Referenced by [mln::util::tree_node< T >::add_child\(\)](#), [mln::util::branch_iter_ind< T >::deepness\(\)](#), and [mln::util::branch_iter< T >::deepness\(\)](#).

10.386.3.10 template<typename T > void mln::util::tree_node< T >::print(std::ostream & ostr, int level = 0) [inline]

Print on `ostr` the arborescence with the current [tree_node](#) as root.

Parameters

[in] `ostr` The output stream.

[in] `level` The deep level

Definition at line 449 of file tree.hh.

References [mln::util::tree_node< T >::elt\(\)](#).

10.386.3.11 template<typename T > tree_node< T > * mln::util::tree_node< T >::search(T & elt) [inline]

Search the [tree_node](#) with value `elt` in the arborescence of the current [tree_node](#).

Parameters

[in] `elt` The value of the searched [tree_node](#).

Returns

If not found 0 else the [tree_node](#) with `elt` value.

Definition at line 507 of file tree.hh.

References [mln::util::tree_node< T >::search_rec\(\)](#).

10.386.3.12 template<typename T> int mln::util::tree_node< T >::search_rec (tree_node< T > ** res, T & elt) [inline]

The using method for method search.

Definition at line 485 of file tree.hh.

Referenced by mln::util::tree_node< T >::search().

10.386.3.13 template<typename T> void mln::util::tree_node< T >::set_parent (tree_node< T > * parent) [inline]

Bind `tree_node` to the current `tree_node` and become its parent.

Parameters

[in] `parent` The new parent `tree_node`.


Definition at line 467 of file tree.hh.

10.387 mln::util::vertex< G > Class Template Reference

[Vertex](#) of a graph `G`.

```
#include <vertex.hh>
```

Inheritance diagram for mln::util::vertex< G >:



Public Types

- **typedef Vertex< void > Category**
Object category.
- **typedef G graph_t**
Graph associated type.
- **typedef vertex_id_t id_t**
The vertex type id.
- **typedef vertex_id_t::value_t id_value_t**
The underlying type used to store vertex ids.

Public Member Functions

- **void change_graph (const G &g)**
Change the parent graph of that vertex.
- **edge< G > edge_with (const vertex< G > &v_id) const**
Returns true if this vertex has an edge with the given vertex.
- **const G & graph () const**
Returns the graph pointer this vertex belongs to.
- **const vertex_id_t & id () const**
Returns the vertex id.
- **void invalidate ()**
Invalidate that vertex.
- **bool is_valid () const**
Check whether the vertex is still part of the graph.
- **edge_id_t ith_nbh_edge (unsigned i) const**
Returns the ith edge starting from this vertex.
- **vertex_id_t ith_nbh_vertex (unsigned i) const**
Returns the ith vertex adjacent to this vertex.
- **unsigned nmax_nbh_edges () const**
Returns the number max of edges starting from this vertex.
- **unsigned nmax_nbh_vertices () const**
Returns the number max of vertices adjacent to this vertex.
- **operator vertex_id_t () const**
Conversion to the vertex id.

- `vertex_id_t other` (const `edge_id_t &id_e`) const
Returns the other vertex located on edge `id_e`.
- `void update_id` (const `vertex_id_t &id`)
Update the vertex id.
- `vertex()`
Constructors.

10.387.1 Detailed Description

`template<typename G> class mln::util::vertex< G >`

[Vertex](#) of a graph `G`.

Definition at line 71 of file `vertex.hh`.

10.387.2 Member Typedef Documentation

10.387.2.1 template<typename G> typedef Vertex<void> mln::util::vertex< G >::Category

[Object](#) category.

Definition at line 77 of file `vertex.hh`.

10.387.2.2 template<typename G> typedef G mln::util::vertex< G >::graph_t

[Graph](#) associated type.

Definition at line 86 of file `vertex.hh`.

10.387.2.3 template<typename G> typedef vertex_id_t mln::util::vertex< G >::id_t

The vertex type id.

Definition at line 83 of file `vertex.hh`.

10.387.2.4 template<typename G> typedef vertex_id_t::value_t mln::util::vertex< G >::id_value_t

The underlying type used to store vertex ids.

Definition at line 80 of file `vertex.hh`.

10.387.3 Constructor & Destructor Documentation

10.387.3.1 template<typename G> mln::util::vertex< G >::vertex() [inline]

Constructors.

Definition at line 226 of file vertex.hh.

References mln::util::vertex< G >::invalidate().

10.387.4 Member Function Documentation

10.387.4.1 template<typename G> void mln::util::vertex< G >::change_graph (const G & g) [inline]

Change the parent graph of that vertex.

Definition at line 331 of file vertex.hh.

10.387.4.2 template<typename G> edge< G > mln::util::vertex< G >::edge_with (const vertex< G > & v_id) const [inline]

Returns true if this vertex has an edge with the given vertex.

Definition at line 321 of file vertex.hh.

10.387.4.3 template<typename G> const G & mln::util::vertex< G >::graph () const [inline]

Returns the graph pointer this vertex belongs to.

Definition at line 348 of file vertex.hh.

Referenced by mln::p_vertices< G, F >::has(), mln::util::line_graph< G >::has(), and mln::util::operator==().

10.387.4.4 template<typename G> const vertex_id_t & mln::util::vertex< G >::id () const [inline]

Returns the vertex id.

Definition at line 356 of file vertex.hh.

Referenced by mln::util::line_graph< G >::has(), and mln::util::operator==().

10.387.4.5 template<typename G> void mln::util::vertex< G >::invalidate () [inline]

Invalidate that vertex.

Definition at line 266 of file vertex.hh.

Referenced by mln::util::vertex< G >::vertex().

10.387.4.6 template<typename G> bool mln::util::vertex< G >::is_valid () const [inline]

Check whether the vertex is still part of the graph.

Definition at line 258 of file vertex.hh.

Referenced by mln::p_vertices< G, F >::has().

10.387.4.7 template<typename G> edge_id_t mln::util::vertex< G >::ith_nbh_edge (unsigned *i*) const [inline]

Returns the *i*th edge starting from this vertex.

Definition at line 285 of file vertex.hh.

10.387.4.8 template<typename G> vertex_id_t mln::util::vertex< G >::ith_nbh_vertex (unsigned *i*) const [inline]

Returns the *i*th vertex adjacent to this vertex.

Definition at line 303 of file vertex.hh.

10.387.4.9 template<typename G> unsigned mln::util::vertex< G >::nmax_nbh_edges () const [inline]

Returns the number max of edges starting from this vertex.

If *g_* is a sub graph of another graph, nmax will be retrived from the initial graph.

Definition at line 294 of file vertex.hh.

10.387.4.10 template<typename G> unsigned mln::util::vertex< G >::nmax_nbh_vertices () const [inline]

Returns the number max of vertices adjacent to this vertex.

Definition at line 312 of file vertex.hh.

10.387.4.11 template<typename G> mln::util::vertex< G >::operator vertex_id_t () const [inline]

Conversion to the vertex id.

FIXME: May cause ambiguities... :(

Definition at line 363 of file vertex.hh.

10.387.4.12 template<typename G> vertex_id_t mln::util::vertex< G >::other (const edge_id_t & *id_e*) const [inline]

Returns the other vertex located on edge *id_e*.

Definition at line 274 of file vertex.hh.

10.387.4.13 template<typename G> void mln::util::vertex< G >::update_id (const vertex_id_t & *id*) [inline]

Update the vertex id.


Definition at line 340 of file vertex.hh.

10.388 mln::util::yes Struct Reference

[Object](#) that always says "yes".

```
#include <yes.hh>
```

Inheritance diagram for mln::util::yes:



10.388.1 Detailed Description

[Object](#) that always says "yes".


Definition at line 76 of file yes.hh.

10.389 mln::Value< E > Struct Template Reference

Base class for implementation classes of values.

```
#include <value.hh>
```

Inheritance diagram for `mln::Value< E >`:



10.389.1 Detailed Description

`template<typename E> struct mln::Value< E >`

Base class for implementation classes of values.

See also

[mln::doc::Value](#) for a complete documentation of this class contents.

Definition at line 57 of file core/concept/value.hh.

10.390 mln::value::float01 Class Reference

Class for floating values restricted to the interval [0..1] and discretized with n bits.

```
#include <float01.hh>
```

Inherits mln::value::Floating<> float01 >.

Public Types

- **typedef std::pair< unsigned, unsigned long > enc**
Encoding associated type.
- **typedef float equiv**
Equivalent associated type.

Public Member Functions

- **float01 ()**
Ctor.
- template<unsigned n>
float01 (const float01_< n > &val)
Ctor.
- **float01 (unsigned nbits, float val)**
Ctor.
- **unsigned nbits () const**
Access to the encoding size.
- **operator float () const**
Conversion to float.
- **float01 & set_nbBits (unsigned nbits)**
Set the encoding size to nbits.
- **const float01 to_nbBits (unsigned nbits) const**
Return an equivalent gray encoded on nbits bits.
- **float value () const**
Access to std type.
- **unsigned long value_index () const**
Access to the position in the quantized interval.

10.390.1 Detailed Description

Class for floating values restricted to the interval [0..1] and discretized with n bits.

Definition at line 56 of file float01.hh.

10.390.2 Member Typedef Documentation

10.390.2.1 `typedef std::pair<unsigned, unsigned long> mln::value::float01::enc`

Encoding associated type.

Definition at line 61 of file float01.hh.

10.390.2.2 `typedef float mln::value::float01::equiv`

Equivalent associated type.

Definition at line 64 of file float01.hh.

10.390.3 Constructor & Destructor Documentation

10.390.3.1 `mln::value::float01::float01() [inline]`

Ctor.

Definition at line 151 of file float01.hh.

10.390.3.2 `template<unsigned n> mln::value::float01::float01(const float01_<n> & val) [inline]`

Ctor.

Definition at line 158 of file float01.hh.

10.390.3.3 `mln::value::float01::float01(unsigned nbits, float val) [inline]`

Ctor.

Definition at line 165 of file float01.hh.

10.390.4 Member Function Documentation

10.390.4.1 `unsigned mln::value::float01::nbits() const [inline]`

Access to the encoding size.

Definition at line 186 of file float01.hh.

10.390.4.2 `mln::value::float01::operator float() const [inline]`

Conversion to float.

Definition at line 224 of file float01.hh.

10.390.4.3 float01 & mln::value::float01::set_nbits(unsigned nbits) [inline]

Set the encoding size to nbits.

Definition at line 193 of file float01.hh.

Referenced by to_nbits().

10.390.4.4 const float01 mln::value::float01::to_nbits(unsigned nbits) const [inline]

Return an equivalent gray encoded on nbits bits.

Definition at line 214 of file float01.hh.

References set_nbits().

10.390.4.5 float mln::value::float01::value() const [inline]

Access to std type.

Definition at line 172 of file float01.hh.

10.390.4.6 unsigned long mln::value::float01::value_ind() const [inline]

Access to the position in the quantized interval.

Definition at line 179 of file float01.hh.

10.391 mln::value::float01_f Struct Reference

Class for floating values restricted to the interval [0..1].

```
#include <float01_f.hh>
```

Inherits mln::value::Floating< float01_f >, and mln::value::internal::value_like_< float,float,float,float01_f >.

Public Member Functions

- [float01_f\(\)](#)

Constructor without argument.

- [float01_f\(float val\)](#)

Constructor from a float.

- [operator float\(\) const](#)

Conversion to a float.

- [float01_f & operator=\(const float val\)](#)

Assignment from a float.

- float `value () const`
Access to float value.

10.391.1 Detailed Description

Class for floating values restricted to the interval [0..1].

Definition at line 84 of file float01_f.hh.

10.391.2 Constructor & Destructor Documentation

10.391.2.1 `mln::value::float01_f::float01_f() [inline]`

Constructor without argument.

Definition at line 115 of file float01_f.hh.

10.391.2.2 `mln::value::float01_f::float01_f(float val) [inline]`

Constructor from a float.

Definition at line 120 of file float01_f.hh.

10.391.3 Member Function Documentation

10.391.3.1 `mln::value::float01_f::operator float() const [inline]`

Conversion to a float.

Definition at line 145 of file float01_f.hh.

10.391.3.2 `float01_f & mln::value::float01_f::operator=(const float val) [inline]`

Assignment from a float.

Definition at line 136 of file float01_f.hh.

10.391.3.3 `float mln::value::float01_f::value() const [inline]`

Access to float value.


Definition at line 129 of file float01_f.hh.

10.392 `mln::value::graylevel< n >` Struct Template Reference

General gray-level class on n bits.

```
#include <graylevel.hh>
```

Inheritance diagram for mln::value::graylevel< n >:



Public Member Functions

- [graylevel \(\)](#)
Constructor without argument.
- [graylevel \(const graylevel< n > &rhs\)](#)
Copy constructor.
- [graylevel \(int val\)](#)
Constructor from int.
- template<unsigned m>
[graylevel \(const graylevel< m > &rhs\)](#)
Constructor from any graylevel.
- [graylevel< n > & operator= \(const graylevel< n > &rhs\)](#)
Assignment.
- [graylevel< n > & operator= \(int val\)](#)
Assignment with int.
- template<unsigned m>
[graylevel< n > & operator= \(const graylevel< m > &rhs\)](#)
Assignment with any graylevel.
- float [to_float \(\) const](#)
Conversion to float between 0 and 1.

- `unsigned value () const`

Access to std type.

- `graylevel (const mln::literal::black_t &)`

Ctors with literals.

- `graylevel< n > & operator= (const mln::literal::black_t &)`

Assignment with literals.

10.392.1 Detailed Description

`template<unsigned n> struct mln::value::graylevel< n >`

General gray-level class on n bits.

Definition at line 257 of file graylevel.hh.

10.392.2 Constructor & Destructor Documentation

10.392.2.1 `template<unsigned n> mln::value::graylevel< n >::graylevel () [inline]`

Constructor without argument.

Definition at line 436 of file graylevel.hh.

10.392.2.2 `template<unsigned n> mln::value::graylevel< n >::graylevel (const graylevel< n > & rhs) [inline]`

Copy constructor.

Definition at line 463 of file graylevel.hh.

10.392.2.3 `template<unsigned n> mln::value::graylevel< n >::graylevel (int val) [inline]`

Constructor from int.

Definition at line 443 of file graylevel.hh.

10.392.2.4 `template<unsigned n> template<unsigned m> mln::value::graylevel< n >::graylevel (const graylevel< m > & rhs) [inline]`

Constructor from any graylevel.

Definition at line 481 of file graylevel.hh.

References `mln::value::graylevel< n >::value()`.

10.392.2.5 template<unsigned n> mln::value::graylevel< n >::graylevel (const mln::literal::black_t &) [inline]

Ctors with literals.

Definition at line 499 of file graylevel.hh.

10.392.3 Member Function Documentation

10.392.3.1 template<unsigned n> graylevel< n > & mln::value::graylevel< n >::operator= (const graylevel< n > & rhs) [inline]

Assignment.

Definition at line 472 of file graylevel.hh.

10.392.3.2 template<unsigned n> graylevel< n > & mln::value::graylevel< n >::operator= (int val) [inline]

Assignment with int.

Definition at line 453 of file graylevel.hh.

10.392.3.3 template<unsigned n> graylevel< n > & mln::value::graylevel< n >::operator= (const mln::literal::black_t &) [inline]

Assignment with literals.

Definition at line 507 of file graylevel.hh.

10.392.3.4 template<unsigned n> template<unsigned m> graylevel< n > & mln::value::graylevel< n >::operator= (const graylevel< m > & rhs) [inline]

Assignment with any graylevel.

Definition at line 490 of file graylevel.hh.

References mln::value::graylevel< n >::value().

10.392.3.5 template<unsigned n> float mln::value::graylevel< n >::to_float () const [inline]

Conversion to float between 0 and 1.

Definition at line 557 of file graylevel.hh.

Referenced by mln::value::graylevel_f::graylevel_f(), and mln::value::graylevel_f::operator=().

10.392.3.6 template<unsigned n> unsigned mln::value::graylevel< n >::value () const [inline]

Access to std type.

Definition at line 549 of file graylevel.hh.

Referenced by `mln::value::graylevel< n >::graylevel()`, and `mln::value::graylevel< n >::operator=()`.

10.393 mln::value::graylevel_f Struct Reference

General gray-level class on n bits.

```
#include <graylevel_f.hh>
```

Inherits `mln::value::Floating< graylevel_f >`, and `mln::value::internal::value_like_< float01_f,float01_f::enc, internal::gray_f,graylevel_f >`.

Public Member Functions

- `graylevel_f()`
Constructor without argument.
- `graylevel_f(const graylevel_f &rhs)`
Copy constructor.
- `graylevel_f(float val)`
Constructor from float.
- template<unsigned n>
`graylevel_f(const graylevel< n > &rhs)`
Constructor from graylevel.
- template<unsigned n>
`operator graylevel< n > () const`
Conversion to graylevel<n>.
- `graylevel_f & operator=(float val)`
Assignment with float.
- `graylevel_f & operator=(const graylevel_f &rhs)`
Assignment.
- template<unsigned n>
`graylevel_f & operator=(const graylevel< n > &rhs)`
Assignment with graylevel.
- `float value() const`
Access to std type.
- `graylevel_f(const mln::literal::black_t &)`
Ctors with literals.
- `graylevel_f & operator=(const mln::literal::black_t &)`
Assignment with literals.

10.393.1 Detailed Description

General gray-level class on n bits.

Definition at line 193 of file graylevel_f.hh.

10.393.2 Constructor & Destructor Documentation

10.393.2.1 mln::value::graylevel_f::graylevel_f() [inline]

Constructor without argument.

Definition at line 341 of file graylevel_f.hh.

10.393.2.2 mln::value::graylevel_f::graylevel_f(const graylevel_f & rhs) [inline]

Copy constructor.

Definition at line 383 of file graylevel_f.hh.

10.393.2.3 mln::value::graylevel_f::graylevel_f(float val) [inline]

Constructor from float.

Definition at line 347 of file graylevel_f.hh.

10.393.2.4 template<unsigned n> mln::value::graylevel_f::graylevel_f(const graylevel<n> & rhs)

Constructor from graylevel.

Definition at line 365 of file graylevel_f.hh.

References mln::value::graylevel<n>::to_float().

10.393.2.5 mln::value::graylevel_f::graylevel_f(const mln::literal::black_t &) [inline]

Ctors with literals.

Definition at line 400 of file graylevel_f.hh.

10.393.3 Member Function Documentation

10.393.3.1 template<unsigned n> mln::value::graylevel_f::operator graylevel<n>() const [inline]

Conversion to graylevel<n>.

Definition at line 443 of file graylevel_f.hh.

10.393.3.2 graylevel_f & mln::value::graylevel_f::operator=(float val) [inline]

Assignment with float.

Definition at line 356 of file graylevel_f.hh.

10.393.3.3 template<unsigned n> graylevel_f & mln::value::graylevel_f::operator= (const graylevel<n> & rhs)

Assignment with graylevel.

Definition at line 374 of file graylevel_f.hh.

References mln::value::graylevel<n>::to_float().

10.393.3.4 graylevel_f & mln::value::graylevel_f::operator= (const mln::literal::black_t &) [inline]

Assignment with literals.

Definition at line 407 of file graylevel_f.hh.

10.393.3.5 graylevel_f & mln::value::graylevel_f::operator= (const graylevel_f & rhs) [inline]

Assignment.

Definition at line 391 of file graylevel_f.hh.

10.393.3.6 float mln::value::graylevel_f::value () const [inline]

Access to std type.

Definition at line 450 of file graylevel_f.hh.


Referenced by mln::value::operator<<().

10.394 mln::value::int_s<n> Struct Template Reference

Signed integer value class.

```
#include <int_s.hh>
```

Inheritance diagram for mln::value::int_s< n >:



Public Member Functions

- `int_s()`
Constructor without argument.
- `int_s(int i)`
Constructor from an integer.
- `operator int() const`
Conversion to an integer.
- `int_s< n > & operator=(int i)`
Assignment from an integer.

- `int_s(const mln::literal::zero_t &)`
Constructors/assignments with literals.

Static Public Attributes

- static const `int_s< n > one = 1`
Unit value.
- static const `int_s< n > zero = 0`
Zero value.

10.394.1 Detailed Description

template<unsigned n> struct mln::value::int_s< n >

Signed integer value class. The parameter is n the number of encoding bits.

Definition at line 115 of file int_s.hh.

10.394.2 Constructor & Destructor Documentation

10.394.2.1 template<unsigned n> mln::value::int_s< n >::int_s() [inline]

Constructor without argument.

Definition at line 179 of file int_s.hh.

10.394.2.2 template<unsigned n> mln::value::int_s< n >::int_s(int i) [inline]

Constructor from an integer.

Definition at line 192 of file int_s.hh.

10.394.2.3 template<unsigned n> mln::value::int_s< n >::int_s(const mln::literal::zero_t &) [inline]

Constructors/assignments with literals.

Definition at line 222 of file int_s.hh.

10.394.3 Member Function Documentation

10.394.3.1 template<unsigned n> mln::value::int_s< n >::operator int() const [inline]

Conversion to an integer.

Definition at line 185 of file int_s.hh.

10.394.3.2 template<unsigned n> int_s< n > & mln::value::int_s< n >::operator=(int i) [inline]

Assignment from an integer.

Definition at line 207 of file int_s.hh.

10.394.4 Member Data Documentation

10.394.4.1 template<unsigned n> const int_s< n > mln::value::int_s< n >::one = 1 [static]

Unit value.

Definition at line 149 of file int_s.hh.

10.394.4.2 template<unsigned n> const int_s< n > mln::value::int_s< n >::zero = 0 [static]

Zero value.


Definition at line 146 of file int_s.hh.

10.395 mln::value::int_u< n > Struct Template Reference

Unsigned integer value class.

```
#include <int_u.hh>
```

Inheritance diagram for mln::value::int_u< n >:



Public Member Functions

- [int_u \(\)](#)
Constructor without argument.
- [int_u \(int i\)](#)
Constructor from an integer.
- [int_u< n > next \(\) const](#)
Give the next value (i.e., $i + 1$).
- [operator unsigned \(\) const](#)
Conversion to an unsigned integer.
- [int operator- \(\) const](#)
Unary operator minus.

- `int_u< n > & operator= (int i)`
Assignment from an integer.

- `int_u (const mln::literal::zero_t &)`
Constructors/assignments with literals.

10.395.1 Detailed Description

`template<unsigned n> struct mln::value::int_u< n >`

Unsigned integer value class. The parameter is n the number of encoding bits.

Definition at line 156 of file int_u.hh.

10.395.2 Constructor & Destructor Documentation

10.395.2.1 template<unsigned n> mln::value::int_u< n >::int_u() [inline]

Constructor without argument.

Definition at line 276 of file int_u.hh.

10.395.2.2 template<unsigned n> mln::value::int_u< n >::int_u(int i) [inline]

Constructor from an integer.

Definition at line 282 of file int_u.hh.

10.395.2.3 template<unsigned n> mln::value::int_u< n >::int_u(const mln::literal::zero_t &) [inline]

Constructors/assignments with literals.

Definition at line 291 of file int_u.hh.

10.395.3 Member Function Documentation

10.395.3.1 template<unsigned n> int_u< n > mln::value::int_u< n >::next() const [inline]

Give the next value (i.e., i + 1).

Definition at line 350 of file int_u.hh.

10.395.3.2 template<unsigned n> mln::value::int_u< n >::operator unsigned() const [inline]

Conversion to an unsigned integer.

Definition at line 323 of file int_u.hh.

10.395.3.3 template<unsigned n> int mln::value::int_u< n >::operator- () const [inline]

Unary operator minus.

Definition at line 331 of file int_u.hh.

10.395.3.4 template<unsigned n> int_u< n > & mln::value::int_u< n >::operator= (int i) [inline]

Assignment from an integer.


Definition at line 339 of file int_u.hh.

10.396 mln::value::int_u_sat< n > Struct Template Reference

Unsigned integer value class with saturation behavior.

```
#include <int_u_sat.hh>
```

Inheritance diagram for mln::value::int_u_sat< n >:



Public Member Functions

- [int_u_sat \(\)](#)

Constructor without argument.

- [int_u_sat \(int i\)](#)

Constructor from an integer.

- `operator int () const`
Conversion to an integer.
- `int_u_sat< n > & operator+= (int i)`
Self addition.
- `int_u_sat< n > & operator-= (int i)`
Self subtraction.
- `int_u_sat< n > & operator=(int i)`
Assignment from an integer.

Static Public Attributes

- `static const int_u_sat< n > one = 1`
Unit value.
- `static const int_u_sat< n > zero = 0`
Zero value.

10.396.1 Detailed Description

`template<unsigned n> struct mln::value::int_u_sat< n >`

Unsigned integer value class with saturation behavior. The parameter is n the number of encoding bits.

Definition at line 90 of file int_u_sat.hh.

10.396.2 Constructor & Destructor Documentation

10.396.2.1 `template<unsigned n> mln::value::int_u_sat< n >::int_u_sat () [inline]`

Constructor without argument.

Definition at line 149 of file int_u_sat.hh.

10.396.2.2 `template<unsigned n> mln::value::int_u_sat< n >::int_u_sat (int i) [inline]`

Constructor from an integer.

Definition at line 155 of file int_u_sat.hh.

10.396.3 Member Function Documentation

10.396.3.1 `template<unsigned n> mln::value::int_u_sat< n >::operator int () const [inline]`

Conversion to an integer.

Definition at line 170 of file int_u_sat.hh.

10.396.3.2 template<unsigned n> int_u_sat< n > & mln::value::int_u_sat< n >::operator+= (int i) [inline]

Self addition.

Definition at line 195 of file int_u_sat.hh.

10.396.3.3 template<unsigned n> int_u_sat< n > & mln::value::int_u_sat< n >::operator-= (int i) [inline]

Self subtraction.

Definition at line 205 of file int_u_sat.hh.

10.396.3.4 template<unsigned n> int_u_sat< n > & mln::value::int_u_sat< n >::operator= (int i) [inline]

Assignment from an integer.

Definition at line 178 of file int_u_sat.hh.

10.396.4 Member Data Documentation

10.396.4.1 template<unsigned n> const int_u_sat< n > mln::value::int_u_sat< n >::one = 1 [static]

Unit value.

Definition at line 115 of file int_u_sat.hh.

10.396.4.2 template<unsigned n> const int_u_sat< n > mln::value::int_u_sat< n >::zero = 0 [static]

Zero value.


Definition at line 112 of file int_u_sat.hh.

10.397 mln::value::Integer< E > Struct Template Reference

Concept of integer.

```
#include <integer.hh>
```

Inheritance diagram for `mln::value::Integer< E >`:



10.397.1 Detailed Description

`template<typename E> struct mln::value::Integer< E >`

Concept of integer.

Definition at line 58 of file concept/integer.hh.

10.398 mln::value::Integer< void > Struct Template Reference

Category flag type.

```
#include <integer.hh>
```

10.398.1 Detailed Description

`template<> struct mln::value::Integer< void >`

Category flag type.

Definition at line 50 of file concept/integer.hh.

10.399 mln::value::label< n > Struct Template Reference

Label value class.

```
#include <label.hh>
```

Inherits `mln::value::Symbolic< label< n > >`, and `mln::value::internal::value_like_< unsigned,internal::encoding_unsigned_< n >::ret,int,label< n > >`.

Public Types

- `typedef internal::encoding_unsigned_< n >::ret enc`
Encoding associated type.

Public Member Functions

- `label ()`

Constructor without argument.

- `label (unsigned i)`

Constructor from an (unsigned) integer.

- `label (const literal::zero_t &v)`

Constructor from `literal::zero`.

- `label< n > next () const`

Return the next value.

- `operator unsigned () const`

Conversion to an unsigned integer.

- `label< n > & operator++ ()`

Self increment.

- `label< n > & operator-- ()`

Self decrement.

- `label< n > & operator= (unsigned i)`

Assignment from an (unsigned) integer.

- `label< n > & operator= (const literal::zero_t &v)`

Assignment from `literal::zero`.

- `label< n > prev () const`

Return the previous value.

10.399.1 Detailed Description

`template<unsigned n> struct mln::value::label< n >`

Label value class. The parameter `n` is the number of encoding bits.

Definition at line 140 of file `label.hh`.

10.399.2 Member Typedef Documentation

10.399.2.1 `template<unsigned n> typedef internal::encoding_unsigned_<n>::ret mln::value::label< n >::enc`

Encoding associated type.

Definition at line 150 of file `label.hh`.

10.399.3 Constructor & Destructor Documentation

10.399.3.1 template<unsigned n> mln::value::label<n>::label() [inline]

Constructor without argument.

Definition at line 271 of file label.hh.

10.399.3.2 template<unsigned n> mln::value::label<n>::label(unsigned i) [inline]

Constructor from an (unsigned) integer.

Definition at line 277 of file label.hh.

10.399.3.3 template<unsigned n> mln::value::label<n>::label(const literal::zero_t & v) [inline]

Constructor from [literal::zero](#).

Definition at line 284 of file label.hh.

10.399.4 Member Function Documentation

10.399.4.1 template<unsigned n> label<n> mln::value::label<n>::next() const [inline]

Return the next value.

Definition at line 338 of file label.hh.

10.399.4.2 template<unsigned n> mln::value::label<n>::operator unsigned() const [inline]

Conversion to an unsigned integer.

Definition at line 291 of file label.hh.

10.399.4.3 template<unsigned n> label<n> & mln::value::label<n>::operator++() [inline]

Self increment.

Definition at line 318 of file label.hh.

10.399.4.4 template<unsigned n> label<n> & mln::value::label<n>::operator--() [inline]

Self decrement.

Definition at line 328 of file label.hh.

10.399.4.5 template<unsigned n> label< n > & mln::value::label< n >::operator= (unsigned i) [inline]

Assignment from an (unsigned) integer.

Definition at line 299 of file label.hh.

10.399.4.6 template<unsigned n> label< n > & mln::value::label< n >::operator= (const literal::zero_t & v) [inline]

Assignment from [literal::zero](#).

Definition at line 309 of file label.hh.

10.399.4.7 template<unsigned n> label< n > mln::value::label< n >::prev () const [inline]

Return the previous value.


Definition at line 346 of file label.hh.

10.400 mln::value::lut_vec< S, T > Struct Template Reference

Class that defines [FIXME](#).

```
#include <lut_vec.hh>
```

Inheritance diagram for `mln::value::lut_vec< S, T >`:



Public Types

- `typedef bkd_viter_< lut_vec< S, T > > bkd_viter`
Backward [Value_Iterator](#) associated type.
- `typedef fwd_viter_< lut_vec< S, T > > fwd_viter`
Forward [Value_Iterator](#) associated type.
- `typedef T value`
[Value](#) associated type.

Public Member Functions

- `bool has (const value &v) const`
Test if v belongs to this set.
- `unsigned index_of (const value &v) const`
Give the index of value v in this set.
- `unsigned nvalues () const`

Give the number of values.

- `T operator[] (unsigned i) const`

Give the i -th value.

- `template<typename F >`
`lut_vec (const S &vset, const Function_v2v< F > &f)`

Constructors

Constructor from a value set and any Function_v2v.

- `template<typename V >`

`lut_vec (const S &vset, const Function_v2v< fun::i2v::array< V > > &f)`

Constructor from a value set and any fun::i2v::array.

- `template<typename V >`

`lut_vec (const S &vset, const Function_v2v< util::array< V > > &f)`

Constructor from a value set and any util::array.

10.400.1 Detailed Description

`template<typename S, typename T> struct mln::value::lut_vec< S, T >`

Class that defines FIXME.

Warning

This is a multi-set!!! FIXME

Definition at line 71 of file lut_vec.hh.

10.400.2 Member Typedef Documentation

10.400.2.1 template<typename S , typename T > typedef bkd_viter_< lut_vec<S,T> >
`mln::value::lut_vec< S, T >::bkd_viter`

Backward [Value_Iterator](#) associated type.

Definition at line 80 of file lut_vec.hh.

10.400.2.2 template<typename S , typename T > typedef fwd_viter_< lut_vec<S,T> >
`mln::value::lut_vec< S, T >::fwd_viter`

Forward [Value_Iterator](#) associated type.

Definition at line 77 of file lut_vec.hh.

10.400.2.3 template<typename S , typename T > typedef T mln::value::lut_vec< S, T >::value

[Value](#) associated type.

Definition at line 74 of file lut_vec.hh.

10.400.3 Constructor & Destructor Documentation

10.400.3.1 template<typename S , typename T > template<typename F > mln::value::lut_vec< S, T >::lut_vec (const S & vset, const Function_v2v< F > & f) [inline]

Constructors

Constructor from a value set and any [Function_v2v](#).

Definition at line 148 of file lut_vec.hh.

10.400.3.2 template<typename S , typename T > template<typename V > mln::value::lut_vec< S, T >::lut_vec (const S & vset, const Function_v2v< fun::i2v::array< V > > & f) [inline]

Constructor from a value set and any [fun::i2v::array](#).

Definition at line 161 of file lut_vec.hh.

10.400.3.3 template<typename S , typename T > template<typename V > mln::value::lut_vec< S, T >::lut_vec (const S & vset, const Function_v2v< util::array< V > > & f) [inline]

Constructor from a value set and any [util::array](#).

Definition at line 172 of file lut_vec.hh.

References [mln::util::array< T >::size\(\)](#), and [mln::util::array< T >::std_vector\(\)](#).

10.400.4 Member Function Documentation

10.400.4.1 template<typename S , typename T > bool mln::value::lut_vec< S, T >::has (const value & v) const

Test if v belongs to this set.

10.400.4.2 template<typename S , typename T > unsigned mln::value::lut_vec< S, T >::index_of (const value & v) const

Give the index of value v in this set.

10.400.4.3 template<typename S , typename T > unsigned mln::value::lut_vec< S, T >::nvalues () const [inline]

Give the number of values.

Definition at line 202 of file lut_vec.hh.

Referenced by [mln::value::lut_vec< S, T >::operator\[\]\(\)](#).

10.400.4.4 template<typename S , typename T > T mln::value::lut_vec< S, T >::operator[] (unsigned i) const [inline]

Give the i -th value.

Definition at line 193 of file lut_vec.hh.


References mln::value::lut_vec< S, T >::nvalues().

10.401 mln::value::proxy< I > Class Template Reference

Generic proxy class for an image pixel value.

```
#include <proxy.hh>
```

Inheritance diagram for mln::value::proxy< I >:



Public Types

- **typedef void enc**
Encoding associated type.
- **typedef I::value equiv**
Equivalent associated type.

Public Member Functions

- `proxy< I > & operator=(const proxy< I > &rhs)`
Assignment (write access); replacement for default op.
- `template<typename J >`
`proxy< I > & operator=(const proxy< J > &rhs)`
Assignment (write access); with other proxy.
- `proxy()`
Constructor.
- `proxy(I &ima, const typename I::psite &p)`
Constructor.
- `I::value to_value() const`
Explicit read access.
- `~proxy()`
Destructor.

10.401.1 Detailed Description

`template<typename I> class mln::value::proxy< I >`

Generic proxy class for an image pixel value. The parameter `I` is an image type.

Definition at line 85 of file `value/proxy.hh`.

10.401.2 Member Typedef Documentation

10.401.2.1 template<typename I> typedef void mln::value::proxy< I >::enc

Encoding associated type.

Definition at line 91 of file `value/proxy.hh`.

10.401.2.2 template<typename I> typedef I ::value mln::value::proxy< I >::equiv

Equivalent associated type.

Definition at line 94 of file `value/proxy.hh`.

10.401.3 Constructor & Destructor Documentation

10.401.3.1 template<typename I> mln::value::proxy< I >::proxy() [inline]

Constructor.

Definition at line 150 of file `value/proxy.hh`.

10.401.3.2 template<typename I> mln::value::proxy< I >::proxy (I & *ima*, const typename I::psite & *p*) [inline]

Constructor.

Definition at line 157 of file value/proxy.hh.

10.401.3.3 template<typename I> mln::value::proxy< I >::~proxy () [inline]

Destructor.

Definition at line 165 of file value/proxy.hh.

10.401.4 Member Function Documentation**10.401.4.1 template<typename I> proxy< I > & mln::value::proxy< I >::operator= (const proxy< I > & *rhs*) [inline]**

Assignment (write access); replacement for default op.

Definition at line 186 of file value/proxy.hh.

References mln::value::proxy< I >::to_value().

10.401.4.2 template<typename I> template<typename J> proxy< I > & mln::value::proxy< I >::operator= (const proxy< J > & *rhs*) [inline]

Assignment (write access); with other proxy.

Definition at line 199 of file value/proxy.hh.

References mln::value::proxy< I >::to_value().

10.401.4.3 template<typename I> I::value mln::value::proxy< I >::to_value () const [inline]

Explicit read access.

Definition at line 226 of file value/proxy.hh.

Referenced by mln::value::proxy< I >::operator=().

10.402 mln::value::qt::rgb32 Struct Reference

Color class for red-green-blue where every component is n-bit encoded.

```
#include <rgb32.hh>
```

Inherits mln::value::Vectorial< rgb32 >, and mln::value::internal::value_like_< algebra::vec< 3, int_u< 8 >,algebra::vec< 3, int_u< 8 >,algebra::vec< 3, int >,rgb32 >.

Public Member Functions

- [rgb32 & operator= \(const rgb32 &rhs\)](#)

Assignment.

- `rgb32` (const algebra::vec< 3, int > &rhs)

Constructor from a algebra::vec.

- `rgb32` (int r, int g, int b)

Constructor from component values.

- `rgb32` ()

Constructor without argument.

- `int_u< 8 > red` () const

Access to red/green/blue component.

- `rgb32` (const mln::literal::zero_t &)

Constructors with literals.

Static Public Attributes

- static const `rgb32 zero`

Zero value.

10.402.1 Detailed Description

Color class for red-green-blue where every component is n-bit encoded.

Definition at line 197 of file rgb32.hh.

10.402.2 Constructor & Destructor Documentation

10.402.2.1 mln::value::qt::rgb32::rgb32() [inline]

Constructor without argument.

Definition at line 385 of file rgb32.hh.

10.402.2.2 mln::value::qt::rgb32::rgb32(int r, int g, int b) [inline]

Constructor from component values.

Definition at line 427 of file rgb32.hh.

10.402.2.3 mln::value::qt::rgb32::rgb32(const algebra::vec< 3, int > & rhs) [inline]

Constructor from a algebra::vec.

Definition at line 391 of file rgb32.hh.

10.402.2.4 mln::value::qt::rgb32::rgb32 (const mln::literal::zero_t &) [inline]

Constructors with literals.

Definition at line 442 of file rgb32.hh.

10.402.3 Member Function Documentation**10.402.3.1 rgb32 & mln::value::qt::rgb32::operator= (const rgb32 & rhs) [inline]**

Assignment.

Definition at line 623 of file rgb32.hh.

10.402.3.2 int_u<8> mln::value::qt::rgb32::red () const [inline]

Access to red/green/blue component.

Definition at line 212 of file rgb32.hh.

10.402.4 Member Data Documentation**10.402.4.1 const rgb32 mln::value::qt::rgb32::zero [static]**

Zero value.

Definition at line 272 of file rgb32.hh.

10.403 mln::value::rgb< n > Struct Template Reference

Color class for red-green-blue where every component is n-bit encoded.

```
#include <rgb.hh>
```

Inherits mln::value::Vectorial< rgb< n > >, and mln::value::internal::value_like_< algebra::vec< 3, int - u< n > >,algebra::vec< 3, int_u< n > >,algebra::vec< 3, int >,rgb< n > >.

Public Member Functions

- **rgb< n > & operator= (const rgb< n > &rhs)**

Assignment.

- **rgb (const algebra::vec< 3, int > &rhs)**

Constructor from a algebra::vec.

- **rgb (int r, int g, int b)**

Constructor from component values.

- **rgb ()**

Constructor without argument.

- `int_u< n > red () const`
Access to red/green/blue component.

- `rgb (const mln::literal::white_t &)`
Constructors with literals.

Static Public Attributes

- `static const rgb< n > zero`
Zero value.

10.403.1 Detailed Description

`template<unsigned n> struct mln::value::rgb< n >`

Color class for red-green-blue where every component is n-bit encoded.

Definition at line 248 of file value/rgb.hh.

10.403.2 Constructor & Destructor Documentation

10.403.2.1 `template<unsigned n> mln::value::rgb< n >::rgb () [inline]`

Constructor without argument.

Definition at line 422 of file value/rgb.hh.

10.403.2.2 `template<unsigned n> mln::value::rgb< n >::rgb (int r, int g, int b) [inline]`

Constructor from component values.

Definition at line 458 of file value/rgb.hh.

10.403.2.3 `template<unsigned n> mln::value::rgb< n >::rgb (const algebra::vec< 3, int > & rhs) [inline]`

Constructor from a algebra::vec.

Definition at line 428 of file value/rgb.hh.

10.403.2.4 `template<unsigned n> mln::value::rgb< n >::rgb (const mln::literal::white_t &) [inline]`

Constructors with literals.

Definition at line 473 of file value/rgb.hh.

10.403.3 Member Function Documentation

10.403.3.1 template<unsigned n> rgb< n > & mln::value::rgb< n >::operator= (const rgb< n > & rhs) [inline]

Assignment.

Definition at line 645 of file value/rgb.hh.

10.403.3.2 template<unsigned n> int_u<n> mln::value::rgb< n >::red () const [inline]

Access to red/green/blue component.

Definition at line 264 of file value/rgb.hh.

Referenced by mln::fun::v2v::rgb8_to_rgn< n >::operator()().

10.403.4 Member Data Documentation

10.403.4.1 template<unsigned n> const rgb< n > mln::value::rgb< n >::zero [static]

Zero value.

Definition at line 322 of file value/rgb.hh.

10.404 mln::value::set< T > Struct Template Reference

Class that defines the set of values of type T.

```
#include <set.hh>
```

Inherits set_selector< T, set< T >, mln::metal::equal< mln::trait::value_< T >::quant, mln::trait::value::quant::low >::value >.

Static Public Member Functions

- static const set< T > & the ()

Return a singleton.

10.404.1 Detailed Description

template<typename T> struct mln::value::set< T >

Class that defines the set of values of type T. This is the exhaustive set of values obtainable from type T.

Definition at line 65 of file value/set.hh.

10.404.2 Member Function Documentation

10.404.2.1 template<typename T> const set<T> & mln::value::set<T>::the() [inline, static]

Return a singleton.

Definition at line 80 of file value/set.hh.

10.405 mln::value::sign Class Reference

The sign class represents the value type composed by the set (-1, 0, 1) sign value type is a subset of the int value type.

```
#include <sign.hh>
```

Inherits Integer< sign >.

Public Types

- `typedef int enc`
FIXME Are these typedefs correct?
- `typedef int equiv`
Define the equivalent type.

Public Member Functions

- `operator int () const`
Conversion to an integer.
- `sign & operator=(int i)`
Assignment from an integer.
- `sign ()`
Constructor without argument.
- `sign (int i)`
Constructor from an integer.
- `sign (const mln::literal::zero_t &)`
Constructors/assignments with literals.

Static Public Attributes

- `static const sign one = 1`
Unit value.

- static const [sign zero = 0](#)

Zero value.

10.405.1 Detailed Description

The sign class represents the value type composed by the set (-1, 0, 1) sign value type is a subset of the int value type.

Definition at line 49 of file value/sign.hh.

10.405.2 Member Typedef Documentation

10.405.2.1 [typedef int mln::value::sign::enc](#)

FIXME Are these typedefs correct?

Define the encoding type

Definition at line 55 of file value/sign.hh.

10.405.2.2 [typedef int mln::value::sign::equiv](#)

Define the equivalent type.

Definition at line 58 of file value/sign.hh.

10.405.3 Constructor & Destructor Documentation

10.405.3.1 [mln::value::sign::sign\(\) \[inline\]](#)

Constructor without argument.

Definition at line 119 of file value/sign.hh.

10.405.3.2 [mln::value::sign::sign\(int i \) \[inline\]](#)

Constructor from an integer.

Definition at line 137 of file value/sign.hh.

10.405.3.3 [mln::value::sign::sign\(const mln::literal::zero_t & \) \[inline\]](#)

Constructors/assignments with literals.

Definition at line 155 of file value/sign.hh.

10.405.4 Member Function Documentation

10.405.4.1 `mln::value::sign::operator int () const [inline]`

Conversion to an integer.

Definition at line 124 of file value/sign.hh.

10.405.4.2 `sign & mln::value::sign::operator=(int i) [inline]`

Assignment from an integer.

Definition at line 146 of file value/sign.hh.

10.405.5 Member Data Documentation

10.405.5.1 `const sign mln::value::sign::one = 1 [static]`

Unit value.

Definition at line 88 of file value/sign.hh.

10.405.5.2 `const sign mln::value::sign::zero = 0 [static]`

Zero value.

Definition at line 85 of file value/sign.hh.

10.406 `mln::value::stack_image< n, I >` Struct Template Reference

Stack image class.

```
#include <stack.hh>
```

Inherits `image_value_morpher< I, algebra::vec< n, I::value >, stack_image< n, I > >`.

Public Types

- `typedef I::domain_t domain_t`
Site_Set associated type.
- `typedef internal::helper_stack_image_lvalue_< n, I >::ret lvalue`
Return type of read-write access.
- `typedef I::psite psite`
Point_Site associated type.
- `typedef value rvalue`
Return type of read-only access.
- `typedef stack_image< n, tag::image_< I > > skeleton`

Skeleton.

- `typedef algebra::vec< n, typename I::value > value`
Value associated type.

Public Member Functions

- `bool is_valid () const`
Test if this image has been initialized.
- `lvalue operator() (const psite &)`
Read-write access of pixel value at point site p.
- `rvalue operator() (const psite &p) const`
Read-only access of pixel value at point site p.
- `stack_image (const algebra::vec< n, I > &imas)`
Constructors.

10.406.1 Detailed Description

`template<unsigned n, typename I> struct mln::value::stack_image< n, I >`

Stack image class. `mln::value::stack_image` stores a vector of n images of the same domain.

The parameter n is the number of images, I is the type of a stack element. Acces a value will compute a vector which contains n coordinates : [stack[0](p), stack[1](p), ... , stack[n](p)]

Definition at line 145 of file stack.hh.

10.406.2 Member Typedef Documentation

10.406.2.1 `template<unsigned n, typename I> typedef I ::domain_t mln::value::stack_image< n, I >::domain_t`

`Site_Set` associated type.

Definition at line 154 of file stack.hh.

10.406.2.2 `template<unsigned n, typename I> typedef internal::helper_-stack_image_lvalue_-<n,I>::ret mln::value::stack_image< n, I >::lvalue`

Return type of read-write access.

Definition at line 166 of file stack.hh.

10.406.2.3 template<unsigned n, typename I> typedef I ::psite mln::value::stack_image< n, I >::psite

[Point_Site](#) associated type.

Definition at line 151 of file stack.hh.

10.406.2.4 template<unsigned n, typename I> typedef value mln::value::stack_image< n, I >::rvalue

Return type of read-only access.

The rvalue type is not a const reference, since the value type is built on the fly, and return by value (copy).

Definition at line 163 of file stack.hh.

10.406.2.5 template<unsigned n, typename I> typedef stack_image< n, tag::image_<I> > mln::value::stack_image< n, I >::skeleton

Skeleton.

Definition at line 170 of file stack.hh.

10.406.2.6 template<unsigned n, typename I> typedef algebra::vec<n, typename I ::value> mln::value::stack_image< n, I >::value

[Value](#) associated type.

Definition at line 157 of file stack.hh.

10.406.3 Constructor & Destructor Documentation

10.406.3.1 template<unsigned n, typename I> mln::value::stack_image< n, I >::stack_image (const algebra::vec< n, I > & imas) [inline]

Constructors.

Definition at line 236 of file stack.hh.

10.406.4 Member Function Documentation

10.406.4.1 template<unsigned n, typename I> bool mln::value::stack_image< n, I >::is_valid () const [inline]

Test if this image has been initialized.

Definition at line 255 of file stack.hh.

10.406.4.2 template<unsigned n, typename I> stack_image< n, I >::lvalue mln::value::stack_image< n, I >::operator() (const psite & p) [inline]

Read-write access of pixel value at point site p.

Definition at line 296 of file stack.hh.

```
10.406.4.3 template<unsigned n, typename I> stack_image<n, I>::rvalue
mln::value::stack_image<n, I>::operator() (const psite & p) const [inline]
```

Read-only access of pixel value at point site p.

Definition at line 277 of file stack.hh.

10.407 mln::value::super_value< sign > Struct Template Reference

Specializations:

```
#include <super_value.hh>
```

10.407.1 Detailed Description

```
template<> struct mln::value::super_value< sign >
```

Specializations: Sign type is a subset of the short value type.

Definition at line 56 of file super_value.hh.

10.408 mln::value::value_array< T, V > Struct Template Reference

Generic array class over indexed by a value set with type T.

```
#include <value_array.hh>
```

Public Member Functions

- const V & **operator()** (const T &v) const
 - }
- const V & **operator[]** (unsigned i) const
 - }
- **value_array ()**

Constructors.
- const mln::value::set< T > & **vset ()** const
 - }

10.408.1 Detailed Description

```
template<typename T, typename V> struct mln::value::value_array< T, V >
```

Generic array class over indexed by a value set with type T.

Definition at line 45 of file value_array.hh.

10.408.2 Constructor & Destructor Documentation

10.408.2.1 template<typename T , typename V > mln::value::value_array< T,V >::value_array() [inline]

Constructors.

{

Definition at line 89 of file value_array.hh.

10.408.3 Member Function Documentation

10.408.3.1 template<typename T , typename V > const V & mln::value::value_array< T,V >::operator()(const T & v) const [inline]

}

Access elements through a value of T. {

Definition at line 128 of file value_array.hh.

10.408.3.2 template<typename T , typename V > const V & mln::value::value_array< T,V >::operator[](unsigned i) const [inline]

}

Access elements through array indexes. {

Definition at line 152 of file value_array.hh.

10.408.3.3 template<typename T , typename V > const mln::value::set< T > & mln::value::value_array< T,V >::vset() const [inline]

}

Reference to the set of T.


Definition at line 144 of file value_array.hh.

10.409 mln::Value_Iterator< E > Struct Template Reference

Base class for implementation of classes of iterator on values.

```
#include <value_iterator.hh>
```

Inheritance diagram for mln::Value_Iterator< E >:



Public Member Functions

- `void next ()`
Go to the next element.

Related Functions

(Note that these are not member functions.)

- `template<typename E>`
`std::ostream & operator<< (std::ostream & ostr, const Value_Iterator< E > & v)`
Print an iterator v on value set into the output stream ostr.

10.409.1 Detailed Description

`template<typename E> struct mln::Value_Iterator< E >`

Base class for implementation of classes of iterator on values. An iterator on values is an iterator that browse over a set of values.

See also

[mln::doc::Value_Iterator](#) for a complete documentation of this class contents.

Definition at line 50 of file `value_iterator.hh`.

10.409.2 Member Function Documentation

10.409.2.1 template<typename E > void mln::Iterator< E >::next() [inherited]

Go to the next element.

Warning

This is a final method; iterator classes should not re-defined this method. The actual "next" operation has to be defined through the *next_* method.

Precondition

The iterator is valid.

Definition at line 102 of file iterator.hh.

10.409.3 Friends And Related Function Documentation

10.409.3.1 template<typename E > std::ostream & operator<< (std::ostream & ostr, const Value_Iterator< E > & v) [related]

Print an iterator *v* on value set into the output stream *ostr*.

Parameters

[in, out] *ostr* An output stream.

[in] *v* An iterator on value set.

Precondition

v is a valid.

Returns

The modified output stream *ostr*.


Definition at line 92 of file value_iterator.hh.

10.410 mln::Value_Set< E > Struct Template Reference

Base class for implementation classes of sets of values.

```
#include <value_set.hh>
```

Inheritance diagram for mln::Value_Set< E >:



10.410.1 Detailed Description

template<typename E> struct mln::Value_Set< E >

Base class for implementation classes of sets of values.

See also

[mln::doc::Value_Set](#) for a complete documentation of this class contents.

Definition at line 57 of file value_set.hh.

10.411 mln::Vertex< E > Struct Template Reference

[Vertex](#) category flag type.

```
#include <vertex.hh>
```

10.411.1 Detailed Description

template<typename E> struct mln::Vertex< E >

[Vertex](#) category flag type.

Definition at line 53 of file vertex.hh.

10.412 mln::vertex_image< P, V, G > Class Template Reference

[Image](#) based on graph vertices.

```
#include <vertex_image.hh>
```

Inherits `image_base< fun::i2v::array< V >, p_vertices< G, internal::vfsite_selector< P, G >::site_function_t >, vertex_image< P, V, G > >`.

Public Types

- `typedef G graph_t`

The type of the underlying graph.

- `typedef vertex_nbh_t nbh_t`

Neighborhood type.

- `typedef internal::vfsite_selector< P, G >::site_function_t site_function_t`

Function mapping graph elements to sites.

- `typedef vertex_image< tag::psite_< P >, tag::value_< V >, tag::graph_< G > > skeleton`

Skeleton type.

- `typedef graph_elt_neighborhood< G, S > vertex_nbh_t`

Vertex Neighborhood type.

- `typedef graph_elt_window< G, S > vertex_win_t`

Vertex Window type.

- `typedef vertex_win_t win_t`

Window type.

Public Member Functions

- `vertex_image()`

Constructors.

- `rvalue operator()(unsigned v_id) const`

Value accessors/operators overloads.

10.412.1 Detailed Description

`template<typename P, typename V, typename G = util::graph> class mln::vertex_image< P, V, G >`

[Image](#) based on graph vertices.

Definition at line 126 of file core/image/vertex_image.hh.

10.412.2 Member Typedef Documentation

**10.412.2.1 `template<typename P, typename V, typename G = util::graph> typedef G
mln::vertex_image< P, V, G >::graph_t`**

The type of the underlying graph.

Definition at line 141 of file core/image/vertex_image.hh.

**10.412.2.2 `template<typename P, typename V, typename G = util::graph> typedef vertex_nbh_t
mln::vertex_image< P, V, G >::nbh_t`**

[Neighborhood](#) type.

Definition at line 165 of file core/image/vertex_image.hh.

**10.412.2.3 `template<typename P, typename V, typename G = util::graph> typedef
internal::vbsite_selector<P,G>::site_function_t mln::vertex_image< P, V, G
>::site_function_t`**

Function mapping graph elements to sites.

Definition at line 145 of file core/image/vertex_image.hh.

**10.412.2.4 `template<typename P, typename V, typename G = util::graph> typedef vertex_image<
tag::psite_<P>, tag::value_<V>, tag::graph_<G>> mln::vertex_image< P, V, G
>::skeleton`**

Skeleton type.

Definition at line 152 of file core/image/vertex_image.hh.

**10.412.2.5 `template<typename P, typename V, typename G = util::graph> typedef
graph_elt_neighborhood<G,S> mln::vertex_image< P, V, G >::vertex_nbh_t`**

[Vertex Neighborhood](#) type.

Definition at line 160 of file core/image/vertex_image.hh.

**10.412.2.6 `template<typename P, typename V, typename G = util::graph> typedef
graph_elt_window<G,S> mln::vertex_image< P, V, G >::vertex_win_t`**

[Vertex Window](#) type.

Definition at line 157 of file core/image/vertex_image.hh.

**10.412.2.7 template<typename P, typename V, typename G = util::graph> typedef vertex_win_t
mln::vertex_image< P, V, G >::win_t**

Window type.

Definition at line 163 of file core/image/vertex_image.hh.

10.412.3 Constructor & Destructor Documentation

10.412.3.1 template<typename P , typename V , typename G > mln::vertex_image< P, V, G >::vertex_image() [inline]

Constructors.

Definition at line 247 of file core/image/vertex_image.hh.

10.412.4 Member Function Documentation

**10.412.4.1 template<typename P , typename V , typename G > vertex_image< P, V, G >::rvalue
mln::vertex_image< P, V, G >::operator() (unsigned v_id) const**

Value accessors/operators overloads.

Definition at line 292 of file core/image/vertex_image.hh.

10.413 mln::violent_cast_image< T, I > Struct Template Reference

Violently cast image values to a given type.

```
#include <violent_cast_image.hh>
```

Inherits image_value_morpher< I, T, violent_cast_image< T, I > >.

Public Types

- **typedef T lvalue**

Return type of read-write access.

- **typedef T rvalue**

Return type of read-only access.

- **typedef violent_cast_image< tag::value_< T >, tag::image_< I > > skeleton**

Skeleton.

- **typedef T value**

Value associated type.

Public Member Functions

- `T operator()` (const typename `I::psite` &`p`) const
Read-only access of pixel value at point site `p`.
- `T operator()` (const typename `I::psite` &`p`)
Mutable access is only OK for reading (not writing).
- `violent_cast_image` (const `Image< I >` &`ima`)
Constructor.

10.413.1 Detailed Description

`template<typename T, typename I> struct mln::violent_cast_image< T, I >`

Violently cast image values to a given type.

Definition at line 112 of file `violent_cast_image.hh`.

10.413.2 Member Typedef Documentation

10.413.2.1 `template<typename T, typename I> typedef T mln::violent_cast_image< T, I >::lvalue`

Return type of read-write access.

Definition at line 122 of file `violent_cast_image.hh`.

10.413.2.2 `template<typename T, typename I> typedef T mln::violent_cast_image< T, I >::rvalue`

Return type of read-only access.

Definition at line 119 of file `violent_cast_image.hh`.

10.413.2.3 `template<typename T, typename I> typedef violent_cast_image< tag::value_< T >, tag::image_< I > > mln::violent_cast_image< T, I >::skeleton`

Skeleton.

Definition at line 125 of file `violent_cast_image.hh`.

10.413.2.4 `template<typename T, typename I> typedef T mln::violent_cast_image< T, I >::value`

`Value` associated type.

Definition at line 116 of file `violent_cast_image.hh`.

10.413.3 Constructor & Destructor Documentation

10.413.3.1 template<typename T , typename I > mln::violent_cast_image< T, I >::violent_cast_image (const Image< I > & *ima*) [inline]

Constructor.

Definition at line 172 of file violent_cast_image.hh.

10.413.4 Member Function Documentation

10.413.4.1 template<typename T , typename I > T mln::violent_cast_image< T, I >::operator() (const typename I::psite & *p*) const [inline]

Read-only access of pixel value at point site *p*.

Definition at line 191 of file violent_cast_image.hh.

10.413.4.2 template<typename T , typename I > T mln::violent_cast_image< T, I >::operator() (const typename I::psite & *p*) [inline]

Mutable access is only OK for reading (not writing).

Definition at line 200 of file violent_cast_image.hh.

10.414 mln::w_window< D, W > Struct Template Reference

Generic [w_window](#) class.

```
#include <w_window.hh>
```

Inherits [weighted_window_base< mln::window< D >, w_window< D, W > >](#).

Public Types

- **typedef with_w_< dpsites_bkd_piter< [w_window](#)< D, W > >, W > [bkd_qiter](#)**
Site_Iterator type to browse (backward) the points of a generic [w_window](#).
- **typedef D [dpsite](#)**
Dpsite associated type.
- **typedef with_w_< dpsites_fwd_piter< [w_window](#)< D, W > >, W > [fwd_qiter](#)**
Site_Iterator type to browse (forward) the points of a generic [w_window](#).
- **typedef W [weight](#)**
Weight associated type.

Public Member Functions

- **void [clear](#) ()**

Clear this window.

- `w_window< D, W > & insert (const W &w, const D &d)`

Insert a couple of weight w and delta-point d.

- `bool is_symmetric () const`

Test if the window is symmetric.

- `const std::vector< D > & std_vector () const`

Give access to the vector of delta-points.

- `void sym ()`

Apply a central symmetry to the window.

- `W w (unsigned i) const`

Give the i-th weight.

- `w_window ()`

Constructor without argument.

- `const std::vector< W > & weights () const`

Give access to the vector of weights.

- `const mln::window< D > & win () const`

Give the corresponding window.

Related Functions

(Note that these are not member functions.)

- `template<typename D , typename W >
std::ostream & operator<< (std::ostream &ostr, const w_window< D, W > &w_win)`

Print a weighted window w_win into an output stream ostr.

- `template<typename D , typename Wl , typename Wr >
bool operator== (const w_window< D, Wl > &lhs, const w_window< D, Wr > &rhs)`

Equality test between two weighted windows lhs and rhs.

10.414.1 Detailed Description

`template<typename D, typename W> struct mln::w_window< D, W >`

Generic `w_window` class. This type of `w_window` is just like a set of delta-points. The parameter `D` is the type of delta-points; the parameter `W` is the type of weights.

Definition at line 100 of file core/w_window.hh.

10.414.2 Member Typedef Documentation

10.414.2.1 template<typename D, typename W> typedef with_w_< dpsites_bkd_piter< w_window<D, W>, W > mln::w_window< D, W >::bkd_qiter

[Site_Iterator](#) type to browse (backward) the points of a generic [w_window](#).

Definition at line 114 of file core/w_window.hh.

10.414.2.2 template<typename D, typename W> typedef D mln::w_window< D, W >::dpsite

Dpsite associated type.

Definition at line 104 of file core/w_window.hh.

10.414.2.3 template<typename D, typename W> typedef with_w_< dpsites_fwd_piter< w_window<D, W>, W > mln::w_window< D, W >::fwd_qiter

[Site_Iterator](#) type to browse (forward) the points of a generic [w_window](#).

Definition at line 111 of file core/w_window.hh.

10.414.2.4 template<typename D, typename W> typedef W mln::w_window< D, W >::weight

Weight associated type.

Definition at line 107 of file core/w_window.hh.

10.414.3 Constructor & Destructor Documentation

10.414.3.1 template<typename D , typename W > mln::w_window< D, W >::w_window() [inline]

Constructor without argument.

Definition at line 213 of file core/w_window.hh.

10.414.4 Member Function Documentation

10.414.4.1 template<typename D , typename W > void mln::w_window< D, W >::clear() [inline]

Clear this window.

Definition at line 308 of file core/w_window.hh.

10.414.4.2 template<typename D , typename W > w_window< D, W > & mln::w_window< D, W >::insert(const W & w, const D & d) [inline]

Insert a couple of weight w and delta-point d.

Definition at line 254 of file core/w_window.hh.

Referenced by mln::w_window< D, W >::sym(), mln::make::w_window(), mln::make::w_window1d(), mln::make::w_window3d(), and mln::make::w_window_directional().

10.414.4.3 template<typename D , typename W > bool mln::w_window< D, W >::is_symmetric () const [inline]

Test if the window is symmetric.

Definition at line 284 of file core/w_window.hh.

References mln::w_window< D, W >::sym().

10.414.4.4 template<typename D , typename W > const std::vector< D > & mln::w_window< D, W >::std_vector () const [inline]

Give access to the vector of delta-points.

Definition at line 228 of file core/w_window.hh.

10.414.4.5 template<typename D , typename W > void mln::w_window< D, W >::sym () [inline]

Apply a central symmetry to the window.

Definition at line 296 of file core/w_window.hh.

References mln::w_window< D, W >::insert().

Referenced by mln::w_window< D, W >::is_symmetric().

10.414.4.6 template<typename D , typename W > W mln::w_window< D, W >::w (unsigned i) const [inline]

Give the *i*-th weight.

Definition at line 244 of file core/w_window.hh.

10.414.4.7 template<typename D , typename W > const std::vector< W > & mln::w_window< D, W >::weights () const [inline]

Give access to the vector of weights.

Definition at line 236 of file core/w_window.hh.

Referenced by mln::w_window< D, W >::operator==().

10.414.4.8 template<typename D , typename W > const mln::window< D > & mln::w_window< D, W >::win () const [inline]

Give the corresponding window.

Definition at line 220 of file core/w_window.hh.

Referenced by mln::w_window< D, W >::operator==().

10.414.5 Friends And Related Function Documentation

10.414.5.1 template<typename D , typename W > std::ostream & operator<< (std::ostream & ostr, const w_window< D, W > & w_win) [related]

Print a weighted window `w_win` into an output stream `ostr`.

Definition at line 420 of file core/w_window.hh.

10.414.5.2 template<typename D , typename Wl , typename Wr > bool operator== (const w_window< D, Wl > & lhs, const w_window< D, Wr > & rhs) [related]

Equality test between two weighted windows `lhs` and `rhs`.

Definition at line 430 of file core/w_window.hh.


References `mln::w_window< D, W >::weights()`, and `mln::w_window< D, W >::win()`.

10.415 mln::Weighted_Window< E > Struct Template Reference

Base class for implementation classes that are `weighted_windows`.

```
#include <weighted_window.hh>
```

Inheritance diagram for `mln::Weighted_Window< E >`:



Related Functions

(Note that these are not member functions.)

- template<typename W >
W **operator-** (const [Weighted_Window< W >](#) &rhs)

Compute the symmetrical weighted window of rhs.

10.415.1 Detailed Description

template<typename E> struct mln::Weighted_Window< E >

Base class for implementation classes that are weighted_windows.

See also

[mln::doc::Weighted_Window](#) for a complete documentation of this class contents.

Definition at line 68 of file weighted_window.hh.

10.415.2 Friends And Related Function Documentation

**10.415.2.1 template<typename W > W operator- (const Weighted_Window< W > & rhs)
[related]**

Compute the symmetrical weighted window of rhs.

10.416 mln::win::backdiag2d Struct Reference

Diagonal line window defined on the 2D square grid.

#include <backdiag2d.hh>

Inherits classical_window_base< dpoint2d, backdiag2d >.

Public Member Functions

- [backdiag2d](#) (unsigned length)

Constructor.

- unsigned [length](#) () const

Give the diagonal length, that is, its width.

10.416.1 Detailed Description

Diagonal line window defined on the 2D square grid. An [backdiag2d](#) is centered and symmetric. its width (length) is odd.

For instance:

```
*   o
*   o
*   x
*   o
*   o
```

is defined with length = 5.

Definition at line 63 of file backdiag2d.hh.

10.416.2 Constructor & Destructor Documentation

10.416.2.1 mln::win::backdiag2d::backdiag2d (*unsigned length*) [inline]

Constructor.

Parameters

[in] *length* Length, thus width, of the diagonal line.

Precondition

length is odd.

Definition at line 93 of file backdiag2d.hh.

10.416.3 Member Function Documentation

10.416.3.1 *unsigned mln::win::backdiag2d::length () const* [inline]

Give the diagonal length, that is, its width.

Definition at line 105 of file backdiag2d.hh.

10.417 mln::win::ball< G, C > Struct Template Reference

Generic ball window defined on a given grid.

```
#include <ball.hh>
```

Inherits classical_window_base< dpoint< G, C >, ball< G, C > >.

Public Member Functions

- **ball** (*unsigned diameter*)

Constructor.

- *unsigned diameter () const*

Give the ball diameter.

10.417.1 Detailed Description

```
template<typename G, typename C> struct mln::win::ball< G, C >
```

Generic ball window defined on a given grid. A ball is centered and symmetric; so its diameter is odd.

G is the given grid on which the ball is defined and C is the type of coordinates.

Definition at line 71 of file ball.hh.

10.417.2 Constructor & Destructor Documentation

10.417.2.1 template<typename G , typename C > mln::win::ball< G, C >::ball (`unsigned diameter`) [inline]

Constructor.

Parameters

[in] `diameter` Diameter of the ball.

Precondition

`diameter` is odd.

Definition at line 99 of file ball.hh.

References mln::literal::origin.

10.417.3 Member Function Documentation

10.417.3.1 template<typename G , typename C > `unsigned mln::win::ball< G, C >::diameter () const` [inline]

Give the ball diameter.

Definition at line 122 of file ball.hh.

10.418 mln::win::cube3d Struct Reference

Cube window defined on the 3D grid.

```
#include <cube3d.hh>
```

Inherits classical_window_base< dpoint3d, cube3d >.

Public Member Functions

- `cube3d (unsigned length)`

Constructor.

- `unsigned length () const`

Give the cube length, that is, its height.

10.418.1 Detailed Description

Cube window defined on the 3D grid. An `cube3d` is centered and symmetric; so its height (length) is odd. For instance:

```
*     o   o   o
*     o   o   o
```

```

*   o   o   o
*
*       o   o   o
*   o   x   o
*   o   o   o
*
*   o   o   o
*   o   o   o
*   o   o   o
*

```

is defined with length = 3.

Definition at line 69 of file cube3d.hh.

10.418.2 Constructor & Destructor Documentation

10.418.2.1 `mln::win::cube3d::cube3d(unsigned length) [inline]`

Constructor.

Parameters

`[in] length` Length, thus height, of the `cube3d`.

Precondition

`length` is odd.

Definition at line 99 of file cube3d.hh.

10.418.3 Member Function Documentation

10.418.3.1 `unsigned mln::win::cube3d::length() const [inline]`

Give the cube length, that is, its height.

Definition at line 113 of file cube3d.hh.

10.419 `mln::win::cuboid3d` Struct Reference

Cuboid defined on the 3-D square grid.

```
#include <cuboid3d.hh>
```

Inherits classical_window_base< dpoint3d, cuboid3d >.

Public Member Functions

- `cuboid3d` (unsigned depth, unsigned height, unsigned width)

Constructor.

- `unsigned volume()` const


Return the volume of the cuboid.

- `unsigned depth () const`
Accessors.
- `unsigned height () const`
Return the height of the cuboid.
- `unsigned width () const`
Return the width of the cuboid.

10.419.1 Detailed Description

Cuboid defined on the 3-D square grid. A `cuboid3d` is a 3-D window with cuboid (also known as rectangular prism or rectangular parallelepiped) shape. It is centered and symmetric.

For instance:



is defined with `depth = 3`, `height = 5` and `width = 7`.

Reference: <http://en.wikipedia.org/wiki/Cuboid>

Definition at line 80 of file `cuboid3d.hh`.

10.419.2 Constructor & Destructor Documentation

10.419.2.1 `mln::win::cuboid3d::cuboid3d (unsigned depth, unsigned height, unsigned width) [inline]`

Constructor.

Parameters

- [in] `depth` The depth of the `cuboid3d`.
- [in] `height` The height of the `cuboid3d`.
- [in] `width` The width of the `cuboid3d`.

Precondition

Argument `depth`, `height` and `width` must be odd.

Definition at line 125 of file cuboid3d.hh.

10.419.3 Member Function Documentation

10.419.3.1 `unsigned mln::win::cuboid3d::depth() const [inline]`

Accessors.

Return the depth of the cuboid.

Definition at line 146 of file cuboid3d.hh.

10.419.3.2 `unsigned mln::win::cuboid3d::height() const [inline]`

Return the height of the cuboid.

Definition at line 153 of file cuboid3d.hh.

10.419.3.3 `unsigned mln::win::cuboid3d::volume() const [inline]`

Return the volume of the cuboid.

Definition at line 167 of file cuboid3d.hh.

10.419.3.4 `unsigned mln::win::cuboid3d::width() const [inline]`

Return the width of the cuboid.

Definition at line 160 of file cuboid3d.hh.

10.420 `mln::win::diag2d` Struct Reference

Diagonal line window defined on the 2D square grid.

```
#include <diag2d.hh>
```

Inherits classical_window_base< dpoint2d, diag2d >.

Public Member Functions

- `diag2d (unsigned length)`
Constructor.
- `unsigned length () const`
Give the diagonal length, that is, its width.

10.420.1 Detailed Description

Diagonal line window defined on the 2D square grid. An `diag2d` is centered and symmetric. its width (`length`) is odd.

For instance:

```
*      o
*      o
*      x
*      o
*      o
*
```

is defined with length = 5.

Definition at line 63 of file diag2d.hh.

10.420.2 Constructor & Destructor Documentation

10.420.2.1 mln::win::diag2d::diag2d (unsigned *length*) [inline]

Constructor.

Parameters

[in] *length* Length, thus width, of the diagonal line.

Precondition

length is odd.

Definition at line 93 of file diag2d.hh.

10.420.3 Member Function Documentation

10.420.3.1 unsigned mln::win::diag2d::length () const [inline]

Give the diagonal length, that is, its width.

Definition at line 106 of file diag2d.hh.

10.421 mln::win::line< M, i, C > Struct Template Reference

Generic line window defined on a given grid in the given dimension.

```
#include <line.hh>
```

Inherits classical_window_base< dpoint< M, C >, line< M, i, C > >.

Public Types

- enum

Direction.

Public Member Functions

- `unsigned length () const`
Give the line length.
- `line (unsigned length)`
Constructor.
- `unsigned size () const`
Give the line size, that is, its length.

10.421.1 Detailed Description

`template<typename M, unsigned i, typename C> struct mln::win::line< M, i, C >`

Generic line window defined on a given grid in the given dimension. An line is centered and symmetric; so its length is odd.

M is the given grid on which the line is defined, i is the given dimension of the line end C is the type of the coordinates.

See also

`mln::win::hline2d` for an exemple of his use.

Definition at line 73 of file `win/line.hh`.

10.421.2 Member Enumeration Documentation

10.421.2.1 `template<typename M , unsigned i, typename C > anonymous enum`

Direction.

Definition at line 76 of file `win/line.hh`.

10.421.3 Constructor & Destructor Documentation

10.421.3.1 `template<typename M , unsigned i, typename C > mln::win::line< M, i, C >::line (unsigned length) [inline]`

Constructor.

Parameters

[in] `length` Length of the line.

Precondition

`length` is odd.

Definition at line 106 of file `win/line.hh`.

References `mln::dpoint< G, C >::set_all()`.

10.421.4 Member Function Documentation

10.421.4.1 `template<typename M , unsigned i, typename C > unsigned mln::win::line< M, i, C >::length() const [inline]`

Give the line length.

Definition at line 125 of file win/line.hh.

10.421.4.2 `template<typename M , unsigned i, typename C > unsigned mln::win::line< M, i, C >::size() const [inline]`

Give the line size, that is, its length.

Definition at line 132 of file win/line.hh.

10.422 `mln::win::multiple< W, F >` Class Template Reference

Multiple window.

```
#include <multiple.hh>
```

Inherits `window_base< W::dpsite, multiple< W, F > >`.

10.422.1 Detailed Description

`template<typename W, typename F> class mln::win::multiple< W, F >`

Multiple window.

Definition at line 76 of file multiple.hh.

10.423 `mln::win::multiple_size< n, W, F >` Class Template Reference

Definition of a multiple-size window.

```
#include <multiple_size.hh>
```

Inherits `window_base< W::dpsite, multiple_size< n, W, F > >`.

10.423.1 Detailed Description

`template<unsigned n, typename W, typename F> class mln::win::multiple_size< n, W, F >`

Definition of a multiple-size window.

Definition at line 78 of file multiple_size.hh.

10.424 mln::win::octagon2d Struct Reference

Octagon window defined on the 2D square grid.

```
#include <octagon2d.hh>
```

Inherits classical_window_base< dpoint2d, octagon2d >.

Public Member Functions

- `unsigned area () const`
Give the area.
- `unsigned length () const`
Give the octagon length, that is, its width.
- `octagon2d (unsigned length)`
Constructor.

10.424.1 Detailed Description

Octagon window defined on the 2D square grid. An `octagon2d` is centered and symmetric.

The length L of the octagon is such as $L = 6 * l + 1$ where $l \geq 0$.

For instance:

```
*      o  o  o
*      o  o  o  o  o
*  o  o  o  o  o  o
*  o  o  o  x  o  o
*  o  o  o  o  o  o
*  o  o  o  o  o
*      o  o  o
*
```

is defined with $L = 7$ ($l = 1$).

Definition at line 67 of file octagon2d.hh.

10.424.2 Constructor & Destructor Documentation

10.424.2.1 mln::win::octagon2d::octagon2d (`unsigned length`) [inline]

Constructor.

Parameters

[in] `length` Length, of the octagon.

Precondition

`length` is such as $length = 6*x + 1$ where $x \geq 0$.

Definition at line 101 of file octagon2d.hh.

10.424.3 Member Function Documentation

10.424.3.1 unsigned mln::win::octagon2d::area () const [inline]

Give the area.

Definition at line 157 of file octagon2d.hh.

10.424.3.2 unsigned mln::win::octagon2d::length () const [inline]

Give the octagon length, that is, its width.

Definition at line 145 of file octagon2d.hh.

10.425 mln::win::rectangle2d Struct Reference

Rectangular window defined on the 2D square grid.

```
#include <rectangle2d.hh>
```

Inherits classical_window_base< dpoint2d, rectangle2d >.

Public Member Functions

- unsigned [area](#) () const

Give the rectangle area.

- unsigned [height](#) () const

Give the rectangle height.

- [rectangle2d](#) (unsigned height, unsigned width)

Constructor.

- const std::vector< [dpoint2d](#) > & [std_vector](#) () const

Give the std vector of delta-points.

- unsigned [width](#) () const

Give the rectangle width.

10.425.1 Detailed Description

Rectangular window defined on the 2D square grid. A [rectangle2d](#) is a 2D window with rectangular shape. It is centered and symmetric.

For instance:

```
*   o   o   o   o   o
*   o   o   x   o   o
*   o   o   o   o   o
*
```

is defined with height = 3 and width = 5.

Definition at line 64 of file rectangle2d.hh.

10.425.2 Constructor & Destructor Documentation

10.425.2.1 `mln::win::rectangle2d::rectangle2d (unsigned height, unsigned width) [inline]`

Constructor.

Parameters

[in] `height` Height of the `rectangle2d`.

[in] `width` Width of the `rectangle2d`.

Precondition

Height and width are odd.

Definition at line 106 of file rectangle2d.hh.

10.425.3 Member Function Documentation

10.425.3.1 `unsigned mln::win::rectangle2d::area () const [inline]`

Give the rectangle area.

Definition at line 132 of file rectangle2d.hh.

10.425.3.2 `unsigned mln::win::rectangle2d::height () const [inline]`

Give the rectangle height.

Definition at line 120 of file rectangle2d.hh.

10.425.3.3 `const std::vector< dpoint2d > & mln::win::rectangle2d::std_vector () const [inline]`

Give the std vector of delta-points.

Definition at line 145 of file rectangle2d.hh.

10.425.3.4 `unsigned mln::win::rectangle2d::width () const [inline]`

Give the rectangle width.

Definition at line 126 of file rectangle2d.hh.

10.426 `mln::Window< E >` Struct Template Reference

Base class for implementation classes that are windows.

```
#include <window.hh>
```

Inheritance diagram for mln::Window< E >:



10.426.1 Detailed Description

```
template<typename E> struct mln::Window< E >
```

Base class for implementation classes that are windows.

See also

[mln::doc::Window](#) for a complete documentation of this class contents.

Definition at line 87 of file concept/window.hh.

10.427 mln::window< D > Class Template Reference

Generic window class.

```
#include <window.hh>
```

Inherits window_base< D, window< D > >.

Public Types

- `typedef dpsites_bkd_piter< window< D > > bkd_qiter`
Site_Iterator type to browse the points of a basic window w.r.t. the reverse ordering of delta-points.
 - `typedef dpsites_fwd_piter< window< D > > fwd_qiter`
Site_Iterator type to browse the points of a basic window w.r.t. the ordering of delta-points.
 - `typedef fwd_qiter qiter`
Site_Iterator type to browse the points of a basic window whatever the ordering of delta-points.
 - `typedef window< D > regular`
Regular window associated type.

Public Member Functions

- void `clear ()`

Clear the window.

- unsigned `delta () const`

Give the maximum coordinate gap between the window center and a window point.

- const D & `dp (unsigned i) const`

Give the i -th delta-point.

- bool `has (const D &dp) const`

Test if dp is in this window definition.

- `window< D > & insert (const D &dp)`

Insert a delta-point dp .

- template<typename W >

`window< D > & insert (const Window< W > &win)`

Insert another window win .

- bool `is_centered () const`

Test if the window is centered.

- bool `is_empty () const`

Test if the window is empty (null size; no delta-point).

- bool `is_symmetric () const`

- void `print (std::ostream &ostr) const`

Print the window definition into $ostr$.

- unsigned `size () const`

Give the window size, i.e., the number of delta-sites.

- const std::vector< D > & `std_vector () const`

Give the std vector of delta-points.

- void `sym ()`

Apply a central symmetry to the target window.

- `window ()`

Constructor without argument.

- `window< D > & insert (const typename D::coord &dind)`

Related Functions

(Note that these are not member functions.)

- template<typename D >
bool **operator==** (const **window**< D > &lhs, const **window**< D > &rhs)
Equality comparison between windows lhs and rhs.

10.427.1 Detailed Description

template<typename D> class mln::window< D >

Generic window class. This type of window is just like a set of delta-points. The parameter is D, type of delta-point.

Definition at line 85 of file window.hh.

10.427.2 Member Typedef Documentation

10.427.2.1 template<typename D> typedef dpsites_bkd_piter< window<D> > mln::window< D >::bkd_qiter

[Site_Iterator](#) type to browse the points of a basic window w.r.t. the reverse ordering of delta-points.

Definition at line 124 of file window.hh.

10.427.2.2 template<typename D> typedef dpsites_fwd_piter< window<D> > mln::window< D >::fwd_qiter

[Site_Iterator](#) type to browse the points of a basic window w.r.t. the ordering of delta-points.

Definition at line 119 of file window.hh.

10.427.2.3 template<typename D> typedef fwd_qiter mln::window< D >::qiter

[Site_Iterator](#) type to browse the points of a basic window whatever the ordering of delta-points.

Definition at line 129 of file window.hh.

10.427.2.4 template<typename D> typedef window<D> mln::window< D >::regular

Regular window associated type.

Definition at line 90 of file window.hh.

10.427.3 Constructor & Destructor Documentation

10.427.3.1 template<typename D > mln::window< D >::window() [inline]

Constructor without argument.

The constructed window is empty.

Definition at line 207 of file window.hh.

10.427.4 Member Function Documentation

10.427.4.1 template<typename D > void mln::window< D >::clear() [inline]

Clear the window.

Definition at line 254 of file window.hh.

10.427.4.2 template<typename D > unsigned mln::window< D >::delta() const [inline]

Give the maximum coordinate gap between the window center and a window point.

Definition at line 262 of file window.hh.

References mln::window< D >::dp(), and mln::window< D >::size().

10.427.4.3 template<typename D > const D & mln::window< D >::dp(unsigned i) const [inline]

Give the i -th delta-point.

Definition at line 302 of file window.hh.

References mln::window< D >::size().

Referenced by mln::window< D >::delta(), and mln::window< D >::insert().

10.427.4.4 template<typename D > bool mln::window< D >::has(const D & dp) const [inline]

Test if dp is in this window definition.

Definition at line 311 of file window.hh.

10.427.4.5 template<typename D > window< D > & mln::window< D >::insert(const D & dp) [inline]

Insert a delta-point dp .

Definition at line 327 of file window.hh.

Referenced by mln::c18(), mln::c26(), mln::c2_3d_sli(), mln::c4_3d(), mln::c6(), mln::window< D >::insert(), mln::morpho::line_gradient(), mln::window< D >::sym(), mln::convert::to_upper_window(), mln::convert::to_window(), mln::win_c4p(), mln::win_c4p_3d(), mln::win_c8p(), and mln::win_c8p_3d().

10.427.4.6 template<typename D > template<typename W > window< D > & mln::window< D >::insert(const Window< W > & win) [inline]

Insert another window win .

Definition at line 337 of file window.hh.

10.427.4.7 template<typename D> window< D > & mln::window< D >::insert (const typename D::coord & dind) [inline]

Insertion of a delta-point with different numbers of arguments (coordinates) w.r.t. the dimension.

Definition at line 349 of file window.hh.

References mln::window< D >::dp(), and mln::window< D >::insert().

10.427.4.8 template<typename D> bool mln::window< D >::is_centered () const [inline]

Test if the window is centered.

Returns

True if the delta-point 0 belongs to the window.

Definition at line 226 of file window.hh.

References mln::literal::zero.

10.427.4.9 template<typename D> bool mln::window< D >::is_empty () const [inline]

Test if the window is empty (null size; no delta-point).

Definition at line 246 of file window.hh.

10.427.4.10 template<typename D> bool mln::window< D >::is_symmetric () const [inline]

Test if the window is symmetric.

Returns

True if for every dp of this window, -dp is also in this window.

Definition at line 216 of file window.hh.

References mln::window< D >::sym().

10.427.4.11 template<typename D> void mln::window< D >::print (std::ostream & ostr) const [inline]

Print the window definition into ostr.

Definition at line 390 of file window.hh.

10.427.4.12 template<typename D> unsigned mln::window< D >::size () const [inline]

Give the window size, i.e., the number of delta-sites.

Definition at line 294 of file window.hh.

Referenced by mln::window< D >::delta(), mln::window< D >::dp(), mln::window< D >::sym(), mln::win_c4p(), mln::win_c4p_3d(), mln::win_c8p(), and mln::win_c8p_3d().

10.427.4.13 template<typename D > const std::vector< D > & mln::window< D >::std_vector() const [inline]

Give the std vector of delta-points.

Definition at line 319 of file window.hh.

10.427.4.14 template<typename D > void mln::window< D >::sym() [inline]

Apply a central symmetry to the target window.

Definition at line 234 of file window.hh.

References mln::window< D >::insert(), and mln::window< D >::size().

Referenced by mln::window< D >::is_symmetric().

10.427.5 Friends And Related Function Documentation

10.427.5.1 template<typename D > bool operator==(const window< D > & lhs, const window< D > & rhs) [related]

Equality comparison between windows lhs and rhs.


Definition at line 400 of file window.hh.

10.428 mln::world::inter_pixel::is_separator Struct Reference

Functor returning whether a site is a separator in an inter-pixel image.

```
#include <is_separator.hh>
```

Inheritance diagram for mln::world::inter_pixel::is_separator:



10.428.1 Detailed Description

Functor returning whether a site is a separator in an inter-pixel image.

Definition at line 52 of file `is_separator.hh`.

10.429 trait::graph< I > Struct Template Reference

Graph traits.

```
#include <morpho.hh>
```

10.429.1 Detailed Description

```
template<typename I> struct trait::graph< I >
```

Graph traits.

Definition at line 73 of file morpho.hh.

10.430 trait::graph< mln::complex_image< 1, G, V > > Struct Template Reference

Graph traits for 1-complexes images.

```
#include <morpho.hh>
```

10.430.1 Detailed Description

```
template<typename G, typename V> struct trait::graph< mln::complex_image< 1, G, V > >
```

Graph traits for 1-complexes images.

Definition at line 133 of file morpho.hh.

10.431 trait::graph< mln::image2d< T > > Struct Template Reference

Graph traits for [mln::image2d](#).

```
#include <morpho.hh>
```

10.431.1 Detailed Description

```
template<typename T> struct trait::graph< mln::image2d< T > >
```

Graph traits for [mln::image2d](#).

Definition at line 94 of file morpho.hh.

Index

~decorated_image
 mln::decorated_image, 598

~proxy
 mln::value::proxy, 1135

~soft_heap
 mln::util::soft_heap, 1091

~tracked_ptr
 mln::util::tracked_ptr, 1094

_1
 mln::algebra::h_mat, 546

1D neighborhoods, 101

1D windows, 112

2D neighborhoods, 102

2D windows, 113

3D neighborhoods, 104

3D windows, 115

a_point_of
 mln, 150

abs
 mln::data, 206
 mln::math, 355

abs_inplace
 mln::data, 206

Accumulators, 99

add
 mln::topo::n_faces_set, 1027

add_child
 mln::util::tree_node, 1099

add_edge
 mln::util::graph, 1062

add_face
 mln::topo::complex, 1006

add_location
 mln::geom::complex_geometry, 726

add_tree_down
 mln::util::tree, 1096

add_tree_up
 mln::util::tree, 1096

add_vertex
 mln::util::graph, 1062

add_vertices
 mln::util::graph, 1062

addr
 mln::topo::complex, 1006

adj_higher_dim_connected_n_face_bkd_iter
 mln::topo::adj_higher_dim_connected_n_-
 face_bkd_iter, 977

adj_higher_dim_connected_n_face_fwd_iter
 mln::topo::adj_higher_dim_connected_n_-
 face_fwd_iter, 979

adj_higher_face_bkd_iter
 mln::topo::adj_higher_face_bkd_iter, 980

adj_higher_face_fwd_iter
 mln::topo::adj_higher_face_fwd_iter, 981

adj_lower_dim_connected_n_face_bkd_iter
 mln::topo::adj_lower_dim_connected_n_-
 face_bkd_iter, 982

adj_lower_dim_connected_n_face_fwd_iter
 mln::topo::adj_lower_dim_connected_n_-
 face_fwd_iter, 983

adj_lower_face_bkd_iter
 mln::topo::adj_lower_face_bkd_iter, 984

adj_lower_face_fwd_iter
 mln::topo::adj_lower_face_fwd_iter, 985

adj_lower_higher_face_bkd_iter
 mln::topo::adj_lower_higher_face_bkd_iter,
 986

adj_lower_higher_face_fwd_iter
 mln::topo::adj_lower_higher_face_fwd_iter,
 988

adj_m_face_bkd_iter
 mln::topo::adj_m_face_bkd_iter, 989

adj_m_face_fwd_iter
 mln::topo::adj_m_face_fwd_iter, 990

adjacency_matrix
 mln::util::adjacency_matrix, 1035, 1036

adjust
 mln::border, 190
 mln::extension, 240

adjust_duplicate
 mln::extension, 241

adjust_fill
 mln::extension, 241

algebraic_face
 mln::topo::algebraic_face, 993

algebraic_n_face
 mln::topo::algebraic_n_face, 998

and_inplace
 mln::logical, 327

and_not
 mln::logical, 327

and_not_inplace
 mln::logical, 327

antialiased
 mln::subsampling, 395

apex
 mln::util::branch, 1044

append
 mln::p_array, 850
 mln::util::array, 1039, 1040

apply
 mln::data, 206

apply_p2p
 mln, 150

area
 mln::accu::site_set::rectangularity, 510
 mln::morpho::attribute::sharpness, 837
 mln::morpho::attribute::volume, 841
 mln::win::octagon2d, 1169
 mln::win::rectangle2d, 1170

argument
 mln::accu::shape::height, 506
 mln::accu::shape::volume, 508
 mln::doc::Accumulator, 600

array
 mln::util::array, 1039

at
 mln::opt, 388

attachment
 mln::make, 335

backdiag2d
 mln::win::backdiag2d, 1160

background
 mln::labeling, 298

ball
 mln::win::ball, 1161

base_level
 mln::morpho::attribute::height, 836

Basic types, 95, 108

bbox
 mln::accu::site_set::rectangularity, 510
 mln::Box, 563
 mln::box, 557
 mln::doc::Box, 603
 mln::doc::Fastest_Image, 610
 mln::doc::Image, 620
 mln::geom, 255
 mln::image1d, 767
 mln::image2d, 772
 mln::image3d, 780
 mln::labeled_image, 792
 mln::labeled_image_base, 795

 mln::p_line2d, 888
 mln::p_run, 915

bbox_t
 mln::labeled_image, 791
 mln::labeled_image_base, 794

bboxes
 mln::labeled_image, 792
 mln::labeled_image_base, 795

before
 mln, 163

begin
 mln::p_line2d, 888

bin_1complex_image2d
 mln, 145

bin_2complex_image3df
 mln, 145

binarization
 mln::binarization, 188

bkd_citer
 mln::topo::complex, 1005

bkd_eiter
 mln::util::array, 1038
 mln::util::set, 1084

bkd_niter
 mln::doc::Neighborhood, 624
 mln::graph_elt_mixed_neighborhood, 734
 mln::graph_elt_neighborhood, 740
 mln::graph_elt_neighborhood_if, 741
 mln::mixed_neighb, 831
 mln::neighb, 843

bkd_piter
 mln::box, 555
 mln::doc::Box, 602
 mln::doc::Fastest_Image, 608
 mln::doc::Image, 618
 mln::doc::Site_Set, 634
 mln::hexa, 760
 mln::image2d_h, 775
 mln::p_array, 849
 mln::p_centered, 854
 mln::p_complex, 857
 mln::p_edges, 861
 mln::p_faces, 866
 mln::p_if, 871
 mln::p_image, 875
 mln::p_key, 882
 mln::p_line2d, 887
 mln::pMutable_array_of, 891
 mln::p_priority, 898
 mln::p_queue, 903
 mln::p_queue_fast, 908
 mln::p_run, 913
 mln::p_set, 918
 mln::p_set_of, 922

mln::p_transformed, 925
mln::p_vaccess, 930
mln::p_vertices, 934
bkd_pixter1d
 mln::bkd_pixter1d, 549
bkd_pixter2d
 mln::bkd_pixter2d, 550
bkd_pixter3d
 mln::bkd_pixter3d, 552
bkd_qiter
 mln::doc::Weighted_Window, 640
 mln::doc::Window, 642
 mln::graph_elt_mixed_window, 736
 mln::graph_elt_window, 744
 mln::graph_elt_window_if, 748
 mln::w_window, 1156
 mln::window, 1173
bkd_viter
 mln::doc::Value_Set, 638
 mln::value::lut_vec, 1131
black
 mln::literal, 323
blobs
 mln::canvas::labeling, 196
 mln::labeling, 299
blobs_and_compute
 mln::labeling, 299
blue
 mln::literal, 323
border
 mln::doc::Fastest_Image, 610
 mln::image1d, 767
 mln::image2d, 772
 mln::image3d, 780
box
 mln::box, 556
 mln::draw, 234
box1d
 mln, 145
 mln::make, 335, 336
box2d
 mln, 145
 mln::make, 336
box2d_h
 mln, 145
 mln::make, 337
box3d
 mln, 146
 mln::make, 338
box_plain
 mln::draw, 234
box_runend_piter
 mln::box_runend_piter, 566
box_runstart_piter
 mln::box_runstart_piter, 568
branch
 mln::util::branch, 1043
brown
 mln::literal, 323
buffer
 mln::doc::Fastest_Image, 611
 mln::image1d, 767
 mln::image2d, 772
 mln::image3d, 780
c18
 modneighb3d, 105
c2
 modneighb1d, 102
c26
 modneighb3d, 105
c2_3d_sli
 modneighb3d, 106
c2_col
 modneighb2d, 103
c2_row
 modneighb2d, 103
c4
 modneighb2d, 103
c4_3d
 modneighb3d, 106
c6
 modneighb3d, 107
c8
 modneighb2d, 104
c8_3d
 modneighb3d, 107
can_stop
 mln::accu::logic::land_basic, 450
 mln::accu::logic::lor_basic, 453
Canvas, 99
card
 mln::set, 393
cast
 mln::value, 427
Category
 mln::util::vertex, 1104
category
 mln::util::edge, 1052
cell
 mln::make, 338
center
 mln::p_centered, 855
center_only_iter
 mln::topo::center_only_iter, 1001
center_t
 mln::graph_elt_mixed_window, 736
 mln::graph_elt_window, 744

mln::graph_window_piter, 756
 center_val
 mln::dpoints_bkd_pixter, 651
 mln::dpoints_fwd_pixter, 654
 centered_bkd_iter_adapter
 mln::topo::centered_bkd_iter_adapter, 1003
 centered_fwd_iter_adapter
 mln::topo::centered_fwd_iter_adapter, 1004
 chamfer
 mln::geom, 255
 change
 mln::p_array, 850
 change_both
 mln::util::couple, 1049
 mln::util::ord_pair, 1079
 change_extension
 mln::extension_val, 665
 change_first
 mln::util::couple, 1049
 mln::util::ord_pair, 1079
 change_graph
 mln::util::edge, 1052
 mln::util::vertex, 1105
 change_key
 mln::p_key, 883
 change_keys
 mln::p_key, 883
 change_mask
 mln::graph_elt_window_if, 750
 change_second
 mln::util::couple, 1049
 mln::util::ord_pair, 1079
 change_target
 mln::complex_psite, 591
 mln::faces_psite, 668
 mln::p_transformed_piter, 928
 change_target_site_set
 mln::graph_window_piter, 757
 change_to
 mln::pixel, 940
 check_consistency
 mln::util::tree, 1096
 mln::util::tree_node, 1099
 children
 mln::util::tree_node, 1100
 clear
 mln::p_array, 850
 mln::p_image, 876
 mln::p_key, 884
 mln::p.Mutable_array_of, 892
 mln::p_priority, 899
 mln::p_queue, 904
 mln::p_queue_fast, 909
 mln::p_set, 919
 mln::p_set_of, 923
 mln::util::array, 1040
 mln::util::fibonacci_heap, 1056
 mln::util::set, 1084
 mln::util::soft_heap, 1091
 mln::w_window, 1156
 mln::window, 1174
 closing
 mln::morpho::elementary, 369
 colorize
 mln::labeling, 299, 300
 complementation
 mln::morpho, 360
 complementation_inplace
 mln::morpho, 360
 complex
 mln::topo::complex, 1006
 Complex based, 109
 complex_geometry
 mln::geom::complex_geometry, 725
 complex_image
 mln::complex_image, 586
 complex_neighborhood_bkd_piter
 mln::complex_neighborhood_bkd_piter, 588
 complex_neighborhood_fwd_piter
 mln::complex_neighborhood_fwd_piter, 589
 complex_psite
 mln::complex_psite, 591
 complex_window_bkd_piter
 mln::complex_window_bkd_piter, 594
 complex_window_fwd_piter
 mln::complex_window_fwd_piter, 596
 compose
 mln, 150
 composed
 mln::fun::x2x::composed, 705
 compute
 mln::accu, 166
 mln::data, 206, 207
 mln::graph, 266
 mln::histo, 268
 mln::labeling, 300–302
 mln::labeling::impl::generic, 313, 314
 mln::set, 393
 compute_attribute_image
 mln::morpho::tree, 373
 compute_attribute_image_from
 mln::morpho::tree, 374
 compute_fastest
 mln::labeling::impl, 311
 compute_has
 mln::p_queue_fast, 909
 compute_image
 mln::labeling, 302, 303

compute_parent
 mln::morpho::tree, 374

compute_with_weights
 mln::set, 393

contrast
 mln::morpho, 360

convert
 mln::data, 207

convolve
 mln::linear::local, 319

coord
 mln::def, 231
 mln::doc::Dpoint, 605
 mln::doc::Fastest_Image, 608
 mln::doc::Image, 618
 mln::doc::Point_Site, 629
 mln::dpoint, 645
 mln::point, 949

coordf
 mln::def, 231

count
 mln::accu::stat::mean, 519

couple
 mln::make, 339

cplx
 mln::p_complex, 858
 mln::p_faces, 867, 868
 mln::topo::algebraic_face, 993
 mln::topo::algebraic_n_face, 998
 mln::topo::face, 1010
 mln::topo::n_face, 1021

crop_wrt
 mln::box, 557

cube3d
 mln::win::cube3d, 1162

cuboid3d
 mln::win::cuboid3d, 1163

cyan
 mln::literal, 323

D
 mln::topo::is_simple_cell, 1019

dark_gray
 mln::literal, 323

dashed_line
 mln::draw, 235

data
 mln::topo::algebraic_face, 993
 mln::topo::algebraic_n_face, 998
 mln::topo::face, 1010
 mln::topo::n_face, 1021

data_t
 mln::fun::x2x::rotation, 708
 mln::fun::x2x::translation, 711

dec_face_id
 mln::topo::algebraic_face, 994
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1010
 mln::topo::n_face, 1021

dec_n
 mln::topo::algebraic_face, 994
 mln::topo::face, 1010

decorated_image
 mln::decorated_image, 598

decoration
 mln::decorated_image, 598

deepness
 mln::util::branch_iter, 1045
 mln::util::branch_iter_ind, 1047

delete_tree_node
 mln::util::tree_node, 1100

delta
 mln::doc::Weighted_Window, 641
 mln::geom, 256
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_elt_window_if, 750
 mln::graph_window_base, 752
 mln::point, 949
 mln::window, 1174

delta_index
 mln::doc::Fastest_Image, 611
 mln::image1d, 767
 mln::image2d, 772
 mln::image3d, 780

depth
 mln::win::cuboid3d, 1164

detach
 mln::topo, 403

detachment
 mln::make, 339

diag2d
 mln::win::diag2d, 1165

diameter
 mln::win::ball, 1161

diff
 mln::Box, 564
 mln::Site_Set, 968
 mln::win, 434

diff_abs
 mln::arith, 177

dilation
 mln::morpho, 360

dim
 mln::complex_image, 586
 mln::doc::Dpoint, 605
 mln::doc::Point_Site, 630
 mln::dpoint, 646

mln::point, 950
 direct
 mln::morpho::tree::filter, 380
 discrete_plane_1complex_geometry
 mln, 146
 discrete_plane_2complex_geometry
 mln, 146
 disk2d
 modwin2d, 114
 display_branch
 mln::util, 417
 display_tree
 mln::util, 417
 distance_and_closest_point_geodesic
 mln::transform, 410
 distance_and_influence_zone_geodesic
 mln::transform, 411
 distance_front
 mln::canvas, 194
 mln::transform, 411
 distance_geodesic
 mln::canvas, 194
 mln::transform, 411
 div
 mln::arith, 177
 div_cst
 mln::arith, 178
 div_inplace
 mln::arith, 178
 domain
 mln::complex_image, 586
 mln::doc::Fastest_Image, 611
 mln::doc::Image, 620
 mln::extended, 659
 mln::flat_image, 671
 mln::hexa, 761
 mln::image1d, 767
 mln::image2d, 772
 mln::image2d_h, 776
 mln::image3d, 781
 mln::image_if, 784
 mln::lazy_image, 798
 mln::p2p_image, 846
 mln::slice_image, 971
 mln::sub_image, 973
 mln::sub_image_if, 974
 mln::tr_image, 1033
 mln::unproject_image, 1034
 Domain morphers, 97
 domain_t
 mln::value::stack_image, 1143
 dp
 mln::window, 1174
 dpoint
 mln::doc::Dpoint, 605
 mln::doc::Fastest_Image, 608
 mln::doc::Image, 618
 mln::doc::Neighborhood, 624
 mln::doc::Point_Site, 629
 mln::doc::Weighted_Window, 640
 mln::dpoint, 646, 647
 dpoint1d
 mln, 146
 dpoint2d
 mln, 146
 dpoint2d_h
 mln, 146
 mln::make, 339
 dpoint3d
 mln, 146
 dpoints_bkd_pixter
 mln::dpoints_bkd_pixter, 650
 dpoints_fwd_pixter
 mln::dpoints_fwd_pixter, 653
 dpsite
 mln::point, 949
 mln::w_window, 1156
 draw_graph
 mln::debug, 226
 dual_input_max_tree
 mln::morpho::tree, 375
 dummy_p_edges
 mln::make, 340
 dummy_p_vertices
 mln::make, 340, 341
 duplicate
 mln, 151
 mln::border, 190
 mln::extension, 241
 e_ith_nbh_edge
 mln::util::graph, 1062
 mln::util::line_graph, 1071
 e_nmax
 mln::util::graph, 1062
 mln::util::line_graph, 1071
 e_nmax_nbh_edges
 mln::util::graph, 1063
 mln::util::line_graph, 1071
 edge
 mln::p_edges, 861
 mln::topo, 403
 mln::util::edge, 1052
 mln::util::graph, 1063
 mln::util::line_graph, 1071
 edge_fwd_iter
 mln::util::graph, 1060
 mln::util::line_graph, 1070

edge_image
 mln::edge_image, 657
 mln::make, 341, 342
edge_nbh_edge_fwd_iter
 mln::util::graph, 1060
 mln::util::line_graph, 1070
edge_nbh_t
 mln::edge_image, 656
edge_win_t
 mln::edge_image, 656
edge_with
 mln::util::vertex, 1105
edges
 mln::util::graph, 1063
edges_set_t
 mln::util::graph, 1060
edges_t
 mln::util::graph, 1060
 mln::util::line_graph, 1070
eiter
 mln::util::array, 1038
 mln::util::set, 1084
element
 mln::box, 555
 mln::graph_window_if_piter, 754
 mln::graph_window_piter, 758
 mln::image1d, 767
 mln::image2d, 772
 mln::image3d, 781
 mln::p_array, 849
 mln::p_centered, 854
 mln::p_complex, 857
 mln::p_edges, 861
 mln::p_faces, 866
 mln::p_if, 871
 mln::p_image, 875
 mln::p_key, 882
 mln::p_line2d, 887
 mln::pMutable_array_of, 891
 mln::p_priority, 898
 mln::p_queue, 903
 mln::p_queue_fast, 908
 mln::p_run, 913
 mln::p_set, 918
 mln::p_set_of, 922
 mln::p_transformed, 925
 mln::p_vaccess, 930
 mln::p_vertices, 934
 mln::util::array, 1038
 mln::util::set, 1084
 mln::util::soft_heap, 1090
elt
 mln::util::tree_node, 1100
empty

 mln::p_queue_fast, 909
enc
 mln::value::float01, 1110
 mln::value::label, 1127
 mln::value::proxy, 1134
 mln::value::sign, 1141
end
 mln::p_line2d, 889
 mln::p_run, 915
enlarge
 mln::box, 557
equalize
 mln::border, 190
 mln::histo, 268
equiv
 mln::value, 427
 mln::value::float01, 1110
 mln::value::proxy, 1134
 mln::value::sign, 1141
erosion
 mln::morpho, 361
exists_key
 mln::p_key, 884
exists_priority
 mln::p_priority, 899
extend
 mln, 151
extended
 mln::extended, 658
extension
 mln::extension_fun, 661
 mln::extension_ima, 663
 mln::extension_val, 665
extension_fun
 mln::extension_fun, 660
extension_ima
 mln::extension_ima, 663
extension_val
 mln::extension_val, 665
f_hsi_to_rgb_3x8
 mln::fun::v2v, 247
f_hsl_to_rgb_3x8
 mln::fun::v2v, 247
f_rgb_to_hsi_f
 mln::fun::v2v, 247
f_rgb_to_hsl_f
 mln::fun::v2v, 247
face
 mln::complex_psite, 592
 mln::faces_psite, 668
 mln::topo::face, 1009
face_bkd_iter
 mln::topo::face_bkd_iter, 1013

face_fwd_iter
 mln::topo::face_fwd_iter, 1014

face_id
 mln::complex_psite, 592
 mln::faces_psite, 668
 mln::topo::algebraic_face, 994
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1010
 mln::topo::n_face, 1021

faces
 mln::topo::n_faces_set, 1027

faces_psite
 mln::faces_psite, 667

faces_type
 mln::topo::n_faces_set, 1026

fast_median
 mln::data, 207

fibonacci_heap
 mln::util::fibonacci_heap, 1056

filename
 mln::debug, 227

fill
 mln::border, 191
 mln::data, 208
 mln::extension, 241
 mln::util::array, 1040

fill_holes
 mln::labeling, 304

fill_with_image
 mln::data, 208
 mln::data::impl::generic, 221

fill_with_value
 mln::data, 208
 mln::data::impl::generic, 221

filter
 mln::morpho::tree::filter, 380

find
 mln::border, 191

first
 mln::accu::pair, 501
 mln::accu::stat::min_max, 529
 mln::util::couple, 1049
 mln::util::ord_pair, 1079
 mln::util::site_pair, 1088

first_accu
 mln::accu::pair, 501
 mln::accu::stat::min_max, 529

first_element
 mln::util::set, 1084

flat_image
 mln::flat_image, 670

flat_zones
 mln::labeling, 304

float01
 mln::value::float01, 1110
 float01_16
 mln::value, 425
 float01_8
 mln::value, 425
 float01_f
 mln::value::float01_f, 1112
 float_2complex_image3df
 mln, 147

flooding
 mln::morpho::watershed, 382, 383

foreground
 mln::labeling, 304

format
 mln::debug, 227

from_to
 mln::convert, 199, 200

front
 mln::p_priority, 899
 mln::p_queue, 904
 mln::p_queue_fast, 909
 mln::util::fibonacci_heap, 1056

fun
 mln::p2p_image, 846

fun_image
 mln::fun_image, 714

fun_t
 mln::p_edges, 862
 mln::p_vertices, 935

Function
 mln::Function, 715

function
 mln::p_edges, 864
 mln::p_transformed, 926
 mln::p_vertices, 937

Functions, 100

fwd_citer
 mln::topo::complex, 1005

fwd_eiter
 mln::util::array, 1039
 mln::util::set, 1084

fwd_niter
 mln::doc::Neighborhood, 624
 mln::graph_elt_mixed_neighborhood, 734
 mln::graph_elt_neighborhood, 740
 mln::graph_elt_neighborhood_if, 741
 mln::mixed_neighb, 831
 mln::neighb, 843

fwd_piter
 mln::box, 555
 mln::doc::Box, 602
 mln::doc::Fastest_Image, 609
 mln::doc::Image, 618
 mln::doc::Site_Set, 634

mln::hexa, 760
mln::image2d_h, 775
mln::p_array, 849
mln::p_centered, 854
mln::p_complex, 857
mln::p_edges, 862
mln::p_faces, 866
mln::p_if, 871
mln::p_image, 875
mln::p_key, 882
mln::p_line2d, 887
mln::p_mutable_array_of, 891
mln::p_priority, 898
mln::p_queue, 903
mln::p_queue_fast, 908
mln::p_run, 913
mln::p_set, 918
mln::p_set_of, 922
mln::p_transformed, 925
mln::p_vaccess, 930
mln::p_vertices, 935
fwd_pixter1d
 mln::fwd_pixter1d, 720
fwd_pixter2d
 mln::fwd_pixter2d, 721
fwd_pixter3d
 mln::fwd_pixter3d, 723
fwd_qiter
 mln::doc::Weighted_Window, 640
 mln::doc::Window, 642
 mln::graph_elt_mixed_window, 736
 mln::graph_elt_window, 744
 mln::graph_elt_window_if, 748
 mln::w_window, 1156
 mln::window, 1173
fwd_viter
 mln::doc::Value_Set, 638
 mln::value::lut_vec, 1131

gaussian
 mln::linear, 315
gaussian_1st_derivative
 mln::linear, 316
gaussian_2nd_derivative
 mln::linear, 316
gaussian_subsampling
 mln::subsampling, 395
general
 mln::morpho, 361
geom
 mln::complex_image, 585
 mln::p_complex, 858
get
 mln::border, 191

 mln::set, 394
get_header
 mln::io::dicom, 272
 mln::io::dump, 273
 mln::io::raw, 293
get_rot
 mln::registration, 390
gl16
 mln::value, 425
gl8
 mln::value, 425
glf
 mln::value, 425
gradient
 mln::morpho, 361
gradient_external
 mln::morpho, 361
gradient_internal
 mln::morpho, 361
graph
 mln::p_edges, 864
 mln::p_graph_piter, 869
 mln::p_vertices, 937
 mln::util::edge, 1052
 mln::util::graph, 1061
 mln::util::line_graph, 1072
 mln::util::vertex, 1105
Graph based, 109
graph_element
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_window_piter, 756
 mln::p_edges, 862
 mln::p_vertices, 935
graph_elt_neighborhood_if
 mln::graph_elt_neighborhood_if, 742
graph_elt_window_if
 mln::graph_elt_window_if, 750
graph_t
 mln::edge_image, 656
 mln::p_edges, 862
 mln::p_vertices, 935
 mln::util::edge, 1052
 mln::util::vertex, 1104
 mln::vertex_image, 1151
graph_window_if_piter
 mln::graph_window_if_piter, 754
graph_window_piter
 mln::graph_window_piter, 757
Graphes, 94
graylevel
 mln::value::graylevel, 1114
graylevel_f
 mln::value::graylevel_f, 1117

green
 mln::literal, 323

grid
 mln::dpoint, 645
 mln::point, 949

h_mat
 mln::algebra::h_mat, 545
 mln::make, 343

h_vec
 mln::algebra::h_vec, 547
 mln::point, 949

has
 mln::box, 557
 mln::doc::Box, 603
 mln::doc::Fastest_Image, 611
 mln::doc::Image, 620
 mln::doc::Site_Set, 634
 mln::doc::Value_Set, 638
 mln::extension_fun, 661
 mln::extension_ima, 663
 mln::extension_val, 666
 mln::flat_image, 671
 mln::hexa, 761
 mln::image1d, 768
 mln::image2d, 773
 mln::image2d_h, 776
 mln::image3d, 781
 mln::interpolated, 786
 mln::lazy_image, 798
 mln::p_array, 850, 851
 mln::p_centered, 855
 mln::p_complex, 858
 mln::p_edges, 864
 mln::p_if, 872
 mln::p_image, 876
 mln::p_key, 884
 mln::p_line2d, 889
 mln::p Mutable_array_of, 892
 mln::p_priority, 899
 mln::p_queue, 904, 905
 mln::p_queue_fast, 910
 mln::p_run, 915
 mln::p_set, 919
 mln::p_set_of, 923
 mln::p_transformed, 926
 mln::p_vaccess, 931
 mln::p_vertices, 937
 mln::set, 394
 mln::tr_image, 1033
 mln::util::line_graph, 1072
 mln::util::set, 1085
 mln::value::lut_vec, 1132
 mln::window, 1174

has_e
 mln::util::graph, 1063
 mln::util::line_graph, 1072

has_index
 mln::p_run, 915

has_v
 mln::util::graph, 1063
 mln::util::line_graph, 1072

height
 mln::morpho::attribute::sharpness, 837
 mln::win::cuboid3d, 1164
 mln::win::rectangle2d, 1170

hexa
 mln::hexa, 761

higher_dim_adj_faces
 mln::topo::algebraic_face, 994
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1010
 mln::topo::n_face, 1021

highest_priority
 mln::p_priority, 899

histo3d_rgb
 mln::accu::stat::histo3d_rgb, 514

hit_or_miss
 mln::morpho, 362

hit_or_miss_background_closing
 mln::morpho, 362

hit_or_miss_background_opening
 mln::morpho, 362

hit_or_miss_closing
 mln::morpho, 362

hit_or_miss_opening
 mln::morpho, 362

hline2d
 modwin2d, 114

horizontal_symmetry
 mln::geom, 256

hough
 mln::transform, 411

i_element
 mln::p_array, 849
 mln::p_image, 875
 mln::p_key, 883
 mln::p Mutable_array_of, 891
 mln::p_priority, 898
 mln::p_queue, 904
 mln::p_queue_fast, 908
 mln::p_set, 918
 mln::p_set_of, 922
 mln::p_vaccess, 930

icp
 mln::registration, 390, 391

id

mln::graph_window_if_piter, 754
mln::graph_window_piter, 758
mln::p_graph_piter, 869
mln::util::edge, 1052
mln::util::vertex, 1105
id_t
 mln::util::edge, 1052
 mln::util::vertex, 1104
id_value_t
 mln::util::edge, 1052
 mln::util::vertex, 1104
identity
 mln::literal, 323
Identity morphers, 98
ima
 mln::doc::Generalized_Pixel, 616
 mln::doc::Pixel_Iterator, 627
 mln::fun::x2x::linear, 706
 mln::util::pix, 1081
image
 mln::bkd_pixter1d, 549
 mln::bkd_pixter2d, 550
 mln::bkd_pixter3d, 551
 mln::doc::Generalized_Pixel, 615
 mln::doc::Pixel_Iterator, 627
 mln::fwd_pixter1d, 720
 mln::fwd_pixter2d, 721
 mln::fwd_pixter3d, 722
 mln::make, 343, 344
 mln::pw::image, 959
Image morphers, 96
image1d
 mln::image1d, 766
image2d
 mln::image2d, 771
 mln::make, 344
image2d_h
 mln::image2d_h, 776
image3d
 mln::image3d, 780
 mln::make, 344
image_if
 mln::image_if, 783
Images, 95
implies
 mln, 152
inc_face_id
 mln::topo::algebraic_face, 994
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1010
 mln::topo::n_face, 1021
inc_n
 mln::topo::algebraic_face, 994
 mln::topo::face, 1011
index
 mln::p_indexed_bkd_piter, 878
 mln::p_indexed_fwd_piter, 880
index_of
 mln::doc::Value_Set, 638
 mln::value::lut_vec, 1132
influence_zone_adjacency_graph
 mln::make, 344
influence_zone_front
 mln::transform, 412
influence_zone_geodesic
 mln::transform, 412
influence_zone_geodesic_saturated
 mln::transform, 413
init
 mln::accu::center, 438
 mln::accu::convolve, 439
 mln::accu::count_adjacent_vertices, 441
 mln::accu::count_labels, 443
 mln::accu::count_value, 444
 mln::accu::label_used, 447
 mln::accu::logic::land, 449
 mln::accu::logic::land_basic, 450
 mln::accu::logic::lor, 452
 mln::accu::logic::lor_basic, 453
 mln::accu::maj_h, 455
 mln::accu::math::count, 456
 mln::accu::math::inf, 458
 mln::accu::math::sum, 459
 mln::accu::math::sup, 460
 mln::accu::max_site, 462
 mln::accu::nil, 497
 mln::accu::p, 498
 mln::accu::pair, 501
 mln::accu::rms, 503
 mln::accu::shape::bbox, 504
 mln::accu::shape::height, 506
 mln::accu::shape::volume, 508
 mln::accu::stat::deviation, 512
 mln::accu::stat::histo3d_rgb, 514
 mln::accu::stat::max, 516
 mln::accu::stat::max_h, 517
 mln::accu::stat::mean, 519
 mln::accu::stat::median_h, 523
 mln::accu::stat::min, 525
 mln::accu::stat::min_h, 527
 mln::accu::stat::min_max, 529
 mln::accu::stat::rank, 531
 mln::accu::stat::rank< bool >, 532
 mln::accu::stat::rank_high_quant, 534
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 538
 mln::accu::tuple, 540
 mln::accu::val, 542

mln::doc::Accumulator, 600
 mln::morpho::attribute::card, 833
 mln::morpho::attribute::count_adjacent_vertices, 834
 mln::morpho::attribute::height, 836
 mln::morpho::attribute::sharpness, 838
 mln::morpho::attribute::sum, 839
 mln::morpho::attribute::volume, 841
 mln::p_run, 915
 initialize
 mln, 152
 insert
 mln::p_array, 851
 mln::p_image, 876
 mln::p_key, 884
 mln::p.Mutable_Array_of, 892
 mln::p_priority, 900
 mln::p_queue, 905
 mln::p_queue_fast, 910
 mln::p_set, 920
 mln::p_set_of, 923
 mln::p_vaccess, 931, 932
 mln::util::set, 1085
 mln::w_window, 1156
 mln::window, 1174
 int_s
 mln::value::int_s, 1120
 int_s16
 mln::value, 425
 int_s32
 mln::value, 426
 int_s8
 mln::value, 426
 int_u
 mln::value::int_u, 1122
 int_u12
 mln::value, 426
 int_u16
 mln::value, 426
 int_u32
 mln::value, 426
 int_u8
 mln::value, 426
 int_u8_1complex_image2d
 mln, 147
 int_u8_2complex_image2d
 mln, 147
 int_u8_2complex_image3df
 mln, 147
 int_u_sat
 mln::value::int_u_sat, 1124
 inter
 mln::Box, 564
 mln::Site_Set, 968
 interpolated
 mln::interpolated, 786
 inv
 mln::fun::x2x::rotation, 709
 mln::fun::x2x::translation, 712
 invalidate
 mln::complex_psite, 592
 mln::doc::Iterator, 623
 mln::doc::Pixel_Iterator, 628
 mln::doc::Site_Iterator, 632
 mln::doc::Value_Iterator, 636
 mln::dpoints_bkd_pixter, 651
 mln::dpoints_fwd_pixter, 654
 mln::faces_psite, 668
 mln::p_edges, 864
 mln::p_vertices, 937
 mln::topo::algebraic_face, 994
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1011
 mln::topo::n_face, 1022
 mln::util::branch_iter, 1045
 mln::util::branch_iter_ind, 1047
 mln::util::edge, 1053
 mln::util::vertex, 1105
 invert
 mln::fun::x2x::rotation, 708
 mln::fun::x2x::translation, 711
 iota
 mln::debug, 228
 is_centered
 mln::doc::Weighted_Window, 641
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_elt_window_if, 750
 mln::graph_window_base, 752
 mln::window, 1175
 is_empty
 mln::Box, 563
 mln::box, 558
 mln::doc::Weighted_Window, 641
 mln::graph_elt_mixed_window, 738
 mln::graph_elt_window, 746
 mln::graph_elt_window_if, 750
 mln::graph_window_base, 752
 mln::util::array, 1040
 mln::util::fibonacci_heap, 1056
 mln::util::set, 1085
 mln::util::soft_heap, 1091
 mln::window, 1175
 is_facet
 mln::topo, 403
 is_subgraph_of
 mln::util::graph, 1064
 mln::util::line_graph, 1073

is_symmetric
 mln::graph_elt_mixed_window, 738
 mln::graph_elt_window, 746
 mln::graph_elt_window_if, 750
 mln::graph_window_base, 753
 mln::w_window, 1157
 mln::window, 1175

is_valid
 mln::accu::center, 438
 mln::accu::convolve, 439
 mln::accu::count_adjacent_vertices, 441
 mln::accu::count_labels, 443
 mln::accu::count_value, 444
 mln::accu::histo, 446
 mln::accu::label_used, 447
 mln::accu::logic::land, 449
 mln::accu::logic::land_basic, 450
 mln::accu::logic::lor, 452
 mln::accu::logic::lor_basic, 453
 mln::accu::maj_h, 455
 mln::accu::math::count, 456
 mln::accu::math::inf, 458
 mln::accu::math::sum, 459
 mln::accu::math::sup, 460
 mln::accu::max_site, 462
 mln::accu::nil, 497
 mln::accu::p, 498
 mln::accu::pair, 501
 mln::accu::rms, 503
 mln::accu::shape::bbox, 504
 mln::accu::shape::height, 506
 mln::accu::shape::volume, 508
 mln::accu::stat::deviation, 512
 mln::accu::stat::histo3d_rgb, 514
 mln::accu::stat::max, 516
 mln::accu::stat::max_h, 517
 mln::accu::stat::mean, 519
 mln::accu::stat::median_alt, 521
 mln::accu::stat::median_h, 523
 mln::accu::stat::min, 525
 mln::accu::stat::min_h, 527
 mln::accu::stat::min_max, 529
 mln::accu::stat::rank, 531
 mln::accu::stat::rank< bool >, 532
 mln::accu::stat::rank_high_quant, 534
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 538
 mln::accu::tuple, 540
 mln::accu::val, 542
 mln::box, 558
 mln::complex_psite, 592
 mln::doc::Fastest_Image, 612
 mln::doc::Image, 621
 mln::doc::Iterator, 623

 mln::doc::Pixel_Iterator, 628
 mln::doc::Site_Iterator, 632
 mln::doc::Value_Iterator, 636
 mln::dpoints_bkd_pixter, 651
 mln::dpoints_fwd_pixter, 654
 mln::faces_psite, 668
 mln::graph_elt_mixed_window, 738
 mln::graph_elt_window, 746
 mln::graph_elt_window_if, 751
 mln::graph_window_base, 753
 mln::interpolated, 786
 mln::morpho::attribute::card, 833
 mln::morpho::attribute::count_adjacent_<
 vertices, 834
 mln::morpho::attribute::height, 836
 mln::morpho::attribute::sharpness, 838
 mln::morpho::attribute::sum, 839
 mln::morpho::attribute::volume, 841
 mln::p_array, 851
 mln::p_centered, 855
 mln::p_complex, 859
 mln::p_edges, 864
 mln::p_faces, 868
 mln::p_if, 872
 mln::p_image, 876
 mln::p_key, 885
 mln::p_line2d, 889
 mln::pMutable_array_of, 892
 mln::p_priority, 900
 mln::p_queue, 905
 mln::p_queue_fast, 910
 mln::p_run, 915
 mln::p_set, 920
 mln::p_set_of, 923
 mln::p_transformed, 926
 mln::p_vaccess, 932
 mln::p_vertices, 938
 mln::pixel, 940
 mln::topo::algebraic_face, 995
 mln::topo::algebraic_n_face, 999
 mln::topo::face, 1011
 mln::topo::n_face, 1022
 mln::tr_image, 1033
 mln::util::branch_iter, 1045
 mln::util::branch_iter_ind, 1047
 mln::util::edge, 1053
 mln::util::fibonacci_heap, 1057
 mln::util::soft_heap, 1091
 mln::util::vertex, 1105
 mln::value::stack_image, 1144

iter
 mln::complex_neighborhood_bkd_piter, 588
 mln::complex_neighborhood_fwd_piter, 590
 mln::complex_window_bkd_piter, 594

mln::complex_window_fwd_piter, 596
 iter_type
 mln::complex_neighborhood_bkd_piter, 587
 mln::complex_neighborhood_fwd_piter, 589
 mln::complex_window_bkd_piter, 594
 mln::complex_window_fwd_piter, 595
 ith_nbh_edge
 mln::util::edge, 1053
 mln::util::vertex, 1105
 ith_nbh_vertex
 mln::util::vertex, 1106

 k
 mln::accu::stat::rank, 531
 key
 mln::p_key, 885
 keys
 mln::p_key, 885

 l1
 mln::norm, 385
 l1_distance
 mln::norm, 385
 l2
 mln::norm, 386
 l2_distance
 mln::norm, 386
 label
 mln::value::label, 1128
 label_16
 mln::value, 426
 label_32
 mln::value, 426
 label_8
 mln::value, 426
 labeled_image
 mln::labeled_image, 791
 labeled_image_base
 mln::labeled_image_base, 794
 labeling
 mln::graph, 266
 laplacian
 mln::morpho, 363
 larger_than
 mln, 152
 last
 mln::util::array, 1040
 last_coord
 mln::point, 951
 last_element
 mln::util::set, 1086
 lazy_image
 mln::lazy_image, 798
 ldlt_decomp

 mln::algebra, 174
 ldlt_solve
 mln::algebra, 174
 lemmings
 mln::util, 417
 len
 mln::Box, 563
 mln::box, 558
 length
 mln::p_run, 916
 mln::win::backdiag2d, 1160
 mln::win::cube3d, 1162
 mln::win::diag2d, 1165
 mln::win::line, 1167
 mln::win::octagon2d, 1169
 light_gray
 mln::literal, 323
 lime
 mln::literal, 323
 line
 mln::accu, 166
 mln::draw, 235
 mln::win::line, 1166
 line_gradient
 mln::morpho, 363
 linear
 mln::fun::x2x::linear, 706
 linfty
 mln::norm, 386
 linfty_distance
 mln::norm, 386
 load
 mln::io::cloud, 271
 mln::io::dicom, 272
 mln::io::dump, 273
 mln::io::fits, 274, 275
 mln::io::fld, 276
 mln::io::magick, 277
 mln::io::off, 278
 mln::io::pbm, 280
 mln::io::pbms, 281
 mln::io::pfm, 283
 mln::io::pgm, 284
 mln::io::pgms, 285
 mln::io::plot, 286
 mln::io::pnm, 288
 mln::io::pnms, 290
 mln::io::ppm, 291
 mln::io::ppms, 292
 mln::io::raw, 293
 mln::io::tiff, 294
 load_ascii_builtin
 mln::io::pnm, 288
 load_ascii_value

mln::io::pnm, 288
load_raw_2d
 mln::io::pnm, 288
lower_dim_adj_faces
 mln::topo::algebraic_face, 995
 mln::topo::algebraic_n_face, 1000
 mln::topo::face, 1011
 mln::topo::n_face, 1022
lowest_priority
 mln::p_priority, 900
lut_vec
 mln::value::lut_vec, 1132
lvalue
 mln::complex_image, 585
 mln::decorated_image, 597
 mln::doc::Fastest_Image, 609
 mln::doc::Image, 619
 mln::doc::Pixel_Iterator, 627
 mln::flat_image, 670
 mln::fun_image, 713
 mln::hexa, 760
 mln::image1d, 766
 mln::image2d, 771
 mln::image2d_h, 775
 mln::image3d, 779
 mln::interpolated, 785
 mln::lazy_image, 797
 mln::tr_image, 1032
 mln::value::stack_image, 1143
 mln::violent_cast_image, 1153

magenta
 mln::literal, 324

main_branch
 mln::util::tree, 1097

make_algebraic_face
 mln::topo, 403

make_debug_graph_image
 mln, 152

make_greater_point
 mln::util, 418

make_greater_psite
 mln::util, 418

mask
 mln::graph_elt_neighborhood_if, 742
 mln::graph_elt_window_if, 751

mask_t
 mln::graph_elt_window_if, 749

mat
 mln::make, 345

max
 mln::literal, 324
 mln::morpho::tree::filter, 380

max_col
 mln::geom, 256

max_component
 mln::io::pnm, 289

max_ind
 mln::geom, 256

max_row
 mln::geom, 257

max_sli
 mln::geom, 257

max_tree
 mln::morpho::tree, 376

mean
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 538
 mln::estim, 238

mean_t
 mln::accu::stat::var, 536

median
 mln::data, 209
 mln::data::approx, 215, 216
 mln::data::naive, 223

medium_gray
 mln::literal, 324

memory_size
 mln::box, 558
 mln::p_array, 851
 mln::p_centered, 855
 mln::p_edges, 865
 mln::p_if, 872
 mln::p_image, 876
 mln::p_key, 885
 mln::p_line2d, 889
 mln::p.Mutable_array_of, 893
 mln::p_priority, 900
 mln::p_queue, 905
 mln::p_queue_fast, 910
 mln::p_run, 916
 mln::p_set, 920
 mln::p_set_of, 923
 mln::p_transformed, 926
 mln::p_vaccess, 932
 mln::p_vertices, 938
 mln::util::array, 1041
 mln::util::set, 1086

merge
 mln::box, 558

mesh
 mln::doc::Point_Site, 629

mesh_corner_point_area
 mln::geom, 257

mesh_curvature
 mln::geom, 258

mesh_normal
 mln::geom, 258

meyer_wst
 mln::morpho, 363
 min
 mln::arith, 179
 mln::literal, 324
 mln::morpho, 364
 mln::morpho::tree::filter, 381
 min_col
 mln::geom, 258
 min_ind
 mln::geom, 259
 min_inplace
 mln::arith, 179
 mln::morpho, 364
 min_max
 mln::estim, 238
 min_row
 mln::geom, 259
 min_sli
 mln::geom, 259
 min_tree
 mln::morpho::tree, 376
 minus
 mln::arith, 179, 180
 mln::morpho, 364
 minus_cst
 mln::arith, 180, 181
 minus_cst_inplace
 mln::arith, 181
 minus_infty
 mln::point, 951
 minus_inplace
 mln::arith, 182
 mirror
 mln::border, 192
 mixed_neighb
 mln::mixed_neighb, 832
 mln, 121
 a_point_of, 150
 apply_p2p, 150
 before, 163
 bin_1complex_image2d, 145
 bin_2complex_image3df, 145
 box1d, 145
 box2d, 145
 box2d_h, 145
 box3d, 146
 compose, 150
 discrete_plane_1complex_geometry, 146
 discrete_plane_2complex_geometry, 146
 dpoint1d, 146
 dpoint2d, 146
 dpoint2d_h, 146
 dpoint3d, 146
 duplicate, 151
 extend, 151
 float_2complex_image3df, 147
 implies, 152
 initialize, 152
 int_u8_1complex_image2d, 147
 int_u8_2complex_image2d, 147
 int_u8_2complex_image3df, 147
 larger_than, 152
 make_debug_graph_image, 152
 mln_exact, 153
 mln_gen_complex_neighborhood, 153
 mln_gen_complex_window, 154
 mln_gen_complex_window_p, 154, 155
 mln_regular, 155
 mln_trait_op_geq, 155
 mln_trait_op_greater, 155
 mln_trait_op_leq, 156
 mln_trait_op_neq, 156
 operator<, 158
 operator<<, 158, 159
 operator<=, 159, 160
 operator*, 157
 operator++, 157
 operator-, 157
 operator--, 158
 operator==, 160, 161
 p_run2d, 147
 p_runs2d, 147
 point1d, 147
 point1df, 148
 point2d, 148
 point2d_h, 148
 point2df, 148
 point3d, 148
 point3df, 148
 primary, 163
 ptransform, 163
 rgb8_2complex_image3df, 148
 sagittal_dec, 163
 space_2complex_geometry, 148
 unsigned_2complex_image3df, 149
 up, 163
 vec2d_d, 149
 vec2d_f, 149
 vec3d_d, 149
 vec3d_f, 149
 w_window1d_float, 149
 w_window1d_int, 149
 w_window2d_float, 149
 w_window2d_int, 150
 w_window3d_float, 150
 w_window3d_int, 150
 mln::accu, 164

compute, 166
line, 166
mln_meta_accu_result, 166
take, 167
mln::accu::center, 437
init, 438
is_valid, 438
nsites, 438
take_as_init, 438
take_n_times, 438
to_result, 438
mln::accu::convolve, 439
init, 439
is_valid, 439
take_as_init, 440
take_n_times, 440
to_result, 440
mln::accu::count_adjacent_vertices, 440
init, 441
is_valid, 441
set_value, 441
take_as_init, 441
take_n_times, 441
to_result, 442
mln::accu::count_labels, 442
init, 443
is_valid, 443
set_value, 443
take_as_init, 443
take_n_times, 443
to_result, 443
mln::accu::count_value, 443
init, 444
is_valid, 444
set_value, 444
take_as_init, 444
take_n_times, 445
to_result, 445
mln::accu::histo, 445
is_valid, 446
take, 446
take_as_init, 446
take_n_times, 446
vect, 446
mln::accu::image, 167
mln::accu::impl, 167
mln::accu::label_used, 446
init, 447
is_valid, 447
take, 447
take_as_init, 447
take_n_times, 448
to_result, 448
mln::accu::logic, 168
mln::accu::logic::land, 448
init, 449
is_valid, 449
take_as_init, 449
take_n_times, 449
to_result, 449
mln::accu::logic::land_basic, 449
can_stop, 450
init, 450
is_valid, 450
take_as_init, 450
take_n_times, 451
to_result, 451
mln::accu::logic::lor, 451
init, 452
is_valid, 452
take_as_init, 452
take_n_times, 452
to_result, 452
mln::accu::logic::lor_basic, 452
can_stop, 453
init, 453
is_valid, 453
take_as_init, 453
take_n_times, 453
to_result, 454
mln::accu::maj_h, 454
init, 455
is_valid, 455
take_as_init, 455
take_n_times, 455
to_result, 455
mln::accu::math, 168
mln::accu::math::count, 455
init, 456
is_valid, 456
set_value, 456
take_as_init, 456
take_n_times, 456
to_result, 457
mln::accu::math::inf, 457
init, 458
is_valid, 458
take_as_init, 458
take_n_times, 458
to_result, 458
mln::accu::math::sum, 458
init, 459
is_valid, 459
take_as_init, 459
take_n_times, 459
to_result, 459
mln::accu::math::sup, 460
init, 460

is_valid, 460
 take_as_init, 461
 take_n_times, 461
 to_result, 461
 mln::accu::max_site, 461
 init, 462
 is_valid, 462
 take_as_init, 462
 take_n_times, 462
 to_result, 462
 mln::accu::meta::center, 463
 mln::accu::meta::count_adjacent_vertices, 463
 mln::accu::meta::count_labels, 464
 mln::accu::meta::count_value, 465
 mln::accu::meta::histo, 466
 mln::accu::meta::label_used, 467
 mln::accu::meta::logic, 169
 mln::accu::meta::logic::land, 468
 mln::accu::meta::logic::land_basic, 469
 mln::accu::meta::logic::lor, 470
 mln::accu::meta::logic::lor_basic, 471
 mln::accu::meta::maj_h, 472
 mln::accu::meta::math, 169
 mln::accu::meta::math::count, 473
 mln::accu::meta::math::inf, 474
 mln::accu::meta::math::sum, 475
 mln::accu::meta::math::sup, 476
 mln::accu::meta::max_site, 477
 mln::accu::meta::nil, 478
 mln::accu::meta::p, 479
 mln::accu::meta::pair, 480
 mln::accu::meta::rms, 481
 mln::accu::meta::shape, 170
 mln::accu::meta::shape::bbox, 482
 mln::accu::meta::shape::height, 483
 mln::accu::meta::shape::volume, 484
 mln::accu::meta::stat, 170
 mln::accu::meta::stat::max, 485
 mln::accu::meta::stat::max_h, 486
 mln::accu::meta::stat::mean, 487
 mln::accu::meta::stat::median_alt, 488
 mln::accu::meta::stat::median_h, 489
 mln::accu::meta::stat::min, 490
 mln::accu::meta::stat::min_h, 491
 mln::accu::meta::stat::rank, 492
 mln::accu::meta::stat::rank_high_quant, 493
 mln::accu::meta::tuple, 494
 mln::accu::meta::val, 495
 mln::accu::nil, 496
 init, 497
 is_valid, 497
 take_as_init, 497
 take_n_times, 497
 to_result, 497
 mln::accu::p, 498
 init, 498
 is_valid, 498
 take_as_init, 499
 take_n_times, 499
 to_result, 499
 mln::accu::pair, 499
 first, 501
 first_accu, 501
 init, 501
 is_valid, 501
 second, 501
 second_accu, 501
 take_as_init, 502
 take_n_times, 502
 to_result, 502
 mln::accu::rms, 502
 init, 503
 is_valid, 503
 take_as_init, 503
 take_n_times, 503
 to_result, 503
 mln::accu::shape, 171
 mln::accu::shape::bbox, 504
 init, 504
 is_valid, 504
 take_as_init, 504
 take_n_times, 505
 to_result, 505
 mln::accu::shape::height, 505
 argument, 506
 init, 506
 is_valid, 506
 set_value, 506
 take_as_init, 507
 take_n_times, 507
 to_result, 507
 value, 506
 mln::accu::shape::volume, 507
 argument, 508
 init, 508
 is_valid, 508
 set_value, 509
 take_as_init, 509
 take_n_times, 509
 to_result, 509
 value, 508
 mln::accu::site_set::rectangularity, 509
 area, 510
 bbox, 510
 rectangularity, 510
 take_as_init, 510
 take_n_times, 511
 to_result, 511

mln::accu::stat, 171
operator==, 173
mln::accu::stat::deviation, 511
 init, 512
 is_valid, 512
 take_as_init, 512
 take_n_times, 512
 to_result, 512
mln::accu::stat::histo3d_rgb, 513
 histo3d_rgb, 514
 init, 514
 is_valid, 514
 take, 514
 take_as_init, 515
 take_n_times, 515
 to_result, 515
mln::accu::stat::max, 515
 init, 516
 is_valid, 516
 set_value, 516
 take_as_init, 516
 take_n_times, 516
 to_result, 516
mln::accu::stat::max_h, 517
 init, 517
 is_valid, 517
 take_as_init, 518
 take_n_times, 518
 to_result, 518
mln::accu::stat::mean, 518
 count, 519
 init, 519
 is_valid, 519
 sum, 519
 take_as_init, 519
 take_n_times, 520
 to_result, 520
mln::accu::stat::median_alt, 520
 is_valid, 521
 take, 521
 take_as_init, 521
 take_n_times, 521
 to_result, 521
mln::accu::stat::median_h, 522
 init, 523
 is_valid, 523
 take_as_init, 523
 take_n_times, 523
 to_result, 523
mln::accu::stat::meta::deviation, 523
mln::accu::stat::min, 524
 init, 525
 is_valid, 525
 set_value, 525
 take_as_init, 525
 take_n_times, 525
 to_result, 526
mln::accu::stat::min_h, 526
 init, 527
 is_valid, 527
 take_as_init, 527
 take_n_times, 527
 to_result, 527
mln::accu::stat::min_max, 527
 first, 529
 first_accu, 529
 init, 529
 is_valid, 529
 second, 529
 second_accu, 529
 take_as_init, 529
 take_n_times, 530
 to_result, 530
mln::accu::stat::rank, 530
 init, 531
 is_valid, 531
 k, 531
 take_as_init, 531
 take_n_times, 531
 to_result, 531
mln::accu::stat::rank< bool >, 532
 init, 532
 is_valid, 532
 take_as_init, 533
 take_n_times, 533
 to_result, 533
mln::accu::stat::rank_high_quant, 533
 init, 534
 is_valid, 534
 take_as_init, 534
 take_n_times, 534
 to_result, 534
mln::accu::stat::var, 535
 init, 536
 is_valid, 536
 mean, 536
 mean_t, 536
 n_items, 536
 take_as_init, 536
 take_n_times, 536
 to_result, 536
 variance, 537
mln::accu::stat::variance, 537
 init, 538
 is_valid, 538
 mean, 538
 n_items, 538
 standard_deviation, 538

sum, 539
 take_as_init, 539
 take_n_times, 539
 to_result, 539
 var, 539
 mln::accu::tuple, 539
 init, 540
 is_valid, 540
 take_as_init, 540
 take_n_times, 541
 to_result, 541
 mln::accu::val, 541
 init, 542
 is_valid, 542
 take_as_init, 542
 take_n_times, 542
 to_result, 542
 mln::Accumulator, 542
 take_as_init, 544
 take_n_times, 544
 mln::algebra, 173
 ldlt_decomp, 174
 ldlt_solve, 174
 operator*, 174
 vprod, 174
 mln::algebra::h_mat, 544
 _1, 546
 h_mat, 545
 t, 546
 mln::algebra::h_vec, 546
 h_vec, 547
 operator mat< n, 1, U >, 547
 origin, 548
 t, 547
 to_vec, 548
 zero, 548
 mln::arith, 175
 diff_abs, 177
 div, 177
 div_cst, 178
 div_inplace, 178
 min, 179
 min_inplace, 179
 minus, 179, 180
 minus_cst, 180, 181
 minus_cst_inplace, 181
 minus_inplace, 182
 plus, 182, 183
 plus_cst, 183, 184
 plus_cst_inplace, 184
 plus_inplace, 185
 revert, 185
 revert_inplace, 186
 times, 186
 times_cst, 186
 times_inplace, 187
 mln::arith::impl, 187
 mln::arith::impl::generic, 188
 mln::binarization, 188
 binarization, 188
 threshold, 188
 mln::bkd_pixter1d, 548
 bkd_pixter1d, 549
 image, 549
 next, 549
 mln::bkd_pixter2d, 549
 bkd_pixter2d, 550
 image, 550
 next, 550
 mln::bkd_pixter3d, 551
 bkd_pixter3d, 552
 image, 551
 next, 552
 mln::border, 189
 adjust, 190
 duplicate, 190
 equalize, 190
 fill, 191
 find, 191
 get, 191
 mirror, 192
 resize, 192
 mln::border::impl, 192
 mln::border::impl::generic, 193
 mln::Box, 560
 bbox, 563
 diff, 564
 inter, 564
 is_empty, 563
 len, 563
 nsites, 563
 operator<, 564
 operator<<, 564
 operator<=, 564, 565
 operator==, 565
 sym_diff, 565
 uni, 565
 unique, 565
 mln::box, 552
 bbox, 557
 bkd_piter, 555
 box, 556
 crop_wrt, 557
 element, 555
 enlarge, 557
 fwd_piter, 555
 has, 557
 is_empty, 558

is_valid, 558
len, 558
memory_size, 558
merge, 558
nsites, 558
operator<<, 560
pcenter, 559
piter, 556
pmax, 559
pmin, 559
psite, 556
site, 556
to_larger, 559
mln::box_runend_piter, 566
 box_runend_piter, 566
 next, 567
 run_length, 567
mln::box_runstart_piter, 567
 box_runstart_piter, 568
 next, 568
 run_length, 568
mln::Browsing, 568
mln::canvas, 193
 distance_front, 194
 distance_geodesic, 194
mln::canvas::browsing, 194
mln::canvas::browsing::backdiagonal2d_t, 569
mln::canvas::browsing::breadth_first_search_t, 571
mln::canvas::browsing::depth_first_search_t, 571
mln::canvas::browsing::diagonal2d_t, 571
mln::canvas::browsing::dir_struct_elt_incr_-
 update_t, 573
mln::canvas::browsing::directional_t, 574
mln::canvas::browsing::fwd_t, 576
mln::canvas::browsing::hyper_directional_t, 577
mln::canvas::browsing::snake_fwd_t, 579
mln::canvas::browsing::snake_generic_t, 580
mln::canvas::browsing::snake_vert_t, 582
mln::canvas::chamfer, 583
mln::canvas::impl, 195
mln::canvas::labeling, 195
 blobs, 196
mln::canvas::labeling::impl, 196
mln::canvas::morpho, 197
mln::category< R(*)(A) >, 583
mln::complex_image, 584
 complex_image, 586
 dim, 586
 domain, 586
 geom, 585
 lvalue, 585
 operator(), 586
 rvalue, 585
 skeleton, 585
 value, 585
 values, 586
mln::complex_neighborhood_bkd_piter, 587
 complex_neighborhood_bkd_piter, 588
 iter, 588
 iter_type, 587
 next, 588
 psite, 587
mln::complex_neighborhood_fwd_piter, 588
 complex_neighborhood_fwd_piter, 589
 iter, 590
 iter_type, 589
 next, 590
 psite, 589
mln::complex_psite, 590
 change_target, 591
 complex_psite, 591
 face, 592
 face_id, 592
 invalidate, 592
 is_valid, 592
 n, 592
 site_set, 592
mln::complex_window_bkd_piter, 593
 complex_window_bkd_piter, 594
 iter, 594
 iter_type, 594
 next, 594
 psite, 594
mln::complex_window_fwd_piter, 595
 complex_window_fwd_piter, 596
 iter, 596
 iter_type, 595
 next, 596
 psite, 595
mln::convert, 197
 from_to, 199, 200
 mln_image_from_grid, 200
 mln_window, 200
 to, 200
 to_dpoint, 201
 to_fun, 201, 203
 to_image, 201
 to_p_array, 201
 to_p_set, 201, 202
 to_qimage, 202
 to_upper_window, 202, 203
 to_window, 203
mln::data, 203
 abs, 206
 abs_inplace, 206
 apply, 206
 compute, 206, 207
 convert, 207

fast_median, 207
 fill, 208
 fill_with_image, 208
 fill_with_value, 208
 median, 209
 mln_meta_accu_result, 209
 paste, 209
 paste_without_localization, 210
 replace, 210
 saturate, 210, 211
 saturate_inplace, 211
 sort_offsets_increasing, 211
 sort_psites_decreasing, 211
 sort_psites_increasing, 212
 stretch, 212
 to_enc, 212
 transform, 213
 transform_inplace, 213, 214
 update, 214
 wrap, 214
 mln::data::approx, 215
 median, 215, 216
 mln::data::approx::impl, 217
 mln::data::impl, 217
 paste_without_localization_fast, 218
 paste_without_localization_fastest, 218
 paste_without_localization_lines, 218
 stretch, 219
 transform_inplace_lowq, 219
 update_fastest, 219
 mln::data::impl::generic, 220
 fill_with_image, 221
 fill_with_value, 221
 paste, 221
 transform, 221, 222
 transform_inplace, 222
 update, 223
 mln::data::naive, 223
 median, 223
 mln::data::naive::impl, 224
 mln::debug, 224
 draw_graph, 226
 filename, 227
 format, 227
 iota, 228
 mosaic, 228
 println, 228
 println_with_border, 228
 put_word, 229
 slices_2d, 229
 superpose, 229
 z_order, 230
 mln::debug::impl, 230
 mln::decorated_image, 596
 ~decorated_image, 598
 decorated_image, 598
 decoration, 598
 lvalue, 597
 operator decorated_image< const I, D >, 599
 operator(), 599
 psite, 598
 rvalue, 598
 skeleton, 598
 mln::def, 230
 coord, 231
 coodrf, 231
 mln::Delta_Point_Site< void >, 599
 mln::display, 231
 mln::display::impl, 232
 mln::display::impl::generic, 232
 mln::doc, 232
 mln::doc::Accumulator, 599
 argument, 600
 init, 600
 take, 600
 mln::doc::Box, 601
 bbox, 603
 bkd_piter, 602
 fwd_piter, 602
 has, 603
 nsites, 603
 pmax, 603
 pmin, 603
 psite, 602
 site, 602
 mln::doc::Dpoint, 604
 coord, 605
 dim, 605
 dpoint, 605
 point, 605
 mln::doc::Fastest_Image, 606
 bbox, 610
 bkd_piter, 608
 border, 610
 buffer, 611
 coord, 608
 delta_index, 611
 domain, 611
 dpoint, 608
 fwd_piter, 609
 has, 611
 is_valid, 612
 lvalue, 609
 nelements, 612
 nsites, 612
 operator(), 612
 point, 609
 point_at_index, 613

pset, 609
psite, 609
rvalue, 610
skeleton, 610
value, 610
values, 614
vset, 610
mln::doc::Generalized_Pixel, 614
 ima, 616
 image, 615
 rvalue, 615
 val, 616
 value, 615
mln::doc::Image, 616
 bbox, 620
 bkd_piter, 618
 coord, 618
 domain, 620
 dpoint, 618
 fwd_piter, 618
 has, 620
 is_valid, 621
 lvalue, 619
 nsites, 621
 operator(), 621
 point, 619
 pset, 619
 psite, 619
 rvalue, 619
 skeleton, 619
 value, 620
 values, 621
 vset, 620
mln::doc::Iterator, 622
 invalidate, 623
 is_valid, 623
 start, 623
mln::doc::Neighborhood, 623
 bkd_niter, 624
 dpoint, 624
 fwd_niter, 624
 niter, 624
 point, 624
mln::doc::Object, 625
mln::doc::Pixel_Iterator, 625
 ima, 627
 image, 627
 invalidate, 628
 is_valid, 628
 lvalue, 627
 rvalue, 627
 start, 628
 val, 628
 value, 627
mln::doc::Point_Site
 dim, 630
mln::doc::Point_Site, 628
 coord, 629
 dpoint, 629
 mesh, 629
 point, 629
 to_point, 630
mln::doc::Site_Iterator, 631
 invalidate, 632
 is_valid, 632
 operator psite, 632
 psite, 632
 start, 632
mln::doc::Site_Set, 633
 bkd_piter, 634
 fwd_piter, 634
 has, 634
 psite, 634
 site, 634
mln::doc::Value_Iterator, 635
 invalidate, 636
 is_valid, 636
 operator value, 636
 start, 636
 value, 636
mln::doc::Value_Set, 636
 bkd_viter, 638
 fwd_viter, 638
 has, 638
 index_of, 638
 nvalues, 638
 value, 638
mln::doc::Weighted_Window, 639
 bkd_qiter, 640
 delta, 641
 dpoint, 640
 fwd_qiter, 640
 is_centered, 641
 is_empty, 641
 point, 640
 sym, 641
 weight, 641
 win, 641
 window, 641
mln::doc::Window, 641
 bkd_qiter, 642
 fwd_qiter, 642
 qiter, 643
mln::Dpoint, 643
 to_dpoint, 643
mln::dpoint, 644
 coord, 645
 dim, 646

dpoint, 646, 647
 grid, 645
 operator `mln::algebra::vec< dpoint< G, C >::dim, Q >`, 647
 psite, 646
 set_all, 648
 site, 646
 to_vec, 648
 vec, 646
`mln::dpoints_bkd_pixter`, 648
 center_val, 651
`dpoints_bkd_pixter`, 650
 invalidate, 651
 is_valid, 651
 next, 651
 start, 651
 update, 651
`mln::dpoints_fwd_pixter`, 652
 center_val, 654
`dpoints_fwd_pixter`, 653
 invalidate, 654
 is_valid, 654
 next, 654
 start, 654
 update, 654
`mln::draw`, 234
 box, 234
 box_plain, 234
 dashed_line, 235
 line, 235
 plot, 236
 polygon, 236
 site_set, 236
`mln::Edge`, 655
`mln::edge_image`, 655
 edge_image, 657
 edge_nbh_t, 656
 edge_win_t, 656
 graph_t, 656
 nbh_t, 656
 operator(), 657
 site_function_t, 656
 skeleton, 657
 win_t, 657
`mln::estim`, 237
 mean, 238
 min_max, 238
 sum, 238, 239
`mln::extended`, 657
 domain, 659
 extended, 658
 skeleton, 658
 value, 658
`mln::extension`, 239
 adjust, 240
 adjust_duplicate, 241
 adjust_fill, 241
 duplicate, 241
 fill, 241
`mln::extension_fun`, 659
 extension, 661
 extension_fun, 660
 has, 661
 operator(), 661
 rvalue, 660
 skeleton, 660
 value, 660
`mln::extension_ima`, 661
 extension, 663
 extension_ima, 663
 has, 663
 operator(), 663
 rvalue, 662
 skeleton, 662
 value, 663
`mln::extension_val`, 664
 change_extension, 665
 extension, 665
 extension_val, 665
 has, 666
 operator(), 666
 rvalue, 665
 skeleton, 665
 value, 665
`mln::faces_psite`, 666
 change_target, 668
 face, 668
 face_id, 668
 faces_psite, 667
 invalidate, 668
 is_valid, 668
 n, 668
 site_set, 668
`mln::flat_image`, 669
 domain, 671
 flat_image, 670
 has, 671
 lvalue, 670
 operator(), 671
 rvalue, 670
 skeleton, 670
 value, 670
`mln::fun`, 242
`mln::fun::access`, 243
`mln::fun::from_accu`, 671
`mln::fun::i2v`, 243
 operator<<, 244
`mln::fun::n2v`, 244

mln::fun::n2v::white_gaussian, 672
mln::fun::p2b, 244
mln::fun::p2b::antilogy, 672
mln::fun::p2b::tautology, 673
mln::fun::p2p, 244
mln::fun::p2v, 245
mln::fun::stat, 245
mln::fun::v2b, 245
mln::fun::v2b::lnot, 675
mln::fun::v2b::threshold, 676
mln::fun::v2i, 245
mln::fun::v2v, 246
 f_hsi_to_rgb_3x8, 247
 f_hsl_to_rgb_3x8, 247
 f_rgb_to_hsi_f, 247
 f_rgb_to_hsl_f, 247
mln::fun::v2v::ch_function_value, 677
mln::fun::v2v::component, 678
mln::fun::v2v::l1_norm, 678
mln::fun::v2v::l2_norm, 679
mln::fun::v2v::linear, 680
mln::fun::v2v::linfty_norm, 681
mln::fun::v2v::rgb8_to_rgbn, 682
 operator(), 684
mln::fun::v2w2v, 247
mln::fun::v2w2v::cos, 684
mln::fun::v2w_w2v, 247
mln::fun::v2w_w2v::l1_norm, 685
mln::fun::v2w_w2v::l2_norm, 687
mln::fun::v2w_w2v::linfty_norm, 688
mln::fun::vv2b, 248
mln::fun::vv2b::eq, 689
mln::fun::vv2b::ge, 689
mln::fun::vv2b::gt, 690
mln::fun::vv2b::implies, 691
mln::fun::vv2b::le, 692
mln::fun::vv2b::lt, 693
mln::fun::vv2v, 249
mln::fun::vv2v::diff_abs, 694
mln::fun::vv2v::land, 695
mln::fun::vv2v::land_not, 696
mln::fun::vv2v::lor, 697
mln::fun::vv2v::lxor, 698
mln::fun::vv2v::max, 699
mln::fun::vv2v::min, 700
mln::fun::vv2v::vec, 701
mln::fun::x2p, 249
mln::fun::x2p::closest_point, 702
mln::fun::x2v, 250
mln::fun::x2v::bilinear, 703
 operator(), 703
mln::fun::x2v::trilinear, 704
mln::fun::x2x, 250
mln::fun::x2x::composed, 704
 composed, 705
mln::fun::x2x::linear, 705
 ima, 706
 linear, 706
 operator(), 706
mln::fun::x2x::rotation, 706
 data_t, 708
 inv, 709
 invert, 708
 operator(), 709
 rotation, 708, 709
 set_alpha, 709
 set_axis, 709
mln::fun::x2x::translation, 710
 data_t, 711
 inv, 712
 invert, 711
 operator(), 712
 set_t, 712
 t, 712
 translation, 711
mln::fun_image, 712
 fun_image, 714
 lvalue, 713
 operator(), 714
 rvalue, 713
 skelton, 713
 value, 714
mln::Function, 715
 Function, 715
mln::Function< void >, 715
mln::Function_n2v, 716
mln::Function_v2b, 716
mln::Function_v2v, 717
mln::Function_vv2b, 718
mln::Function_vv2v, 718
mln::fwd_pixter1d, 719
 fwd_pixter1d, 720
 image, 720
 next, 720
mln::fwd_pixter2d, 720
 fwd_pixter2d, 721
 image, 721
 next, 722
mln::fwd_pixter3d, 722
 fwd_pixter3d, 723
 image, 722
 next, 723
mln::Gdpoint, 723
mln::Gdpoint< void >, 724
mln::geom, 250
 bbox, 255
 chamfer, 255
 delta, 256

horizontal_symmetry, 256
 max_col, 256
 max_ind, 256
 max_row, 257
 max_sli, 257
 mesh_corner_point_area, 257
 mesh_curvature, 258
 mesh_normal, 258
 min_col, 258
 min_ind, 259
 min_row, 259
 min_sli, 259
 ncols, 259
 ninds, 260
 nrows, 260
 nsites, 260
 nslis, 260
 pmin_pmax, 260, 261
 rotate, 261, 262
 seeds2tiling, 262
 seeds2tiling_roundness, 263
 translate, 263, 264
 vertical_symmetry, 264
 mln::geom::complex_geometry, 725
 add_location, 726
 complex_geometry, 725
 operator(), 726
 mln::geom::impl, 264
 seeds2tiling, 265
 mln::Gpoint, 726
 operator<<, 730
 operator+, 728
 operator+=, 728
 operator-, 729
 operator-=, 729
 operator/, 730
 operator==, 730
 mln::Graph, 731
 mln::graph, 265
 compute, 266
 labeling, 266
 to_neighb, 266
 to_win, 267
 mln::graph::attribute::card_t, 732
 result, 732
 mln::graph::attribute::representative_t, 732
 result, 733
 mln::graph_elt_mixed_neighborhood, 733
 bkd_niter, 734
 fwd_niter, 734
 niter, 734
 mln::graph_elt_mixed_window, 734
 bkd_qiter, 736
 center_t, 736
 delta, 737
 fwd_qiter, 736
 graph_element, 737
 is_centered, 737
 is_empty, 738
 is_symmetric, 738
 is_valid, 738
 psite, 737
 qiter, 737
 site, 737
 sym, 738
 target, 737
 mln::graph_elt_neighborhood, 738
 bkd_niter, 740
 fwd_niter, 740
 niter, 740
 mln::graph_elt_neighborhood_if, 740
 bkd_niter, 741
 fwd_niter, 741
 graph_elt_neighborhood_if, 742
 mask, 742
 niter, 741
 mln::graph_elt_window, 742
 bkd_qiter, 744
 center_t, 744
 delta, 745
 fwd_qiter, 744
 graph_element, 745
 is_centered, 745
 is_empty, 746
 is_symmetric, 746
 is_valid, 746
 psite, 745
 qiter, 745
 site, 745
 sym, 746
 target, 745
 mln::graph_elt_window_if, 746
 bkd_qiter, 748
 change_mask, 750
 delta, 750
 fwd_qiter, 748
 graph_elt_window_if, 750
 is_centered, 750
 is_empty, 750
 is_symmetric, 750
 is_valid, 751
 mask, 751
 mask_t, 749
 psite, 749
 qiter, 749
 site, 749
 sym, 751
 target, 749

mln::graph_window_base, 751
 delta, 752
 is_centered, 752
 is_empty, 752
 is_symmetric, 753
 is_valid, 753
 site, 752
 sym, 753
mln::graph_window_if_piter, 753
 element, 754
 graph_window_if_piter, 754
 id, 754
 next, 755
 P, 754
mln::graph_window_piter, 755
 center_t, 756
 change_target_site_set, 757
 element, 758
 graph_element, 756
 graph_window_piter, 757
 id, 758
 next, 758
 P, 756
 target_site_set, 758
mln::grid, 267
mln::hexa, 758
 bkd_piter, 760
 domain, 761
 fwd_piter, 760
 has, 761
 hexa, 761
 lvalue, 760
 operator(), 762
 psite, 760
 rvalue, 761
 skeleton, 761
 value, 761
mln::histo, 267
 compute, 268
 equalize, 268
mln::histo::array, 762
mln::histo::impl, 269
mln::histo::impl::generic, 269
mln::Image, 762
mln::image1d, 764
 bbox, 767
 border, 767
 buffer, 767
 delta_index, 767
 domain, 767
 element, 767
 has, 768
 image1d, 766
 lvalue, 766
nelements, 768
ninds, 768
operator(), 768
point_at_index, 768
rvalue, 766
skeleton, 766
value, 766
vbbox, 769
mln::image2d, 769
 bbox, 772
 border, 772
 buffer, 772
 delta_index, 772
 domain, 772
 element, 772
 has, 773
 image2d, 771
 lvalue, 771
 ncols, 773
 nelements, 773
 nrows, 773
 operator(), 773
 point_at_index, 773
 rvalue, 771
 skeleton, 771
 value, 771
mln::image2d_h, 774
 bkd_piter, 775
 domain, 776
 fwd_piter, 775
 has, 776
 image2d_h, 776
 lvalue, 775
 operator(), 777
 psite, 776
 rvalue, 776
 skeleton, 776
 value, 776
mln::image3d, 777
 bbox, 780
 border, 780
 buffer, 780
 delta_index, 780
 domain, 781
 element, 781
 has, 781
 image3d, 780
 lvalue, 779
 ncols, 781
 nelements, 781
 nrows, 782
 nslis, 782
 operator(), 782
 point_at_index, 782

rvalue, 779
 skeleton, 779
 value, 779
 vbbox, 782
 mln::image_if, 782
 domain, 784
 image_if, 783
 operator image_if< const I, F >, 784
 skeleton, 783
 mln::impl, 269
 mln::interpolated, 784
 has, 786
 interpolated, 786
 is_valid, 786
 lvalue, 785
 psite, 785
 rvalue, 785
 skeleton, 785
 value, 785
 mln::io, 269
 mln::io::cloud, 271
 load, 271
 save, 271
 mln::io::dicom, 272
 get_header, 272
 load, 272
 mln::io::dicom::dicom_header, 786
 mln::io::dump, 273
 get_header, 273
 load, 273
 save, 274
 mln::io::dump::dump_header, 786
 mln::io::fits, 274
 load, 274, 275
 mln::io::fld, 275
 load, 276
 read_header, 276
 write_header, 276
 mln::io::fld::fld_header, 787
 mln::io::magick, 276
 load, 277
 save, 277
 mln::io::off, 278
 load, 278
 save, 279
 save_bin_alt, 279
 mln::io::pbm, 279
 load, 280
 save, 280
 mln::io::pbm::impl, 281
 mln::io::pbms, 281
 load, 281
 mln::io::pbms::impl, 282
 mln::io::pfm, 282
 load, 283
 save, 283
 mln::io::pfm::impl, 283
 mln::io::pgm, 284
 load, 284
 save, 284
 mln::io::pgms, 285
 load, 285
 mln::io::plot, 285
 load, 286
 save, 286, 287
 mln::io::pnm, 287
 load, 288
 load_ascii_builtin, 288
 load_ascii_value, 288
 load_raw_2d, 288
 max_component, 289
 save, 289
 mln::io::pnms::impl, 289
 mln::io::pnms, 289
 load, 290
 mln::io::ppm, 290
 load, 291
 save, 291
 mln::io::ppms, 292
 load, 292
 mln::io::raw, 292
 get_header, 293
 load, 293
 save, 293
 mln::io::raw::raw_header, 787
 mln::io::tiff, 294
 load, 294
 mln::io::txt, 294
 save, 295
 mln::Iterator, 787
 next, 789
 mln::labeled_image, 789
 bbox, 792
 bbox_t, 791
 bboxes, 792
 labeled_image, 791
 nlabels, 792
 relabel, 792
 skeleton, 791
 subdomain, 792
 update_data, 792
 mln::labeled_image_base, 793
 bbox, 795
 bbox_t, 794
 bboxes, 795
 labeled_image_base, 794
 nlabels, 795
 relabel, 795

subdomain, 795
update_data, 796
mln::labeling, 295
 background, 298
 blobs, 299
 blobs_and_compute, 299
 colorize, 299, 300
 compute, 300–302
 compute_image, 302, 303
 fill_holes, 304
 flat_zones, 304
 foreground, 304
 pack, 305
 pack_inplace, 306
 regional_maxima, 306
 regional_minima, 306
 relabel, 307
 relabel_inplace, 308
 superpose, 308
 value, 309
 value_and_compute, 309
 wrap, 310
mln::labeling::impl, 310
 compute_fastest, 311
mln::labeling::impl::generic, 312
 compute, 313, 314
mln::lazy_image, 796
 domain, 798
 has, 798
 lazy_image, 798
 lvalue, 797
 operator(), 798
 rvalue, 797
 skeleton, 797
mln::linear, 314
 gaussian, 315
 gaussian_1st_derivative, 316
 gaussian_2nd_derivative, 316
 mln_ch_convolve, 317
 mln_ch_convolve_grad, 318
mln::linear::impl, 318
mln::linear::local, 318
 convolve, 319
mln::linear::local::impl, 319
mln::Literal, 799
mln::literal, 319
 black, 323
 blue, 323
 brown, 323
 cyan, 323
 dark_gray, 323
 green, 323
 identity, 323
 light_gray, 323
 lime, 323
 magenta, 324
 max, 324
 medium_gray, 324
 min, 324
 olive, 324
 one, 324
 orange, 324
 origin, 324
 pink, 325
 purple, 325
 red, 325
 teal, 325
 violet, 325
 white, 325
 yellow, 325
 zero, 325
mln::literal::black_t, 801
mln::literal::blue_t, 802
mln::literal::brown_t, 802
mln::literal::cyan_t, 803
mln::literal::green_t, 804
mln::literal::identity_t, 805
mln::literal::light_gray_t, 806
mln::literal::lime_t, 807
mln::literal::magenta_t, 808
mln::literal::max_t, 809
mln::literal::min_t, 810
mln::literal::olive_t, 811
mln::literal::one_t, 812
mln::literal::orange_t, 813
mln::literal::origin_t, 814
mln::literal::pink_t, 815
mln::literal::purple_t, 816
mln::literal::red_t, 817
mln::literal::teal_t, 818
mln::literal::violet_t, 819
mln::literal::white_t, 820
mln::literal::yellow_t, 821
mln::literal::zero_t, 822
mln::logical, 326
 and_inplace, 327
 and_not, 327
 and_not_inplace, 327
 not_inplace, 328
 or_inplace, 328
 xor_inplace, 329
mln::logical::impl, 329
mln::logical::impl::generic, 329
mln::make, 330
 attachment, 335
 box1d, 335, 336
 box2d, 336
 box2d_h, 337

box3d, 338
 cell, 338
 couple, 339
 detachment, 339
 dpoint2d_h, 339
 dummy_p_edges, 340
 dummy_p_vertices, 340, 341
 edge_image, 341, 342
 h_mat, 343
 image, 343, 344
 image2d, 344
 image3d, 344
 influence_zone_adjacency_graph, 344
 mat, 345
 ord_pair, 345
 p_edges_with_mass_centers, 345
 p_vertices_with_mass_centers, 346
 pix, 346
 pixel, 346
 point2d_h, 347
 rag_and_labeled_wsl, 347
 region_adjacency_graph, 348
 relabelfun, 348
 vec, 349, 350
 vertex_image, 350
 voronoi, 351
 w_window, 351
 w_window1d, 351
 w_window1d_int, 352
 w_window2d, 352
 w_window2d_int, 353
 w_window3d, 353
 w_window3d_int, 353
 w_window_directional, 354
 mln::math, 354
 abs, 355
 mln::Mesh, 823
 mln::Meta_Accumulator, 824
 mln::Meta_Function, 826
 mln::Meta_Function_v2v, 827
 mln::Meta_Function_vv2v, 827
 mln::metal, 355
 mln::metal::ands, 828
 mln::metal::converts_to, 828
 mln::metal::equal, 828
 mln::metal::goes_to, 829
 mln::metal::impl, 356
 mln::metal::is, 829
 mln::metal::is_a, 830
 mln::metal::is_not, 830
 mln::metal::is_not_a, 830
 mln::metal::math, 356
 mln::metal::math::impl, 357
 mln::mixed_neighb, 830
 bkd_niter, 831
 fwd_niter, 831
 mixed_neighb, 832
 niter, 831
 mln::morpho, 357
 complementation, 360
 complementation_inplace, 360
 contrast, 360
 dilation, 360
 erosion, 361
 general, 361
 gradient, 361
 gradient_external, 361
 gradient_internal, 361
 hit_or_miss, 362
 hit_or_miss_background_closing, 362
 hit_or_miss_background_opening, 362
 hit_or_miss_closing, 362
 hit_or_miss_opening, 362
 laplacian, 363
 line_gradient, 363
 meyer_wst, 363
 min, 364
 min_inplace, 364
 minus, 364
 plus, 364
 rank_filter, 365
 thick_miss, 365
 thickening, 365
 thin_fit, 365
 thinning, 365
 top_hat_black, 366
 top_hat_self_complementary, 366
 top_hat_white, 366
 mln::morpho::approx, 367
 mln::morpho::attribute, 367
 mln::morpho::attribute::card, 832
 init, 833
 is_valid, 833
 take_as_init, 833
 take_n_times, 833
 to_result, 833
 mln::morpho::attribute::count_adjacent_vertices,
 833
 init, 834
 is_valid, 834
 take_as_init, 834
 take_n_times, 834
 to_result, 834
 mln::morpho::attribute::height, 835
 base_level, 836
 init, 836
 is_valid, 836
 take_as_init, 836

take_n_times, 836
to_result, 836
mln::morpho::attribute::sharpness, 836
area, 837
height, 837
init, 838
is_valid, 838
take_as_init, 838
take_n_times, 838
to_result, 838
volume, 838
mln::morpho::attribute::sum, 839
init, 839
is_valid, 839
set_value, 840
take_as_init, 840
take_n_times, 840
to_result, 840
untake, 840
mln::morpho::attribute::volume, 840
area, 841
init, 841
is_valid, 841
take_as_init, 842
take_n_times, 842
to_result, 842
mln::morpho::closing::approx, 367
structural, 368
mln::morpho::elementary, 368
closing, 369
mln_trait_op_minus_twice, 369
opening, 369
top_hat_black, 369
top_hat_white, 369
mln::morpho::impl, 370
mln::morpho::impl::generic, 370
mln::morpho::opening::approx, 370
structural, 371
mln::morpho::reconstruction, 371
mln::morpho::reconstruction::by_dilation, 371
mln::morpho::reconstruction::by_erosion, 371
mln::morpho::tree, 372
compute_attribute_image, 373
compute_attribute_image_from, 374
compute_parent, 374
dual_input_max_tree, 375
max_tree, 376
min_tree, 376
propagate_if, 376, 377
propagate_if_value, 377
propagate_node_to_ancestors, 378
propagate_node_to_descendants, 378, 379
propagateRepresentative, 379
mln::morpho::tree::filter, 379
direct, 380
filter, 380
max, 380
min, 381
subtractive, 381
mln::morpho::watershed, 382
flooding, 382, 383
superpose, 383
topological, 383
mln::morpho::watershed::watershed, 384
mln::morpho::watershed::watershed::generic, 384
mln::neighb, 842
bkd_niter, 843
fwd_niter, 843
neighb, 843
niter, 843
mln::Neighborhood, 844
mln::Neighborhood< void >, 844
mln::norm, 384
l1, 385
l1_distance, 385
l2, 386
l2_distance, 386
linfty, 386
linfty_distance, 386
sqr_l2, 386
mln::norm::impl, 386
mln::Object, 844
mln::opt, 387
at, 388
mln::opt::impl, 388
mln::p2p_image, 845
domain, 846
fun, 846
operator(), 846, 847
p2p_image, 846
skeleton, 846
mln::p_array, 847
append, 850
bkd_piter, 849
change, 850
clear, 850
element, 849
fwd_piter, 849
has, 850, 851
i_element, 849
insert, 851
is_valid, 851
memory_size, 851
nsites, 851
p_array, 850
piter, 849
psite, 849
reserve, 852

resize, 852
 std_vector, 852
 mln::p_centered, 852
 bkd_piter, 854
 center, 855
 element, 854
 fwd_piter, 854
 has, 855
 is_valid, 855
 memory_size, 855
 p_centered, 854
 piter, 854
 psite, 854
 site, 854
 window, 855
 mln::p_complex, 855
 bkd_piter, 857
 cplx, 858
 element, 857
 fwd_piter, 857
 geom, 858
 has, 858
 is_valid, 859
 nfaces, 859
 nfaces_of_dim, 859
 nsites, 859
 p_complex, 858
 piter, 857
 psite, 857
 mln::p_edges, 859
 bkd_piter, 861
 edge, 861
 element, 861
 fun_t, 862
 function, 864
 fwd_piter, 862
 graph, 864
 graph_element, 862
 graph_t, 862
 has, 864
 invalidate, 864
 is_valid, 864
 memory_size, 865
 nedges, 865
 nsites, 865
 p_edges, 863
 piter, 862
 psite, 862
 mln::p_faces, 865
 bkd_piter, 866
 cplx, 867, 868
 element, 866
 fwd_piter, 866
 is_valid, 868
 nfaces, 868
 nsites, 868
 p_faces, 867
 piter, 867
 psite, 867
 mln::p_graph_piter, 868
 graph, 869
 id, 869
 mln_q_subject, 869
 next, 870
 p_graph_piter, 869
 mln::p_if, 870
 bkd_piter, 871
 element, 871
 fwd_piter, 871
 has, 872
 is_valid, 872
 memory_size, 872
 overset, 872
 p_if, 872
 piter, 871
 pred, 873
 predicate, 873
 psite, 872
 mln::p_image, 873
 bkd_piter, 875
 clear, 876
 element, 875
 fwd_piter, 875
 has, 876
 i_element, 875
 insert, 876
 is_valid, 876
 memory_size, 876
 nsites, 877
 operator typename internal::p_image_site_-
 set< I >::ret, 877
 p_image, 876
 piter, 875
 psite, 875
 r_element, 875
 remove, 877
 S, 875
 toggle, 877
 mln::p_indexed_bkd_piter, 877
 index, 878
 next, 878
 p_indexed_bkd_piter, 878
 mln::p_indexed_fwd_piter, 879
 index, 880
 next, 880
 p_indexed_fwd_piter, 879
 mln::p_indexed_psite, 880
 mln::p_key, 880

bkd_piter, 882
change_key, 883
change_keys, 883
clear, 884
element, 882
exists_key, 884
fwd_piter, 882
has, 884
i_element, 883
insert, 884
is_valid, 885
key, 885
keys, 885
memory_size, 885
nsites, 885
operator(), 885
p_key, 883
piter, 883
psite, 883
r_element, 883
remove, 885
remove_key, 885
mln::p_line2d, 886
bbox, 888
begin, 888
bkd_piter, 887
element, 887
end, 889
fwd_piter, 887
has, 889
is_valid, 889
memory_size, 889
nsites, 889
p_line2d, 888
piter, 887
psite, 888
q_box, 888
std_vector, 890
mln::p_mutable_array_of, 890
bkd_piter, 891
clear, 892
element, 891
fwd_piter, 891
has, 892
i_element, 891
insert, 892
is_valid, 892
memory_size, 893
nelements, 893
p_mutable_array_of, 892
piter, 892
psite, 892
reserve, 893
mln::p_n_faces_bkd_piter, 893
n, 894
next, 894
p_n_faces_bkd_piter, 894
mln::p_n_faces_fwd_piter, 895
n, 895
next, 895
p_n_faces_fwd_piter, 895
mln::p_priority, 896
bkd_piter, 898
clear, 899
element, 898
exists_priority, 899
front, 899
fwd_piter, 898
has, 899
highest_priority, 899
i_element, 898
insert, 900
is_valid, 900
lowest_priority, 900
memory_size, 900
nsites, 900
operator(), 901
p_priority, 899
piter, 898
pop, 901
pop_front, 901
priorities, 901
psite, 898
push, 901
mln::p_queue, 902
bkd_piter, 903
clear, 904
element, 903
front, 904
fwd_piter, 903
has, 904, 905
i_element, 904
insert, 905
is_valid, 905
memory_size, 905
nsites, 905
p_queue, 904
piter, 904
pop, 905
pop_front, 906
psite, 904
push, 906
std_deque, 906
mln::p_queue_fast, 906
bkd_piter, 908
clear, 909
compute_has, 909
element, 908

empty, 909
 front, 909
 fwd_piter, 908
 has, 910
 i_element, 908
 insert, 910
 is_valid, 910
 memory_size, 910
 nsites, 910
 p_queue_fast, 909
 piter, 909
 pop, 911
 pop_front, 911
 psite, 909
 purge, 911
 push, 911
 reserve, 911
 std_vector, 911
 mln::p_run, 912
 bbox, 915
 bkd_piter, 913
 element, 913
 end, 915
 fwd_piter, 913
 has, 915
 has_index, 915
 init, 915
 is_valid, 915
 length, 916
 memory_size, 916
 nsites, 916
 p_run, 914
 piter, 914
 psite, 914
 q_box, 914
 start, 916
 mln::p_set, 916
 bkd_piter, 918
 clear, 919
 element, 918
 fwd_piter, 918
 has, 919
 i_element, 918
 insert, 920
 is_valid, 920
 memory_size, 920
 nsites, 920
 p_set, 919
 piter, 918
 psite, 919
 r_element, 919
 remove, 920
 std_vector, 920
 util_set, 920
 mln::p_set_of, 921
 bkd_piter, 922
 clear, 923
 element, 922
 fwd_piter, 922
 has, 923
 i_element, 922
 insert, 923
 is_valid, 923
 memory_size, 923
 nelements, 924
 p_set_of, 923
 piter, 922
 psite, 923
 mln::p_transformed, 924
 bkd_piter, 925
 element, 925
 function, 926
 fwd_piter, 925
 has, 926
 is_valid, 926
 memory_size, 926
 p_transformed, 926
 piter, 925
 primary_set, 927
 psite, 926
 mln::p_transformed_piter, 927
 change_target, 928
 next, 928
 p_transformed_piter, 928
 mln::p_vaccess, 928
 bkd_piter, 930
 element, 930
 fwd_piter, 930
 has, 931
 i_element, 930
 insert, 931, 932
 is_valid, 932
 memory_size, 932
 operator(), 932
 p_vaccess, 931
 piter, 930
 pset, 931
 psite, 931
 value, 931
 values, 932
 vset, 931
 mln::p_vertices, 932
 bkd_piter, 934
 element, 934
 fun_t, 935
 function, 937
 fwd_piter, 935
 graph, 937

graph_element, 935
graph_t, 935
has, 937
invalidate, 937
is_valid, 938
memory_size, 938
nsites, 938
nvertices, 938
operator(), 938
p_vertices, 936
piter, 935
psite, 935
vertex, 935
mln::pixel, 939
 change_to, 940
 is_valid, 940
 pixel, 940
mln::Pixel_Iterator, 940
 next, 941
mln::plain, 942
 operator I, 943
 operator=, 943
 plain, 943
 skeleton, 942
mln::Point, 943
 operator+=, 945
 operator-=, 946
 operator/, 946
 point, 945
 to_point, 945
mln::point, 946
 coord, 949
 delta, 949
 dim, 950
 dpsite, 949
 grid, 949
 h_vec, 949
 last_coord, 951
 minus_infty, 951
 operator+=, 951
 operator-=, 951
 origin, 953
 plus_infty, 952
 point, 950, 951
 set_all, 952
 to_h_vec, 952
 to_vec, 952
 vec, 950
mln::Point_Site, 953
 operator<<, 956
 operator+, 954
 operator-, 955
 operator==, 956
mln::Point_Site< void >, 956
mln::Proxy, 957
mln::Proxy< void >, 957
mln::Pseudo_Site, 957
mln::Pseudo_Site< void >, 958
mln::pw, 389
mln::pw::image, 958
 image, 959
 skeleton, 959
mln::registration, 389
 get_rot, 390
 icp, 390, 391
 registration1, 391
 registration2, 391
 registration3, 391
mln::registration::closest_point_basic, 959
mln::registration::closest_point_with_map, 960
mln::Regular_Grid, 960
mln::safe_image, 961
 operator safe_image< const I >, 961
 skeleton, 961
mln::select, 392
mln::select::p_of, 961
mln::set, 392
 card, 393
 compute, 393
 compute_with_weights, 393
 get, 394
 has, 394
 mln_meta_accu_result, 394
mln::Site, 962
mln::Site< void >, 963
mln::Site_Iterator, 963
 next, 965
mln::Site_Proxy, 965
mln::Site_Proxy< void >, 966
mln::Site_Set, 966
 diff, 968
 inter, 968
 operator<, 968
 operator<<, 968
 operator<=, 968
 operator==, 968
 sym_diff, 969
 uni, 969
 unique, 969
mln::Site_Set< void >, 969
mln::slice_image, 969
 domain, 971
 operator slice_image< const I >, 971
 operator(), 971
 skeleton, 970
 sli, 971
 slice_image, 971
mln::sub_image, 972

domain, 973
 operator sub_image< const I, S >, 973
 skeleton, 972
 sub_image, 973
 mln::sub_image_if, 973
 domain, 974
 skeleton, 974
 sub_image_if, 974
 mln::subsampling, 394
 antialiased, 395
 gaussian_subsampling, 395
 subsampling, 396
 mln::tag, 396
 mln::test, 396
 positive, 397
 predicate, 397, 398
 mln::test::impl, 398
 mln::thru_image, 975
 operator thru_image< const I, F >, 975
 mln::thrubin_image, 975
 operator thrubin_image< const I1, const I2, F >, 976
 psite, 976
 rvalue, 976
 skeleton, 976
 value, 976
 mln::topo, 398
 detach, 403
 edge, 403
 is_facet, 403
 make_algebraic_face, 403
 operator<, 405, 406
 operator<<, 406, 407
 operator+, 404
 operator-, 405
 operator==, 407, 408
 mln::topo::adj_higher_dim_connected_n_face_-
 bkd_iter, 977
 adj_higher_dim_connected_n_face_bkd_iter,
 977
 next, 978
 mln::topo::adj_higher_dim_connected_n_face_-
 fwd_iter, 978
 adj_higher_dim_connected_n_face_fwd_iter,
 979
 next, 979
 mln::topo::adj_higher_face_bkd_iter, 979
 adj_higher_face_bkd_iter, 980
 next, 980
 mln::topo::adj_higher_face_fwd_iter, 980
 adj_higher_face_fwd_iter, 981
 next, 981
 mln::topo::adj_lower_dim_connected_n_face_-
 bkd_iter, 981
 adj_lower_dim_connected_n_face_bkd_iter,
 982
 next, 982
 mln::topo::adj_lower_dim_connected_n_face_-
 fwd_iter, 982
 adj_lower_dim_connected_n_face_fwd_iter,
 983
 next, 983
 mln::topo::adj_lower_face_bkd_iter, 984
 adj_lower_face_bkd_iter, 984
 next, 984
 mln::topo::adj_lower_face_fwd_iter, 985
 adj_lower_face_fwd_iter, 985
 next, 985
 mln::topo::adj_lower_higher_face_bkd_iter, 986
 adj_lower_higher_face_bkd_iter, 986
 next, 987
 mln::topo::adj_lower_higher_face_fwd_iter, 987
 adj_lower_higher_face_fwd_iter, 988
 next, 988
 mln::topo::adj_m_face_bkd_iter, 988
 adj_m_face_bkd_iter, 989
 next, 989
 mln::topo::adj_m_face_fwd_iter, 989
 adj_m_face_fwd_iter, 990
 next, 991
 mln::topo::algebraic_face, 991
 algebraic_face, 993
 cplx, 993
 data, 993
 dec_face_id, 994
 dec_n, 994
 face_id, 994
 higher_dim_adj_faces, 994
 inc_face_id, 994
 inc_n, 994
 invalidate, 994
 is_valid, 995
 lower_dim_adj_faces, 995
 n, 995
 set_cplx, 995
 set_face_id, 995
 set_n, 995
 set_sign, 996
 sign, 996
 mln::topo::algebraic_n_face, 996
 algebraic_n_face, 998
 cplx, 998
 data, 998
 dec_face_id, 999
 face_id, 999
 higher_dim_adj_faces, 999
 inc_face_id, 999
 invalidate, 999

is_valid, 999
lower_dim_adj_faces, 1000
n, 1000
set_cplx, 1000
set_face_id, 1000
set_sign, 1000
sign, 1000
mln::topo::center_only_iter, 1001
center_only_iter, 1001
next, 1002
mln::topo::centered_bkd_iter_adapter, 1002
centered_bkd_iter_adapter, 1003
next, 1003
mln::topo::centered_fwd_iter_adapter, 1003
centered_fwd_iter_adapter, 1004
next, 1004
mln::topo::complex, 1004
add_face, 1006
addr, 1006
bkd_citer, 1005
complex, 1006
fwd_citer, 1005
nfacs, 1006
nfacs_of_dim, 1007
nfacs_of_static_dim, 1007
print, 1007
print_faces, 1007
mln::topo::face, 1007
cplx, 1010
data, 1010
dec_face_id, 1010
dec_n, 1010
face, 1009
face_id, 1010
higher_dim_adj_faces, 1010
inc_face_id, 1010
inc_n, 1011
invalidate, 1011
is_valid, 1011
lower_dim_adj_faces, 1011
n, 1011
set_cplx, 1011
set_face_id, 1011
set_n, 1012
mln::topo::face_bkd_iter, 1012
face_bkd_iter, 1013
next, 1013
start, 1013
mln::topo::face_fwd_iter, 1013
face_fwd_iter, 1014
next, 1014
start, 1014
mln::topo::is_n_face, 1014
mln::topo::is_simple_2d_t, 1015
mln::topo::is_simple_cell, 1016
D, 1019
mln_geom, 1018
operator(), 1018
psite, 1018
result, 1018
set_image, 1019
mln::topo::n_face, 1019
cplx, 1021
data, 1021
dec_face_id, 1021
face_id, 1021
higher_dim_adj_faces, 1021
inc_face_id, 1021
invalidate, 1022
is_valid, 1022
lower_dim_adj_faces, 1022
n, 1022
n_face, 1020
set_cplx, 1022
set_face_id, 1022
mln::topo::n_face_bkd_iter, 1023
n, 1024
n_face_bkd_iter, 1023
next, 1024
start, 1024
mln::topo::n_face_fwd_iter, 1024
n, 1025
n_face_fwd_iter, 1025
next, 1025
start, 1025
mln::topo::n_faces_set, 1026
add, 1027
faces, 1027
faces_type, 1026
reserve, 1027
mln::topo::skeleton::is_simple_point, 1027
mln::topo::static_n_face_bkd_iter, 1028
next, 1029
start, 1029
static_n_face_bkd_iter, 1028
mln::topo::static_n_face_fwd_iter, 1029
next, 1030
start, 1030
static_n_face_fwd_iter, 1030
mln::tr_image, 1030
domain, 1033
has, 1033
is_valid, 1033
lvalue, 1032
operator(), 1033
psite, 1032
rvalue, 1032
set_tr, 1033

site, 1032
 skeleton, 1032
 tr, 1033
 tr_image, 1032
 value, 1032
 mln::trace, 408
 mln::trait, 408
 mln::transform, 408
 distance_and_closest_point_geodesic, 410
 distance_and_influence_zone_geodesic, 411
 distance_front, 411
 distance_geodesic, 411
 hough, 411
 influence_zone_front, 412
 influence_zone_geodesic, 412
 influence_zone_geodesic_saturated, 413
 mln::unproject_image, 1033
 domain, 1034
 operator(), 1034, 1035
 unproject_image, 1034
 mln::util, 413
 display_branch, 417
 display_tree, 417
 lemmings, 417
 make_greater_point, 418
 make_greater_psite, 418
 operator<, 418
 operator<<, 418
 operator==, 418, 419
 ord_strict, 419
 ord_weak, 419
 tree_fast_to_image, 419
 tree_to_fast, 419
 tree_to_image, 420
 vertex_id_t, 417
 mln::util::adjacency_matrix, 1035
 adjacency_matrix, 1035, 1036
 mln::util::array, 1036
 append, 1039, 1040
 array, 1039
 bkd_eiter, 1038
 clear, 1040
 eiter, 1038
 element, 1038
 fill, 1040
 fwd_eiter, 1039
 is_empty, 1040
 last, 1040
 memory_size, 1041
 nelements, 1041
 operator(), 1041
 reserve, 1042
 resize, 1042
 result, 1039
 size, 1042
 std_vector, 1043
 mln::util::branch, 1043
 apex, 1044
 branch, 1043
 util_tree, 1044
 mln::util::branch_iter, 1044
 deepness, 1045
 invalidate, 1045
 is_valid, 1045
 next, 1045
 operator util::tree_node< T > &, 1045
 start, 1046
 mln::util::branch_iter_ind, 1046
 deepness, 1047
 invalidate, 1047
 is_valid, 1047
 next, 1047
 operator util::tree_node< T > &, 1047
 start, 1047
 mln::util::couple, 1047
 change_both, 1049
 change_first, 1049
 change_second, 1049
 first, 1049
 second, 1049
 mln::util::eat, 1049
 mln::util::edge, 1050
 category, 1052
 change_graph, 1052
 edge, 1052
 graph, 1052
 graph_t, 1052
 id, 1052
 id_t, 1052
 id_value_t, 1052
 invalidate, 1053
 is_valid, 1053
 ith_nbh_edge, 1053
 nmax_nbh_edges, 1053
 operator edge_id_t, 1053
 update_id, 1053
 v1, 1053
 v2, 1054
 v_other, 1054
 mln::util::fibonacci_heap, 1054
 clear, 1056
 fibonacci_heap, 1056
 front, 1056
 is_empty, 1056
 is_valid, 1057
 nelements, 1057
 operator=, 1057
 pop_front, 1057

push, 1057, 1058
mln::util::graph, 1058
add_edge, 1062
add_vertex, 1062
add_vertices, 1062
e_ith_nbh_edge, 1062
e_nmax, 1062
e_nmax_nbh_edges, 1063
edge, 1063
edge_fwd_iter, 1060
edge_nbh_edge_fwd_iter, 1060
edges, 1063
edges_set_t, 1060
edges_t, 1060
graph, 1061
has_e, 1063
has_v, 1063
is_subgraph_of, 1064
v1, 1064
v2, 1064
v_ith_nbh_edge, 1064
v_ith_nbh_vertex, 1064
v_nmax, 1064
v_nmax_nbh_edges, 1065
v_nmax_nbh_vertices, 1065
vertex, 1065
vertex_fwd_iter, 1061
vertex_nbh_edge_fwd_iter, 1061
vertex_nbh_vertex_fwd_iter, 1061
vertices_t, 1061
mln::util::greater_point, 1065
operator(), 1066
mln::util::greater_psite, 1066
operator(), 1066
mln::util::head, 1066
mln::util::ignore, 1067
mln::util::ilcell, 1067
mln::util::impl, 420
mln::util::line_graph, 1068
e_ith_nbh_edge, 1071
e_nmax, 1071
e_nmax_nbh_edges, 1071
edge, 1071
edge_fwd_iter, 1070
edge_nbh_edge_fwd_iter, 1070
edges_t, 1070
graph, 1072
has, 1072
has_e, 1072
has_v, 1072
is_subgraph_of, 1073
v1, 1073
v2, 1073
v_ith_nbh_edge, 1073
v_ith_nbh_vertex, 1073
v_nmax, 1073
v_nmax_nbh_edges, 1074
v_nmax_nbh_vertices, 1074
vertex, 1074
vertex_fwd_iter, 1070
vertex_nbh_edge_fwd_iter, 1070
vertex_nbh_vertex_fwd_iter, 1071
vertices_t, 1071
mln::util::nil, 1074
mln::util::node, 1075
mln::util::object_id, 1075
object_id, 1077
value_t, 1077
mln::util::ord, 1077
mln::util::ord_pair, 1077
change_both, 1079
change_first, 1079
change_second, 1079
first, 1079
second, 1079
mln::util::pix, 1080
ima, 1081
p, 1081
pix, 1081
psite, 1080
v, 1081
value, 1080
mln::util::set, 1081
bkd_eiter, 1084
clear, 1084
eiter, 1084
element, 1084
first_element, 1084
fwd_eiter, 1084
has, 1085
insert, 1085
is_empty, 1085
last_element, 1086
memory_size, 1086
nelements, 1086
remove, 1087
set, 1084
std_vector, 1087
mln::util::site_pair, 1087
first, 1088
pair, 1088
second, 1089
mln::util::soft_heap, 1089
~soft_heap, 1091
clear, 1091
element, 1090
is_empty, 1091
is_valid, 1091

nelements, 1091
 pop_front, 1091
 push, 1091, 1092
 soft_heap, 1090
 mln::util::timer, 1092
 mln::util::tracked_ptr, 1093
 ~tracked_ptr, 1094
 operator bool, 1094
 operator->, 1094
 operator=, 1095
 tracked_ptr, 1094
 mln::util::tree, 1095
 add_tree_down, 1096
 add_tree_up, 1096
 check_consistency, 1096
 main_branch, 1097
 root, 1097
 tree, 1096
 mln::util::tree_node, 1097
 add_child, 1099
 check_consistency, 1099
 children, 1100
 delete_tree_node, 1100
 elt, 1100
 parent, 1101
 print, 1101
 search, 1101
 search_rec, 1101
 set_parent, 1102
 tree_node, 1099
 mln::util::vertex, 1102
 Category, 1104
 change_graph, 1105
 edge_with, 1105
 graph, 1105
 graph_t, 1104
 id, 1105
 id_t, 1104
 id_value_t, 1104
 invalidate, 1105
 is_valid, 1105
 ith_nbh_edge, 1105
 ith_nbh_vertex, 1106
 nmax_nbh_edges, 1106
 nmax_nbh_vertices, 1106
 operator vertex_id_t, 1106
 other, 1106
 update_id, 1106
 vertex, 1104
 mln::util::yes, 1107
 mln::Value, 1107
 mln::value, 420
 cast, 427
 equiv, 427
 float01_16, 425
 float01_8, 425
 gl16, 425
 gl8, 425
 glf, 425
 int_s16, 425
 int_s32, 426
 int_s8, 426
 int_u12, 426
 int_u16, 426
 int_u32, 426
 int_u8, 426
 label_16, 426
 label_32, 426
 label_8, 426
 operator<<, 428–431
 operator*, 427
 operator+, 427, 428
 operator-, 428
 operator/, 428
 operator==, 431
 other, 432
 rgb16, 427
 rgb8, 427
 stack, 432
 mln::value::float01, 1109
 enc, 1110
 equiv, 1110
 float01, 1110
 nbits, 1110
 operator float, 1110
 set_nbits, 1111
 to_nbits, 1111
 value, 1111
 value_ind, 1111
 mln::value::float01_f, 1111
 float01_f, 1112
 operator float, 1112
 operator=, 1112
 value, 1112
 mln::value::graylevel, 1112
 graylevel, 1114
 operator=, 1115
 to_float, 1115
 value, 1115
 mln::value::graylevel_f, 1116
 graylevel_f, 1117
 operator graylevel< n >, 1117
 operator=, 1117, 1118
 value, 1118
 mln::value::impl, 432
 mln::value::int_s, 1118
 int_s, 1120
 one, 1120

operator int, 1120
operator=, 1120
zero, 1120
mln::value::int_u, 1121
int_u, 1122
next, 1122
operator unsigned, 1122
operator-, 1123
operator=, 1123
mln::value::int_u_sat, 1123
int_u_sat, 1124
one, 1125
operator int, 1124
operator+=, 1125
operator-=, 1125
operator=, 1125
zero, 1125
mln::value::Integer, 1125
mln::value::Integer< void >, 1126
mln::value::label, 1126
enc, 1127
label, 1128
next, 1128
operator unsigned, 1128
operator++, 1128
operator--, 1128
operator=, 1128, 1129
prev, 1129
mln::value::lut_vec, 1129
bkd_viter, 1131
fwd_viter, 1131
has, 1132
index_of, 1132
lut_vec, 1132
nvalues, 1132
value, 1131
mln::value::proxy, 1133
~proxy, 1135
enc, 1134
equiv, 1134
operator=, 1135
proxy, 1134
to_value, 1135
mln::value::qt::rgb32, 1135
operator=, 1137
red, 1137
rgb32, 1136
zero, 1137
mln::value::rgb, 1137
operator=, 1139
red, 1139
rgb, 1138
zero, 1139
mln::value::set, 1139

the, 1140
mln::value::sign, 1140
enc, 1141
equiv, 1141
one, 1142
operator int, 1142
operator=, 1142
sign, 1141
zero, 1142
mln::value::stack_image, 1142
domain_t, 1143
is_valid, 1144
lvalue, 1143
operator(), 1144, 1145
psite, 1143
rvalue, 1144
skeleton, 1144
stack_image, 1144
value, 1144
mln::value::super_value< sign >, 1145
mln::value::value_array, 1145
operator(), 1146
value_array, 1146
vset, 1146
mln::Value_Iterator, 1146
next, 1148
operator<<, 1148
mln::Value_Set, 1148
mln::Vertex, 1149
mln::vertex_image, 1150
graph_t, 1151
nbh_t, 1151
operator(), 1152
site_function_t, 1151
skeleton, 1151
vertex_image, 1152
vertex_nbh_t, 1151
vertex_win_t, 1151
win_t, 1151
mln::violent_cast_image, 1152
lvalue, 1153
operator(), 1154
rvalue, 1153
skeleton, 1153
value, 1153
violent_cast_image, 1154
mln::w_window, 1154
bkd_qiter, 1156
clear, 1156
dpsite, 1156
fwd_qiter, 1156
insert, 1156
is_symmetric, 1157
operator<<, 1158

operator==, 1158
 std_vector, 1157
 sym, 1157
 w, 1157
 w_window, 1156
 weight, 1156
 weights, 1157
 win, 1157
 mln::Weighted_Window, 1158
 operator-, 1159
 mln::win, 432
 diff, 434
 mln_regular, 434
 sym, 434
 mln::win::backdiag2d, 1159
 backdiag2d, 1160
 length, 1160
 mln::win::ball, 1160
 ball, 1161
 diameter, 1161
 mln::win::cube3d, 1161
 cube3d, 1162
 length, 1162
 mln::win::cuboid3d, 1162
 cuboid3d, 1163
 depth, 1164
 height, 1164
 volume, 1164
 width, 1164
 mln::win::diag2d, 1164
 diag2d, 1165
 length, 1165
 mln::win::line, 1165
 length, 1167
 line, 1166
 size, 1167
 mln::win::multiple, 1167
 mln::win::multiple_size, 1167
 mln::win::octagon2d, 1168
 area, 1169
 length, 1169
 octagon2d, 1168
 mln::win::rectangle2d, 1169
 area, 1170
 height, 1170
 rectangle2d, 1170
 std_vector, 1170
 width, 1170
 mln::Window, 1170
 mln::window, 1171
 bkd_qiter, 1173
 clear, 1174
 delta, 1174
 dp, 1174
 fwd_qiter, 1173
 has, 1174
 insert, 1174
 is_centered, 1175
 is_empty, 1175
 is_symmetric, 1175
 operator==, 1176
 print, 1175
 qiter, 1173
 regular, 1173
 size, 1175
 std_vector, 1175
 sym, 1176
 window, 1173
 mln::world::inter_pixel::is_separator, 1176
 mln_ch_convolve
 mln::linear, 317
 mln_ch_convolve_grad
 mln::linear, 318
 mln_exact
 mln, 153
 mln_gen_complex_neighborhood
 mln, 153
 mln_gen_complex_window
 mln, 154
 mln_gen_complex_window_p
 mln, 154, 155
 mln_geom
 mln::topo::is_simple_cell, 1018
 mln_image_from_grid
 mln::convert, 200
 mln_meta_accu_result
 mln::accu, 166
 mln::data, 209
 mln::set, 394
 mln_q_subject
 mln::p_graph_piter, 869
 mln_regular
 mln, 155
 mln::win, 434
 mln_trait_op_geq
 mln, 155
 mln_trait_op_greater
 mln, 155
 mln_trait_op_leq
 mln, 156
 mln_trait_op_minus_twice
 mln::morpho::elementary, 369
 mln_trait_op_neq
 mln, 156
 mln_window
 mln::convert, 200
 modneighb1d
 c2, 102

n
 neighb1d, 102
 modneighb2d
 c2_col, 103
 c2_row, 103
 c4, 103
 c8, 104
 neighb2d, 103
 modneighb3d
 c18, 105
 c26, 105
 c2_3d_sli, 106
 c4_3d, 106
 c6, 107
 c8_3d, 107
 neighb3d, 105
 modwin1d
 segment1d, 112
 window1d, 113
 modwin2d
 disk2d, 114
 hline2d, 114
 vline2d, 114
 win_c4p, 115
 win_c8p, 115
 window2d, 114
 modwin3d
 sline3d, 116
 sphere3d, 116
 win_c4p_3d, 117
 win_c8p_3d, 117
 window3d, 117
 mosaic
 mln::debug, 228
 Multiple accumulators, 94
 Multiple windows, 118

n
 mln::complex_psite, 592
 mln::faces_psite, 668
 mln::p_n_faces_bkd_piter, 894
 mln::p_n_faces_fwd_piter, 895
 mln::topo::algebraic_face, 995
 mln::topo::algebraic_n_face, 1000
 mln::topo::face, 1011
 mln::topo::n_face, 1022
 mln::topo::n_face_bkd_iter, 1024
 mln::topo::n_face_fwd_iter, 1025

N-D windows, 118

n_face
 mln::topo::n_face, 1020
 n_face_bkd_iter
 mln::topo::n_face_bkd_iter, 1023
 n_face_fwd_iter
 mln::topo::n_face_fwd_iter, 1025

n_items
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 538

nbh_t
 mln::edge_image, 656
 mln::vertex_image, 1151

nbits
 mln::value::float01, 1110

ncols
 mln::geom, 259
 mln::image2d, 773
 mln::image3d, 781

nedges
 mln::p_edges, 865

neighb
 mln::neighb, 843

neighb1d
 modneighb1d, 102

neighb2d
 modneighb2d, 103

neighb3d
 modneighb3d, 105

Neighborhoods, 101

nelements
 mln::doc::Fastest_Image, 612
 mln::image1d, 768
 mln::image2d, 773
 mln::image3d, 781
 mln::pMutable_array_of, 893
 mln::p_set_of, 924
 mln::util::array, 1041
 mln::util::fibonacci_heap, 1057
 mln::util::set, 1086
 mln::util::soft_heap, 1091

next
 mln::bkd_pixter1d, 549
 mln::bkd_pixter2d, 550
 mln::bkd_pixter3d, 552
 mln::box_runend_piter, 567
 mln::box_runstart_piter, 568
 mln::complex_neighborhood_bkd_piter, 588
 mln::complex_neighborhood_fwd_piter, 590
 mln::complex_window_bkd_piter, 594
 mln::complex_window_fwd_piter, 596
 mln::dpoints_bkd_pixter, 651
 mln::dpoints_fwd_pixter, 654
 mln::fwd_pixter1d, 720
 mln::fwd_pixter2d, 722
 mln::fwd_pixter3d, 723
 mln::graph_window_if_piter, 755
 mln::graph_window_piter, 758
 mln::Iterator, 789
 mln::p_graph_piter, 870
 mln::p_indexed_bkd_piter, 878

mln::p_indexed_fwd_piter, 880
 mln::p_n_faces_bkd_piter, 894
 mln::p_n_faces_fwd_piter, 895
 mln::p_transformed_piter, 928
 mln::Pixel_Iterator, 941
 mln::Site_Iterator, 965
 mln::topo::adj_higher_dim_connected_n-face_bkd_iter, 978
 mln::topo::adj_higher_dim_connected_n-face_fwd_iter, 979
 mln::topo::adj_higher_face_bkd_iter, 980
 mln::topo::adj_higher_face_fwd_iter, 981
 mln::topo::adj_lower_dim_connected_n-face_bkd_iter, 982
 mln::topo::adj_lower_dim_connected_n-face_fwd_iter, 983
 mln::topo::adj_lower_face_bkd_iter, 984
 mln::topo::adj_lower_face_fwd_iter, 985
 mln::topo::adj_lower_higher_face_bkd_iter, 987
 mln::topo::adj_lower_higher_face_fwd_iter, 988
 mln::topo::adj_m_face_bkd_iter, 989
 mln::topo::adj_m_face_fwd_iter, 991
 mln::topo::center_only_iter, 1002
 mln::topo::centered_bkd_iter_adapter, 1003
 mln::topo::centered_fwd_iter_adapter, 1004
 mln::topo::face_bkd_iter, 1013
 mln::topo::face_fwd_iter, 1014
 mln::topo::n_face_bkd_iter, 1024
 mln::topo::n_face_fwd_iter, 1025
 mln::topo::static_n_face_bkd_iter, 1029
 mln::topo::static_n_face_fwd_iter, 1030
 mln::util::branch_iter, 1045
 mln::util::branch_iter_ind, 1047
 mln::value::int_u, 1122
 mln::value::label, 1128
 mln::Value_Iterator, 1148
 nfaces
 mln::p_complex, 859
 mln::p_faces, 868
 mln::topo::complex, 1006
 nffaces_of_dim
 mln::p_complex, 859
 mln::topo::complex, 1007
 nffaces_of_static_dim
 mln::topo::complex, 1007
 ninds
 mln::geom, 260
 mln::image1d, 768
 niter
 mln::doc::Neighborhood, 624
 mln::graph_elt_mixed_neighborhood, 734
 mln::graph_elt_neighborhood, 740
 nlabeled
 mln::labeled_image, 792
 mln::labeled_image_base, 795
 nmax_nbh_edges
 mln::util::edge, 1053
 mln::util::vertex, 1106
 nmax_nbh_vertices
 mln::util::vertex, 1106
 not_inplace
 mln::logical, 328
 nrows
 mln::geom, 260
 mln::image2d, 773
 mln::image3d, 782
 nsites
 mln::accu::center, 438
 mln::Box, 563
 mln::box, 558
 mln::doc::Box, 603
 mln::doc::Fastest_Image, 612
 mln::doc::Image, 621
 mln::geom, 260
 mln::p_array, 851
 mln::p_complex, 859
 mln::p_edges, 865
 mln::p_faces, 868
 mln::p_image, 877
 mln::p_key, 885
 mln::p_line2d, 889
 mln::p_priority, 900
 mln::p_queue, 905
 mln::p_queue_fast, 910
 mln::p_run, 916
 mln::p_set, 920
 mln::p_vertices, 938
 nslis
 mln::geom, 260
 mln::image3d, 782
 nvalues
 mln::doc::Value_Set, 638
 mln::value::lut_vec, 1132
 nvertices
 mln::p_vertices, 938
 object_id
 mln::util::object_id, 1077
 octagon2d
 mln::win::octagon2d, 1168
 olive
 mln::literal, 324
 On images, 91

On site sets, 91
On values, 92
one
 mln::literal, 324
 mln::value::int_s, 1120
 mln::value::int_u_sat, 1125
 mln::value::sign, 1142
opening
 mln::morpho::elementary, 369
operator bool
 mln::util::tracked_ptr, 1094
operator decorated_image< const I, D >
 mln::decorated_image, 599
operator edge_id_t
 mln::util::edge, 1053
operator float
 mln::value::float01, 1110
 mln::value::float01_f, 1112
operator graylevel< n >
 mln::value::graylevel_f, 1117
operator I
 mln::plain, 943
operator image_if< const I, F >
 mln::image_if, 784
operator int
 mln::value::int_s, 1120
 mln::value::int_u_sat, 1124
 mln::value::sign, 1142
operator mat< n, 1, U >
 mln::algebra::h_vec, 547
operator mln::algebra::vec< dpoint< G, C >::dim,
 Q >
 mln::dpoint, 647
operator psite
 mln::doc::Site_Iterator, 632
operator safe_image< const I >
 mln::safe_image, 961
operator slice_image< const I >
 mln::slice_image, 971
operator sub_image< const I, S >
 mln::sub_image, 973
operator thru_image< const I, F >
 mln::thru_image, 975
operator thrubin_image< const I1, const I2, F >
 mln::thrubin_image, 976
operator typename internal::p_image_site_set< I
 >::ret
 mln::p_image, 877
operator unsigned
 mln::value::int_u, 1122
 mln::value::label, 1128
operator util::tree_node< T > &
 mln::util::branch_iter, 1045
 mln::util::branch_iter_ind, 1047
operator value
 mln::doc::Value_Iterator, 636
operator vertex_id_t
 mln::util::vertex, 1106
operator<
 mln, 158
 mln::Box, 564
 mln::Site_Set, 968
 mln::topo, 405, 406
 mln::util, 418
operator<<
 mln, 158, 159
 mln::Box, 564
 mln::box, 560
 mln::fun::i2v, 244
 mln::Gpoint, 730
 mln::Point_Site, 956
 mln::Site_Set, 968
 mln::topo, 406, 407
 mln::util, 418
 mln::value, 428–431
 mln::Value_Iterator, 1148
 mln::w_window, 1158
operator<=

 mln, 159, 160
 mln::Box, 564, 565
 mln::Site_Set, 968
operator*
 mln, 157
 mln::algebra, 174
 mln::value, 427
operator()
 mln::complex_image, 586
 mln::decorated_image, 599
 mln::doc::Fastest_Image, 612
 mln::doc::Image, 621
 mln::edge_image, 657
 mln::extension_fun, 661
 mln::extension_ima, 663
 mln::extension_val, 666
 mln::flat_image, 671
 mln::fun::v2v::rgb8_to_rgbn, 684
 mln::fun::x2v::bilinear, 703
 mln::fun::x2x::linear, 706
 mln::fun::x2x::rotation, 709
 mln::fun::x2x::translation, 712
 mln::fun_image, 714
 mln::geom::complex_geometry, 726
 mln::hexa, 762
 mln::image1d, 768
 mln::image2d, 773
 mln::image2d_h, 777
 mln::image3d, 782
 mln::lazy_image, 798

mln::p2p_image, 846, 847
 mln::p_key, 885
 mln::p_priority, 901
 mln::p_vaccess, 932
 mln::p_vertices, 938
 mln::slice_image, 971
 mln::topo::is_simple_cell, 1018
 mln::tr_image, 1033
 mln::unproject_image, 1034, 1035
 mln::util::array, 1041
 mln::util::greater_point, 1066
 mln::util::greater_psite, 1066
 mln::value::stack_image, 1144, 1145
 mln::value::value_array, 1146
 mln::vertex_image, 1152
 mln::violent_cast_image, 1154
operator+
 mln::Gpoint, 728
 mln::Point_Site, 954
 mln::topo, 404
 mln::value, 427, 428
operator++
 mln, 157
 mln::value::label, 1128
operator+=
 mln::Gpoint, 728
 mln::Point, 945
 mln::point, 951
 mln::value::int_u_sat, 1125
operator-
 mln, 157
 mln::Gpoint, 729
 mln::Point_Site, 955
 mln::topo, 405
 mln::value, 428
 mln::value::int_u, 1123
 mln::Weighted_Window, 1159
operator->
 mln::util::tracked_ptr, 1094
operator--
 mln, 158
 mln::value::label, 1128
operator-=
 mln::Gpoint, 729
 mln::Point, 946
 mln::point, 951
 mln::value::int_u_sat, 1125
operator/
 mln::Gpoint, 730
 mln::Point, 946
 mln::value, 428
operator=
 mln::plain, 943
 mln::util::fibonacci_heap, 1057
 mln::util::tracked_ptr, 1095
 mln::value::float01_f, 1112
 mln::value::graylevel, 1115
 mln::value::graylevel_f, 1117, 1118
 mln::value::int_s, 1120
 mln::value::int_u, 1123
 mln::value::int_u_sat, 1125
 mln::value::label, 1128, 1129
 mln::value::proxy, 1135
 mln::value::qt::rgb32, 1137
 mln::value::rgb, 1139
 mln::value::sign, 1142
operator==
 mln, 160, 161
 mln::accu::stat, 173
 mln::Box, 565
 mln::Gpoint, 730
 mln::Point_Site, 956
 mln::Site_Set, 968
 mln::topo, 407, 408
 mln::util, 418, 419
 mln::value, 431
 mln::w_window, 1158
 mln::window, 1176
or_inplace
 mln::logical, 328
orange
 mln::literal, 324
ord_pair
 mln::make, 345
ord_strict
 mln::util, 419
ord_weak
 mln::util, 419
origin
 mln::algebra::h_vec, 548
 mln::literal, 324
 mln::point, 953
other
 mln::util::vertex, 1106
 mln::value, 432
overset
 mln::p_if, 872
P
 mln::graph_window_if_piter, 754
 mln::graph_window_piter, 756
p
 mln::util::pix, 1081
p2p_image
 mln::p2p_image, 846
p_array
 mln::p_array, 850
p_centered

mln::p_centered, 854
p_complex
 mln::p_complex, 858
p_edges
 mln::p_edges, 863
p_edges_with_mass_centers
 mln::make, 345
p_faces
 mln::p_faces, 867
p_graph_piter
 mln::p_graph_piter, 869
p_if
 mln::p_if, 872
p_image
 mln::p_image, 876
p_indexed_bkd_piter
 mln::p_indexed_bkd_piter, 878
p_indexed_fwd_piter
 mln::p_indexed_fwd_piter, 879
p_key
 mln::p_key, 883
p_line2d
 mln::p_line2d, 888
pMutable_array_of
 mln::pMutable_array_of, 892
p_n_faces_bkd_piter
 mln::p_n_faces_bkd_piter, 894
p_n_faces_fwd_piter
 mln::p_n_faces_fwd_piter, 895
p_priority
 mln::p_priority, 899
p_queue
 mln::p_queue, 904
p_queue_fast
 mln::p_queue_fast, 909
p_run
 mln::p_run, 914
p_run2d
 mln, 147
p_runs2d
 mln, 147
p_set
 mln::p_set, 919
p_set_of
 mln::p_set_of, 923
p_transformed
 mln::p_transformed, 926
p_transformed_piter
 mln::p_transformed_piter, 928
p_vaccess
 mln::p_vaccess, 931
p_vertices
 mln::p_vertices, 936
p_vertices_with_mass_centers
 mln::make, 346
pack
 mln::labeling, 305
pack_inplace
 mln::labeling, 306
pair
 mln::util::site_pair, 1088
parent
 mln::util::tree_node, 1101
paste
 mln::data, 209
 mln::data::impl::generic, 221
paste_without_localization
 mln::data, 210
paste_without_localization_fast
 mln::data::impl, 218
paste_without_localization_fastest
 mln::data::impl, 218
paste_without_localization_lines
 mln::data::impl, 218
pcenter
 mln::box, 559
pink
 mln::literal, 325
piter
 mln::box, 556
 mln::p_array, 849
 mln::p_centered, 854
 mln::p_complex, 857
 mln::p_edges, 862
 mln::p_faces, 867
 mln::p_if, 871
 mln::p_image, 875
 mln::p_key, 883
 mln::p_line2d, 887
 mln::pMutable_array_of, 892
 mln::p_priority, 898
 mln::p_queue, 904
 mln::p_queue_fast, 909
 mln::p_run, 914
 mln::p_set, 918
 mln::p_set_of, 922
 mln::p_transformed, 925
 mln::p_vaccess, 930
 mln::p_vertices, 935
pix
 mln::make, 346
 mln::util::pix, 1081
pixel
 mln::make, 346
 mln::pixel, 940
plain
 mln::plain, 943
plot

mln::draw, 236
 plus
 mln::arith, 182, 183
 mln::morpho, 364
 plus_cst
 mln::arith, 183, 184
 plus_cst_inplace
 mln::arith, 184
 plus_infny
 mln::point, 952
 plus_inplace
 mln::arith, 185
 pmax
 mln::box, 559
 mln::doc::Box, 603
 pmin
 mln::box, 559
 mln::doc::Box, 603
 pmin_pmax
 mln::geom, 260, 261
 point
 mln::doc::Dpoint, 605
 mln::doc::Fastest_Image, 609
 mln::doc::Image, 619
 mln::doc::Neighborhood, 624
 mln::doc::Point_Site, 629
 mln::doc::Weighted_Window, 640
 mln::Point, 945
 mln::point, 950, 951
 point1d
 mln, 147
 point1df
 mln, 148
 point2d
 mln, 148
 point2d_h
 mln, 148
 mln::make, 347
 point2df
 mln, 148
 point3d
 mln, 148
 point3df
 mln, 148
 point_at_index
 mln::doc::Fastest_Image, 613
 mln::image1d, 768
 mln::image2d, 773
 mln::image3d, 782
 polygon
 mln::draw, 236
 pop
 mln::p_priority, 901
 mln::p_queue, 905
 mln::p_queue_fast, 911
 pop_front
 mln::p_priority, 901
 mln::p_queue, 906
 mln::p_queue_fast, 911
 mln::util::fibonacci_heap, 1057
 mln::util::soft_heap, 1091
 positive
 mln::test, 397
 pred
 mln::p_if, 873
 predicate
 mln::p_if, 873
 mln::test, 397, 398
 prev
 mln::value::label, 1129
 primary
 mln, 163
 primary_set
 mln::p_transformed, 927
 print
 mln::topo::complex, 1007
 mln::util::tree_node, 1101
 mln::window, 1175
 print_faces
 mln::topo::complex, 1007
 println
 mln::debug, 228
 println_with_border
 mln::debug, 228
 priorities
 mln::p_priority, 901
 propagate_if
 mln::morpho::tree, 376, 377
 propagate_if_value
 mln::morpho::tree, 377
 propagate_node_to_ancestors
 mln::morpho::tree, 378
 propagate_node_to_descendants
 mln::morpho::tree, 378, 379
 propagateRepresentative
 mln::morpho::tree, 379
 proxy
 mln::value::proxy, 1134
 pset
 mln::doc::Fastest_Image, 609
 mln::doc::Image, 619
 mln::p_vaccess, 931
 psite
 mln::box, 556
 mln::complex_neighborhood_bkd_piter, 587
 mln::complex_neighborhood_fwd_piter, 589
 mln::complex_window_bkd_piter, 594
 mln::complex_window_fwd_piter, 595

mln::decorated_image, 598
mln::doc::Box, 602
mln::doc::Fastest_Image, 609
mln::doc::Image, 619
mln::doc::Site_Iterator, 632
mln::doc::Site_Set, 634
mln::dpoint, 646
mln::graph_elt_mixed_window, 737
mln::graph_elt_window, 745
mln::graph_elt_window_if, 749
mln::hexa, 760
mln::image2d_h, 776
mln::interpolated, 785
mln::p_array, 849
mln::p_centered, 854
mln::p_complex, 857
mln::p_edges, 862
mln::p_faces, 867
mln::p_if, 872
mln::p_image, 875
mln::p_key, 883
mln::p_line2d, 888
mln::pMutable_array_of, 892
mln::p_priority, 898
mln::p_queue, 904
mln::p_queue_fast, 909
mln::p_run, 914
mln::p_set, 919
mln::p_set_of, 923
mln::p_transformed, 926
mln::p_vaccess, 931
mln::p_vertices, 935
mln::thrubar_image, 976
mln::topo::is_simple_cell, 1018
mln::tr_image, 1032
mln::util::pix, 1080
mln::value::stack_image, 1143
ptransform
 mln, 163
purge
 mln::p_queue_fast, 911
purple
 mln::literal, 325
push
 mln::p_priority, 901
 mln::p_queue, 906
 mln::p_queue_fast, 911
 mln::util::fibonacci_heap, 1057, 1058
 mln::util::soft_heap, 1091, 1092
put_word
 mln::debug, 229
q_box
 mln::p_line2d, 888
 mln::p_run, 914
qiter
 mln::doc::Window, 643
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_elt_window_if, 749
 mln::window, 1173
Queue based, 110
r_element
 mln::p_image, 875
 mln::p_key, 883
 mln::p_set, 919
rag_and_labeled_wsl
 mln::make, 347
rank_filter
 mln::morpho, 365
read_header
 mln::io::fld, 276
rectangle2d
 mln::win::rectangle2d, 1170
rectangularity
 mln::accu::site_set::rectangularity, 510
red
 mln::literal, 325
 mln::value::qt::rgb32, 1137
 mln::value::rgb, 1139
region_adjacency_graph
 mln::make, 348
regional_maxima
 mln::labeling, 306
regional_minima
 mln::labeling, 306
registration1
 mln::registration, 391
registration2
 mln::registration, 391
registration3
 mln::registration, 391
regular
 mln::window, 1173
relabel
 mln::labeled_image, 792
 mln::labeled_image_base, 795
 mln::labeling, 307
relabel_inplace
 mln::labeling, 308
relabelfun
 mln::make, 348
remove
 mln::p_image, 877
 mln::p_key, 885
 mln::p_set, 920
 mln::util::set, 1087

remove_key
 mln::p_key, 885

replace
 mln::data, 210

reserve
 mln::p_array, 852
 mln::p.Mutable_Array_of, 893
 mln::p_queue_fast, 911
 mln::topo::n_faces_set, 1027
 mln::util::array, 1042

resize
 mln::border, 192
 mln::p_array, 852
 mln::util::array, 1042

result
 mln::graph::attribute::card_t, 732
 mln::graph::attribute::representative_t, 733
 mln::topo::is_simple_cell, 1018
 mln::util::array, 1039

revert
 mln::arith, 185

revert_inplace
 mln::arith, 186

rgb
 mln::value::rgb, 1138

rgb16
 mln::value, 427

rgb32
 mln::value::qt::rgb32, 1136

rgb8
 mln::value, 427

rgb8_2complex_image3df
 mln, 148

root
 mln::util::tree, 1097

rotate
 mln::geom, 261, 262

rotation
 mln::fun::x2x::rotation, 708, 709

Routines, 99

run_length
 mln::box_runend_piter, 567
 mln::box_runstart_piter, 568

rvalue
 mln::complex_image, 585
 mln::decorated_image, 598
 mln::doc::Fastest_Image, 610
 mln::doc::Generalized_Pixel, 615
 mln::doc::Image, 619
 mln::doc::Pixel_Iterator, 627
 mln::extension_fun, 660
 mln::extension_ima, 662
 mln::extension_val, 665
 mln::flat_image, 670

mln::fun_image, 713
 mln::hexa, 761
 mln::image1d, 766
 mln::image2d, 771
 mln::image2d_h, 776
 mln::image3d, 779
 mln::interpolated, 785
 mln::lazy_image, 797
 mln::thrubar_image, 976
 mln::tr_image, 1032
 mln::value::stack_image, 1144
 mln::violent_cast_image, 1153

S

 mln::p_image, 875

sagittal_dec
 mln, 163

saturate
 mln::data, 210, 211

saturate_inplace
 mln::data, 211

save
 mln::io::cloud, 271
 mln::io::dump, 274
 mln::io::magick, 277
 mln::io::off, 279
 mln::io::pbm, 280
 mln::io::pfm, 283
 mln::io::pgm, 284
 mln::io::plot, 286, 287
 mln::io::pnm, 289
 mln::io::ppm, 291
 mln::io::raw, 293
 mln::io::txt, 295

save_bin_alt
 mln::io::off, 279

search
 mln::util::tree_node, 1101

search_rec
 mln::util::tree_node, 1101

second
 mln::accu::pair, 501
 mln::accu::stat::min_max, 529
 mln::util::couple, 1049
 mln::util::ord_pair, 1079
 mln::util::site_pair, 1089

second_accu
 mln::accu::pair, 501
 mln::accu::stat::min_max, 529

seeds2tiling
 mln::geom, 262
 mln::geom::impl, 265

seeds2tiling_roundness
 mln::geom, 263

segment1d
 modwin1d, 112

set
 mln::util::set, 1084

set_all
 mln::dpoint, 648
 mln::point, 952

set_alpha
 mln::fun::x2x::rotation, 709

set_axis
 mln::fun::x2x::rotation, 709

set_cplx
 mln::topo::algebraic_face, 995
 mln::topo::algebraic_n_face, 1000
 mln::topo::face, 1011
 mln::topo::n_face, 1022

set_face_id
 mln::topo::algebraic_face, 995
 mln::topo::algebraic_n_face, 1000
 mln::topo::face, 1011
 mln::topo::n_face, 1022

set_image
 mln::topo::is_simple_cell, 1019

set_n
 mln::topo::algebraic_face, 995
 mln::topo::face, 1012

set_nbts
 mln::value::float01, 1111

set_parent
 mln::util::tree_node, 1102

set_sign
 mln::topo::algebraic_face, 996
 mln::topo::algebraic_n_face, 1000

set_t
 mln::fun::x2x::translation, 712

set_tr
 mln::tr_image, 1033

set_value
 mln::accu::count_adjacent_vertices, 441
 mln::accu::count_labels, 443
 mln::accu::count_value, 444
 mln::accu::math::count, 456
 mln::accu::shape::height, 506
 mln::accu::shape::volume, 509
 mln::accu::stat::max, 516
 mln::accu::stat::min, 525
 mln::morpho::attribute::sum, 840

sign
 mln::topo::algebraic_face, 996
 mln::topo::algebraic_n_face, 1000
 mln::value::sign, 1141

site
 mln::box, 556
 mln::doc::Box, 602

 mln::doc::Site_Set, 634
 mln::dpoint, 646
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_elt_window_if, 749
 mln::graph_window_base, 752
 mln::p_centered, 854
 mln::tr_image, 1032

Site sets, 108

site_function_t
 mln::edge_image, 656
 mln::vertex_image, 1151

site_set
 mln::complex_psite, 592
 mln::draw, 236
 mln::faces_psite, 668

size
 mln::util::array, 1042
 mln::win::line, 1167
 mln::window, 1175

skeleton
 mln::complex_image, 585
 mln::decorated_image, 598
 mln::doc::Fastest_Image, 610
 mln::doc::Image, 619
 mln::edge_image, 657
 mln::extended, 658
 mln::extension_fun, 660
 mln::extension_ima, 662
 mln::extension_val, 665
 mln::flat_image, 670
 mln::fun_image, 713
 mln::hexa, 761
 mln::image1d, 766
 mln::image2d, 771
 mln::image2d_h, 776
 mln::image3d, 779
 mln::image_if, 783
 mln::interpolated, 785
 mln::labeled_image, 791
 mln::lazy_image, 797
 mln::p2p_image, 846
 mln::plain, 942
 mln::pw::image, 959
 mln::safe_image, 961
 mln::slice_image, 970
 mln::sub_image, 972
 mln::sub_image_if, 974
 mln::thrubin_image, 976
 mln::tr_image, 1032
 mln::value::stack_image, 1144
 mln::vertex_image, 1151
 mln::violent_cast_image, 1153

sli

mln::slice_image, 971
 slice_image
 mln::slice_image, 971
 slices_2d
 mln::debug, 229
 sline3d
 modwin3d, 116
 soft_heap
 mln::util::soft_heap, 1090
 sort_offsets_increasing
 mln::data, 211
 sort_psites_decreasing
 mln::data, 211
 sort_psites_increasing
 mln::data, 212
 space_2complex_geometry
 mln, 148
 Sparse types, 109
 sphere3d
 modwin3d, 116
 sqr_l2
 mln::norm, 386
 stack
 mln::value, 432
 stack_image
 mln::value::stack_image, 1144
 standard_deviation
 mln::accu::stat::variance, 538
 start
 mln::doc::Iterator, 623
 mln::doc::Pixel_Iterator, 628
 mln::doc::Site_Iterator, 632
 mln::doc::Value_Iterator, 636
 mln::dpoints_bkd_pixter, 651
 mln::dpoints_fwd_pixter, 654
 mln::p_run, 916
 mln::topo::face_bkd_iter, 1013
 mln::topo::face_fwd_iter, 1014
 mln::topo::n_face_bkd_iter, 1024
 mln::topo::n_face_fwd_iter, 1025
 mln::topo::static_n_face_bkd_iter, 1029
 mln::topo::static_n_face_fwd_iter, 1030
 mln::util::branch_iter, 1046
 mln::util::branch_iter_ind, 1047
 static_n_face_bkd_iter
 mln::topo::static_n_face_bkd_iter, 1028
 static_n_face_fwd_iter
 mln::topo::static_n_face_fwd_iter, 1030
 std_deque
 mln::p_queue, 906
 std_vector
 mln::p_array, 852
 mln::p_line2d, 890
 mln::p_queue_fast, 911
 mln::p_set, 920
 mln::util::array, 1043
 mln::util::set, 1087
 mln::w_window, 1157
 mln::win::rectangle2d, 1170
 mln::window, 1175
 stretch
 mln::data, 212
 mln::data::impl, 219
 structural
 mln::morpho::closing::approx, 368
 mln::morpho::opening::approx, 371
 sub_image
 mln::sub_image, 973
 sub_image_if
 mln::sub_image_if, 974
 subdomain
 mln::labeled_image, 792
 mln::labeled_image_base, 795
 subsampling
 mln::subsampling, 396
 subtractive
 mln::morpho::tree::filter, 381
 sum
 mln::accu::stat::mean, 519
 mln::accu::stat::variance, 539
 mln::estim, 238, 239
 superpose
 mln::debug, 229
 mln::labeling, 308
 mln::morpho::watershed, 383
 sym
 mln::doc::Weighted_Window, 641
 mln::graph_elt_mixed_window, 738
 mln::graph_elt_window, 746
 mln::graph_elt_window_if, 751
 mln::graph_window_base, 753
 mln::w_window, 1157
 mln::win, 434
 mln::window, 1176
 sym_diff
 mln::Box, 565
 mln::Site_Set, 969
 t
 mln::algebra::h_mat, 546
 mln::algebra::h_vec, 547
 mln::fun::x2x::translation, 712
 take
 mln::accu, 167
 mln::accu::histo, 446
 mln::accu::label_used, 447
 mln::accu::stat::histo3d_rgb, 514
 mln::accu::stat::median_alt, 521

mln::doc::Accumulator, 600
take_as_init
 mln::accu::center, 438
 mln::accu::convolve, 440
 mln::accu::count_adjacent_vertices, 441
 mln::accu::count_labels, 443
 mln::accu::count_value, 444
 mln::accu::histo, 446
 mln::accu::label_used, 447
 mln::accu::logic::land, 449
 mln::accu::logic::land_basic, 450
 mln::accu::logic::lor, 452
 mln::accu::logic::lor_basic, 453
 mln::accu::maj_h, 455
 mln::accu::math::count, 456
 mln::accu::math::inf, 458
 mln::accu::math::sum, 459
 mln::accu::math::sup, 461
 mln::accu::max_site, 462
 mln::accu::nil, 497
 mln::accu::p, 499
 mln::accu::pair, 502
 mln::accu::rms, 503
 mln::accu::shape::bbox, 504
 mln::accu::shape::height, 507
 mln::accu::shape::volume, 509
 mln::accu::site_set::rectangularity, 510
 mln::accu::stat::deviation, 512
 mln::accu::stat::histo3d_rgb, 515
 mln::accu::stat::max, 516
 mln::accu::stat::max_h, 518
 mln::accu::stat::mean, 519
 mln::accu::stat::median_alt, 521
 mln::accu::stat::median_h, 523
 mln::accu::stat::min, 525
 mln::accu::stat::min_h, 527
 mln::accu::stat::min_max, 529
 mln::accu::stat::rank, 531
 mln::accu::stat::rank< bool >, 533
 mln::accu::stat::rank_high_quant, 534
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 539
 mln::accu::tuple, 540
 mln::accu::val, 542
 mln::Accumulator, 544
 mln::morpho::attribute::card, 833
 mln::morpho::attribute::count_adjacent_-
 vertices, 834
 mln::morpho::attribute::height, 836
 mln::morpho::attribute::sharpness, 838
 mln::morpho::attribute::sum, 840
 mln::morpho::attribute::volume, 842
take_n_times
 mln::accu::center, 438
mln::accu::convolve, 440
mln::accu::count_adjacent_vertices, 441
mln::accu::count_labels, 443
mln::accu::count_value, 445
mln::accu::histo, 446
mln::accu::label_used, 448
mln::accu::logic::land, 449
mln::accu::logic::land_basic, 451
mln::accu::logic::lor, 452
mln::accu::logic::lor_basic, 453
mln::accu::maj_h, 455
mln::accu::math::count, 456
mln::accu::math::inf, 458
mln::accu::math::sum, 459
mln::accu::math::sup, 461
mln::accu::max_site, 462
mln::accu::nil, 497
mln::accu::p, 499
mln::accu::pair, 502
mln::accu::rms, 503
mln::accu::shape::bbox, 505
mln::accu::shape::height, 507
mln::accu::shape::volume, 509
mln::accu::site_set::rectangularity, 511
mln::accu::stat::deviation, 512
mln::accu::stat::histo3d_rgb, 515
mln::accu::stat::max, 516
mln::accu::stat::max_h, 518
mln::accu::stat::mean, 520
mln::accu::stat::median_alt, 521
mln::accu::stat::median_h, 523
mln::accu::stat::min, 525
mln::accu::stat::min_h, 527
mln::accu::stat::min_max, 530
mln::accu::stat::rank, 531
mln::accu::stat::rank< bool >, 533
mln::accu::stat::rank_high_quant, 534
mln::accu::stat::var, 536
mln::accu::stat::variance, 539
mln::accu::tuple, 541
mln::accu::val, 542
mln::Accumulator, 544
mln::morpho::attribute::card, 833
mln::morpho::attribute::count_adjacent_-
 vertices, 834
mln::morpho::attribute::height, 836
mln::morpho::attribute::sharpness, 838
mln::morpho::attribute::sum, 840
mln::morpho::attribute::volume, 842
target
 mln::graph_elt_mixed_window, 737
 mln::graph_elt_window, 745
 mln::graph_elt_window_if, 749
target_site_set

mln::graph_window_piter, 758
 teal
 mln::literal, 325
 the
 mln::value::set, 1140
 thick_miss
 mln::morpho, 365
 thickening
 mln::morpho, 365
 thin_fit
 mln::morpho, 365
 thinning
 mln::morpho, 365
 threshold
 mln::binarization, 188
 times
 mln::arith, 186
 times_cst
 mln::arith, 186
 times_inplace
 mln::arith, 187
 to
 mln::convert, 200
 to_dpoint
 mln::convert, 201
 mln::Dpoint, 643
 to_enc
 mln::data, 212
 to_float
 mln::value::graylevel, 1115
 to_fun
 mln::convert, 201, 203
 to_h_vec
 mln::point, 952
 to_image
 mln::convert, 201
 to_larger
 mln::box, 559
 to_nbts
 mln::value::float01, 1111
 to_neighb
 mln::graph, 266
 to_p_array
 mln::convert, 201
 to_p_set
 mln::convert, 201, 202
 to_point
 mln::doc::Point_Site, 630
 mln::Point, 945
 to_qimage
 mln::convert, 202
 to_result
 mln::accu::center, 438
 mln::accu::convolve, 440
 mln::accu::count_adjacent_vertices, 442
 mln::accu::count_labels, 443
 mln::accu::count_value, 445
 mln::accu::label_used, 448
 mln::accu::logic::land, 449
 mln::accu::logic::land_basic, 451
 mln::accu::logic::lor, 452
 mln::accu::logic::lor_basic, 454
 mln::accu::maj_h, 455
 mln::accu::math::count, 457
 mln::accu::math::inf, 458
 mln::accu::math::sum, 459
 mln::accu::math::sup, 461
 mln::accu::max_site, 462
 mln::accu::nil, 497
 mln::accu::p, 499
 mln::accu::pair, 502
 mln::accu::rms, 503
 mln::accu::shape::bbox, 505
 mln::accu::shape::height, 507
 mln::accu::shape::volume, 509
 mln::accu::site_set::rectangularity, 511
 mln::accu::stat::deviation, 512
 mln::accu::stat::histo3d_rgb, 515
 mln::accu::stat::max, 516
 mln::accu::stat::max_h, 518
 mln::accu::stat::mean, 520
 mln::accu::stat::median_alt, 521
 mln::accu::stat::median_h, 523
 mln::accu::stat::min, 526
 mln::accu::stat::min_h, 527
 mln::accu::stat::min_max, 530
 mln::accu::stat::rank, 531
 mln::accu::stat::rank< bool >, 533
 mln::accu::stat::rank_high_quant, 534
 mln::accu::stat::var, 536
 mln::accu::stat::variance, 539
 mln::accu::tuple, 541
 mln::accu::val, 542
 mln::morpho::attribute::card, 833
 mln::morpho::attribute::count_adjacent_-
 vertices, 834
 mln::morpho::attribute::height, 836
 mln::morpho::attribute::sharpness, 838
 mln::morpho::attribute::sum, 840
 mln::morpho::attribute::volume, 842
 to_upper_window
 mln::convert, 202, 203
 to_value
 mln::value::proxy, 1135
 to_vec
 mln::algebra::h_vec, 548
 mln::dpoint, 648
 mln::point, 952

to_win
 mln::graph, 267

to_window
 mln::convert, 203

toggle
 mln::p_image, 877

top_hat_black
 mln::morpho, 366

top_hat_self_complementary
 mln::morpho, 366

top_hat_white
 mln::morpho, 366

topological
 mln::morpho::watershed, 383

tr
 mln::tr_image, 1033

tr_image
 mln::tr_image, 1032

tracked_ptr
 mln::util::tracked_ptr, 1094

trait::graph, 1177

trait::graph< mln::complex_image< 1, G, V > >, 1178

trait::graph< mln::image2d< T > >, 1178

transform
 mln::data, 213

 mln::data::impl::generic, 221, 222

transform_inplace
 mln::data, 213, 214

 mln::data::impl::generic, 222

transform_inplace_lowq
 mln::data::impl, 219

translate
 mln::geom, 263, 264

translation
 mln::fun::x2x::translation, 711

tree
 mln::util::tree, 1096

tree_fast_to_image
 mln::util, 419

tree_node
 mln::util::tree_node, 1099

tree_to_fast
 mln::util, 419

tree_to_image
 mln::util, 420

Types, 98

uni
 mln::Box, 565

 mln::Site_Set, 969

unique

mln::Box, 565

mln::Site_Set, 969

unproject_image
 mln::unproject_image, 1034

unsigned_2complex_image3df
 mln, 149

untake
 mln::morpho::attribute::sum, 840

up
 mln, 163

update
 mln::data, 214

 mln::data::impl::generic, 223

 mln::dpoints_bkd_pixter, 651

 mln::dpoints_fwd_pixter, 654

update_data
 mln::labeled_image, 792

 mln::labeled_image_base, 796

update_fastest
 mln::data::impl, 219

update_id
 mln::util::edge, 1053

 mln::util::vertex, 1106

util_set
 mln::p_set, 920

util_tree
 mln::util::branch, 1044

Utilities, 110

v

v1
 mln::util::edge, 1053

 mln::util::graph, 1064

 mln::util::line_graph, 1073

v2
 mln::util::edge, 1054

 mln::util::graph, 1064

 mln::util::line_graph, 1073

v2w2v functions, 118

v2w_w2v functions, 119

v_ith_nbh_edge
 mln::util::graph, 1064

 mln::util::line_graph, 1073

v_ith_nbh_vertex
 mln::util::graph, 1064

 mln::util::line_graph, 1073

v_nmax
 mln::util::graph, 1064

 mln::util::line_graph, 1073

v_nmax_nbh_edges
 mln::util::graph, 1065

 mln::util::line_graph, 1074

v_nmax_nbh_vertices

mln::util::graph, 1065
 mln::util::line_graph, 1074
 v_other
 mln::util::edge, 1054
 val
 mln::doc::Generalized_Pixel, 616
 mln::doc::Pixel_Iterator, 628
 value
 mln::accu::shape::height, 506
 mln::accu::shape::volume, 508
 mln::complex_image, 585
 mln::doc::Fastest_Image, 610
 mln::doc::Generalized_Pixel, 615
 mln::doc::Image, 620
 mln::doc::Pixel_Iterator, 627
 mln::doc::Value_Iterator, 636
 mln::doc::Value_Set, 638
 mln::extended, 658
 mln::extension_fun, 660
 mln::extension_ima, 663
 mln::extension_val, 665
 mln::flat_image, 670
 mln::fun_image, 714
 mln::hexa, 761
 mln::image1d, 766
 mln::image2d, 771
 mln::image2d_h, 776
 mln::image3d, 779
 mln::interpolated, 785
 mln::labeling, 309
 mln::p_vaccess, 931
 mln::thrubin_image, 976
 mln::tr_image, 1032
 mln::util::pix, 1080
 mln::value::float01, 1111
 mln::value::float01_f, 1112
 mln::value::graylevel, 1115
 mln::value::graylevel_f, 1118
 mln::value::lut_vec, 1131
 mln::value::stack_image, 1144
 mln::violent_cast_image, 1153
 value_and_compute
 mln::labeling, 309
 value_array
 mln::value::value_array, 1146
 value_ind
 mln::value::float01, 1111
 value_t
 mln::util::object_id, 1077
 values
 mln::complex_image, 586
 mln::doc::Fastest_Image, 614
 mln::doc::Image, 621
 mln::p_vaccess, 932
 Values morphers, 96
 var
 mln::accu::stat::variance, 539
 variance
 mln::accu::stat::var, 537
 vbox
 mln::image1d, 769
 mln::image3d, 782
 vec
 mln::dpoint, 646
 mln::make, 349, 350
 mln::point, 950
 vec2d_d
 mln, 149
 vec2d_f
 mln, 149
 vec3d_d
 mln, 149
 vec3d_f
 mln, 149
 vect
 mln::accu::histo, 446
 vertex
 mln::p_vertices, 935
 mln::util::graph, 1065
 mln::util::line_graph, 1074
 mln::util::vertex, 1104
 vertex_fwd_iter
 mln::util::graph, 1061
 mln::util::line_graph, 1070
 vertex_id_t
 mln::util, 417
 vertex_image
 mln::make, 350
 mln::vertex_image, 1152
 vertex_nbh_edge_fwd_iter
 mln::util::graph, 1061
 mln::util::line_graph, 1070
 vertex_nbh_t
 mln::vertex_image, 1151
 vertex_nbh_vertex_fwd_iter
 mln::util::graph, 1061
 mln::util::line_graph, 1071
 vertex_win_t
 mln::vertex_image, 1151
 vertical_symmetry
 mln::geom, 264
 vertices_t
 mln::util::graph, 1061
 mln::util::line_graph, 1071
 violent_cast_image
 mln::violent_cast_image, 1154
 violet
 mln::literal, 325

vline2d
 modwin2d, 114

volume
 mln::morpho::attribute::sharpness, 838
 mln::win::cuboid3d, 1164

voronoi
 mln::make, 351

vprod
 mln::algebra, 174

vset
 mln::doc::Fastest_Image, 610
 mln::doc::Image, 620
 mln::p_vaccess, 931
 mln::value::value_array, 1146

vv2b functions, 119

w
 mln::w_window, 1157

w_window
 mln::make, 351
 mln::w_window, 1156

w_window1d
 mln::make, 351

w_window1d_float
 mln, 149

w_window1d_int
 mln, 149
 mln::make, 352

w_window2d
 mln::make, 352

w_window2d_float
 mln, 149

w_window2d_int
 mln, 150
 mln::make, 353

w_window3d
 mln::make, 353

w_window3d_float
 mln, 150

w_window3d_int
 mln, 150
 mln::make, 353

w_window_directional
 mln::make, 354

weight
 mln::doc::Weighted_Window, 641
 mln::w_window, 1156

weights
 mln::w_window, 1157

white
 mln::literal, 325

width
 mln::win::cuboid3d, 1164
 mln::win::rectangle2d, 1170

win
 mln::doc::Weighted_Window, 641
 mln::w_window, 1157

win_c4p
 modwin2d, 115

win_c4p_3d
 modwin3d, 117

win_c8p
 modwin2d, 115

win_c8p_3d
 modwin3d, 117

win_t
 mln::edge_image, 657
 mln::vertex_image, 1151

window
 mln::doc::Weighted_Window, 641
 mln::p_centered, 855
 mln::window, 1173

window1d
 modwin1d, 113

window2d
 modwin2d, 114

window3d
 modwin3d, 117

Windows, 111

wrap
 mln::data, 214
 mln::labeling, 310

write_header
 mln::io::fld, 276

xor_inplace
 mln::logical, 329

yellow
 mln::literal, 325

z_order
 mln::debug, 230

zero
 mln::algebra::h_vec, 548
 mln::literal, 325
 mln::value::int_s, 1120
 mln::value::int_u_sat, 1125
 mln::value::qt::rgb32, 1137
 mln::value::rgb, 1139
 mln::value::sign, 1142