

# Vaucanson XML format description

Valentin David, [valentin@lrde.epita.fr](mailto:valentin@lrde.epita.fr)

December 2003

This document describe the Vaucanson XML format.

## Contents

<b>1</b>	<b>Namespace</b>	<b>1</b>
<b>2</b>	<b>Global format</b>	<b>1</b>
<b>3</b>	<b>Type description</b>	<b>2</b>
3.1	Monoid . . . . .	2
3.2	Semiring . . . . .	2
<b>4</b>	<b>Content</b>	<b>3</b>
4.1	States . . . . .	3
4.2	Transitions . . . . .	3
4.3	Initial states and final states . . . . .	3
<b>5</b>	<b>Geometry</b>	<b>4</b>
<b>6</b>	<b>Session</b>	<b>5</b>

Vaucanson XML obeys to W3C XML 1.0 recommandations.

## 1 Namespace

The namespace of the Vaucanson XML format is "http://www.lrde.epita.fr/vaucanson"

## 2 Global format

An automaton is described by its type and its content. The global format is quit like this :

---

```
<automaton>
  <type>
    <!-- type description -->
  </type>
  <content>
    <!-- content description -->
  </content>
</automaton>
```

---

### 3 Type description

Labels on transitions of automata are elements of rationnal series. This serie is built on a monoid an a semiring. They have both to be defined. We can have something like that :

---

```
<type>
  <monoid type="free" generators="letters">
    <generator value="A"/>
    <generator value="B"/>
  </monoid>
  <semiring set="B" operations="boolean"/>
</type>
```

---

#### 3.1 Monoid

Monoids are defined with a **type** attribute and a **generators** one. Generators have to be passed as children. **type** can be set to "free" or "unit". **generators** can be "letters", "pair", "weighted" or "integers".

Here are some example of monoids :

---

```
<monoid type="free" generators="pair">
  <generators value="(a,a)"/>
  <generators value="(a,b)"/>
  <generators value="(b,a)"/>
  <generators value="(b,b)"/>
</monoid>
```

---

```
<monoid type="free" generators="weighted">
  <generators value="1x"/>
  <generators value="2y"/>
  <generators value="3z"/>
</monoid>
```

---

```
<monoid type="free" generators="integers">
  <generators value="1"/>
  <generators value="2"/>
  <generators value="4"/>
  <generators value="8"/>
</monoid>
```

---

#### 3.2 Semiring

Semiring is defined with two attributes : **set** and **operations**. **set** describes the set where the semiring is defined, and **operations** define the operators used. **set** can be "B", "Z", "R", or "ratseries". When using simple sets, this **operation** attribute can be "boolean", "numerical", "tropicalMax" or "tropicalMin". Here is an example.

---

```
<semiring set="Z" operations="tropicalMin"/>
```

---

When the semiring is a "ratseries" one, a `semiring` and a `monoid` have to be give as children. Then the `operations` attribute can be set to either "function" or "hadamard" or "shuffle".

---

```
<semiring set="ratseries" operations="function">
  <monoid type="free" generators="letters">
    <generator value="A"/>
    <generator value="B"/>
    <generator value="C"/>
  </monoid>
  <semiring set="Z" operations="numerical"/>
</semiring>
```

---

## 4 Content

The content is divided in four parts :

- the states
- the transitions
- the initial states
- the final states

Each of these parts are list of elements.

### 4.1 States

States are mainly described by a name. This name is require and is unique. According to the XML 1.0 recommandation, this name must begin with a alphabetic letter. A optionnal label attribute can be set.

### 4.2 Transitions

Transitions must refer to states as source and destination. The label is give with a regular expression, spontaneous by default.

### 4.3 Initial states and final states

Like transition but there is only one reference to a state.

Here is an example of content :

---

```
<content>
  <states>
    <state name="a"/>
    <state name="b"/>
  </states>
  <transitions>
    <transition src="a" dst="b" label="(2 A)*"/>
  </transitions>
</content>
```

```

</transitions>
<initials>
  <initial state="a"/>
</initials>
<finals>
  <final state="b"/>
</finals>
</content>

```

---

## 5 Geometry

Geometry can be passed on all stages by a `geometry` element. The geometry is conserved to all descendant node. Geometry attribute are mainly taken from Vancanson-G project. See the DTD for more informations.

---

```

<automaton>
  <geometry
    ZZSize="1cm"
  />
  <type>
  <content>
    <states>
      <state name="a">
        <geometry
          x="0"
          y="0"
        />
      </state>
      <state name="b">
        <geometry
          x="2"
          y="0"
        />
      </state>
    </states>
    <transitions>
      <geometry
        curvature="edge"
      />
      <transition src="a" dst="b" label="(2 A)*"/>
    </transitions>
    <initials>
      <initial state="a">
        <geometry
          direction="W"
        />
      </initial>
    </initials>
    <finals>
      <final state="b">
        <geometry

```

```
        direction="E"  
    />  
    </final>  
    </finals>  
    </content>
```

---

## 6 Session

Severals automata can be saved into the same XML document with sessions. It is just a list of automata.

---

```
<session>  
  <automaton name="automanton_1">  
    <!-- definition of automanton_1 -->  
  </automaton>  
  <automaton name="automanton_2">  
    <!-- definition of automanton_2 -->  
  </automaton>  
</session>
```

---