F_iNK – the LATEX 2ε File Name Keeper*

Didier Verna
mailto:didier@lrde.epita.fr
http://www.lrde.epita.fr/~didier/

v2.2.1 (2011/10/19)

Warning! As of version 2.2.1, F_iNK has been deprecated and is not maintained anymore. People interested in F_iNK 's functionality are invited to use a package named currfile instead.

1 Description

This package is a real fink indeed: it looks over your shoulder and keeps track of files \input'ed (the LATEX way) or \include'ed in your document. You then have a permanent access to the directory, name and extension of the file currently being processed through several macros. Dis packache fas orichinally a hack dat I used somefere elss, but since it might be off a cheneral interest, I'fe decided to make it a separate fink...

The F_iNK package is Copyright © 1999, 2000, 2001, 2002, 2007, 2008, 2010, 2011 Didier Verna, and distributed under the terms of the LPPL license.

2 User Interface

To use the package, simply say $\spackage[\langle options \rangle]$ {fink} in the preamble of your document. This will do everything for you. Available options will be described when appropriate.

2.1 Retrieving the current file's name components

\finkdir \finkbase \finkext The file currently being processed is described by the macros \finkdir, \finkbase and \finkext which expand (as you may have guessed) to the directory, base name (sans extension), and extension of the file.

\finkfile \finkpath Additionally, the macro \finkfile is defined to be \finkbase.\finkext (as in previous versions), and the macro \finkpath (new in version 2.0) is defined to be \finkdir\finkfile. Feel free to use these macros in your sources.

^{*}FiNK homepage: http://www.lrde.epita.fr/~didier/software/latex.php#fink

2.2 Main file's name components

maindir mainext Because there's no way T_EX can give you back information about the file being processed (apart from its base name), F_iNK provides the options maindir (defaults to ./) and mainext (defaults to tex) for changing the directory and the extension of the main source file. For instance, suppose your source file is in src/foo.ltx and you are compiling in pdf/. You can then use the package as follows:

\usepackage[maindir=../src,mainext=ltx]{fink}

3 AUC-T_EX support

AUC-TEX is a powerful major mode for editing TEX documents in Emacs or XEmacs. In particular, it provides automatic completion of macro names once they are known. FiNK supports AUC-TEX by providing a style file named fink.el which contains AUC-TEX definitions for the relevant macros. This file should be installed to a location where AUC-TEX can find it (usually in a subdirectory of your IATEX styles directory). Please refer to the AUC-TEX documentation for more information on this.

4 Caveat

 F_iNK cannot follow files included with the TEX \input primitive. That's because TEX has a very insensible way of defining primitives whose argument parsing syntax is not available for macros. As a consequence, it's almost impossible to redefine the \input primitive without breaking its syntax (one would have to parse the characters one by one, and I'm not ready to do so...). F_iNK currently does not follow auxiliary files either.

5 Hints, Tricks, Tips

5.1 File names with special characters

Here, "special" is to be taken in the \LaTeX sense, for instance, a directory or file name containing an underscore. If this situation occurs, you're likely to face problems with F_iNK macros because they don't try to properly escape those characters. So for instance, an underscore alone will make \LaTeX think that you forgot the math mode \$ sign before it. There are actually two problems that you may encounter:

Characters not displayed properly Try to change your font encoding by putting this in your document's preamble: \usepackage[T1]{fontenc}.

Compilation breakage The url package might be of some help here. Put \usepackage{url} in your document's preamble first. Then (assuming that \finkfile is the culprit), instead of using \finkfile directly, use this instead: \expandafter\url\expandafter{\finkfile}. You might also want to play with \urlstyle to have your file name displayed in the font you prefer.

6 Changes

- v2.2.1 Declare package as obsolete.
 - v2.2 Fix incompatibility with the memoir class, reported by Lars Madsen
- v2.1.1 Fix trailing whitespace in \fink@restore, reported by Maverick Woo Added some hints about filenames with special characters, suggested by David P. Goodall
 - v2.1 Fix bug preventing expansion in math mode, reported by Alain Schremmer, fixed by Morten Hoegholm before I could even raise my little finger.
 - v2.0 New macros \finkdir, \finkbase, \finkext and \finkpath suggested by Alain Schremmer

 New options mainext and maindir, use kvoptions for options management
 - v1.2 Fixed conflict with \includegraphics, reported by Jim Crumley
 - v1.1 Fixed missing 3rd arg to \PackageError call from \finkextension

7 The Code

```
1 \langle fink \\ NeedsTeXFormat{LaTeX2e}
2 \langle *header \rangle
3 \\ ProvidesPackage{fink}[2011/10/19 v2.2.1 Keep track of the current filename]
4
5 \langle /header \rangle
6 \langle *fink \rangle
7 \\ PackageWarning{FiNK}{as of version 2.2.1, FiNK has been deprecated and is
8 not\MessageBreak
9 maintained anymore. People interested in FiNK's\MessageBreak
10 functionality are invited to use a package named\MessageBreak
11 "currfile" instead,}
12
13 \\ RequirePackage{kvoptions}
14 \\ SetupKeyvalOptions{family=fnk,prefix=fnk@}
15
```

7.1 Main file initial settings

```
maindir
mainext
```

```
16 \DeclareStringOption[\@currdir]{maindir}
17 \DeclareStringOption[tex]{mainext}
```

The following is for backward compatibility only (not documented anymore). It provides support for the old tex and ltx options (still functionnal), and for the \finkextension macro. However, this macro is now defined to trigger an error, begging the user to use the new option instead.

```
19 \newcommand*\@fink@mainext[1]{\setkeys{fnk}{mainext={#1}}}
20 \newcommand*\fink@mainext{%
```

```
\expandafter\@fink@mainext\expandafter{\CurrentOption}}
22 \DeclareVoidOption{tex}{\fink@mainext}
23 \DeclareVoidOption{ltx}{\fink@mainext}
25 \newcommand*\finkextension[1]{%
    \PackageError{FiNK}{%
      \protect\finkextension\space shouldn't be used anymore.\MessageBreak
      Please use the 'mainext' package option instead.}{%
28
29
      No big deal right ?\MessageBreak
      Type X to quit and modify your source.}}
30
31 \@onlypreamble\finkextension
33 \ProcessKeyvalOptions*
34
```

File's name components macros

```
\finkdir We declare the user-level macros here. \fink@file is used to compute file names,
\finkbase possibly with no extension.
\verb|\finkext| 35 \verb|\newcommand*\finkdir{\fink@maindir}|
\finkfile 36 \newcommand*\finkbase{\jobname}
\finkpath 37 \newcommand*\finkext{\fnk@mainext}
           39 \newcommand*\finkfile{}
           40 \newcommand*\fink@file[2]{#1\ifx\\#2\\\else.#2\fi}
           41 \xdef\finkfile{\fink@file{\jobname}{\fnk@mainext}}
           43 \newcommand*\finkpath{}
           44 \xdef\finkpath{\finkdir\finkfile}
           46 \PackageInfo{FiNK}{main file set to "\finkpath"}
```

Commands overriding

\fink@beginfile

The memoir class redefines \InputIfFileExists as well, in order to provide its \fink@endfile file hooks. Since we override its definition, we need to take care of those hooks ourselves.

```
48 \@ifclassloaded{memoir}{
  \let\fink@beginfile\m@matbeginf
  \def\fink@beginfile#1{}
  \def\fink@endfile#1{}}
52
```

Note: as of version 1.2, every call to \filename@parse is done in a group of its own. This fixes a problem that appeared when using \includegraphics with a filename with an explicit extension. \includegraphics calls \filename@parse itself, so it is important that our call(s) only have a local effect.

\fink@input \fink@restore These macros are defined for a convenient use of \expandafter. They save and restore the current filename. Remember that \@@input is IATEX's redefinition of the T_EX input primitive.

```
54 \newcommand*\fink@input[1]{%
   \begingroup%
55
      \filename@parse{#1}%
56
      \xdef\finkdir{%
57
        \ifx\filename@area\@empty%
58
          \fnk@maindir%
59
        \else%
60
          \fnk@maindir\filename@area%
61
62
        fi}%
      \xdef\finkbase{\filename@base}%
63
      \xdef\finkext{\ifx\filename@ext\relax tex\else\filename@ext\fi}%
64
      \xdef\finkfile{\fink@file{\finkbase}{\finkext}}%
65
      \xdef\finkpath{\finkdir\finkfile}%
66
    \endgroup%
67
    \fink@beginfile{#1}%
68
    \@@input\@filef@und%
69
    \fink@endfile{#1}}
70
71
72 \newcommand*\fink@restore[1]{%
73
   \begingroup%
      \filename@parse{#1}%
74
      \xdef\finkdir{\filename@area}%
75
      \xdef\finkbase{\filename@base}%
76
      \xdef\finkext{\filename@ext}%
77
      \xdef\finkfile{\fink@file{\finkbase}{\finkext}}%
78
79
      \xdef\finkpath{\finkdir\finkfile}%
80
    \endgroup}
```

Note: in earlier versions, we redefined $\fiftheref{liffileExists}$ to prepare the name of the next file, but this is bad because it can be used outside of F_iNK 's scope. We also redefined $\gray \$ but neither $\$ include nor $\$ use it.

\InputIfFileExists

LATEX's \input and \include commands use \InputIfFileExists, so let's redefine it here:

```
82 \long\def\InputIfFileExists#1#2{%
83 \IfFileExists{#1}{%
84 #2\@addtofilelist{#1}%
85 \edef\fink@before{\noexpand\fink@input{#1}}%
86 \edef\fink@after{\noexpand\fink@restore{\finkpath}}%
87 \expandafter\fink@before\fink@after}
88
89 \/fink\
```

Well, I think that's it. Enjoy using $F_iNK!$